

Maximum Permissible Exposure (MPE) Evaluation Report

Report No. : TS10070160-EME

Model No. : WiDRIVE DX-325

Issued Date : Sep. 13, 2010

**Applicant: EDSLAB Technologies Inc.
4F., No. 150, Sec. 2, Nanking E Rd., Taipei City 10489,
Taiwan**

Test Method/ FCC 1.1310

Standard:

**Test By: Intertek Testing Services Taiwan Ltd.
No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,
Shiang-Shan District, Hsinchu City, Taiwan**

It may be duplicated completely for legal use with the allowance of the applicant. It shall not be reproduced except in full, without the written approval of Intertek Laboratory. The test result(s) in this report only applies to the tested sample(s).

The test report was prepared by:

Sign on File
Grace Lee/ Assistant

These measurements were taken by:

Sign on File
Jacky Chen/ Engineer

The test report was reviewed by:

Name Rex Liao
Title Engineer

Table of Contents

| | |
|-----------------------------------|---|
| Summary of Tests | 3 |
| 1. Introduction | 4 |
| 2. RF Exposure Limit | 4 |
| 3. RF Exposure calculations | 5 |
| 4 Description of EUT | 6 |
| 5. Test results | 7 |

Summary of Tests**MPE Evaluation meet FCC OET No. 65: 1997, IEEE C95.1-2005**

WiFi Storage Router-Model: DX-325
FCC ID: WYR-EDS-1388

| Test | Reference | Results |
|----------------|--|----------|
| MPE Evaluation | FCC Guidelines for Human Exposure IEEE C95.1 | Complies |

1. Introduction

The EUT operates in the 2.4 GHz ISM band. Due to the EUT (include antenna) at its normal operation distance is at least 20 cm from the human body, the EUT was defined as a Mobile Device.

The reason to do the MPE Evaluation is to avoid the RF hazard to human body. The maximum output power and gain of the antenna were used to calculate the limited Power density (S) at 20 cm distance away from the product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and Safety Code 6 are followed.

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Average Time (minutes) |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational / Control Exposures | | | | |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | - | - | F/300 | 6 |
| 1500-100,000 | - | - | 5 | 6 |
| (B) Limits for General Population / Uncontrolled Exposure | | | | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | - | - | F/1500 | 30 |
| 1500-100,000 | - | - | 1.0 | 30 |

F= Frequency in MHz

3. RF Exposure calculations

From §FCC 1.1310 table 1, the maximum permissible RF exposure for an uncontrolled environment is 1 mW/(cm²) (or 10 W/m²)*

Power density (S) is calculated by the following formula:

$$S = (P * G) / 4\pi R^2$$

where, S = Power density (mW/cm²)

P = Output power to antenna (mW)

R = Distance between radiating structure and observation point (cm)

G = Gain of antenna in numeric

$\pi = 3.1416$

Example:

Assume a mobile device operates at 2412MHz and its maximum output power is 50mW, and the maximum gain of antenna is 1 (numeric) /0dBi.

then the power density (S) = $(50 * 1) / 4 * \pi * 20^2 = 0.00995$ (mW/cm²) (or = 0.0995 W/m²)

4 Description of EUT

The EUT is a WiFi Storage Router, and was defined as information technology equipment.

4.1 Antenna description

The antenna is affixed to the EUT using a unique connector, which allows for replacement of a broken antenna, but DOES NOT use a standard antenna jack or electrical connector.

Antenna 0

Antenna Gain: -3.14 dBi max

Antenna Type: PCB Printed antenna

Connector Type: N/A

Antenna 1

Antenna Gain: -3.55dBi max

Antenna Type: PCB printed antenna

Connector Type: N/A

5. Test results

For Single Tx

| Mode | Frequency (MHz) | Antenna Gain (numeric) | Output power to antenna (mW) | Power density (mW/cm ²) | Limit of power density (mW/cm ²) | Distance (cm) |
|---------|-----------------|------------------------|------------------------------|-------------------------------------|--|---------------|
| 802.11b | 2412 | 0.49 | 112.72 | 0.010882537 | 1.0 | 20 |
| | 2437 | 0.49 | 63.97 | 0.006176325 | 1.0 | 20 |
| | 2462 | 0.49 | 72.95 | 0.007042553 | 1.0 | 20 |
| 802.11g | 2412 | 0.49 | 228.03 | 0.022015581 | 1.0 | 20 |
| | 2437 | 0.49 | 215.28 | 0.020784048 | 1.0 | 20 |
| | 2462 | 0.49 | 205.12 | 0.019802962 | 1.0 | 20 |

For 2Tx

| Mode | Frequency (MHz) | Antenna Gain0 (numeric) | Antenna Gain1 (numeric) | Output power to antenna 0 (mW) | Output power to antenna 1 (mW) | Power density (mW/cm ²) | Limit of power density (mW/cm ²) | Distance (cm) |
|--------------|-----------------|-------------------------|-------------------------|--------------------------------|--------------------------------|-------------------------------------|--|---------------|
| 802.11n HT20 | 2412 | 0.49 | 0.44 | 212.32 | 171.79 | 0.355903019 | 1.0 | 20 |
| | 2437 | 0.49 | 0.44 | 166.72 | 161.81 | 0.303109042 | 1.0 | 20 |
| | 2462 | 0.49 | 0.44 | 167.88 | 191.87 | 0.330630806 | 1.0 | 20 |
| 802.11n HT40 | 2422 | 0.49 | 0.44 | 187.93 | 179.47 | 0.339101922 | 1.0 | 20 |
| | 2437 | 0.49 | 0.44 | 179.47 | 187.93 | 0.338366265 | 1.0 | 20 |
| | 2452 | 0.49 | 0.44 | 187.07 | 171.00 | 0.330825982 | 1.0 | 20 |

The Notice in Installation Manual has been stated as below:

While installing and operating this transmitter, the radio frequency exposure limit of 1 mW/ (cm²) may be exceeded at distances close to the transmitter. therefore, the user must maintain a minimum distance of 20 cm from the device at all time.