

FCC Part 1 Subpart I FCC Part 2 Subpart J INDUSTRY CANADA RSS 102 ISSUE 5

RF EXPOSURE REPORT

FOR

RFID INTERROGATOR

MODEL NUMBER: SM-NV

FCC ID: WZ4-NOVA001 IC: 5893A-NOVA001

REPORT NUMBER: 15U20118 - E3, REVISION D

ISSUE DATE: MAY 12, 2015

Prepared for SKYETEK, INC 1415 LARIMER St, STE 207 Denver, CO 80202, U.S.A.

Prepared by

UL VERIFICATION SERVICES INC. 47173 BENICIA STREET FREMONT, CA 94538, U.S.A. TEL: (510) 771-1000

FAX: (510) 661-08888



NVLAP LAB CODE 200065-0

REPORT NO: 15U20118-E3D FCC ID: WZ4-NOVA001

Revision History

Rev.	Issue Date	Revisions	Revised By
	03/25/14	Initial Issue	H. Mustapha
A	04/09/15	Corrected RSS-102 issue number Revised IC exemption paragraph Revised RF exposure results tables	H. Mustapha
В	04/16/15	Corrected RSS-102 issue number Revised RX exposure results tables	H. Mustapha
С	05/04/15	Corrected Duty Cycle	H. Mustapha
D	05/12/15	Added power density to RF exposure results table for IC	H. Mustapha

DATE: MAY 12, 2015

IC: 5893A-NOVA001

TABLE OF CONTENTS

1.	AT	TESTATION OF TEST RESULTS	4
2.	TES	ST METHODOLOGY	6
3.	RE	FERENCES	6
4.	FA	CILITIES AND ACCREDITATION	6
5.	MA	XIMUM PERMISSIBLE RF EXPOSURE	7
	5.1.	FCC RULES	7
	5.2.	IC RULES	8
	5.3.	EQUATIONS	9
	5.4.	LIMITS AND IC EXEMPTION	10
6.	ON	TIME AND DUTY CYCLE RESULTS	11
	6.1.	DUTY CYCLE PLOT	1
7.	RF	EXPOSURE RESULTS	12

DATE: MAY 12, 2015

IC: 5893A-NOVA001

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: SKYETEK, INC

1415 LARIMER St, STE 207 Denver, CO 80202, U.S.A.

EUT DESCRIPTION: RFID INTERROGATOR

MODEL: SM-NV

SERIAL NUMBER: Conducted: FCC 2

Radiated: FCC 1

DATE TESTED: Feb 23 to Feb 28, 2015

APPLICABLE STANDARDS

STANDARD TEST RESULTS

FCC PART 1 SUBPART I & PART 2 SUBPART J

Pass

INDUSTRY CANADA RSS 102 ISSUE 5

Pass

UL Verification Services Inc. calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

REPORT NO: 15U20118-E3D FCC ID: WZ4-NOVA001

Approved & Released For UL Verification Services Inc. By:

Huda Mustapha

HUDA MUSTAPHA
PROJECT LEAD
UL Verification Services Inc.

Calculated By:

Myryantia

DATE: MAY 12, 2015

IC: 5893A-NOVA001

LIEU NGUYEN
LAB EMC ENGINEER
UL Verification Services Inc.

FRANK IBRAHIM PROGRAM MANAGER UL Verification Services Inc.

2. TEST METHODOLOGY

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01 and IC Safety Code 6.

3. REFERENCES

All measurements were made as documented in test report UL Verification Services Inc. 15U20118-E1 for operation in the 900 MHz band.

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at http://ts.nist.gov/standards/scopes/2000650.htm.

5. MAXIMUM PERMISSIBLE RF EXPOSURE

5.1. **FCC RULES**

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1-LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)						
(A) Limits for Occupational/Controlled Exposures										
0.3–3.0 3.0–30 30–300 300–1500 1500–100,000	614 1842/f 61.4	1.63 4.89# 0.163	*(100) *(900/f²) 1.0 f/300 5	6 6 6 6						
(B) Limits	for General Populati	on/Uncontrolled Exp	oosure							
0.3–1.34	614 824/f	1.63 2.19/f	*(100) *(180/f²)	30 30						

TABLE 1-LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)-Continued

Frequency range (MHz)	Electric field strength (V/m)	strength strength		Averaging time (minutes)	
30–300	27.5	0.073	0.2	30	
300–1500 1500–100,000			f/1500 1.0	30 30	

f = frequency in MHz

exposure or can not exercise control over their exposure.

^{* =} Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposure, or can not expense control over their exposure.

5.2. IC RULES

IC Safety Code 6, Section 2.2.1 (a) A person other than an RF and microwave exposed worker shall not be exposed to electromagnetic radiation in a frequency band listed in Column 1 of Table 5, if the field strength exceeds the value given in Column 2 or 3 of Table 5, when averaged spatially and over time, or if the power density exceeds the value given in Column 4 of Table 5, when averaged spatially and over time.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ₂)	(minutes)
0.003-1021	83	90	-	Instantaneous*
0.1-10	-	0.73/f	-	6**
1.1-10	87/ f 0.5	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f 0.25	0.1540/f 0.25	8.944/ f 0.5	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f 0.3417	0.008335 f 0.3417	0.02619f0.6834	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f 1.2
150000-300000	0.158 f 0.5	4.21 x 10-4 f 0.5	6.67 x 10-5 <i>f</i>	616000/ f 1.2

Note: *f* is frequency in MHz.

*Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).

5.3. EQUATIONS

POWER DENSITY

Power density is given by:

 $S = EIRP / (4 * Pi * D^2)$

Where

S = Power density in mW/cm^2 EIRP = Equivalent Isotropic Radiated Power in mW D = Separation distance in cm

Power density in units of mW/cm² is converted to units of W/m² by multiplying by 10.

DISTANCE

Distance is given by:

D = SQRT (EIRP / (4 * Pi * S))

Where

D = Separation distance in cm EIRP = Equivalent Isotropic Radiated Power in mW S = Power density in mW/cm²

SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

Source-based time-averaged EIRP = (DC / 100) * EIRP

Where

DC = Duty Cycle in %, as applicable EIRP = Equivalent Isotropic Radiated Power in W

5.4. LIMITS AND IC EXEMPTION

INDUSTRY CANADA EXEMPTION

RSS-102 Clause 2.5.2: RF exposure evaluation is required if the separation distance between the user and the device's radiating element is greater than 20 cm, except when the device operates as follows:


- below 20 MHz6 and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 22.48/f0.5W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1.31 x 10-2 f0.6834 W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

6. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time	Period	Duty Cycle	Duty
	В		x	Cycle
	(msec)	(msec)	(linear)	(%)
902-928 MHz Band FHSS OFF/PR-ASK	8.940	19.47	0.459	45.92%

DUTY CYCLE PLOT 6.1.

HOPPING OFF



7. RF EXPOSURE RESULTS

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

For IC:

EUT with Planar Inverted "F" (PIFA) and Dipole Antennas										
Single Chain an	Single Chain and non-colocated transmitters									
Band	Band Mode Separatio Output Antenna Duty EIRP IC Power									
		Distance	AVG	Gain	Cycle		Density			
			Power							
		(cm)	(dBm)	(dBi)	(%)	(mW)	(W/m^2)			
902-928 MHz	PR-ASK	20	26.66	2.00	45.9	337.1	0.67			
902-928 MHz	PR-ASK	20	26.66	5.40	45.9	737.6	1.47			

EUT with Line	EUT with Linearly Polarized Patch and Circularly Polarized Patch Antennas										
Single Chain a	Single Chain and non-colocated transmitters										
Band Mode IC Output Antenna EIRP Duty EIRP Separation IC Power								IC Power			
		Limit	AVG	Gain		Cycle		Distance	Density		
			Power								
		(W/m^2)	(dBm)	(dBi)	(dBm)	(%)	(mW)	(cm)	(W/m^2)		
902-928 MHz	PR-ASK	2.7	26.66	9.00	35.66	45.9	1689.7	22.32	2.7		

For FCC:

EUT with Highest Antenna Gain									
Single Chain and non-colocated transmitters									
Band Mode Separatio Output Antenna Duty EIRP FCC									
	Distance	AVG	Gain	Cycle		Density			
			Power						
		(cm)	(dBm)	(dBi)	(%)	(mW)	(mW/cm		
902-928 MHz	PR-ASK	20	26.66	9.00	45.9	1689.7	0.336		

Notes:

1) A tolerance value of +0.2 dB was included in the output power values above to cover the output power tolerance of +0.2/-1.0 dB under extreme conditions in the real field as declared by the client.

END OF REPORT