



10. RF EXPOSURE STATEMENT

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures				
Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

FCC CERTIFICATION REPORT				www.hct.co.kr
Test Report No. HCTR1002FR06	Date of Issue: January 20, 2010	EUT Type: Booster		FCC ID: WZI-UHR-230L

2-1. GSM Uplink

Max Peak output Power at antenna input terminal	14.980	dBm
Max Peak output Power at antenna input terminal	31.477	mW
Prediction distance	20.000	cm
Prediction frequency	824.200	MHz
Antenna Gain(typical)	5.000	dBi
Antenna Gain(numeric)	3.162	-
Power density at prediction frequency(S)	0.020	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.549	mW/cm ²

3. RESULTS

The power density level at 20 cm is 0.020 (GSM), which is below the uncontrolled exposure limit for GSM band.

Warning: In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, it must also have a minimum distance of 20 cm from the body during normal operation.

FCC CERTIFICATION REPORT			www.hct.co.kr
Test Report No. HCTR1002FR06	Date of Issue: January 20, 2010	EUT Type: Booster	FCC ID: WZI-UHR-230L