

# FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.249

**Equipment** : Motion Recognition Controller  
**Model No.** : CW-CL01KP-C  
**Brand Name** : CyWee  
**Filing Type** : Existing Change  
**Applicant** : CyWee Group Ltd.  
· 3F, 28 Jing Ye 1st Road, Lane 128, Taipei, Taiwan 10462  
**FCC ID** : WZS-CWCL01KP-C  
**Manufacturer** : Dongguan Kunying Computer Products Co., Ltd  
· Baodun Industrial District, Houjie Town, Dongguan City,  
Guangdong Province, 523961 China  
**Received Date** : Dec. 02, 2008  
**Final Test Date** : Mar. 27, 2009

## Statement

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



**SPORTON International Inc.**

6F, No. 106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

## Table of Contents

<b>1. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>2. GENERAL INFORMATION.....</b>	<b>3</b>
2.1. Product Details .....	3
2.2. Table for Carrier Frequencies .....	3
2.3. Table for Test Modes .....	3
2.4. Table for Testing Locations.....	4
2.5. Table for Supporting Units.....	4
2.6. Test Configurations .....	4
<b>3. TEST RESULT .....</b>	<b>5</b>
3.1. AC Power Line Conducted Emissions Measurement.....	5
3.2. Field Strength of Fundamental Emissions Measurement.....	8
3.3. 20dB Spectrum Bandwidth Measurement.....	11
3.4. Radiated Emissions Measurement.....	14
3.5. Band Edge Emissions Measurement .....	26
3.6. Antenna Requirements.....	29
<b>4. LIST OF MEASURING EQUIPMENTS .....</b>	<b>30</b>
<b>5. TEST LOCATION .....</b>	<b>31</b>
<b>6. TAF CERTIFICATE OF ACCREDITATION.....</b>	<b>32</b>
<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1 ~ A4</b>
<b>APPENDIX B. PHOTOGRAPHS OF EUT .....</b>	<b>B1 ~ B7</b>

## History of This Test Report

Original Issue Date: Apr. 01, 2009

Report No.: FR8N1221-01

- No additional attachment.
- Additional attachment were issued as following record:

# CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.249

Equipment : Motion Recognition Controller

Model No. : CW-CL01KP-C

Brand Name : CyWee

Applicant : CyWee Group Ltd.  
3F, 28 Jing Ye 1st Road, Lane 128, Taipei, Taiwan 10462

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Dec. 02, 2008 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Lee / Supervisor

**SPORTON International Inc.**

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

## 1. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	-	-
3.2	15.249(a)	Field Strength of Fundamental Emissions	Complies	12.76 dB
3.3	15.215(c)	20dB Spectrum Bandwidth	Complies	-
3.4	15.249(a)/(d)	Radiated Emissions	Complies	3.02 dB
3.5	15.249(d)	Band Edge Emissions	Complies	1.31 dB
3.6	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Field Strength of Fundamental Emissions	±0.8dB	Confidence levels of 95%
20dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

## 2. GENERAL INFORMATION

### 2.1. Product Details

This product is an extension of original one reported under Sporton project number: FR8N1221. It's changed lower gain antenna. Therefore, new test results (Field Strength of Fundamental Emissions/ Radiated Emissions/ Band Edge Emissions) were verified with the EUT of original test.

Items	Description
Power Type	3Vdc from battery
Modulation	GFSK
Frequency Range	2400 ~ 2483.5MHz
Channel Number	5
Channel Band Width (99%)	2.12 MHz
Max. Field Strength	81.14 dBuV/m at 3m (Average)
Antenna gain (dBi)	0.78 dBi (Internal Antenna)

### 2.2. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency
2400 ~ 2483.5MHz	1	2402 MHz
	:	:
	3	2441 MHz
	:	:
	5	2480 MHz

### 2.3. Table for Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Channel	Antenna
Field Strength of Fundamental Emissions 20dB Spectrum Bandwidth	CTX	1/3/5	1
Radiated Emissions 9kHz~1GHz	CTX	3	1
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	CTX	1/3/5	1
Band Edge Emissions	CTX	1/5	1

Note: CTX=continuously transmitting

## 2.4. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No.
03CH02-HY	SAC	Hwa Ya	101377	IC 4086B-1	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).


## 2.5. Table for Supporting Units

The EUT was tested alone.


## 2.6. Test Configurations

### 2.6.1. Radiation Emissions Test Configuration

< 30MHz~1GHz >



<Above 1GHz >



### 3. TEST RESULT

#### 3.1. AC Power Line Conducted Emissions Measurement

##### 3.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

##### 3.1.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

##### 3.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

### 3.1.4. Test Setup Layout



## LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50 \Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

**3.1.5. Test Deviation**

There is no deviation with the original standard.

**3.1.6. EUT Operation during Test**

The EUT was placed on the test table and programmed in normal function.

**3.1.7. Results of AC Power Line Conducted Emissions Measurement**

The EUT is battery powered and the AC power line Conducted Emission is not required.

### 3.2. Field Strength of Fundamental Emissions Measurement

#### 3.2.1. Limit

The field strength of fundamental emissions within these bands specified at a distance of 3 meters (measurement instrumentation employing an average detector) shall comply with the following table.

Frequency Band (MHz)	Fundamental Emissions Limit (dBuV/m) at 3m
2400-2483.5	94
5725-5875	94

#### 3.2.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Power Meter Parameter	Setting
RB	1 MHz Peak / 1MHz Average
VB	1 MHz Peak / 10Hz Average
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 3.2.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. For Fundamental emissions, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

### 3.2.4. Test Setup Layout



### 3.2.5. Test Deviation

There is no deviation with the original standard.

### 3.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 3.2.7. Test Result of Field Strength of Fundamental Emissions

Test date	Mar. 27, 2009	Test Site No.	03CH02-HY
Temperature	24	Humidity	52%
Test Engineer	David	Configurations	Channel 1/3/5

## Channel 1

## Vertical

Freq	Level	Over Limit		Read		Ant	Table
		Line	Limit	Antenna	Level		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	deg
3	2401.770	101.23	-12.77	114.00	66.44	31.79	3.00
3	2401.770	72.07	-21.93	94.00	37.28	31.79	3.00
						0.00	---
						0.00	---

## Channel 3

## Vertical

Freq	Level	Over Limit		Read		Ant	Table
		Line	Limit	Antenna	Level		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	deg
1	2440.330	101.24	-12.76	114.00	66.21	31.99	3.04
1	2441.100	71.97	-22.03	94.00	36.94	31.99	3.04
						0.00	---
						0.00	---

## Channel 5

## Vertical

Freq	Level	Over Limit		Read		Ant	Table
		Line	Limit	Antenna	Level		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	deg
1	2480.050	101.21	-12.79	114.00	66.02	32.13	3.06
1	2480.050	72.16	-21.84	94.00	36.97	32.13	3.06
						0.00	---
						0.00	---

## Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

### 3.3. 20dB Spectrum Bandwidth Measurement

#### 3.3.1. Limit

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emissions in the specific band (2400 ~ 2483.5MHz).

#### 3.3.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 20dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 3.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.

#### 3.3.4. Test Setup Layout



#### 3.3.5. Test Deviation

There is no deviation with the original standard.

#### 3.3.6. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

## 3.3.7. Test Result of 20dB Spectrum Bandwidth

Test date	Dec. 02, 2008	Test Site No.	TH01-HY
Temperature	26°C	Humidity	56%
Test Engineer	Tom	Configurations	Channel 1/3/5


Frequency	20dB BW (MHz)	99% OBW (MHz)	Frequency range (MHz) $f_L > 2400\text{MHz}$	Frequency range (MHz) $f_H < 2483.5\text{MHz}$	Test Result
2402 MHz	2.09	2.12	2400.7400	-	Complies
2441 MHz	1.78	1.81	-	-	Complies
2480 MHz	1.78	1.89	-	2480.8500	Complies

## 20 dB/99% Bandwidth Plot on 2402 MHz




Date: 2.DEC.2008 07:08:57

## 20 dB/99% Bandwidth Plot on 2441 MHz



Date: 2.DEC.2008 07:12:04

## 20 dB/99% Bandwidth Plot on 2480 MHz



Date: 2.DEC.2008 07:12:04

### 3.4. Radiated Emissions Measurement

#### 3.4.1. Limit

Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### 3.4.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

### 3.4.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

### 3.4.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

### 3.4.5. Test Deviation

There is no deviation with the original standard.

### 3.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 3.4.7. Results of Radiated Emissions (9kHz~30MHz)

Test date	Mar. 27, 2009	Test Site No.	03CH02-HY
Temperature	24	Humidity	52%
Test Engineer	David		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

## Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.


## 3.4.8. Results of Radiated Emissions (30MHz~1GHz)

Test date	Mar. 27, 2009	Test Site No.	03CH02-HY
Temperature	24	Humidity	52%
Test Engineer	David	Configurations	Channel 3

**Horizontal**

Freq	Level	Over Limit	Line	Read		Ant	Table	Pos	Pos
				Antenna	Cable				Remark
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 @	90.140	17.70	-25.80	43.50	37.07	9.50	1.93	30.80	---
2 @	188.110	24.47	-19.03	43.50	41.92	10.48	2.69	30.62	---
3 @	295.780	23.43	-22.57	46.00	36.74	13.65	3.45	30.41	---
4 @	381.140	31.27	-14.73	46.00	42.76	14.97	3.79	30.24	---
5 @	443.220	25.76	-20.24	46.00	35.63	16.14	4.06	30.07	---
6 @	641.100	28.26	-17.74	46.00	32.97	19.63	5.10	29.44	---

## Vertical



Freq	MHz	Level	Over Limit	Line	Read	Antenna Factor	Cable Loss	Preamp Factor	Table	
									Pos	Pos
1	90.140	23.51	-19.99	43.50	42.88	9.50	1.93	30.80	---	--- Peak
2	214.300	17.96	-25.54	43.50	33.78	11.83	2.92	30.57	---	--- Peak
3	296.750	17.90	-28.10	46.00	31.19	13.66	3.46	30.41	---	--- Peak
4	641.100	24.61	-21.39	46.00	29.32	19.63	5.10	29.44	---	--- Peak
5	797.270	25.01	-20.99	46.00	28.30	20.23	5.49	29.01	---	--- Peak
6	963.140	26.98	-27.02	54.00	27.75	21.59	6.09	28.45	---	--- Peak

## Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


3.4.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

Test date	Mar. 27, 2009	Test Site No.	03CH02-HY
Temperature	24	Humidity	52%
Test Engineer	David	Configurations	Channel 1

*Horizontal*


Freq	Level	Over Limit	Line	Read		Ant	Table	Pos	Pos	Remark
				Antenna	Cable					
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4804.000	48.63	-5.37	54.00	43.26	35.73	4.57	34.94	---	--- PK
2	7210.000	51.26	-22.74	74.00	43.04	37.84	5.62	35.25	---	--- PEAK
3	7210.000	43.72	-10.28	54.00	35.50	37.84	5.62	35.25	---	--- Average
4	9604.000	53.81	-20.19	74.00	43.85	39.32	6.34	35.70	---	--- PEAK
5	9604.000	46.27	-7.73	54.00	36.31	39.32	6.34	35.70	---	--- Average

## Vertical




Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	
		Line	Limit	Level	Factor	Loss	Factor	Pos	Pos	Remark
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4804.000	49.29	-4.71	54.00	44.55	35.11	4.57	34.94	---	--- PK
2	7202.000	50.74	-3.26	54.00	43.48	36.88	5.62	35.24	---	--- PK
3	9608.000	52.59	-21.41	74.00	43.42	38.52	6.34	35.70	---	--- PEAK
4	9608.000	45.04	-8.96	54.00	35.88	38.52	6.34	35.70	---	--- Average

Test date	Mar. 27, 2009	Test Site No.	03CH02-HY
Temperature	24	Humidity	52%
Test Engineer	David	Configurations	Channel 3


**Horizontal**

Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	
		Line	Limit	Level	Factor	Loss	Factor	Pos	Pos	Remark
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	4882.000	48.68	-5.32	54.00	43.14	35.83	4.64	34.93	---	--- PK
2	7319.000	50.98	-3.02	54.00	42.74	37.87	5.64	35.27	---	--- PK
3	9768.000	53.68	-20.32	74.00	43.48	39.53	6.36	35.70	---	--- Peak
4	9768.000	46.14	-7.86	54.00	35.95	39.53	6.36	35.70	---	--- Average


**Vertical**

Freq	Level	Over Limit	Limit Line	Read		Ant Pos	Table Pos	Remark	
				Antenna Factor	Cable Loss Factor				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4882.000	49.59	-4.41	54.00	44.70	35.18	4.64	34.93	---
2	7322.840	55.97	-18.03	74.00	48.66	36.93	5.64	35.27	---
3	7322.840	48.43	-5.57	54.00	41.13	36.93	5.64	35.27	---
4	9764.000	52.38	-21.62	74.00	42.99	38.73	6.36	35.70	---
5	9764.000	44.84	-9.16	54.00	35.45	38.73	6.36	35.70	---

Test date	Mar. 27, 2009	Test Site No.	03CH02-HY
Temperature	24	Humidity	52%
Test Engineer	David	Configurations	Channel 5

**Horizontal**

Freq	Level	Over Limit	Limit Line	Read		Ant Pos	Table Pos	Remark	
				Antenna	Cable				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4960.000	50.56	-3.44	54.00	44.80	35.95	4.72	34.91	---
2	7440.000	53.62	-20.38	74.00	45.36	37.89	5.65	35.29	---
3	7440.000	46.08	-7.92	54.00	37.83	37.89	5.65	35.29	---
4	9920.000	54.05	-19.95	74.00	43.64	39.72	6.39	35.70	---
5	9920.000	46.51	-7.49	54.00	36.10	39.72	6.39	35.70	---

**Vertical**

	Freq	Level	Over Limit	Limit Line	Read		Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark	
					MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm
1	4964.000	49.96	-4.04	54.00	44.89	35.27	4.72	34.91	4.72	34.91	---	---	PK
2	7440.000	53.93	-20.07	74.00	46.59	36.98	5.65	35.29	5.65	35.29	---	---	Peak
3	7440.000	46.38	-7.62	54.00	39.04	36.98	5.65	35.29	5.65	35.29	---	---	Average
4	9920.000	53.09	-20.91	74.00	43.48	38.92	6.39	35.70	6.39	35.70	---	---	PEAK
5	9920.000	45.55	-8.45	54.00	35.94	38.92	6.39	35.70	6.39	35.70	---	---	Average

## Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

### 3.5. Band Edge Emissions Measurement

#### 3.5.1. Limit

Band edge emissions radiated outside of the specified frequency bands shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### 3.5.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

#### 3.5.3. Test Procedures

1. The test procedure is the same as section 3.2.3, only the frequency range investigated is limited to 2MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

#### 3.5.4. Test Setup Layout

This test setup layout is the same as that shown in section 3.2.4.

#### 3.5.5. Test Deviation

There is no deviation with the original standard.

#### 3.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 3.5.7. Test Result of Band Edge and Fundamental Emissions

Test date	Nov. 19, 2008	Test Site No.	03CH02-HY
Temperature	24	Humidity	52%
Test Engineer	Duncan	Configurations	Channel 1, 5

## Channel 1

Freq	Level	Over Limit		Read	Antenna	Cable	Preamp	Ant	Table		Remark
		MHz	dBuV/m			Level	Factor		Pos	Pos	
				dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	2390.000	67.79	-6.21	74.00	33.00	31.79	3.00	0.00	---	---	Peak
2	2400.000	72.69	-1.31	74.00	37.90	31.79	3.00	0.00	---	---	Peak
3	2401.770	101.23	-12.77	114.00	66.44	31.79	3.00	0.00	---	---	Peak
1	2326.530	47.66	-6.34	54.00	13.19	31.51	2.96	0.00	---	---	Average
2	2400.000	33.28	-20.72	54.00	-1.51	31.79	3.00	0.00	---	---	Average
3	2401.770	72.07	-21.93	94.00	37.28	31.79	3.00	0.00	---	---	Average

## Channel 5


Freq	Level	Over Limit		Read	Antenna	Cable	Preamp	Ant	Table		Remark
		MHz	dBuV/m			Level	Factor		Pos	Pos	
				dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	2480.050	101.21	-12.79	114.00	66.02	32.13	3.06	0.00	---	---	Peak
2	2483.500	67.28	-6.72	74.00	32.09	32.13	3.06	0.00	---	---	Peak
1	2480.050	72.16	-21.84	94.00	36.97	32.13	3.06	0.00	---	---	Average
2	2483.500	38.23	-15.77	54.00	3.04	32.13	3.06	0.00	---	---	Average

## Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).


Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## Low Band Edge Plot on 2402 MHz



Date: 2.DEC.2008 07:10:30

## High Band Edge Plot on 2480 MHz



Date: 2.DEC.2008 07:15:52

### **3.6. Antenna Requirements**

#### **3.6.1. Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

#### **3.6.2. Antenna Connector Construction**

Please refer to section 2.1 in this test report; antenna connector complied with the requirements.

#### 4. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30 MHz - 1 GHz 3m	May 12, 2008	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11146	100 kHz – 1.3 GHz	Jul. 11, 2008	Radiation (03CH02-HY)
Spectrum Analyzer	R&S	FSP40	100305/040	9 kHz - 40GHz	Feb. 04, 2009	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30 MHz - 2 GHz	Nov. 30, 2008	Radiation (03CH02-HY)
Turn Table	HD	DS 420	420/649/00	0 - 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	HD	MA 240	240/559/00	1 m - 4 m	N/A	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB020	30 MHz - 1 GHz	Dec. 17, 2008	Radiation (03CH02-HY)
Amplifier	Agilent	8449B	3008A02373	1GHz – 26.5 GHz	Jul. 16, 2008	Radiation (03CH02-HY)
Horn Antenna	ETS-LINDGREN	3117	00091920	1GHz-18GHz	Oct. 22, 2008	Radiation (03CH02-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX106	03CH02-HY	1GHz-40GHz	Dec. 17, 2008	Radiation (03CH02-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 11, 2008	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2008	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Jul. 18, 2008	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2008	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2008	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 13, 2008	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 10, 2008	Conducted (TH01-HY)
Oscilloscope	Tektonix	TDS380	B016197	400MHz/ 2GS/s	Jun. 27, 2008	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year. NCR: Non-Calibration required.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul 28, 2008*	Radiation (03CH02-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 30, 2008*	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

## 5. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 728, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

## 6. TAF CERTIFICATE OF ACCREDITATION



Certificate No.: L1190-070110

財團法人全國認證基金會  
Taiwan Accreditation Foundation

## Certificate of Accreditation

This is to certify that

**Sporton International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria : ISO/IEC 17025:2005  
Accreditation Number : 1190  
Originally Accredited : December 15, 2003  
Effective Period : January 10, 2007 to January 09, 2010  
Accredited Scope : Testing Field, see described in the Appendix  
Specific Accreditation Program : Accreditation Program for Designated Testing Laboratory  
for Commodities Inspection  
: Accreditation Program for Telecommunication Equipment  
Testing Laboratory

Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : January 10, 2007

P1, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.