



Test report No:  
NIE: 62129RRF.017

## Partial Test report

USA FCC Part 15.247, 15.209

CANADA RSS-247, RSS-Gen

Radio Frequency Devices.

Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz.

Radiated emission limits; general requirements.

Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices.

General Requirements and Information for the Certification of Radio Apparatus.

(*) Identification of item tested	Wireless hearing instrument
(*) Trademark	ReSound, Beltone, Interton, GN Hearing
(*) Model and /or type reference	CAR13A
Other identification of the product	HW version: PCBA, CAMBR RIE13 PB, V1.A, rev. B SW version: Dooku 2 FCC ID: X26CAR13A IC: 6941C-CAR13A
(*) Features	Audio amplification, proprietary 2.4 GHz wireless functionality (Proximity), Bluetooth 5.0 and 10.667 MHz wireless magnetic induction functionality
Applicant	GN HEARING A/S Lautrupbjerg 7, 2750 Ballerup, Denmark
Test method requested, standard	USA FCC Part 15.247 (10-1-19) Edition: Operation within the bands 902 - 928 MHz, 2400 -2483.5 MHz, and 5725 - 5850 MHz. USA FCC Part 15.209 (10-1-19) Edition: Radiated emission limits; general requirements. CANADA RSS-247 Issue 2 (February 2017). CANADA RSS-Gen Issue 5 (March 2019). -Transmitter out of band radiated emissions with simultaneous transmissions. Guidance for Performing Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid Systems Devices Operating Under Section 15.247 of the FCC Rules. 558074 D01 Meas Guidance v05r02 dated April 2, 2019. ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.
Approved by (name / position & signature)	Rafael López Martín EMC Consumer & RF Lab. Manager
Date of issue	2020-07-06
Report template No	FDT08_22 (*) "Data provided by the client"

## Index

Competences and guarantees .....	3
General conditions.....	3
Uncertainty.....	3
Data provided by the client .....	3
Usage of samples .....	3
Test sample description.....	4
Identification of the client .....	6
Testing period and place .....	6
Document history.....	6
Environmental conditions .....	6
Remarks and comments.....	6
Testing verdicts.....	8
Summary .....	8
Appendix A: Test results. Bluetooth Low Energy 5.0 (2M, 1M) + SRD 10.667 MHz .....	9
Appendix B: Test results. Proprietary protocol 2.4 GHz + SRD 10.667 MHz .....	19

## Competences and guarantees

---

DEKRA Testing and Certification is a testing laboratory accredited by the National Accreditation Body (ENAC - Entidad Nacional de Acreditación), to perform the tests indicated in the Certificate No. 51/LE 147.

DEKRA Testing and Certification is a FCC-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

DEKRA Testing and Certification is an ISED-recognized accredited testing laboratory with appropriate scope of accreditation that include testing performed in this test report.

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification at the time of performance of the test.

DEKRA Testing and Certification is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification.

## General conditions

---

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification and the Accreditation Bodies.

## Uncertainty

---

Uncertainty (factor  $k=2$ ) was calculated according to the DEKRA Testing and Certification internal document PODT000.

## Data provided by the client

---

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item tested", "Trademark", "Model and/or type reference tested").
2. The sample of the model CAR13A is a wireless hearing aid.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of result.

## Usage of samples

Samples undergoing test have been selected by: The client.

- Sample S/01 is composed of the following elements:

Control Nº	Description	Model	Serial Nº	Date of reception
62129C/268	Wireless hearing instrument	CAR13A	2000801584	2020/04/16

Sample S/01 has undergone the test(s): The Radiated tests indicated in Appendixes A, B.

## Test sample description

Ports.....:	Port name and description	Cable							
		Specified max length [m]	Attached during test	Shielded	Coupled to patient <sup>(3)</sup>				
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
Supplementary information to the ports.....:									
Rated power supply .....	Voltage and Frequency	Reference poles							
		L1	L2	L3	N				
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
		<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
		<input checked="" type="checkbox"/>	DC: Internal non-rechargeable battery.						
Rated Power .....	1.45 V								
Clock frequencies.....:	2.48 GHz and 10.667 MHz								
Other parameters .....									

Software version .....	Dooku 2		
Hardware version .....	PCBA, CAMBR RIE13 PB, V1.A, rev. B		
Dimensions in cm (W x H x D) ....:			
Mounting position .....	<input type="checkbox"/>	Table top equipment	
	<input type="checkbox"/>	Wall/Ceiling mounted equipment	
	<input type="checkbox"/>	Floor standing equipment	
	<input type="checkbox"/>	Hand-held equipment	
	<input checked="" type="checkbox"/>	Other: Placed behind ear	
Modules/parts.....:	Module/parts of test item	Type	Manufacturer
Accessories (not part of the test item) .....	Description	Type	Manufacturer
	Computer	Certified according to IEC 60950-1, IEC 62368-1 or equivalent standard	
Documents as provided by the applicant .....	Description	File name	Issue date

<sup>(3)</sup> Only for Medical Equipment

## Identification of the client

GN HEARING A/S  
Lautrupbjerg 7, 2750 Ballerup, Denmark

## Testing period and place

<b>Test Location</b>	DEKRA Testing and Certification S.A.U.
<b>Date (start)</b>	2020-05-18
<b>Date (finish)</b>	2020-05-19

## Document history

Report number	Date	Description
62129RRF.017	2020-07-06	First release

## Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 20 % Max. = 75 %
<b>Air pressure</b>	Min. = 860 mbar Max. = 1060 mbar

In the semianechoic chamber, the following limits were not exceeded during the test.

<b>Temperature</b>	Min. = 15 °C Max. = 35 °C
<b>Relative humidity</b>	Min. = 20 % Max. = 75 %
<b>Air pressure</b>	Min. = 860 mbar Max. = 1060 mbar

## Remarks and comments

The tests have been performed by the technical personnel: José Manuel Jiménez and José Gabriel Pérez.

Used instrumentation:

### Radiated Measurements:

		Last Calibration	Due Calibration
1.	Semianechoic Absorber Lined Chamber ETS LINDGREN FACT 3 200 STP	N.A.	N.A.
2.	Shielded Room ETS LINDGREN S101	N.A.	N.A.
3.	Active Loop Antenna HEWLETT PACKARD 11966A	2018/06	2020/06
4.	EMI Test Receiver 7 GHz ROHDE AND SCHWARZ ESR7	2018/10	2020/10
5.	DC Power Supply 30V/5A KEYSIGHT TECHNOLOGIES U8002A	N.A.	N.A.
6.	Digital Multimeter, FLUKE 175	2019/10	2020/10
7.	Biconical/Log Antenna 30MHz - 6GHz ETS LINDGREN 3142E	2017/09	2020/09
8.	RF Pre-amplifier 40 dB, 10 MHz - 6 GHz BONN ELEKTRONIK BLNA 0160-01N	2020/02	2021/02
9.	Horn antenna 1-18 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9120 D	2018/01	2021/01
10.	Broadband Horn antenna 18 - 40 GHz SCHWARZBECK MESS-ELEKTRONIK BBHA 9170	2018/07	2021/07
11.	RF Pre-amplifier G>30dB, 1-18GHz BONN ELEKTRONIK BLMA 0118-3A	2019/11	2020/11
12.	Low Noise Amplifier G>30dB, 18 - 40 GHz BONN ELEKTRONIK BLMA 1840-1M	2019/02	2021/02
13.	Signal and Spectrum Analyzer ROHDE AND SCHWARZ FSV40	2019/10	2021/10

## Testing verdicts

Not applicable:	N/A
Pass:	P
Fail:	F
Not measured:	N/M

## Summary

FCC PART 15 PARAGRAPH / RSS-247		
Requirement – Test case	Verdict	Remark
FCC 15.31 (h), 15.209 (a), 15.247 (d) / RSS-Gen 8.9, RSS-247 5.5: - Emission limitations radiated (Transmitter)	P	(1)
<u>Supplementary information and remarks:</u>		
(1) Only co-location radiated spurious emission test was requested.		

## **Appendix A: Test results. Bluetooth Low Energy 5.0 (2M, 1M) + SRD 10.667 MHz**

## INDEX

TEST CONDITIONS.....	11
FCC 15.31 (h), 15.209 (a), 15.247 (d) / RSS-Gen 8.9, RSS-247 5.5 Emission limitations radiated (Transmitter) .....	14

## TEST CONDITIONS

### POWER SUPPLY (V):

Vnominal: 1.45 Vdc

Type of Power Supply: Battery.

### ANTENNA:

Type of Antenna: Integral.

Maximum Declared Antenna Gain for Bluetooth LE: -11.1 dBi

Maximum Declared Antenna Gain for Inductive coil: Not Applicable

### RADIOS AND CHANNELS TESTED:

	Bluetooth Low Energy 5.0 (2M, 1M) / DTS	
Mode:	1M (GFSK - 1DH5)	
Channel Spacing:	2 MHz	
Frequency Range:	2402 MHz to 2480 MHz	
Transmit Channel:	Channel	Channel Frequency (MHz)
	39	2480

	SRD 10.667 MHz / D-BPSK	
Mode:	Single Channel	
Channel Spacing:	Not Applicable	
Frequency Range:	5 – 30 MHz	
Transmit Channel:	Channel	Channel Frequency (MHz)
	1	10.667

The EUT was tested in the following operating mode:

- Continuous transmission with a modulated carrier at maximum power in all required channels selecting the supported data rates/modulations types.

During transmitter test the EUT was being controlled by the SW tool to operate in a continuous transmit mode on the test channel as required and in each of the different modulation modes.

### Transmission modes selected with each Radio:

The following configurations were selected based on preliminary testing that identified those corresponding to the worst cases:

\* Bluetooth Low Energy: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in 1Mbps.

\* SRD 10.667 MHz: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in the single channel configuration supported by this radio.

### Simultaneous transmission modes selected:

\* Co-location Bluetooth, SRD 10.667 MHz, with the EUT configured to simultaneously transmit two signals at maximum output power: Bluetooth Low Energy in 1Mbps mode, SRD 10.667 MHz.


### RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m (Loop antenna for the range between 9 kHz to 30 MHz and Bilog antenna for 30 MHz to 1000 MHz) and at a distance of 1 m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-26 GHz horn antenna).


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.


Radiated measurements setup 30 MHz < f < 1 GHz:



Radiated measurements setup  $f > 1$  GHz up to 17 GHz:



Radiated measurements setup  $f > 17$  GHz up to 40 GHz:



## FCC 15.31 (h), 15.209 (a), 15.247 (d) / RSS-Gen 8.9, RSS-247 5.5 Emission limitations radiated (Transmitter)

### SPECIFICATION:

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), appearing outside of the band 13.110 MHz - 14.010 MHz band must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength ( $\mu$ V/m)	Field strength (dB $\mu$ V/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	29.54	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 40000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Test performed on the following worst cases in all relevant tests channels.

### **Frequency range 9 kHz - 30 MHz**

The spurious emissions do not depend on either the operating channel or the modulation mode.

No spurious frequencies detected at less than 20 dB below the limit.

Measurement uncertainty (dB):  $< \pm 2.99$

### **Frequency range 30 MHz - 1 GHz**

The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode.

No spurious frequencies detected at less than 20 dB below the limit.

Measurement uncertainty (dB):  $< \pm 5.08$


### **Frequency range 1 - 26 GHz**

Spurious frequencies detected closest to the limit:


Spurious frequency (GHz)	Emission Level (dB $\mu$ V/m)	Polarization	Detector	Measurement Uncertainty (dB)
4.96023	49.71	V	Peak	$< \pm 5.13$
9.92043	51.11	V	Peak	$< \pm 5.13$

Verdict: PASS


**FREQUENCY RANGE 9 kHz - 30 MHz (worst case):**




**FREQUENCY RANGE 30 MHz - 1 GHz (worst case):**




**FREQUENCY RANGE 1 – 3 GHz (worst case):**



**FREQUENCY RANGE 3 – 17 GHz (worst case):**



**FREQUENCY RANGE 17 – 26 GHz (worst case):**



## **Appendix B: Test results. Proprietary protocol 2.4 GHz + SRD 10.667 MHz**

## INDEX

TEST CONDITIONS.....	21
FCC 15.31 (h), 15.209 (a), 15.247 (d) / RSS-Gen 8.9, RSS-247 5.5 Emission limitations radiated (Transmitter) .....	24

## TEST CONDITIONS

### POWER SUPPLY (V):

Vnominal: 1.45 Vdc

Type of Power Supply: Battery.

### ANTENNA:

Type of Antenna: Integral.

Maximum Declared Antenna Gain for Proprietary protocol 2.4 GHz: -11.1 dBi

Maximum Declared Antenna Gain for Inductive coil: Not Applicable

### RADIOS AND CHANNELS TESTED:

	Proprietary protocol 2.4 GHz / DTS	
Mode:	2 Mbps	
Channel Spacing:	2 MHz	
Frequency Range:	2402 MHz to 2480 MHz	
Transmit Channel:	Channel	Channel Frequency (MHz)
	39	2480

	SRD 10.667 MHz / D-BPSK	
Mode:	Single Channel	
Channel Spacing:	Not Applicable	
Frequency Range:	5 – 30 MHz	
Transmit Channel:	Channel	Channel Frequency (MHz)
	1	10.667

The EUT was tested in the following operating mode:

- Continuous transmission with a modulated carrier at maximum power in all required channels selecting the supported data rates/modulations types.

During transmitter test the EUT was being controlled by the SW tool to operate in a continuous transmit mode on the test channel as required and in each of the different modulation modes.

### Transmission modes selected with each Radio:

The following configurations were selected based on preliminary testing that identified those corresponding to the worst cases:

- \* Proprietary protocol 2.4 GHz: Transmitter radiated spurious emissions tests were performed with the EUT transmitting with a bit rate of 2 Mbps.
- \* SRD 10.667 MHz: Transmitter radiated spurious emissions tests were performed with the EUT transmitting in the single channel configuration supported by this radio.

### Simultaneous transmission modes selected:

- \* Co-location Bluetooth, SRD 10.667 MHz, with the EUT configured to simultaneously transmit two signals at maximum output power: Proprietary protocol 2.4 GHz in 2 Mbps mode, SRD 10.667 MHz.


### RADIATED MEASUREMENTS

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m (Loop antenna for the range between 9 kHz to 30 MHz and Bilog antenna for 30 MHz to 1000 MHz) and at a distance of 1 m for the frequency range 1 GHz-26 GHz (1 GHz-18 GHz Double ridge horn antenna and 18 GHz-26 GHz horn antenna).


The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.


Radiated measurements setup 30 MHz < f < 1 GHz:



Radiated measurements setup  $f > 1$  GHz up to 17 GHz:



Radiated measurements setup  $f > 17$  GHz up to 40 GHz:



## FCC 15.31 (h), 15.209 (a), 15.247 (d) / RSS-Gen 8.9, RSS-247 5.5 Emission limitations radiated (Transmitter)

### SPECIFICATION:

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), appearing outside of the band 13.110 MHz - 14.010 MHz band must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c) / RSS-Gen):

Frequency Range (MHz)	Field strength ( $\mu$ V/m)	Field strength ( $\text{dB}\mu$ V/m)	Measurement distance (m)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705 - 30.0	30	29.54	30
30 - 88	100	40	3
88 - 216	150	43.5	3
216 - 960	200	46	3
960 - 40000	500	54	3

The emission limits shown in the above table are based on measurements employing CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

For average radiated emission measurements above 1000 MHz, there is also a limit corresponding to 20 dB above the indicated values in the table is specified when measuring with peak detector function.

RSS-247. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### RESULTS:

The situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

All tests were performed in a semi-anechoic chamber at a distance of 3 m for the frequency range 30 MHz-1000 MHz and at distance of 1m for the frequency range 1 GHz-26 GHz.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

Test performed on the following worst cases in all relevant tests channels.

### **Frequency range 9 kHz - 30 MHz**

The spurious emissions do not depend on either the operating channel or the modulation mode.

No spurious frequencies detected at less than 20 dB below the limit.

Measurement uncertainty (dB):  $< \pm 2.99$

### **Frequency range 30 MHz - 1 GHz**

The spurious emissions below 1 GHz do not depend on either the operating channel or the modulation mode.

No spurious frequencies detected at less than 20 dB below the limit.

Measurement uncertainty (dB):  $< \pm 5.08$


### **Frequency range 1 - 26 GHz**

Spurious frequencies detected closest to the limit:


Spurious frequency (GHz)	Emission Level (dB $\mu$ V/m)	Polarization	Detector	Measurement Uncertainty (dB)
4.95930	49.40	V	Peak	$< \pm 5.13$
9.92137	49.38	V	Peak	$< \pm 5.13$

Verdict: PASS


**FREQUENCY RANGE 9 kHz - 30 MHz (worst case):**



**FREQUENCY RANGE 30 MHz - 1 GHz (worst case):**




### FREQUENCY RANGE 1 – 3 GHz (worst case):



Date: 19.MAY.2020 19:14:18

The peak above the highest limit is the Proprietary protocol 2.4 GHz carrier frequency.

### FREQUENCY RANGE 3 – 17 GHz (worst case):



Date: 19.MAY.2020 19:04:50

**FREQUENCY RANGE 17 – 26 GHz (worst case):**

