

Test report No:  
NIE: 79301RAN.002A1

## Assessment report

### RF EXPOSURE REPORT ACCORDING TO

FCC 47 CFR Part 2.1093  
FCC 47 CFR Part 1.1307

(*) Identification of item under evaluation	Rechargeable hearing instrument
(*) Trademark	ReSound, Beltone, Interton, GN Hearing, Danavox, Audigy, Jabra, GN Audio
(*) Model and /or type reference	LUBR90
(*) Other identification of the product	FCC ID : X26LUBR90 IC ID : 6941C-LUBR90 HW version : LUBR90,V2,C6.0 SW Version : Dooku3
(*) Features	BT 1/2Mbit, proximity & MI radio, rechargeable battery, IP68 enclosure
(*) Manufacturer	GN Hearing A/S Lautrupbjerg 7 DK-2750 Ballerup, Denmark
Test method requested, standard	FCC 47 CFR Part 2.1093. Radiofrequency radiation exposure evaluation: portable devices. FCC 47 CFR Part 1.1307: Actions that may have a significant environmental effect, for which Environmental Assessments (EAs) must be prepared.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Manuel García Antennas Lab Technical Responsible
Date of issue	2025-07-10
Report template No	FAN24_03 (*) "Data provided by the client"

## Index

Competences and guarantees .....	3
General conditions .....	3
Data provided by the client.....	3
Identification of the client.....	3
Document history .....	3
Appendix A: FCC RF Exposure assessment result .....	5
General description of the device under evaluation .....	6
Evaluation Results.....	6
Appendix B: FCC RF Exposure information .....	8
RF Exposure determination of exemption.....	9

## Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

## General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This assessment report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U.

## Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "General description of the device", "Other identification of the product").
2. Maximum output power, maximum antenna gain, maximum duty cycle and use distance information.
3. The device under evaluation consists of a Rechargeable wireless hearing aid.

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

## Identification of the client

GN Hearing A/S  
Lautrupbjerg 7  
DK-2750 Ballerup, Denmark

## Document history

Report number	Date	Description
79301RAN.002	2025-07-03	First release.

Report number	Date	Description
79301RAN.002A1	2025-07-10	Second release. Typo in FCC ID fixed. Maximum output power for 2.4 GHz BTLE and Proximity updated. This test report replaces and cancels 79301RAN.002.

## **Appendix A: FCC RF Exposure assessment result**

## General description of the device under evaluation

Table 1 provides details for the RF Evaluation, based on the following declared device specifications:

**Description and technologies:** the device under evaluation consists of a Rechargeable wireless hearing aid and supports the following radios technologies: BTLE Advertisements 1/2Mbit, BTLE, Proximity and MI radio. The RF Exposure evaluation applies only to all transmission technologies supported by the device.

**Evaluation Distance:** according to the manufacturer, during normal use, the device's radiating structures will maintain a separation distance greater than 5 cm from nearby users. For assessment purposes, a conservative evaluation distance of 0 cm (5mm applied for the evaluation) has been applied.

### Maximum output power:

Values corresponding to maximum output power have been declared by the device manufacturer. These values are stated in RF Exposure info document.

**Antennas:** the device supports several antennas for the following transmission technologies:

- “Integral antenna” for BTLE Advertisements 1/2Mbit and BTLE and Proximity transmissions.
- “MI coil antenna” for MI radio transmissions.

The manufacturer has declared the maximum peak gain values, as stated in the antenna manufacturer's datasheet.

The following table shows the information provided above:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Maximum Conducted Output Power (Incl. Tune-Up) (dBm)	Duty Cycle (%)	Time Averaged Conducted Power (dBm)	Antenna peak gain (dBi)	Maximum Average E.R.P (dBm)	Maximum Average E.R.P (mW)	Maximum Average E.I.R.P (dBm)	Maximum Average E.I.R.P (mW)
BTLE	2.4 GHz	2402 - 2480	9.50	8.18	-1.37	-8.30	-11.82	0.07	-9.67	0.11
BTLE Advertisements	2.4 GHz	2402 - 2480	3.00	1.88	-14.26	-8.30	-24.71	0.00	-22.56	0.01
Mi Radio	10.6 MHz	10.6	-6.02	50.00	-9.03	0.00	-11.18	0.08	-9.03	0.13
Proximity	2.4 GHz	2402 - 2480	9.50	0.43	-14.17	-8.30	-24.62	0.00	-22.47	0.01

Table 1: Equipment specifications

### Simultaneous Transmission Conditions:

The device supports the following simultaneous transmissions modes:

Simultaneous Transmission configuration
BTLE + Proximity + BTLE Advertisements + Mi Radio

## Evaluation Results

The determination of the exemption for the minimum intended use distance of 0 mm (5 mm applied for the evaluation) will result as follows:

Technology / Mode	Operating Band	Frequency under evaluation (MHz)	Distance (cm)	Time Averaged Conducted Power (mW)	Maximum Average d.E.R.P (mW)	§1.1307(b)(3).i.(A) Exposure Limit (mW)	§1.1307(b)(3).i.(C) Exposure Limit (mW)	§1.1307(b)(3).i.(B) Exposure Limit (mW)	Verdict
BTLE	2.4 GHz	2402 - 2480	0.50	0.73	0.07	1.00	N/A	N/A	Pass
BTLE Advertisements	2.4 GHz	2402 - 2480	0.50	0.04	0.00338	1.00	N/A	N/A	Pass
Mi Radio	10.6 MHz	10.6	0.50	0.13	0.08	1.00	N/A	N/A	Pass
Proximity	2.4 GHz	2402 - 2480	0.50	0.04	0.00346	1.00	N/A	N/A	Pass

**Table 2:** FCC Exemption Evaluation Result

The computed value(s) are below the exemption limit(s), so these modes meet the requirements stated in FCC 47 CFR Part 1.1307.

### Simultaneous transmission assessment:

The device under evaluation is able to transmit simultaneously using Proximity, 2.4 GHz BTLE, 2.4GHz BTLE Advertisements and MI Radio transmitters, therefore the most conservative approach for the evaluation of the simultaneous transmission will be:

Simultaneous technologies and modes	Result ( $\sum$ of $P_{out}/P_{max}$ ratios)	Verdict ( $\sum \leq 1$ )
BTLE 2.4 GHz + BTLE Advertisements 2.4 GHz + Mi Radio 10.6 MHz + Proximity 2.4 GHz	0.93	Pass

**Table 3:** Simultaneous Result

As the compliance criteria is fulfilled, simultaneous transmission condition is in compliance with the RF exposure requirements.

## **Appendix B: FCC RF Exposure information**

## RF Exposure determination of exemption

According to FCC 47 CFR §1.1307 (b)(3) Determination of exemption:

(i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2), a single RF source is exempt if:

(A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

(B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

(C) Or using Table 1 and the minimum separation distance ( $R$  in meters) from the body of a nearby person for the frequency ( $f$  in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply,  $R$  must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

TABLE 1 TO §1.1307(b)(3)(i)(C)—SINGLE RF SOURCES SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$ .
1.34-30	$3,450 R^2/f^2$ .
30-300	$3.83 R^2$ .
300-1,500	$0.0128 R^2 f$ .
1,500-100,000	$19.2 R^2$ .

(ii) For multiple RF sources: Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(B) of this section for Pth, including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph (b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

Pi = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

Pth,i = the exemption threshold power (Pth) according to paragraph (b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.

ERPj = the ERP of fixed, mobile, or portable RF source j.

ERPth,j = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Evaluated,k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

Exposure Limit,k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from §1.1310 of this chapter.

The available maximum time-averaged power or effective radiated power (ERP), can be calculated using the following formula to assess compliance with the Exemption Limits:

$$P_{E.I.R.P.} = P_T + G_T - L_C$$

Where:

P<sub>T</sub> = transmitter time-averaged output power (including Duty Cycle and tune-up tolerance, if applicable)

G<sub>T</sub> = gain of the transmitting antenna

L<sub>C</sub> = signal attenuation in the connecting cable between the transmitter and the antenna if applicable

$$P_{E.R.P.} = P_{E.I.R.P.} - 2.15 \text{ dB}$$