Shanghai Smarfid Security Equipment Co.,Ltd


Contactless Door Egress Device(US Standard)

Main Model: REX2110-s

Serial Model: REX2140-s,REX2110-e,REX2110-i

March 21, 2014

Report No.: 14020266-FCC-E



Modifications made to the product: None

This Test Report is Issued Under the Authority of:

William long Alex-Lin

William Long Compliance Engineer Alex Liu Technical Manager



This test report may be reproduced in full only.

Test result presented in this test report is applicable to the representative sample only.

EMC Test Report

SIEMIC, INC.
Accessing global mark

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to <u>testing</u> and <u>certification</u>, SIEMIC provides initial design reviews and <u>compliance</u> <u>management</u> through out a project. Our extensive experience with <u>China</u>, <u>Asia Pacific</u>, <u>North America</u>, <u>European</u>, <u>and international</u> compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the <u>global markets</u>.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, Telecom
Canada	EMC, RF/Wireless, Telecom
Taiwan	EMC, RF, Telecom, Safety
Hong Kong	RF/Wireless ,Telecom
Australia	EMC, RF, Telecom, Safety
Korea	EMI, EMS, RF, Telecom, Safety
Japan	EMI, RF/Wireless, Telecom
Singapore	EMC, RF, Telecom
Europe	EMC, RF, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	5
2	TECHNICAL DETAILS	6
3	MODIFICATION	7
4	TEST SUMMARY	8
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
AN]	NEX A. TEST INSTRUMENTATION & GENERAL PROCEDURES	13
AN	NEX B. EUT AND TEST SETUP PHOTOGRAPHS	18
AN]	NEX C. TEST SETUP AND SUPPORTING EQUIPMENT	24
AN]	NEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	27
AN	NEX E. DECLARATION OF SIMILARITY	28

Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 5 of 28

1 EXECUTIVE SUMMARY & EUT INFORMATION

The purpose of this test programme was to demonstrate compliance of the Shanghai Smarfid Security Equipment Co.,Ltd, Contactless Door Egress Device(US Standard) and Model: REX2110-s against the current Stipulated Standards. The Contactless Door Egress Device(US Standard) has demonstrated compliance with the FCC Part 15 Subpart B Class B: 2013, ANSI C63.4: 2009.

EUT Information

EUT Description	Contactless Door Egress Device(US Standard)
Main Model	REX2110-s
Serial Model	REX2140-s,REX2110-e,REX2110-i
Input Power	9 - 15VDC 150mA
Antenna Gain	12dbi
Classification Per Stipulated Test Standard	Per FCC Part 15 Subpart B Class B: 2013, ANSI C63.4: 2009

Note: the difference between these models please refer to the Annex E.

2 TECHNICAL DETAILS

Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 6 of 28

	- IECHI (ICHE DETIILE)
Purpose	Compliance testing of Contactless Door Egress Device(US Standard) with stipulated standards
Applicant / Client	Shanghai Smarfid Security Equipment Co.,Ltd Room 301,4th Bldg.,No.4 TongLi Road,Songjiang District,Shanghai 201615,China
Manufacturer	Shanghai Smarfid Security Equipment Co.,Ltd Room 301,4th Bldg.,No.4 TongLi Road,Songjiang District,Shanghai 201615,China
Laboratory performing the tests	SIEMIC (Nanjing-China) Laboratories NO.2-1,Longcang Dadao, Yuhua Economic Development Zone, Nanjing, China Tel: +86(25)86730128/86730129 Fax: +86(25)86730127 Email: China@siemic.com
Test report reference number	14020266-FCC-E
Date EUT received	January 08,2014
Standard applied	FCC Part 15 Subpart B Class B: 2013, ANSI C63.4: 2009
Equipment Category	СҮҮ
Dates of test (from – to)	March 20,2014
No of Units	#1
Trade Name	VITTO
RF Operating Frequency (ies)	433.896MHz:(Rx)
FCC ID	X3AREX2110EIS



Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 7 of 28

MODIFICATION

NONE

Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 8 of 28

www.siemic.com.cn

4 TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

Test Results Summary

	Emissions					
Test Standard	Description	Product Class	Pass / Fail			
§ 15.107	Conducted Emissions	N/A	N/A			
§ 15.109	Radiated Emissions	Class B	Pass			

All measurement uncertainty is not taken into consideration for all presented test result.

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 § 15.107 Conducted Emissions Test Result

Note:

- 1. All possible modes of operation were investigated. Only the several worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
- 2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
- 3. <u>Conducted Emissions Measurement Uncertainty</u>

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz - 30MHz (Average & Quasi-peak) is $\pm 3.86dB$.

4. Environmental Conditions Temperature 20°C

Relative Humidity 50% Atmospheric Pressure 1009mbar

5. Test date : --Tested By : --

Test Result: N/A

Battery Operated

5.2 § 15.109 Radiated Emissions Test Result

Note:

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.

2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.

3. Radiated Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30 MHz - 1 GHz (QP only @ 3m & 10m) is +6 dB/-6 dB (for EUTs < 0.5 m X 0.5m).

4. Environmental Conditions Temperature 20°C Relative Humidity 50%

Atmospheric Pressure 1011mbar


5. Test date: March 20, 2014 Tested By: William Long

Test Result: Pass

Test Mode: Normal Working

Below 1GHz

Peak Detector Quasi Peak Limit



Test Data


Vertical & Horizontal Polarity Plot at 3m


Frequency (MHz)	Quasi Peak (dBµV/m)	Azimuth	Polarity (H/V)	Height (cm)	Factors (dB)	Limit (dBµV/m)	Margin (dB)
167.50	39.23	168.00	Н	171.00	-31.78	43.50	-4.27
164.20	40.96	166.00	Н	181.00	-31.65	43.50	-2.54
153.03	36.98	169.00	Н	170.00	-31.78	43.50	-6.52
287.18	29.44	308.00	V	272.00	-29.65	46.00	-16.56
128.39	34.17	154.00	Н	323.00	-31.47	43.50	-9.33
263.35	26.44	321.00	V	104.00	-30.01	46.00	-19.56

Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 12 of 28 www.siemic.com.c

Test Mode: Normal Working

1-3**GHz**





Test Data

Vertical & Horizontal Polarity Plot at 3m

Frequency (MHz)	Peak (dBuV/m)	Azimuth	Polarity(H /V)	Height (cm)	Factors (dB)	Limit (dBuV/m)	Margin (dB)
2289.00	28.36	63.10	V	100.00	-33.98	70.00	-41.64
2463.50	27.62	74.10	Н	100.00	-33.69	70.00	-42.38
1990.00	27.33	74.10	V	100.00	-34.53	70.00	-42.67
2203.50	27.22	74.10	Н	100.00	-34.13	70.00	-42.78
2083.50	27.09	74.10	V	100.00	-34.33	70.00	-42.91
1948.25	26.99	76.90	V	100.00	-34.77	70.00	-43.01

Note: The data above 3GHz which below 20 dB to the limit was not recorded.

Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 13 of 28

Annex A. TEST INSTRUMENTATION & GENERAL PROCEDURES

Annex A.i. TEST INSTRUMENTATION


Instrument	Model	Serial #	Calibration Date	Calibration Due Date
Radiated Emissions				
Hp Spectrum Analyzer	8563E	3821A09023	09/27/2013	09/26/2014
R&S EMI Receiver	ESPI3	101216	09/27/2013	09/26/2014
Antenna (30MHz~6GHz)	JB6	A121411	03/27/2013	03/26/2014
ETS-Lindgren Antenna (1 ~18GHz)	3115	N/A	10/09/2013	10/08/2014
A-INFOMW Antenna (1 ~18GHz)	JXTXLB- 10180	J2031081120 092	10/09/2013	10/08/2014
Horn Antenna (18~40GHz)	AH-840	101013	04/22/2013	04/22/2014
Microwave Pre-Amp (18~40GHz)	PA-840	181250	05/30/2013	05/29/2014
Hp Agilent Pre-Amplifier	8447F	1937A01160	10/27/2013	10/26/2014
MITEQ Pre-Amplifier (0.1 ~ 18GHz)	AMF-7D- 00101800- 30-10P	1451709	10/27/2013	10/26/2014
Chamber	3m	N/A	04/13/2013	04/12/2014
SIEMIC Labview Radiated Emissions software	V1.0	N/A	N/A	N/A

Annex A.ii. AC LINE CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
- 2. The power supply for the EUT was fed through a $50\Omega/50\mu$ H EUT LISN, connected to filtered mains.
- 3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.

4. All other supporting equipments were powered separately from another main supply.



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration1

Test Method

- 1. The EUT was switched on and allowed to warm up to its normal operating condition.
- 2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
- 3. High peaks, relative to the limit line, were then selected.
- 4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
- 5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Description of Conducted Emission Program

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the common scan range from 150 kHz to 30 MHz; the program will first start a peak and average scan on selectable measurement time and step size. After the program complete the pre-scan, this program will perform the Quasi Peak and Average measurement, based on the pre-scan peak data reduction result.

Sample Calculation Example

At 20 MHz $limit = 250 \mu V = 47.96 dB\mu V$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = $40.00~\text{dB}\mu\text{V}$ (Calibrated for system losses)

Therefore, Q-P margin = 47.96 - 40.00 = 7.96 i.e. **7.96 dB below limit**

Annex A. iii. RADIATED EMISSIONS TEST DESCRIPTION


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8 m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred; clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS) or 3m EMC chamber.

Test Set-up

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5mX1.0mX0.8m high, non-conductive table.
- 2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
- 3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



For the actual test configuration, please refer to the related item - Photographs of the Test Configuration2

Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

- 1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

- 1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
- 2. For emission frequencies measured below 1GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on an open test site. As the same purpose, for emission frequencies measured above 1GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below and above 1GHz, set the spectrum analyzer on a 100kHz and 1MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
- 5. Repeat step 4 until all frequencies need to be measured was complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100kHz	100kHz
Above 1000	Peak	1MHz	1MHz
Above 1000	Average	1MHz	10Hz

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

Peak = Reading + Corrected Factor

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any) And the average value is

Average = Peak Value + Duty Factor or Set RBW = 1MHz, VBW = 10Hz.


Note:

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1GHz. And the measuring instrument is set to quasi peak detector function.


Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 18 of 28

Annex B. EUT AND TEST SETUP PHOTOGRAPHS

Annex B.i. Photograph: EUT External Photo



EUT - Front View



EUT - Rear View


SIEMIC, INC.

Accessing global markets
Title: EMC Test Report for Contactless Door Egress Device(US Standard)
Main Model: REX2110-s
Serial Model: REX2140-s,REX2110-e,REX2110-i
To: FCC Part 15 Subpart B Class B: 2013, ANSI C63.4:2009

Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 19 of 28



EUT – Top View



EUT – Bottom View (Receiver)




SIEMIC, INC.

Accessing global markets
Title: EMC Test Report for Contactless Door Egress Device(US Standard)
Main Model: REX2110-s
Serial Model: REX2140-s, REX2110-e, REX2110-i
To: FCC Part 15 Subpart B Class B: 2013, ANSI C63.4:2009

Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 20 of 28




EUT - Left View




EUT - Right View

Annex B.ii. Photograph 2: EUT Internal Photo



EUT (Receiver) – Uncover Front View



EUT (Receiver)-PCB 1 Front View

Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 22 of 28


6 Militaria de de la companio del la companio del la companio de la companio del la companio de la companio del la companio de la companio del la companio 6

EUT (Receiver)-PCB 1 Rear View


PCB Antenna

Report No.: 14020266-FCC-E Issue Date: March 21, 2014 Page: 23 of 28 www.sjemic.com.c

Annex B.iii. Photograph 3: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz - Front View



Radiated Spurious Emissions Test Setup Above 1GHz-Front View

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

	Manufacturer	Equipment Description (Including Brand Name)	Model	Calibration Due Date
1	N/A	N/A	N/A	N/A

Block Configuration Diagram for Radiated Emission



Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions	Normal Working

Annex D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment

Annex E. DECLARATION OF SIMILARITY

SMARFID

Shanghai Smarfid Security Equipment Co., Ltd.

Add: Room 301, 4th Bldg., No.4 TongLi Road, SongJiang District, Shanghai 201615, China

Tel: (86-21) 54260103, 54260132 ext.215 Fax: (86-21) 54260132 ext.222

DECLARATION OF SIMILARITY

March, 25, 2014

To: SIEMIC (Nanjing-China) Laboratories

Tel: 25-8673 0128-618 Fax: +86-25-8673 0127

www.siemic.com.cn

Dear Sir or Madam:

For our business issue and marketing requirement, we would like to list different models numbers on the FCC certificates and reports, as following:

The product name: Contactless Door Egress Device. (US Standard)

Model No.: REX2110-s, REX2140-s , REX2110-e, REX2110-i

The four models have the same Circuits, components, and color.

A description of the differences between the tested model and those that are declared similar areas follows:

Models	REX21 10-s	REX214	REX211 O-i	REX2110-
proximity	Y	Y	Y	Y
doorbell	Y	Y	Y	N
alarm	Y	Y	Y	N
glass broken	Y	Y	N	N

Please contact me should there be need for any additional clarification or information. Best Regards,

Songlin dai

Manager

