

FCC ID.: X3WP1BC Report No.: TS10010017-EME

RF Exposure Statement

Equipment Information

Type of equipment: Beacon Type / Model: T500, R360

Applicant: Taiwan Jaio Co., Ltd.

21F-2 No.83, Sec.1, Zhongxiao E. Rd., Taipei City 10049, Taiwan

The EUT is a Beacon, and was defined as information technology equipment.

The customer confirmed the different model numbers serve as marketing strategy. These models are identical in hardware aspect.

The differences between main model and series model are listed as below.

Model No.	Differences
1500	Standard Version with all features for US (pre-loaded with map information for US market)
1 2360	Rangefinder Version with simplified UI and less features for US (pre-loaded with map information for US market)

Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Measurement Result:

This is a portable device with the max. peak output power -0.74 dBm (0.84 mW) much lower than the low threshold 60/f GHz mW (24.48 mW), d<2.5 cm general population category.

Therefore, the SAR/MPE measurement is not necessary.

Date of issue: Jan. 22, 2010

Dex Liao

Rex Liao

Engineer

Intertek Testing Services Taiwan Ltd.

No. 11, Lane 275, Ko-Nan 1 Street, Chia-Tung Li,

Shiang-Shan District, Hsinchu City, Taiwan