

MRT Technology (Suzhou) Co., Ltd Phone: +86-512-66308358

Web: www.mrt-cert.com

Report No.: 1710WSU01001 Report Version: V02 Issue Date: 04-16-2018

MEASUREMENT REPORT

FCC PART 15.247 Bluetooth

FCC ID: X3ZWFMOD1

APPLICANT: Amp'ed RF Technology, Inc.

Application Type: Certification

Product: Wi-Fi & BLE combo module

Model No.: ART6212

Brand Name: ART

FCC Classification: Digital Transmission System (DTS)

FCC Rule Part(s): Part15 Subpart C (Section 15.247)

Test Procedure(s): ANSI C63.10-2013

KDB 558074 D01v04

Test Date: October 10, 2016 ~ April 04, 2017

Reviewed By : Kein Como

Kevin Guo)

Approved By : Marlinchen

(Marlin Chen)





The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01v04. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co.. Ltd.

FCC ID: X3ZWFMOD1 Page Number: 1 of 44



Revision History

Report No.	Version	Description	Issue Date	Note
1710WSU01001	Rev. 01	Initial Report	01-11-2018	Invalid
1710WSU01001	Rev. 02	Add antenna description	04-16-2018	Valid

FCC ID: X3ZWFMOD1 Page Number: 2 of 44



CONTENTS

De	scription	on	Page
1.	INTR	ODUCTION	6
	1.1.	Scope	6
	1.2.	MRT Test Location	6
2.	PRO	DUCT INFORMATION	7
	2.1.	Feature of Equipment under Test	7
	2.2.	Working Frequencies	8
	2.3.	Description of Avilable Antenna	8
	2.4.	Description of Test Software	8
	2.5.	Device Capabilities	8
	2.6.	Test Configuration	9
	2.7.	EMI Suppression Device(s)/Modifications	9
	2.8.	Labeling Requirements	9
3.	DES	CRIPTION OF TEST	10
	3.1.	Evaluation Procedure	10
	3.2.	AC Line Conducted Emissions	10
	3.3.	Radiated Emissions	11
4.	ANTI	ENNA REQUIREMENTS	12
5.	TEST	Γ EQUIPMENT CALIBRATION DATE	13
6.	MEA	SUREMENT UNCERTAINTY	14
7.	TEST	Γ RESULT	15
	7.1.	Summary	15
	7.2.	6dB Bandwidth Measurement	16
	7.2.1.	Test Limit	16
	7.2.2.	Test Procedure used	16
	7.2.3.	Test Setting	16
	7.2.4.	Test Setup	16
	7.2.5.	Test Result	17
	7.3.	Output Power Measurement	18
	7.3.1.	Test Limit	18
	7.3.2.	Test Procedure Used	18
	7.3.3.	Test Setting	18
	7.3.4.	Test Setup	18
	7.3.5.	Test Result of Output Power	19



7.4.	Power Spectral Density Measurement	20
7.4.1.	Test Limit	20
7.4.2.	Test Procedure Used	20
7.4.3.	Test Setting	20
7.4.4.	Test Setup	20
7.4.5.	Test Result	21
7.5.	Conducted Band Edge and Out-of-Band Emissions	22
7.5.1.	Test Limit	22
7.5.2.	Test Procedure Used	22
7.5.3.	Test Settitng	22
7.5.4.	Test Setup	23
7.5.5.	Test Result	24
7.6.	Radiated Spurious Emission Measurement	26
7.6.1.	Test Limit	26
7.6.2.	Test Procedure Used	26
7.6.3.	Test Setting	26
7.6.4.	Test Setup	28
7.6.5.	Test Result	30
7.7.	Radiated Restricted Band Edge Measurement	35
7.7.1.	Test Result	35
7.8.	AC Conducted Emissions Measurement	43
7.8.1.	Test Limit	43
7.8.2.	Test Setup	43
7.8.3.	Test Result	43
CONC	CLUSION	44



§2.1033 General Information

Applicant:	Amp'ed RF Technology, Inc.		
Applicant Address:	1879 Lundy Ave, Suite 138, San Jose, CA, 95131		
Manufacturer:	Amp'ed RF Technology, Inc.		
Manufacturer Address:	1879 Lundy Ave, Suite 138, San Jose, CA, 95131		
Test Site:	MRT Technology (Suzhou) Co., Ltd		
Test Site Address:	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development		
	Zone, Suzhou, China		
MRT Registration No.:	893164		
FCC Rule Part(s):	Part15 Subpart C (Section 15.247)		
Test Device Serial No.:	N/A ☐ Production ☐ Pre-Production ☐ Engineering		

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 893164) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-4179, G-814, C-4664, T-2206) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications and Radio testing for FCC, Industry Canada, EU and TELEC Rules.



FCC ID: X3ZWFMOD1 Page Number: 5 of 44



1. INTRODUCTION

1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



FCC ID: X3ZWFMOD1 Page Number: 6 of 44



2. PRODUCT INFORMATION

2.1. Feature of Equipment under Test

Wi-Fi & BLE combo module
ART6212
ART
DC 3.6V
n
2402 ~ 2480MHz
V4.1
GFSK
PCB
3 dBi
2.4GHz:
For 802.11b/g/n-HT20: 2412 ~ 2462 MHz
5GHz:
For 802.11a/n-HT20-VHT20: 5180~5240MHz, 5745~5825MHz
802.11b: DSSS
802.11a/g/n: OFDM
Chip
0.5 dBi for 2.4GHz
2 dBi for 5GHz

Note: For other features of this EUT, test report will be issued separately.

FCC ID: X3ZWFMOD1 Page Number: 7 of 44



2.2. Working Frequencies

Channel List for BLE

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz
03	2408 MHz	04	2410 MHz	05	2412 MHz
06	2414 MHz	07	2416 MHz	08	2418 MHz
09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz
15	2432 MHz	16	2434 MHz	17	2436 MHz
18	2438 MHz	19	2440 MHz	20	2442 MHz
21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz
27	2456 MHz	28	2458 MHz	29	2460 MHz
30	2462 MHz	31	2464 MHz	32	2466 MHz
33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz
39	2480 MHz				

2.3. Description of Avilable Antenna

Antenna Specification							
Model Name Type Frequency Band Connector Max. Peak Gain							
AT3216-B2R7HAA	Surface Mount	2.4G WiFi	Solder	0.2 dBi			
AT3216-B5R5HAA	Surface Mount	5G WiFi	Solder	2 dBi			
479501011	PCB Trace	Bluetooth	U.FL	3 dBi			

2.4. Description of Test Software

The test utility software used during testing was "Wi-Fi Term", and the version was "v4.11".

2.5. Device Capabilities

This device contains the following capabilities:

802.11a/b/g/n Wi-Fi and BLE Device.

FCC ID: X3ZWFMOD1 Page Number: 8 of 44



2.6. Test Configuration

The **Wi-Fi & BLE combo module** was tested per the guidance of KDB 558074 D01v04. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

2.7. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.8. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

FCC ID: X3ZWFMOD1 Page Number: 9 of 44



3. DESCRIPTION OF TEST

3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01v04 were used in the measurement of the **Wi-Fi & BLE combo module.**

Deviation from measurement procedure......None

3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, $50\Omega/50uH$ Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions were used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.8.

FCC ID: X3ZWFMOD1 Page Number: 10 of 44



3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the Antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive Antenna height using a broadband Antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn Antennas were used. For frequencies below 30MHz, a calibrated loop Antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband Antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive Antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn Antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive Antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive Antenna, whichever produced the worst-case emissions. According to 3dB Beam-Width of horn Antenna, the horn Antenna should be always directed to the EUT when rising height.

FCC ID: X3ZWFMOD1 Page Number: 11 of 44



4. ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

Conclusion:

The Wi-Fi & BLE combo module unit complies with the requirement of §15.203.

FCC ID: X3ZWFMOD1 Page Number: 12 of 44



5. TEST EQUIPMENT CALIBRATION DATE

Conducted Emissions - SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR3	MRTSUE06185	1 year	2018/04/28
Two-Line V-Network	R&S	ENV216	MRTSUE06002	1 year	2018/06/21
Two-Line V-Network	R&S	ENV216	MRTSUE06003	1 year	2018/06/21
Temperature/Humidity Meter	Yuhuaze	HTC-2	MRTSUE06179	1 year	2017/12/22
Shielding Anechoic Chamber	Mikebang	Chamber-SR2	MRTSUE06215	1 year	2018/05/10

Radiated Disturbance - AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
MXE EMI Receiver	Agilent	N9038A	MRTSUE06125	1 year	2018/08/03
Microwave System Amplifier	Agilent	83017A	MRTSUE06076	1 year	2018/03/28
Loop Antenna	Schwarzbeck	FMZB1519	MRTSUE06025	1 year	2017/12/21
Bilog Period Antenna	Schwarzbeck	VULB 9168	MRTSUE06172	1 year	2017/11/19
Horn Antenna	Schwarzbeck	BBHA9120D	MRTSUE06023	1 year	2017/10/22
Broadband Horn Antenna	Schwarzbeck	BBHA9170	MRTSUE06024	1 year	2018/04/25
Digitial Thermometer & Hygrometer	Minggao	ETH529	MRTSUE06170	1 year	2017/11/30
Anechoic Chamber	TDK	Chamber-AC1	MRTSUE06212	1 year	2018/05/10

Conducted Test Equipment - TR3

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9020A	MRTSUE06106	1 year	2018/04/25
USB Wideband Power Sensor	Boonton	55006	MRTSUE06109	1 year	2018/04/25
Temperature/Humidity Meter	Yuhuaze	HTC-2	MRTSUE06184	1 year	2017/12/22

Software	Version	Function
e3	V8.3.5	EMI Test Software

FCC ID: X3ZWFMOD1 Page Number: 13 of 44



Report No.: 1710WSU01001

6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

AC Conducted Emission Measurement - SR2

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):


150kHz~30MHz: 3.46dB

Radiated Emission Measurement - AC1

Measuring Uncertainty for a Level of Confidence of 95% (U=2Uc(y)):

9kHz ~ 1GHz: ± 4.18dB 1GHz ~ 25GHz: ± 4.76dB

FCC ID: X3ZWFMOD1 Page Number: 14 of 44





7. TEST RESULT

7.1. Summary

Company Name: Wi-Fi & BLE combo module

FCC ID: X3ZWFMOD1

FCC Classification: <u>Digital Transmission System (DTS)</u>

Data Rate(s) Tested: 1Mbps(GFSK) (BLE)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference			
15.247(a)(2)	6dB Bandwidth	≥ 500kHz	Conducted	Pass			Pass	Section 7.2
15.247(b)(3)	Output Power	≤ 1Watt			Pass	Section 7.3		
15.247(e)	Power Spectral Density	≤ 8dBm / 3kHz		Pass	Section 7.4			
15.247(d)	Band Edge / Out-of-Band Emissions	≥ 20dBc(Peak)		Pass	Section 7.5			
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Radiated	Pass	Section 7.6 & 7.7			
15.207	AC Conducted Emissions 150kHz - 30MHz	< FCC 15.207 limits	Line Conducted	N/A	Section 7.8			

Notes:

- The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 2) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 3) Test Items "6dB Bandwidth" & "Band Edge / Out-of-Band Emissions" have been assessed single, and showed the worst test data in this report.

FCC ID: X3ZWFMOD1 Page Number: 15 of 44



7.2. 6dB Bandwidth Measurement

7.2.1.Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.2.2.Test Procedure used

KDB 558074 D01v04 - Section 8.2 Option 2

7.2.3.Test Setting

- The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. Set RBW = 100 kHz
- 3. VBW ≥ 3 × RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. Allow the trace was allowed to stabilize

7.2.4.Test Setup




FCC ID: X3ZWFMOD1 Page Number: 16 of 44

Report No.: 1710WSU01001



7.2.5.Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
BLE	1	00	2402	0.73	≥ 0.5	Pass
BLE	1	19	2440	0.73	≥ 0.5	Pass
BLE	1	39	2480	0.73	≥ 0.5	Pass



FCC ID: X3ZWFMOD1 Page Number: 17 of 44



7.3. Output Power Measurement

7.3.1.Test Limit

The maximum out power shall be less 1 Watt (30dBm).

7.3.2.Test Procedure Used


KDB 558074 D01v04 - Section 9.1.2 PKPM1 - Peak Power Method

7.3.3.Test Setting

Method PKPM1 (Peak Power Measurement of Signals with DTS BW ≤ 50MHz)

Peak power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The pulse sensor employs a VBW = 50MHz so this method was only used for signals whose DTS bandwidth was less than or equal to 50MHz.

7.3.4.Test Setup



FCC ID: X3ZWFMOD1 Page Number: 18 of 44



7.3.5.Test Result of Output Power

Test Result of Peak Output Power

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Peak Power (dBm)	Limit (dBm)	Result
BLE	1	00	2402	1.17	≤ 30	Pass
BLE	1	19	2440	1.25	≤ 30	Pass
BLE	1	39	2480	<mark>1.36</mark>	≤ 30	Pass

FCC ID: X3ZWFMOD1 Page Number: 19 of 44



7.4. Power Spectral Density Measurement

7.4.1.Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.


7.4.2.Test Procedure Used

KDB 558074 D01v04 - Section 10.2 Method PKPSD

7.4.3.Test Setting

- 1. Analyzer was set to the center frequency of the DTS channel under investigation
- 2. Span = 1.5 times the DTS channel bandwidth
- 3. RBW = 3kHz
- 4. VBW = 10kHz
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Trace was allowed to stabilize

7.4.4.Test Setup




FCC ID: X3ZWFMOD1 Page Number: 20 of 44



7.4.5.Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	PSD Result (dBm / 3kHz)	Limit (dBm / 3kHz)	Result
BLE	1	00	2402	-8.65	≤ 8	Pass
BLE	1	19	2440	-8.89	≤ 8	Pass
BLE	1	39	2480	-9.27	≤ 8	Pass



FCC ID: X3ZWFMOD1 Page Number: 21 of 44



7.5. Conducted Band Edge and Out-of-Band Emissions

7.5.1.Test Limit

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

7.5.2.Test Procedure Used

KDB 558074 D01v04 - Section 11.2 & Section 11.3

7.5.3.Test Settitng

Reference level measurement

- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to ≥ 1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- 4. Set the VBW ≥ 3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- 7. Trace mode = max hold
- 8. Allow trace to fully stabilize

Emission level measurement

Set the center frequency and span to encompass frequency range to be measured

RBW = 100kHz

VBW = 300kHz

Detector = Peak

Number of sweep points ≥ 2 x Span/RBW

Trace mode = max hold


Sweep time = auto couple

The trace was allowed to stabilize

FCC ID: X3ZWFMOD1 Page Number: 22 of 44



7.5.4.Test Setup




FCC ID: X3ZWFMOD1 Page Number: 23 of 44



7.5.5.Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Limit	Result
BLE	1	00	2402	20dBc	Pass
BLE	1	19	2440	20dBc	Pass
BLE	1	39	2480	20dBc	Pass



FCC ID: X3ZWFMOD1 Page Number: 24 of 44



Channel 19 (2440MHz) 100kHz PSD reference Level Spurious Emission 30MHz ~ 25GHz | Agitam Spatters | Agitam Spa Avg Type: Log-Pwr Avg|Hold:>100/100 Avg Type: Log-Pwr Avg|Hold:>100/100 738 25 GF 0.579 dBi Ref Offset 11.8 dB Ref 11.80 dBm Ref Offset 11.8 dB Ref 11.80 dBm -57.471 dBm -54.975 dBm -55.469 dBm Mkr-RefLv More 1 of 2 More 1 of 2 **Channel 39 (2480MHz)** 100kHz PSD reference Level **High Band Edge** Avg Type: Log-Pwr Avg|Hold:>100/100 Avg Type: Log-Pwr Avg|Hold:>100/100 241 50 GF 0.161 dBi Ref Offset 11.8 dB Ref 11.80 dBm Ref Offset 11.8 dB Ref 11.80 dBm Marker Marker Marker Mkr→RefLv More 1 of 2 More 1 of 2 **Spurious Emission 30MHz ~ 25GHz** Avg Type: Log-Pwr Avg|Hold:>100/100 Ref Offset 11.8 dB Ref 11.80 dBm 6.472 GHz -56.432 dBm 9.119 GHz -55.059 dBm 13.064 GHz -55.165 dBm

FCC ID: X3ZWFMOD1 Page Number: 25 of 44

More 1 of 2



7.6. Radiated Spurious Emission Measurement

7.6.1.Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209									
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]							
0.009 - 0.490	2400/F (kHz)	300							
0.490 - 1.705	24000/F (kHz)	30							
1.705 - 30	30	30							
30 - 88	100	3							
88 - 216	150	3							
216 - 960	200	3							
Above 960	500	3							

7.6.2.Test Procedure Used

KDB 558074 D01v04 - Section 12.2.3 (quasi-peak measurements)

KDB 558074 D01v04 - Section 12.2.4 (peak power measurements)

KDB 558074 D01v04 - Section 12.2.5 (average power measurements)

7.6.3.Test Setting

Peak Field Strength Measurements per Section 12.2.4 of KDB 558074 D01v04

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = as specified in Table 1
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple

FCC ID: X3ZWFMOD1 Page Number: 26 of 44



- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements per Section 12.2.4 of KDB 558074 D01v04


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ 1/T
- 4. De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
- 5. Detector = Peak
- 6. Sweep time = auto
- 7. Trace mode = max hold
- 8. Allow max hold to run for at least 50 times (1/duty cycle) traces

FCC ID: X3ZWFMOD1 Page Number: 27 of 44




7.6.4.Test Setup

9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




FCC ID: X3ZWFMOD1 Page Number: 28 of 44



1GHz ~ 18GHz Test Setup:




18GHz ~25GHz Test Setup:



FCC ID: X3ZWFMOD1 Page Number: 29 of 44







7.6.5.Test Result

Test Mode:	BLE	Test Site:	AC1					
Test Channel:	00	Test Engineer:	Will Yan					
Remark:	Average measurement was not performed if peak level lower than average							
	limit.							
	2. Other frequency was 20dB bel	2. Other frequency was 20dB below limit line within 1-18GHz, there is not show						
	in the report.							


Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
*	3533.0	35.3	-1.0	34.4	74	-39.6	Peak	Horizontal
*	4417.0	36.4	1.4	37.9	74	-36.1	Peak	Horizontal
	4799.5	47.0	2.7	49.7	74	-24.3	Peak	Horizontal
	5400.0	34.2	3.1	37.3	74	-36.7	Peak	Horizontal
*	3517.0	35.8	-1.1	34.7	74	-39.3	Peak	Vertical
*	4419.0	35.8	1.4	37.2	74	-36.8	Peak	Vertical
	4799.5	39.7	2.7	42.4	74	-31.6	Peak	Vertical
	7415.0	34.4	8.0	42.3	74	-31.7	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (93.9dBµV/m) or 15.209 which is higher.

Note 2: Measure Level (dBµV/m) = Reading Level (dBµV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

FCC ID: X3ZWFMOD1 Page Number: 30 of 44





Test Mode:	BLE	Test Site:	AC1					
Test Channel:	19	Test Engineer:	Will Yan					
Remark:	Average measurement was no limit.	Average measurement was not performed if peak level lower than average limit.						
	Other frequency was 20dB bel in the report.	ow limit line within 1	-18GHz, there is not show					


Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
*	3522.0	36.1	-1.0	35.0	74	-39.0	Peak	Horizontal
*	4425.0	35.8	1.4	37.3	74	-36.7	Peak	Horizontal
	4876.0	44.8	2.7	47.4	74	-26.6	Peak	Horizontal
	7617.0	34.4	8.1	42.4	74	-31.6	Peak	Horizontal
*	3417.0	35.9	-1.6	34.3	74	-39.7	Peak	Vertical
*	4425.0	36.1	1.4	37.6	74	-36.4	Peak	Vertical
	4876.0	40.3	2.7	42.9	74	-31.1	Peak	Vertical
	7418.0	34.7	8.0	42.6	74	-31.4	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (93.7dBµV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

FCC ID: X3ZWFMOD1 Page Number: 31 of 44





Test Mode:	BLE	Test Site:	AC1
Test Channel:	39	Test Engineer:	Will Yan
Remark:	 Average measurement was no limit. Other frequency was 20dB bel in the report. 		·

Mark	Frequency	Reading	Factor	Measure	Limit	Margin	Detector	Polarization
	(MHz)	Level	(dB)	Level	(dBµV/m)	(dB)		
		(dBµV)		(dBµV/m)				
*	3417.0	36.5	-1.6	34.9	74	-39.1	Peak	Horizontal
*	4425.0	36.1	1.4	37.5	74	-36.5	Peak	Horizontal
	4961.0	45.2	2.9	48.1	74	-25.9	Peak	Horizontal
	7425.0	34.9	8.0	42.9	74	-31.1	Peak	Horizontal
*	3426.0	36.5	-1.5	35.0	74	-39.0	Peak	Vertical
*	4435.0	36.1	1.5	37.6	74	-36.4	Peak	Vertical
	4961.0	42.0	2.9	44.9	74	-29.1	Peak	Vertical
	7456.0	34.2	8.1	42.3	74	-31.7	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (92.2dBµV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

FCC ID: X3ZWFMOD1 Page Number: 32 of 44



The worst case of Radiated Emission below 1GHz:

Note: There is the worst case within frequency range 30MHz~1GHz.						
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V					
Probe: VULB9168_20-2000MHz	Polarity: Horizontal					
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang					
Site: AC1	Time: 2017/04/01 - 10:48					



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	229.335	30.385	18.654	-15.615	46.000	11.731	QP
2			249.705	29.691	17.390	-16.309	46.000	12.301	QP
3			265.225	28.617	16.054	-17.383	46.000	12.563	QP
4			402.480	30.326	15.314	-15.674	46.000	15.012	QP
5			676.020	29.218	10.354	-16.782	46.000	18.864	QP
6			780.295	27.781	7.649	-18.219	46.000	20.132	QP

Note 1: Measure Level ($dB\mu V/m$) = Reading Level ($dB\mu V$) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)


Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

FCC ID: X3ZWFMOD1 Page Number: 33 of 44



Note: There is the worst case within frequency range 30MHz~1GHz.						
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V					
Probe: VULB9168_20-2000MHz	Polarity: Vertical					
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang					
Site: AC1	Time: 2017/04/01 - 10:55					

Note: There is the worst case within frequency range 30MHz~1GHz.



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)	(dB)	
				(dBuV/m)	(dBuV)				
1		*	32.910	25.742	13.678	-14.258	40.000	12.064	QP
2			57.160	23.715	10.034	-16.285	40.000	13.681	QP
3			143.490	26.074	17.664	-17.426	43.500	8.410	QP
4			358.830	26.449	12.117	-19.551	46.000	14.332	QP
5			403.450	27.414	12.387	-18.586	46.000	15.027	QP
6			472.320	27.255	11.323	-18.745	46.000	15.932	QP

Note 1: Measure Level ($dB\mu V/m$) = Reading Level ($dB\mu V$) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: $9kHz \sim 30MHz$, $18GHz \sim 25GHz$), therefore no data appear in the report..


FCC ID: X3ZWFMOD1 Page Number: 34 of 44



7.7. Radiated Restricted Band Edge Measurement

7.7.1.Test Result

Site: AC1	Time: 2016/10/18 - 01:06				
Limit: FCC_Part15.209_RE(3m)	Engineer: Will Yan				
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal				
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V				
Test Mode: Transmit by BLE at Channel 2402MHz					



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)		
				(dBuV/m)	(dBuV)				
1			2378.637	58.145	26.921	-15.855	74.000	31.223	PK
2			2390.000	56.534	25.331	-17.466	74.000	31.203	PK
3		*	2402.292	93.850	62.666	19.850	74.000	31.184	PK


Note: Measure Level (dB μ V/m) = Reading Level (dB μ V) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: X3ZWFMOD1 Page Number: 35 of 44



Site: AC1	Time: 2016/10/18 - 01:11				
Limit: FCC_Part15.209_RE(3m)	Engineer: Will Yan				
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal				
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V				
Test Mode: Transmit by BLE at Channel 2402MHz					




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)		
				(dBuV/m)	(dBuV)				
1			2390.000	43.666	12.463	-10.334	54.000	31.203	AV
2		*	2402.008	92.933	61.749	38.933	54.000	31.184	AV

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: X3ZWFMOD1 Page Number: 36 of 44



Site: AC1	Time: 2016/10/18 - 01:12
Limit: FCC_Part15.209_RE(3m)	Engineer: Will Yan
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V
Test Mode: Transmit by BLE at Channel 2402MHz	•




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)		
				(dBuV/m)	(dBuV)				
1			2388.470	58.383	27.177	-15.617	74.000	31.206	PK
2		*	2401.722	88.486	57.302	14.486	74.000	31.184	PK

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: X3ZWFMOD1 Page Number: 37 of 44



Site: AC1	Time: 2016/10/18 - 01:14				
Limit: FCC_Part15.209_RE(3m)	Engineer: Will Yan				
Probe: BBHA9120D_1-18GHz	Polarity: Vertical				
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V				
Test Mode: Transmit by BLE at Channel 2402MHz					




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)		
				(dBuV/m)	(dBuV)				
1			2390.000	43.664	12.461	-10.336	54.000	31.203	AV
2		*	2402.008	87.843	56.659	33.843	54.000	31.184	AV

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: X3ZWFMOD1 Page Number: 38 of 44



Site: AC1	Time: 2016/10/18 - 01:15			
Limit: FCC_Part15.209_RE(3m)	Engineer: Will Yan			
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal			
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V			
Test Mode: Transmit by BLE at Channel 2480MHz				




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)		
				(dBuV/m)	(dBuV)				
1		*	2479.771	92.249	61.065	18.249	74.000	31.184	PK
2			2483.500	56.800	25.607	-17.200	74.000	31.194	PK
3			2484.974	58.162	26.965	-15.838	74.000	31.197	PK

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: X3ZWFMOD1 Page Number: 39 of 44



Site: AC1	Time: 2016/10/18 - 01:17			
Limit: FCC_Part15.209_RE(3m)	Engineer: Will Yan			
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal			
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V			
Test Mode: Transmit by BLE at Channel 2480MHz				




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)		
				(dBuV/m)	(dBuV)				
1		*	2480.002	91.441	60.257	37.441	54.000	31.184	AV
2			2483.500	44.187	12.994	-9.813	54.000	31.194	AV

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: X3ZWFMOD1 Page Number: 40 of 44



Site: AC1	Time: 2016/10/18 - 01:17			
Limit: FCC_Part15.209_RE(3m)	Engineer: Will Yan			
Probe: BBHA9120D_1-18GHz	Polarity: Vertical			
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V			
Test Mode: Transmit by BLE at Channel 2480MHz				




No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)		
				(dBuV/m)	(dBuV)				
1		*	2480.145	86.516	55.332	12.516	74.000	31.185	PK
2			2483.500	56.832	25.639	-17.168	74.000	31.194	PK
3			2484.710	58.723	27.526	-15.277	74.000	31.197	PK

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: X3ZWFMOD1 Page Number: 41 of 44



Site: AC1	Time: 2016/10/18 - 01:20			
Limit: FCC_Part15.209_RE(3m)	Engineer: Will Yan			
Probe: BBHA9120D_1-18GHz	Polarity: Vertical			
EUT: Wi-Fi & BLE combo module	Power: DC 3.6V			
Test Mode: Transmit by BLE at Channel 2480MHz				



No	Flag	Mark	Frequency	Measure	Reading	Over Limit	Limit	Factor	Туре
			(MHz)	Level	Level	(dB)	(dBuV/m)		
				(dBuV/m)	(dBuV)				
1		*	2480.079	85.595	54.411	31.595	54.000	31.184	AV
2			2483.500	44.115	12.922	-9.885	54.000	31.194	AV

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

FCC ID: X3ZWFMOD1 Page Number: 42 of 44



7.8. AC Conducted Emissions Measurement


7.8.1.Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits								
Frequency QP AV (dBuV) (dBuV)								
0.15 - 0.50	66 - 56	56 - 46						
0.50 - 5.0	56	46						
5.0 - 30	60	50						

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.8.2.Test Setup



7.8.3.Test Result

This test was not performed since the EUT is a build-in module which will be powerd by the host equipment.

FCC ID: X3ZWFMOD1 Page Number: 43 of 44



Report No.: 1710WSU01001

8. CONCLUSION

The data collected relate only the item(s) tested and show that the **Wi-Fi & BLE combo module** is in compliance with Part 15C of the FCC Rules.

———— The End ————

FCC ID: X3ZWFMOD1 Page Number: 44 of 44