FCC ID: X4D-COM-PT

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB 447498 (2)(a)(i)

Frequency Range		Center	
Low Frequency (MHz)	High Frequency(MHz)	frequency (MHz)	60/f SAR Limitation (mw)
2412	2462	2437	25

Maximum measured transmitter power 802.11b

Conducted Power (mw)	Max Antenna Gain (dBi)	EIRP (mw)
15.85	0.79	19.02

Maximum measured transmitter power 802.11g

Conducted Power (mw)	Max Antenna Gain (dBi)	EIRP (mw)
12.88	0.79	15.46

Maximum measured transmitter power 802.11n-20MHz

Conducted Power (mw)	Max Antenna Gain (dBi)	EIRP (mw)
9.12	0.79	10.94

Maximum measured transmitter power 802.11n-40MHz

Conducted Power (mw)	Max Antenna Gain (dBi)	EIRP (mw)
7.59	0.79	9.11

Threshold at which no SAR required is 25 mw.

Maximum Tx power is 19.02mw EIRP.

Conclusion: No SAR is required.

SIMULTANEOUS TRANSMISSION EVALUATION

N/A