



**Solutions**

**FCC Part 1 Subpart I  
FCC Part 2 Subpart J  
INDUSTRY CANADA RSS-102 ISSUE 5**

**RF EXPOSURE REPORT**

**FOR**

**TASER 7 VR CONTROLLER**

**MODEL NAME: VR1002**

**FCC ID: X4GS01834B  
IC: 8803A-S01834B**

**REPORT NUMBER: R14950775-E3**

**ISSUE DATE: 2023-12-18**

**Prepared for  
AXON ENTERPRISE INC.  
17800 NORTH 85TH STREET  
SCOTTSDALE, AZ 85255, USA**

**Prepared by  
UL LLC  
12 LABORATORY DR.  
RESEARCH TRIANGLE PARK, NC 27709 USA  
TEL: (919) 549-1400**



## REPORT REVISION HISTORY

Rev.	Issue Date	Revisions	Revised By
V1	2023-10-30	Initial Issue	Charles Moody
V2	2023-12-06	Revised Declared Maximum Output Power	Charles Moody
V3	2023-12-18	Revised Declared Separation Distance	Charles Moody

## TABLE OF CONTENTS

<b>REPORT REVISION HISTORY .....</b>	<b>2</b>
<b>TABLE OF CONTENTS .....</b>	<b>3</b>
<b>1. ATTESTATION OF TEST RESULTS .....</b>	<b>4</b>
<b>2. TEST METHODOLOGY .....</b>	<b>5</b>
<b>3. REFERENCES .....</b>	<b>5</b>
<b>4. FACILITIES AND ACCREDITATION .....</b>	<b>5</b>
<b>5. DECISION RULES AND MEASUREMENT UNCERTAINTY.....</b>	<b>6</b>
5.1. <i>METROLOGICAL TRACEABILITY .....</i>	<i>6</i>
5.2. <i>DECISION RULES.....</i>	<i>6</i>
<b>6. DEVICE UNDER TEST.....</b>	<b>6</b>
<b>7. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....</b>	<b>7</b>
7.1. <i>FCC .....</i>	<i>7</i>
7.2. <i>ISED CANADA .....</i>	<i>8</i>
<b>END OF TEST REPORT .....</b>	<b>8</b>

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** Axon Enterprise Inc.  
17800 North 85th Street  
Scottsdale, AZ 85255, USA

**EUT DESCRIPTION:** TASER 7 VR CONTROLLER

**MODEL:** VR1002

**SAMPLE RECEIPT DATE:** 2023-09-29

**DATE TESTED:** 2023-10-09

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies
ISED CANADA RSS-102 ISSUE 5	Complies

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document.

Approved & Released  
For UL LLC By:



Michael Ferrer  
Staff Engineer  
Consumer, Medical and IT Segment  
UL LLC

Prepared By:



Charles Moody  
Engineer  
Consumer, Medical and IT Segment  
UL LLC

## 2. TEST METHODOLOGY

All calculations were made in accordance with FCC Parts 1.1310, 2.1091, 2.1093, KDB 447498 D01 v06, KDB 447498 D03 V01, IEEE Std C95.1-2005, and IEEE Std C95.3-2002.

This report contains data provided by the customer which can impact the validity of results. UL LLC is only responsible for the validity of results after the integration of the data provided by the customer.

## 3. REFERENCES

Output power, Duty cycle and Antenna gain data is excerpted from the applicable test reports or client declarations.

## 4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, certification # 0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input type="checkbox"/>	Building: 12 Laboratory Dr RTP, NC 27709, U.S.A	US0067	2180C	825374
<input checked="" type="checkbox"/>	Building: 2800 Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A		27265	

## 5. DECISION RULES AND MEASUREMENT UNCERTAINTY

### 5.1. METROLOGICAL TRACEABILITY

The measuring equipment used to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 5.2. DECISION RULES

For all tests where the applicable  $U_{LAB} \leq U_{MAX}$  the Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2, where  $U_{MAX} = 30\% (0.3)$  for RF Exposure evaluations. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

For all tests where the applicable  $U_{LAB} > U_{MAX}$  the Decision Rule is based on Guarded Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.3.2, with a guard band equal to  $(U_{LAB} - U_{MAX})$ , where  $U_{MAX} = 30\% (0.3)$  for RF Exposure evaluations. (Test results are adjusted by the value of the guard band to determine conformity with a specified requirement.)

## 6. DEVICE UNDER TEST

The EUT is a TASER 7 VR CONTROLLER that contains a BLE transceiver.

Separation distances, output power, and antenna gain have been declared by the manufacturer and can be found in documentation provided.

## 7. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

### 7.1. FCC

SAR test exclusion in accordance with KDB 447498.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$\{(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})\} \cdot [f(\text{GHz})] \leq 3.0$ , for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison.

This test exclusion is applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $> 50$  mm are determined by:

1.  $\{(\text{Power allowed at numeric threshold for } 50 \text{ mm})] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$  mW, for 100 MHz to 1500 MHz
  - $f_{(\text{MHz})}$  is the RF channel transmit frequency in MHz.
2.  $\{(\text{Power allowed at numeric threshold for } 50 \text{ mm})] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\}$  mW, for  $> 1500$  MHz and  $\leq 6$  GHz.

#### SAR Exclusion Calculation Table for Portable Devices (separation distance $< 50$ mm)

Tx	Frequency (MHz)	Average Output power		Separation distances (mm)	Calculated Threshold
		dBm	mW		
BLE 2.4 GHz	2480	7.00	5.01	23.61	0.3

#### Conclusion:

The calculated threshold value is  $< 3$ ; therefore, the device qualifies for Standalone SAR test exclusion.

Note: minimum distance used in above table is lowest value declared distance.

## 7.2. ISED CANADA

The SAR exclusion table from RSS-102 issue 5 is reproduced below:

**Table 1: SAR evaluation - exemption limits for routine evaluation based on frequency and separation distance.**

Frequency MHz	Exemption Limits (mW)				
	At separation distance of ≤5mm	At separation distance of 10mm	At separation distance of 15mm	At separation distance of 20mm	At separation distance of 25mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency MHz	Exemption Limits (mW)				
	At separation distance of 30mm	At separation distance of 35mm	At separation distance of 40mm	At separation distance of 45mm	At separation distance of ≥50mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

The minimum antenna to user distance that will be encountered in normal use is 23.61mm while in use (trigger finger – limb worn) and 37.58mm while not in use (holster - body). This results in an exemption limit of 114.71mW while in use (limb worn) and 148.8mW while not in use (body) at 2450 MHz. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5.

Tx	Frequency (MHz)	Maximum Pk Power	Antenna Gain	3.83 dBi
			(dBm)	(mW)
BLE	2480	Conducted	7.00	5.01
		E.I.R.P	10.83	12.11

As the maximum average output power is 5.01 mW conducted and 12.11 mW EIRP, the DUT qualifies for SAR test exclusion.

## END OF TEST REPORT