



FCC PART 15.407

TEST REPORT

For

NEXXT SOLUTIONS

3505 N.W 107TH AVE, MIAMI, FL,33178, United States

FCC ID: X4Y604U1

Report Type: Original Report	Product Type: Wireless-N Dual Band Gigabit Router
Test Engineer: <u>Ares Liu</u> 	
Report Number: <u>R2DG130515001-00B</u>	
Report Date: <u>2013-06-03</u>	
Reviewed By: RF Leader	<u>Ivan Cao</u> 
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxihu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk “★”
(Rev.2), This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY.....	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.407(f) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	9
APPLICABLE STANDARD	9
FCC §15.203 – ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP	11
EMI TEST RECEIVER SETUP	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST PROCEDURE	13
TEST RESULTS SUMMARY.....	13
TEST DATA	13
FCC §15.209, §15.205 & §15.407(b) (1) (6) (7) – UNDESIRABLE EMISSION & RESTRICTED BANDS	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY	16
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST EQUIPMENT LIST AND DETAILS.....	18
TEST RESULTS SUMMARY.....	19
TEST DATA	19
CONDUCTED SPURIOUS EMISSION AT ANTENNA PORT.....	23
TEST DATA	23
FCC §15.407(b) (1) (2) (3) (4) – OUT OF BAND EMISSIONS	44
APPLICABLE STANDARD	44
TEST PROCEDURE	44
TEST EQUIPMENT LIST AND DETAILS.....	44
TEST DATA	45

FCC §15.407(a) (1) – 26 dB OCCUPIED BANDWIDTH	51
APPLICABLE STANDARD	51
TEST EQUIPMENT LIST AND DETAILS.....	51
TEST PROCEDURE	51
TEST DATA	51
FCC §15.407(a) (1) – CONDUCTED TRANSMITTER OUTPUT POWER.....	60
APPLICABLE STANDARD	60
TEST EQUIPMENT LIST AND DETAILS.....	60
TEST PROCEDURE	60
TEST DATA	61
FCC §15.407(a) (1) (5) - POWER SPECTRAL DENSITY	69
APPLICABLE STANDARD	69
TEST PROCEDURE	69
TEST EQUIPMENT LIST AND DETAILS.....	69
TEST DATA	70
FCC §15.407(a) (6) – PEAK EXCURSION RATIO.....	79
APPLICABLE STANDARD	79
TEST PROCEDURE	79
TEST EQUIPMENT LIST AND DETAILS.....	79
TEST DATA	79

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *NEXXT SOLUTIONS*'s product, model number: *ARN02604U1 (FCC ID: X4Y604U1)* or ("EUT") in this report is a *Wireless-N Dual Band Gigabit Router*, which was measured approximately: 17.2 cm (L) x13.6 cm (W) x18 cm (H), rated input voltage: DC 9V from adapter.

Adapter information:

Model: TEA09U-09100

Input: 100-240V, 50/60Hz, 0.3A

Output: DC 9V, 1.0A

** All measurement and test data in this report was gathered from production sample serial number: 130515001 (Assigned by BACL, Dongguan). The EUT was received on 2013-05-15.*

Objective

This type approval report is prepared on behalf of *NEXXT SOLUTIONS* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: *X4Y604U1*

FCC Part 15B JBP submissions with FCC ID: *X4Y604U1*.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at <http://ts.nist.gov/standards/scopes/5000690.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

For 5180~5240MHz band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 802.11a and 802.11n20, Channel 36, 40 and 48 was tested, for 802.11n40, Channel 38, 46 was tested.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all date rates bandwidths, and modulations.

For 802.11a, the EUT can transmit with chain 0 or chain 1, therefore investigated worst case to representative chain 0 in test report.

EUT Exercise Software

The test was performed under “*Duck 1.1.9*” which was provided by the manufacturer.

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
HP	Printer	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL05DC
SAST	Modem	AEM-2100	0293
DELL	PC	GX620	JPTVOB2337
Kingston	Flash Disk	DT101 G2	N/A

External Cable

Cable Description	Length (m)	From Port	To
Shielded Detachable Printer Cable	1.2	Parallel Port of Laptop	Printer
Shielded Detachable Serial Cable	1.2	Serial Port of Laptop	Modem
Shielded Detachable Keyboard Cable	1.5	Keyboard Port of Laptop	Keyboard
RJ45 Cable	1.0	RJ45 Port of Laptop	RJ45 Port of EUT
RJ45 Cable*4	10	RJ45 Port of PC	RJ45 Port of EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.407(b)(6)& §15.207(a)	Conducted Emissions	Compliance
§15.205& §15.209 &§15.407(b) (1),(6),(7)	Undesirable Emission& Restricted Bands	Compliance
§15.407(b) (1),(2),(3),(4)	Out Of Band Emissions	Compliance
§15.407(a) (1)	26 dB Bandwidth	Compliance
§15.407(a)(1),	Conducted Transmitter Output Power	Compliance
§15.407 (a)(1),(5)	Power Spectral Density	Compliance
§15.407(a)(6)	Peak Excursion Ratio	Compliance

FCC §15.407(f) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.407(f) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain		Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11a	5240	5	3.16	12.2	16.60	20.00	0.01045	1.0
802.11n ht20	5200	5	3.16	12.25	16.79	20.00	0.01057	1.0
802.11n ht40	5230	5	3.16	11.78	15.07	20.00	0.00948	1.0

Result: The device meet FCC MPE at 20 cm distance

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to FCC 47 CFR section 15.407 (a)(1), if transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has two dipole antennas permanently soldered on the printed circuit boards, which complied with 15.203, the maximum gain is 5.0 dBi in 2400-2483.5MHz and 5150-5850MHz, please refer to the internal photos.

Result: Compliance.

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cisp}})$, exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cisp}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCS 30	830245/006	2013-1-10	2014-1-9
R&S	L.I.S.N 1	ESH3-Z5	843331/015	2012-9-17	2013-9-16
R&S	L.I.S.N 2	ESH3-Z5	100113	2012-11-29	2013-11-28
BACL	Test Software	BACL-EMC	V1.0-2010	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the adapter was connected to the LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

12.96 dB at 0.455 MHz in the **Line** conducted mode

Test Data


Environmental Conditions

Temperature:	26.3 ° C
Relative Humidity:	68 %
ATM Pressure:	100 kPa

The testing was performed by Ares Liu on 2013-05-27.

Test Mode: Transmitting

120 V, 60 Hz, Line:



Frequency (MHz)	Cord. Reading (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (QP/AV/QP)
0.455	44.33	0.42	57.29	12.96	QP
0.455	33.72	0.42	47.29	13.57	AV
0.590	42.20	0.43	56.00	13.80	QP
0.590	31.67	0.43	46.00	14.33	AV
0.715	41.21	0.44	56.00	14.79	QP
0.715	28.87	0.44	46.00	17.13	AV
0.915	41.55	0.45	56.00	14.45	QP
0.920	28.89	0.45	46.00	17.11	AV
1.395	39.87	0.46	56.00	16.13	QP
1.390	27.93	0.46	46.00	18.07	AV
2.565	32.69	0.49	56.00	23.31	QP
2.585	22.29	0.49	46.00	23.71	AV

120V, 60 Hz, Neutral:

Frequency (MHz)	Cord. Reading (dB μ V)	Correction Factor (dB)	Limit (dB μ V)	Margin (dB)	Detector (PK/AV/QP)
0.465	43.21	0.42	57.00	13.79	QP
0.465	33.46	0.42	47.00	13.54	AV
0.520	41.58	0.42	56.00	14.42	QP
0.520	28.09	0.42	46.00	17.91	AV
0.590	39.91	0.43	56.00	16.09	QP
0.590	28.22	0.43	46.00	17.78	AV
0.930	42.26	0.45	56.00	13.74	QP
0.930	28.51	0.45	46.00	17.49	AV
1.405	41.22	0.46	56.00	14.78	QP
1.395	27.35	0.46	46.00	18.65	AV
3.635	35.21	0.50	56.00	20.79	QP
3.625	22.32	0.50	46.00	23.68	AV

FCC §15.209, §15.205 & §15.407(b) (1) (6) (7) – UNDESIRABLE EMISSION & RESTRICTED BANDS

Applicable Standard

FCC §15.407 (b) (1), (6), (7); §15.209; §15.205;

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

According to KDB 789033 D01 General UNII Test Procedures v01, emission shall be computed as:
 $E[\text{dBuV/m}] = \text{EIRP}[\text{dBm}] + 95.2$, for $d = 3$ meters.

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cisp}})$, exceeds the disturbance limit;
- non - compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} - U_{\text{cisp}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB

Table 1 – Values of U_{cisp}


Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1 G:



Above 1 G:



The radiated emission tests were performed in the 3 meters chamber, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source,

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 40 GHz	1 MHz	3 MHz	PK
1000 MHz – 40 GHz	1 MHz	10 Hz	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCI	100224	2013-5-6	2014-5-5
Sunol Sciences	Antenna	JB3	A060611-1	2012-9-6	2015-9-5
HP	HP AMPLIFIER	8447E	2434A02181	N/A	N/A
R&S	Spectrum analyzer	FSEM 30	849016/001	2012-9-4	2013-9-3
ETS LINDGREN	horn antenna	3115	000 527 35	2012-9-6	2015-9-5
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	N/A	N/A
R&S	Spectrum analyzer	FSEM 30	849016/001	2012-9-4	2013-9-3

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, Section 15.205, 15.209 and 15.407, with the worst margin reading of:

3.06 dB at 10400 MHz in the Vertical polarization for 802.11n20 Mode

Test Data

Environmental Conditions

Temperature:	29.7°C
Relative Humidity:	65 %
ATM Pressure:	99.8 kPa

The testing was performed by Ares Liu on 2013-06-03.

Mode: Transmitting

802.11a Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	FCC 15.407	
	Reading (dB μ V)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dB μ V/m)	Margin (dB)
Low Channel: 5180MHz									
5180	54.74	AV	H	33.92	5.49	0.00	94.15	N/A	N/A
5180	61.24	PK	H	33.92	5.49	0.00	100.65	N/A	N/A
5180	71.68	AV	V	33.92	5.49	0.00	111.09	N/A	N/A
5180	77.61	PK	V	33.92	5.49	0.00	117.02	N/A	N/A
10360	42.36	PK	V	39.80	8.34	26.81	63.69	68.20	4.51*
5150	25.3	PK	V	33.87	5.45	0.00	64.62	68.20	3.58*
5150	11.2	AV	V	33.87	5.45	0.00	50.52	54.00	3.48 *
1468.36	40.28	PK	H	25.47	2.94	27.29	41.40	68.20	26.80
1468.36	34.03	AV	H	25.47	2.94	27.29	35.15	54.00	18.85
15540	30.25	PK	V	44.51	11.42	24.45	61.73	68.20	6.47
15540	18.45	AV	V	44.51	11.42	24.45	49.93	54.00	4.07
400.36	42.85	QP	H	16.19	2.43	27.36	34.11	46.00	11.89
625.14	38.42	QP	H	19.88	3.06	27.42	33.94	46.00	12.06
Middle Channel: 5200MHz									
5200	57.58	AV	H	33.96	5.51	0.00	97.05	N/A	N/A
5200	64.32	PK	H	33.96	5.51	0.00	103.79	N/A	N/A
5200	70.24	AV	V	33.96	5.51	0.00	109.71	N/A	N/A
5200	75.42	PK	V	33.96	5.51	0.00	114.89	N/A	N/A
10400	42.06	PK	V	39.86	8.34	26.81	63.45	68.20	4.75*
15600	30.25	PK	V	44.38	11.46	24.41	61.68	68.20	6.52
15600	18.45	AV	V	44.38	11.46	24.41	49.88	54.00	4.12*
1347.25	41.38	PK	H	25.35	2.91	27.43	42.21	68.20	25.99
1347.25	39.52	AV	H	25.35	2.91	27.43	40.35	54.00	13.65
4324.52	40.52	PK	H	32.54	6.42	26.77	52.70	68.20	15.50
4324.52	31.02	AV	H	32.54	6.42	26.77	43.20	54.00	10.80
625.14	38.42	AV	H	19.88	3.06	22.28	39.08	46.00	6.92
425.36	34.68	QP	H	16.72	2.49	21.83	32.06	46.00	13.94
High Channel: 5240MHz									
5240	57.15	AV	H	34.03	5.09	0.00	96.28	N/A	N/A
5240	61.75	PK	H	34.03	5.09	0.00	100.88	N/A	N/A
5240	67.86	AV	V	34.03	5.09	0.00	106.99	N/A	N/A
5240	80.24	PK	V	34.03	5.09	0.00	119.37	N/A	N/A
10480	42.38	PK	V	39.97	8.34	26.82	63.87	68.20	4.33*
15720	29.15	PK	V	44.12	11.54	24.32	60.49	68.20	7.71
15720	18.26	AV	V	44.12	11.54	24.32	49.60	54.00	4.40*
5350	26.1	PK	H	34.23	4.58	0.00	64.91	68.20	3.29*
5350	12.02	AV	H	34.23	4.58	0.00	50.83	54.00	3.17*
2256.32	42.15	PK	V	30.24	3.77	27.61	48.54	68.20	19.66
2256.32	34.06	AV	H	30.24	3.77	27.61	40.45	54.00	13.55
400.36	38.57	QP	H	16.19	2.43	27.35	29.84	46.00	16.16
345.12	36.24	QP	H	14.98	2.22	21.63	31.80	46.00	14.20

*Within measurement uncertainty!

802.11n20 Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	FCC 15.407	
	Reading (dB μ V)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dB μ V/m)	Margin (dB)
Low Channel: 5180MHz									
5180	56.36	AV	H	33.92	5.49	0.00	95.77	N/A	N/A
5180	62.47	PK	H	33.92	5.49	0.00	101.88	N/A	N/A
5180	70.69	AV	V	33.92	5.49	0.00	110.10	N/A	N/A
5180	80.27	PK	V	33.92	5.49	0.00	119.68	N/A	N/A
10360	43.52	PK	V	39.80	8.34	26.81	64.85	68.20	3.35*
5150	25.31	PK	V	33.87	5.45	0.00	64.63	68.20	3.57*
5150	10.56	AV	V	33.87	5.45	0.00	49.88	54.00	4.12*
15540	30.24	PK	V	44.51	11.42	24.45	61.72	68.20	6.48
15540	18.17	AV	V	44.51	11.42	24.45	49.65	54.00	4.35*
1376.36	41.36	PK	H	25.38	2.87	27.45	42.15	68.20	26.05
1376.36	32.69	AV	H	25.38	2.87	27.45	33.48	54.00	20.52
400.32	40.25	QP	H	16.19	2.43	27.36	31.51	46.00	14.49
725.11	38.67	QP	H	21.01	3.27	27.42	35.53	46.00	10.47
Middle Channel: 5200MHz									
5200	56.59	AV	H	33.96	5.51	0.00	96.06	N/A	N/A
5200	65.21	PK	H	33.96	5.51	0.00	104.68	N/A	N/A
5200	68.52	AV	V	33.96	5.51	0.00	107.99	N/A	N/A
5200	76.34	PK	V	33.96	5.51	0.00	115.81	N/A	N/A
10400	43.75	PK	V	39.86	8.34	26.81	65.14	68.20	3.06 *
15600	29.16	PK	V	44.38	11.46	24.41	60.59	68.20	7.61
15600	16.29	AV	V	44.38	11.46	24.41	47.72	54.00	6.28
1347.26	38.62	PK	H	25.35	2.91	27.43	39.45	68.20	28.75
1347.26	30.15	AV	H	25.35	2.91	27.43	30.98	46.00	15.02
3338.35	41.37	PK	H	31.44	4.59	27.38	50.02	68.20	18.18
3338.35	31.26	AV	H	31.44	4.59	27.38	39.91	54.00	14.09
725.11	36.29	QP	H	21.01	3.27	27.42	33.15	46.00	12.85
500.12	35.87	QP	H	18.10	2.72	22.02	34.67	46.00	11.33
High Channel: 5240MHz									
5240	55.15	AV	H	34.03	5.09	0.00	94.28	N/A	N/A
5240	60.47	PK	H	34.03	5.09	0.00	99.60	N/A	N/A
5240	65.37	AV	V	34.03	5.09	0.00	104.50	N/A	N/A
5240	80.76	PK	V	34.03	5.09	0.00	119.89	N/A	N/A
10480	41.96	PK	V	39.97	8.34	26.82	63.45	68.20	4.75 *
15720	28.56	PK	V	44.12	11.54	24.32	59.90	68.20	8.30
15720	16.57	AV	V	44.12	11.54	24.32	47.91	54.00	6.09
5350	25.66	PK	H	34.23	4.58	0.00	64.47	68.20	3.73 *
5350	10.29	AV	H	34.23	4.58	0.00	49.10	54.00	4.90*
1626.32	40.82	PK	V	26.33	3.17	27.30	43.03	68.20	25.17
1626.32	31.62	AV	V	26.33	3.17	27.30	33.83	54.00	20.17
400.26	40.18	QP	H	16.19	2.43	27.35	31.45	46.00	14.55
525.41	37.52	QP	H	18.31	2.79	22.08	36.54	46.00	9.46

*Within measurement uncertainty!

802.11n40 Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	FCC 15.407	
	Reading (dB μ V)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dB μ V/m)	Margin (dB)
Low Channel: 5190MHz									
5190	58.15	AV	H	33.94	5.50	0.00	97.59	N/A	N/A
5190	63.47	PK	H	33.94	5.50	0.00	102.91	N/A	N/A
5190	69.45	AV	V	33.94	5.50	0.00	108.89	N/A	N/A
5190	78.15	PK	V	33.94	5.50	0.00	117.59	N/A	N/A
10380	42.56	PK	V	39.83	8.34	26.81	63.92	68.20	4.28 *
15570	32.29	PK	H	44.45	11.44	24.43	63.75	68.20	4.45*
15570	16.58	AV	V	44.45	11.44	24.43	48.04	54.00	5.96*
5150	25.21	PK	V	33.87	5.45	0.00	64.53	68.20	3.67*
5150	10.72	AV	V	33.87	5.45	0.00	50.04	54.00	3.96 *
1472.36	40.25	PK	H	25.47	2.95	27.29	41.38	68.20	26.82
1472.36	39.86	AV	V	25.47	2.95	27.29	40.99	54.00	13.01
400.03	41.53	QP	H	16.18	2.43	27.36	32.78	46.00	13.22
825.12	37.64	QP	H	22.15	3.48	27.42	35.85	46.00	10.15
High Channel: 5230MHz									
5230	54.73	AV	H	34.01	5.20	0.00	93.94	N/A	N/A
5230	61.47	PK	H	34.01	5.20	0.00	100.68	N/A	N/A
5230	66.28	AV	V	34.01	5.20	0.00	105.49	N/A	N/A
5230	79.43	PK	V	34.01	5.20	0.00	118.64	N/A	N/A
10460	40.66	PK	V	39.94	8.34	26.82	62.13	68.20	6.07
15690	31.25	PK	H	44.18	11.52	24.34	62.61	68.20	5.59 *
15690	16.59	AV	V	44.18	11.52	24.34	47.95	54.00	6.05 *
5350	25.74	PK	H	34.23	4.58	0.00	64.55	68.20	3.65 *
5350	11.05	AV	H	34.23	4.58	0.00	49.86	54.00	4.14 *
1472.36	42.36	PK	V	25.47	2.95	27.29	43.49	68.20	24.71
1472.36	40.47	AV	H	25.47	2.95	27.29	41.60	54.00	12.40
400.03	41.23	QP	H	16.18	2.43	27.35	32.49	46.00	13.51
550.31	37.52	QP	H	18.60	2.85	22.15	36.82	46.00	9.18

*Within measurement uncertainty!

Conducted Spurious Emission at Antenna Port

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The Resolution bandwidth is set to 1MHz, The Video bandwidth is set to \geq 1MHz, report the peak value out of the operating band. Offset the antenna gain and cable loss.
3. Repeat above procedures until all frequencies measured were complete.



Test data


Mode: Transmitting

Please refer to the following table and plots.


Frequency (MHz)	Worst Reading Level (dBm)	Limit (dBm)	Result
802.11a			
5180	-34.88	-27	PASS
5200	-35.98	-27	PASS
5240	-34.71	-27	PASS
802.11n20 Chain 0			
5180	-39.23	-27	PASS
5200	-39.01	-27	PASS
5240	-40.34	-27	PASS
802.11n20 Chain 1			
5180	-39.62	-27	PASS
5200	-39.30	-27	PASS
5240	-40.15	-27	PASS
802.11n20 Total:Chain 0+Chain 1			
5180	-36.41	-27	PASS
5200	-36.14	-27	PASS
5240	-37.23	-27	PASS
802.11n40 Chain 0			
5190	-40.68	-27	PASS
5230	-39.18	-27	PASS
802.11n40 Chain 1			
5190	-39.95	-27	PASS
5230	-38.83	-27	PASS
802.11n40 Total:Chain 0+Chain 1			
5190	-36.72	-27	PASS
5230	-35.99	-27	PASS

Note: the antenna gain is 5dBi, cable loss 0.5dB.

Please refer to the following plots.


802.11a Low Channel 30M-1G

Date: 03.JUN.2013 21:36:29

802.11a Low Channel 1G-26.5G


Date: 03.JUN.2013 21:36:57

802.11a Low Channel 26.5-40G







Date: 3.JUN.2013 15:31:07

802.11a Middle Channel 30M-1G




Date: 03.JUN.2013 21:37:45

802.11a Middle Channel 1G -26.5G**802.11a Middle Channel 26.5-40G**


802.11a High Channel 30M-1G**802.11a High Channel 1G-26.5G**

802.11a High Channel 26.5-40G







Date: 3.JUN.2013 15:52:51


Chain 0: 802.11n20 Low Channel 30M-1G




Date: 03.JUN.2013 21:41:57

Chain 0: 802.11n20 Low Channel 1G-26.5G**Chain 0: 802.11n20 Low Channel 26.5-40G**



Chain 0: 802.11n20 Middle Channel 30M-1G**Chain 0: 802.11n20 Middle Channel 1G -26.5G**



Chain 0: 802.11n20 Middle Channel 26.5-40G


Date: 3.JUN.2013 16:01:47

Chain 0: 802.11n20 High Channel 30M-1G


Date: 03.JUN.2013 21:44:32

Chain 0: 802.11n20 High Channel 1G-26.5G**Chain 0: 802.11n20 High Channel 26.5-40G**



Chain 1: 802.11n20 Low Channel 30M-1G**Chain 1: 802.11n20 Low Channel 1G-26.5G**



Chain 1: 802.11n20 Low Channel 26.5-40G

Date: 3.JUN.2013 16:38:12


Chain 1: 802.11n20 Middle Channel 30M-1G

Date: 03.JUN.2013 21:42:52

Chain 1: 802.11n20 Middle Channel 1G -26.5G**Chain 1: 802.11n20 Middle Channel 26.5-40G**


Chain 1: 802.11n20 High Channel 30M-1G**Chain 1: 802.11n20 High Channel 1G-26.5G**

Chain 1: 802.11n20 High Channel 26.5-40G







Date: 3.JUN.2013 16:21:07


Chain 0: 802.11n40 Low Channel 30M-1G



Date: 03.JUN.2013 21:46:12


Chain 0: 802.11n40 Low Channel 1G-26.5G**Chain 0: 802.11n40 Low Channel 26.5-40G**

Chain 0: 802.11n40 High Channel 30M-1G**Chain 0: 802.11n40 High Channel 1G-26.5G****Chain 0: 802.11n40 High Channel 26.5-40G**







Date: 3.JUN.2013 17:20:09

Chain 1: 802.11n40 Low Channel 30M-1G




Date: 03.JUN.2013 21:46:20

Chain 1: 802.11n40 Low Channel 1G-26.5G**Chain 1: 802.11n40 Low Channel 26.5-40G**

Chain 1: 802.11n40 High Channel 30M-1G**Chain 1: 802.11n40 High Channel 1G-26.5G**

Chain 1: 802.11n40 High Channel 26.5-40G



Date: 3.JUN.2013 16:37:28

FCC §15.407(b) (1) (2) (3) (4) – OUT OF BAND EMISSIONS

Applicable Standard

FCC §15.407 (b) (1),(2), (3), (4),;

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz.

For transmitters operating in the 5.25–5.35 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz. Devices operating in the 5.25–5.35 GHz band that generate emissions in the 5.15–5.25 GHz band must meet all applicable technical requirements for operation in the 5.15–5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of –27 dBm/MHz in the 5.15–5.25 GHz band.

For transmitters operating in the 5.47–5.725 GHz band: all emissions outside of the 5.47–5.725 GHz band shall not exceed an EIRP of –27 dBm/MHz.

For transmitters operating in the 5.725–5.825 GHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of –17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of –27 dBm/MHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibration or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 1 MHz and VBW to 3MHz of spectrum analyzer. Offset the antenna gain and cable loss.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	ESPI	100337	2012-11-10	2013-11-9

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.7 °C
Relative Humidity:	65 %
ATM Pressure:	99.8 kPa


The testing was performed by Ares Liu on 2013-06-03.

Please refer to the following table and plots.

Bandedge	Worst Reading Level (dBm)	Limit (dBm)	Result
802.11a			
Left	-36.90	-27	PASS
Right	-43.64	-27	PASS
802.11n20 Chain 0			
Left	-39.83	-27	PASS
Right	-43.37	-27	PASS
802.11n20 Chain 1			
Left	-40.76	-27	PASS
Right	-44.58	-27	PASS
802.11n20 Total:Chain 0+Chain 1			
Left	-36.97	-27	PASS
Right	-40.89	-27	PASS
802.11n40 Chain 0			
Left	-37.59	-27	PASS
Right	-43.88	-27	PASS
802.11n40 Chain 1			
Left	-38.78	-27	PASS
Right	-45.01	-27	PASS
802.11n40 Total:Chain 0+Chain 1			
Left	-35.13	-27	PASS
Right	-41.40	-27	PASS


Note: the antenna gain is 5 dBi, the cable loss is 0.5 dB.

802.11a Left Bandedge




Date: 3.JUN.2013 15:36:07


802.11a Right Bandedge



Date: 3.JUN.2013 15:59:51


Chain 0:802.11n20 Left Bandedge

Date: 3.JUN.2013 16:14:20

Chain 0:802.11n20 Right Bandedge


Date: 3.JUN.2013 16:36:01

Chain 1:802.11n20 Left Bandedge




Date: 3.JUN.2013 16:14:46

Chain 1:802.11n20 Right Bandedge




Date: 3.JUN.2013 16:36:21

Chain 0:802.11n40 Left Bandedge




Date: 3.JUN.2013 16:53:44

Chain 0:802.11n40 Right Bandedge




Date: 3.JUN.2013 16:56:52

Chain 1:802.11n40 Left Bandedge



Date: 3.JUN.2013 16:54:19

Chain 1:802.11n40 Right Bandedge



Date: 3.JUN.2013 16:57:28

FCC §15.407(a) (1) – 26 dB OCCUPIED BANDWIDTH

Applicable Standard

For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or $4 \text{ dBm} + 10 \log B$, where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	ESPI	100337	2012-11-10	2013-11-9

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

6. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
7. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
8. Use a RBW = approximately 1% of the emission bandwidth. Set the VBW > RBW. Use a peak detector. Do not use the Max Hold function. Rather, use the view button to capture the emission. Measure maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
9. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	26.8 °C
Relative Humidity:	69 %
ATM Pressure:	100.3kPa


The testing was performed by Ares Liu on 2013-06-03.

Test Result: Pass.


Please refer to the following tables and plots.

Test mode: Transmitting

Channel	Frequency	26 dB Bandwidth
	(MHz)	(MHz)
802.11a mode		
Low	5180	19.68
Middle	5200	19.68
High	5240	19.68
chain 0:802.11n20 mode		
Low	5180	19.84
Middle	5200	19.84
High	5240	19.84
chain 1:802.11n20 mode		
Low	5180	19.84
Middle	5200	19.84
High	5240	19.84
chain 0:802.11n40 mode		
Low	5190	39.68
High	5230	39.84
Chain1:802.11n40 mode		
Low	5190	39.68
High	5230	39.84


802.11a Low Channel

Date: 3.JUN.2013 15:19:14

802.11a Middle Channel


Date: 3.JUN.2013 15:44:21

802.11a High Channel




Date: 3.JUN.2013 15:53:19


Chain 0:802.11n20 Low Channel



Date: 3.JUN.2013 16:04:42


Chain 0:802.11n20 Middle Channel

Date: 3.JUN.2013 16:20:23

Chain 0:802.11n20 High Channel


Date: 3.JUN.2013 16:26:49

Chain 1:802.11n20 Low Channel




Date: 3.JUN.2013 16:07:26

Chain 1:802.11n20 Middle Channel




Date: 3.JUN.2013 16:21:03

Chain 1:802.11n20 High Channel




Date: 3.JUN.2013 16:27:33

Chain 0:802.11n40 Low Channel




Date: 3.JUN.2013 16:42:28

Chain 0:802.11n40 High Channel




Date: 3.JUN.2013 17:00:09

Chain 1:802.11n40 Low Channel



Date: 3.JUN.2013 16:43:54

Chain 1:802.11n40 High Channel



Date: 3.JUN.2013 17:01:14

FCC §15.407(a) (1) – CONDUCTED TRANSMITTER OUTPUT POWER**Applicable Standard**

For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or $4 \text{ dBm} + 10 \log B$, where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	ESPI	100337	2012-11-10	2013-11-9

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set span to encompass the entire emission bandwidth (EBW) of the signal. Set RBW = 1 MHz. Set $\text{VBW} \geq 3 \text{ MHz}$. Use sample detector mode. Use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at full control power for entire sweep of every sweep. If the device transmits continuously, with no off intervals or reduced power intervals, the trigger may be set to “free run”. Trace average 100 traces in power averaging mode. Compute power by integrating the spectrum across the 26 dB EBW of the signal. The integration can be performed using the spectrum analyzer’s band power measurement function with band limits set equal to the EBW band edges or by summing power levels in each 1 MHz band in linear power terms. The 1 MHz band power levels to be summed can be obtained by averaging, in linear power terms, power levels in each frequency bin across the 1 MHz.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	29.7 °C
Relative Humidity:	65 %
ATM Pressure:	99.8 kPa


The testing was performed by Ares Liu on 2013-06-03.

Test Mode: Transmitting


Channel	Frequency	Conducted Output Power	Limit	Result
	(MHz)	(dBm)	(dBm)	
802.11a mode				
Low	5180	12.13	17	PASS
Middle	5200	12.15	17	PASS
High	5240	12.20	17	PASS
chain 0:802.11n20 mode				
Low	5180	9.03	17	PASS
Middle	5200	9.28	17	PASS
High	5240	9.18	17	PASS
chain 1:802.11n20 mode				
Low	5180	9.04	17	PASS
Middle	5200	9.19	17	PASS
High	5240	9.21	17	PASS
chain 0:802.11n40 mode				
Low	5190	8.77	17	PASS
High	5230	8.47	17	PASS
chain 1:802.11n40 mode				
Low	5190	8.55	17	PASS
High	5230	8.47	17	PASS

Total power of 802.11n: chain 0+ chain 1


Channel	Frequency	Conducted Output Power	Limit	Result
	(MHz)	(dBm)	(dBm)	
Total:802.11n20 mode				
Low	5180	12.05	17	PASS
Middle	5200	12.25	17	PASS
High	5240	12.21	17	PASS
Total:802.11n40 mode				
Low	5190	11.67	17	PASS
High	5230	11.78	17	PASS

802.11a RF Output Power, Low Channel


Date: 3.JUN.2013 15:21:13

802.11a RF Output Power, Middle Channel


Date: 3.JUN.2013 15:44:57

802.11a RF Output Power, High Channel


Date: 3.JUN.2013 15:53:53

Chain 0:802.11n20 RF Output Power, Low Channel


Date: 3.JUN.2013 16:05:29

Chain 0:802.11n20 RF Output Power, Middle Channel


Date: 3.JUN.2013 16:18:34

Chain 0:802.11n20 RF Output Power, High Channel


Date: 3.JUN.2013 16:27:51

Chain 1:802.11n20 RF Output Power, Low Channel


Date: 3.JUN.2013 16:06:06

Chain 1:802.11n20 RF Output Power, Middle Channel


Date: 3.JUN.2013 16:18:46

Chain 1:802.11n20 RF Output Power, High Channel


Date: 3.JUN.2013 16:28:09

Chain 0:802.11n40 RF Output Power, Low Channel


Date: 3.JUN.2013 16:44:22

Chain 0:802.11n40 RF Output Power, High Channel

Date: 3.JUN.2013 17:01:54

Chain 1:802.11n40 RF Output Power, Low Channel

Date: 3.JUN.2013 16:44:43

Chain 1:802.11n40 RF Output Power, High Channel

Date: 3.JUN.2013 17:02:16

FCC §15.407(a) (1) (5) - POWER SPECTRAL DENSITY

Applicable Standard

For the band 5.15–5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed the lesser of 50 mW or $4 \text{ dBm} + 10 \log B$, where B is the 26-dB emission bandwidth in MHz. In addition, the peak power spectral density shall not exceed 4 dBm in any 1-MHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The peak power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A resolution bandwidth less than the measurement bandwidth can be used, provided that the measured power is integrated to show total power over the measurement bandwidth. If the resolution bandwidth is approximately equal to the measurement bandwidth, and much less than the emission bandwidth of the equipment under test, the measured results shall be corrected to account for any difference between the resolution bandwidth of the test instrument and its actual noise bandwidth.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Use sample detector and power averaging (not video averaging) mode. Set RBW= 1 MHz, VBW > 1 MHz. The PPSD is the highest level found across the emission in any 1-MHz band after 100 sweeps of averaging. This method is permitted only if the transmission pulse or sequence of pulses remains at maximum transmits power throughout each of the 100 sweeps of averaging and that the interval between pulses is not included in any of the sweeps.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	ESPI	100337	2012-11-10	2013-11-9

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.7 °C
Relative Humidity:	65 %
ATM Pressure:	99.8 kPa

The testing was performed by Ares Liu on 2013-06-03.

Test Mode: Transmitting


Test Result: Pass

Test mode: Transmitting


Channel	Power Spectral Density	Limit	Result
	(dBm/MHz)	(dBm/MHz)	
802.11a mode			
Low	3.01	4	PASS
Middle	3.58	4	PASS
High	3.67	4	PASS
Chain 0:802.11n20 mode			
Low	-0.20	4	PASS
Middle	0.34	4	PASS
High	1.07	4	PASS
Chain 1:802.11n20 mode			
Low	-0.37	4	PASS
Middle	0.19	4	PASS
High	0.83	4	PASS
Chain 0:802.11n40 mode			
Low	-1.97	4	PASS
High	-2.68	4	PASS
Chain 1:802.11n40 mode			
Low	-2.38	4	PASS
High	-2.61	4	PASS

Total power of 802.11n: chain 0+ chain 1


Channel	Power Spectral Density	Limit	Result
	(dBm/MHz)	(dBm/MHz)	
Total:802.11n20 mode			
Low	2.73	4	PASS
Middle	3.28	4	PASS
High	3.96	4	PASS
Total:802.11n40 mode			
Low	3.45	4	PASS
High	3.20	4	PASS

Power Spectral Density, 802.11a Low Channel


Date: 3.JUN.2013 15:21:50

Power Spectral Density, 802.11a Middle Channel


Date: 3.JUN.2013 15:45:47

Power Spectral Density, 802.11a High Channel


Date: 3.JUN.2013 15:54:58

Chain 0:Power Spectral Density, 802.11n20 Low Channel


Date: 3.JUN.2013 16:08:47

Chain 0:Power Spectral Density, 802.11n20 Middle Channel


Date: 3.JUN.2013 16:21:47

Chain 0:Power Spectral Density, 802.11n20 High Channel


Date: 3.JUN.2013 16:28:50

Chain 1:Power Spectral Density, 802.11 n20 Low Channel


Date: 3.JUN.2013 16:09:01

Chain 1:Power Spectral Density, 802.11n20 Middle Channel


Date: 3.JUN.2013 16:22:02

Chain 1:Power Spectral Density, 802.11n20 High Channel


Date: 3.JUN.2013 16:29:46

Chain 0:Power Spectral Density, 802.11n40 Low Channel


Date: 3.JUN.2013 16:45:35

Chain 0:Power Spectral Density, 802.11n40 High Channel

Date: 3.JUN.2013 17:02:51

Chain 1:Power Spectral Density, 802.11n40 Low Channel

Date: 3.JUN.2013 16:46:18

Chain 1:Power Spectral Density, 802.11n40 High Channel

Date: 3.JUN.2013 17:03:01

FCC §15.407(a) (6) – PEAK EXCURSION RATIO

Applicable Standard

According to §15.407(a) (6), the ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum conducted output power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emission bandwidth whichever is less.

Test Procedure

Set the spectrum analyzer span to view the entire emission bandwidth.


The largest difference between the following two traces must be ≤ 13 dB for all frequencies across the emission bandwidth. Submit a plot.

1st Trace:

- Set RBW = 1 MHz, VBW \geq 3 MHz with peak detector and maxhold settings.

2nd Trace:

- create the 2nd trace using the settings described in the setion “FCC §15.407(a)(1)(2) – CONDUCTED TRANSMITTER OUTPUT POWER”.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	ESPI	100337	2012-11-10	2013-11-9

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	29.7°C
Relative Humidity:	65 %
ATM Pressure:	99.8 kPa


The testing was performed by Ares Liu on 2013-06-03.

Test Mode: Transmitting

Channel	Peak Excursion	Limit	Result
	Ratio (dB)		
802.11a mode			
Low	1.27	13	PASS
Middle	1.21	13	PASS
High	1.54	13	PASS
Chain 0:802.11n20 mode			
Low	1.42	13	PASS
Middle	1.82	13	PASS
High	1.26	13	PASS
Chain 1:802.11n20 mode			
Low	1.16	13	PASS
Middle	2.16	13	PASS
High	1.64	13	PASS
Chain 0:802.11n40 mode			
Low	0.24	13	PASS
High	1.65	13	PASS
Chain 1:802.11n40 mode			
Low	0.45	13	PASS
High	1.39	13	PASS


802.11a Peak Excursion, Low Channel

Date: 3.JUN.2013 15:33:53

802.11a Peak Excursion, Middle Channel


Date: 3.JUN.2013 15:47:48

802.11a Peak Excursion, High Channel




Date: 3.JUN.2013 15:57:43


Chain 0:802.11 n20 Peak Excursion, Low Channel



Date: 3.JUN.2013 16:10:38


Chain 0:802.11 n20 Peak Excursion, Middle Channel

Date: 3.JUN.2013 16:22:36

Chain 0:802.11 n20 Peak Excursion, High Channel


Date: 3.JUN.2013 16:32:59

Chain 1:802.11 n20 Peak Excursion, Low Channel




Date: 3.JUN.2013 16:12:30

Chain 1:802.11 n20 Peak Excursion, Middle Channel




Date: 3.JUN.2013 16:23:22

Chain 1:802.11 n20 Peak Excursion, High Channel




Date: 3.JUN.2013 16:34:23


Chain 0:802.11 n40 Peak Excursion, Low Channel




Date: 3.JUN.2013 16:48:25

Chain 0:802.11 n40 Peak Excursion, High Channel

Date: 3.JUN.2013 17:03:55

Chain 1:802.11 n40 Peak Excursion, Low Channel

Date: 3.JUN.2013 16:50:13

Chain 1:802.11 n40 Peak Excursion, High Channel

Date: 3.JUN.2013 17:05:14

******* END OF REPORT *******