# FCC Part 22H and 24E Test Report

For

#### MOBILE PHONE

**Model Name: X200** 

**Brand Name: BESTPOWER** 

FCC ID: X56-X200

Report No.: AGC10141201SZ03-1E4A

Date of Issue: Feb. 03, 2010

Prepared For

Smart Communication Device Corporation Limited 10F, Building A, Guo Qi Plaza, Shang Bu Road, Fu Tian District, Shenzhen, Guangdong, China

TEL: 0086-755-2588 0420

FAX: 0086-755-2588 0410

Prepared By

Attestation of Global Compliance Co., Ltd.

2F., No.2 Building, Huafeng No.1 Technical Industrial Park, Sanwei,
Xixiang, Baoan District, Shenzhen, China

TEL: 0086-755-2908 1966

FAX: 0086-755-2600 8484

Report No.: AGC10141201SZ03-1E4A Page 1 of 61

#### **VERIFICATION OF COMPLIANCE**

	Smart Communication Device Corporation Limited
Applicant:	10F, Building A, Guo Qi Plaza, Shang Bu Road,
	Futian District, Shenzhen, Guangdong, China
	Smart Communication Device Corporation Limited
Manufacturer:	10F, Building A, Guo Qi Plaza, Shang Bu Road,
	Futian District, Shenzhen, Guangdong, China
Product Description:	MOBILE PHONE
Brand Name:	BESTPOWER
Model Number:	X200
FCC ID:	X56-X200
Date of Test:	Dec. 20, 2009 to Dec.31, 2009

# We hereby certify that:

The above equipment was tested by Attestation of Global Compliance Co., Ltd. The data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C 63.4:2009 and TIA/EIA 603. The sample tested as described in this report is in compliance with the FCC Rules Part 22H and 24E

The test results of this report relate only to the tested sample identified in this report.

Tony Tian Feb.03, 2010 Checked By:

Authorized By King Zhang Feb.03, 2010

# **TABLE OF CONTENTS**

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION	4
1.2RELATED SUBMITTAL(S) / GRANT (S)	4
1.3 TEST METHODOLOGY	4
1.4 TEST FACILITY	4
1.5 MEASUREMENT INSTRUMENTS	5
1.6 SPECIAL ACCESSORIES	5
1.7 EQUIPMENT MODIFICATIONS	5
2. SYSTEM TEST CONFIGURATION	6
2.1 EUT CONFIGURATION	6
2.2 EUT EXERCISE	6
2.3 GENERAL TECHNICAL REQUIREMENTS	6
2.4 CONFIGURATION OF EUT SYSTEM	6
3. SUMMARY OF TEST RESULTS	7
4. DESCRIPTION OF TEST MODES	7
5. OUTPUT POWER	8
5.1 CONDUCTED OUTPUT POWER	8
5.2 RADIATED OUTPUT POWER	9
6. SPURIOUS EMISSION	11
6.1 CONDUCTED SPURIOUS EMISSION	11
6.2 RADIATED SPURIOUS EMISSION	13
7. CONDUCTED EMISSION	17
7.1 MEASUREMENT METHOD	17
7.2 PROVISIONS APPLICABLE	17
7.3 MEASUREMENT RESULT	17
8. FREQUENCY STABILITY	19

8.1 MEASUREMENT METHOD	19
8.2 PROVISIONS APPLICABLE	19
8.3 MEASUREMENT RESULT	20
9. OCCUPIED BANDWIDTH	21
9.1 MEASUREMENT METHOD	21
9.2 PROVISIONS APPLICABLE	21
9.3 MEASUREMENT RESULT	21
10. EMISSION BANDWIDTH	22
10.1 MEASUREMENT METHOD	22
10.2 PROVISIONS APPLICABLE	22
10.3 MEASUREMENT RESULT	22
11. BAND EDGE	23
11.1 MEASUREMENT METHOD	23
11.2 PROVISIONS APPLICABLE	23
11.3 MEASUREMENT RESULT	23
APPENDIX I_TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION	24
APPENDIX II_TEST PLOTS FOR RADIATED SPURIOUS EMISSION	33
APPENDIX III_TEST PLOTS FOR OCCUPIED BANDWIDTH (99%)	42
APPENDIX IV_TEST PLOTS FOR BAND EDGES	49
APPENDIX V_PHOTOGRAPHS OF TEST SETUP	54
APPENDIX VI_PHOTOGRAPHS OF EUT	56

Report No.: AGC10141201SZ03-1E4A Page 4 of 61

#### 1. GENERAL INFORMATION

#### 1.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

Product Name:	MOBILE PHONE
Model:	X200
Brand:	BESTPOWER
FCC Identifier:	X56-X200
Frequency:	GSM 850 MHz; PCS 1900 MHz
Antenna:	Internal
Power Supply:	Battery
Output Power:	26.88 dBm Maximum ERP measured for GSM 850 1.72 W Maximum Conducted Power for GSM 850 24.61 dBm Maximum EIRP measured for GSM 1900 1.16 W Maximum Conducted Power for GSM 1900
Extreme Vol. Limits:	3.5 VDC to 4.2 VDC (Nominal 3.7 VDC)
Extreme Temp. Tolerance	-30°C to +50°C

#### 1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: X56-X200 filing to comply with the FCC Part 22H and 24E requirements.

#### 1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of ANSI C 63.4: 2009; TIA/EIA 603 and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

#### 1.4 TEST FACILITY

The test site used to collect the radiated data is located on the address of World Standardization Certification & Testing Co., Ltd. 1-2/F, Dachong Keji Building, No.28 of Tonggu Road, Nanshan District, Shenzhen, China. The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2009.

FCC register No.: 276008 and IC register No.: 7700A-1.

Report No.: AGC10141201SZ03-1E4A Page 5 of 61

#### 1.5 MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	CAL. DATE
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	2009.06
TEST RECEIVER	R&S	ESCI	A0304218	2009.06
COMMUNICATION TESTER	AGILENT	8960	3104A03367	2009.06
COMMUNICATION TESTER	R&S	CMU200	A0304247	2009.06
TEST RECEIVER	R&S	FCKL1528	A0304230	2009.06
LISN	SCHWARZBECK	NSLK8127	A0304233	2009.06
Climate Chamber	Albatross			2009.12
LOOP ANTENNA	R&S	HFH2-Z2	A0304220	2009.06
BROADBAND ANT.	R&S	HL562	A0304224	2009.06
HORN ANT.	R&S	HF906	100150	2009.06

#### **1.6 SPECIAL ACCESSORIES**

The battery and travel charger supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

#### 1.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

Report No.: AGC10141201SZ03-1E4A Page 6 of 61

#### 2. SYSTEM TEST CONFIGURATION

#### 2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

#### 2.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

#### 2.3 GENERAL TECHNICAL REQUIREMENTS

Item Number	Item Description			FCC Rules
1	Output Dower	Conducted		22.042(a) / 24.222 (b)
ı	Output Power	Radiated		22.913(a) / 24.232 (b)
		Conducted	Spurious	
2	Spurious	s Emission		2.1051 / 22.917 / 24.238
2	Emission	Radiated	Spurious	2.1051 / 22.917 / 24.236
		Emission		
3	Mains Conducted E	Emission		15.107 / 15.207
4	Frequency Stability			2.1055 /24.235
5	Occupied Bandwidth			2.1049 (h)(i)
6	Emission Bandwidth			22.917(b) / 24.238 (b)
7	Band Edge			22.917(b) / 24.238 (b)

#### 2.4 CONFIGURATION OF EUT SYSTEM

Fig. 2-1 Configuration of EUT System

EUT

Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	MOBILE PHONE	X200	FCC ID: WA6I305	EUT
2	CHARGER	X200	5V / 500mA	A.E.
3	BATTERY	X200	1200 mAH	A.E.

Report No.: AGC10141201SZ03-1E4A Page 7 of 61

# 3. SUMMARY OF TEST RESULTS

Item Number	Item Description			FCC Rules	Result	
		Conducted	Output	22.913(a) / 24.232		
1	Output Power	Power		(b)	Pass	
		Radiated Out	put Power	(6)		
		Conducted	Spurious			
2	Spurious	Emission		2.1051 / 22.917 /	Door	
2	Emission	Radiated	Spurious	24.238	Pass	
		Emission				
3	Mains Conducted	d Emission		15.107 / 15.207	Pass	
4	Frequency Stabil	ity		2.1055 /24.235	Pass	
5	Occupied Bandw	idth		2.1049 (h)(i)	Pass	
6	C Fraincian Bandwid			22.917(b) / 24.238	Door	
0	EIIIISSIOII Dailuwi	Emission Bandwidth			Pass	
7	Pand Edga			22.917(b) / 24.238	Page	
/	Band Edge			(b)	Pass	

#### 4. DESCRIPTION OF TEST MODES

During the testing, the EUT (GSM Dual Band GPRS Digital Mobile Phone) was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GSM and PCS frequency band.

Report No.: AGC10141201SZ03-1E4A Page 8 of 61

# **5. OUTPUT POWER**

# **5.1 Conducted Output Power**

#### **5.1.1 MEASUREMENT METHOD**

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes(GSM, GPRS, EGPRS) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band.

#### **5.1.2 PROVISIONS APPLICABLE**

Conducted Output Power Limits for GSM 850 MHZ					
Mode	Power Step	Nominal Peak Power	Tolerance(dB)		
GSM	5	33 dBm (2W)	+/- 2		
GPRS	3	33 dBm (2W)	+/- 2		

Conducted Output Power Limits for PCS 1900 MHZ					
Mode Power Step Nominal Peak Power Tolerance(dB)					
GSM	0	30 dBm (1W)	+/- 2		
GPRS	3	30 dBm (1W)	+/- 2		

#### **5.1.3 MEASUREMENT RESULT**

Conducted Output Power for GSM 850 MHZ					
	Result				
Mode	Frequency	Power Step	Peak Power	Tolerance	Conclusion
			(dBM)	(dB)	
	824.2	5	31.64	-1.36	Pass
GSM	836.6	5	32.36	-0.64	Pass
	848.8	5	32.27	-0.73	Pass
	824.2	3	31.75	-1.25	Pass
GPRS	836.6	3	32.36	-0.64	Pass
	848.8	3	32.36	-0.64	Pass

Conducted Output Power for PCS 1900 MHZ					
	Result				
Mode	Frequency	Power Step	Peak Power	Tolerance	Conclusion
			(dBM)	(dB)	
	1850.2	0	30.66	0.66	Pass
GSM	1880.0	0	30.24	0.24	Pass
	1909.8	0	30.04	0.04	Pass
	1850.2	3	30.65	0.65	Pass
GPRS	1880.0	3	30.16	0.16	Pass
	1909.8	3	30.05	0.05	Pass

Report No.: AGC10141201SZ03-1E4A Page 9 of 61

#### **5.2 Radiated Output Power**

#### **5.2.1 MEASUREMENT METHOD**

The measurements procedures specified in TIA-603C-2004 were applied.

- In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (Pin) is applied to the input of the dipole, and the power received (Pr) at the chamber's probe antenna is recorded.
- 2 The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as ARpl=Pin + 2.15 Pr. The ARpl is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: Power=PMea+ARpl
- 3 The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4 From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5 The EUT is then put into continuously transmitting mode at its maximum power level.
- Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
- 7 This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (Pin).
- 8 ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi..

#### **5.2.2 PROVISIONS APPLICABLE**

This is the test for the maximum radiated power from the EUT. Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Radiated Power Limits for GSM 850 MHZ (ERP)							
Mode	Mode Power Step Nominal Peak Power						
GSM	5	<=38.45 dBm (7W)					
GPRS	3	<=38.45 dBm (7W)					

Radiated Power Limits for PCS 1900 MHZ (E.I.R.P.)					
Mode Power Step Nominal Peak Power					
GSM	0	<=33 dBm (2W)			
GPRS	3	<=33 dBm (2W)			

Report No.: AGC10141201SZ03-1E4A Page 10 of 61

#### **5.2.3 MEASUREMENT RESULT**

Radiated Power (ERP) for GSM 850 MHZ						
			Res			
Mode	Frequency	Power Step	Max. Peak ERP	Polarization	Conclusion	
			(dBm)	Of Max. ERP		
	824.2	5	26.31	Horizontal	Pass	
GSM	836.6	5	26.63	Horizontal	Pass	
	848.8	5	26.88	Horizontal	Pass	
	824.2	3	25.53	Horizontal	Pass	
GPRS	836.6	3	25.62	Horizontal	Pass	
	848.8	3	25.89	Horizontal	Pass	

	Radiated Power (E.I.R.P) for PCS 1900 MHZ							
Result								
Mode	Frequency	Power Step	Max. Peak	Polarization	Conclusion			
			E.I.R.P.(dBm)	Of Max. E.I.R.P.				
	1850.2	0	24.61	Horizontal	Pass			
GSM	1880.0	0	24.39	Horizontal	Pass			
	1909.8	0	24.26	Horizontal	Pass			
	1850.2	3	24.31	Horizontal	Pass			
GPRS	1880.0	3	24.38	Horizontal	Pass			
	1909.8	3	24.29	Horizontal	Pass			

Report No.: AGC10141201SZ03-1E4A Page 11 of 61

#### 6. SPURIOUS EMISSION

#### **6.1 CONDUCTED SPURIOUS EMISSION**

#### **6.1.1 MEASUREMENT METHOD**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.
- 2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

Typical Channels for testing of GSM 850 MHz					
Channel	Frequency (MHz)				
128	824.2				
190	836.6				
251	848.8				

Typical Channels for testing of PCS 1900 MHz					
Channel	Frequency (MHz)				
512	1850.2				
661	1880.0				
810	1909.8				

#### **6.1.2 PROVISIONS APPLICABLE**

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

Report No.: AGC10141201SZ03-1E4A Page 12 of 61

#### **6.1.3 MEASUREMENT RESULT**

Conducted Spurious Emission for GSM 850 MHz									
Harmonic	Tx ch. 128 Freq. (MHz)	Level (dBm)	Tx ch. 190 Freq. (MHz)	Level (dBm)	Tx ch. Freq. (MHz) 251	Level (dBm)			
2	1648.4	B.I.N.F	1673.2	nf	1697.6	B.I.N.F			
3	2472.6	B.I.N.F	2509.8	nf	2546.4	B.I.N.F			
4	3296.8	B.I.N.F	3346.4	nf	3395.2	B.I.N.F			
5	4121	B.I.N.F	4183	nf	4244	B.I.N.F			
6	4945.2	B.I.N.F	5019.6	nf	5092.8	B.I.N.F			
7	5769.4	B.I.N.F	5856.2	nf	5941.6	B.I.N.F			
8	6593.6	B.I.N.F	6692.8	nf	6790.4	B.I.N.F			
9	7417.8	B.I.N.F	7529.4	nf	7639.2	B.I.N.F			
10	8242	B.I.N.F	8366	nf	8488	B.I.N.F			
B.I.N.F	B.I.N.F: Below Instruments Noise floor								

Conducted Spurious Emission for PCS 1900 MHz								
Harmonic	Tx ch. 512 Freq. (MHz)	Level (dBm)	Tx ch. 661 Freq. (MHz)	Level (dBm)	Tx ch. 810 Freq. (MHz)	Level (dBm)		
2	3700.4	B.I.N.F	3760	nf	3819.6	B.I.N.F		
3	5550.6	B.I.N.F	5640	nf	5729.4	B.I.N.F		
4	7400.8	B.I.N.F	7520	nf	7639.2	B.I.N.F		
5	9251.0	B.I.N.F	9400	nf	9549.0	B.I.N.F		
6	11101.2	B.I.N.F	11280	nf	11458.8	B.I.N.F		
7	12951.4	B.I.N.F	13160	nf	13368.6	B.I.N.F		
8	14801.6	B.I.N.F	15040	nf	15278.4	B.I.N.F		
9	16651.8	B.I.N.F	16920	nf	17188.2	B.I.N.F		
10	18502.0	B.I.N.F	18800	nf	19098.0	B.I.N.F		
• BINE	: Below Instrume	nts Noise	floor					

# B.I.N.F: Below Instruments Noise floor

Report No.: AGC10141201SZ03-1E4A Page 13 of 61


#### 6.2 Radiated Spurious Emission

#### **6.2.1 MEASUREMENT METHOD**


The measurements procedures specified in TIA-603C-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GSM, GPRS, EGPRS) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for both GSM band and PCS band.

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, RSE=Rx(dBuV)+CL(dB)+SA(dB)+Gain(dBi)-107(dBuV to dBm) The SA is calibrated using following setup.



b) EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz), GSM850 band (824.2MHz, 836.6MHz,

Report No.: AGC10141201SZ03-1E4A Page 14 of 61

848.8MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 ,GSM850 into any

of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A<sub>Rpl</sub> is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: Power=P<sub>Mea</sub>+A<sub>Rpl</sub>

#### **6.2.2 PROVISIONS APPLICABLE**

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least 43+10Log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Report No.: AGC10141201SZ03-1E4A Page 15 of 61

#### **6.2.3 MEASUREMENT RESULT**

The Worst Test Results for Channel 128 / 824.2 MHz							
Frequency(GHz)	Power(dBm)	A <sub>Rpl</sub> (dBm)	Р <sub>меа</sub> (dВm)	Limit (dBm)	Polarity		
1155.50	-55.00	-1.55	-53.45	-13.00	Horizontal		
1648.00	-42.80	-2.95	-39.85	-13.00	Horizontal		
1752.00	-49.80	-0.35	-49.45	-13.00	Vertical		
9996.00	-39.00	10.45	-49.45	-13.00	Horizontal		

The Worst Test Results for Channel 190/836.6 MHz							
Frequency(GHz)	Power(dBm)	A <sub>Rpl</sub> (dBm)	P <sub>Mea</sub> (dBm)	Limit (dBm)	Polarity		
1673.00	-42.80	-2.08	-40.72	-13.00	Horizontal		
1752.00	-50.20	-0.35	-49.85	-13.00	Vertical		
9998.00	-39.60	10.55	-50.15	-13.00	Vertical		

The Worst Test Results for Channel 251/848.8 MHz							
Frequency(GHz)	Power(dBm)	A <sub>Rpl</sub> (dBm)	Р <sub>меа</sub> (dВm)	Limit (dBm)	Polarity		
1698.00	-43.70	-2.25	-41.45	-13.00	Horizontal		
1787.50	-50.40	-0.25	-50.15	-13.00	Vertical		
3142.50	-50.60	0.85	-51.45	-13.00	Vertical		
9999.20	-39.00	10.45	-49.45	-13.00	Horizontal		

The Worst Test Results for Channel 512/1850.2 MHz								
Frequency(GHz)	Power(dBm)	A <sub>Rpl</sub> (dBm)	Рмеа(dBm)	Limit (dBm)	Polarity			
2001.00	-46.20	9.60	-55.80	-13.00	Horizontal			
9252.00	-38.50	10.50	-49.00	-13.00	Horizontal			
12950.40	-39.70	12.30	-52.00	-13.00	Vertical			
14800.80	-37.50	15.40	-52.90	-13.00	Horizontal			
17919.60	-37.00	18.70	-55.70	-13.00	Vertical			

The Worst Test Results for Channel 661/1880.0 MHz					
Frequency(GHz)	Power(dBm)	A <sub>Rpl</sub> (dBm)	P <sub>Mea</sub> (dBm)	Limit (dBm)	Polarity
2000.50	-45.70	9.80	-55.50	-13.00	Vertical
9399.00	-38.70	11.80	-50.50	-13.00	Vertical
13160.40	-34.50	14.40	-48.90	-13.00	Horizontal
15039.60	-36.30	14.90	-51.20	-13.00	Vertical
17941.20	-37.80	19.90	-57.70	-13.00	Horizontal
	The Worst Tes	t Results for	Channel 810/	1909.8 MHz	
Frequency(GHz)	Power(dBm)	A <sub>Rpl</sub> (dBm)	P <sub>Mea</sub> (dBm)	Limit (dBm)	Polarity
2000.00	-30.00	9.80	-39.80	-13.00	Vertical
9548.50	-38.10	11.30	-49.40	-13.00	Horizontal
13367.40	-41.20	12.40	-53.60	-13.00	Horizontal
15277.80	-34.80	14.80	-49.60	-13.00	Vertical

Page 16 of 61

17931.60 -37.70 19.00 -56.70 -13.00 Horizontal
--

Page 17 of 61

#### 7. CONDUCTED EMISSION

#### 7.1 MEASUREMENT METHOD


The measurement procedure specified in ANSI C63.4-2009 was used for testing. Conducted Emission was measured with travel charger.

#### 7.2 PROVISIONS APPLICABLE

Frequency of Emission (MHz)	Conducted Limit(dBuV)	
, ,	Quasi-Peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50
* Decreases with the logarithm of the frequency.		


#### 7.3 MEASUREMENT RESULT

#### LINE CONDUCTED EMISSION - L



Page 18 of 61

#### LINE CONDUCTED EMISSION - N



Report No.: AGC10141201SZ03-1E4A Page 19 of 61

#### 8. FREQUENCY STABILITY

#### **8.1 MEASUREMENT METHOD**

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1 , Measure the carrier frequency at room temperature.
- 2 , Subject the EUT to overnight soak at  $-30^{\circ}$ C.
- 3 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 , channel 190 for GSM850 measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4 , Repeat the above measurements at  $10^{\circ}$ C increments from  $-30^{\circ}$ C to  $+50^{\circ}$ C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5 , Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6 , Subject the EUT to overnight soak at +50°C.
- 7 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8 , Repeat the above measurements at 10 C increments from  $+50^{\circ}$ C to  $-30^{\circ}$ C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9 , At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

#### **8.2 PROVISIONS APPLICABLE**

#### 8.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.8VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

#### 8.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried

Report No.: AGC10141201SZ03-1E4A Page 20 of 61

battery equipment.

#### **8.3 MEASUREMENT RESULT**

Frequency Error Against Voltage for GSM 850 MHz			
Voltage(V)	Frequency error(Hz)	Frequency error(ppm)	
3.5	21	0.025	
3.8	18	0.021	
4.2	24	0.028	

Frequency Error Against Temperature for GSM 850 MHz			
temperature(°C)	Frequency error(Hz)	Frequency error(ppm)	
-30	31	0.036	
-20	29	0.034	
-10	28	0.033	
0	24	0.028	
10	22	0.026	
20	18	0.021	
30	21	0.025	
40	25	0.029	
50	29	0.034	

Frequency Error Against Voltage for PCS 1900 MHz			
Voltage(V)	Frequency error(Hz)	Frequency error(ppm)	
3.5	31	0.016	
3.8	29	0.015	
4.2	35	0.018	

Frequency Error Against Temperature for PCS 1900 MHz			
$temperature(^{\circ}\mathbb{C})$	Frequency error(Hz)	Frequency error(ppm)	
-30	46	0.054	
-20	43	0.051	
-10	42	0.049	
0	39	0.046	
10	36	0.042	
20	35	0.041	
30	38	0.045	
40	40	0.047	
50	43	0.051	

Report No.: AGC10141201SZ03-1E4A Page 21 of 61

#### 9. OCCUPIED BANDWIDTH

#### 9.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

#### 9.2 PROVISIONS APPLICABLE

The occupied bandwidth (99%) shall not exceed 300 KHz.

#### 9.3 MEASUREMENT RESULT

Occupied Bandwidth (99%) for GSM 850 MHz			
Mode	Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
	824.2	246.61	
GSM	836.6	244.34	
	848.8	250.03	
	824.2	250.37	
GPRS	836.6	241.66	
	848.8	251.30	

Occupied Bandwidth (99%) for PCS 1900 MHz			
Mode	Frequency(MHz)	Occupied Bandwidth (99%)( kHz)	
	1850.2	245.65	
GSM	1880.0	238.11	
	1909.8	243.69	
	1850.2	254.30	
GPRS	1880.0	245.34	
	1909.8	242.82	

Report No.: AGC10141201SZ03-1E4A Page 22 of 61

#### 10. EMISSION BANDWIDTH

#### **10.1 MEASUREMENT METHOD**

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

#### **10.2 PROVISIONS APPLICABLE**

The emission bandwidth is defined as two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power

#### **10.3 MEASUREMENT RESULT**

Emission Bandwidth (-26dBc) for GSM 850 MHz			
Mode	Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
	824.2	313.36	
GSM	836.6	322.14	
	848.8	331.69	
	824.2	324.99	
GPRS	836.6	318.07	
	848.8	321.42	

Emission Bandwidth (-26dBc) for PCS 1900 MHz			
Mode	Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)	
	1850.2	313.21	
GSM	1880.0	313.45	
	1909.8	315.93	
	1850.2	321.55	
GPRS	1880.0	317.95	
	1909.8	317.55	

Page 23 of 61

#### 11. BAND EDGE

#### 11.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

#### 11.2 PROVISIONS APPLICABLE

as Specified in FCC rules of 22.917(b) and 24.238(b)

#### 11.3 MEASUREMENT RESULT


Please refers to Appendix V for compliance test plots for band edges

Report No.: AGC10141201SZ03-1E4A Page 24 of 61


# **APPENDIX I**

**TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION** 


# CONDUCTED EMISSION IN GSM BAND Conducted Emission Transmitting Mode CH 128 30MHz – 1GHz




#### Conducted Emission Transmitting Mode CH 128 1GHz - 26.5GHz




Conducted Emission Transmitting Mode CH 190 30MHz - 1GHz




#### Conducted Emission Transmitting Mode CH 190 1GHz - 26.5GHz




Conducted Emission Transmitting Mode CH 251 30MHz - 1GHz




Conducted Emission Transmitting Mode CH 251 1GHz - 26.5GHz




#### Conducted Emission Idle Mode 30MHz – 1GHz




#### Conducted Emission Idle Mode 1GHz – 26.5GHz




# CONDUCTED EMISSION IN PCS BAND Conducted Emission Transmitting Mode CH 512 30MHz – 1GHz




#### Conducted Emission Transmitting Mode CH 512 1GHz - 26.5GHz




Conducted Emission Transmitting Mode CH 661 30MHz - 1GHz




#### Conducted Emission Transmitting Mode CH 661 1GHz - 26.5GHz




Conducted Emission Transmitting Mode CH 810 30MHz - 1GHz




Conducted Emission Transmitting Mode CH 810 1GHz - 26.5GHz



#### Conducted Emission Idle Mode 30MHz – 1GHz



#### Conducted Emission Idle Mode 1GHz – 26.5GHz




Report No.: AGC10141201SZ03-1E4A Page 33 of 61


# **APPENDIX II**

**TEST PLOTS FOR RADIATED SPURIOUS EMISSION** 


SPURIOUS EMISSION IN GSM BAND
Spurious Emission Transmitting Mode CH 128 30MHz – 1GHz




Spurious Emission Transmitting Mode CH 190 30MHz – 1GHz




Spurious Emission Transmitting Mode CH 251 30MHz – 1GHz




Spurious Emission Transmitting Mode CH 128 1GHz – 10GHz




Spurious Emission Transmitting Mode CH 190 1GHz – 10GHz




Spurious Emission Transmitting Mode CH 251 1GHz – 10GHz




Spurious Emission Idle Mode 30MHz - 1GHz




Spurious Emission Idle Mode 1GHz – 10GHz




SPURIOUS EMISSION IN PCS BAND
Spurious Emission Transmitting Mode CH 512 30MHz – 2GHz




Spurious Emission Transmitting Mode CH 661 30MHz – 2GHz




Spurious Emission Transmitting Mode CH 810 30MHz – 2GHz




Spurious Emission Transmitting Mode CH 512 2GHz – 10GHz




Spurious Emission Transmitting Mode CH 661 2GHz – 10GHz




Spurious Emission Transmitting Mode CH 810 2GHz – 10GHz



Radiated Emission Idle Mode 30MHz - 2GHz



Radiated Emission Idle Mode 2GHz - 18GHz




Report No.: AGC10141201SZ03-1E4A Page 42 of 61


## **APPENDIX III**

# TEST PLOTS FOR OCCUPIED BANDWIDTH (99%) EMISSION BANDWIDTH (-26dBC)


Occupied Bandwidth (99%) GSM 850 BAND CH 128




Occupied Bandwidth (99%) GSM 850 BAND CH 190




Occupied Bandwidth (99%) GSM 850 BAND CH 251




Occupied Bandwidth (99%) GPRS 850 BAND CH 128




Occupied Bandwidth (99%) GPRS 850 BAND CH 190




Occupied Bandwidth (99%) GPRS 850 BAND CH 251




Occupied Bandwidth (99%) PCS 1900 BAND CH 512




Occupied Bandwidth (99%) PCS 1900 BAND CH 661




Occupied Bandwidth (99%) PCS 1900 BAND CH 810



Occupied Bandwidth (99%) GPRS 1900 BAND CH 512



Occupied Bandwidth (99%) GPRS 1900 BAND CH 661



Occupied Bandwidth (99%) GPRS 1900 BAND CH 810




Page 49 of 61


## **APPENDIX IV**

## **TEST PLOTS FOR BAND EDGES**


Low Band Edge GSM 850 BAND CH 128




High Band Edge GSM 850 BAND CH 251




Low Band Edge GPRS 850 BAND CH 128




High Band Edge GPRS 850 BAND CH 251




Low Band Edge PCS 1900 BAND CH 512




High Band Edge PCS 1900 BAND CH 810



Low Band Edge GPRS 1900 BAND CH 512



High Band Edge GPRS 1900 BAND CH 810



Page 54 of 61

# **APPENDIX V**

## **PHOTOGRAPHS OF TEST SETUP**

## CONDUCTED EMISSION



RADIATED SPURIOUS EMISSION



Page 56 of 61

# **APPENDIX VI**

## **PHOTOGRAPHS OF EUT**

Page 57 of 61

### ADAPTER AND BATTERY



TOP VIEW OF SAMPLE



Report No.: AGC10141201SZ03-1E4A Page 58 of 61

### BOTTOM VIEW OF SAMPLE



LEFT VIEW OF SAMPLE



Report No.: AGC10141201SZ03-1E4A Page 59 of 61

### RIGHT VIEW OF SAMPLE




FRONT VIEW OF SAMPLE



Report No.: AGC10141201SZ03-1E4A Page 60 of 61

### BACK VEIW OF SAMPLE



#### INTERNAL PHOTO OF SAMPLE – 1



INTERNAL PHOTO OF SAMPLE - 2



----END OF REPORT----