

FCC/IC Radio Test Report

FCC ID: X5B-PL6322B IC: 8814A-PL6322B

This report concerns (check one): Original Grant Class II Change

Issued Date : Jun. 11, 2012
Project No. : 1205C142
Equipment : AP.2 for PS3
Model Name : PL-6322B

Applicant: Performance Designed Products, LLC

Address: 14144 Ventura Blvd. Suite 200, Sherman Oaks, CA

91423

Manufacturer: Performance Designed Products, LLC

Address: 14144 Ventura Blvd. Suite 200, Sherman Oaks, CA

91423

Tested by:

Neutron Engineering Inc. EMC Laboratory

Date of Receipt: May. 18, 2012

Date of Test:

May. 18, 2012 ~ Jun. 08, 2012

Testing Engineer

(David Mao)

Technical Manager

(Leo Hund)

Authorized Signatory

(Steven Lu)

Neutron Engineering Inc.

No.3,Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.

TEL: (0769) 8318-3000 FAX: (0769) 8319-6000

Report No.: NEI-FICP-1-1205C142 Page 1 of 67



Declaration

Neutron represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **R.O.C.**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

Neutron's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **Neutron** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **Neutron** issued reports.

Neutron's reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **Neutron-self**, extracts from the test report shall not be reproduced except in full with **Neutron**'s authorized written approval.

Neutron's laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Report No.: NEI-FICP-1-1205C142 Page 2 of 67

Table of Contents	Page
1. CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3. GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	11
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	11
3.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	D 12
3.5 DESCRIPTION OF SUPPORT UNITS	13
4 . EMC EMISSION TEST	14
4.1 CONDUCTED EMISSION MEASUREMENT	14
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING	14
4.1.3 TEST PROCEDURE 4.1.4 DEVIATION FROM TEST STANDARD	15 15
4.1.5 TEST SETUP	15
4.1.6 EUT OPERATING CONDITIONS	15
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 RADIATED EMISSION LIMITS	17
4.2.2 MEASUREMENT INSTRUMENTS LIST ANS SETTING	18
4.2.3 TEST PROCEDURE 4.2.4 DEVIATION FROM TEST STANDARD	20 20
4.2.5 TEST SETUP	20 21
4.2.6 EUT OPERATING CONDITIONS	22
4.2.7 TEST RESULTS (BETWEEN30 – 1000 MHZ)	23
4.2.8 TEST RESULTS (ABOVE 1000 MHZ)	27
5 . NUMBER OF HOPPING CHANNEL	45
5.1 APPLIED PROCEDURES / LIMIT	45
5.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	45 45
5.1.2 TEST PROCEDURE 5.1.3 DEVIATION FROM STANDARD	45 45
5.1.4 TEST SETUP	45 45
5.1.5 EUT OPERATION CONDITIONS	45
5.1.6 TEST RESULTS	46

Report No.: NEI-FICP-1-1205C142 Page 3 of 67

Table of Contents	Page
6 . AVERAGE TIME OF OCCUPANCY	47
6.1 APPLIED PROCEDURES / LIMIT	47 47
6.1.1 MEASUREMENT INSTRUMENTS LIST 6.1.2 TEST PROCEDURE	47 47
6.1.3 DEVIATION FROM STANDARD	47
6.1.4 TEST SETUP	48
6.1.5 EUT OPERATION CONDITIONS	48
6.1.6 TEST RESULTS	49
7. HOPPING CHANNEL SEPARATION MEASUREMENT	51
7.1 APPLIED PROCEDURES / LIMIT	51
7.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	51
7.1.2 TEST PROCEDURE	51
7.1.3 DEVIATION FROM STANDARD	51
7.1.4 TEST SETUP	51
7.1.5 EUT OPERATION CONDITIONS	51 52
7.1.6 TEST RESULTS	52
8 . BANDWIDTH TEST	54
8.1 APPLIED PROCEDURES / LIMIT	54
8.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	54
8.1.2 TEST PROCEDURE	54
8.1.3 DEVIATION FROM STANDARD	54
8.1.4 TEST SETUP 8.1.5 EUT OPERATION CONDITIONS	54 54
8.1.6 TEST RESULTS	55
9 . PEAK OUTPUT POWER TEST	57
9.1 APPLIED PROCEDURES / LIMIT	57
9.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	57 57
9.1.2 TEST PROCEDURE	57
9.1.3 DEVIATION FROM STANDARD	57
9.1.4 TEST SETUP	57
9.1.5 EUT OPERATION CONDITIONS	57
9.1.6 TEST RESULTS	58
10. ANTENNA CONDUCTED SPURIOUS EMISSION	60
10.1 APPLIED PROCEDURES / LIMIT	60
10.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING	60
10.1.2 TEST PROCEDURE	60
10.1.3 DEVIATION FROM STANDARD	60
10.1.4 TEST SETUP	60 60
10.1.5 EUT OPERATION CONDITIONS	60

Report No.: NEI-FICP-1-1205C142 Page 4 of 67

Table of Contents	Page
10.1.6 TEST RESULTS	61
11 . EUT TEST PHOTO	67

Report No.: NEI-FICP-1-1205C142 Page 5 of 67

1. CERTIFICATION

Equipment: AP.2 for PS3
Brand Name: Afterglow
Model Name: PL-6322B

Applicant: Performance Designed Products, LLC Factory: Performance Designed Products, LLC

A d d r e s s: 14144 Ventura Blvd. Suite 200, Sherman Oaks, CA 91423

Date of Test: May. 18, 2012 ~ Jun. 08, 2012 Test Item: ENGINEERING SAMPLE

Standards: FCC Part15, Subpart C(15.247) / ANSI C63.4: 2003/ Canada RSS-210:2010

The above equipment has been tested and found compliance with the requirement of the relative standards by Neutron Engineering Inc. EMC Laboratory.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. NEI-FICP-1-1205C142) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of NVLAP and TAF according to the ISO-17025 quality assessment standard and technical standard(s).

Report No.: NEI-FICP-1-1205C142 Page 6 of 67



2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

APP	APPLIED STANDARD: 47 CFR Part 15, Subpart C; Canada RSS-210:2010							
Standard Section								
RSS-210	47 CFR Part 15	Test Item	Judgment	Remark				
RSS-GEN 7.2.2	15.207	Conducted Emission	N/A					
RSS-210 Annex 8 (A8.1d)	15.247(d)	Antenna conducted Spurious Emission	PASS					
RSS-210 Annex 8 (A8.1d)	15.247 (a)(1)	Hopping Channel Separation	PASS					
RSS-210 Annex 8 (A8.1b)	15.247 (b)(1)	Peak Output Power	PASS					
RSS-210 Annex 8 (A8.1a)	15.247(d) 15.209	Radiated Spurious Emission	PASS					
RSS-210 Annex 8 (A8.4(2))	15.247 (a)(1)(iii)	Number of Hopping Frequency	PASS					
RSS-210 Annex 8 (A8.5)	15.247 (a)(1)(iii)	Dwell Time	PASS					
RSS-Gen 7.2.3	15.205	Restricted Bands	PASS					
RSS-210 Annex 8 (A8.5)	15.203	Antenna Requirement	PASS					

NOTE:

- (1)" N/A" denotes test is not applicable in this Test Report
- (2)The EUT is used new battery.

Report No.: NEI-FICP-1-1205C142 Page 7 of 67

2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3, Jinshagang 1st Road, ShiXia, Dalang Town, Dong Guan, China.523792 Neutron's test firm number for FCC 319330 Neutron's test firm number for IC 4428B-1

2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement $\mathbf{y} \pm \mathbf{U}$, where expended uncertainty \mathbf{U} is based on a standard uncertainty multiplied by a coverage factor of $\mathbf{k=2}$, providing a level of confidence of approximately 95 % \circ

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U, (dB)	NOTE
DG-C02	CISPR	150 KHz ~ 30MHz	2.59	

B. Radiated Measurement:

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)	NOTE
		30MHz ~ 200MHz	V	3.22	
DG-CB03	CISPR	30MHz ~ 200MHz	Н	3.60	
DG-CB03	CISER	200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	Н	3.94	

Report No.: NEI-FICP-1-1205C142 Page 8 of 67



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Equipment	AP.2 for PS3		
Brand Name	Afterglow		
Model Name for FCC	PL-6322B		
OEM Brand/Model Name	N/A		
Model Difference	N/A		
	The EUT is a AP.2 for P	PS3	
	Operation Frequency:	2402~2480 MHz	
	Modulation Type:	CESK (1Mbps)	
	Bit Rate of Transmitter:	GFSK (1Mbps)	
	Number Of Channel	64 CH Please see Note 2.	
	Antenna Designation:	Please see Note 3.	
Product Description	Antenna Gain(Peak)	Please see Note 3.	
	Output Power:	-11.45 dBm	
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical		
Power Source	DC Voltage supplied from Lithium-ion battery		
Power Rating	DC 3.7V		
Connecting I/O Port(s)	Please refer to the User	's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Report No.: NEI-FICP-1-1205C142 Page 9 of 67

2

	Frequency Channel						
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402	17	2422	33	2438	49	2459
02	2403	18	2423	34	2439	50	2461
03	2404	19	2424	35	2440	51	2463
04	2405	20	2425	36	2441	52	2465
05	2406	21	2426	37	2443	53	2466
06	2407	22	2427	38	2445	54	2467
07	2408	23	2428	39	2447	55	2468
08	2409	24	2429	40	2449	56	2469
09	2411	25	2430	41	2450	57	2470
10	2413	26	2431	42	2451	58	2471
11	2415	27	2432	43	2452	59	2472
12	2417	28	2433	44	2453	60	2473
13	2418	29	2434	45	2454	61	2474
14	2419	30	2435	46	2455	62	2476
15	2420	31	2436	47	2456	63	2478
16	2421	32	2437	48	2457	64	2480

Frequenc	Frequency Group 1		cy Group 2	Frequen	cy Group 3	Frequen	cy Group 4
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402	01	2404	01	2406	01	2408
02	2467	02	2469	02	2471	02	2473
03	2434	03	2436	03	2438	03	2440
04	2450	04	2452	04	2454	04	2456
05	2466	05	2468	05	2470	05	2472
06	2403	06	2405	06	2407	06	2409
07	2419	07	2421	07	2423	07	2425
08	2435	08	2437	08	2439	08	2441
09	2451	09	2453	09	2455	09	2457
10	2418	10	2420	10	2422	10	2424
11	2474	11	2476	11	2478	11	2480
12	2411	12	2413	12	2415	12	2417
13	2427	13	2429	13	2431	13	2433
14	2443	14	2445	14	2447	14	2449
15	2459	15	2461	15	2463	15	2465
16	2426	16	2428	16	2430	16	2432

The EUT 16 channels of each sequence, total 4 sequences is used

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Printed	N/A	2.5

Report No.: NEI-FICP-1-1205C142 Page 10 of 67

3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode NOTE (1)

The EUT system operated these modes were found to be the worst case during the pre-scanning test as Following:

For Conducted Emission				
Final Test Mode Description				
-	"N/A" denotes test is not applicable in this Test Report			

For Radiated Emission			
Final Test Mode Description			
Mode 1	TX Mode NOTE (1)		

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: manual control		
Frequency (MHz)	2402 MHz	2441 MHz	2480 MHz
Parameters	DEF	DEF	DEF

Report No.: NEI-FICP-1-1205C142 Page 11 of 67



Report No.: NEI-FICP-1-1205C142 Page 12 of 67

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	AP.2 for PS3	Afterglow	PL-6322B	X5B-PL6322B / 8814A-PL6322B	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length"</code> column.

Report No.: NEI-FICP-1-1205C142 Page 13 of 67

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard	
FREQUENCT (MITZ)	Quasi-peak	Average	Quasi-peak	Average	Stariuaru	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR	
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR	
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR	

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	May.04.2013
2	LISN	R&S	ENV216	100087	May.04.2013
3	Test Cable	N/A	C_17	N/A	Mar.28.2013
4	EMI TEST RECEIVER	R&S	ESCS30	826547/022	May.04.2013
5	50Ω Terminator	SHX	TF2-3G-A	08122902	May.04.2013

Remark: "N/A" denotes No Model No., Serial No. or No Calibration specified.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

Report No.: NEI-FICP-1-1205C142 Page 14 of 67


4.1.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.1.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT was programmed to be in continuously transmitting /Hopping on mode.

Report No.: NEI-FICP-1-1205C142 Page 15 of 67

4.1.7 TEST RESULTS

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:		Relative Humidity:	
Pressure:		Test Power :	
Test Mode :	"N/A" denotes test is not applicable in this Test Report		

Remark

- (1) All readings are QP Mode value unless otherwise stated AVG in column of Note ... If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform on this case, a " * " marked in AVG Mode column of Interference Voltage Measured on the North AVG Mode column of Interference Voltage Measured on
- (2) Measuring frequency range from 150KHz to 30MHz o

Report No.: NEI-FICP-1-1205C142 Page 16 of 67



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength Measurement Dis	
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)		
FREQUENCT (IVITIZ)	PEAK	AVERAGE	
Above 1000	74	54	

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Report No.: NEI-FICP-1-1205C142 Page 17 of 67

4.2.2 MEASUREMENT INSTRUMENTS LIST ANS SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Active Loop Antenna	R&S	HFH2-Z2	830749/020	May.04.2013
2	Bi-log Antenna	Schwarbeck	VULB9160	9160-3232	May.25.2013
3	Horn Antenna	ETS	3115	00075789	May.25.2013
4	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170340	Dec.14.2012
5	Amplifier	HP	8447D	2944A09673	May.04.2013
6	Amplifier	Agilent	8449B	3008A02274	May.04.2013
7	Amplifier	EMC	EMC2654045	980039	Oct.30.2012
8	Test Receiver	R&S	ESCI	100895	May.04.2013
9	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2012
10	Test Cable	N/A	C-01_CB03	N/A	May.03.2013
11	Test Cable	HUBER+SUHNER	SUCOFLEX_8 m	313794/4	Apr.10.2013
12	Controller	СТ	SC100	N/A	N/A

Remark: "N/A" denotes No Model Name / Serial No. and No Calibration specified.

Spectrum Parameter	Setting		
Attenuation	Auto		
Start Frequency	1000 MHz		
Stop Frequency	10th carrier harmonic		
RB / VB (emission in restricted	1 MHz / 1 MHz for Dook 1 MHz / 10Hz for Average		
band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average		

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz for PK/AVG detector
Start ~ Stop Frequency	90kHz~110kHz for QP detector
Start ~ Stop Frequency	110kHz~490kHz for PK/AVG detector
Start ~ Stop Frequency	490kHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

Report No.: NEI-FICP-1-1205C142 Page 18 of 67

DUTY CYCLE: TX 2441MHz

Dwell time=ON/ON+OFF


ON:1.8 msec

ON+OFF: (total time):17.3msec

Dwell time: 10.40%

AV=PK+20 log(Dwell time)

AV=PK-19.66



Report No.: NEI-FICP-1-1205C142 Page 19 of 67



4.2.3 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.


4.2.4 DEVIATION FROM TEST STANDARD
No deviation

Report No.: NEI-FICP-1-1205C142 Page 20 of 67




4.2.5 TEST SETUP

(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



Report No.: NEI-FICP-1-1205C142 Page 21 of 67

Report No.: NEI-FICP-1-1205C142 Page 22 of 67


4.2.7 TEST RESULTS (BETWEEN30 - 1000 MHZ)

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz		

Freq.	Ant.	Reading(RA)	Corr.Factor(CF)	Measured(FS)	Limits(QP)	Margin	Note
(MHz)	H/V	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	NOLE
46.98	V	29.10	-17.09	12.01	40.00	- 27.99	
202.18	V	28.71	-16.51	12.20	43.50	- 31.30	
272.50	V	37.66	-13.12	24.54	46.00	- 21.46	
362.23	V	29.23	-10.40	18.83	46.00	- 27.17	
633.83	V	27.66	-3.63	24.03	46.00	- 21.97	
757.50	V	28.03	-2.46	25.57	46.00	- 20.43	

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = $0.3 \text{ sec./MHz} \circ$
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note \rceil . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform \circ
- (3) Measuring frequency range from 30MHz to 1000MHz $^{\circ}$
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table \circ




Report No.: NEI-FICP-1-1205C142 Page 23 of 67



EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
32.43	Н	42.13	-16.50	25.63	40.00	- 14.37	
163.38	Н	37.93	-17.53	20.40	43.50	- 23.10	
231.28	Η	40.36	-15.56	24.80	46.00	- 21.20	
287.05	Н	38.34	-12.23	26.11	46.00	- 19.89	
432.55	Н	32.68	-8.43	24.25	46.00	- 21.75	
522.28	Н	31.93	-6.52	25.41	46.00	- 20.59	

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz $^{\circ}$
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note \rceil . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform \circ
- (3) Measuring frequency range from 30MHz to 1000MHz o
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table \circ




Report No.: NEI-FICP-1-1205C142 Page 24 of 67



EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	RX Mode 2402MHz		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
76.08	V	36.88	-18.86	18.02	40.00	- 21.98	
224.00	V	32.44	-15.76	16.68	46.00	- 29.32	
287.05	V	33.80	-12.23	21.57	46.00	- 24.43	
498.03	V	33.08	-7.39	25.69	46.00	- 20.31	
672.63	V	28.41	-3.26	25.15	46.00	- 20.85	
776.90	V	29.25	-2.19	27.06	46.00	- 18.94	

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz $^{\circ}$
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m l}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m o}$
- (3) Measuring frequency range from 30MHz to 1000MHz \circ
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table \circ






EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	RX Mode 2402MHz		

Freq. (MHz)	Ant. H/V	Reading(RA) (dBuV)	Corr.Factor(CF) (dB)	Measured(FS) (dBuV/m)	Limits(QP) (dBuV/m)	Margin (dB)	Note
44.55	Η	44.19	-16.98	27.21	40.00	- 12.79	
73.65	Н	37.33	-18.68	18.65	40.00	- 21.35	
127.00	Η	37.17	-18.16	19.01	43.50	- 24.49	
240.98	Н	37.30	-15.10	22.20	46.00	- 23.80	
558.65	Н	27.83	-5.28	22.55	46.00	- 23.45	
789.03	Н	27.54	-2.02	25.52	46.00	- 20.48	

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz \circ
- (2) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m l}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m o}$
- (3) Measuring frequency range from 30MHz to 1000MHz o
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table \circ



4.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	V	22.63	2.97	31.91	54.54	34.88	74.00	54.00	X/E
2400.00	V	34.39	14.73	31.90	66.29	46.63	74.00	54.00	X/E
2402.25	V	62.19	42.53	31.90	94.09	74.43			X/F
4803.50	V	57.72	38.06	5.21	62.93	43.27	74.00	54.00	X/H


Remark:

- (1) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency of F' denotes fundamental frequency; "H' denotes spurious frequency. "E' denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:

 Average = Peak value + 20log(Duty cycle) , Final AV=PK-19.66

Report No.: NEI-FICP-1-1205C142 Page 27 of 67

Neutron Engineering Inc.= TX CH01(Above 1000 MHz, Vertical) 110.0 dBuV/m Limit: AVG: 70 30.0 2377.000 2382.00 2387.00 2392.00 2397.00 2402.00 2407.00 2412.00 2417.00 2427.00 MHz 80.0 dBuV/m



EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2390.00	Н	23.18	3.52	31.91	55.09	35.43	74.00	54.00	X/E
2400.00	Н	37.01	17.35	31.90	68.91	49.25	74.00	54.00	
2401.75	Н	62.68	43.02	31.90	94.58	74.92			X/F
4803.38	Н	54.38	34.72	5.21	59.59	39.93	74.00	54.00	X/H


- (1) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:

 Average = Peak value + 20log(Duty cycle) , Final AV=PK-19.66

Report No.: NEI-FICP-1-1205C142 Page 29 of 67

Neutron Engineering Inc.





Report No.: NEI-FICP-1-1205C142 Page 30 of 67

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2441MHz		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2441.75	V	61.21	41.55	31.85	93.06	73.40			X/F
4883.63	V	59.10	39.44	5.50	64.60	44.94	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency of F' denotes fundamental frequency; "H' denotes spurious frequency. "E' denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:

 Average = Peak value + 20log(Duty cycle) , Final AV=PK-19.66

Report No.: NEI-FICP-1-1205C142 Page 31 of 67

Neutron Engineering Inc.= TX CH36 (Above 1000 MHz, Vertical) 110.0 dBuV/m Limit: AVG: 70 30.0 2417.000 2422.00 2427.00 2432.00 2442.00 2447.00 2457.00 2467.00 MHz 2437.00 2452.00 80.0 dBuV/m Limit: X ž 40 1000.000 3550.00 6100.00 8650.00 11200.00 13750.00 16300.00 26500.00 MHz

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2441MHz		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2441.88	Н	61.25	41.59	31.85	93.10	73.44			X/F
4883.38	Н	51.33	31.67	5.50	56.83	37.17	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform \circ
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ∘
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:

 Average = Peak value + 20log(Duty cycle) , Final AV=PK-19.66

Report No.: NEI-FICP-1-1205C142 Page 33 of 67

Neutron Engineering Inc.



EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2480MHz		


Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2479.75	V	61.14	41.48	31.80	92.94	73.28			X/F
2483.50	V	32.32	12.66	31.80	64.12	44.46	74.00	54.00	X/E
4959.50	V	59.28	39.62	5.78	65.06	45.40	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform \circ
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:

 Average = Peak value + 20log(Duty cycle) , Final AV=PK-19.66

Report No.: NEI-FICP-1-1205C142 Page 35 of 67

Neutron Engineering Inc.



EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2480MHz		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
2479.88	Н	59.90	40.24	31.80	91.70	72.04			X/F
2483.50	Н	34.87	15.21	31.80	66.67	47.01	74.00	54.00	X/E
4959.63	Н	53.64	33.98	5.78	59.42	39.76	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform \circ
- (2) Measuring frequency range from 30MHz to 1000MHz or the 10th harmonic of highest fundamental frequency "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission ∘
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand
- (7) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (8) The average value of fundamental frequency is:

 Average = Peak value + 20log(Duty cycle) , Final AV=PK-19.66


Report No.: NEI-FICP-1-1205C142 Page 37 of 67

1000.000 3550.00

6100.00

8650.00

11200.00



13750.00

16300.00

21400.00

18850.00


26500.00 MHz

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	RX Mode 2402MHz		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
1460.46	V	48.96	36.74	-6.63	42.33	30.11	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (2) Measuring frequency range from 1000MHz to 6000MHz or the 10th harmonic of highest fundamental frequency of F' denotes fundamental frequency; "H' denotes spurious frequency. (E' denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:

"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand




Report No.: NEI-FICP-1-1205C142

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	RX Mode 2402MHz		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
1420.00	Н	50.24	37.52	-6.84	43.40	30.68	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (2) Measuring frequency range from 1000MHz to 6000MHz or the 10th harmonic of highest fundamental frequency of F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:


"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand



EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	RX Mode 2441MHz		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
1568.30	V	49.25	36.17	-5.67	43.58	30.50	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (2) Measuring frequency range from 1000MHz to 6000MHz or the 10th harmonic of highest fundamental frequency of F' denotes fundamental frequency; "H' denotes spurious frequency. "E' denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand




Report No.: NEI-FICP-1-1205C142

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	RX Mode 2441MHz		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Limit		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
1762.50	Н	47.89	34.58	-3.53	44.36	31.05	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (2) Measuring frequency range from 1000MHz to 6000MHz or the 10th harmonic of highest fundamental frequency of F' denotes fundamental frequency; "H' denotes spurious frequency. "E' denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand



EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	RX Mode 2480MHz		

Freq.	Ant.Pol.	Reading		Ant./CF	Act.		Lir		
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
1805.20	V	46.75	35.82	-3.06	43.69	32.76	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of ${}^{\mathbb{F}}$ Note $_{\mathbb{J}}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform \circ
- (2) Measuring frequency range from 1000MHz to 6000MHz or the 10th harmonic of highest fundamental frequency of F' denotes fundamental frequency; "H' denotes spurious frequency. (E' denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission •
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:

"X" - denotes Laid on Table; "Y" - denotes Vertical Stand; "Z" - denotes Side Stand




Report No.: NEI-FICP-1-1205C142

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	RX Mode 2480MHz		

Freq.	Ant.Pol.	Rea	ding	Ant./CF	A	ct.	Lir	nit	
		Peak	AV		Peak	AV	Peak	AV	Note
(MHz)	H/V	(dBuV)	(dBuV)	CF(dB)	(dBuV/m)	(dBuV/m)	(dBuV/m)	(dBuV/m)	
1753.30	Н	48.70	36.92	-3.63	45.07	33.29	74.00	54.00	X/H

- (1) All readings are Peak unless otherwise stated QP in column of \lceil Note $_{
 m J}$. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform $_{
 m O}$
- (2) Measuring frequency range from 1000MHz to 6000MHz or the 10th harmonic of highest fundamental frequency of F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency. (This judgment method includes the Band Edge Requirement.)
- (3) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission \circ
- (4) Data of measurement within this frequency range shown " * " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (6) EUT Orthogonal Axis:
 - "X" denotes Laid on Table; "Y" denotes Vertical Stand; "Z" denotes Side Stand



5. NUMBER OF HOPPING CHANNEL

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Frequency Range (MHz)	Result	
15.247 (a)(1)(iii)	Number of Hopping Channel	2400-2483.5	PASS	

5.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2012

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


5.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

5.1.3 DEVIATION FROM STANDARD

No deviation.

5.1.4 TEST SETUP



5.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.


Report No.: NEI-FICP-1-1205C142 Page 45 of 67



5.1.6 TEST RESULTS

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1009 hPa	Test Voltage :	DC 3.7V
Test Mode :	Hopping Mode		

Number of Hopping Channel	16



Report No.: NEI-FICP-1-1205C142 Page 46 of 67

6. AVERAGE TIME OF OCCUPANCY

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C					
Section Test Item Limit Frequency Range (MHz) Result					
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS	

6.1.1 MEASUREMENT INSTRUMENTS LIST

It	tem	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
	1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2012

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.


6.1.2 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- C. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- j. Dwell time = [spreading rate/16] x duty-cycle x 0.4 seconds

6.1.3 DEVIATION FROM STANDARD

No deviation.

Report No.: NEI-FICP-1-1205C142 Page 47 of 67



Report No.: NEI-FICP-1-1205C142 Page 48 of 67

6.1.6 TEST RESULTS


EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1009 hPa	Test Voltage :	DC 3.7V
Test Mode :	Hopping Mode -Group 3		

Mode	Number of transmission in a 6.4(16Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
2480MHz	(6/1) *6.4=38.4 times Note1	0.18	6.912	400

Note1: 6 times of occupied channels per 1 second

	Results
Measured cycle (sec)	16 CH*0.4=6.4
The total number of frequency-hopping per second	((6/1)*16)=96
The number of occupied channels per second	96/16=6(number/sec)
occupied time for each channel(1)	0.18ms
The total number of channels occupied within one cycle (2)	(6/1) *6.4=38.4 times
The average time of occupancy within one cycle(1)*(2)	6.912msec
LIMIT (msec)	400msec

Report No.: NEI-FICP-1-1205C142 Page 49 of 67



7. HOPPING CHANNEL SEPARATION MEASUREMENT

7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

7.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2012

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.1.2 TEST PROCEDURE

- a. The EUT must have its hopping function enabled
- b. Span = wide enough to capture the peaks of two adjacent channels Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span Video (or Average) Bandwidth (VBW) ≥ RBW Sweep = auto Detector function = peak Trace = max hold

7.1.3 DEVIATION FROM STANDARD

No deviation.

7.1.4 TEST SETUP



7.1.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in hopping mode.


Report No.: NEI-FICP-1-1205C142 Page 51 of 67

7.1.6 TEST RESULTS


EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	60 %
Pressure:	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	Hopping on -CH01 / CH36 /CH64		

Frequency	Ch. Separation (MHz)	20dB Bandwidth (MHz)	Result
2402 MHz	1.172	1.520	Complies
2441 MHz	1.142	1.480	Complies
2480 MHz	1.106	1.380	Complies

Ch. Separation Limits: >20dB bandwidth or >2/3 of 20dB bandwidth



Report No.: NEI-FICP-1-1205C142 Page 52 of 67



8. BANDWIDTH TEST

8.1 APPLIED PROCEDURES / LIMIT

	FCC Part15 (15.247) , Subpart C						
Section	Test Item	Limit	Frequency Range (MHz)	Result			
15.247	Bandwidth	<= 1 MHz	2400-2483.5	PASS			
(a)(2)	Danuwiutii	(20dB bandwidth)	2400-2463.5	FAGG			

8.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2012

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz (20dB Bandwidth) / 30 kHz (Channel Separation)
VB	100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

8.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

8.1.3 DEVIATION FROM STANDARD

No deviation.

8.1.4 TEST SETUP



8.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FICP-1-1205C142 Page 54 of 67


8.1.6 TEST RESULTS

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1009 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH01 / CH36 /CH64		

Frequency	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Channel Separation (MHz)	Result
2402 MHz	1.520	3.400	<= 1MHz	PASS
2441 MHz	1.480	2.840	<= 1MHz	PASS
2480 MHz	1.380	2.390	<= 1MHz	PASS



Report No.: NEI-FICP-1-1205C142 Page 55 of 67



9. PEAK OUTPUT POWER TEST

9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C						
Section	Test Item	Limit	Frequency Range (MHz)	Result		
15.247 (b)(1)	Peak Output Power	0.125 watt or 21dBm	2400-2483.5	PASS		

9.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2012

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.

9.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 3MHz, VBW= 3MHz, Sweep time = Auto.

9.1.3 DEVIATION FROM STANDARD

No deviation.

9.1.4 TEST SETUP



9.1.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FICP-1-1205C142 Page 57 of 67


9.1.6 TEST RESULTS

EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1009 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH01/ CH36 /CH64	·	

Te	est Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)	LIMIT (W)
	CH01	2402	-11.45	21	0.125
	CH36	2441	-12.49	21	0.125
	CH64	2480	-13.62	21	0.125



Report No.: NEI-FICP-1-1205C142 Page 58 of 67



Report No.: NEI-FICP-1-1205C142 Page 59 of 67

Date: 7.JUN.2012 20:48:37

10. ANTENNA CONDUCTED SPURIOUS EMISSION

10.1 APPLIED PROCEDURES / LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

10.1.1 MEASUREMENT INSTRUMENTS LIST AND SETTING

ĺ	Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
	1	Spectrum Analyzer	R&S	FSP 40	100185	Nov.25.2012

Remark: "N/A" denotes No Model Name, Serial No. or No Calibration specified.


10.1.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

10.1.3 DEVIATION FROM STANDARD

No deviation.

10.1.4 TEST SETUP



10.1.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.6 Unless otherwise a special operating condition is specified in the follows during the testing.

Report No.: NEI-FICP-1-1205C142 Page 60 of 67


10.1.6 TEST RESULTS


EUT:	AP.2 for PS3	Model Name :	PL-6322B
Temperature:	25 ℃	Relative Humidity:	58 %
Pressure:	1009 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH01 / CH36 / CH64 & Hopping on mode		


	•	e max. radio frequency power in any 100kHz bandwidth outside the frequency band		The max. radio frequency power in any 100 kHz bandwidth within the frequency band.		
	FREQUENCY(MHz)	POWER(dBm)	FREQUENCY(MHz)	POWER(dBm)		
	2400.00	-51.20	2483.50	-56.33		
Result						

In any 100kHz bandwidth outside the frequency band, the radio frequency power is at least 20dB below that in the 100kHz bandwidth within the band that contains the highest lever of the desired power.


Report No.: NEI-FICP-1-1205C142 Page 61 of 67








Report No.: NEI-FICP-1-1205C142 Page 64 of 67








11. EUT TEST PHOTO

Radiated Measurement Photos





Report No.: NEI-FICP-1-1205C142 Page 67 of 67