

Shenzhen Huatongwei International Inspection Co., Ltd.

Keji S,12th, Road, Hi-tech Industrial Park, Shenzhen, Guangdong, China Phone:86-755-26748099 Fax:86-755-26748089 http://www.szhtw.com.cn







MPE TEST REPORT

FCC Per 47 CFR 2.1091(b)

Report Reference No..... WE11080016 FCC ID.....:: X5QRD77715

Compiled by

(position+printed name+signature)..: File administrators Tim Zhang

Supervised by

Test Engineer Eric Zhang (position+printed name+signature)..:

Approved by

(position+printed name+signature)... Manager Wenliang Li

Date of issue..... Sep 21, 2011

Testing Laboratory Name Shenzhen Huatongwei International Inspection Co., Ltd

Address....: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name..... Jetlun(ShenZhen)Corporation

1008A Skyworth Building Gao-xin RD South High-tech Park Address....:

Nanshan District Shenzhen China

Test specification:

Standard: FCC Part 15.247: Operation within the bands 920-928 MHz,

2400-2483.5 MHz and 5725-5850 MHz Direct Sequence System

TRF Originator....: Shenzhen Huatongwei International Inspection CO., Ltd

Dated 2006-06 Master TRF.....:

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Appliance Module, Appliance Gauge, ZigBee Extender

Trade Mark:

Model/Type reference....: RD77715

Modulation Type **QPSK**

Listed Models: RD77711,RD77721,LSM1E103T0

Result....: **Positive** V1.0 Page 2 of 6 Report No.: WE11080016

TEST REPORT

Test Report No. :	Test Report No. : WE11080016	Sep 21, 2011
rest Report No	WE11000010	Date of issue

Equipment under Test Appliance Module, Appliance Gauge, ZigBee Extender

Model /Type RD77715

Listed Models RD77711,RD77721,LSM1E103T0

Applicant Jetlun(ShenZhen)Corporation

1008A Skyworth Building Gao-xin RD South High-tech Park Nanshan District Shenzhen China. Address

Manufacturer ZhuHai YueHua Electronic Co.,Ltd.

13, Pingdong Road4, NanPing Science&Technology Address

Industrial Garden, Zhuhai, China.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	SUMMARY	4
1.1.	EUT configuration	4
1.2.	NOTE	4
<u>2.</u>	TEST ENVIRONMENT	5
2.1. 2.2.	Address of the test laboratory Environmental conditions	5 5
2.3.	Statement of the measurement uncertainty	5
<u>3.</u>	METHOD OF MEASUREMENT	5
3.1.	Applicable Standard	5
3.2. 3.3.	Limit MPE Calculation Method	6 6
<u>4.</u>	CONCLUSION	6

V1.0 Page 4 of 6 Report No.: WE11080016

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

supplied by the manufacturer

○ - supplied by the lab

O Power Cable Length (m): /

Shield: /
Detachable: /

Manufacturer: /

Model No.: /

1.2. **NOTE**

O Multimeter

1. The EUT is an IEEE 802.15 ZigBee Standard type device, The functions of the EUT listed as below:

	Test Standards Reference Repor		
Zigbee	FCC Part 15 Subpart C (Section15.247)	WE11080015	
Zigbee	MPE	WE11080016	

2. The frequency bands used in this EUT are listed as follows:

Frequency Band(MHz)	2400-2483.5	5150-5350	5470-5725	5725-5850
Zigbee	\checkmark	_		_

3. The EUT provides one completed transmitter and receiver.

Modulation Mode	TX Function	
Zigbee	1TX	

V1.0 Page 5 of 6 Report No.: WE11080016

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

2.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 950-1050mbar

2.3. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.24 dB	(1)
Radiated Emission	1~18GHz	5.16 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.39 dB	(1)

⁽¹⁾ This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

3.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time
Range(MHz)	Strength(V/m)	Strength(A/m)	(mW/cm²)	(minute)
	Limits for Oc	cupational/Controll	ed Exposure	
0.3 - 3.0	614	1.63	(100) *	6
3.0 - 30	1842/f	4.89/f (900/f)* 6		6
30 – 300	61.4	0.163	1.0	6
300 – 1500	1	1	f/300	6
1500 – 100,000	1	1	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency	Electric Field	Magnetic Field	Power Density	Averaging Time
Range(MHz)	Strength(V/m)	Strength(A/m)	(mW/cm²)	(minute)
Limits for Occupational/Controlled Exposure				
0.3 - 3.0	614	1.63	(100) *	30
3.0 - 30	824/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	1	f/1500	30
1500 – 100,000	1	1	1.0	30

F=frequency in MHz

3.3. MPE Calculation Method

Predication of MPE limit at a given distance Equation from page 18 of OET Bulletin 65, Edition 97-01

S=PG/4πR²

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the antenna is 3.0 dBi, the RF power density can be obtained.

TEST RESULTS

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm²)	Power Density At 20 cm (mW/cm²)	Test Results
2405	20.00	19.39	86.896	1.995	1.000	0.034506	Pass
2440	20.00	19.65	92.257	1.995	1.000	0.036635	Pass
2480	20.00	3.451	2.213	1.995	1.000	0.000879	Pass

4. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the controlled RF Exposure.

End of Re	eport
-----------	-------

^{*=}Plane-wave equivalent power density