



No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM130300119801
Page: 1 of 25

FCC REPORT

Application No. :	SZEM1303001198RF
Applicant:	Pixel Enterprise Limited
Product Name:	ROOK
Model No.(EUT):	RF-508
FCC ID:	X5SROOK-RF-508
Standards:	47 CFR Part 15, Subpart C (2012)
Date of Receipt:	2013-03-19
Date of Test:	2013-04-19 to 2013-04-25
Date of Issue:	2013-05-10

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203	ANSI C63.10 (2009)	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 (2009)	N/A
Field Strength of the Fundamental Signal	47 CFR Part 15, Subpart C Section 15.249 (a)	ANSI C63.10 (2009)	PASS
Spurious Emissions	47 CFR Part 15, Subpart C Section 15.249 (a)/15.209	ANSI C63.10 (2009)	PASS
Band Edge (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.249(a)/15.205	ANSI C63.10 (2009)	PASS
20dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.215 (c)	ANSI C63.10 (2009)	PASS

Remark:

N/A: In this while report not applicable

Note: Due to the EUT is powered by the battery only, the AC Power Line Conducted Emission is not applicable.

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 TEST ENVIRONMENT AND MODE.....	5
4.4 DESCRIPTION OF SUPPORT UNITS	5
4.5 TEST LOCATION.....	5
4.6 TEST FACILITY.....	6
4.7 DEVIATION FROM STANDARDS	6
4.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
4.10 EQUIPMENT LIST	7
5 TEST RESULTS AND MEASUREMENT DATA	9
5.1 ANTENNA REQUIREMENT	9
5.2 RADIATED SPURIOUS EMISSIONS	10
5.3 BAND EDGE (RADIATED EMISSION).....	17
5.4 20dB BANDWIDTH.....	23-25

4 General Information

4.1 Client Information

Applicant:	Pixel Enterprise Limited
Address of Applicant:	Rm1228, 12/F, One Grand Tower, 639 Nathan Road, Mong K, Hong Kong

4.2 General Description of EUT

Product Name:	ROOK
Model No.:	RF-508
Frequency Range:	2406.52 MHz ~ 2445.00MHz
Modulation Type:	FSK
Number of Channels:	4 (declared by the client)
Sample Type:	Portable production
Antenna Type:	Integral
Antenna Gain:	0dBi
Power Supply:	3.0V DC (1.5V x 2 "AAA" Size Batteries)
Test Voltage:	3.0V DC (1.5V x 2 "AAA" Size Batteries)

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency
1CH	2406.52MHz	3CH	2421.00MHz
2CH	2410.00MHz	4CH	2445.00MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The Lowest channel(CH1)	2406.52MHz
The Middle channel(CH3)	2421.00MHz
The Highest channel(CH4)	2445.00MHz

4.3 Test Environment and Mode

Operating Environment:	
Temperature:	26.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010mbar
Test mode:	
Transmitting mode:	Keep the EUT in continue transmitting mode at special channel with modulation.

4.4 Description of Support Units

The EUT has been tested independent unit.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.



4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1 & 4620C-2.

4.7 Deviation from Standards

None.

4.8 Abnormalities from Standard Conditions

None.

4.9 Other Information Requested by the Customer

None.

4.10 Equipment List


RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2013-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2013-05-17
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2013-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2013-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2013-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2013-05-17
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2013-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2013-05-59
10	Coaxial cable	SGS	N/A	SEL0189	2013-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2013-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
13	Band filter	Amindeon	82346	SEL0094	2013-05-17
14	Barometer	Chang Chun	DYM3	SEL0088	2013-05-24
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
16	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2013-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2013-05-17
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2013-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2013-06-04

RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2013-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2013-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2013-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2013-05-24
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2013-05-17
8	Band filter	amideon	82346	SEL0094	2013-05-17
9	POWER METER	R & S	NRVS	SEL0144	2013-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2013-05-17
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2013-10-24

Note: The calibration interval is one year, all the instruments are valid.




5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
EUT Antenna:	
	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.
	

5.2 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.249 and 15.209				
Test Method:	ANSI C63.10: 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit: (Spurious Emissions)	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	2400MHz-2483.5MHz		94.0	Average Value	
			114.0	Peak Value	

Test Setup:

Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz

Figure 3. Above 1 GHz
Test Procedure:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the

	limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel h. The radiation measurements are performed in X, Y, Z axis positioning. And found the Z axis positioning which is worse case, Only the test worst case mode is recorded in the report. i. Repeat above procedures until all frequencies measured was complete.
Test Mode:	Transmitting mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

Measurement Data

5.2.1.1 Field Strength Of The Fundamental Signal

Peak value:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2406.600	2.99	32.54	39.86	74.49	70.16	114	-43.84	Horizontal
2406.900	2.99	32.54	39.86	73.96	69.63	114	-44.37	Vertical
2420.830	2.99	32.58	39.88	69.65	65.34	114	-48.66	Horizontal
2421.030	3.00	32.58	39.88	70.31	66.01	114	-47.99	Vertical
2445.160	3.01	32.61	39.89	72.45	68.18	114	-45.82	Horizontal
2445.160	3.01	32.61	39.89	72.48	68.21	114	-45.79	Vertical

Remark:

As shown in this section, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.


5.2.1.2 Spurious Emissions

30MHz~1GHz	
Test mode:	Transmitting

QP value:

Vertical

Data: 4



Condition: 47 CFR PART 15 B 3m 3142C NEW VERTICAL


Job No. : 1198RF

Mode : Transmitting

Freq	Cable		Antenna	Preamp	Read	Limit	Over	
	Loss	Factor	Factor	Level	Level			
MHz	dB	dB/m		dB	dBuV	dBuV/m	dBuV/m	dB
1	31.510	0.60	16.73	27.35	27.34	17.32	40.00	-22.68
2	60.492	0.80	4.98	27.27	30.45	8.96	40.00	-31.04
3	104.903	1.21	6.90	27.17	36.94	17.88	43.50	-25.62
4	153.200	1.32	9.47	26.89	29.87	13.77	43.50	-29.73
5	449.556	2.41	12.76	27.44	30.36	18.09	46.00	-27.91
6	972.337	3.67	21.20	26.44	32.61	31.04	54.00	-22.96

Horizontal

Data: 3



Condition: 47 CFR PART 15 B 3m 3142C NEW HORIZONTAL

Job No. : 1198RF

Mode : Transmitting

Freq	Cable	Antenna	Preamp	Read	Limit	Over	Limit
	Loss	Factor	Factor	Level	Level	Line	
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	30.853	0.60	17.23	27.35	27.58	18.06	40.00 -21.94
2	104.903	1.21	6.90	27.17	31.28	12.22	43.50 -31.28
3	163.182	1.34	9.50	26.85	30.91	14.90	43.50 -28.60
4	287.990	1.85	9.27	26.43	30.21	14.90	46.00 -31.10
5	517.248	2.62	13.97	27.67	29.67	18.59	46.00 -27.41
6	948.761	3.65	21.40	26.54	32.62	31.13	46.00 -14.87

Above 1GHz								
Test mode:		Transmitting	Test channel:	Lowest	Remark:		Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2008.676	2.84	31.80	39.57	46.88	41.95	74	-32.05	Vertical
3588.939	3.81	33.30	40.73	47.91	44.29	74	-29.71	Vertical
5448.410	4.94	34.85	41.40	47.83	46.22	74	-27.78	Vertical
6747.341	5.32	36.06	40.28	48.03	49.13	74	-24.87	Vertical
8271.294	6.19	36.11	38.95	47.13	50.48	74	-23.52	Vertical
10916.260	6.20	38.47	37.83	44.74	51.58	74	-22.42	Vertical
1913.838	2.78	31.18	39.53	49.77	44.20	74	-29.80	Horizontal
3598.087	3.82	33.32	40.74	48.17	44.57	74	-29.43	Horizontal
4594.102	4.55	35.06	41.47	48.55	46.69	74	-27.31	Horizontal
6347.466	5.22	36.12	40.63	48.60	49.31	74	-24.69	Horizontal
8549.586	6.18	36.24	38.72	46.53	50.23	74	-23.77	Horizontal
10999.950	6.22	38.50	37.86	45.42	52.28	74	-21.72	Horizontal

Test mode:		Transmitting	Test channel:	Middle		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1913.838	2.78	31.18	39.53	45.33	39.76	74	-34.24	Vertical
4223.950	4.31	34.45	41.21	48.90	46.45	74	-27.55	Vertical
5674.896	5.01	35.18	41.20	49.04	48.03	74	-25.97	Vertical
7319.964	5.92	35.93	39.77	46.85	48.93	74	-25.07	Vertical
8527.851	6.18	36.23	38.73	47.14	50.82	74	-23.18	Vertical
11169.240	6.26	38.47	37.93	44.67	51.47	74	-22.53	Vertical
1993.395	2.84	31.68	39.56	47.07	42.03	74	-31.97	Horizontal
3489.840	3.73	33.21	40.66	47.69	43.97	74	-30.03	Horizontal
5925.863	5.10	35.59	40.99	48.63	48.33	74	-25.67	Horizontal
7470.558	6.08	35.99	39.64	48.25	50.68	74	-23.32	Horizontal
9734.779	5.98	37.44	37.68	45.27	51.01	74	-22.99	Horizontal
11545.040	6.35	38.43	38.09	46.15	52.84	74	-21.16	Horizontal



Test mode:	Transmitting		Test channel:		Highest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2008.676	2.84	31.80	39.57	47.30	42.37	74	-31.63	Vertical
3824.757	4.01	33.59	40.91	48.68	45.37	74	-28.63	Vertical
5674.896	5.01	35.18	41.20	48.68	47.67	74	-26.33	Vertical
7643.683	6.23	36.00	39.49	47.53	50.27	74	-23.73	Vertical
9636.161	5.99	37.34	37.76	45.17	50.74	74	-23.26	Vertical
10614.840	6.13	38.35	37.70	44.63	51.41	74	-22.59	Vertical
1759.638	2.69	30.07	39.46	47.77	41.07	74	-32.93	Horizontal
3445.704	3.69	33.22	40.63	46.49	42.77	74	-31.23	Horizontal
4700.566	4.62	34.87	41.56	47.62	45.55	74	-28.45	Horizontal
6611.326	5.28	36.20	40.40	49.08	50.16	74	-23.84	Horizontal
7643.683	6.23	36.00	39.49	47.11	49.85	74	-24.15	Horizontal
10916.260	6.20	38.47	37.83	44.64	51.48	74	-22.52	Horizontal

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$
- 2) The EUT was tested from 9kHz to 25GHz, the disturbance above 12GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

5.3 Band Edge (Radiated Emission)

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205	
Test Method:	ANSI C63.10: 2009	
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)	
Limit(band edge):	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.	
Frequency	Limit (dBuV/m @3m)	Remark
30MHz-88MHz	40.0	Quasi-peak Value
88MHz-216MHz	43.5	Quasi-peak Value
216MHz-960MHz	46.0	Quasi-peak Value
960MHz-1GHz	54.0	Quasi-peak Value
Above 1GHz	54.0	Average Value
	74.0	Peak Value

Test Setup:




Figure 1. 30MHz to 1GHz





Figure 2. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none">a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channelg. Test the EUT in the lowest channel , the Highest channelh. The radiation measurements are performed in X, Y, Z axis positioning. And found the Z axis positioning which it is worse case, Only the test worst case mode is recorded in the report.i. Repeat above procedures until all frequencies measured was complete.
Test Mode :	Transmitting mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

Test plot as follows:

Test mode:	Transmitting	Test channel:	Lowest	Remark:	Peak	Vertical
------------	--------------	---------------	--------	---------	------	----------




Condition : FCC PART15.249 2.4PK 3m VERTICAL

Job No. : 1198RF

Mode : 2406.52MHz Bandedge

	Freq	Cable			Antenna		Preamp	Read	Limit	Over
		Loss	Factor	Factor				Level		
	MHz	dB	dB/m			dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	2.98	32.51	39.85	46.29	41.93	74.00	74.00	-32.07	
2	2400.000	2.98	32.51	39.86	46.95	42.58	74.00	74.00	-31.42	
3	2406.600	2.99	32.54	39.86	74.49	70.16	114.00	114.00	-43.84	

Test mode:	Transmitting	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	--------------	---------------	--------	---------	------	------------




Condition : FCC PART15.249 2.4PK 3m HORIZONTAL

Job No. : 1198RF

Mode : 2406.52MHz Bandedge

	Freq	Cable			Antenna		Preamp	Read	Limit	Line	Over
		Loss	Factor	Factor	Level	Level					
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB			
1	2390.000	2.98	32.51	39.85	47.52	43.17	74.00	-30.83			
2	2400.000	2.98	32.51	39.86	47.54	43.18	74.00	-30.82			
3	2406.900	2.99	32.54	39.86	73.95	69.63	114.00	-44.37			

Test mode:	Transmitting	Test channel:	Highest	Remark:	Peak	Vertical
------------	--------------	---------------	---------	---------	------	----------




Condition : FCC PART15.249 2.4PK 3m VERTICAL

Job No. : 1198RF

Mode : 2445MHz Bandedge

	Cable	Antenna	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m
1	2445.160	3.01	32.61	39.89	72.49	68.21	114.00
2	2483.500	3.03	32.67	39.92	46.05	41.83	74.00
0							-45.79
							-32.17

Test mode:	Transmitting	Test channel:	Highest	Remark:	Peak	Horizontal
------------	--------------	---------------	---------	---------	------	------------



Condition : FCC PART15.249 2.4PK 3m HORIZONTAL

Job No. : 1198RF

Mode : 2445MHz Bandedge

	Freq	Cable		Antenna		Preamp	Read	Limit	Line	Over
		Loss	Factor	Factor	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m			dB
1	2445.160	3.01	32.61	39.89	72.45	68.18	114.00	-45.82		
2	2483.500	3.03	32.67	39.92	45.92	41.70	74.00	-32.30		

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation


with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

5.4 20dB Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.215
Test Method:	ANSI C63.10:2009
Test Setup:	
Limit:	N/A
Test Mode:	Transmitting mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

Measurement Data


Test Channel	20dB bandwidth (MHz)	Results
Lowest	0.920	Pass
Middle	0.932	Pass
Highest	0.908	Pass

Test plot as follows:

Test channel:	Lowest
---------------	--------



Test channel:	Middle
---------------	--------



Test channel:	Highest
---------------	---------

