

Report No: GTSE11110092702

TEST REPORT

Applicant: CARRIN ELECTRONICS COMPANY LIMITED

Address of Applicant: UNIT 2105~2106, TOWER A, REGENT CENTRE, 63 WO YI HOP RD, KWAI CHUNG, HONG KONG

Equipment Under Test (EUT)

Product Name: WEATHER STATION

Model No.: KW9007, 47022RX, 47023RX

FCC ID: X6I-9007

Applicable standards: FCC CFR Title 47 Part 15 Subpart B:2010

Date of sample receipt: Nov. 18, 2011

Date of Test: Nov. 18-22, 2011

Date of report issued: Nov. 23, 2011

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Stephen Guo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Version No.	Date	Description
00	Nov. 23, 2011	Original

Prepared by:

Collin. He

Date:

Nov. 23, 2011

Project Engineer

Reviewed by:

Hans. Hu

Date:

Nov. 23, 2011

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T	5
5.3 TEST MODE AND VOLTAGE	5
5.4 TEST FACILITY	5
5.5 TEST LOCATION	6
5.6 DESCRIPTION OF SUPPORT UNITS	6
5.7 DEVIATION FROM STANDARDS	6
5.8 ABNORMALITIES FROM STANDARD CONDITIONS	6
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
6 TEST INSTRUMENTS LIST	7
7 TEST RESULTS AND MEASUREMENT DATA	8
7.1 RADIATED EMISSION	8
8 TEST SETUP PHOTO	14
9 EUT CONSTRUCTIONAL DETAILS	15

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	N/A
Radiated Emissions	Part15.109	PASS

PASS: The EUT complies with the essential requirements in the standard.

N/A: not applicable.

5 General Information

5.1 Client Information

Applicant:	CARRIN ELECTRONICS COMPANY LIMITED
Address of Applicant:	UNIT 2105~2106, TOWER A, REGENT CENTRE, 63 WO YI HOP RD, KWAI CHUNG, HONG KONG
Manufacturer/Factory:	CARRIN ELECTRONICS COMPANY LIMITED
Address of Manufacturer/ Factory:	UNIT 2105~2106, TOWER A, REGENT CENTRE, 63 WO YI HOP RD, KWAI CHUNG, HONG KONG

5.2 General Description of E.U.T.

Product Name:	WEATHER STATION
Model No.:	KW9007, 47022RX, 47023RX
Power supply:	DC 4.5V (3x1.5 "AA" Size)
Remark:	<p>1. Only the model KW9007 was tested.</p> <p>KW9007, 47022RX, 47023RX are identical in the same PCB layout, interior structure and electrical circuits. The only differences are the model name and appearance color for commercial purpose.</p> <p>2. The test battery is new battery.</p>

5.3 Test mode and voltage

Test mode:	
Receiver mode	Keep the EUT in receiver mode
Remark:	Signal generators transmit an unmodulated carrier on the receiver frequency from an antenna in the proximity of the receiver. Care was taken to avoid overload of the receiver, vary the amplitude and frequency of the stabilizing signal to obtain the highest level of the spurious emissions from the receiver.

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, July 20, 2010.

● **Industry Canada (IC)**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-1.

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

5.6 Description of Support Units

None.

5.7 Deviation from Standards

Biconical, log.per. antenna and horn antenna were used instead of dipole antenna.

Semi-anechoic Chamber was used as alternation of open air test sites, and all test suites were performed with radiated method in it.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.



6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 30 2011	Mar. 29 2012
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 04 2011	Jul. 03 2012
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Feb. 26 2011	Feb. 25 2012
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 30 2011	June 29 2012
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 30 2011	Mar. 29 2012
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	Apr. 01 2011	Mar. 31 2012
9	Coaxial Cable	GTS	N/A	GTS211	Apr. 01 2011	Mar. 31 2012
9	Coaxial cable	GTS	N/A	GTS210	Apr. 01 2011	Mar. 31 2012
11	Coaxial Cable	GTS	N/A	GTS212	Apr. 01 2011	Mar. 31 2012
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 04 2011	Jul. 03 2012
13	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 04 2011	Jul. 03 2012
14	Pre-amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 30 2011	June 29 2012
15	Band filter	Amindeon	82346	GTS219	June 30 2011	June 29 2012
16	Signal generator	Rohde & Schwarz	1090.3000.12	GTS330	June 30 2011	June 29 2012

7 Test results and Measurement Data

7.1 Radiated Emission

Test Requirement:	FCC Part15 B Section 15.109																								
Test Method:	ANSI C63.4:2003																								
Test Frequency Range:	30MHz to 2GHz																								
Class / Severity:	Class B																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table border="1"> <thead> <tr> <th>Frequency</th><th>Detector</th><th>RBW</th><th>VBW</th><th>Remark</th></tr> </thead> <tbody> <tr> <td>30MHz-1GHz</td><td>Quasi-peak</td><td>100KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr> <tr> <td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr> <tr> <td>Peak</td><td>1MHz</td><td>3MHz</td><td>Average Value</td></tr> </tbody> </table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	3MHz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	Peak	1MHz	3MHz	Average Value																					
Limit:	<table border="1"> <thead> <tr> <th>Frequency</th><th>Limit (dBuV/m @3m)</th><th>Remark</th></tr> </thead> <tbody> <tr> <td>30MHz-88MHz</td><td>40.00</td><td>Quasi-peak Value</td></tr> <tr> <td>88MHz-216MHz</td><td>43.50</td><td>Quasi-peak Value</td></tr> <tr> <td>216MHz-960MHz</td><td>46.00</td><td>Quasi-peak Value</td></tr> <tr> <td>960MHz-1GHz</td><td>54.00</td><td>Quasi-peak Value</td></tr> <tr> <td rowspan="2">Above 1GHz</td><td>54.00</td><td>Average Value</td></tr> <tr> <td>74.00</td><td>Peak Value</td></tr> </tbody> </table>					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.00	Quasi-peak Value	88MHz-216MHz	43.50	Quasi-peak Value	216MHz-960MHz	46.00	Quasi-peak Value	960MHz-1GHz	54.00	Quasi-peak Value	Above 1GHz	54.00	Average Value	74.00	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.00	Quasi-peak Value																							
88MHz-216MHz	43.50	Quasi-peak Value																							
216MHz-960MHz	46.00	Quasi-peak Value																							
960MHz-1GHz	54.00	Quasi-peak Value																							
Above 1GHz	54.00	Average Value																							
	74.00	Peak Value																							
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 																								

Test setup:	Below 1GHz
	
	Above 1GHz
	
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1 012mbar
Measurement Record:	Uncertainty: $\pm 4.5\text{dB}$
Test Instruments:	Refer to section 6 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Note:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$

Measurement Data

Below 1 G:

Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163 HORIZONTAL


Job No. : 927RF

Test mode : Receiving mode

Test Engineer: Aarons

Freq	ReadAntenna		Cable		Preamp Loss Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	Level Factor	dB					
1	37.94	36.53	13.06	0.25	32.16	17.68	40.00	-22.32	QP
2	51.12	36.39	13.21	0.32	32.01	17.91	40.00	-22.09	QP
3	96.44	36.28	12.94	0.47	31.71	17.98	43.50	-25.52	QP
4	218.31	36.62	11.13	0.78	32.28	16.25	46.00	-29.75	QP
5	435.59	37.19	15.54	1.33	32.07	21.99	46.00	-24.01	QP
6	766.06	35.62	19.63	2.00	31.56	25.69	46.00	-20.31	QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163 VERTICAL
 Job No. : 927RF
 Test mode : Receiving mode
 Test Engineer: Aarons

Freq	ReadAntenna		Cable Preamp		Limit Level	Over Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB				
1	43.05	36.77	13.56	0.28	32.12	18.49	40.00	-21.51 QP
2	97.11	36.18	12.97	0.47	31.71	17.91	43.50	-25.59 QP
3	185.14	36.43	10.16	0.68	32.18	15.09	43.50	-28.41 QP
4	362.98	37.89	14.45	1.19	32.31	21.22	46.00	-24.78 QP
5	597.22	36.29	18.40	1.67	31.30	25.06	46.00	-20.94 QP
6	962.16	36.08	21.49	2.23	31.50	28.30	54.00	-25.70 QP

Above 1 G:


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120 (>1GHZ) HORIZONTAL
 Job No. : 927RF
 Test mode : Receiving mode
 Test Engineer: Aarons

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	
1	1017.00	53.13	24.44	2.32	34.51	45.38	74.00 -28.62 Peak
2	1017.00	44.37	24.44	2.32	34.51	36.62	54.00 -17.38 Average
3	1194.00	47.44	24.88	2.59	34.55	40.36	74.00 -33.64 Peak
4	1194.00	39.13	24.88	2.59	34.55	32.05	54.00 -21.95 Average
5	1377.00	46.06	25.50	2.84	34.59	39.81	74.00 -34.19 Peak
6	1377.00	37.82	25.50	2.84	34.59	31.57	54.00 -22.43 Average
7	1581.00	44.24	25.02	3.08	34.63	37.71	74.00 -36.29 Peak
8	1581.00	35.17	25.02	3.08	34.63	28.64	54.00 -25.36 Average
9	1741.00	45.27	25.04	3.26	34.66	38.91	74.00 -35.09 Peak
10	1741.00	37.28	25.04	3.26	34.66	30.92	54.00 -23.08 Average
11	1931.00	45.30	25.87	3.44	34.69	39.92	74.00 -34.08 Peak
12	1931.00	36.81	25.87	3.44	34.69	31.43	54.00 -22.57 Average

Vertical:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(>1GHZ) VERTICAL
 Job No. : 927RF
 Test mode : Receiving mode
 Test Engineer: Aarons

Freq	ReadAntenna		Cable		Preamp	Limit	Over	Remark
	Level	Factor	Loss	Factor				
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1017.00	54.37	24.44	2.32	34.51	46.62	74.00	-27.38 Peak
2	1017.00	45.38	24.44	2.32	34.51	37.63	54.00	-16.37 Average
3	1173.00	48.28	24.75	2.57	34.55	41.05	74.00	-32.95 Peak
4	1173.00	40.13	24.75	2.57	34.55	32.90	54.00	-21.10 Average
5	1329.00	46.27	25.65	2.78	34.58	40.12	74.00	-33.88 Peak
6	1329.00	37.81	25.65	2.78	34.58	31.66	54.00	-22.34 Average
7	1583.00	43.95	25.02	3.10	34.63	37.44	74.00	-36.56 Peak
8	1583.00	34.28	25.02	3.10	34.63	27.77	54.00	-26.23 Average
9	1768.00	45.56	25.17	3.29	34.66	39.36	74.00	-34.64 Peak
10	1768.00	37.20	25.17	3.29	34.66	31.00	54.00	-23.00 Average
11	1927.00	45.47	25.87	3.44	34.69	40.09	74.00	-33.91 Peak
12	1927.00	36.57	25.87	3.44	34.69	31.19	54.00	-22.81 Average