



Nemko Test Report: 1024712RUS1 Rev 1

Applicant: Biscotti, Inc.
700 Central Expressway South
Suite 240
Allen, TX 75013
USA

Equipment Under Test: BIS100
(E.U.T.)

In Accordance With: FCC Part 15, Subpart C, 15.247 &
Industry Canada, RSS-210, Issue 8
Digital Transmission Systems

Tested By: Nemko USA, Inc.
802 N. Kealy
Lewisville, Texas 75057-3136

TESTED BY: 

David Light, Senior Wireless Engineer

DATE: 17-Oct-2011

APPROVED BY: 

Mike Cantwell, GM

DATE: 18-Oct-2011

Number of Pages: 67

Table of Contents

SECTION 1. SUMMARY OF TEST RESULTS	3
SECTION 2. EQUIPMENT UNDER TEST (E.U.T.)	5
SECTION 3. OCCUPIED BANDWIDTH	6
SECTION 4. MAXIMUM PEAK OUTPUT POWER	19
SECTION 5. SPURIOUS EMISSIONS AT ANTENNA TERMINALS	29
SECTION 6. RADIATED EMISSIONS	42
SECTION 7. PEAK POWER SPECTRAL DENSITY	44
SECTION 8. POWERLINE CONDUCTED EMISSIONS	48
SECTION 9. TEST EQUIPMENT LIST	56
ANNEX A - TEST DETAILS	57
ANNEX B - TEST DIAGRAMS	65

Section 1. Summary of Test Results

Manufacturer: Biscotti, Inc.

Model No.: BIS100

Model Name: Biscotti

Serial No.: None

General: **All measurements are traceable to national standards.**

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, Subpart C, Paragraph 15.247 and Industry Canada RSS-210, Issue 8 for Digital Transmission Systems. Radiated tests were conducted in accordance with ANSI C63.4-2003. Radiated emissions are made on an open area test site. A description of the test facility is on file with the FCC and Industry Canada.



New Submission



Production Unit



Class II Permissive Change



Pre-Production Unit

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.**THE FOLLOWING DEVIATIONS FROM, ADDITIONS TO, OR EXCLUSIONS FROM THE TEST SPECIFICATIONS HAVE BEEN MADE.**

See "Summary of Test Data".



NVLAP Lab Code 100426-0

Nemko USA, Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety, for use by the company's employees only.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. Nemko USA, Inc. is a NVLAP accredited laboratory.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko USA, Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Summary Of Test Data

NAME OF TEST	PARA. NO.	RESULT
Powerline Conducted Emissions	15.207(a) / RSS-Gen 7.2.4	Complies
Minimum 6 dB Bandwidth	15.247(a)(2) / A8.2	Complies
Maximum Peak Power Output	15.247(b)(3) / A8.4(4)	Complies
Spurious Emissions (Antenna Conducted)	15.247(d) / A8.5	Complies
Spurious Emissions (Restricted Bands)	15.247(d)/15.209(a) / RSS-Gen 7.2.2	Complies
Peak Power Spectral Density	15.247(e) / A8.2(b)	Complies
Receiver Spurious Emissions	RSS-Gen 6.1	Not tested*

Footnotes:

Please refer to separate exhibit for receiver spurious emission data.

This report updated to include 802.11n.

Section 2. Equipment Under Test (E.U.T.)**General Equipment Information**

Frequency Band (MHz): 902-928 2400-2483.5 5725-5850

Operating Frequency of Test Sample: 2412 to 2462 MHz

Channel Spacing: 5 MHz


User Frequency Adjustment: Software controlled

Section 3. Occupied Bandwidth


NAME OF TEST: Occupied Bandwidth	PARA. NO.: 15.247(a)(2)
TESTED BY: David Light	DATE: 27 April 2011 14 October 2011

Test Results: Complies.**Measurement Data:** See 6 dB BW plot
Measured 6 dB bandwidth: 16.4 MHz max
Channel Separation: 5 MHz**Test Conditions:** 45%RH
23°C**Measurement Uncertainty:** $\pm 1 \times 10^{-7}$ ppm**Test Equipment Used:** 1767-1082-1469

Test Data – Occupied Bandwidth




Test Data – Occupied Bandwidth




Date: 27.APR.2011 12:00:23

Test Data – Occupied Bandwidth

High Channel
b Mode


Date: 27.APR.2011 11:59:16

Test Data – Occupied Bandwidth




Date: 27.APR.2011 12:02:35

Test Data – Occupied Bandwidth


Low Channel
g Mode

Test Data – Occupied Bandwidth




Date: 27.APR.2011 08:22:52

Test Data – Occupied Bandwidth




Date: 27.APR.2011 08:21:49

Test Data – Occupied Bandwidth




Test Data – Occupied Bandwidth

Low Channel
n Mode


Date: 14.OCT.2011 13:15:48

Test Data – Occupied Bandwidth




Date: 14.OCT.2011 13:20:46

Test Data – Occupied Bandwidth

High Channel
n Mode

Date: 14.OCT.2011 13:26:46

Test Data – Occupied Bandwidth



Section 4. Maximum Peak Output Power

NAME OF TEST: Maximum Peak Output power	PARA. NO.: 15.247(b)(3)
TESTED BY: David Light	DATE: 27 April 2011 14 October 2011

Test Results: Complies.**Measurement Data:** Refer to attached data**Test Conditions:** 45%RH
22°C**Measurement Uncertainty:** +/-1.7 dB**Test Equipment Used:** 1767-1082-1469-1472

- This device was tested at +/- 15% input power per 15.31(e), with no variation in output power.
- For battery powered equipment, the device was tested with a fresh battery per 15.31(e).
- The device was tested on three channels per 15.31(l).
- This test was performed radiated.


Detector: Peak

Note: The EUT was set at power level 18 for all channels except highest (channel 11). Power must be lowered to 15 at the highest channel to comply with upper band edge requirements.

Test Data – Peak Power


Low Channel

802.11b



Date: 27.APR.2011 12:05:58

Test Data – Peak Power




Date: 27.APR.2011 12:06:38


Test Data – Peak Power

High Channel


802.11b



Test Data – Peak Power




Test Data – Peak Power



Test Data – Peak Power

High Channel


802.11g



Test Data – Peak Power


Low Channel

802.11n



Date: 14.OCT.2011 13:18:11


Test Data – Peak Power



Test Data – Peak Power

High Channel

802.11n



Section 5 Spurious Emissions at Antenna Terminals


NAME OF TEST: Spurious Emissions at Antenna Terminals PARA. NO.: 15.247 (d)

TESTED BY: David Light

DATE: 27 April 2011

14 October 2011


Test Results: Complies.**Measurement Data:** See attached plots.**Test Conditions:** 45%RH
22°C**Measurement Uncertainty:** +/-1.7 dB**Test Equipment Used:** 1767-1082-1469

Test Data – Spurious Emissions at Antenna Terminals**Lower Band Edge****802.11b**

Date: 27.APR.2011 12:03:42

Test Data – Spurious Emissions at Antenna Terminals


802.11b



Date: 27.APR.2011 12:10:47

Test Data – Spurious Emissions at Antenna Terminals


802.11b



Date: 27.APR.2011 12:09:30

Test Data – Spurious Emissions at Antenna Terminals

802.11b




Date: 27.APR.2011 12:08:27

Test Data – Spurious Emissions at Antenna Terminals

Lower Band Edge


802.11g



Date: 27.APR.2011 08:26:33

Test Data – Spurious Emissions at Antenna Terminals


802.11g



Date: 27.APR.2011 08:37:57

Test Data – Spurious Emissions at Antenna Terminals


802.11g



Date: 27.APR.2011 08:36:58

Test Data – Spurious Emissions at Antenna Terminals

802.11g




Date: 27.APR.2011 08:35:24

Test Data – Spurious Emissions at Antenna Terminals

Lower Band Edge

802.11n




Date: 14.OCT.2011 13:17:24

Test Data – Spurious Emissions at Antenna Terminals

Low Channel

802.11n




Date: 14.OCT.2011 07:38:20

Test Data – Spurious Emissions at Antenna Terminals

Mid Channel

802.11n




Date: 14.OCT.2011 08:55:31

Test Data – Spurious Emissions at Antenna Terminals

Highest Channel

802.11n



Date: 14.OCT.2011 10:00:38

Section 6. Radiated Emissions

NAME OF TEST: Radiated Emissions	PARA. NO.: 15.247 (d)
TESTED BY: David Light	DATE: 27 April 2011 14 October 2011

Test Results: Complies.**Measurement Data:** See attached table.**Test Conditions:** 45 %RH
22 °C**Measurement Uncertainty:** +/-1.7 dB**Test Equipment Used:** 1464-1484-1485-791-1016-1480-993**Notes:**

- For handheld devices, the EUT was tested on three orthogonal axis'
- The device was tested from 30 MHz to the tenth harmonic of the highest fundamental frequency per 15.33
- The device was tested on three channels per 15.31(l).
- No emissions were detected within 20 dB of the specification limit therefore none are reported per 15.31(o). Band edge data is presented below.

RBW=VBW=100 kHz below 1000 MHz

RBW=VBW=1 MHz above 1000 MHz (Peak)

RBW= 1 MHz VBW=10Hz (Average)

Radiated Emissions**802.11b**

Meas. Freq. (MHz)	Ant. Pol. (H/V)	Duty Cycle (dB)	Meter Reading (dBuV)	Antenna Factor (dB)	Path Loss (dB)	RF Gain (dB)	Corrected Reading (dBuV/m)	Spec. limit (dBuV/m)	CR/SL Diff. (dB)	Pass Fail	Unc.	Comment
												Ch11 11 Mbps
2483.5	V	0	52.5	29	3.1	31.8	52.8	74.0	-21.2	Pass		Power level 15
2483.5	V	-6.2	52.5	29	3.1	31.8	46.6	54.0	-7.4	Pass		
2483.5	H	0	56	29	3.1	31.8	56.3	74.0	-17.7	Pass		
2483.5	H	-6.2	56	29	3.1	31.8	50.1	54.0	-3.9	Pass		

802.11g

												Ch11 54 Mbps
2483.5	V	0	64.3	29	3.1	31.8	64.6	74.0	-9.4	Pass		Power level 15
2483.5	V	-15.4	64.3	29	3.1	31.8	49.2	54.0	-4.8	Pass		
2483.5	H	0	66.6	29	3.1	31.8	66.9	74.0	-7.1	Pass		
2483.5	H	-15.4	66.6	29	3.1	31.8	51.5	54.0	-2.5	Pass		

802.11n

												Ch11 65 Mbps
2483.5	V	0	59.3	29	3.1	31.8	59.6	74.0	-14.4	Pass		Power level 15
2483.5	V	-15.6	59.3	29	3.1	31.8	44.0	54.0	-10.0	Pass		
2483.5	H	0	63.6	29	3.1	31.8	63.9	74.0	-10.1	Pass		
2483.5	H	-15.6	63.6	29	3.1	31.8	48.3	54.0	-5.7	Pass		

Corrected reading=Meter reading+AF+Path Loss+Duty Cycle-RF Gain

Nemko USA, Inc.

EQUIPMENT: BIS100

FCC PART 15, SUBPART C & RSS-210

Digital Transmission Systems

Test Report No.: 1024712RUS1 Rev 1

Section 7. Peak Power Spectral Density

NAME OF TEST: Peak Power Spectral Density	PARA. NO.: 15.247(e)
---	----------------------

TESTED BY: David Light	DATE: 27 April 2011 14 October 2011
------------------------	--

Test Results: Complies.

Measurement Data: See attached data..

Test Conditions: 45 %RH
22 °C


Measurement Uncertainty: +/-1.7 dB

Test Equipment Used: 1767-1082-1469

Peak Power Spectral Density

Low Channel

802.11b




Date: 27.APR.2011 12:42:07

Peak Power Spectral Density

Mid Channel

802.11b




Date: 27.APR.2011 13:12:48

Peak Power Spectral Density

High Channel

802.11b




Date: 27.APR.2011 13:58:44

Peak Power Spectral Density

Low Channel

802.11g




Date: 27.APR.2011 09:30:13

Peak Power Spectral Density

Mid Channel

802.11g




Date: 27.APR.2011 10:16:01

Peak Power Spectral Density

High Channel


802.11g



Peak Power Spectral Density

Low Channel

802.11n




Date: 14.OCT.2011 08:49:45

Peak Power Spectral Density

Mid Channel

802.11n




Date: 14.OCT.2011 09:54:21

Peak Power Spectral Density

High Channel

802.11n



Date: 14.OCT.2011 11:23:22

Nemko USA, Inc.

EQUIPMENT: BIS100

FCC PART 15, SUBPART C & RSS-210

Digital Transmission Systems

Test Report No.: 1024712RUS1 Rev 1

Section 8. Powerline Conducted Emissions

NAME OF TEST: Powerline Conducted Emissions	PARA. NO.: 15.207(a)
TESTED BY: Brian Boyea	DATE: 25 April 2011

Test Results: Complies.

Measurement Data: See attached tables.

Measurement Uncertainty: +/- 1.7 dB

Test Equipment Used: 644-704-1258-1663-1988-1548

Test Data – Powerline Conducted Emissions

Line 1

Frequency MHz	FCCB QP LIMIT	FCCB AVG LIMIT	AVG Meas	AVG Margin	QP Meas	QP Margin
11.20	60.0	50.0	40.4	-9.6	50.3	-9.7
11.70	60.0	50.0	38.7	-11.3	49.9	-10.1
14.51	60.0	50.0	43.7	-6.3	51.8	-8.2
14.61	60.0	50.0	44.1	-5.9	51.7	-8.3
14.62	60.0	50.0	44.0	-6.0	51.3	-8.7
15.21	60.0	50.0	43.3	-6.7	51.8	-8.2
15.22	60.0	50.0	43.3	-6.7	51.4	-8.6
15.52	60.0	50.0	42.5	-7.5	50.7	-9.3
15.52	60.0	50.0	42.8	-7.2	51.0	-9.0
15.82	60.0	50.0	43.0	-7.0	51.0	-9.0

Line 2

Frequency MHz	FCCB QP Limit	FCCB AVG Limit	AVG Meas	AVG Margin	QP Meas	QP Margin
11.29	60.0	50.0	41.0	-9.0	50.3	-9.7
11.62	60.0	50.0	38.9	-11.1	49.9	-10.1
11.70	60.0	50.0	39.4	-10.6	49.3	-10.7
14.41	60.0	50.0	44.0	-6.0	50.9	-9.1
14.61	60.0	50.0	44.4	-5.6	51.2	-8.8
14.62	60.0	50.0	44.4	-5.6	51.1	-8.9
15.42	60.0	50.0	43.0	-7.0	50.8	-9.2
15.82	60.0	50.0	43.1	-6.9	50.6	-9.4
16.12	60.0	50.0	42.5	-7.5	50.5	-9.5
16.20	60.0	50.0	42.6	-7.4	50.8	-9.2

Section 9. Test Equipment List

Asset Tag	Description	Manufacturer	Model	Serial #	Last Cal	Next Cal
674	Limiter	Hewlett Packard	11947A	3107A02200	26-Oct-2010	26-Oct-2011
704	Filter, High Pass, 5KHz	Solar Electronics	7930-5.0	933126	29-Sep-2010	29-Sep-2011
993	Antenna, Horn	A.H. Systems	SAS-200/571	162	09-Sep-2009	09-Sep-2011
1016	Preamplifier	Hewlett Packard	8449A	2749A00159	19-Jun-2010	19-Jun-2011
1082	Cable, 2m	Astrolab	32027-2-29094-72TC		Verify B4 Use	
1258	LISN .15mhz-30mhz	EMCO	3825/2	1305	25-Oct-2010	25-Oct-2011
1464	Spectrum Analyzer	Hewlett Packard	8563E	3551A04428	16-May-2011	16-May-2013
1469	Attenuator, 10 db	MCL Inc.	BW-S10W2 10db-2WDC		Verify B4 Use	
1484	Cable	Storm	PR90-010-072		19-Jun-2010	19-Jun-2011
1485	Cable	Storm	PR90-010-216		19-Jun-2010	19-Jun-2011
1663	Spectrum Analyzer	Rohde & Schwartz	FSP3	100073	23-Aug-2010	23-Aug-2011
1767	Receiver,	Rohde & Schwartz	ESIB26	837491/0002	01-Dec-2010	01-Dec-2011
1988	Cable, Coaxial	Nemko USA, Inc.			03-Nov-2010	03-Nov-2011
791	30MHz to 1GHz Pre Amplifier	Nemko, USA	CRA69 321003 9605	119	19-May-2011	19-May-2012
1548	0.5m Cable Assy	Nemko USA	RG213		01-Oct-2010	01-Oct-2011
1472	20 dB Attenuator	MCL Inc.	BW-S202 20 dB-2WDC		Verify B4 Use	

Nemko USA, Inc.

EQUIPMENT: BIS100

FCC PART 15, SUBPART C & RSS-210

Digital Transmission Systems

Test Report No.: 1024712RUS1 Rev 1

ANNEX A - TEST DETAILS

NAME OF TEST: Powerline Conducted Emissions

PARA. NO.: 15.207(a)

Minimum Standard: §15.207 Conducted limits.

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 mH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of Conducted Emission (MHz)	Limit (dBmV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current systems containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 mV within the frequency band 535-1705 kHz, as measured using a 50 mH/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits as provided in §15.205 and §§15.209, 15.221, 15.223, 15.225 or 15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provision for, the use of battery chargers which permit operating while charging, AC adaptors or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

Nemko USA, Inc.

EQUIPMENT: BIS100

FCC PART 15, SUBPART C & RSS-210

Digital Transmission Systems

Test Report No.: 1024712RUS1 Rev 1

NAME OF TEST: Occupied Bandwidth	PARA. NO.: 15.247(a)(2)
----------------------------------	-------------------------

Minimum Standard: The minimum 6 dB bandwidth shall be at least 500 kHz

NAME OF TEST: Maximum Peak Output Power

PARA. NO.: 15.247(b)(3)

Minimum Standard: The maximum peak output power shall not exceed 1 watt.

If transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point to point operation may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceed 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operation may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.

Direct Measurement Method For Detachable Antennas:

If the antenna is detachable, a peak power meter is used to measure the power output with the transmitter operating into a 50 ohm load. The dBi gain of the antenna(s) employed shall be reported.

Substitution Antenna Method for Integral Antennas:

The peak field strength of the carrier is measured in a worst-case configuration with a RBW > 5 times the occupied bandwidth of the transmitted waveform. For cases where the RBW of the test instrument is not sufficient, the power is measured using a peak power meter instead of the spectrum analyzer.

The RBW of the spectrum analyzer shall be set to a value greater than the measured 6 dB occupied bandwidth of the E.U.T.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Occupied Bandwidth

PARA. NO.: 15.247(a)(2)

Minimum Standard: Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Method Of Measurement:

The spectrum analyzer is set as follows:

RBW = VBW = 100 kHz.

Span: Sufficient to display 6 dB bandwidth

LOG dB/div.: 10 dB

Sweep: Auto

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Spurious Emissions(conducted) PARA. NO.: 15.247(d)

Minimum Standard: In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits. Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (μ V/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM IS SEARCHED TO THE 10th HARMONIC OF THE HIGHEST FREQUENCY GENERATED IN THE EUT.

Method Of Measurement:

30 MHz - 10th harmonic plot

RBW: 100 kHz

VBW: 300 kHz

Sweep: Auto

Display line: -20 dBc

Lower Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 902 MHz, 2400 MHz, or 5725 MHz

Marker: Peak of fundamental emission

Marker Δ : Peak of highest spurious level below center frequency.

Upper Band Edge

RBW: At least 1% of span/div.

VBW: >RBW

Span: As necessary to display any spurious at band edge.

Sweep: Auto

Center Frequency: 928 MHz, 2483.5 MHz, or 5850 MHz

Marker: Peak of fundamental emission

Marker Δ : Peak of highest spurious level above center frequency.

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Radiated Spurious Emissions

PARA. NO.: 15.247(c)

Minimum Standard: In any 100kHz bandwidth outside the frequency band in which the transmitter is operating, emissions shall be at least 20 dB below the fundamental emission or shall not exceed the following field strength limits:

Emissions falling in the restricted bands of 15.205 shall not exceed the following field strength limits:

Frequency (MHz)	Field Strength (μ V/m @ 3m)	Field Strength (dB @ 3m)
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

THE SPECTRUM WAS SEARCHED TO THE 10th HARMONIC

15.205 Restricted Bands

MHz	MHz	MHz	GHz
0.09-0.11	16.42-16.423	399.9-410	4.5-5.25
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.125-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41	1718		

Number of channels tested:

Tuning range	Number of channels tested	Channel location in band
1 MHz or less	1	middle
1 to 10 MHz	2	top and bottom
more than 10 MHz	3	top, middle, bottom

NAME OF TEST: Transmitter Power Density

PARA. NO.: 15.247(d)

Minimum Standard: The transmitted power density averaged over any 1 second interval shall not be greater than +8 dBm in any 3 kHz bandwidth.

Method Of Measurement: The spectrum analyzer is set as follows:

RBW: 3 kHz
VBW: >3 kHz
Span: => measured 6 dB bandwidth
Sweep: Span(kHz)/3 (i.e. for a span of 1.5 MHz the sweep rate is 1500/3 = 500 sec.
LOG dB/div.: 2 dB

Note: For devices with spectrum line spacing =< 3 kHz, the RBW of the analyzer is reduced until the spectral lines are resolved. The measurement data is normalized to 3 kHz by summing the power of all the individual spectral lines within a 3 kHz band in linear power units.

For Devices With Integral Antenna:

For devices with non-detachable antennas, the received field strength is peaked and the spectrum analyzer is set as above. The peak emission level is then measured and converted to a field strength by adding the appropriate antenna factor and cable loss. This field strength is then converted to an equivalent isotropic radiated power using the same method as described for Peak Power output.

Number of channels tested:

Tuning Range	Number Of Channels Tested	Channel Location In Band
1 MHz or Less	1	Middle
1 to 10 MHz	2	Top And Bottom
More Than 10 MHz	3	Top, Middle, Bottom

Nemko USA, Inc.



EQUIPMENT: BIS100


FCC PART 15, SUBPART C & RSS-210

Digital Transmission Systems

Test Report No.: 1024712RUS1 Rev 1

ANNEX B - TEST DIAGRAMS

Test Site For Radiated Emissions**Conducted Emissions**

Peak Power At Antenna Terminals

Note: A spectrum analyzer may be substituted for Peak Power Meter given that the measurement bandwidth is sufficient to capture the 60 dB bandwidth of the transmitter.

**Minimum 6 dB Bandwidth
Peak Power Spectral Density
Spurious Emissions (conducted)**