

## FCC CFR 47 PART 15 SUBPART C(15.249)

FOR

Xuzhou Fly-Dream Electronic CO.,LTD.

2.4G transmitter system

Model No.: F6TB

Additional Model No.: F6TA, F6TB, K6T, PTR, K8T

Prepared for : Xuzhou Fly-Dream Electronic CO.,LTD.  
Address : Room6101,No.23,The North Of Beijing Road, Tongshan District,  
Xuzhou, Jiangsu, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd  
Address : 1F., Xingyuan Industrial Park, Tongda Road, Bao'an Blvd., Bao'an  
District, Shenzhen, Guangdong, China

Date of receipt of test sample : February 01, 2013  
Number of tested samples : 1  
Serial number : Prototype  
Date of Test : February 01, 2013 - March 15, 2013  
Date of Report : March 15, 2013

**FCC TEST REPORT****FCC CFR 47 PART 15 C(15.249)****Report Reference No. .... : LCS130201022TF**

Date of Issue ..... : March 15, 2013

**Testing Laboratory Name ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.**

Address ..... : 1F., Xingyuan Industrial Park, Tongda Road, Bao'an Blvd., Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure ..... : Full application of Harmonised standards Partial application of Harmonised standards Other standard testing method **Applicant's Name..... : Xuzhou Fly-Dream Electronic CO.,LTD.**

Address ..... : Room6101, No.23, The North Of Beijing Road, Tongshan District, Xuzhou, Jiangsu, China

**Test Specification**

Standard ..... : FCC CFR 47 PART 15 Subpart C: 2011, ANSI C63.4-2003

Test Report Form No. ..... : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF ..... : Dated 2011-03

**SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. All rights reserved.**


This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description. .... : 2.4G transmitter system**


Trade Mark..... : N/A

Model/ Type reference ..... : F6TB

Ratings ..... : DC 6.0V by 4\*AA batteries

**Result ..... : Positive****Compiled by:**

Yoyo Wang/ File administrators

**Supervised by:**

Fox Zhang / Technique principal

**Approved by:**

Gavin Liang/ Manager

## FCC -- TEST REPORT

<b>Test Report No. : LCS130201022TF</b>	<u>March 15, 2013</u>
	Date of issue

Type / Model..... : F6TB

EUT..... : 2.4G transmitter system

**Applicant..... : Xuzhou Fly-Dream Electronic CO.,LTD.**

Address..... : Room6101,No.23,The North Of Beijing Road,  
Tongshan District, Xuzhou, Jiangsu, China

Telephone..... : /

Fax..... : /

**Manufacturer..... : Xuzhou Fly-Dream Electronic CO.,LTD.**

Address..... : Room6101,No.23,The North Of Beijing Road,  
Tongshan District, Xuzhou, Jiangsu, China

Telephone..... : /

Fax..... : /

**Factory..... : Xuzhou Fly-Dream Electronic CO.,LTD.**

Address..... : Room6101,No.23,The North Of Beijing Road,  
Tongshan District, Xuzhou, Jiangsu, China

Telephone..... : /

Fax..... : /

<b>Test Result:</b>	<b>Positive</b>
---------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. Description of Device (EUT).....	5
1.2. Host System Configuration List and Details .....	5
1.3. External I/O .....	5
1.4. Description of Test Facility .....	6
1.5. Statement of the measurement uncertainty .....	6
1.6. Measurement Uncertainty.....	6
1.7. Description Of Test Modes.....	7
<b>2. TEST METHODOLOGY .....</b>	<b>8</b>
2.1. EUT Configuration .....	8
2.2. EUT Exercise.....	8
2.3. General Test Procedures .....	8
<b>3. CONNECTION DIAGRAM OF TEST SYSTEM.....</b>	<b>9</b>
3.1. Justification.....	9
3.2. EUT Exercise Software .....	9
3.3. Special Accessories .....	9
3.4. Block Diagram/Schematics.....	9
3.5. Equipment Modifications .....	9
3.6. Test Setup .....	9
<b>4. SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
<b>5. ANTENNA REQUIREMENT .....</b>	<b>11</b>
5.1. Standard Applicable .....	11
5.2. Antenna Connected Construction .....	11
<b>6. RADIATED EMISSION MEASUREMENT .....</b>	<b>12</b>
6.1. Standard Applicable .....	12
6.2. Measuring Instruments and Setting .....	12
6.3. Test Procedure .....	13
6.4. Test Equipment List and Details.....	14
6.5. Block Diagram of Test Setup .....	14
6.6. Test Results.....	15
<b>7. BAND EDGES MEASUREMENT.....</b>	<b>23</b>
7.1. Standard Applicable .....	23
7.2. Test Equipment List and Details.....	23
7.3. Block Diagram of Test Setup .....	23
7.4. Test Procedure .....	24
7.5. Test Results.....	25
<b>8. 20 DB BANDWIDTH MEASUREMENT.....</b>	<b>27</b>
8.1. Standard Applicable .....	27
8.2. Test Equipment List and Details.....	27
8.3. Block Diagram of Test Setup .....	27
8.4. Test Procedure .....	27
8.5. Test Results.....	28
<b>9. MANUFACTURER/ APPROVAL HOLDER DECLARATION .....</b>	<b>30</b>

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

EUT : 2.4G transmitter system

Model Number : F6TB

Power Supply : DC 6.0V by 4\*AA batteries

Frequency Range : 2404.00-2480.00MHz

Modulation Technology : GFSK

Channel Number & : 20 channels, See more details at page 7, Channel list

Channel Spacing

Antenna Gain : Integral Antenna on PCB, 3.0dBi(Max.)

### 1.2. Host System Configuration List and Details

N/A

### 1.3. External I/O

N/A

## 1.4. Description of Test Facility

### Site Description

EMC Lab.

: Accredited by CNAS, June 04, 2010

The Certificate Registration Number. is L4595.

Accredited by FCC, July 14, 2011

The Certificate Registration Number. is 899208.

Accredited by Industry Canada, May. 02, 2011

The Certificate Registration Number. is 9642A-1

## 1.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 1.6. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty :	9KHz~30MHz	±3.10dB	(1)
	30MHz~200MHz	±2.96dB	(1)
	200MHz~1000MHz	±3.10dB	(1)
	1GHz~26.5GHz	±4.00dB	(1)
	26.5GHz~40GHz	±3.90dB	(1)
Conduction Uncertainty :	150kHz~30MHz	±1.63dB	(1)
Power disturbance	30MHz~300MHz	±1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 1.7. Description Of Test Modes

The EUT operates in the unlicensed ISM Band at 2.4GHz.

The channel list as showed follow:

Channel No.	Freq.(MHz)	Channel No.	Freq.(MHz)
CH1	2404	CH11	2444
CH2	2408	CH12	2448
CH3	2412	CH13	2452
CH4	2416	CH14	2456
CH5	2420	CH15	2460
CH6	2424	CH16	2464
CH7	2428	CH17	2468
CH8	2432	CH18	2472
CH9	2436	CH19	2476
CH10	2440	CH20	2480

The following operating modes were applied for the related test items.

The EUT received DC 6V power from 4\*AA batteries which are new and full power.

All test modes were tested, only the result of the worst case was recorded in the report.

Mode of Operations	Frequency Range (MHz)	Modulation
Tx	2404	GFSK
	2444	
	2480	
For Conducted Emission		
Test Mode		N/A
For Radiated Emission		
Test Mode		Tx Mode

## 2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.4, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd..

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.249 under the FCC Rules Part 15 Subpart C.

### 2.3. General Test Procedures

#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4

### **3. CONNECTION DIAGRAM OF TEST SYSTEM**

#### **3.1. Justification**

The system was configured for testing in a continuous transmit condition.

#### **3.2. EUT Exercise Software**

N/A

#### **3.3. Special Accessories**

N/A

#### **3.4. Block Diagram/Schematics**

Please refer to the related document

#### **3.5. Equipment Modifications**

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### **3.6. Test Setup**

Please refer to the test setup photo.

## 4. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conduction Emissions	N/A
§15.205(a), §15.209(a), §15.249(a), §15.249(c)	Radiated Emissions Measurement	Compliant
§15.249	Band Edges Measurement	Compliant
§15.249, §15.215	20 dB Bandwidth	Compliant

\*\*\*Note: The EUT received DC 6V power from 4\*AA batteries and no interface to receive power from other external power supply, so line conduction emissions test is not applicable.

## 5. ANTENNA REQUIREMENT

### 5.1. Standard Applicable

According to §15.203, Antenna requirement.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

### 5.2. Antenna Connected Construction

The directional gains of antenna used for transmitting is 3.0dBi(Max.), and EUT is equipped with an integral antenna and no consideration of replacement. Please see EUT photo for details.

Result: Compliance.

## 6. RADIATED EMISSION MEASUREMENT

### 6.1. Standard Applicable

1. Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.
2. 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) and 15.249 limit in the table below has to be followed.

Fundamental Frequency	Field Strength of fundamental (millivolts/meter)	Field Strength of harmonics (microvolts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1000KHz / 1000KHz for peak

### 6.3. Test Procedure


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 m to 4 m) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

#### 6.4. Test Equipment List and Details


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2012-06-18	2013-06-17
2	Amplifier	SCHAFFNER	COA9231A	18667	2012-06-18	2013-06-17
3	Amplifier	Agilent	8449B	3008A02120	2012-06-16	2013-06-15
4	Amplifier	MITEQ	AMF-6F-260 400	9121372	2012-06-16	2013-06-15
5	Spectrum Analyzer	Agilent	E4407B	MY41440292	2012-06-16	2013-06-15
6	Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	2012-06-16	2013-06-15
7	Loop Antenna	R&S	HFH2-Z2	860004/001	2012-06-18	2013-06-17
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2012-06-10	2013-06-09
9	Horn Antenna	EMCO	3115	6741	2012-06-10	2013-06-09
10	Horn Antenna	SCHWARZBECK	BBHA9170	BBHA91701 54	2012-06-10	2013-06-09
11	RF Cable-R03m	Jye Bao	RG142	CB021	2012-06-18	2013-06-17
12	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2012-06-18	2013-06-17

#### 6.5. Block Diagram of Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

## 6.6. Test Results

### Results of Radiated Emissions (9kHz~30MHz)


Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
				See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);  
 Limit line = specific limits (dBuV) + distance extrapolation factor.


## Results of Radiated Emissions (30MHz~1000MHz)



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6.0V  
 Test Mode: Tx-2404  
 Operator: Andy  
 Memo:  
 Pol: VERTICAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	55.22	3.61	0.46	13.01	0.00	17.08	40.00	-22.92	QP
2	144.46	13.44	0.77	8.22	0.00	22.43	43.50	-21.07	QP
3	159.98	14.03	0.75	8.67	0.00	23.45	43.50	-20.05	QP
4	259.89	10.60	1.01	12.05	0.00	23.66	46.00	-22.34	QP
5	607.15	4.09	1.57	18.48	0.00	24.14	46.00	-21.86	QP
6	832.19	5.67	1.86	20.39	0.00	27.92	46.00	-18.08	QP


Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6.0V  
 Test Mode: Tx-2404  
 Operator: Andy  
 Memo:  
 Pol: HORIZONTAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	95.96	7.72	0.58	12.90	0.00	21.20	43.50	-22.30	QP
2	127.97	18.23	0.67	9.24	0.00	28.14	43.50	-15.36	QP
3	144.46	22.20	0.77	8.22	0.00	31.19	43.50	-12.31	QP
4	159.98	19.48	0.75	8.67	0.00	28.90	43.50	-14.60	QP
5	312.27	12.23	1.09	13.23	0.00	26.55	46.00	-19.45	QP
6	721.61	4.75	1.63	19.08	0.00	25.46	46.00	-20.54	QP


Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6.0V  
 Test Mode: Tx-2444  
 Operator: Andy  
 Memo:  
 pol: HORIZONTAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	95.96	7.72	0.58	12.90	0.00	21.20	43.50	-22.30	QP
2	127.97	17.41	0.67	9.24	0.00	27.32	43.50	-16.18	QP
3	144.46	18.61	0.77	8.22	0.00	27.60	43.50	-15.90	QP
4	159.98	19.37	0.75	8.67	0.00	28.79	43.50	-14.71	QP
5	312.27	12.70	1.09	13.23	0.00	27.02	46.00	-18.98	QP
6	608.12	4.42	1.45	18.48	0.00	24.35	46.00	-21.65	QP


Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6.0V  
 Test Mode: Tx-2444  
 Operator: Andy  
 Memo:  
 pol: VERTICAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	47.46	3.50	0.35	13.40	0.00	17.25	40.00	-22.75	QP
2	127.97	8.95	0.67	9.24	0.00	18.86	43.50	-24.64	QP
3	159.98	14.21	0.75	8.67	0.00	23.63	43.50	-19.87	QP
4	259.89	10.45	1.01	12.05	0.00	23.51	46.00	-22.49	QP
5	516.94	2.81	1.42	16.90	0.00	21.13	46.00	-24.87	QP
6	832.19	7.94	1.86	20.39	0.00	30.19	46.00	-15.81	QP

Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins:

24 °C / 56%

EUT:

2.4G transmitter system

M/N:

F6TB

Power Rating:

DC 6.0V

Test Mode:

Tx-2480

Operator:

Andy

Memo:


VERTICAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV		dB	dB/m	dB	dBuV/m	dBuV/m	dB
1	40.67	3.37		0.50	13.58	0.00	17.45	40.00	-22.55
2	127.97	8.90		0.67	9.24	0.00	18.81	43.50	-24.69
3	159.98	14.03		0.75	8.67	0.00	23.45	43.50	-20.05
4	259.89	10.57		1.01	12.05	0.00	23.63	46.00	-22.37
5	689.60	6.20		1.60	18.77	0.00	26.57	46.00	-19.43
6	892.33	5.70		1.86	21.01	0.00	28.57	46.00	-17.43

Note: 1. All readings are Quasi-peak values.

2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.

3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins:

24 °C / 56%

EUT:

2.4G transmitter system

M/N:

F6TB

Power Rating:

DC 6.0V

Test Mode:

Tx-2480

Operator:

Andy

Memo:

HORIZONTAL


	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV		dB	dB/m	dB	dBuV/m	dBuV/m	dB
1	46.49	3.18		0.35	13.46	0.00	16.99	40.00	-23.01
2	127.97	12.21		0.67	9.24	0.00	22.12	43.50	-21.38
3	159.98	18.19		0.75	8.67	0.00	27.61	43.50	-15.89
4	259.89	19.29		1.01	12.05	0.00	32.35	46.00	-13.65
5	312.27	20.94		1.09	13.23	0.00	35.26	46.00	-10.74
6	832.19	8.61		1.86	20.39	0.00	30.86	46.00	-15.14

Note: 1. All readings are Quasi-peak values.

2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.

3. The emission levels that are 20dB below the official limit are not reported.


## Results for Radiated Emissions (Above 1GHz)



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2404  
 Operator: Andy  
 Memo:  
 Pol: HORIZONTAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2404.00	93.45	5.07	27.89	37.10	89.31	114.00	-24.69	Peak
2	4808.87	40.91	7.69	33.32	36.44	45.48	54.00	-8.52	Average
3	4809.00	46.00	7.69	33.32	36.44	50.57	74.00	-23.43	Peak
4	17557.91	18.04	11.17	41.28	35.85	34.64	54.00	-19.36	Average
5	17558.00	36.10	11.17	41.28	35.85	52.70	74.00	-21.30	Peak

Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.




Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2404  
 Operator: Andy  
 Memo:  
 Pol: VERTICAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2404.00	94.43	5.07	27.89	37.10	90.29	114.00	-23.71	Peak
2	4808.87	40.02	7.69	33.32	36.44	44.59	54.00	-9.41	Average
3	4809.00	46.00	7.69	33.32	36.44	50.57	74.00	-23.43	Peak
4	17558.00	36.10	11.17	41.28	35.85	52.70	74.00	-21.30	Peak
5	17558.16	18.14	11.17	41.28	35.85	34.74	54.00	-19.26	Average

Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.

## Field Strength Of Fundamental


Frequency (MHz)	Pol.	Measure Result (PK, dBuV/m)	Measure Result (AVG, dBuV/m)	Peak Limit (dBuV/m)	AVG Limit (dBuV/m)	Result
2404	H	89.31	81.87	114	94	Pass
2404	V	90.29	82.74	114	94	Pass



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2444  
 Operator: Andy  
 Memo:  
 pol: HORIZONTAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2444.00	92.32	5.12	27.77	37.10	88.11	114.00	-25.89	Peak
2	4887.70	43.09	7.73	33.52	36.42	47.92	74.00	-26.08	Peak
3	4887.91	32.88	7.73	33.52	36.42	37.71	54.00	-16.29	Average
4	17762.00	31.12	11.23	41.70	30.82	53.23	74.00	-20.77	Peak
5	17762.11	12.07	11.23	41.70	30.82	34.18	54.00	-19.82	Average

Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.




Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2444  
 Operator: Andy  
 Memo:  
 pol: VERTICAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2444.00	90.32	5.12	27.77	37.10	86.11	114.00	-27.89	Peak
2	4888.04	32.90	7.73	33.52	36.42	37.73	54.00	-16.27	Average
3	4888.97	43.05	7.73	33.52	36.42	47.88	74.00	-26.12	Peak
4	16588.91	19.05	10.88	39.25	34.95	34.23	54.00	-19.77	Average
5	16589.00	38.13	10.88	39.25	34.95	53.31	74.00	-20.69	Peak

Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.

#### Field Strength Of Fundamental


Frequency (MHz)	Pol.	Measure Result (PK, dBuV/m)	Measure Result (AVG, dBuV/m)	Peak Limit (dBuV/m)	AVG Limit (dBuV/m)	Result
2444	H	88.11	79.24	114	94	Pass
2444	V	86.11	78.31	114	94	Pass



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2480  
 Operator: Andy  
 Memo:  
 pol: HORIZONTAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2480.00	83.08	5.17	27.66	30.16	85.75	114.00	-28.25	Peak
2	4960.13	28.59	7.78	33.70	30.27	39.80	54.00	-14.20	Average
3	4960.24	37.61	7.78	33.70	30.27	48.82	74.00	-25.18	Peak
4	17558.00	31.06	11.17	41.28	30.81	52.70	74.00	-21.30	Peak
5	17558.10	12.00	11.17	41.28	30.81	33.64	54.00	-20.36	Average

Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2480  
 Operator: Andy  
 Memo:  
 pol: VERTICAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dB	dBuV/m	dBuV/m	dB	
1	2480.00	89.02	5.17	27.66	37.10	84.75	114.00	-29.25	Peak
2	4960.87	33.88	7.78	33.70	36.40	38.96	54.00	-15.04	Average
3	4961.00	43.98	7.78	33.70	36.40	49.06	74.00	-24.94	Peak
4	17558.00	36.10	11.17	41.28	35.85	52.70	74.00	-21.30	Peak
5	17558.03	17.00	11.17	41.28	35.85	33.60	54.00	-20.40	Average

Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.

#### Field Strength Of Fundamental

Frequency (MHz)	Pol.	Measure Result (PK, dBuV/m)	Measure Result (AVG, dBuV/m)	Peak Limit (dBuV/m)	AVG Limit (dBuV/m)	Result
2480	H	85.75	78.33	114	94	Pass
2480	V	84.75	77.47	114	94	Pass

**Notes:**

1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
3. No emission was be recorded above 18GHz means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 7. BAND EDGES MEASUREMENT


### 7.1. Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

### 7.2. Test Equipment List and Details

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
1	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2012-06-18	2013-06-17
2	Amplifier	SCHAFFNER	COA9231A	18667	2012-06-18	2013-06-17
3	Amplifier	Agilent	8449B	3008A02120	2012-06-16	2013-06-15
4	Amplifier	MITEQ	AMF-6F-260 400	9121372	2012-06-16	2013-06-15
5	Spectrum Analyzer	Agilent	E4407B	MY41440292	2012-06-16	2013-06-15
6	Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	2012-06-16	2013-06-15
7	Loop Antenna	R&S	HFH2-Z2	860004/001	2012-06-18	2013-06-17
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2012-06-10	2013-06-09
9	Horn Antenna	EMCO	3115	6741	2012-06-10	2013-06-09
10	Horn Antenna	SCHWARZBECK	BBHA91701 54	BBHA91701 54	2012-06-10	2013-06-09
11	RF Cable-R03m	Jye Bao	RG142	CB021	2012-06-18	2013-06-17
12	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2012-06-18	2013-06-17

### 7.3. Block Diagram of Test Setup



#### 7.4. Test Procedure


The EUT is placed on a turntable, which is 0.8m above the ground plane. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

Peak: RBW=VBW=1MHz / Sweep=AUTO

Repeat the procedures until the peak versus polarization are measured.


## 7.5. Test Results



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2404  
 Operator: Andy  
 Memo:  
 Pol: HORIZONTAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV		dB	dB/m	dB	dBuV/m	dBuV/m	dB
1	2396.34	35.69		5.05	27.91	37.10	31.55	54.00	-22.45
2	2396.38	44.71		5.05	27.91	37.10	40.57	74.00	-33.43
3	2399.94	36.44		5.06	27.90	37.10	32.30	54.00	-21.70
4	2400.00	45.44		5.06	27.90	37.10	41.30	74.00	-32.70
5	2404.00	90.15		5.07	27.89	37.10	86.01	114.00	-27.99


Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2404  
 Operator: Andy  
 Memo:  
 Pol: VERTICAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV		dB	dB/m	dB	dBuV/m	dBuV/m	dB
1	2397.95	44.17		5.06	27.91	37.10	40.04	74.00	-33.96
2	2397.99	36.12		5.06	27.91	37.10	31.99	54.00	-22.01
3	2399.91	36.35		5.06	27.90	37.10	32.21	54.00	-21.79
4	2399.99	45.39		5.06	27.90	37.10	41.25	74.00	-32.75
5	2404.00	89.87		5.07	27.89	37.10	85.73	114.00	-28.27


Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2480  
 Operator: Andy  
 Memo:  
 pol: HORIZONTAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV		dB	dB/m	dB	dBuV/m	dBuV/m	dB
1	2480.00	84.86		5.17	27.66	37.10	80.59	114.00	-33.41 Peak
2	2483.50	43.37		5.18	27.65	37.10	39.10	74.00	-34.90 Peak
3	2483.51	35.33		5.18	27.65	37.10	31.06	54.00	-22.94 Average
4	2485.93	36.13		5.18	27.64	37.10	31.85	54.00	-22.15 Average
5	2485.96	45.16		5.18	27.64	37.10	40.88	74.00	-33.12 Peak

Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.



Env. / Ins: 24 °C / 56%  
 EUT: 2.4G transmitter system  
 M/N: F6TB  
 Power Rating: DC 6V  
 Test Mode: Tx-2480  
 Operator: Andy  
 Memo:  
 pol: VERTICAL

	Freq	Reading	CabLoss	AntFac	PreFac	Measured	Limit	Over	Remark
	MHz	dBuV		dB	dB/m	dB	dBuV/m	dBuV/m	dB
1	2480.00	84.80		5.17	27.66	37.10	80.53	114.00	-33.47 Peak
2	2483.49	34.04		5.18	27.65	37.10	29.77	94.00	-64.23 Average
3	2483.50	42.13		5.18	27.65	37.10	37.86	74.00	-36.14 Peak
4	2487.68	44.03		5.18	27.64	37.10	39.75	74.00	-34.25 Peak
5	2487.71	34.95		5.18	27.64	37.10	30.67	54.00	-23.33 Average

Note: 1. All readings are Quasi-peak values.  
 2. Measured = Reading + Antenna Factor + Cable Loss - Amp Factor.  
 3. The emission levels that are 20dB below the official limit are not reported.

## 8. 20 DB BANDWIDTH MEASUREMENT


### 8.1. Standard Applicable

According to §15.215.

### 8.2. Test Equipment List and Details

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Spectrum Analyzer	Agilent	E4407B	MY41440754	2012-06-16
2	DC Filter	MPE	23872C	N/A	2012-06-18

### 8.3. Block Diagram of Test Setup



### 8.4. Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW  $\geq$  1% of the 20 dB bandwidth

VBW  $\geq$  RBW



Sweep = auto


Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

## 8.5. Test Results





## 9. MANUFACTURER/ APPROVAL HOLDER DECLARATION

The following identical model(s):

F6TA	K6T	PTR	K8T
------	-----	-----	-----

Belong to the tested device:

Product description : 2.4G transmitter system

Model name : F6TB

*Remark: PCB board, structure and internal of these model(s) are the same, So no additional models were tested.*

-----THE END OF REPORT-----