

RF Exposure Evaluation declaration

Product Name : Wireless Monitor Controller

Model No. : M2M-W02

FCC ID : X7H-M2MW02

Applicant : Commtiva Technology Taiwan Ltd

Address : 4F, No.408, Rueiguang Rd, Neihu District, Taipei, Taiwan

Date of Receipt : Jul. 01, 2010

Date of Declaration : Jul. 13, 2010

Report No. : 107071R-RF-US-RFEXP

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	30
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 23°C and 58% RH.

1.3. Test Result of RF Exposure Evaluation

Product : Wireless Monitor Controller
 Test Item : RF Exposure Evaluation
 Test Site : N/A

GSM 850 GPRS-Peak Gain: 2.76dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
824.2	32.12	1/8	203.7	0.0765	0.55	Pass
836.4	32.34	1/8	214.2	0.0805	0.55	Pass
848.8	32.53	1/8	223.8	0.0841	0.55	Pass

PCS 1900 GPRS-Peak Gain: 2.48dBi

Frequency (MHz)	Conducted Power (dBm)	Duty Cycle	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Pass/Fail
1850.2	30.30	1/8	133.9	0.0472	1	Pass
1880	30.13	1/8	128.8	0.0454	1	Pass
1909.8	29.81	1/8	119.6	0.0421	1	Pass

Note: The conducted output power is refer to report No.: 107071R-HPUSP07V01 from the QuieTek.