



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15B

TEST REPORT

For

SkyHawke Technologies, LLC

274 Commerce Park Drive, Ridgeland, Mississippi United States

FCC ID: X8F-LX5

Report Type: Original Report	Product Type: smart watch
Report Number:	RDG191025007-00C
Report Date:	2019-11-11
Reviewed By:	Gavin Xu RF Engineer
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

TABLE OF CONTENTS

General Information	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
DECLARATIONS	4
System Test Configuration	5
DESCRIPTION OF TEST CONFIGURATION.....	5
EQUIPMENT MODIFICATIONS.....	5
EUT EXERCISE SOFTWARE	5
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	5
SUPPORT CABLE LIST AND DETAILS.....	5
BLOCK DIAGRAM OF TEST SETUP	6
TEST EQUIPMENT LIST	7
ENVIRONMENTAL CONDITIONS	7
Summary of Test Results.....	8
Conducted emissions.....	9
EUT SETUP	9
EMI TEST RECEIVER SETUP	9
TEST PROCEDURE.....	9
TEST DATA.....	11
Radiated emissions.....	13
EUT SETUP	13
EMI TEST RECEIVER SETUP	14
TEST PROCEDURE.....	14
CORRECTED AMPLITUDE & MARGIN CALCULATION.....	14
TEST DATA.....	15

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:	smart watch
EUT Model:	LX5
Rated Input Voltage:	DC 3.85Vdc from battery or DC 5V from adapter
The Highest Operating Frequency:	2480MHz
External Dimension:	264mm(L)*51mm(W)*15mm(H)
Serial Number:	RDG191025007-RF-S4
EUT Received Date:	2019/10/28
EUT Received Status:	Good

Objective

This report is prepared on behalf of **SkyHawke Technologies, LLC** in accordance with FCC Part 15B Part 2, subpart J, and Part 15, Subpart A and B of the Federal Communications Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15 B Class B.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: X8F-LX5

FCC Part 15C DTS submissions with FCC ID: X8F-LX5

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Temperature	±1°C
Humidity	±5%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “ Δ ”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in downloading mode.

Equipment Modifications

No modification was made to the EUT.

EUT Exercise Software


The software "Winthrax.exe" was used during test.

Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
HP	Printer	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL05DC
SAST	Modem	AEM-2100	293

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Serial Cable	Yes	No	1.2	Serial Port of Laptop	Modem
Parallel Cable	Yes	No	1.2	Parallel Port of Laptop	Printer
Keyboard Cable	Yes	No	1.8	USB Port of Laptop	Keyboard
USB Cable	Yes	No	0.8	Laptop	EUT

Block Diagram of Test Setup

Test Equipment List

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted emissions					
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2019-09-05	2020-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2019-09-12	2020-09-12
R&S	EMI Test Receiver	ESCI	101121	2019-05-09	2020-05-09
Radiated emissions Below 1GHz					
R&S	EMI Test Receiver	ESR3	102453	2019-09-12	2020-09-12
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0075-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-1400-01	2019-05-06	2020-05-06
HP	Amplifier	8447D	2727A05902	2019-09-05	2020-09-05
Radiated emissions Above 1GHz					
Rohde & Schwarz	Signal Analyzer	FSIQ26	831929/005	2019-09-12	2020-09-12
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05
MITEQ	Amplifier	AFS42-00101800-25-S-42	2001271	2019-09-05	2020-09-05

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Environmental Conditions


Test Item:	Conducted emissions	Radiated emissions Below 1GHz	Radiated emissions Above 1GHz
Test Date:	2019-10-29	2019-10-30	2019-11-06
Tester:	Sem Xiang	Neil Liao	Neil Liao
Temperature:	26.8°C	25.5°C	25.6°C
Relative Humidity:	48 %	43 %	46%
ATM Pressure:	100.1 kPa	101.2kPa	100.9 kPa

SUMMARY OF TEST RESULTS

Rule and Clause	Description of Test	Test Result
FCC §15.107	Conducted emissions	Compliance
FCC §15.109	Radiated emissions	Compliance

CONDUCTED EMISSIONS

EUT Setup



Note:

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to the Main LISN with 120V/60Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the Adapter of Laptop was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_c + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_c : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN


The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data

Please refer to following table and plots:

Port: L
 Test Mode: Downloading
 Power Source: AC 120V/60Hz
 Note:




Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.153015	39.3	9.000	L1	11.1	26.5	65.8
0.480499	29.7	9.000	L1	9.9	26.6	56.3
0.552321	37.0	9.000	L1	9.8	19.0	56.0
1.601690	30.0	9.000	L1	9.7	26.0	56.0
17.446496	35.9	9.000	L1	10.0	24.1	60.0
19.464503	39.1	9.000	L1	10.1	20.9	60.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.485304	23.9	9.000	L1	9.9	22.3	46.2
0.569057	31.2	9.000	L1	9.8	14.8	46.0
0.737074	23.3	9.000	L1	9.8	22.7	46.0
1.650223	24.0	9.000	L1	9.7	22.0	46.0
17.620961	28.9	9.000	L1	10.0	21.1	50.0
19.659148	31.0	9.000	L1	10.1	19.0	50.0

Port: N
 Test Mode: Downloading
 Power Source: AC 120V/60Hz
 Note:



Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.165693	41.1	9.000	N	10.9	24.1	65.2
0.208304	35.7	9.000	N	10.6	27.6	63.3
0.541438	36.4	9.000	N	9.8	19.6	56.0
1.585832	30.9	9.000	N	9.8	25.1	56.0
17.620961	36.3	9.000	N	10.0	23.7	60.0
19.855740	42.4	9.000	N	10.0	17.6	60.0


Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.563423	30.8	9.000	N	9.8	15.2	46.0
0.687483	24.3	9.000	N	9.8	21.7	46.0
0.737074	23.6	9.000	N	9.8	22.4	46.0
1.617707	24.7	9.000	N	9.8	21.3	46.0
17.620961	29.2	9.000	N	10.0	20.8	50.0
19.659148	34.8	9.000	N	10.0	15.2	50.0


RADIATED EMISSIONS

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 10 meters chamber test site, above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.4-2014. The specification used was with the FCC Part 15 B Class B limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 13 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
	1 MHz	Reduced video bandwidth	/	AVG

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

During the radiated emissions, the adapter of laptop was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Meter Reading + Corrected

Note:

Corrected = Antenna Factor + Cable Loss - Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Result}$$

Test Data

Please refer to following table and plots:

Condition: FCC Part 15B Class B
EUT: smart watch
Model: LX5
Test Mode: Downloading
Note:


Polarization: Horizontal
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
85.2900	42.53	peak	-11.41	31.12	40.00	8.88
113.4200	36.45	peak	-5.55	30.90	43.50	12.60
227.8800	47.30	QP	-6.57	40.73	46.00	5.27
245.3400	44.50	QP	-5.97	38.53	46.00	7.47
265.7100	41.16	peak	-4.49	36.67	46.00	9.33
715.7900	30.84	peak	3.25	34.09	46.00	11.91

Condition: FCC Part 15B Class B
EUT: smart watch
Model: LX5
Test Mode: Downloading
Note:


Polarization: Vertical
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
30.000	25.91	peak	1.72	27.63	40.00	12.37
86.2600	40.57	peak	-11.42	29.15	40.00	10.85
114.3900	35.06	peak	-5.37	29.69	43.50	13.81
286.0800	36.93	peak	-4.03	32.90	46.00	13.10
599.3900	31.83	peak	1.00	32.83	46.00	13.17
879.7200	35.24	peak	-0.47	34.77	46.00	11.23


Condition: FCC Part 15B Class B
EUT: smart watch
Model: LX5
Test Mode: Downloading
Note:

Polarization: Horizontal
Power: AC 120V/60Hz
Distance: 3m



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1793.587	60.65	peak	-7.82	52.83	74.00	21.17
1793.587	45.21	AVG	-7.82	37.39	54.00	16.61
1985.972	66.17	peak	-7.23	58.94	74.00	15.06
1985.972	51.11	AVG	-7.23	43.88	54.00	10.12
3789.579	53.31	peak	-2.57	50.74	74.00	23.26
3789.579	38.35	AVG	-2.57	35.78	54.00	18.22

Condition: FCC Part 15B Class B
EUT: smart watch
Model: LX5
Test Mode: Downloading
Note:



Frequency (MHz)	Reading (dB μ V)	Detector	Corrected (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
1793.587	61.94	peak	-7.82	54.12	74.00	19.88
1793.587	47.65	AVG	-7.82	39.83	54.00	14.17
1985.972	65.95	peak	-7.23	58.72	74.00	15.28
1985.972	51.44	AVG	-7.23	44.21	54.00	9.79
3789.579	56.15	peak	-2.57	53.58	74.00	20.42
3789.579	41.54	AVG	-2.57	38.97	54.00	15.03

*****END OF REPORT*****