



TESTING LABORATORY
CERTIFICATE #4820.01



FCC PART 15.247

RSS-GEN, ISSUE 5, MARCH 2019 AMENDMENT 1

RSS-247, ISSUE 2, FEBRUARY 2017

TEST REPORT

For

SkyHawke Technologies, LLC

FCC Add: 274 Commerce Park Drive Ridgeland Mississippi United States

IC Add: 274 Commerce Park Drive Ridgeland MS 39157 United States Of America (Excluding The States Of Alaska)

FCC ID: X8FSX550
IC: 12059A-SX550

Report Type: Original Report	Product Name: Golf GPS Receiver
Report Number: RDG210412031-00B	
Report Date: 2021-05-28	
Reviewed By: Gavin Xu RF Engineer	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.12, Pulong East 1 st Road, Tangxia Town, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
TECHNICAL SPECIFICATION	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
DECLARATIONS.....	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	7
EQUIPMENT MODIFICATIONS	10
SUPPORT EQUIPMENT LIST AND DETAILS	10
SUPPORT CABLE LIST AND DETAILS	10
BLOCK DIAGRAM OF TEST SETUP	10
SUMMARY OF TEST RESULTS.....	11
1 - RF EXPOSURE.....	12
APPLICABLE STANDARD	12
MEASUREMENT RESULT	12
2 - EXEMPTION LIMITS FOR ROUTINE EVALUATION – SAR EVALUATION	13
APPLICABLE STANDARD	13
MEASUREMENT RESULT	13
3 - ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
4 – AC LINE CONDUCTED EMISSIONS.....	15
APPLICABLE STANDARD	15
TEST SYSTEM SETUP.....	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS.....	16
TEST DATA	17
5 - SPURIOUS EMISSIONS.....	19
APPLICABLE STANDARD	19
TEST SYSTEM SETUP.....	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST EQUIPMENT LIST AND DETAILS.....	21
TEST DATA	21
6-6 dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	30
APPLICABLE STANDARD	30
TEST PROCEDURE	31
TEST EQUIPMENT LIST AND DETAILS.....	31
TEST DATA	31

7 - MAXIMUM PEAK CONDUCTED OUTPUT POWER	45
APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST EQUIPMENT LIST AND DETAILS.....	45
TEST DATA	46
8 – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	47
APPLICABLE STANDARD	47
TEST PROCEDURE	47
TEST EQUIPMENT LIST AND DETAILS.....	48
TEST DATA	48
9 - POWER SPECTRAL DENSITY.....	53
APPLICABLE STANDARD	53
TEST PROCEDURE	53
TEST EQUIPMENT LIST AND DETAILS.....	53
TEST DATA	54

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

EUT Name:		Golf GPS Receiver
EUT Model:		SX550
Rated Input Voltage:		DC 3.85V from Battery or DC 5V from adapter
Adapter Information	Manufacturer:	Shenzhen Flypower Technology Co., Ltd.
	Model:	PS10UA050K2000UU
	Input:	AC 100~240V, 50/60Hz, 0.35A Max.
	Output:	DC 5.0V, 2.0A, 10.0W
Serial Number:		RDG210412031-RF-S1
EUT Received Date:		2021.04.12
EUT Received Status:		Good

Technical Specification

Operation Frequency Range (MHz):		2412-2462
Max. RF Output Power (dBm):	Conducted:	802.11b: 11.65 802.11g: 11.30 802.11n20: 11.76 BLE: 3.89
	EIRP	802.11b: 13.15 802.11g: 12.80 802.11n20: 13.26 BLE: 5.39
Number of Chain	Transmit:	1
	Receive:	1
Antenna Gain (dBi)[▲]:		1.5
Modulation Type:		WIFI: DSSS, OFDM BLE: GFSK

Objective

This report is prepared on behalf of **SkyHawke Technologies, LLC** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules and RSS-247, Issue 2, February 2017, RSS-Gen, Issue 5, March 2019 Amendment 1 of the Innovation, Science and Economic Development Canada.

The tests were performed in order to determine the EUT compliance with FCC Rules Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules and RSS-247, Issue 2, February 2017, RSS-Gen, Issue 5, March 2019 Amendment 1 of the Innovation, Science and Economic Development Canada.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r02, RSS-247, Issue 2, February 2017, RSS-Gen Issue 5, April 2018 of the Innovation, Science and Economic Development Canada.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For 2.4GHz band, total 11 channels are provided:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were test with channel 1,6,11.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404
...
...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

EUT Exercise Software


The software “Engineering Mode” was used for testing, which was provided by manufacturer. The maximum power was configured as below table, that provided by the manufacturer▲:

Mode	Channel	Frequency (MHz)	Data rate	Power level Setting
802.11 b	Low	2412	1Mbps	17
	Middle	2437	1Mbps	17
	High	2462	1Mbps	17
802.11 g	Low	2412	6Mbps	17
	Middle	2437	6Mbps	17
	High	2462	6Mbps	17
802.11n ht20	Low	2412	MCS0	17
	Middle	2437	MCS0	17
	High	2462	MCS0	17
BLE	Low	2402	1Mbps	Default
	Middle	2440	1Mbps	Default
	High	2480	1Mbps	Default

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100
802.11g	1.355	1.435	94.43
802.11n ht20	1.254	1.319	95.07
BLE	0.4108	0.6291	65.30

802.11b




Date: 7.MAY.2021 04:38:56

802.11g




Date: 28.MAY.2021 08:36:16

802.11n ht20



Date: 28.MAY.2021 08:37:31

BLE



Date: 20.APR.2021 10:40:44

Equipment Modifications

No modification was made to the EUT.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	No	No	0.8	Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

S/N	Rules	Description of Test	Result
1	FCC§15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
2	RSS-102 §2.5.1	Exemption Limits for Routine Evaluation -SAR Evaluation	Compliance
3	FCC §15.203, RSS-GEN Clause 6.8	Antenna Requirement	Compliance
4	FCC §15.207 (a); RSS-Gen Clause 8.8	AC Line Conducted Emissions	Compliance
5	FCC §15.205, §15.209, §15.247(d); RSS-247 Clause 5.5 RSS-Gen Clause 8.10	Spurious Emissions	Compliance
6	FCC §15.247 (a)(2); RSS-247 Clause 5.2 a) RSS-Gen Clause 6.7	6 dB Bandwidth and 99% Occupied Bandwidth	Compliance
7	FCC §15.247(b)(3); RSS-247 Clause 5.4 d)	Maximum Conducted Output Power	Compliance
8	FCC §15.247(d); RSS-247 Clause 5.5	100 kHz Bandwidth of Frequency Band Edge	Compliance
9	FCC §15.247(e) RSS-247 Clause 5.2 b)	Power Spectral Density	Compliance

1 - RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

For BLE:

The max conducted power including tune-up tolerance is 4.0 dBm (2.51 mW).

$[(\text{max. power of channel, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 $= 2.51 / 5 * (\sqrt{2.480}) = 0.8 < 3.0$

Result: Compliance. So the stand-alone SAR evaluation is not necessary.

For 802.11b/g/n:

Result: Compliance. Please refer to the SAR test report: RDG210412031-20.

2 - EXEMPTION LIMITS FOR ROUTINE EVALUATION – SAR EVALUATION

Applicable Standard

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5.

Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance⁴⁵

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥50 mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

Measurement Result

For BLE:

The max tune-up conducted power is 4.0 dBm, Antenna Gain is 1.5 dBi, so the tune-up EIRP is 5.5 dBm (3.55mW)

The exemption power(P) limits for routine evaluation in 2402-2480MHz is:
 $(2480-2450)/(3500-2450)=(4-P)/(4-2) \Rightarrow P=3.94 \text{ mW} @ 2480 \text{ MHz} > 3.55 \text{ mW}$

So the stand-alone SAR evaluation can be exempted.

For WIFI: Please refer to the SAR report: RDG210412031-20.

3 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

According to RSS-Gen §6.8, The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer. The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

Antenna Connector Construction

The EUT has one internal antenna arrangement, fulfill the requirement of this section. Please refer to below information and the EUT photos:

Antenna Type	input impedance (Ohm)	Antenna Gain /Frequency Range
FPC	50	1.5 dBi/2.4~2.5GHz


Result: Compliance.

4 – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207(a), RSS-GEN CLAUSE 8.8.

Test System Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 and RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main LISN with a 120 V/60 Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN.

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase ("hot") line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_c + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_c : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV 216	101614	2020-09-12	2021-09-12
R&S	EMI Test Receiver	ESCI	101121	2020-07-07	2021-07-07
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2020-09-05	2021-09-05
R&S	Test Software	EMC32	Version 9.10.00	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	24.6°C
Relative Humidity:	52 %
ATM Pressure:	101.3kPa
Tester:	Walker Chen
Test Date:	2021-05-01

Test Result: Compliance

Test Mode: Transmitting


AC120 V, 60 Hz, Line:



Final Result

Frequency (MHz)	QuasiPeak (dB μV)	Average (dB μV)	Limit (dB μV)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.150750	---	31.38	55.96	24.58	9.000	L1	9.6
0.154557	51.64	---	65.75	14.11	9.000	L1	9.6
0.257055	36.81	---	61.53	24.72	9.000	L1	9.6
0.419083	---	22.05	47.47	25.42	9.000	L1	9.6
0.465358	36.55	---	56.60	20.05	9.000	L1	9.6
0.516743	---	29.73	46.00	16.27	9.000	L1	9.6
0.998148	---	21.40	46.00	24.60	9.000	L1	9.7
1.086470	34.27	---	56.00	21.73	9.000	L1	9.7
1.287253	32.71	---	56.00	23.29	9.000	L1	9.7
1.287253	---	22.46	46.00	23.54	9.000	L1	9.7
2.272976	---	20.77	46.00	25.23	9.000	L1	9.7
2.377330	30.66	---	56.00	25.34	9.000	L1	9.7

AC120 V, 60 Hz, Neutral:



Final_Result

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.150000	49.59	---	66.00	16.41	9.000	N	9.6
0.177720	---	27.16	54.59	27.43	9.000	N	9.6
0.282606	37.88	---	60.74	22.86	9.000	N	9.6
0.336506	---	25.53	49.29	23.76	9.000	N	9.6
0.521923	---	30.07	46.00	15.93	9.000	N	9.6
0.529791	38.82	---	56.00	17.18	9.000	N	9.6
0.959105	---	21.54	46.00	24.46	9.000	N	9.6
1.136351	32.46	---	56.00	23.54	9.000	N	9.6
1.387250	---	19.53	46.00	26.47	9.000	N	9.6
1.495016	27.69	---	56.00	28.31	9.000	N	9.6
2.130277	30.53	---	56.00	25.47	9.000	N	9.6
2.295763	---	19.12	46.00	26.88	9.000	N	9.6


5 - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205; RSS-247 §5.5, RSS-GEN §8.10.

Test System Setup

Below 1GHz:



Above 1GHz:



The radiated emission below 1GHz tests were performed in the 10 meters chamber test site, above 1GHz tests were performed in the 3 meters chamber test site B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98% <98%	1MHz	10 Hz 1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated emissions Below 1GHz					
Sunol Sciences	Antenna	JB3	A060611-2	2020-08-25	2023-08-25
R&S	EMI Test Receiver	ESCI	100224	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2020-09-05	2021-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2020-09-24	2021-09-24
Sonoma	Amplifier	310N	185914	2020-10-13	2021-10-13
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Radiated emissions Above 1GHz					
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020-10-13	2023-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2020-12-05	2023-12-04
R&S	Spectrum Analyzer	FSP 38	100478	2020-07-07	2021-07-07
HUBER+SUHNE R	Coaxial Cable	SUCOFLEX 126EA	MY369/26/26 EA	2020-09-25	2021-09-25
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2020-09-05	2021-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2020-06-27	2021-06-27
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Test Items	Radiation Below 1GHz	Radiation Above 1GHz
Temperature:	25.6°C	26.1°C
Relative Humidity:	53%	68%
ATM Pressure:	100.8 kPa	101 kPa
Tester:	King Wang	Joker Chen
Test Date:	2021-05-05	2021-05-06


Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plots.

1) 30MHz-1GHz(802.11n20 mode middle channel was the worst)

Horizontal:

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
57.1600	49.74	peak	-16.42	33.32	40.00	6.68
148.3400	43.69	peak	-9.22	34.47	43.50	9.03
196.8400	44.38	peak	-9.65	34.73	43.50	8.77
250.1900	48.28	QP	-9.73	38.55	46.00	7.45
292.8700	45.66	peak	-7.74	37.92	46.00	8.08
451.9500	40.15	peak	-4.24	35.91	46.00	10.09

Vertical:

Frequency (MHz)	Receiver Reading (dBuV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBuV/m)	Limit (dBuV/m)	Margin (dB)
35.8200	41.80	QP	-7.15	34.65	40.00	5.35
56.1900	52.31	QP	-16.32	35.99	40.00	4.01
83.3500	49.02	peak	-15.53	33.49	40.00	6.51
94.0200	48.51	peak	-14.71	33.80	43.50	9.70
148.3400	39.31	peak	-9.22	30.09	43.50	13.41
245.3400	41.67	peak	-9.88	31.79	46.00	14.21

2) 1-25GHz:

802.11b Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	69.46	PK	H	28.12	2.50	0.00	100.08	N/A	N/A
2412.00	66.23	AV	H	28.12	2.50	0.00	96.85	N/A	N/A
2412.00	66.53	PK	V	28.12	2.50	0.00	97.15	N/A	N/A
2412.00	63.28	AV	V	28.12	2.50	0.00	93.90	N/A	N/A
2390.00	27.41	PK	H	28.08	2.50	0.00	57.99	74.00	16.01
2390.00	14.07	AV	H	28.08	2.50	0.00	44.65	54.00	9.35
4824.00	42.44	PK	H	32.92	3.59	27.41	51.54	74.00	22.46
4824.00	36.82	AV	H	32.92	3.59	27.41	45.92	54.00	8.08
7236.00	35.94	PK	H	35.62	4.67	27.22	49.01	74.00	24.99
7236.00	24.46	AV	H	35.62	4.67	27.22	37.53	54.00	16.47
Middle Channel: 2437 MHz									
2437.00	68.00	PK	H	28.17	2.51	0.00	98.68	N/A	N/A
2437.00	64.49	AV	H	28.17	2.51	0.00	95.17	N/A	N/A
2437.00	64.96	PK	V	28.17	2.51	0.00	95.64	N/A	N/A
2437.00	61.68	AV	V	28.17	2.51	0.00	92.36	N/A	N/A
4874.00	36.75	PK	H	33.00	3.58	27.54	45.79	74.00	28.21
4874.00	30.93	AV	H	33.00	3.58	27.54	39.97	54.00	14.03
7311.00	35.84	PK	H	35.78	4.65	27.28	48.99	74.00	25.01
7311.00	24.40	AV	H	35.78	4.65	27.28	37.55	54.00	16.45
High Channel: 2462 MHz									
2462.00	71.20	PK	H	28.22	2.52	0.00	101.94	N/A	N/A
2462.00	68.16	AV	H	28.22	2.52	0.00	98.90	N/A	N/A
2462.00	68.14	PK	V	28.22	2.52	0.00	98.88	N/A	N/A
2462.00	65.06	AV	V	28.22	2.52	0.00	95.80	N/A	N/A
2483.50	27.37	PK	H	28.27	2.53	0.00	58.17	74.00	15.83
2483.50	14.64	AV	H	28.27	2.53	0.00	45.44	54.00	8.56
4924.00	35.89	PK	H	33.08	3.58	27.51	45.04	74.00	28.96
4924.00	30.22	AV	H	33.08	3.58	27.51	39.37	54.00	14.63
7386.00	35.75	PK	H	35.95	4.62	27.18	49.14	74.00	24.86
7386.00	24.27	AV	H	35.95	4.62	27.18	37.66	54.00	16.34

802.11g Mode:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	70.96	PK	H	28.12	2.50	0.00	101.58	N/A	N/A
2412.00	62.30	AV	H	28.12	2.50	0.00	92.92	N/A	N/A
2412.00	66.67	PK	V	28.12	2.50	0.00	97.29	N/A	N/A
2412.00	58.12	AV	V	28.12	2.50	0.00	88.74	N/A	N/A
2390.00	26.46	PK	H	28.08	2.50	0.00	57.04	74.00	16.96
2390.00	14.94	AV	H	28.08	2.50	0.00	45.52	54.00	8.48
4824.00	37.60	PK	H	32.92	3.59	27.41	46.70	74.00	27.30
4824.00	26.01	AV	H	32.92	3.59	27.41	35.11	54.00	18.89
7236.00	35.46	PK	H	35.62	4.67	27.22	48.53	74.00	25.47
7236.00	23.71	AV	H	35.62	4.67	27.22	36.78	54.00	17.22
Middle Channel: 2437 MHz									
2437.00	73.96	PK	H	28.17	2.51	0.00	104.64	N/A	N/A
2437.00	65.20	AV	H	28.17	2.51	0.00	95.88	N/A	N/A
2437.00	69.12	PK	V	28.17	2.51	0.00	99.80	N/A	N/A
2437.00	60.59	AV	V	28.17	2.51	0.00	91.27	N/A	N/A
4874.00	35.80	PK	H	33.00	3.58	27.54	44.84	74.00	29.16
4874.00	24.31	AV	H	33.00	3.58	27.54	33.35	54.00	20.65
7311.00	35.66	PK	H	35.78	4.65	27.28	48.81	74.00	25.19
7311.00	23.87	AV	H	35.78	4.65	27.28	37.02	54.00	16.98
High Channel: 2462 MHz									
2462.00	74.65	PK	H	28.22	2.52	0.00	105.39	N/A	N/A
2462.00	65.97	AV	H	28.22	2.52	0.00	96.71	N/A	N/A
2462.00	70.10	PK	V	28.22	2.52	0.00	100.84	N/A	N/A
2462.00	61.24	AV	V	28.22	2.52	0.00	91.98	N/A	N/A
2483.50	33.71	PK	H	28.27	2.53	0.00	64.51	74.00	9.49
2483.50	17.72	AV	H	28.27	2.53	0.00	48.52	54.00	5.48
4924.00	36.35	PK	H	33.08	3.58	27.51	45.50	74.00	28.50
4924.00	24.95	AV	H	33.08	3.58	27.51	34.10	54.00	19.90
7386.00	35.63	PK	H	35.95	4.62	27.18	49.02	74.00	24.98
7386.00	24.16	AV	H	35.95	4.62	27.18	37.55	54.00	16.45

802.11n ht20 Mode:




Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2412 MHz									
2412.00	71.69	PK	H	28.12	2.50	0.00	102.31	N/A	N/A
2412.00	61.90	AV	H	28.12	2.50	0.00	92.52	N/A	N/A
2412.00	69.11	PK	V	28.12	2.50	0.00	99.73	N/A	N/A
2412.00	59.26	AV	V	28.12	2.50	0.00	89.88	N/A	N/A
2390.00	26.76	PK	H	28.08	2.50	0.00	57.34	74.00	16.66
2390.00	14.93	AV	H	28.08	2.50	0.00	45.51	54.00	8.49
4824.00	37.98	PK	H	32.92	3.59	27.41	47.08	74.00	26.92
4824.00	26.57	AV	H	32.92	3.59	27.41	35.67	54.00	18.33
7236.00	35.93	PK	H	35.62	4.67	27.22	49.00	74.00	25.00
7236.00	24.28	AV	H	35.62	4.67	27.22	37.35	54.00	16.65
Middle Channel: 2437 MHz									
2437.00	73.28	PK	H	28.17	2.51	0.00	103.96	N/A	N/A
2437.00	63.56	AV	H	28.17	2.51	0.00	94.24	N/A	N/A
2437.00	70.93	PK	V	28.17	2.51	0.00	101.61	N/A	N/A
2437.00	61.33	AV	V	28.17	2.51	0.00	92.01	N/A	N/A
4874.00	35.64	PK	H	33.00	3.58	27.54	44.68	74.00	29.32
4874.00	24.09	AV	H	33.00	3.58	27.54	33.13	54.00	20.87
7311.00	35.40	PK	H	35.78	4.65	27.28	48.55	74.00	25.45
7311.00	24.07	AV	H	35.78	4.65	27.28	37.22	54.00	16.78
High Channel: 2462 MHz									
2462.00	73.64	PK	H	28.22	2.52	0.00	104.38	N/A	N/A
2462.00	64.88	AV	H	28.22	2.52	0.00	95.62	N/A	N/A
2462.00	71.20	PK	V	28.22	2.52	0.00	101.94	N/A	N/A
2462.00	61.50	AV	V	28.22	2.52	0.00	92.24	N/A	N/A
2483.50	36.93	PK	H	28.27	2.53	0.00	67.73	74.00	6.27
2483.50	19.24	AV	H	28.27	2.53	0.00	50.04	54.00	3.96
4924.00	36.05	PK	H	33.08	3.58	27.51	45.20	74.00	28.80
4924.00	24.46	AV	H	33.08	3.58	27.51	33.61	54.00	20.39
7386.00	36.72	PK	H	35.95	4.62	27.18	50.11	74.00	23.89
7386.00	25.31	AV	H	35.95	4.62	27.18	38.70	54.00	15.30

BLE:

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
	Reading (dB μ V)	Detector	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	63.53	PK	H	28.10	2.50	0.00	94.13	N/A	N/A
2402.00	61.94	AV	H	28.10	2.50	0.00	92.54	N/A	N/A
2402.00	62.68	PK	V	28.10	2.50	0.00	93.28	N/A	N/A
2402.00	61.34	AV	V	28.10	2.50	0.00	91.94	N/A	N/A
2390.00	26.54	PK	H	28.08	2.50	0.00	57.12	74.00	16.88
2390.00	15.31	AV	H	28.08	2.50	0.00	45.89	54.00	8.11
4804.00	36.05	PK	H	32.89	3.59	27.36	45.17	74.00	28.83
4804.00	23.72	AV	H	32.89	3.59	27.36	32.84	54.00	21.16
7206.00	35.78	PK	H	35.55	4.68	27.19	48.82	74.00	25.18
7206.00	23.46	AV	H	35.55	4.68	27.19	36.50	54.00	17.50
Middle Channel: 2440 MHz									
2440.00	67.65	PK	H	28.18	2.51	0.00	98.34	N/A	N/A
2440.00	65.86	AV	H	28.18	2.51	0.00	96.55	N/A	N/A
2440.00	66.43	PK	V	28.18	2.51	0.00	97.12	N/A	N/A
2440.00	65.02	AV	V	28.18	2.51	0.00	95.71	N/A	N/A
4880.00	35.46	PK	H	33.01	3.58	27.55	44.50	74.00	29.50
4880.00	23.05	AV	H	33.01	3.58	27.55	32.09	54.00	21.91
7320.00	36.09	PK	H	35.80	4.64	27.26	49.27	74.00	24.73
7320.00	23.44	AV	H	35.80	4.64	27.26	36.62	54.00	17.38
High Channel: 2480 MHz									
2480.00	66.14	PK	H	28.26	2.52	0.00	96.92	N/A	N/A
2480.00	64.62	AV	H	28.26	2.52	0.00	95.40	N/A	N/A
2480.00	64.87	PK	V	28.26	2.52	0.00	95.65	N/A	N/A
2480.00	63.56	AV	V	28.26	2.52	0.00	94.34	N/A	N/A
2483.50	25.71	PK	H	28.27	2.53	0.00	56.51	74.00	17.49
2483.50	15.83	AV	H	28.27	2.53	0.00	46.63	54.00	7.37
4960.00	36.28	PK	H	33.14	3.59	27.37	45.64	74.00	28.36
4960.00	23.90	AV	H	33.14	3.59	27.37	33.26	54.00	20.74
7440.00	37.60	PK	H	36.07	4.61	27.22	51.06	74.00	22.94
7440.00	25.18	AV	H	36.07	4.61	27.22	38.64	54.00	15.36




4) Test plots(802.11b Low channel was the worst case)**Horizontal:**

Fundamental
Test with Band
Rejection Filter



Vertical:

Fundamental Test with Band Rejection Filter



6– 6 dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH

Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

According to RSS-247 §5.2 a)

The minimum 6 dB bandwidth shall be 500 kHz.

According to RSS-Gen §6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A
E-Microwave	Coaxial Attenuators	EMCA10-5RN-6	OE01203239	2020-09-06	2021-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	25.4~27.4 °C
Relative Humidity:	39~49 %
ATM Pressure:	100.4~101.5 kPa
Tester:	Joe Qiao
Test Date:	2021-04-20~2021-05-07


Test Mode: Transmitting

Test Result: Compliance. please refer to the following table and plots.

Test mode	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)
802.11 b	2412	8.640	11.737	≥0.5
	2437	10.080	12.695	≥0.5
	2462	9.200	12.615	≥0.5
802.11 g	2412	14.160	16.447	≥0.5
	2437	15.920	17.166	≥0.5
	2462	15.680	17.166	≥0.5
802.11n ht20	2412	14.640	17.405	≥0.5
	2437	17.200	18.124	≥0.5
	2462	16.400	18.044	≥0.5
BLE	2402	0.680	1.026	≥0.5
	2440	0.676	1.026	≥0.5
	2480	0.692	1.022	≥0.5


6dB Bandwidth:**802.11b Low Channel**

Date: 7.MAY.2021 03:43:24

802.11b Middle Channel


Date: 7.MAY.2021 04:15:55

802.11b High Channel




Date: 7.MAY.2021 03:47:10

802.11g Low Channel




Date: 7.MAY.2021 04:03:40

802.11g Middle Channel




Date: 7.MAY.2021 04:16:35

802.11g High Channel




Date: 7.MAY.2021 04:18:06

802.11n ht20 Low Channel




Date: 7.MAY.2021 04:19:06

802.11n ht20 Middle Channel



Date: 7.MAY.2021 04:22:44

802.11n ht20 High Channel



Date: 7.MAY.2021 04:21:39

BLE Low Channel




Date: 20.APR.2021 07:12:59

BLE Middle Channel



Date: 20.APR.2021 07:17:01

BLE High Channel




Date: 20.APR.2021 07:18:50

99% Occupied Bandwidth:**802.11b Low Channel**

Date: 7.MAY.2021 03:43:34

802.11b Middle Channel

Date: 7.MAY.2021 04:16:02


802.11b High Channel

Date: 7.MAY.2021 03:47:18

802.11g Low Channel

Date: 7.MAY.2021 04:03:51

802.11g Middle Channel



Date: 7.MAY.2021 04:16:45

802.11g High Channel



Date: 7.MAY.2021 04:18:19

802.11n ht20 Low Channel



Date: 7.MAY.2021 04:19:17

802.11n ht20 Middle Channel



Date: 7.MAY.2021 04:22:55

802.11n ht20 High Channel



Date: 7.MAY.2021 04:21:52

BLE Low Channel



Date: 20.APR.2021 07:13:07

BLE Middle Channel



Date: 20.APR.2021 07:17:09

BLE High Channel



Date: 20.APR.2021 07:18:58

7 - MAXIMUM PEAK CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to RSS-247§5.4 d) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(e), the e.i.r.p. shall not exceed 4 W.

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power meter to test average output power, record the result as average power.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
E-Microwave	Coaxial Attenuators	EMCA10-5RN-6	OE01203239	2020-09-06	2021-09-06
Agilent	USB Wideband Power Sensor	U2021XA	MY5425009	2020-09-12	2021-09-12

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Test Data

Environmental Conditions

Temperature:	23.9 °C
Relative Humidity:	38 %
ATM Pressure:	101.1 kPa
Tester:	Joe Qiao
Test Date:	2021-04-26

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table.

Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)	Peak Conducted Output Power Limit (dBm)	EIRP (dBm)	EIRP Limit For ISED (dBm)
802.11b	2412	11.64	30	13.14	36
	2437	11.65	30	13.15	36
	2462	11.15	30	12.65	36
802.11g	2412	9.56	30	11.06	36
	2437	11.15	30	12.65	36
	2462	11.30	30	12.80	36
802.11n ht20	2412	9.54	30	11.04	36
	2437	11.76	30	13.26	36
	2462	11.27	30	12.77	36
BLE	2402	0.93	30	2.43	36
	2440	2.26	30	3.76	36
	2480	3.89	30	5.39	36

Note: The data above was tested in conducted mode, the antenna gain is 1.5 dBi.

8 – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to RSS-247 Clause 5.5:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	25.4~27.4 °C
Relative Humidity:	39~49 %
ATM Pressure:	100.4~101.5 kPa
Tester:	Joe Qiao
Test Date:	2021-04-20~2021-05-07

Test mode: Transmitting


Test Result: Compliance. Please refer to following plots.

802.11b: Band Edge, Left Side




Date: 7.MAY.2021 03:43:45

802.11b: Band Edge, Right Side




Date: 7.MAY.2021 03:47:29

802.11g: Band Edge, Left Side




Date: 7.MAY.2021 04:04:01

802.11g: Band Edge, Right Side



Date: 7.MAY.2021 04:18:30

802.11n ht20: Band Edge, Left Side




Date: 7.MAY.2021 04:19:27

802.11n ht20: Band Edge, Right Side




Date: 7.MAY.2021 04:22:03

BLE: Band Edge, Left Side



Date: 20.APR.2021 07:13:59

BLE: Band Edge, Right Side



Date: 20.APR.2021 07:19:50

9 - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

According to RSS-247 §5.2 b):

- b) The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESR3	102453	2020-09-12	2021-09-12
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


Test Data**Environmental Conditions**

Temperature:	25.4~27.4 °C
Relative Humidity:	39~66 %
ATM Pressure:	100.4~101.5 kPa
Tester:	Joe Qiao
Test Date:	2021-04-20~2021-05-28

Test Result: Compliance, *Please refer to the following table and plots**Test Mode: Transmitting*

Test mode	Frequency (MHz)	Power Spectral Density	Limit (dBm/3kHz)
802.11 b	2412	-8.88	≤8
	2437	-8.48	≤8
	2462	-8.87	≤8
802.11 g	2412	-10.73	≤8
	2437	-8.89	≤8
	2462	-9.86	≤8
802.11n ht20	2412	-10.81	≤8
	2437	-10.21	≤8
	2462	-9.69	≤8
BLE	2402	-14.05	≤8
	2440	-12.67	≤8
	2480	-11.12	≤8

Power Spectral Density, 802.11b Low Channel




Date: 28.MAY.2021 08:55:36


Power Spectral Density, 802.11b Middle Channel



Date: 7.MAY.2021 04:27:03


Power Spectral Density, 802.11b High Channel

Date: 7.MAY.2021 04:27:25

Power Spectral Density, 802.11g Low Channel


Date: 7.MAY.2021 04:27:55

Power Spectral Density, 802.11g Middle Channel




Date: 7.MAY.2021 04:28:16

Power Spectral Density, 802.11g High Channel




Date: 7.MAY.2021 04:28:39

Power Spectral Density, 802.11n ht20 Low Channel




Date: 7.MAY.2021 04:29:12

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 7.MAY.2021 04:29:34

Power Spectral Density, 802.11n ht20 High Channel




Date: 7.MAY.2021 04:29:52


Power Spectral Density, BLE Low Channel



Date: 20.APR.2021 07:13:27

Power Spectral Density, BLE Middle Channel

Date: 20.APR.2021 07:17:29

Power Spectral Density, BLE High Channel

Date: 20.APR.2021 07:19:17

******* END OF REPORT *******