# TEST REPORT

of

# FCC Part 15 Subpart C AND CANADA RSS-247

# **Full Modular Approval**

New App	olication;
<b>Product:</b>	Bluetooth 4.1 Module
Brand:	Fanstel
Model:	ВН676СР
<b>Model Difference:</b>	N/A
FCC ID:	X8WBH676CP
IC:	4100A-BH676CP
FCC Rule Part:	§15.247, Cat: DTS
IC Rule Part:	RSS-247 issue 1: May 28, 2015
	RSS-Gen issue 4: 2014
Applicant:	Fanstel Corporation, Taipei

10F-10, No. 79, Sec. 1, Hsin Tai Wu Rd., Hsi-Chih, New Taipei City 221 Taiwan

### Test Performed by: International Standards Laboratory

<Lung-Tan LAB>

\*Site Registration No.

BSMI: SL2-IN-E-0013; MRA TW1036; TAF: 0997; IC: IC4067B-3;

\*Address:

**Address:** 

No. 120, Lane 180, Hsin Ho Rd.

Lung-Tan Dist., Tao Yuan City 325, Taiwan \*Tel: 886-3-407-1718; Fax: 886-3-407-1738

Report No.: ISL-16LR013FC

Issue Date: 2016/02/24

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This report MUST not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory.

Page: 1 of 40

-2 of 40-

FCC ID: X8WBH676CP IC: 4100A-BH676CP

### VERIFICATION OF COMPLIANCE

**Applicant:** Fanstel Corporation, Taipei

**Product Description:** Bluetooth 4.1 Module

**Brand Name:** Fanstel

Model No.: BH676CP

**Model Difference:** N/A

FCC ID: X8WBH676CP

**IC:** 4100A-BH676CP

**Date of test:**  $2016/01/26 \sim 2016/02/18$ 

**Date of EUT Received:** 2016/01/26

## We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:	Dino Chen	Date:	2016/02/24
Prepared By:	Dion Chang / Engineer	Date:	2016/02/24
Approved By:	Eva Kao / Technical Supervisor  Vincent Su / Technical Manager	Date:	2016/02/24



# Version

Version No.	Date	Description	
00	2016/02/24	Initial creation of document	



Report Number: ISL-16LR013FC

## **Table of Contents**

1	GEN	VERAL INFORMATION	6
	1.1	Related Submittal(s) / Grant (s)	7
	1.2	Test Methodology	7
	1.3	Test Facility	7
	1.4	Special Accessories	7
	1.5	Equipment Modifications	7
2	SYS	TEM TEST CONFIGURATION	8
	2.1	EUT Configuration	8
	2.2	EUT Exercise	8
	2.3	Test Procedure	8
	2.4	Configuration of Tested System	9
3	SUM	IMARY OF TEST RESULTS	11
4	DES	CRIPTION OF TEST MODES	11
5	CON	NDUCTED EMISSION TEST	12
	5.1	Standard Applicable:	
	5.2	Measurement Equipment Used:	12
	5.3	EUT Setup:	
	5.4	Measurement Procedure:	
	5.5	Measurement Result:	13
6	<b>PEA</b>	K OUTPUT POWER MEASUREMENT	16
	6.1	Standard Applicable:	
	6.2	Measurement Equipment Used:	
	6.3	Test Set-up:	
	6.4	Measurement Procedure:	
	6.5	Measurement Result:	18
7	6dB	Bandwidth & 99% Bandwidth	
	7.1	Standard Applicable:	19
	7.2	Measurement Equipment Used:	
	7.3	Test Set-up:	
	7.4	Measurement Procedure:	
	7.5	Measurement Result:	19
8	100K	KHZ BANDWIDTH OF BAND EDGES MEASUREMENT	23
	8.1	Standard Applicable:	
	8.2	Measurement Equipment Used:	
	8.3	Test SET-UP:	
	8.4	Measurement Procedure:	
	8.5	Field Strength Calculation:	
	8.6	Measurement Result:	26
9	SPU	RIOUS RADIATED EMISSION TEST	29
	9.1	Standard Applicable	
	9.2	Measurement Equipment Used:	
	9.3	Test SET-UP:	
	9.4	Measurement Procedure:	
	9.5	Field Strength Calculation	
	9.6	Measurement Result:	30





10	Peak	Power Spectral Density	37
		Standard Applicable:	
		Measurement Equipment Used:	
		Test Set-up:	
		Measurement Procedure:	
	10.5	Measurement Result:	37
11	ANT	ENNA REQUIREMENT	4(
		Standard Applicable:	
		Antenna Connected Construction:	



## 1 GENERAL INFORMATION

## General:

Generan	
Product Name:	Bluetooth 4.1 Module
Brand Name:	Fanstel
Model Name:	ВН676СР
Model Difference:	N/A
Power Supply:	3.3Vdc

### IC RSS-Gen:

Product SW version	001version
Product HW version	001version
Radio SW version	001version
Radio HW version	001version
Test SoftWare Version	HCI Tester 2.1.00
RF power setting:	0x25

### Bluetooth:

Frequency Range:	2402 – 2480MHz
Bluetooth Version:	V4.1
Channel number:	40 channels, 2MHz step
Modulation type	Digital Modulation
Modulation type:	GFSK
Tune-up power	+/- 1dBm
Rated Power:	-1.5dBm
Dwell Time:	N/A
Antenna Designation:	PCB Ant, -3.71dBi

**Remark:** The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.1 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID:** <u>X8WBH676CP</u> filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules and **IC:** <u>4100A-BH676CP</u> filing to comply with Industry Canada RSS-247 issue 1: 2015.

### 1.2 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4: 2014, ANSI C63.10: 2013 and RSS-Gen issue 4: 2014. Radiated testing was performed at an antenna to EUT distance 3 meters.

KDB Document: 558074 D01 DTS Meas Guidance v03r04

### 1.3 Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of International Standards Laboratory <Lung-Tan LAB> No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2014. FCC Registration Number is: 872200; Designation Number is: TW1036, Canada Registration Number: 4067B-3.

### 1.4 Special Accessories

Not available for this EUT intended for grant.

### 1.5 Equipment Modifications

Not available for this EUT intended for grant.



### 2 SYSTEM TEST CONFIGURATION

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

### 2.3 Test Procedure

### 2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 5 and 7 of ANSI C63.4: 2014 and RSS-Gen issue 4: 2014. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR 16-1-1 Quasi-Peak and Average detector mode.

### 2.3.2 Radiated Emissions


The EUT is a placed on as turn table which is 0.8 m/1.5m(Frequency above 1GHz) above ground plane. The turn table shall rotate 360 degrees to determine the position of maxi-mum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 6 and 11 of ANSI C63.10: 2013.




## 2.4 Configuration of Tested System

Fig. 2-1 Configuration

## Radiation



## **AC Power Line**



-----remote-----

Tablet PC



**Table 2-1 Equipment Used in Tested System** 

Item	Equipment	Mfr/Brand	Model/ Type No.	Series No.	Data Cable	Power Cord
1	NB	НР	440G1	2CE40911GZ	Non-shield	Non-shield
2	24" LCD Monitor	DELL	ST2420Lb	N/A	Shielded /1.8M	Non-shielded /1.8M
3	Portable Computer	НР	440G1	2CE40911GZ	Non-shielded /0.2M	Non-shielded /1.8M
4	USB mouse	DELL	MOCZUL	N/A	Shielded /1.8M	N/A
5	Printer	LEXMARK	Z43	4101002	Shielded /1.8M	Non-shielded /1.8M
6	Tablet PC	SONY	SGP311	N/A	N/A	N/A

I/O Cable Condition of EUT and Support Units

1/O Cable Condition of EO1 and Support Omis					
<b>Description</b> Path		Cable Length	Cable Type	<b>Connector Type</b>	
	110V (~240V) to				
AC Power Cable	Portable Computer	1.8M	Non-shielded	Plastic Head	
	SPS				
USB mouse Data	USB mouse to				
Cable	Portable Computer	1.8M	Non-shielded	Metal Head	
Cable	USB Port				
	24" LCD Monitor				
Monitor Data Ca-	D-SUB Port to	1.8M	Shielded (with core)	Metal Head	
ble	Portable Computer	1.01V1			
	D-SUB Port				
Printer Data Cable	Printer to Personal	1.8M	Chialdad	Metal Head	
Fillitei Data Cable	Compute USB Port	1.01VI	Shielded	wietai Head	
USB Data Cable	EUT to Portable	1M	Shielded	Motal Hand	
USB Data Cable	Computer USB Port	1 1VI		Metal Head	

**Note:** All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.

**Grounding:** Grounding was in accordance with the manufacturer's requirements and conditions for the intended use.



## 3 SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§15.207(a) RSS-Gen §8.8	AC Power Line Conducted Emission	Compliant
\$15.247(b) (3),(4) RSS-247 issue 1,\$5.4(4)	Peak Output Power/ EIRP	Compliant
\$15.247(a)(2) RSS-247 issue 1, \$5.2(1) RSS-Gen \$6.6	6dB & 99% Power Bandwidth	Compliant
§15.247(d) RSS-247 issue 1, §5.5	100 KHz Bandwidth Of Frequency Band Edges	Compliant
§15.247(d) RSS-247 issue 1, §5.5	Spurious Emission	Compliant
\$15.247(e) RSS-247 issue 1, \$5.2(2)	Peak Power Density	Compliant
§15.203 RSS-GEN 8.3	Antenna Requirement	Compliant

### 4 DESCRIPTION OF TEST MODES

The EUT has been tested under engineering operating condition.

Test program used to control the EUT for staying in continuous transmitting mode is programmed.

BT LE mode: Channel low (2402MHz), mid (2442MHz) and high (2480MHz) are chosen for full testing.



### 5 CONDUCTED EMISSION TEST

### **5.1** Standard Applicable:

According to §15.207 and RSS-Gen §7.2.4, frequency range within 150KHz to 30MHz shall not exceed the Limit table as below.

	Limits		
Frequency range	dB(uV)		
MHz	Quasi-peak	Average	
0.15 to 0.50	66 to 56	56 to 46	
0.50 to 5	56	46	
5 to 30	60	50	

Note

1. The lower limit shall apply at the transition frequencies

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

**5.2** Measurement Equipment Used:

	AC Power Line Test Site							
<b>EQUIPMENT</b>	MFR	MODEL	SERIAL	LAST	CAL DUE.			
TYPE		NUMBER	NUMBER	CAL.				
Conduction 04-3 Cable	WOKEN	CFD 300-NL	Conduction 04 -3	07/28/2015	07/27/2016			
EMI Receiver 17	Rohde & Schwarz	ESCI 7	100887	09/08/2015	09/07/2016			
LISN 18	ROHDE & SCHWARZ	ENV216	101424	02/11/2016	02/10/2017			
LISN 19	ROHDE & SCHWARZ	ENV216	101425	03/12/2015	03/11/2016			
Test Software	Farad	EZEMC Ver:ISL-03A2	N/A	N/A	N/A			

### **5.3 EUT Setup:**

- 1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4: 2014.
- 2. The AC/DC Power adaptor of EUT was plug-in LISN. The EUT was placed flushed with the rear of the table.
- 3. The LISN was connected with 120Vac/60Hz power source.



### **5.4** Measurement Procedure:

- 1. The EUT was placed on a table which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured were complete.

### **5.5** Measurement Result:

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.


Note: Refer to next page for measurement data and plots.



Report Number: ISL-16LR013FC

## AC POWER LINE CONDUCTED EMISSION TEST DATA

Operation Mode:	Operation Mode	Test Date:	2016/02/15
Test By:	Lake		



Limit: CISPR22 Class B Conduction

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.394	26.82	26.20	9.69	36.51	57.98	-21.47	35.89	47.98	-12.09
2	1.282	19.12	13.83	9.73	28.85	56.00	-27.15	23.56	46.00	-22.44
3	1.414	20.67	13.65	9.73	30.40	56.00	-25.60	23.38	46.00	-22.62
4	1.730	23.31	19.08	9.75	33.06	56.00	-22.94	28.83	46.00	-17.17
5	1.954	18.94	12.91	9.76	28.70	56.00	-27.30	22.67	46.00	-23.33
6	2.834	20.32	11.34	9.78	30.10	56.00	-25.90	21.12	46.00	-24.88






Report Number: ISL-16LR013FC



Address:No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist., Tao Yuan City 325, Taiwan. Tel:03-4071718



Limit: CISPR22 Class B Conduction

No.	Frequency (MHz)	QP_R (dBuV)	AVG_R (dBuV)	Correct Factor (dB)	QP Emission (dBuV)	QP Limit (dBuV)	QP Margin (dB)	AVG Emission (dBuV)	AVG Limit (dBuV)	AVG Margin (dB)
1	0.386	23.27	17.66	9.67	32.94	58.15	-25.21	27.33	48.15	-20.82
2	1.590	18.35	13.96	9.73	28.08	56.00	-27.92	23.69	46.00	-22.31
3	1.738	23.19	16.55	9.73	32.92	56.00	-23.08	26.28	46.00	-19.72
4	2.278	16.22	11.76	9.74	25.96	56.00	-30.04	21.50	46.00	-24.50
5	10.594	20.34	17.36	9.96	30.30	60.00	-29.70	27.32	50.00	-22.68
6	21.122	31.91	27.13	10.18	42.09	60.00	-17.91	37.31	50.00	-12.69



### 6 PEAK OUTPUT POWER/ERIP MEASUREMENT

## **6.1 Standard Applicable:**

According to  $\S15.247(b)(3),(4)(b)$ 

- (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
- (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (c) Operation with directional antenna gains greater than 6 dBi.
- (1) Fixed point-to-point operation:
- (i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.
- (ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

### According to RSS-247 issue 1,§5.4

(4) For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.


As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.



**6.2** Measurement Equipment Used:

Conducted Emission Test Site							
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.		
TYPE		NUMBER	NUMBER	CAL.			
Power Meter 05	Anritsu	ML2495A	1116010	07/29/2015	07/28/2016		
Power Sensor 05	Anritsu	MA2411B	34NKF50	07/29/2015	07/28/2016		
Power Sensor 06	DARE	RPR3006W	13I00030SNO3 3	11/03/2015	11/02/2016		
Power Sensor 07	DARE	RPR3006W	13I00030SNO3 4	11/03/2015	11/02/2016		
Temperature Chamber	KSON	THS-B4H100	2287	06/05/2015	06/04/2016		
DC Power supply	ABM	8185D	N/A	09/05/2015	09/04/2016		
AC Power supply	EXTECH	CFC105W	NA	12/26/2015	12/25/2016		
Attenuator	Woken	Watt-65m3502	11051601	NA	NA		
Splitter	MCLI	PS4-199	12465	12/26/2015	12/25/2017		
Spectrum analyzer	Agilent	N9030A	MY51360021	10/02/2015	10/01/2016		
Test Sofware	DARE	Radimation Ver:2013.1.23	NA	NA	NA		

## 6.3 Test Set-up:



### **6.4** Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter
- 3. Record the max. reading.
- 4. Repeat above procedures until all frequency measured were complete.



## **6.5** Measurement Result:

Frequency (MHz)	Peak Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
Low	-2.92	0.00	-2.92	0.00051	1
Mid	-2.41	0.00	-2.41	0.00057	1
High	-2.18	0.00	-2.18	0.00061	1

Offset: 1dB



## 7 6dB Bandwidth & 99% Bandwidth

### 7.1 Standard Applicable:

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz,2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

According to RSS-247 issue 1, §5.2

(1) The minimum 6 dB bandwidth shall be 500 kHz.

### 7.2 Measurement Equipment Used:

Refer to section 6.2 for details.

### 7.3 Test Set-up:

Refer to section 6.3 for details.

### 7.4 Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW=100KHz, VBW = 3\*RBW, Span= cover the complete power envelope of the signal of the UUT Sweep=auto
- 4. Mark the peak frequency and –6dB (upper and lower) frequency.
- 5. Repeat above procedures until all frequency measured were complete.

#### 7.5 Measurement Result:

Frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Bandwidth (KHz)	Result
Low	0.6801	1.2338	> 500	PASS
Mid	0.6698	1.2317	> 500	PASS
High	0.6782	1.2392	> 500	PASS

Note: Refer to next page for plots.

類智科技股份有限公司 International Standards Laboratory

FCC ID: X8WBH676CP IC: 4100A-BH676CP

### 6dB Bandwidth Test Data CH-Low



### 6dB Band Width Test Data CH-Mid




類智科技股份有限公司 International Standards Laboratory

FCC ID: X8WBH676CP IC: 4100A-BH676CP

## 6dB Band Width Test Data CH-High



### 99% Bandwidth Test Data CH-Low





### 99% Band Width Test Data CH-Mid



99% Band Width Test Data CH-High





### 8 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT

### 8.1 Standard Applicable:

According to §15.247(c), in any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

### According to RSS-247 issue 1, §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digi-tally modulated device is operating, the RF power that is produced shall be at least 20 dB be-low that in the 100 kHz bandwidth within the band that contains the highest level of the de-sired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.



Report Number: ISL-16LR013FC

## 8.2 Measurement Equipment Used:

## **8.2.1** Conducted Emission at antenna port:

Refer to section 6.2 for details.

### 8.2.2 Radiated emission:

	Ch	amber 14(966)	)		
EQUIPMENT	MFR	MODEL	SERIAL	LAST	CAL DUE.
TYPE		NUMBER	NUMBER	CAL.	
Spectrum Analyzer 21(26.5GHz)	Agilent	N9010A	MY49060537	07/29/2015	07/28/2016
Spectrum Analyzer 20(6.5GHz)	Agilent	E4443A	MY48250315	05/21/2015	05/20/2016
Spectrum Analyzer 22(43GHz)	R&S	FSU43	100143	05/07/2015	05/06/2016
Loop Antenna9K-30M	A.H.SYSTEM	SAS-564	294	06/17/2015	06/16/2017
Bilog Antenna30-1G	Schaffner	CBL 6112D	37873	06/16/2015	06/15/2016
Horn antenna1-18G	ETS	3117	00066665	11/30/2015	11/29/2016
Horn antenna26-40G(05)	Com-power	AH-640	100A	01/21/2015	01/20/2017
Horn antenna18-26G(04)	Com-power	AH-826	081001	07/24/2015	07/23/2017
Preamplifier9-1000M	HP	8447D	NA	03/12/2015	03/11/2016
Preamplifier1-18G	MITEQ	AFS44-001018 00-25-10P-44	1329256	07/28/2015	07/27/2016
Preamplifier1-26G	EM	EM01M26G	NA	03/11/2015	03/10/2016
Preamplifier26-40G	MITEQ	JS-26004000-2 7-5A	818471	07/23/2015	07/22/2017
Cable1-18G	HUBER SUHNER	Sucoflex 106	NA	11/25/2015	11/24/2016
Cable UP to 1G	HUBER SUHNER	RG 214/U	NA	10/02/2015	10/01/2016
SUCOFLEX 1GHz~40GHz cable	HUBER SUHNER	Sucoflex 102	27963/2&3742 1/2	11/03/2015	11/02/2017
2.4G Filter	Micro-Tronics	Brm50702	76	12/26/2015	12/25/2016
Test Software	Audix	E3 Ver:6.12023	N/A	N/A	N/A




### 8.3 Test SET-UP:

## 8.3.1 Conducted Emission at antenna port:


Refer to section 6.3 for details.

### 8.3.2 Radiated emission:

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



-26 of 40-

FCC ID: X8WBH676CP IC: 4100A-BH676CP

#### **8.4** Measurement Procedure:

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set center frequency of spectrum analyzer = operating frequency.
- 4. Set the spectrum analyzer as RBW, VBW=100KHz, Span=25MHz, Sweep = auto
- 5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
- 6. Repeat above procedures until all frequency measured were complete.

### **8.5** Field Strength Calculation:

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

#### **8.6** Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.



-27 of 40- FCC ID: X8WBH676CP

IC: 4100A-BH676CP

**Report Number: ISL-16LR013FC** 

### **Radiated Emission:**

Operation Mode TX CH Low Test Date 2016/02/15 Fundamental Frequency 2402 MHz Test By Lake Temperature 25  $^{\circ}$ C Humidity 60  $^{\circ}$ 

No	Freq	Reading	Factor	Level	Limit	Over Limit	Remark	Pol
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		V/H
1	2390.00	47.60	-10.74	36.86	74.00	-37.14	Peak	VERTICAL
2	2400.00	45.76	-10.71	35.05	44.04	-8.54	Peak	VERTICAL
3	2401.79	74.74	-10.70	64.04	F	-	Peak	VERTICAL
1	2390.00	48.19	-10.74	37.45	74.00	-36.55	Peak	HORIZONTAL
2	2400.00	48.86	-10.71	38.15	51.86	-13.17	Peak	HORIZONTAL
3	2402.26	82.56	-10.70	71.86	F		Peak	HORIZONTAL

#### Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- $_{\rm 4}$  Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: "F" denotes fundamental frequency



-28 of 40- FCC ID: X8WBH676CP

IC: 4100A-BH676CP

**Report Number: ISL-16LR013FC** 

Operation Mode TX CH High Test Date 2016/02/15 Fundamental Frequency 2480 MHz Test By Lake Temperature 25  $^{\circ}$ C Humidity 60  $^{\circ}$ 

No	Freq	Reading	Factor	Level	Limit	Over Limit	Remark	Pol
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		V/H
1	2483.50	45.08	-10.40	34.68	74.00	-39.32	Peak	VERTICAL
2	2483.58	47.77	-10.40	37.37	74.00	-36.63	Peak	VERTICAL
1	2483.50	44.84	-10.40	34.44	74.00	-39.56	Peak	HORIZONTAL
2	2493.20	47.92	-10.38	37.54	74.00	-36.46	Peak	HORIZONTAL

#### Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Note: "F" denotes fundamental frequency



### 9 SPURIOUS RADIATED EMISSION TEST

### 9.1 Standard Applicable

According to §15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

According to RSS-247 issue 1, §5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digi-tally modulated device is operating, the RF power that is produced shall be at least 20 dB be-low that in the 100 kHz bandwidth within the band that contains the highest level of the de-sired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### 9.2 Measurement Equipment Used:

### 9.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.

### 9.2.2 Radiated emission:

Refer to section 7.2 for details.

#### 9.3 Test SET-UP:

### 9.3.1 Conducted Emission at antenna port:

Refer to section 6.3 for details.

### 9.3.2 Radiated emission:

Refer to section 7.3 for details.

-30 of 40- FCC ID: X8WBH676CP

IC: 4100A-BH676CP

### 9.4 Measurement Procedure:

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- 4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 7. Repeat above procedures until all frequency measured were complete.

## 9.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where	FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
	RA = Reading Amplitude	AG = Amplifier Gain
	AF = Antenna Factor	

### 9.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.



-31 of 40- FCC ID: X8WBH676CP

IC: 4100A-BH676CP

### **Radiated Spurious Emission Measurement Result (below 1GHz)**

Operation Mode TX CH Low Test Date 2016/02/15

Fundamental Frequency 2402 MHz Test By Lake Temperature  $25\ ^{\circ}\text{C}$  Pol Ver./Hor

Humidity 60 %

No	Freq	Reading	Factor	Level	Limit	Over Limit	Remark	Pol
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		V/H
1	106.63	48.15	-16.09	32.06	43.50	-11.44	Peak	VERTICAL
2	286.08	42.26	-11.62	30.64	46.00	-15.36	Peak	VERTICAL
3	398.60	36.63	-9.46	27.17	46.00	-18.83	Peak	VERTICAL
4	499.48	33.72	-7.90	25.82	46.00	-20.18	Peak	VERTICAL
5	597.45	27.52	-6.06	21.46	46.00	-24.54	Peak	VERTICAL
6	833.16	30.39	-2.44	27.95	46.00	-18.05	Peak	VERTICAL
1	96.93	46.01	-17.68	28.33	43.50	-15.17	Peak	HORIZONTAL
2	281.23	40.77	-11.75	29.02	46.00	-16.98	Peak	HORIZONTAL
3	398.60	35.34	-9.46	25.88	46.00	-20.12	Peak	HORIZONTAL
4	456.80	30.86	-8.31	22.55	46.00	-23.45	Peak	HORIZONTAL
5	497.54	30.88	-7.91	22.97	46.00	-23.03	Peak	HORIZONTAL
6	898.15	25.19	-1.39	23.80	46.00	-22.20	Peak	HORIZONTAL

#### Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.



-32 of 40- FCC ID: X8WBH676CP

IC: 4100A-BH676CP

## Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode TX CH Mid Test Date 2016/02/15 Fundamental Frequency 2442MHz Temperature 25  $^{\circ}$ C Pol Ver./Hor

Humidity 60 %

No	Freq	Reading	Factor	Level	Limit	Over Limit	Remark	Pol
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		V/H
1	71.71	41.97	-15.23	26.74	40.00	-13.26	Peak	VERTICAL
2	106.63	48.73	-16.09	32.64	43.50	-10.86	Peak	VERTICAL
3	285.11	42.48	-11.65	30.83	46.00	-15.17	Peak	VERTICAL
4	398.60	36.46	-9.46	27.00	46.00	-19.00	Peak	VERTICAL
5	499.48	33.69	-7.90	25.79	46.00	-20.21	Peak	VERTICAL
6	832.19	30.68	-2.46	28.22	46.00	-17.78	Peak	VERTICAL
1	96.93	45.60	-17.68	27.92	43.50	-15.58	Peak	HORIZONTAL
2	191.99	39.88	-14.74	25.14	43.50	-18.36	Peak	HORIZONTAL
3	399.57	35.74	-9.45	26.29	46.00	-19.71	Peak	HORIZONTAL
4	460.68	31.44	-8.26	23.18	46.00	-22.82	Peak	HORIZONTAL
5	497.54	30.34	-7.91	22.43	46.00	-23.57	Peak	HORIZONTAL
6	905.91	25.11	-1.26	23.85	46.00	-22.15	Peak	HORIZONTAL

### Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.



-33 of 40- FCC ID: X8WBH676CP

IC: 4100A-BH676CP

## Radiated Spurious Emission Measurement Result (below 1GHz)

Operation Mode TX CH High Test Date 2016/02/15 Fundamental Frequency 2480MHz Test By Lake Temperature 25  $^{\circ}$ C Pol Ver./Hor

Humidity 60 %

No	Freq	Reading	Factor	Level	Limit	Over Limit	Remark	Pol
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		V/H
1	106.63	48.21	-16.09	32.12	43.50	-11.38	Peak	VERTICAL
2	286.08	42.06	-11.62	30.44	46.00	-15.56	Peak	VERTICAL
3	398.60	37.38	-9.46	27.92	46.00	-18.08	Peak	VERTICAL
4	499.48	33.28	-7.90	25.38	46.00	-20.62	Peak	VERTICAL
5	833.16	30.81	-2.44	28.37	46.00	-17.63	Peak	VERTICAL
6	900.09	26.45	-1.37	25.08	46.00	-20.92	Peak	VERTICAL
1	96.93	45.66	-17.68	27.98	43.50	-15.52	Peak	HORIZONTAL
2	193.93	40.86	-14.80	26.06	43.50	-17.44	Peak	HORIZONTAL
3	285.11	40.55	-11.65	28.90	46.00	-17.10	Peak	HORIZONTAL
4	398.60	35.70	-9.46	26.24	46.00	-19.76	Peak	HORIZONTAL
5	499.48	30.89	-7.90	22.99	46.00	-23.01	Peak	HORIZONTAL
6	851.59	26.33	-2.15	24.18	46.00	-21.82	Peak	HORIZONTAL

### Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.



-34 of 40- FCC ID: X8WBH676CP

IC: 4100A-BH676CP

**Report Number: ISL-16LR013FC** 

## Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH Low Test Date 2016/02/15 Fundamental Frequency 2402MHz Test By Lake Temperature 25  $^{\circ}$ C Pol Ver./Hor

Humidity 60 %

No	Freq	Reading	Factor	Level	Limit	Over Limit	Remark	Pol
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		V/H
1	4804.00	47.17	-3.29	43.88	74.00	-30.12	Peak	VERTICAL
2	7206.00	44.67	4.00	48.67	74.00	-25.33	Peak	VERTICAL
1	4804.00	56.55	-3.29	53.26	74.00	-20.74	Peak	HORIZONTAL
2	7206.00	47.60	4.00	51.60	74.00	-22.40	Peak	HORIZONTAL

#### Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



-35 of 40- FCC ID: X8WBH676CP

IC: 4100A-BH676CP

**Report Number: ISL-16LR013FC** 

### Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH Mid Test Date 2016/02/15 Fundamental Frequency 2442MHz Temperature 25  $^{\circ}$ C Pol Ver./Hor

Humidity 60 %

No	Freq	Reading	Factor	Level	Limit	Over Limit	Remark	Pol
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		V/H
1	4885.00	46.62	-3.09	43.53	74.00	-30.47	Peak	VERTICAL
2	7326.00	42.87	4.23	47.10	74.00	-26.90	Peak	VERTICAL
1	4884.00	55.49	-3.10	52.39	74.00	-21.61	Peak	HORIZONTAL
2	7326.00	46.82	4.23	51.05	74.00	-22.95	Peak	HORIZONTAL

### Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- <sup>2</sup> Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting: 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



-36 of 40- FCC ID: X8WBH676CP

IC: 4100A-BH676CP

**Report Number: ISL-16LR013FC** 

## Radiated Spurious Emission Measurement Result (above 1GHz)

Operation Mode TX CH High Test Date 2016/02/15 Fundamental Frequency 2480MHz Temperature 25  $^{\circ}$ C Pol Ver./Hor

Humidity 60 %

No	Freq	Reading	Factor	Level	Limit	Over Limit	Remark	Pol
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB		V/H
1	4960.00	46.10	-2.94	43.16	74.00	-30.84	Peak	VERTICAL
2	7440.00	43.21	4.42	47.63	74.00	-26.37	Peak	VERTICAL
1	4960.00	54.31	-2.94	51.37	74.00	-22.63	Peak	HORIZONTAL
2	7440.00	44.68	4.42	49.10	74.00	-24.90	Peak	HORIZONTAL

### Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- Measurement of data within this frequency range shown "-" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.



## 10 Peak Power Spectral Density

### 10.1 Standard Applicable:

According to §15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

According to RSS-247 issue 1, §5.2

(2)The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

### **10.2** Measurement Equipment Used:

Refer to section 6.2 for details.

### 10.3 Test Set-up:

Refer to section 6.3 for details.

### **10.4 Measurement Procedure:**

- 1. Place the EUT on the table and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 3. Set the spectrum analyzer as RBW =100KHz, VBW = 300KHz, Span =5 to 30% greater than emission BW, Sweep=Auto
- 4. Record the max. reading.
- 5. Repeat above procedures until all frequency measured were complete.

### 10.5 Measurement Result:

Frequency MHz	Power Density Reading (dBm)	Maximum Limit (dBm)
Low	-16.941	8
Mid	-17.395	8
High	-16.84	8

Offset: 1dB



## **Power Spectral Density Test Plot (CH-Low)**




**Power Spectral Density Test Plot (CH-Mid)** 





**Power Spectral Density Test Plot (CH-High)** 





## 11 ANTENNA REQUIREMENT

## 11.1 Standard Applicable:

According to §15.203, Antenna requirement.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

According to RSS-GEN 7.1.2, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. Testing shall be performed using the highest-gain antenna of each combination of transmitter and antenna type for which certification is being sought, with the transmitter output power set at the maximum level. Any antenna of the same type and having equal or lesser gain as an antenna that had been successfully tested for certification with the transmitter, will also be considered certified with the transmitter, and may be used and marketed with the transmitter. The manufacturer shall include with the application for certification a list of acceptable antenna types to be used with the transmitter.

When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. Any antenna gain in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power before using the power limits specified in RSS-210 or RSS-310 for devices of RF output powers of 10 milliwatts or less. For devices of output powers greater than 10 milliwatts, except devices subject to RSS-210 Annex 8 (Frequency Hopping and Digital Modulation Systems Operating in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz Bands) or RSS-210 Annex 9 (Local Area Network Devices), the total antenna gain shall be ad

ded to the measured RF output power before using the specified power limits. For devices subject to RSS-210 Annex 8 or Annex 9, the antenna gain shall not be added.

### 11.2 Antenna Connected Construction:

The directional gins of antenna used for transmitting is -3.71dBi, and this is fixed PCB antenna type and no consideration of re-placement by user. Please see EUT photo and antenna spec. for details.