

## RF Exposure Evaluation Report

**FCC ID** : X8Y600  
**Equipment** : Swiftpoint G4 Computer Mouse  
**Brand Name** : SWIFTPOINT  
**Model Name** : 600 ; 601 ; 602 ; 603  
**Applicant** : Swiftpoint Limited  
77 Montreal St. Christchurch 8023 New Zealand  
**Manufacturer** : Swiftpoint Limited  
77 Montreal St. Christchurch 8023 New Zealand  
**Standard** : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Jul. 26, 2018, and testing was started from Aug. 10, 2018 and completed on Sep. 11, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2014 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

## Table of Contents

<b>HISTORY OF THIS TEST REPORT .....</b>	<b>3</b>
<b>1. GENERAL DESCRIPTION .....</b>	<b>4</b>
1.1. EUT General Information .....	4
1.2. Table for Multiple Listing .....	4
1.3. Testing Location Information.....	4
<b>2. RF EXPOSURE EVALUATION .....</b>	<b>5</b>
1.4. Applicable Standard .....	5
1.5. SAR evaluation.....	5

### Photographs of EUT V01



## HISTORY OF THIS TEST REPORT

Reviewed by: Sam Tsai

**Report Producer: Debby Hung**

## 1. GENERAL DESCRIPTION

### 1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz SRD	2400-2483.5	2402-2480	GFSK
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)

### 1.2. Table for Multiple Listing

The brand/model names in the following table are all refer to the identical product.

Brand Name	Model Name	BUTTON	Description
SWIFTPONT	600	3	All the models are electrically identical, the difference model for difference brand and button served as marketing strategy.
SWIFTPONT	601	2	
SWIFTPONT	602	2	
SWIFTPONT	603	2	

### 1.3. Testing Location Information

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL : 886-3-327-3456 FAX : 886-3-327-0973	
Test site Designation No. TW1190 with FCC.			
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.) TEL : 886-3-656-9065 FAX : 886-3-656-9085	
Test site Designation No. TW0006 with FCC.			

## 2. RF EXPOSURE EVALUATION

### 1.4. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

### 1.5. SAR evaluation

1. Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq$  50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$$

$$[\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

♦  $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz

♦ Power and distance are rounded to the nearest mW and mm before calculation

♦ The result is rounded to one decimal place for comparison

Max. Power (dBm)	Gain (dBi)	Tolerance (dB)	Tune-up Max. Power (dBm)	Max. Power (mW)	Test Distance (mm)	Frequency (GHz)	Exclusion Thresholds
-17.58	-0.16	0.5	-18.26	0.05	5	2.44	0.02

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is  $0.02 < 7.5$ , RF exposure evaluation is not required.

—————THE END—————