

FCC EVALUATION REPORT FOR CERTIFICATION

Applicant : 3H VISION Co., Ltd.

427 Gumi 4Danji, Bongsan-ri, Sanding-myeon,
Cumi-City, Gyeong-buk

Attn: Mr. Tae-Eun Kwon / Section chief

Date of Issue : March 24, 2010

Order Number: GETEC-C1-10-049

Test Report Number: GETEC-E3-10-024

Test Site: Gumi College EMC Center

FCC Registration Number: (100749, 443957)

FCC ID.: X93WC1000

Applicant: 3H VISION Co., Ltd.

Rule Part(s) : FCC Part 15 Subpart B

Equipment Class : Class B computing device peripheral (JBP)

EUT Type : USB camera module

Type of Authority : Certification

Model Name : WC-1000

This equipment has been shown to be in compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2003

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Tested by,

Soon-Hoon Jeong
Soon-Hoon Jeong, Engineer
GUMI College EMC center

Reviewed by,

Jae-Hoon Jeong
Jae-Hoon Jeong, Senior Engineer
GUMI College EMC center



CONTENTS

1. GENERAL INFORMATION	3
2. INTRODUCTION	4
3. PRODUCT INFORMATION	5
3.1 DESCRIPTION OF EUT.....	5
3.2 SUPPORT EQUIPMENT / CABLES USED	6
3.3 MODIFICATION ITEM(S)	6
4. DESCRIPTION OF TESTS.....	7
4.1 TEST CONDITION.....	7
4.2 CONDUCTED EMISSION	8
4.3 RADIATED EMISSION	9
5. CONDUCTED EMISSION.....	10
5.1 OPERATING ENVIRONMENT	10
5.2 TEST SET-UP	10
5.3 MEASUREMENT UNCERTAINTY.....	10
5.4 LIMIT	11
5.5 TEST EQUIPMENT USED.....	11
5.6 TEST DATA FOR CONDUCTED EMISSION	11
6. RADIATED EMISSION	14
6.1 OPERATING ENVIRONMENT	14
6.2 TEST SET-UP	14
6.3 MEASUREMENT UNCERTAINTY.....	14
6.4 LIMIT	15
6.5 TEST EQUIPMENT USED.....	15
6.6 TEST DATA FOR RADIATED EMISSION	16
7. SAMPLE CALCULATIONS.....	17
7.1 EXAMPLE 1 :	17
7.2 EXAMPLE 2 :	17
8. RECOMMENDATION & CONCLUSION.....	18

APPENDIX A – ATTESTATION STATEMENT

APPENDIX B – ID SAMPLE LABEL & LOCATION

APPENDIX C – BLOCK DIAGRAM

APPENDIX D – TEST SET-UP PHOTOGRAPHS

APPENDIX E – EXTERNAL PHOTOGRAPHS

APPENDIX F – USER’S MANUAL



Scope: Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and / or unintentional radiators for compliance with technical rules and regulations of the Federal Communications Commission.

1. General Information

Applicant: 3H VISION Co., Ltd.

Applicant Address: 427 Gumi 4Danji, Bongsan-ri, Sanding-myeon, Cumi-City, Gyeong-buk

Manufacturer: 3H VISION Co., Ltd.

Manufacturer Address: 427 Gumi 4Danji, Bongsan-ri, Sanding-myeon, Cumi-City, Gyeong-buk

Contact Person: Mr. Tae-Eun Kwon / Section chief

Tel Number: +82-54-474-1400 **Fax Number:** +82-54-474-1420

- **FCC ID.** X93WC1000
- **EUT Type** USB camera module
- **Model Name** WC-1000
- **Serial Number** Prototype
- **Rule Part(s)** FCC Part 15 Subpart B
- **Type of Authority** Certification
- **Test Procedure(s)** ANSI C63.4 (2003)
- **Dates of Test** March 8, 2010
- **Place of Test** Gumi College EMC Center (FCC Registration Number: 100749, 443957)
407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.
- **Test Report Number** GETEC-E3-10-024
- **Dates of Issue** March 24, 2010

EUT Type: USB camera module

FCC ID.: X93WC1000




2. Introduction

The measurement procedure described in American National Standard for Methods of Measurement of Radio-Nose Emissions From Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ASNI C63.4-2003) was used in determining radiated and conducted emissions emanating from **3H VISION Co., Ltd. USB camera module (Model Name: WC-1000)**

These measurement tests were conducted at **Gumi College EMC Center**.

The site address is 407, Bugok-dong, Gumi-si, Gyeongbuk, Korea.

This test site is one of the highest point of Gumi 1 college at about 200 km away from Seoul city and 40 km away from Daegu city. It is located in the valley surrounded by mountains in all directions where ambient radio signal conditions are quiet and a favorable area to measure the radio frequency interference on open field test site for the computing and ISM devices manufactures. The detailed description of the measurement facility was found to be in compliance with the requirements of §2.948 according to ANSI C63.4 (2003)



GUMI COLLEGE EMC CENTER
407, Bugok-dong, Gumi-si,
Gyeongbuk 730-711, Korea.
Tel: +82-54-440-1195
Fax: +82-54-440-1199

Fig 1. The map above shows the Gumi College in vicinity area.



3. Product Information

3.1 Description of EUT

The Equipment under Test (EUT) is the **3H VISION Co., Ltd. USB camera module (Model Name: WC-1000)**

FCC ID.: X93WC1000

-. Rated Voltage	: DC 5 V
-. Feature	: YUV 8 Bit Digital Data Output Support UVC. LED Indicator Color:Red High Speed USB 2.0 Interface Auto Exposure, Auto White Balance, Color Correction, Hue, Edge Enhancement
-. Resolution	: 1 280 × 1 024 (1.3 M)
-. Dimension	: 60 mm(W) × 9 mm(H) × 13 mm(D)
-. Image Sensor	: Image format: S5K6AAFX13(SAMSUNG LSI), 1/6", 1.3 M, COB TYPE Effective resolution: 1 280 × 1 024 Active pixel size: 1 284 × 1 028 Pixel size: 1.75 cm Shutter type: Electronic rolling shutter Package dimension: 4 560cm × 4 580 cm Max frame rate: 15 fpe @ SXGA, 30 fpe @ VGA Max pixel clock frequency 56 MHz Color filter: RGB Bayer pattern ADC accuracy: 10 bit



3.2 Support Equipment / Cables used

3.2.1 Used Support Equipment

Description	Manufacturer	Model Name	S/N & FCC ID.
Notebook PC	Samsung	NT-Q45	S/N: CNBA4300168AI00682D5800 FCC ID.: DoC
USB mouse	Samsung	M-U48a	S/N: LZAO4869182 FCC ID: -

See "Appendix D – Test Setup Photographs" for actual system test set-up

3.2.2 System configuration

Description	Manufacturer	Model Name	S/N & FCC ID.
None	-	-	-

3.2.3 Used Cable(s)

Cable Name	Condition	Description
USB cable	Connected to the EUT and notebook PC	1.80 m shielded

3.3 Modification Item(s)

- None



4. Description of tests

4.1 Test Condition

The EUT was installed, arranged and operated in a manner that is most representative of equipment as typically used. The measurements were carried out while varying operating modes and cable positions within typically arrangement to determine maximum emission level.

The representative and worst test mode(s) were noted in the test report.

- Test Voltage / Frequency : AC 120 V / 60 Hz
- Test Mode(s)
 - . Normal operating mode



4.2 Conducted Emission

The Line conducted emission test facility is inside a 4 m × 8 m × 2.5 m shielded enclosure. (FCC Registration No.: 100749)

The EUT was placed on a non-conducting 1.0 m by 1.5 m table, which is 0.8 m in height and 0.4 m away from the vertical wall of the shielded enclosure.

The EUT is powered from the Rohde & Schwarz LISN (ESH2-Z5) and the support equipment is powered from the Rohde & Schwarz LISN (ESH3-Z5). Powers to the LISN are filtered by high-current high insertion loss power line filter.

Sufficient time for EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

The RF output of the LISN was connected to the EMI test receiver (Rohde & Schwarz, ESCS30).

The EMI test receiver was scanned from 150 kHz to 30 MHz with 20 ms sweep time to determine the frequency producing the maximum EME from the EUT. The frequency producing the maximum level was re-examined using Quasi-Peak mode of the EMI test receiver.

The bandwidth of Quasi-peak mode was set to 9 kHz. Each emission was maximized consistent with typical applications by varying the configuration of the test sample. Interface cables were connected to the available interface ports of the test unit. The effect of varying the position of cables was investigated to find the configuration that produces maximum diagram emission. Excess cable lengths were bundled at center with 30 cm ~ 40 cm.

Each EME reported was calibrated using the R/S signal generator




Fig 2. Impedance of LISN



4.3 Radiated Emission

Preliminary measurements were conducted 3 m semi anechoic chamber using broadband antennas to determine the frequency producing the maximum EME. Appropriate precaution was taken to ensure that all EME from the EUT were maximized and investigated. The technology configuration, mode of operation and turntable azimuth with respect to antenna was note for each frequency found.

Final measurements were made 3 m chamber (FCC registration No.: 443957) and/or 10 m OATS (FCC registration No.: 100749).

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition.

Each frequency found during pre-scan measurements was re-examined and investigated using EMI test receiver. The detector function was set to CISPR quasi-peak mode average mode and the bandwidth of the receiver was set to 120 kHz or 1 MHz depending on the frequency or type of signal.

The EUT, support equipment and interconnecting cables were reconfigured to the setup producing the maximum emission for the frequency and were placed on top of a 0.8 m high non-metallic 1.0 m × 1.5 m table.

The turntable containing the test sample was rotated; the antenna height was varied 1 to 4 meter and stopped at the azimuth or height producing the maximum emission.

Each EME reported was calibrated using the R/S signal generator




Fig 3. Dimensions of test site.



5. Conducted Emission

5.1 Operating Environment

Temperature : 28 °C
Relative Humidity : 40 % R.H.

5.2 Test Set-up

The conducted emission measurements were performed in the shielded room.

The EUT was placed on wooden table, 0.8 m heights above the floor, 0.4 m from the reference ground plane (GRP) wall and 0.8 m from AMN.

AMN is bonded on horizontal reference ground plane.

The ground plane, which was electrically bonded to the shield room, ground system and all power lines entering the shield room, were filtered.

5.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement.”

The measurement uncertainty was given with a confidence of 95 %.

Test Items	Uncertainty	Remark
Conducted emission (9 kHz ~ 150 kHz)	± 2.69 dB	Confidence levels of 95 % ($k = 2$)
Conducted emission (150 kHz ~ 30 MHz)	± 4.16 dB	Confidence levels of 95 % ($k = 2$)



5.4 Limit

RFI Conducted	FCC Limit(dB μ V/m) Class B	
Freq. Range	Quasi-Peak	Average
150 kHz ~ 0.5 MHz	66 ~ 56*	56 ~ 46*
0.5 MHz ~ 5 MHz	56	46
5 MHz ~ 30 MHz	60	50

*Limits decreases linearly with the logarithm of frequency.

5.5 Test Equipment used


Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESCS30	Rohde & Schwarz	EMI test receiver	839809/003	12. 10. 2010
■ - ESH3-Z5	Rohde & Schwarz	LISN	838979/020	12. 10. 2010
■ - ESH2-Z5	Rohde & Schwarz	LISN	829991/009	12. 10. 2010
□ - ISN T8	TESEQ. GmbH	ISN	24568	10. 16. 2010

5.6 Test data for Conducted Emission

- Test Date : March 8, 2010
- Resolution Bandwidth : 9 kHz
- Frequency Range : 0.15 MHz ~ 30 MHz



Voltage with 4-Line-LISN L1



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.150000	42.9	1000.000	9.000	GND	L1	10.0	23.1	66.0	
0.195000	38.4	1000.000	9.000	GND	L1	10.0	25.3	63.7	
0.270000	46.4	1000.000	9.000	GND	L1	10.0	14.5	60.9	
0.405000	38.0	1000.000	9.000	GND	L1	10.0	19.6	57.6	
0.540000	34.1	1000.000	9.000	GND	L1	10.0	21.9	56.0	
0.675000	32.3	1000.000	9.000	GND	L1	10.0	23.7	56.0	
0.945000	31.9	1000.000	9.000	GND	L1	10.0	24.1	56.0	
4.050000	34.5	1000.000	9.000	GND	L1	10.2	21.5	56.0	
5.535000	39.8	1000.000	9.000	GND	L1	10.2	20.2	60.0	
6.405000	24.4	1000.000	9.000	GND	L1	10.3	35.6	60.0	


Final Measurement Detector 2

Frequency (MHz)	Average (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.270000	39.3	1000.000	9.000	GND	L1	10.0	11.6	50.9	
0.405000	33.7	1000.000	9.000	GND	L1	10.0	14.0	47.6	
0.540000	30.6	1000.000	9.000	GND	L1	10.0	15.4	46.0	
0.675000	26.9	1000.000	9.000	GND	L1	10.0	19.1	46.0	
1.080000	28.1	1000.000	9.000	GND	L1	10.0	17.9	46.0	
1.215000	27.7	1000.000	9.000	GND	L1	10.1	18.3	46.0	
1.755000	28.3	1000.000	9.000	GND	L1	10.1	17.7	46.0	
2.295000	25.3	1000.000	9.000	GND	L1	10.1	20.7	46.0	
4.185000	32.5	1000.000	9.000	GND	L1	10.2	13.5	46.0	
4.725000	33.4	1000.000	9.000	GND	L1	10.2	12.6	46.0	

< Fig 4. Conducted emission result (Live line)>



Voltage with 4-Line-LISN N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.150000	41.9	1000.000	9.000	GND	N	10.0	24.1	66.0	
0.180000	35.9	1000.000	9.000	GND	N	10.0	28.5	64.4	
0.270000	45.6	1000.000	9.000	GND	N	10.0	15.3	60.9	
0.405000	37.5	1000.000	9.000	GND	N	10.0	20.1	57.6	
0.540000	33.2	1000.000	9.000	GND	N	10.0	22.8	56.0	
0.945000	31.5	1000.000	9.000	GND	N	10.0	24.5	56.0	
1.215000	30.2	1000.000	9.000	GND	N	10.1	25.8	56.0	
3.855000	34.0	1000.000	9.000	GND	N	10.2	22.0	56.0	
4.935000	37.1	1000.000	9.000	GND	N	10.2	18.9	56.0	
6.150000	34.8	1000.000	9.000	GND	N	10.2	25.2	60.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	PE	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.270000	38.5	1000.000	9.000	GND	N	10.0	12.4	50.9	
0.405000	33.3	1000.000	9.000	GND	N	10.0	14.3	47.6	
0.540000	30.1	1000.000	9.000	GND	N	10.0	15.9	46.0	
1.080000	27.6	1000.000	9.000	GND	N	10.1	18.4	46.0	
1.620000	27.0	1000.000	9.000	GND	N	10.1	19.0	46.0	
1.755000	26.7	1000.000	9.000	GND	N	10.1	19.3	46.0	
3.855000	31.8	1000.000	9.000	GND	N	10.2	14.2	46.0	
4.530000	35.0	1000.000	9.000	GND	N	10.2	11.0	46.0	
6.015000	26.0	1000.000	9.000	GND	N	10.2	24.0	50.0	
29.730000	22.5	1000.000	9.000	GND	N	10.8	27.5	50.0	

< Fig 5. Conducted emission result (Neutral line)>



6. Radiated Emission

6.1 Operating Environment

Temperature : 24 °C
Relative Humidity : 43 % R.H.

6.2 Test Set-up

A preliminary and final measurement was at 3 m anechoic chamber.

The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The turntable with EUT was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels.

This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

6.3 Measurement Uncertainty

The measurement uncertainty was calculated in accordance with ISO “Guide to the expression of uncertainty in measurement”.

The measurement uncertainty was given with a confidence of 95 %.

Test Items(Chamber)	Uncertainty	Remark
Radiated emission (30 MHz ~ 300 MHz, 3 m, Vertical)	± 4.32 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (30 MHz ~ 300 MHz, 3 m, Horizontal)	± 4.21 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Vertical)	± 3.96 dB	Confidence levels of 95 % ($k = 2$)
Radiated emission (300 MHz ~ 1 000 MHz, 3 m, Horizontal)	± 3.97 dB	Confidence levels of 95 % ($k = 2$)



6.4 Limit

Frequency (MHz)	FCC Limit @ 3 m. dB μ V/m	CISPR Limit @ 10 m. dB μ V/m
30 ~ 88	40.0	30.0
88 ~ 216	43.5	30.0
216 ~ 230	46.0	30.0
230 ~ 960	46.0	37.0
960 ~ 1 000	54.0	37.0
> 1 000	54.0	No Specified limit

6.5 Test Equipment used

Model Name	Manufacturer	Description	Serial Number	Due to Calibration
■ - ESI	Rohde & Schwarz	EMI test receiver	830482/010	12. 11. 2010
■ - VULB9160	Schwarzbeck	Broadband Test Antenna	3099	07. 21. 2011
■ - MCU066	maturo GmbH	Position Controller	1390306	N/A
■ - TT2.5SI	maturo GmbH	Turntable	1390307	N/A
■ - AM 4.0	maturo GmbH	Antenna Mast	1390308	N/A




6.6 Test data for Radiated Emission

- Test Date : March 8, 2010
- Resolution Bandwidth : 120 kHz
- Frequency Range : 30 MHz ~ 1 000 MHz
- Measurement Distance : 3 m
- Note : The highest frequency of the internal source of the EUT is less than 108 MHz.
The measurement was made up to 1 GHz.

◆ Detector mode: Quasi- peak detector mode

Frequency (MHz)	Measurement Level				Limit (dB μ V/m)	Margin (dB)	Positioning System		
	Reading	Antenna	Cable	Test Result			Pol. (H/V)	Height (cm)	Angle (°)
	Value(dB μ V)	Factor(dB/m)	Loss(dB)	(dB μ V/m)					
119.87	13.75	11.37	3.33	28.45	43.50	15.05	V	100	0
181.98	20.67	11.49	4.02	36.18	43.50	7.32	V	126	93
203.15	18.76	9.40	4.33	32.49	43.50	11.01	H	108	94
300.53	11.18	13.29	5.64	30.11	46.00	15.89	H	110	172
663.90	13.69	21.18	7.78	42.65	46.00	3.35	V	217	196
700.20	3.00	21.54	7.96	32.50	46.00	13.50	V	103	202



< Fig 6. Radiated emission result (30 MHz ~ 1 000 MHz)>



7. Sample Calculations

$$\begin{aligned} \text{dB}\mu\text{V} &= 20 \log_{10}(\mu\text{V}/\text{m}) \\ \text{dB}\mu\text{V} &= \text{dBm} + 107 \\ \mu\text{V} &= 10^{(\text{dB}\mu\text{V}/20)} \end{aligned}$$

7.1 Example 1 :

■ 20.3 MHz

Class B Limit	= 250 μV = 48 dB μV
Reading	= 39.2 dB μV
$10^{(39.2\text{dB}\mu\text{V}/20)}$	= 91.2 μV
Margin	= 48 dB μV - 39.2 dB μV
	= 8.8 dB

7.2 Example 2 :

■ 66.7 MHz

Class B Limit	= 100 $\mu\text{V}/\text{m}$ = 40.0 dB $\mu\text{V}/\text{m}$
Reading	= 31.0 dB μV
Antenna Factor + Cable Loss = 5.8 dB	
Total	= 36.8 dB $\mu\text{V}/\text{m}$
Margin	= 40.0 dB $\mu\text{V}/\text{m}$ - 36.8 dB $\mu\text{V}/\text{m}$
	= 3.2 dB



8. Recommendation & Conclusion

The data collected shows that the **3H VISION Co., Ltd. USB camera module (Model Name: WC-1000)** was complies with §15.107 and 15.109 of the FCC Rules.