



## FCC TEST REPORT

for

HUIYANG TECHNOLOGY CO.,LTD

Bluetooth Music Receiver

Model Number: BT-MP

Prepared for : HUIYANG TECHNOLOGY CO.,LTD

Address : 406Room,365Dezheng west Road,ChangAn Town,Dongguan City,  
Guangdong Province,China

Prepared By : NS Technology Co., Ltd.

Address : Chenwu Industrial Zone, Houjie Town, Dongguan City,  
Guangdong, China

Tel: +86-769-85935656

Fax: +86-769-85991080

Report Number : NSE-F10054776

Date of Test : May 4, 2010

Date of Report : May 8, 2010





# NS Technology Co., Ltd.

<b>Applicant:</b>	HUIYANG TECHNOLOGY CO.,LTD		
<b>Address:</b>	406Room,365Dezheng west Road,ChangAn Town,Dongguan City, Guangdong Province,China		
<b>Manufacturer:</b>	HUIYANG TECHNOLOGY CO.,LTD		
<b>Address:</b>	406Room,365Dezheng west Road,ChangAn Town,Dongguan City, Guangdong Province,China		
<b>E.U.T:</b>	Bluetooth Music Receiver		
<b>Model Number:</b>	BT-MP		
<b>Report Number:</b>	NSE-F10054777		
<b>Trade Name:</b>	-----		
<b>Operating Frequency:</b>	2402~2480MHz		
<b>Date of Receipt:</b>	Mar.5, 2010	<b>Date of Test:</b>	May 4, 2010
<b>Test Specification:</b>	47 CFR FCC Part 2 Subpart J, section 2.1091		
<b>Test Result:</b>	The equipment under test was found to be compliance with the requirements of the standards applied.		
<b>Issue Date: May 8, 2010</b>			
Tested by:	Reviewed by:	Approved by:	
			
Jade/ Engineer	Iceman Hu / Supervisor	Steven Lee / Manager	
<b>Other Aspects:</b>			
None.			
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
<p><i>This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of NS Technology Co., Ltd.</i></p>			



## Maximum Permissible Exposure

### 1 Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density(S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

#### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density(S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

### 2 MPE Calculation Method

$$E \text{ (V/m)} = (30*P*G)^{0.5}/d$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2/377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30*P*G) / (377*d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.



### 3 Calculated Result and Limit

Mode	CH	Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	MPE estimation result (mW/cm <sup>2</sup> ) at 20cm	Limit of MPE Estimation (mW/cm <sup>2</sup> )	Test result
TX	Low:2402MHz	0.72	1.18	0.5	0.00007	1	Compiles
	Middle:2441MHz	0.63	1.16	0.5	0.00005	1	Compiles
	High:2480MHz	0.48	1.12	0.5	0.00002	1	Compiles

