# FCC Part 15 EMI TEST REPORT

# of

E.U.T. : Wireless Keyboard

MODEL : SBW-97-TP

Serial Model : SBW-97-TP-0

FCC ID. : XA9-SBW97TP

Frequency Range : 2402MHz~2478MHz

# for

APPLICANT: iKEY, Ltd

ADDRESS : 2621 Ridgepoint Drive, Austin, TX 78754

Test Performed by

#### **ELECTRONICS TESTING CENTER, TAIWAN**

NO. 34. LIN 5, DINGFU VIL., LINKOU DIST., NEW TAIPEI CITY, TAIWAN, 24442, R.O.C. TEL: (02)26023052 FAX: (02)26010910

http://www.etc.org.tw; e-mail: emc@etc.org.tw

Report Number: 12-08-RBF-021-04

# TEST REPORT CERTIFICATION

Applicant : iKEY, Ltd

2621 Ridgepoint Drive, Austin, TX 78754

Manufacturer : IPA Electronics (Taiwan) Corp.

5F-3, #190, Sec. 2, Zhong Xing Rd, Xindian District, New Taipei City,

Taiwan 231

Description of EUT

a) Type of EUT : Wireless Keyboard

b) Trade Name : iKEY

c) Model No. : SBW-97-TPd) Serial Model : SBW-97-TP-0e) Power Supply : Power From PC

f) Frequency Range : 2402MHz~2478MHz

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4, and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Note: 1. The result of the testing report relate only to the item tested.

2. The testing report shall not be reproduced expect in full, without the written approval of ETC.

#### **Summary of Tests**

Test	Results
Radiated Emission	Pass
Conducted Emission	Pass
Band Edge Requirement	Pass

Date Test Item Received : Aug. 24, 2012
Date Test Campaign Completed : Sep. 18, 2012
Date of Issue : Oct. 29, 2012

Test Engineer:

(Jiapeng Chen, Engineer)

Approve & Authorized Signer:

S. S. Liou, Section Manager EMC Dept. II of ELECTRONICS TESTING CENTER, TAIWAN

Table of Contents	Page
1 GENERAL INFORMATION	1
1.1 Product Description	1
1.2 Characteristics of Device	1
1.3 Test Methodology	1
1.4 Test Facility	1
2 PROVISIONS APPLICABLE	2
2.1 Definition	2
2.2 Requirement for Compliance	3
2.3 Restricted Bands of Operation	5
2.4 Labeling Requirement	5
2.5 User Information	6
3. SYSTEM TEST CONFIGURATION	7
3.1 Justification	7
3.2 Devices for Tested System	7
4 RADIATED EMISSION MEASUREMENT	8
4.1 Applicable Standard	8
4.2 Measurement Procedure	8
4.3 Measuring Instrument	10
4.4 Radiated Emission Data	11
4.4.1 RF Portion	
4.4.2 Other Emissions	
4.5 Field Strength Calculation	
4.6 Photos of Radiation Measuring Setup	18
5 CONDUCTED EMISSION MEASUREMENT	
5.1 Standard Applicable	19
5.2 Measurement Procedure	
5.3 Conducted Emission Data	
5.4 Result Data Calculation	
5.5 Conducted Measurement Equipment	
5.6 Photos of Conduction Measuring Setup	23
6 ANTENNA REQUIREMENT	24
6.1 Standard Applicable	
6.2 Antenna Construction	24
7 BAND EDGES MEASUREMENT	25

7.1	Standard Applicable	25
7.2	Measurement Procedure	25
7.3	Measurement Equipment	26
7.4	Measurement Data	26

#### 1 GENERAL INFORMATION

### 1.1 Product Description

a) Type of EUT : Wireless Keyboard

b) Trade Name : iKEY

c) Model No. : SBW-97-TP
d) Serial Model : SBW-97-TP-0
e) Power Supply : Power From PC

f) Frequency Range : 2402MHz~2478MHz

#### 1.2 Characteristics of Device

Wireless Keyboard working on 2.4GHz frequency band.

Serial model SBW-97-TP-0 is identical with main model SBW-97-TP and the only difference is the model name designation.

### 1.3 Test Methodology

Both conducted and radiated emissions were performed according to the procedures illustrated in ANSI C63.4 (2003). Other required measurements were illustrated in separate sections of this test report for details.

#### 1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the roof top of Building at No.34, Lin 5, Dingfu Vil., Linkou Dist., New Taipei City, Taiwan 24442, R.O.C.

This site has been fully described in a report submitted to your office, and accepted in a letter dated Jan. 11, 2011.

#### 2 PROVISIONS APPLICABLE

#### 2.1 Definition

#### **Unintentional radiator:**

A device that intentionally generates and radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

#### Class A Digital Device:

A digital device which is marketed for use in commercial or business environment; exclusive of a device which is market for use by the general public, or which is intended to be used in the home.

#### Class B Digital Device:

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business of industrial environment. Example of such devices that are marketed for the general public.

Note: A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

#### **Intentional radiator:**

A device that intentionally generates and emits radio frequency energy by radiation or induction.

Sheet 3 of 28 Sheets FCC ID.: XA9-SBW97TP

#### 2.2 Requirement for Compliance

## (1) Conducted Emission Requirement

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50MH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the band edges.

Frequency	Quasi Peak	Average
MHz	dΒμV	dΒμV
0.15 - 0.5	66-56	56-46
0.5 - 5.0	56	46
5.0 - 30.0	60	50

#### (2) Radiated Emission Requirement

For unintentional device, according to §15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency MHz	Distance Meters	Radiated dBμV/m	Radiated μV/m
30 - 88	3	40.0	100
88 - 216	3	43.5	150
216 - 960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to §15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

Sheet 4 of 28 Sheets FCC ID.: XA9-SBW97TP

For intentional radiator device, per §15.249(a), the field strength of emissions shall comply with the following :

Frequency	Distance	Fundamental		Harn	nonic
MHz	Meters	dBμV/m mV/m		dBμV/m	$\mu V/m$
902 - 928	3	94	50	54	500
2400 - 2483.5	3	94	50	54	500
5725 - 5875	3	94	50	54	500
24000 - 24250	3	108	250	68	2500

In accordance with §15.249(e), limits shown in above table are based on average limits for frequencies above 1000 MHz, and frequencies below 1000 MHz are based on quasi peak. However, the peak field strength of any emission shall not exceed the maximum permitted average limits by more than 20 dB.

#### (3) Spurious in Out Band Requirement

For intentional device, according to §15.249 (d), emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of fundamental or to the general radiated emission limits in §15.209.

#### (4) Antenna Requirement

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

## 2.3 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
IVIIIZ	IVIIIZ	IVIIIZ	GHZ
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

<sup>\*\*:</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

## 2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

#### 2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -- Reorient or relocate the receiving antenna.
- -- Increase the separation between the equipment and receiver.
- -- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -- Consult the dealer or an experienced radio / TV technician for help.

#### 3. SYSTEM TEST CONFIGURATION

#### 3.1 Justification

For both radiated and conducted emissions, the system was configured for testing in a typical fashion as a customer would normally use it. The peripherals other than EUT were connected in normally standing by situation.

All measurement were intentional to maximum the emissions from EUT by varying the connection cables, therefore, the test result is sure to meet the applicable requirement.

## 3.2 Devices for Tested System

Device	Manufacturer	Model / FCC ID	Description
	IPA Electronics (Taiwan) Corp.	SBW-97-TP / XA9-SBW97TP	1.6m Shielded USB Cable

Remark "\*" means equipment under test.

#### 4 RADIATED EMISSION MEASUREMENT

### 4.1 Applicable Standard

For intentional radiators, according to §15.249 (a), the fundamental field strength shall not exceed 94 dBuV/m and the harmonics shall not exceed 54 dBuV/m. For out band emission except for harmonics shall be comply with §15.209 or at least attenuated by 50 dB below the level of the fundamental.

#### 4.2 Measurement Procedure

- 1. Setup the configuration per figure 1 and 2 for frequencies measured below and above 1 GHz respectively.
- 2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
- 5. Repeat step 4 until all frequencies need to be measured were complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.
- 7. Check the three frequencies of highest emission with varying the placement of cables associated with EUT to obtain the worse case and record the result.





Figure 1: Frequencies measured below 1 GHz configuration

Figure 2: Frequencies measured above 1 GHz configuration



## 4.3 Measuring Instrument

The following instrument are used for radiated emissions measurement:


Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Test Receiver	Rohde & Schwarz	ESVS30	2012/05/07	2013/05/07
EMI Test Receiver	Rohde & Schwarz	ESL	2012/07/30	2013/07/30
Bi-Log Antenna	ETC	MCTD 2756	2012/01/10	2013/01/09
Log-periodic Antenna	EMCO	3146	2011/11/04	2012/11/03
Double Ridged Guide				
Horn Antenna	EMCO	3116	2011/10/24	2012/10/26
Biconical Antenna	EMCO	3110B	2011/11/18	2012/11/17
Double Ridged				
Antenna	EMCO	3115	2012/05/18	2013/05/18
Amplifier	HP	8449B	2011/12/28	2012/12/27
Amplifier	HP	83051A	2012/05/16	2013/05/16
Amplifier	HP	8447D	2012/05/16	2013/05/16
Spectrum	Rohde & Schwarz	FSP40	2011/09/21	2012/09/20

Measuring instrument setup in measured frequency band when specified detector function is used:

Frequency Band	Instrument	Function	Resolution	Video
(MHz)	THOU WHICH	T directori	bandwidth	Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
30 to 1000	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10Hz

#### 4.4 Radiated Emission Data

#### 4.4.1 RF Portion



Site :chamber #2 Date :2012-09-17
Limit :FCC 2.4GHZ PEAK Ant. Pol. :HORIZONTAL
EUT :Wireless Keyboard Temp. :24 °C


EUT :Wireless Keyboard Temp. :24 °C
Power Rating :Power From PC Humi. :56%
Model :SBW-97-TP Engineer. :Jiapeng

Memo :TX – CH Low/Mid/High Memo :

Freq	Reading	Correction	Result	Limits	Over limit	Detector
		Factor				
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
2402.0000	98.6	-5.9	92.7	94.0	-1.3	Average
2402.0000	100.0	-5.9	94.1	114.0	-19.9	Peak
2442.0000	97.8	-5.7	92.1	114.0	-21.9	Peak
2478.0000	98.3	-5.5	92.8	94.0	-1.2	Average
2478.0000	100.6	-5.5	95.1	114.0	-18.9	Peak

- 1. Result = Reading + Corrected Factor
- 2. Corrected Factor = Antenna Factor + Cable Loss Amplifier Gain (if any)
- 3. The margin value=Limit Result
- 4. Peak measurements are compared to the average limit as peak measurements are below the average limit, they also comply with the peak limit

Sheet 12 of 28 Sheets FCC ID.: XA9-SBW97TP




Site :chamber #2 Date :2012-09-17 Limit :FCC 2.4GHZ PEAK Ant. Pol. :VERTICAL EUT :24 °C :Wireless Keyboard Temp. **Power Rating** :Power From PC Humi. :56% Model :SBW-97-TP Engineer. :Jiapeng Memo :TX – CH Low/Mid/High Memo

Freq	Reading	Correction	Result	Limits	Over limit	Detector
		Factor				
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
2402.0000	95.0	-5.9	89.1	114.0	-24.9	Peak
2442.0000	95.5	-5.7	89.8	114.0	-24.2	Peak
2478.0000	97.3	-5.5	91.8	114.0	-22.2	Peak

- 1. Result = Reading + Corrected Factor
- 2. Corrected Factor = Antenna Factor + Cable Loss Amplifier Gain (if any)
- 3. The margin value=Limit Result
- 4. Peak measurements are compared to the average limit as peak measurements are below the average limit, they also comply with the peak limit

Sheet 13 of 28 Sheets FCC ID.: XA9-SBW97TP




Site :CHAMBER #2 Date :2012-09-17 Limit :1G TO 40G PEAK Ant. Pol. :HORIZONTAL EUT :25 °C :Keyboard Temp. **Power Rating** :Power From PC Humi. :56% :SBW-97-TP Model Engineer. :Jiapeng Test Mode :CH Low & High - Restricted Bands Memo

Freq	Reading	Correction	Result	Limits	Over limit	Detector
		Factor				
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
2313.4500	50.8	-6.2	44.6	74.0	-29.4	Peak
2358.4600	51.2	-6.0	45.2	74.0	-28.8	Peak
2488.7500	51.7	-5.5	46.2	74.0	-27.8	Peak
2490.1700	52.3	-5.5	46.8	74.0	-27.2	Peak

- 1. Result = Reading + Corrected Factor
- 2. Corrected Factor = Antenna Factor + Cable Loss Amplifier Gain (if any)
- 3. The margin value=Limit Result
- 4. Peak measurements are compared to the average limit as peak measurements are below the average limit, they also comply with the peak limit

Sheet 14 of 28 Sheets FCC ID.: XA9-SBW97TP



Site :CHAMBER #2 Date :2012-09-17 Limit :1G TO 40G PEAK Ant. Pol. :VERTICAL EUT :25 °C :Keyboard Temp. **Power Rating** :Power From PC Humi. :56% :SBW-97-TP Model Engineer. :Jiapeng Test Mode :CH Low & High - Restricted Bands Memo

Freq	Reading	Correction	Result	Limits	Over limit	Detector
		Factor				
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
2312.7800	51.4	-6.2	45.2	74.0	-28.8	Peak
2335.6700	50.9	-6.0	44.9	74.0	-29.1	Peak
2492.1600	51.2	-5.5	45.7	74.0	-28.3	Peak
2495.6900	52.3	-5.5	46.8	74.0	-27.2	Peak


- 1. Result = Reading + Corrected Factor
- 2. Corrected Factor = Antenna Factor + Cable Loss Amplifier Gain (if any)
- 3. The margin value=Limit Result
- 4. Peak measurements are compared to the average limit as peak measurements are below the average limit, they also comply with the peak limit

#### 4.4.2 Other Emissions

a) Emission frequencies below 1 GHz

Operation Mode : Charging & Key-in


Test Date : Sep. 18, 2012 Temperature : 27 °C Humidity : 56 %



Site :Open site Date :2012-09-18 **EUT** :Wireless Keyboard Ant. Pol. :HORIZONTAL Model :SBW-97-TP Detector :Q.P. Power Rating :Power From PC Engineer :Jiapeng :FCC CLASS-B :27 °C Limit Temp. Memo :Charging & Key-in Humi. :56 %

Freq	Reading	Correction	Result	Limits	Over limit
		Factor			dB
MHz	dBuV	dB	dBuV/m	dBuV/m	
34.8800	16.9	14.3	31.2	40.0	-8.8
129.1900	16.1	13.1	29.2	43.5	-14.3
149.7800	14.6	14.2	28.8	43.5	-14.7
223.4900	17.5	13.7	31.2	46.0	-14.8
233.2500	18.8	13.9	32.7	46.0	-13.3
845.3000	9.1	27.5	36.6	46.0	-9.4

- 1. Result = Reading + Corrected Factor
- 2. Corrected Factor = Antenna Factor + Cable Loss Amplifier Gain (if any)
- 3. The margin value=Limit Result



Site :Open site Date :2012-09-18 **EUT** :Wireless Keyboard Ant. Pol. :VERTICAL :SBW-97-TP Detector Model :Q.P. Power Rating :Power From PC Engineer :Jiapeng Limit :FCC CLASS-B :27 °C Temp. Memo :Charging & Key-in Humi. :56 %

Freq	Reading	Correction	Result	Limits	Over limit
		Factor			dB
MHz	dBuV	dB	dBuV/m	dBuV/m	
42.4700	20.0	13.0	33.0	40.0	-7.0
138.9400	19.4	13.6	33.0	43.5	-10.5
147.8900	17.0	14.1	31.1	43.5	-12.4
216.1800	15.3	13.9	29.2	46.0	-16.8
444.9000	13.1	20.1	33.2	46.0	-12.8
749.4000	10.0	25.8	35.8	46.0	-10.2

- 1. Result = Reading + Corrected Factor
- 2. Corrected Factor = Antenna Factor + Cable Loss Amplifier Gain (if any)
- 3. The margin value=Limit Result

#### b) Emission frequencies above 1 GHz

Radiated emission frequencies above 1 GHz to 26.5 GHz were too low to be measured with a pre-amplifier of 35 dB.

## 4.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss(if used) and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

where Corrected Factor

= Antenna FACTOR + Cable Loss + High Pass Filter Loss - Amplifier Gain

# 4.6 Photos of Radiation Measuring Setup





#### **5 CONDUCTED EMISSION MEASUREMENT**

#### 5.1 Standard Applicable

For unintentional and intentional device, Line Conducted Emission Limits are in accordance to §15.107(a) and §15.207(a) respectively. Both Limits are identical specification.

#### **5.2 Measurement Procedure**

LISN

- 1. Setup the configuration per figure 3.
- 2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
- 3. Record the 6 or 8 highest emissions relative to the limit.
- 4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
- 5. Confirm the highest three emissions with variation of the EUT cable configuration and record the final data.
- 6. Repeat all above procedures on measuring each operation mode of EUT.


Vertical Reference
Ground Plane

Test Receiver

Reference Ground Plane

Figure 3: Conducted emissions measurement configuration

## **5.3 Conducted Emission Data**




Site : conducted #1 Date : 09-18-2012 Condition : CLASS-B QP LISN : NEUTRAL : 26 °C / 55% : Charging & Key-in Tem / Hum Test Mode EUT : Keyboard Power Rating : Power From PC

Memo : Memo :

Freq (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBuV)	Limit Line (dBuV)	Over Limit (dB)	Remark
0.1758	51.8	0.2	52.0	64.7	-12.7	QP
0.2366	43.9	0.2	44.1	62.2	-18.1	QP
0.2955	38.3	0.2	38.5	60.4	-21.9	QP
0.3634	38.1	0.2	38.3	58.7	-20.4	QP
0.4838	38.0	0.2	38.2	56.3	-18.1	QP
0.5293	35.4	0.2	35.6	56.0	-20.4	QP

- 1. Result = Reading + Factor
- 2. Factor = LISN Factor + Cable Loss



Site : conducted #1 Date : 09-18-2012

Condition : CLASS-B QP LISN : LINE

Tem / Hum :  $26 \,^{\circ}\text{C} / 55\%$  Test Mode : Charging & Key-in

EUT : Keyboard Power Rating : Power From PC

Memo : Memo

11141110	•			1,141110		•
Emag			Emission	Limit	Over	
Freq (MHz)	Reading	Factor	Level	Line	Limit	Remark
(11112)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dB)	
0.1027	51.5	0.2	<b>71</b> 0	64.0	10.5	0.0
0.1835	51.5	0.3	51.8	64.3	-12.5	QP
0.2341	40.8	0.3	41.1	62.3	-21.2	QP
0.2971	37.4	0.3	37.7	60.3	-22.6	QP
0.3673	37.6	0.3	37.9	58.6	-20.7	QP
0.4889	37.1	0.3	37.4	56.2	-18.8	QP
0.5293	35.0	0.3	35.3	56.0	-20.7	QP

- 1. Result = Reading + Factor
- 2. Factor = LISN Factor + Cable Loss

#### **5.4 Result Data Calculation**

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$RESULT = READING + LISN FACTOR$$

Assume a receiver reading of 22.5 dB $\mu$ V is obtained, and LISN Factor is 0.1 dB, then the total of disturbance voltage is 22.6 dB $\mu$ V.

RESULT = 
$$22.5 + 0.1 = 22.6 \text{ dB}\mu\text{V}$$
  
Level in  $\mu\text{V} = \text{Common Antilogarithm}[(22.6 \text{ dB}\mu\text{V})/20]$   
=  $13.48 \ \mu\text{V}$ 

## 5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test.

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESCI	2012/07/16	2013/07/16
LISN	EMCO	3625/2	2012/03/30	2013/04/02
LISN	Rohde & Schwarz	ESH2-Z5	2012/08/23	2013/08/23

# **5.6 Photos of Conduction Measuring Setup**





ETC Report No.: 12-08-RBF-021-04 Sheet 24 of 28 Sheets FCC ID.: XA9-SBW97TP

## **6 ANTENNA REQUIREMENT**

## 6.1 Standard Applicable

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 6.2 Antenna Construction

The antenna is integrated on the device. No consideration of replacement. Please refer to the construction Photo for details.

#### 7 BAND EDGES MEASUREMENT

#### 7.1 Standard Applicable

According to 15.249(d), out band emission except for harmonics shall be comply with §15.209 or at least attenuated by 50 dB below the level of the fundamental.

#### 7.2 Measurement Procedure

#### A) 50 dB attenuation method

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT as shown in figure 4 without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 4. Repeat above procedures until all measured frequencies were complete.

#### B) Radiated Emission method

- 1. Following the measurement procedures in section 4.2 with the EUT set to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 2. Measure the highest amplitude appearing on spectral displayed.
- 3. Repeat above procedures until all measured frequencies were complete.

Measuring instrument setup in measured frequency band when specified detector function is used:

Frequency Band	Instrument	Function	Resolution	Video
(MHz)	11100101110110	1 411 410 11	bandwidth	Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
30 to 1000	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	10Hz

## 7.3 Measurement Equipment

A) 50 dB attenuation method

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Spectrum Analyzer	Rohde & Schwarz	FSP40	2011/09/21	2012/09/20

B) Radiated Emission method

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
Test Receiver	Rohde & Schwarz	ESVS30	2012/05/07	2013/05/07
EMI Test Receiver	Rohde & Schwarz	ESL	2012/07/30	2013/07/30
Bi-Log Antenna	ETC	MCTD 2756	2012/01/10	2013/01/09
Log-periodic Antenna	EMCO	3146	2011/11/04	2012/11/03
Double Ridged Guide				
Horn Antenna	EMCO	3116	2011/10/24	2012/10/26
Biconical Antenna	EMCO	3110B	2011/11/18	2012/11/17
Double Ridged				
Antenna	EMCO	3115	2012/05/18	2013/05/18
Amplifier	HP	8449B	2011/12/28	2012/12/27
Amplifier	HP	83051A	2012/05/16	2013/05/16
Amplifier	HP	8447D	2012/05/16	2013/05/16
Spectrum Analyzer	Rohde & Schwarz	FSP40	2011/09/21	2012/09/20


## 7.4 Measurement Data

Test Result: (Radiated Emission method)

The radiated emission test results of the lower and the upper band edges were comply with §15.209. Please refer to the following pages for test results.

Sheet 27 of 28 Sheets FCC ID.: XA9-SBW97TP

#### **Radiated Emission Test Results of the Band Edges**




Site :CHAMBER #2 Date :2012-09-17 Limit :FCC 2.4GHZ PEAK Ant. Pol. :HORIZONTAL

EUT :Keyboard Temp. :25  $^{\circ}$ C Power Rating :Power From PC Humi. :56% Model :SBW-97-TP Engineer. :Jiapeng

Freq	Reading	Correction	Result	Limits	Over limit	Detector
		Factor				
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
2400.0000	58.8	-5.9	52.9	74.0	-21.1	Peak
2483.5000	58.1	-5.5	52.6	74.0	-21.4	Peak

- 1. Result = Reading + Corrected Factor
- 2. Corrected Factor = Antenna Factor + Cable Loss Amplifier Gain (if any).
- 3. The margin value=Limit Result
- 4. Peak measurements are compared to the average limit as peak measurements are below the average limit, they also comply with the peak limit

Sheet 28 of 28 Sheets FCC ID.: XA9-SBW97TP



Site	:CHAMBER #2	Date	:2012-09-17
Limit	:FCC 2.4GHZ PEAK	Ant. Pol.	:VERTICAL
EUT	:Keyboard	Temp.	:25 °C
Power Rating	:Power From PC	Humi.	:56%
Model	:SBW-97-TP	Engineer.	:Jiapeng

Freq	Reading	Correction	Result	Limits	Over limit	Detector
		Factor				
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
2400.0000	58.9	-5.9	53.0	74.0	-21.0	Peak
2483.5000	58.6	-5.5	53.1	74.0	-20.9	Peak

- 1. Result = Reading + Corrected Factor
- 2. Corrected Factor = Antenna Factor + Cable Loss Amplifier Gain (if any).
- 3. The margin value=Limit Result
- 4. Peak measurements are compared to the average limit as peak measurements are below the average limit, they also comply with the peak limit

1.






3.





5.







7.








10.





12.

