



Test Report No.: RF121126N003-1



FCC TEST REPORT

(PART 22)

REPORT NO.: RF121126N003-1

MODEL NO.: Ex-Handy 08 .3 - A

FCC ID: XAM500045GR01

RECEIVED: Nov. 28, 2012

TESTED: Nov. 28 ~ Mar. 12, 2013

ISSUED: Mar. 13, 2013

APPLICANT: ecom instruments GmbH

ADDRESS: Industriestraße 2, 97959 Assamstadt, Germany

ISSUED BY: Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

LAB ADDRESS: No. 34, Chenwulu Section, Guantai Road, Houjie
Town, Dongguan City, Guangdong 523942, China

TEST LOCATION: No. 34, Chenwulu Section, Guantai Road, Houjie
Town, Dongguan City, Guangdong 523942, China

This report should not be used by the client to claim
product certification, approval, or endorsement by A2LA
or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 CERTIFICATION.....	5
2 SUMMARY OF TEST RESULTS	6
2.1 MEASUREMENT UNCERTAINTY.....	6
3 GENERAL INFORMATION.....	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.3 DESCRIPTION OF SUPPORT UNITS	10
3.4 TEST ITEM AND TEST CONFIGURATION.....	11
3.5 EUT OPERATING CONDITIONS	12
3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	12
4 TEST TYPES AND RESULTS	13
4.1 output power Measurement.....	13
4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	13
4.1.2 TEST PROCEDURES	13
4.1.3 TEST SETUP.....	14
4.1.4 TEST RESULTS	15
4.2 FREQUENCY stability MEASUREMENT	17
4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	17
4.2.2 TEST PROCEDURE	17
4.2.3 TEST SETUP.....	17
4.2.4 TEST RESULTS	18
4.3 OCCUPIED BANDWIDTH MEASUREMENT	19
4.3.1 TEST PROCEDURES	19
4.3.2 TEST SETUP.....	19
4.3.3 TEST RESULTS	20
4.4 BAND EDGE MEASUREMENT	21
4.4.1 LIMITS OF BAND EDGE MEASUREMENT	21
4.4.2 TEST SETUP.....	21
4.4.3 TEST PROCEDURES	21
4.4.4 TEST RESULTS	22
4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT.....	23
4.5.2 TEST PROCEDURE.....	23
4.5.3 TEST SETUP.....	23
4.6 RADIATED Emission Measurement	27
4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....	27
4.6.2 TEST PROCEDURES	27
4.6.3 DEVIATION FROM TEST STANDARD.....	27
4.6.4 TEST SETUP.....	28



Test Report No.: RF121126N003-1

4.6.5 TEST RESULTS	29
5 PHOTOGRAPHS OF THE TEST CONFIGURATION	31
6 INFORMATION ON THE TESTING LABORATORIES	32
7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	33



Test Report No.: RF121126N003-1

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF121126N003-1	Original release	Mar. 13, 2013

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: RF121126N003-1

1 CERTIFICATION

PRODUCT: GSM/WCDMA Mobile Phone

MODEL: See section 3.1

BRAND: ecom

APPLICANT: ecom instruments GmbH

TESTED: Nov. 28 ~ Mar. 12, 2013

TEST SAMPLE: Production Unit

STANDARDS: FCC PART 22, Subpart H

The above equipment (model: Ex-Handy 08 .3 – A & Ex-HSPA 08 .3 – A) have been tested by **Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

TESTED BY :  , DATE : Mar. 13, 2013
Kent Liu / Project Engineer

APPROVED BY :  , DATE : Mar. 13, 2013
Sam Tung / Technical Manager



Test Report No.: RF121126N003-1

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 22.913 (a)	Effective Radiated Power	PASS	Meet the requirement of limit.
2.1055 22.355	Frequency Stability	PASS	Meet the requirement of limit.
2.1049	Occupied Bandwidth	PASS	Meet the requirement of limit.
22.917	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 22.917	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 22.917	Radiated Spurious Emissions	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.94dB
Radiated emissions	30MHz ~ 1GHz	3.64dB
	1GHz ~ 18GHz	2.2dB
	18GHz ~ 40GHz	1.94dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



2.2 TEST SITE AND INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Spectrum Analyzer Agilent	E4446A	MY46180622	May 02, 12	May 01, 13
Test Receiver ROHDE & SCHWARZ	ESVD	841431/004	May 15,12	May 14,13
Bilog Antenna TESEQ	CBL 6111D	27089	July 16,12	July 15,13
Horn Antenna EMCO	3117	00062558	Oct.18,12	Oct.17,13
10m Semi-anechoic Chamber ETS-LINDGREN	21.4m*12.1m*8.8m	NSEMC006	Mar. 24,12	Mar. 23,13
Signal Amplifier EMCI	EMC330	980095	Nov 02,12	Nov 01,13
Signal Amplifier SONOMA	310N	186955	Mar. 14,12	Mar. 13,13
Signal Amplifier HP	8449B	3008A00409	May 31,12	May 30,13
Spectrum Analyzer Agilent	E7405A	MY45118807	May 15,12	May 14,13
Digital Multimeter FLUKE	15B	A1220010DG	Oct .31,12	Oct. 30,13
Power Meter Anritsu	ML2495A	1139001	Nov. 05,12	Nov. 04,13
Universal Radio Communication Tester Rohde & Schwarz	CMU 200	123259	Apr 16,12	Apr 15,13
Test software ADT	ADT_Radiated_V7. 6.15	N/A	N/A	N/A

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA.
2. The test was performed in Dongguan Chamber 10m.
3. The horn antenna are used only for the measurement of emission frequency above 1GHz if tested.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	GSM/WCDMA Mobile Phone
MODEL NO.	Ex-Handy 08 .3 – A, Ex-HSPA 08 .3 – A
TYPE NUMBER	P35F009AB
POWER SUPPLY	5.0Vdc (adapter or host equipment) 3.7Vdc (battery)
MODULATION TYPE	GSM, GPRS: GMSK EDGE: 8PSK WCDMA : BPSK
FREQUENCY RANGE	GSM, GPRS, EDGE: 824.2MHz ~ 848.8MHz WCDMA: 826.4MHz ~ 846.6MHz
MAX. ERP POWER	GSM: 1.82Watts EDGE: 0.92Watts WCDMA: 0.3Watts
POWER CLASS	4
ANTENNA TYPE	Fixed Internal antenna with 0 dBi gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB Cable: Shielded, Detachable, 1.1m, with Safety box; Earphone Cable: Unshielded, Detachable, 1.5m

NOTE:

1. There are Bluetooth, GSM, WCDMA technology used for the EUT.
2. The EUT has several models as the following:

Model Name	Type	Battery & Cover	Software difference				Colors
			Camera*	LWP*	PTT*	ATT*	
Ex-Handy 08 .0 – A	Z1	Ex-BPH-08HC or Ex-BPH-08SC Battery	No	No	No	No	Black and Yellow
Ex-Handy 08 .1 – A			No	Yes	No	No	Yellow, colored keys
Ex-Handy 08 .2 – A			Yes	No	No	No	Black and Yellow
Ex-Handy 08 .3 – A			Yes	Yes	No	No	Yellow, colored keys
Ex-Handy 08 .4 – A			No	No	Yes	No	Black and Yellow
Ex-Handy 08 .5 – A			Yes	No	Yes	No	Black and Yellow
Ex-Handy 08 .4 – ATT			No	No	Yes	Yes	Black and Yellow
Ex-Handy 08 .5 – ATT			Yes	No	Yes	Yes	Black and Yellow
Ex-HSPA 08 .0 – A	Z2	Ex-BPH 28 Battery + Normal cover or NFC cover	No	No	No	No	Black
Ex-HSPA 08 .1 – A			No	Yes	No	No	Yellow, colored keys
Ex-HSPA 08 .2 – A			Yes	No	No	No	Black
Ex-HSPA 08 .3 – A			Yes	Yes	No	No	Yellow, colored keys
Ex-HSPA 08 .4 – A			No	No	Yes	No	Black
Ex-HSPA 08 .5 – A			Yes	No	Yes	No	Black



Test Report No.: RF121126N003-1

***Camera:** The camera application.

***LWP:** Lone worker protection mobile application.

***PTT:** Push to talk application.

***ATT:** SW customizations for carrier AT&T, Firmware change from MTK's generic implementation to ADAPT implementation.

The HW difference between Z1/Z2 Type	
Rear housing difference	
Foolproof to prevent misusage of regular battery on Z1 phones	
Cavity width is smaller in Z2 to make the regular battery stay put	
Z1 and Z2 use different battery and cover, please refer the above table in Note1	

According to the differences described in the above tables, models EX-HANDY 08 .3 - A and EX-HSPA 08. 3 - A are selected for the main test models, and full tests for the model EX-HANDY 08. 3 - A, partial tests for the model EX-HSPA 08. 3 - A.

3. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	Sonim
MODEL:	3202
INPUT:	AC 100-240V, 50/60Hz, 150mA
OUTPUT:	DC 5V, 700mA
DC LINE:	Shielded, Detachable,1.1m,with Safety box

4. The EUT was powered by the following Battery:

BATTERY 1	
BRAND:	ECOM
MODEL:	EX-BPH-08HC
OUTPUT:	3.7 VDC, 1960 mAh
BATTERY 2	
BRAND:	ECOM
MODEL:	EX-BPH-08SC
OUTPUT:	3.7 VDC, 1280 mAh
BATTERY 3	
BRAND:	Sonim
MODEL:	EX-BPH 28
OUTPUT:	3.7 VDC, 1950 mAh

5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

6. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.




Test Report No.: RF121126N003-1

BUREAU
VERITAS

3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	5P2PM2X	12400120329	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1.	AC Line :Unshielded, Detachable,1.5m;DC Line: Unshielded, Undetachable,1.8m;



3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned X-axis for ERP and for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

MODEL	EUT CONFIGURE MODE	DESCRIPTION
EX-HANDY 08 .3 - A	A	EUT + Battery 1 + USB cable + Earphone with 2/3G link
EX-HANDY 08 .3 - A	B	EUT + Battery 2 + USB cable + Earphone with 2/3G link
EX-HANDY 08 .3 - A	C	EUT + Adapter + USB cable+ Earphone with 2/3G link (with battery 2)
EX-HANDY 08 .3 - A	D	EUT + USB cable + Notebook + Earphone with 2/3G link (with battery 2)
Ex-HSPA 08 .3 - A	E	EUT + Adapter + USB cable+ Earphone with 2/3G link (with battery 3 + Normal cover)
Ex-HSPA 08 .3 - A	F	EUT + Adapter + USB cable+ Earphone with 2/3G link (with battery 3 + NFC cover)

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
C	ERP	128 to 251	128, 190, 251	GSM, EDGE
C	FREQUENCY STABILITY	128 to 251	190	GSM, EDGE
C	OCCUPIED BANDWIDTH	128 to 251	128, 190, 251	GSM, GPRS, EDGE
C	BAND EDGE	128 to 251	128, 251	GSM, GPRS, EDGE
C	CONDUCED EMISSION	128 to 251	128, 190, 251	GSM
A,B,C,D,E,F	RADIATED EMISSION	128 to 251	190	GSM, EDGE

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
C	ERP	4132 to 4233	4132, 4182, 4233	WCDMA
C	FREQUENCY STABILITY	4132 to 4233	4182	WCDMA
C	OCCUPIED BANDWIDTH	4132 to 4233	4132, 4182, 4233	WCDMA, HSDPA, HSUPA
C	BAND EDGE	4132 to 4233	4132, 4233	WCDMA, HSDPA, HSUPA
C	CONDUCED EMISSION	4132 to 4233	4132, 4182, 4233	WCDMA
A,B,C,D,E,F	RADIATED EMISSION	4132 to 4233	4182	WCDMA



Test Report No.: RF121126N003-1

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	22deg. C, 62%RH	3.7Vdc from Battery	Venless Long
FREQUENCY STABILITY	22deg. C, 62%RH	3.7Vdc from Battery	Venless Long
OCCUPIED BANDWIDTH	22deg. C, 62%RH	3.7Vdc from Battery	Venless Long
BAND EDGE	22deg. C, 62%RH	3.7Vdc from Battery	Venless Long
CONDUCTED EMISSION	22deg. C, 62%RH	5Vdc from adapter	Venless Long
RADIATED EMISSION	25deg. C, 60%RH	5Vdc from adapter	Venless Long

3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

ANSI/TIA/EIA-603-C 2004

NOTE: All test items have been performed and recorded as per the above standards.



4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

4.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:


- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS & EDGE and 5MHz for WCDMA mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step b. Record the power level of S.G
- d. EIRP = Output power level of S.G - TX cable loss + Antenna gain of substitution horn. E.R.P power can be calculated from E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15dBi.

CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with GSM, GPRS, EDGE & WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

4.1.3 TEST SETUP

EIRP / ERP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).



Test Report No.: RF121126N003-1

4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM850		
Channel	128	190	251
Frequency (MHz)	824.2	836.4	848.8
GSM	33.04	32.78	32.86
GPRS 8	32.99	32.83	32.90
GPRS 10	32.18	31.93	32.00
EDGE 8 (MCS1)	33.02	32.79	32.89
EDGE 10 (MCS1)	32.16	31.93	31.99
EDGE 8 (MCS9)	27.02	27.03	26.90
EDGE 10 (MCS9)	25.92	25.90	25.82

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	23.52	24.43	23.43
HSDPA Subtest-1	22.97	24.08	23.06
HSDPA Subtest-2	23.02	23.94	23.02
HSDPA Subtest-3	22.95	23.82	22.95
HSDPA Subtest-4	22.94	23.78	22.93
HSUPA Subtest-1	20.88	21.62	20.92
HSUPA Subtest-2	21.45	22.28	21.37
HSUPA Subtest-3	21.04	21.86	21.01
HSUPA Subtest-4	21.52	22.31	21.42
HSUPA Subtest-5	21.34	22.18	21.37



Test Report No.: RF121126N003-1

BUREAU
VERITAS

ERP POWER (dBm)

GSM 850 (Horizontal)					
CHANNEL NO.	FREQUENCY (MHz)	SPA Reading (dBm)	CORRECTION FACTOR (dB)	OUTPUT POWER	
				dBm	Watt
128	824.2	1.05	32.91	31.81	1.52
189	836.4	0.93	33.7	32.48	1.77
251	848.8	0.62	34.14	32.61	1.82

GSM 850 (Vertical)

CHANNEL NO.	FREQUENCY (MHz)	SPA Reading (dBm)	CORRECTION FACTOR (dB)	OUTPUT POWER	
				dBm	Watt
128	824.2	-10.13	35.18	22.90	0.19
189	836.4	-9.69	35.27	23.43	0.22
251	848.8	-9.45	35.27	23.67	0.23

EDGE 850 (1 Uplink) (Horizontal)

CHANNEL NO.	FREQUENCY (MHz)	SPA Reading (dBm)	CORRECTION FACTOR (dB)	OUTPUT POWER	
				dBm	Watt
128	824.2	-2.46	32.91	28.30	0.68
190	836.6	-2.60	33.7	28.95	0.79
251	848.8	-2.33	34.14	29.66	0.92

EDGE 850 (1 Uplink) (Vertical)

CHANNEL NO.	FREQUENCY (MHz)	SPA Reading (dBm)	CORRECTION FACTOR (dB)	OUTPUT POWER	
				dBm	Watt
128	824.2	-12.42	35.18	20.61	0.12
190	836.6	-12.27	35.27	20.85	0.12
251	848.8	-12.71	35.27	20.41	0.11

WCDMA Band V_RMC 12.2K (Horizontal)

CHANNEL NO.	FREQUENCY (MHz)	SPA Reading (dBm)	CORRECTION FACTOR (dB)	OUTPUT POWER	
				dBm	Watt
4132	826.4	-6.86	33.11	24.10	0.26
4182	836.4	-7.01	33.7	24.54	0.28
4233	846.6	-7.25	34.13	24.73	0.30

WCDMA Band V_RMC 12.2K (Vertical)

CHANNEL NO.	FREQUENCY (MHz)	SPA Reading (dBm)	CORRECTION FACTOR (dB)	OUTPUT POWER	
				dBm	Watt
4132	826.4	-15.89	35.28	17.24	0.05
4182	836.4	-16.43	35.27	16.69	0.05
4233	846.6	-16.72	35.37	16.50	0.04

REMARKS: 1. ERP Output Power (dBm) = SPA Reading (dBm) + Correction Factor (dB) -2.15 (dB)

2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


1.5 ppm is for base and fixed station. 2.5 ppm is for mobile station.

4.2.2 TEST PROCEDURE

- a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP





Test Report No.: RF121126N003-1

BUREAU
VERITAS

4.2.4 TEST RESULTS

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)			LIMIT (ppm)
	GSM	EDGE	WCDMA	
4.2	-0.01	-0.02	-0.01	2.5
3.4	-0.01	-0.01	-0.01	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.4Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.


TEMP. (°C)	FREQUENCY ERROR (ppm)			LIMIT (ppm)
	GSM	EDGE	WCDMA	
40	-0.02	-0.01	-0.02	2.5
30	-0.02	-0.02	-0.01	2.5
20	-0.01	-0.01	-0.02	2.5
10	-0.02	-0.01	-0.02	2.5
0	-0.02	-0.02	-0.01	2.5
-10	-0.01	-0.01	-0.02	2.5
-20	-0.02	-0.01	-0.02	2.5

4.3 OCCUPIED BANDWIDTH MEASUREMENT

4.3.1 TEST PROCEDURES

The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.


4.3.2 TEST SETUP





4.3.3 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (kHz)		CHANNEL	FREQUENCY (MHz)	99% OCCUPIED BANDWIDTH (MHz)	
		GSM	EDGE			WCDMA	
128	824.2	244.57	237.76	4132	826.4	4.155	
190	836.6	243.12	239.76	4182	836.4	4.185	
251	848.8	243.12	239.76	4233	846.6	4.175	




4.4 BAND EDGE MEASUREMENT

4.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 TEST SETUP




4.4.3 TEST PROCEDURES

- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1.5 MHz. RB of the spectrum is 3kHz and VB of the spectrum is 10kHz (GSM/GPRS/EDGE).
- c. The center frequency of spectrum is the band edge frequency and span is 10MHz. RB of the spectrum is 100kHz and VB of the spectrum is 300kHz (WCDMA).
- d. Record the max trace plot into the test report.




4.4.4 TEST RESULTS


GSM



EDGE



WCDMA



4.5 CONDUCTED SPURIOUS EMISSIONS


4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.

4.5.2 TEST PROCEDURE


- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- Measuring frequency range is from 9 kHz to 9GHz. 20dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.5.3 TEST SETUP





4.5.4 TEST RESULTS






Test Report No.: RF121126N003-1


EDGE

CHANNEL 128


FREQUENCY RANGE : 30MHz~1GHz




FREQUENCY RANGE : 1GHz~3GHz



FREQUENCY RANGE : 3GHz~7GHz



FREQUENCY RANGE : 7GHz~9GHz



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd.,
Houjie Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080


Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: RF121126N003-1

WCDMA

CHANNEL 4133





4.6 RADIATED EMISSION MEASUREMENT

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.6.2 TEST PROCEDURES


- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dBi.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

4.6.3 DEVIATION FROM TEST STANDARD

No deviation

4.6.4 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).



Test Report No.: RF121126N003-1

BUREAU
VERITAS

4.6.5 TEST RESULTS

GSM:

FREQUENCY RANGE	Below 1000MHz	INPUT POWER	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH	TESTED BY	Venless Long

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBuV)	Limit (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)
1	1672	-51.78	-13	-47.09	0.46	-46.63
2	2509	-50.4	-13	-41.70	0.17	-41.53
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBuV)	Limit (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)
1	1672	-53.34	-13	-46.14	0.46	-45.68
2	2509	-45.55	-13	-35.34	0.17	-35.17

REMARKS:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB) - 2.15 (dB)

EDGE:

FREQUENCY RANGE	Below 1000MHz	INPUT POWER	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	26deg. C, 65%RH	TESTED BY	Venless Long

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBuV)	Limit (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)
1	1672	-54.33	-13	-49.71	0.46	-49.25
2	2509	-60.23	-13	-51.93	0.17	-51.76
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M						
No.	Freq. (MHz)	Emission Level (dBuV)	Limit (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)
1	1672	-53.42	-13	-46.23	0.46	-45.77
2	2509	-43.11	-13	-32.82	0.17	-32.65

REMARKS:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB) - 2.15 (dB)



Test Report No.: RF121126N003-1

WCDMA:

FREQUENCY RANGE	Below 1000MHz	INPUT POWER	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	25deg. C, 60%RH	TESTED BY	Venless Long

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV)	Limit (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)
1	1672	-56.23	-13	-51.66	0.46	-51.20
2	2509	-63.54	-13	-55.38	0.17	-55.21

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV)	Limit (dBm)	S.G Power Value (dBm)	Correction Factor (dB)	ERP (dBm)
1	1672	-56.33	-13	-49.26	0.46	-48.80
2	2509	-46.05	-13	-35.86	0.17	-35.69

REMARKS:

1. ERP (dBm) = S.G Value (dBm) + Correction Factor (dB).
2. Correction Factor (dB) = Substitution Antenna Gain (dB) + Cable Loss (dB) - 2.15 (dB)



Test Report No.: RF121126N003-1

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF121126N003-1

6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch, were founded in 2002 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Dongguan EMC/RF Lab:

Tel: +86-769-85935656

Fax: +86-769-85931080

Email: customerservice.dg@cn.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



Test Report No.: RF121126N003-1

7 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---