



**HCT CO., LTD.**

Product Compliance Division

TEL : +82 31 639 8518 FAX : +82 31 639 8535

**CERTIFICATE OF COMPLIANCE**  
**FCC Certification**

**Applicant Name:**  
Vertex Wireless Co., Ltd.

**Address:**  
5F, Dongnam B/D, 8-8 Sunae-Dong, Bundang-Gu,  
Seongnam-City, Kyunggi-Do, Korea

**Date of Issue:**

July 30, 2010

**Location:**

HCT CO., LTD., San 136-1 Ami-ri, Bubal-eup, Icheon-si,  
Kyungki-do, Korea

**Test Report No.:** HCTR1007FR26

**HCT FRN:** 0005866421

**IC Recognition No.:** IC 5944A-1

<b>FCC ID</b>	: XAVVW440
	:
<b>APPLICANT</b>	: Vertex Wireless Co., Ltd.

**FCC Model(s):** VW440

**IC Model(s):** VW440

**EUT Type:** CDMA EV-DO Rev.A Terminal

**Tx Frequency:** 824.70 — 848.31 MHz (CDMA)  
1 851.25 — 1 908.75 MHz (PCS CDMA)

**Rx Frequency:** 869.70 — 893.31 MHz (CDMA)  
1 931.25 — 1 988.75 MHz (PCS CDMA)

**Max. RF Output Power:** 1.076 W ERP CDMA (30.32 dBm) / 0.667 W EIRP PCS CDMA (28.24 dBm) /  
1.324 W ERP CDMA EVDO (31.22 dBm) / 0.824 W EIRP PCS EVDO (29.16 dBm)

**Emission Designator(s):** 1M28F9W (CDMA), 1M29F9W (PCS CDMA),  
1M28F9W (CDMA EVDO), 1M28F9W (PCS CDMA EVDO)

**FCC Classification:** PCS Licensed Transmitter (PCB)

**FCC Rule Part(s):** §22, §24, §2

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has been denied FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998, 21 U.S.C. 853(a)

Hyo Sun Kwak

Report prepared by

: Hyo Sun Kwak

Test engineer of RF Team

Approved by

: Sang Jun Lee

Manager of RF Team

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Date of Issue: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVW440	Page 1 of 41



## Version

TEST REPORT NO.	DATE	DESCRIPTION
HCTR1007FR26	July 30, 2010	- First Approval Report

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 2 of 41

## Table of Contents

1. GENERAL INFORMATION .....	4
2. INTRODUCTION .....	5
2.1. EUT DESCRIPTION.....	5
2.2. MEASURING INSTRUMENT CALIBRATION.....	5
2.3. TEST FACILITY .....	5
3. DESCRIPTION OF TESTS .....	6
3.1 EFFECTIVE RADIATED POWER/EQUIVALENT ISOTROPIC RADIATED POWER.....	6
3.2 OCCUPIED BANDWIDTH.....	7
3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.....	8
3.4 RADIATED SPURIOUS AND HARMONIC EMISSIONS .....	9
3.5 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	1 0
4. LIST OF TEST EQUIPMENT .....	1 1
5. SUMMARY OF TEST RESULTS .....	1 2
6. SAMPLE CALCULATION .....	1 3
7. TEST DATA .....	1 4
7.1 CONDUCTED OUTPUT POWER .....	1 4
7.2 PEAK-TO-AVERAGE RATIO .....	1 4
7.3 OCCUPIED BANDWIDTH .....	1 5
7.4 CONDUCTED SPURIOUS EMISSIONS .....	1 5
7.4.1 BAND EDGE.....	1 5
7.5 EFFECTIVE RADIATED POWER OUTPUT(CDMA) .....	1 6
7.6 EQUIVALENT ISOTROPIC RADIATED POWER (E.I.R.P.) (PCS CDMA) .....	1 7
7.7 RADIATED SPURIOUS EMISSIONS .....	1 8
7.7.1 RADIATED APURIOUS EMISSIONS(FETAP on CDMA EVDO Rev.A Mode).....	1 8
7.7.2 RADIATED SPURIOUS EMISSIONS(FTAP on PCS EVDO Rev.A Mode).....	1 9
7.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE .....	2 0
7.8.1 FREQUENCY STABILITY(CDMA).....	2 0
7.8.2 FREQUENCY STABILITY(PCS CDMA) .....	2 1
8. TEST PLOTS.....	2 2

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 3 of 41



# MEASUREMENT REPORT

## 1. GENERAL INFORMATION

**Applicant Name:** Vertex Wireless Co., Ltd.

**Address:** 5F, Dongnam B/D, 8-8 Sunae-Dong, Bundang-Gu, Seongnam-City, Kyunggi-Do, Korea

**Contact Person:** Name: Brian Jun  
Phone #: TEL :+82-31-702-4901 / FAX : +82-31-702-4567

**FCC ID:** XAVVW440

**Application Type:** Certification

**FCC Classification:** PCS Licensed Transmitter (PCB)

**FCC Rule Part(s):** §22, §24, §2

**EUT Type:** CDMA EV-DO Rev.A Terminal

**FCC Model(s):** VW440

**IC Model(s):** VW440

**Tx Frequency:** 824.70 — 848.31 MHz (CDMA)  
1 851.25 — 1 908.75 MHz (PCS CDMA)

**Rx Frequency:** 869.70 — 893.31 MHz (CDMA)  
1 931.25 — 1 988.75 MHz (PCS CDMA)

**Max. RF Output Power:** 1.076 W ERP CDMA (30.32 dBm) / 0.667 W EIRP PCS CDMA (28.24 dBm) /  
1.324 W ERP CDMA EVDO (31.22 dBm) / 0.824 W EIRP PCS EVDO (29.16 dBm)

**Emission Designator(s):** 1M28F9W (CDMA), 1M29F9W (PCS CDMA),  
1M28F9W (CDMA EVDO), 1M28F9W (PCS CDMA EVDO)

**Antenna Specification**  
Manufacturer: Hankook Antenna CO,.LTD  
Antenna type: Dipole Antenna  
Peak Gain: 2.05 dBi

**Date(s) of Tests:** July 26, 2010 ~ July 29, 2010

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVW440	Page 4 of 41



## 2. INTRODUCTION

### **2.1. EUT DESCRIPTION**

The VW440 CDMA EV-DO Rev.A Terminal consists of Cellular CDMA, PCS CDMA and 1xEVDO Rev.A.

### **2.2. MEASURING INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

### **2.3. TEST FACILITY**


The open area test site and conducted measurement facility used to collect the radiated data are located at the 254-1, Maekok-Ri, Hobup-Myun, Ichon-Si, Kyoungki-Do, 467-701, KOREA. The site is constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. Detailed description of test facility was submitted to the Commission and accepted dated June 10, 2009 (Registration Number: 90661)

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 5 of 41

### 3. DESCRIPTION OF TESTS

#### 3.1 EFFECTIVE RADIATED POWER/EQUIVALENT ISOTROPIC RADIATED POWER

##### Test Set-up



##### Test Procedure

Radiated emission measurements were performed at an open Site.

The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

A wooden turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.


The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC1/SO55, with 'All Up' power control bits.

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 6 of 41

### 3.2 OCCUPIED BANDWIDTH.

#### Test set-up



(Configuration of conducted Emission measurement)

#### Test Procedure

The EUT was setup to maximum output power at its lowest channel. The occupied bandwidth was measured using a spectrum analyzer. The measurements are repeated for the highest and a middle channel. The EUT's occupied bandwidth is measured as the width of the signal between two points, one below the carrier center frequency and one above the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Plots of the EUT's occupied bandwidth are shown herein.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC1/SO55, with 'All Up' power control bits.

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 7 of 41



### 3.3 SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL.

#### Test Procedure

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer.

The EUT was setup to maximum output power at its lowest channel. The Resolution BW of the analyzer is set to 1 % of the emission bandwidth to show compliance with the – 13 dBm limit, in the 1 MHz bands immediately outside and adjacent to the edge of the frequency block. The 1 MHz RBW was used to scan from 30 MHz to 10 GHz. (PCS CDMA Mode: 30 MHz to 20 GHz). A display line was placed at – 13 dBm to show compliance. The high, lowest and a middle channel were tested for out of band measurements.


- Band Edge Requirement : In the 1MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions. Limit, -13dBm.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC1/SO55, with 'All Up' power control bits.

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 8 of 41

### 3.4 RADIATED SPURIOUS AND HARMONIC EMISSIONS

#### Test Set-up



The measurement facilities used for this test have been documented in previous filings with the commission pursuant to section § 2.948. The open field test site is situated in open field with ground screen whose site attenuation characteristics meet ANSI C63.4 –2003. A mast capable of lifting the receiving antenna from a height of one to four meters is used together with a rotatable wooden platform mounted at three from the antenna mast.

- 1) The unit mounted on a wooden table 1.5 m × 1.0 m × 0.80 m is 0.8 meter above test site ground level.
- 2) During the emission test, the turntable is rotated and the EUT is manipulated to find the configuration resulting in maximum emission under normal condition of installation and operation.
- 3) The antenna height and polarization are also varied from 1 to 4 meters until the maximum signal is found.
- 4) The spectrum shall be scanned up to the 10<sup>th</sup> harmonic of the fundamental frequency.

#### Test Procedure

The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

A wooden turntable was rotated 360° and the receiving antenna scanned from 1-4m in order to capture the maximum emission. A half wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the previously recorded signal was duplicated.


The maximum EIRP was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried out with the receiving antenna in both vertical and horizontal polarization. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC1/SO55, with 'All Up' power control bits.

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 9 of 41

### 3.5 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

#### Test Set-up



#### Test Procedure

The frequency stability of the transmitter is measured by:

- a.) **Temperature:** The temperature is varied from - 30 °C to + 50 °C using an environmental chamber.
- b.) **Primary Supply Voltage:** The primary supply voltage is varied from battery end point to 115 % of the voltage normally at the input to the device or at the power supply terminals if cables are not normally supplied.

Specification — the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.000\ 25\% (\pm 2.5\ ppm)$  of the center frequency.

#### Time Period and Procedure:

The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).

1. The equipment is turned on in a “standby” condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
2. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

**NOTE: The EUT is tested down to the battery endpoint.**

Note : This device was tested under all R.C.s and S.O.s and worst case is reported with RC1/SO55, with 'All Up' power control bits.

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 10 of 41



#### 4. LIST OF TEST EQUIPMENT

Manufacture	Model/ Equipment	Serial Number	Calibration Interval	Calibration Due
R&S	ESI40/ Spectrum Analyzer	831564/003	Annual	10/30/2010
Agilent	E4416A/ Power Meter	GB41291412	Annual	01/14/2011
Agilent	E9327A/ Power Sensor	MY4442009	Annual	07/23/2011
Agilent	8960 (E5515C)/ Base Station	GB44400269	Annual	02/10/2011
MITEQ	AMF-6D-001180-35-20P/AMP	990893	Annual	05/20/2011
Wainwright	WHK1.2/15G-10EF/H.P.F	2	Annual	06/25/2011
Wainwright	WHK3.3/18G-10EF/H.P.F	1	Annual	06/25/2011
Agilent	775D/ Dual Directional Coupler	12922	Annual	12/24/2010
Agilent	11636B/ Power Divider	11377	Annual	12/24/2010
Digital	EP-3010/ Power Supply	3110117	Annual	01/08/2011
Schwarzbeck	UHAP/ Dipole Antenna	585	Biennial	02/13/2011
Schwarzbeck	UHAP/ Dipole Antenna	558	Biennial	02/13/2011
Korea Engineering	KR-1005L / Chamber	KRAB07063-2CH	Annual	12/28/2010
Schwarzbeck	BBHA 9120D/ Horn Antenna	296	Biennial	09/23/2011
Agilent	E4440A/Spectrum Analyzer	US45303008	Annual	06/09/2011

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 11 of 41



## 5. SUMMARY OF TEST RESULTS

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result
2.1049, 22.917(a), 24.238(a), 27.53(h)	Occupied Bandwidth	N/A	CONDUCTED	PASS
2.1051, 22.917(a), 24.238(a), 27.53(h)	Band Edge / Spurious and Harmonic Emissions at Antenna Terminal.	< 43 + 10log <sub>10</sub> (P[Watts]) at Band Edge and for all out-of-band emissions		PASS
2.1046	Conducted Output Power	N/A		PASS
24.232(d),	Peak- to- Average Ratio	< 13 dB		PASS
2.1055, 22.355, 24.235, 27.54	Frequency stability / variation of ambient temperature	< 2.5 ppm		PASS
22.913(a)(2) 24.232(c), 27.50(d)(2)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS
	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP(PCS) < 1 Watts max. EIRP(AWS)		PASS
2.1053, 22.917(a), 24.238(a), 27.53(h)	Radiated Spurious and Harmonic Emissions	< 43 + 10log <sub>10</sub> (P[Watts]) for all out-of band emissions		PASS

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 1 2 of 41



## 6. SAMPLE CALCULATION

### **A. ERP Sample Calculation**

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL(dBm)	Ant. Gain	C.L	Pol.	ERP	
	channel	Freq.(MHz)						W	dBm
CDMA	384	836.52	-10.96	24.81	2.50	1.19	H	0.41	26.12

**ERP = SubstituteLEVEL(dBm) + Ant. Gain – CL(Cable Loss)**

- 1) The EUT mounted on a wooden tripod is 0.8 meter above test site ground level.
- 2) During the test , the turn table is rotated and the antenna height is also varied from 1 to 4 meters until the maximum signal is found.
- 3) Record the field strength meter's level.
- 4) Replace the EUT with dipole/Horn antenna that is connected to a calibrated signal generator.
- 5) Increase the signal generator output till the field strength meter's level is equal to the item (3).
- 6) The signal generator output level with Ant. Gain and cable loss are the rating of effective radiated power (**ERP**).

### **B. Emission Designator**

#### **CDMA Emission Designator**

**Emission Designator = 1M27F9W**

CDMA BW = 1.27 MHz (Measured at the 99% power bandwidth)

F = Frequency Modulation

9 = Composite Digital Info


W = Combination (Audio/Data)

FCC CERTIFICATION REPORT					<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No.	Test Dates:	EUT Type:	FCC ID:		Page 13 of 41
HCTR1007FR26	July 30, 2010	CDMA EV-DO Rev.A Terminal	XAVVVW440		

## 7. TEST DATA

### 7.1 CONDUCTED OUTPUT POWER

A base station simulator was used to establish communication with The EUT. The base station simulator parameters were set to produce the maximum power from the EUT. This device was tested under all configurations and the highest power is reported. Conducted Output Powers of EUT are reported below.



Band	Channel	SO2	SO2	SO55	SO55	TDSO SO32	1xEvD Rev.O	1xEvD Rev.O	1xEvDO Rev.1	1xEvDO Rev.1
		RC1/1	RC3/3	RC1/1	RC3/3	RC3/3	(FTAP)	(RTAP)	(FETAP)	(RETAP)
CDMA	1013	23.31	23.34	23.34	23.31	23.40	23.29	23.25	23.29	23.27
	384	23.66	23.75	23.78	23.75	23.87	23.60	23.59	23.61	23.56
	777	23.50	23.53	23.47	23.42	23.45	23.22	23.26	23.34	23.33
PCS	25	23.75	23.71	23.66	23.67	23.69	24.33	24.30	24.35	24.32
	600	23.41	23.43	23.33	23.34	23.39	24.84	24.78	24.82	24.81
	1175	23.71	23.61	23.62	23.75	23.72	23.45	23.45	23.49	23.47

(Maximum Conducted Output Powers)

### 7.2 PEAK-TO-AVERAGE RATIO

- Plots of the EUT's Peak- to- Average Ratio are shown Page 27.

FCC CERTIFICATION REPORT					<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal		FCC ID: XAVVVW440	Page 14 of 41



### 7.3 OCCUPIED BANDWIDTH

Band	Channel	Frequency(MHz)	Data (kHz)
CDMA	1013	824.70	1.2802
	384	836.52	1.2842
	777	848.31	1.2801
CDMA EVDO	384	836.52	1.2817
PCS	25	1851.25	1.2922
	600	1880.00	1.2840
	1175	1908.75	1.2875
PCS EVDO	25	1851.25	1.2847

- Plots of the EUT's Occupied Bandwidth are shown Page 22 ~ 26.

### 7.4 CONDUCTED SPURIOUS EMISSIONS

Band	Channel	Frequency of Maximum Harmonic (GHz)	Maximum Data (dBm)
CDMA	1013	3.3000	-39.08
	384	3.3500	-37.80
	777	1.6970	-38.19
PCS	25	14.4000	-37.22
	600	13.9200	-36.67
	1175	1.8500	-36.06

- Plots of the EUT's Conducted Spurious Emissions are shown Page 35 ~ 41

#### 7.4.1 BAND EDGE

- Plots of the EUT's Band Edge are shown Page 27 ~35.

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 15 of 41
HCTR1007FR26	July 30, 2010	CDMA EV-DO Rev.A Terminal	XAVVVW440	



## 7.5 EFFECTIVE RADIATED POWER OUTPUT(CDMA)

### (CDMA Mode)

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain	C.L	Pol. (EUT–Antenna of EUT – Detecting Antenna)	ERP	
	channel	Freq.(MHz)						W	dBm
CDMA	1013	824.70	-7.14	40.63	-10.25	1.17	y – y – V	0.83	29.21
	384	836.52	-7.31	41.32	-10.36	1.19	y – y – V	0.95	29.77
	777	848.31	-7.48	41.99	-10.47	1.20	y – y – V	1.08	30.32
EVDO	1013	824.70	-6.07	41.70	-10.25	1.17	y – y – V	1.07	30.28
	384	836.52	-6.42	42.21	-10.36	1.19	y – y – V	1.16	30.66
	777	848.31	-6.58	42.89	-10.47	1.20	y – y – V	1.32	31.22

Note: This unit was tested with a notebook computer.

### NOTES:

Effective Radiated Power Output Measurements by Substitution Method

according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is in y plane in CDMA mode. Also worst case of detecting Antenna is in vertical polarization in CDMA mode.

The EVDO mode testing were performed using FETAP on Rev.A because FETAP on Rev.A is highest power in EVDO mode.

FCC CERTIFICATION REPORT					<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page	of 41
HCTR1007FR26	July 30, 2010	CDMA EV-DO Rev.A Terminal	XAVVVW440	16	of 41



## 7.6 EQUIVALENT ISOTROPIC RADIATED POWER (E.I.R.P.) (PCS CDMA)

### (PCS CDMA Mode)

Mode	Ch./ Freq.		Measured Level(dBm)	Substitute LEVEL (dBm)	Ant. Gain	C.L	Pol. (EUT–Antenna of EUT – Detecting Antenna)	EIRP	
	channel	Freq.(MHz)						W	dBm
PCS	25	1,851.25	-11.50	19.75	10.40	1.91	x – x – H	0.67	28.24
	600	1,880.00	-11.69	19.75	10.43	1.95	x – x – H	0.67	28.23
	1175	1,908.75	-12.29	19.20	10.47	1.97	x – x – H	0.59	27.70
EVDO	25	1,851.25	-10.58	20.67	10.40	1.91	x – x – H	0.82	29.16
	600	1,880.00	-10.79	20.65	10.43	1.95	x – x – H	0.82	29.13
	1175	1,908.75	-11.81	19.68	10.47	1.97	x – x – H	0.66	28.18

Note: This unit was tested with a notebook computer.

### NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method  
according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For CDMA signals, a peak detector is used, with RBW = VBW = 3 MHz. For WCDMA signals, a peak detector is used, with RBW = VBW = 5MHz. For AMPS, GSM, and NADC TDMA signals, a peak detector is used, with RBW = VBW = 1 MHz. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all configurations and the highest power is reported.

Also, we have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna. The worst case of the EUT is in x plane and worst case of detecting Antenna is in Horizontal polarization.

The EVDO mode testing were performed using FETAP on Rev.A because FETAP on Rev.A is highest power in EVDO mode.

FCC CERTIFICATION REPORT					<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page	of 41
HCTR1007FR26	July 30, 2010	CDMA EV-DO Rev.A Terminal	XAVVVW440	1 7	of 41



## 7.7 RADIATED SPURIOUS EMISSIONS

### 7.7.1 RADIATED SPURIOUS EMISSIONS(FETAP on CDMA EVDO Rev.A Mode)

MEASURED OUTPUT POWER: 31.22 dBm = 1.324 W

MODULATION SIGNAL: CDMA EVDO

DISTANCE: 3 meters

LIMIT: - (43 + 10 log<sub>10</sub> (W)) = - 44.22 dBc

Ch.	Freq.(MHz)	<u>Measured Level</u> [dBm]	Ant. Gain	<u>Substitute</u> <u>Level</u> [dBm]	C.L	Pol.	ERP (dBm)	dBc
1013	1,649.40	-35.22	7.09	-45.75	1.73	H	-40.39	-70.71
	2,474.10	-43.56	8.12	-50.67	2.28	H	-44.83	-75.15
	3,298.80	-36.55	9.72	-44.13	2.57	H	-36.98	-67.30
384	1,673.04	-40.61	7.23	-51.37	1.79	H	-45.93	-76.25
	2,509.56	-48.36	8.14	-55.49	2.33	V	-49.68	-80.00
	3,346.08	-37.58	9.99	-45.61	2.66	V	-38.28	-68.60
777	1,696.62	-36.27	7.41	-46.88	1.83	H	-41.30	-71.62
	2,544.93	-45.70	8.21	-52.98	2.34	V	-47.11	-77.43
	3,393.24	-35.59	9.91	-43.22	2.85	V	-36.16	-66.48

**NOTES:**

1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:
2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5<sup>th</sup> Harmonic for all channel.
3. we have done x, y planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The testing were performed using FETAP on Rev.A because FETAP on Rev.A is highest power in CDMA EVDO and CDMA mode.

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 18 of 41



### 7.7.2 RADIATED SPURIOUS EMISSIONS(FTAP on PCS EVDO Rev.A Mode)

- MEASURED OUTPUT POWER: 29.16 dBm = 0.824 W
- MODULATION SIGNAL: PCS CDMA EVDO
- DISTANCE: 3 meters
- LIMIT: - (43 + 10  $\log_{10}$  (W)) = - 42.16 dBc

Ch.	Freq.(MHz)	<u>Measured Level</u> <u>[dBm]</u>	Ant. Gain	<u>Substitute</u> <u>Level</u> <u>[dBm]</u>	C.L	Pol.	ERP (dBm)	dBc
25	3,702.50	-49.68	12.46	-55.95	2.73	V	-46.22	-74.46
	5,553.75	-32.41	12.70	-33.99	3.60	H	-24.89	-53.13
	7,405.00	-53.50	11.36	-44.62	3.88	V	-37.14	-65.38
600	3,760.00	-47.32	12.47	-53.29	2.73	H	-43.55	-71.79
	5,640.00	-31.04	12.75	-32.69	3.60	H	-23.54	-51.78
	7,520.00	-50.97	11.33	-41.87	3.88	V	-34.42	-62.66
1175	3,817.50	-49.22	12.49	-55.10	2.73	V	-45.34	-73.58
	5,726.25	-30.46	12.80	-31.77	3.60	V	-22.57	-50.81
	7,635.00	-47.38	11.30	-38.05	3.88	V	-30.63	-58.87

**NOTES:**

1. Radiated Spurious Emission Measurements at 3 meters by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004;
2. The magnitude of spurious emissions attenuated more than 20dB below the limit above 5<sup>th</sup> Harmonic for all channel.
3. we have done x, y planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The testing were performed using FETAP on Rev.A because FETAP on Rev.A is highest power in CDMA EVDO and CDMA mode.


FCC CERTIFICATION REPORT					<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No.	Test Dates:	EUT Type:	FCC ID:	Page 19 of 41	
HCTR1007FR26	July 30, 2010	CDMA EV-DO Rev.A Terminal	XAVVVW440		

## 7.8 FREQUENCY STABILITY / VARIATION OF AMBIENT TEMPERATURE

### 7.8.1 FREQUENCY STABILITY(CDMA)

OPERATING FREQUENCY: 836,520,000 Hz  
 CHANNEL: 384  
 REFERENCE VOLTAGE: 3.7 VDC  
 DEVIATION LIMIT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	836 519 998	0	0.000 000	0.000
100%		-30	836 520 007	6.78	0.000 001	0.008
100%		-20	836 520 007	6.67	0.000 001	0.008
100%		-10	836 520 015	15.24	0.000 002	0.018
100%		0	836 520 002	1.95	0.000 000	0.002
100%		+10	836 520 012	11.97	0.000 001	0.014
100%		+30	836 520 004	3.60	0.000 000	0.004
100%		+40	836 519 994	-6.36	-0.000 001	-0.008
100%		+50	836 520 001	1.23	0.000 000	0.001
115%	4.255	+20	836 519 992	-8.20	-0.000 001	-0.010
Batt. Endpoint	3.400	+20	836 519 993	-7.44	-0.000 001	-0.009




FCC CERTIFICATION REPORT					<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal		FCC ID: XAVVVW440	Page 20 of 41

### 7.8.2 FREQUENCY STABILITY(PCS CDMA)

OPERATING FREQUENCY: 1880,000,000 Hz  
 CHANNEL: 600  
 REFERENCE VOLTAGE: 3.7 VDC  
 DEVIATION LIM IT: ± 0.000 25 % or 2.5 ppm

Voltage (%)	Power (VDC)	Temp. (°C)	Frequency (Hz)	Frequency Error (Hz)	Deviation (%)	ppm
100%	3.700	+20(Ref)	1879 999 999	0	0.000 000	0.000
100%		-30	1880 000 009	8.86	0.000 000	0.005
100%		-20	1879 999 998	-1.54	0.000 000	-0.001
100%		-10	1879 999 997	-2.89	0.000 000	-0.002
100%		0	1880 000 004	3.68	0.000 000	0.002
100%		+10	1880 000 005	4.51	0.000 000	0.002
100%		+30	1879 999 995	-4.89	0.000 000	-0.003
100%		+40	1879 999 999	-1.38	0.000 000	-0.001
100%		+50	1880 000 012	11.67	0.000 001	0.006
115%	4.255	+20	1880 000 003	3.44	0.000 000	0.002
Batt. Endpoint	3.400	+20	1880 000 007	6.61	0.000 000	0.004




FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 21 of 41




## 8. TEST PLOTS

FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 22 of 41


■ CDMA MODE (1013 CH.) Occupied Bandwidth




■ CDMA MODE (384 CH.) Occupied Bandwidth



■ CDMA MODE (777 CH.) Occupied Bandwidth



■ CDMA EVDO MODE (384 CH.) Occupied Bandwidth




FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 24 of 41


■ PCS CDMA MODE (25 CH.) Occupied Bandwidth




■ PCS CDMA MODE (600 CH.) Occupied Bandwidth



■ PCS CDMA MODE (1175 CH.) Occupied Bandwidth



■ PCS CDMA EVDO MODE (25 CH.) Occupied Bandwidth




FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 26 of 41


■ PCS CDMA MODE (600 CH.) Peak-to-Average Ratio




■ CDMA MODE (1013 CH.) Block Edge



## ■ CDMA MODE (777 CH.) Block Edge




## ■ CDMA EVDO MODE (1013 CH.) Block Edge



Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 28 of 41
---------------------------------	------------------------------	--	----------------------	---------------

■ CDMA EVDO MODE (777 CH.) Block Edge



■ CDMA MODE (1013 CH.) 4 MHz Span



FCC CERTIFICATION REPORT

[www.hct.co.kr](http://www.hct.co.kr)

Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 29 of 41
---------------------------------	------------------------------	--	----------------------	---------------

■ CDMA MODE (777 CH.) 4 MHz Span




■ CDMA EVDO MODE (1013 CH.) 4 MHz Span




Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 30 of 41
---------------------------------	------------------------------	--	----------------------	---------------

■ CDMA EVDO MODE (777 CH.) 4 MHz Span




■ PCS CDMA MODE (25 CH.) Block Edge




FCC CERTIFICATION REPORT

Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	<a href="http://www.hct.co.kr">www.hct.co.kr</a>
				Page 31 of 41

■ PCS CDMA MODE (1175 CH.) Block Edge




■ PCS CDMA EVDO MODE (25 CH.) Block Edge




FCC CERTIFICATION REPORT

Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	<a href="http://www.hct.co.kr">www.hct.co.kr</a>
				Page 32 of 41


■ PCS CDMA EVDO MODE (1175 CH.) Block Edge




■ PCS CDMA MODE (25 CH.) 4 MHz Span



■ PCS CDMA MODE (1175 CH.) 4 MHz Span



■ PCS CDMA EVDO MODE (25 CH.) 4 MHz Span




FCC CERTIFICATION REPORT


[www.hct.co.kr](http://www.hct.co.kr)

Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 34 of 41
---------------------------------	------------------------------	--	----------------------	---------------

■ PCS CDMA EVDO MODE (1175 CH.) 4 MHz Span




■ CDMA MODE (1013 CH.) Conducted Spurious Emissions - 1




FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 35 of 41

■ CDMA MODE (1013 CH.) Conducted Spurious Emissions - 2




■ CDMA MODE (384 CH.) Conducted Spurious Emissions - 1




FCC CERTIFICATION REPORT

Test Report No.	Test Dates:	EUT Type:	FCC ID:	<a href="http://www.hct.co.kr">www.hct.co.kr</a>
HCTR1007FR26	July 30, 2010	CDMA EV-DO Rev.A Terminal	XAVVVW440	Page 36 of 41


■ CDMA MODE (384 CH.) Conducted Spurious Emissions - 2




■ CDMA MODE (777 CH.) Conducted Spurious Emissions - 1



■ CDMA MODE (777 CH.) Conducted Spurious Emissions - 2




■ PCS CDMA MODE (25 CH.) Conducted Spurious Emissions - 1




Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 38 of 41
---------------------------------	------------------------------	--	----------------------	---------------

■ PCS CDMA MODE (25 CH.) Conducted Spurious Emissions - 2




■ PCS CDMA MODE (600 CH.) Conducted Spurious Emissions - 1




Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 39 of 41
---------------------------------	------------------------------	--	----------------------	---------------


■ PCS CDMA MODE (600 CH.) Conducted Spurious Emissions - 2



■ PCS CDMA MODE (1175 CH.) Conducted Spurious Emissions - 1



■ PCS CDMA MODE (1175 CH.) Conducted Spurious Emissions - 2



FCC CERTIFICATION REPORT				<a href="http://www.hct.co.kr">www.hct.co.kr</a>
Test Report No. HCTR1007FR26	Test Dates: July 30, 2010	EUT Type: CDMA EV-DO Rev.A Terminal	FCC ID: XAVVVW440	Page 41 of 41