

# MPE REPORT

FCC ID: XBD-BT38ISC

Date of issue: Mar. 23, 2018

Report Number: MTi190311E030

Sample Description: CallCassette

Model(s): BT38IS Rev C, BTHFS380 Rev C

Applicant: AAMP of Florida, Inc. dba AAMP Global

Address: 15500 Lightwave Dr. Suite 202 Clearwater,

Florida 33760 United States

Date of Test: Mar. 04, 2019 – Mar. 13, 2019

Shenzhen Microtest Co., Ltd. http://www.mtitest.com

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Report No.: MTi190311E030



| TEST RESULT CERTIFICATION    |   |  |  |  |
|------------------------------|---|--|--|--|
| Applicant's name:            | AAMP of Florida, Inc. dba AAMP Global   |  |  |  |
| Address:                     | 15500 Lightwave Dr. Suite 202 Clearwater, Florida 33760 United States                             |  |  |  |
| Manufacture's Name:          | Skytech creations limited   |  |  |  |
| Address:                     | Unit 507, 5/F., IC Development Centre, No.6 Science Park West Avenue, Shatin, Hong Kong           |  |  |  |
| Product name:                | CallCassette  |  |  |  |
| Trademark:                   | iSimple   |  |  |  |
| Model and/or type reference: | BT38IS Rev C  |  |  |  |
| Serial Model:                | BTHFS380 Rev C  |  |  |  |
| Difference in series models: | All models are the same circuit and RF module, except for the appearance of the model silk screen |  |  |  |
| RF Exposure Procedures:      | KDB 447498 D01 v06  |  |  |  |

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

| Tested by:   | Denrythia  |               |  |  |  |
|--------------|------------|---------------|--|--|--|
|              | Demi Mu    | Mar. 13, 2019 |  |  |  |
| Reviewed by: | 13 hu      | 13 lue. Zherg |  |  |  |
|              | Blue Zheng | Mar. 23, 2019 |  |  |  |
| Approved by: | Snio       | Gohen         |  |  |  |
|              | Smith Chen | Mar. 23, 2019 |  |  |  |

Tel:(86-755)88850135 Fax: (86-755) 88850136 Web: http://www.mtitest.com E-mail: mti@51mti.com
Address: No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China

Report No.: MTi190311E030



## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency range<br>(MHz)                        | Electric field strength<br>(V/m) | magnetic nera attengar      | Power density<br>(mW/cm <sup>2</sup> ) | Averaging time<br>(minutes) |  |  |  |  |
|---|----------------------------------|-----------------------------|--|-----------------------------|--|--|--|--|
| (A) Limits for Occupational/Controlled Exposure |                                  |                             |  |                             |  |  |  |  |
| 0.3-3.0   | 614                              | 1.63                        | *100                                   | 6                           |  |  |  |  |
| 3.0-30  | 1842/                            | 4.89/f                      | *900/f <sup>2</sup>                    | 6                           |  |  |  |  |
| 30-300  | 61.4                             | 0.163                       | 1.0                                    | 6                           |  |  |  |  |
| 300-1,500                                       |                                  |                             | f/300                                  | 6                           |  |  |  |  |
| 1,500-100,000                                   |                                  |                             | 5                                      | 6                           |  |  |  |  |
|   | (B) Limits for Gene              | ral Population/Uncontrolled | Exposure                               |                             |  |  |  |  |
| 0.3-1.34  | 614                              | 1.63                        | *100                                   | 30                          |  |  |  |  |
| 1.34-30   | 824/                             | 2.19/f                      | *180/f <sup>2</sup>                    | 30                          |  |  |  |  |
| 30-300  | 27.5                             | 0.073                       | 0.2                                    | 30                          |  |  |  |  |
| 300-1,500                                       |                                  |                             | f/1500                                 | 30                          |  |  |  |  |
| 1,500-100,000                                   |                                  |                             | 1.0                                    | 30                          |  |  |  |  |

f = frequency in MHz \* = Plane-wave equivalent power density

#### MPE Calculation Method

Friis transmission formula: Pd= (Pout\*G)\ (4\*pi\*R2)

Where

Pd= Power density in mW/cm2

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1415926

R= distance between observation point and center of the radiator in cm(20cm)

Pd the limit of MPE, 1mW/cm2. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Tel:(86-755)88850135 Fax: (86-755) 88850136 Web: http://www.mtitest.com E-mail: mti@51mti.com
Address: No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China

Report No.: MTi190311E030



## **Measurement Result**

BT:

Operation Frequency: BT GFSK/π/4-DQPSK/8DPSK: 2402-2480MHz,

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: BT Antenna: PCB Antenna;

BT antenna gain: 0dBi

R=20cm

 $mW=10^{(dBm/10)}$ 

antenna gain Numeric=10^(dBi/10)= 10^(0/10)=1.00

| Channel<br>Freq. (MHz) modulation |            | conducted power | Tune-up power (dBm) | Max           |       | Antenna |         | Evaluation result | Power density<br>Limits |
|-----------------------------------|------------|-----------------|---------------------|---------------|-------|---------|---------|-------------------|-------------------------|
|                                   | modulation | odulation (dBm) |                     | tune-up power |       | Gain    |         | (m)\//om2 )       | (m)\/\(\alpha\)         |
|                                   |            |                 |                     | (dBm)         | (mW)  | (dBi)   | Numeric | (mW/cm2)          | (mW/cm2)                |
| 2402                              | GFSK       | -3.912          | -3±1                | -2            | 0.631 | 0       | 1.00    | 0.0001            | 1                       |
| 2441                              |            | -4.108          | -3±1                | -2            | 0.631 | 0       | 1.00    | 0.0001            | 1                       |
| 2480                              |            | -3.930          | -3±1                | -2            | 0.631 | 0       | 1.00    | 0.0001            | 1                       |
| 2402                              | π/4-DQPSK  | -3.217          | -3±1                | -2            | 0.631 | 0       | 1.00    | 0.0001            | 1                       |
| 2441                              |            | -3.744          | -3±1                | -2            | 0.631 | 0       | 1.00    | 0.0001            | 1                       |
| 2480                              |            | -3.350          | -3±1                | -2            | 0.631 | 0       | 1.00    | 0.0001            | 1                       |
| 2402                              | 8DPSK      | -3.123          | -3±1                | -2            | 0.631 | 0       | 1.00    | 0.0001            | 1                       |
| 2441                              |            | -3.199          | -3±1                | -2            | 0.631 | 0       | 1.00    | 0.0001            | 1                       |
| 2480                              |            | -3.097          | -3±1                | -2            | 0.631 | 0       | 1.00    | 0.0001            | 1                       |

### Conclusion:

For the max result: 0.0001≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----

Tel:(86-755)88850135 Fax: (86-755) 88850136 Web: http://www.mtitest.com E-mail: mti@51mti.com
Address: No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China