

243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 449-822 Tel: +82-31-323-6008 Fax: +82-31-323-6010 http://www.ltalab.com



Dates of Tests: August 5 ~ 11, 2009 Test Site: LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

APPLICANT

XBQ-S7

YUKYUNG TECHNOLOGIES INC.

Classification : Licensed Transmitter worn on body (PCT)

Manufacturing Description : MID(MOBILE INTERNET DEVICE)

Manufacturer : YUKYUNG TECHNOLOGIES INC.

Manufacturer (RF Module) : Huawei Technologies Co.,Ltd (FCC ID:QISEM770W)

Model name : S7

Variant Model name S7 3G, S7 PREMIUM S

Test Device Serial No.: : Identical prototype
Rule Part(s) : \$24(E), \$22(H), \$2

Frequency Range (Tx / Rx) : 826.40~846.60 MHz / 871.40~891.60 MHz (Cellular WCDMA)

1852.4~1907.6 MHz / 1932.4~1987.6 MHz (PCS WCDMA)

Max. RF Output Power : 0.104 W ERP Cellular WCDMA

0.173 W EIRP PCS WCDMA

Data of issue : August 11, 2009

This test report is issued under the authority of:

The test was supervised by:

Dong -Min JUNG, Technical Manager

Kyung-Taek LEE, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. This report must not be used by the applicant to claim product endorsement by any agency.

NVLAP

NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

2. INFORMATION'S ABOUT TEST ITEM 4 3. TEST REPORT 5
3. TEST REPORT 5
3.1 SUMMARY OF TESTS 5
3.2 TECHNICAL CHARACTERISTICS TEST 6
3.2.1 EFFECTIVE RADIATED POWER OUTPUT 6
3.3 DESCRIPTION OF TEST 7
3.3.1 OUTPUT POWER (RADIATED) 7
3.3.2 SPURIOUS EMISSIONS (RADIATED)8
APPENDIX
APPENDIX TEST EQUIPMENT USED FOR TESTS 14

1. General information's

1-1 Test Performed

Company name : LTA Co., Ltd.

Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 449-822

Web site : http://www.ltalab.com
E-mail : chahn@ltalab.com
Telephone : +82-31-323-6008
Facsimile +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the "General requirements for the competents of calibration and testing laboratory".

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference	
NVLAP	U.S.A	200723-0	2009-09-30	ECT accredited Lab.	
RRL	KOREA	KR0049	2010-06-20	EMC accredited Lab.	
FCC	U.S.A	610755	2011-04-22	FCC filing	
VCCI	JAPAN	R2133, C2307	2011-06-21	VCCI registration	
IC	CANADA	IC5799	2010-05-03	IC filing	

2. Information's about test item

2-1 Applicant & Manufacturer

Company name : YUKYUNG TECHNOLOGIES INC.

Address : 200-11, Anyang-Dong, Manan-Ku, Anyang-Si, Kyunggi-Do, Korea

Tel / Fax : TEL No : +82-31-463-6906 / FAX No : +82-31-445-5995

2-2 Equipment Under Test (EUT)

Trade name : MID(MOBILE INTERNET DEVICE)

Model name : S7

Variant Model : S7 3G, S7 PREMIUM S

Date of receipt : July 30, 2009

EUT condition : Pre-production, not damaged

HSPA Module : Huawei Technologies Co.,Ltd (FCC ID:QISEM770W)

Identification mark: 0682

Antenna type : Swivel Antenna

RF output power : Cellular WCDMA(21.4dBm) / PCS WCDMA (21.9dBm) – Conducted power

Modulation : QPSK

Temperature range : 0° C ~ +40 $^{\circ}$ C

Power for Batt. : Battery Pack: 7.4V (Li-Ion Polymer RECHARGEABLE BATTERY)

2-3 Tested frequency

	Cellular WCDMA		PCS WCDMA		
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
LOW	4132	826.4	9262	1852.4	
MID	4182	836.4	9400	1880.0	
HIGH	4233	846.4	9538	1907.6	

2-5 Model Description

Model Name	3G Modem	Wifi / BT	SSD	CPU	Note
S 7	О	O	32/ 64	2.0GHz	Tested
S7 3G	0	О	32/64	2.0GHz	-
S7 PREMIUM S	X	О	32/64	2.0GHz	-

3. Test Report

3.1 Summary of tests

Parameter	Status				
Transmitter Requirements					
I. FCC Part Section(s)					
WCDMA Module is certified by FCC(FCC ID: QISEM770W).					
Refer to the test report of FCC ID:QISEM770W.					
Output Power	С				
Spurious emission	С				
Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable					
<u>Note 2</u> : The data in this test report are traceable to the national or international standards.					

The sample was tested according to the following specification:

ANSI C-63.4-2003

3.2 Technical Characteristics Test

3.2.1 Effective Radiated Power Output

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 3-meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. For GSM signals, an average detector is used, with RBW=VBW=3MHz, SPAN=10MHz. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

3.2.2 Radiation Spurious and Harmonic Emissions

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

Radiation and harmonic emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 3-meters from the receive antenna.

The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. The Spectrum was investigated from 30MHz to the 10th Harmonic of the fundamental. A peak detector is used. With RBW=VBW=1MHz. The value that we could measure was only reported. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer reading. This level is recorded. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

3.3 DESCRIPTION OF TESTS

3.3.1 Output Power

Effective Radiated Power Output (Cellular WCDMA)

Measurement Data:

	Frequency	TEST CONDITIONS						
Channel	annel (MHz)	Ref. level (dBm)	Pol. (H/V)	ERP (dBm)	ERP (W)	Battery		
4132	826.4	-20.93	V	19.7	0.093	STD		
4182	836.4	-22.14	V	20.15	0.104	STD		
4233	846.4	-20.31	V	19.03	0.080	STD		

Note 1: Radiated measurements at 3 meters by Substitution Method.

Equivalent Isotropic Radiated Power (PCS WCDMA)

Measurement Data:

	Frequency	TEST CONDITIONS						
Channel	Channel (MHz)	Ref. level (dBm)	Pol. (H/V)	EIRP (dBm)	EIRP (W)	Battery		
9262	1852.4	-19.04	V	22.37	0.173	STD		
9400	1880	-19.49	V	22.03	0.160	STD		
9538	1907.6	-19.60	V	21.63	0.146	STD		

Note 2: Radiated measurements at 3 meters by Substitution Method.

OPERATING FREQUENCY : 826.4 MHz

CHANNEL: 4132(Low)

MEASURED OUTPUT POWER : $\underline{20.15}$ $\underline{dBm} = \underline{0.104}$ W

MODULATION : WCDMA

DISTANCE: 3 meters

LIMIT : $43 + 10 \log_{10} (W) = 33.15$ dBc

Freq.	LEVEL@	SUBSTITUTE	CORRECT	POL			
	ANTENNA	ANTENNA	GENERATOR				
	TERMINALS	GAIN	LEVEL				
(MHz)	(dBm)	(dBi)	(dBm)	(H/V)	(dBc)		
-	-	-	-	-	-		
No emissions were detected are a level greater than 20dB below limit.							
-	-	-	-	-	-		

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Continue

OPERATING FREQUENCY : 836.4 MHz

CHANNEL: 4182(Mid)

MEASURED OUTPUT POWER : $\underline{20.15}$ $\underline{dBm} = \underline{0.104}$ W

MODULATION : WCDMA

DISTANCE : 3 meters

LIMIT : $43 + 10 \log_{10} (W) = 33.15$ dBc

Freq.	LEVEL@	SUBSTITUTE	CORRECT	POL			
	ANTENNA	ANTENNA	GENERATOR				
	TERMINALS	GAIN	LEVEL				
(MHz)	(dBm)	(dBi)	(dBm)	(H/V)	(dBc)		
-	-	-	-	-	-		
No emissions were detected are a level greater than 20dB below limit.							
-	-	-	-	-	-		

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Continue

OPERATING FREQUENCY : 846.4 MHz

CHANNEL: 4233(High)

MEASURED OUTPUT POWER : $\underline{20.15}$ $\underline{dBm} = \underline{0.104}$ W

MODULATION : WCDMA

DISTANCE : 3 meters

LIMIT : $43 + 10 \log_{10} (W) = 33.15$ dBc

Freq.	LEVEL@	SUBSTITUTE	CORRECT	POL			
	ANTENNA	ANTENNA	GENERATOR				
	TERMINALS	GAIN	LEVEL				
(MHz)	(dBm)	(dBi)	(dBm)	(H/V)	(dBc)		
-	-	-	-	-	-		
No emissions were detected are a level greater than 20dB below limit.							
-	-	-	-	-	-		

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Continue

OPERATING FREQUENCY : 1852.4 MHz

CHANNEL : 9262(Low)

MEASURED OUTPUT POWER : 22.37 dBm = 0.173 W

MODULATION : WCDMA

DISTANCE : <u>3</u> meters

LIMIT : $43 + 10 \log_{10} (W) = 35.37$ dBc

Freq.	LEVEL@	SUBSTITUTE	CORRECT	POL			
	ANTENNA	ANTENNA	GENERATOR				
	TERMINALS	GAIN	LEVEL				
(MHz)	(dBm)	(dBi)	(dBm)	(H/V)	(dBc)		
-	-	-	-	-	-		
No emissions were detected are a level greater than 20dB below limit.							
_	-	-	-	-	-		

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Continue

OPERATING FREQUENCY : <u>1880.0</u> MHz

CHANNEL : 9400(Mid)

MEASURED OUTPUT POWER : 22.37 dBm = 0.173 W

MODULATION : WCDMA

DISTANCE : <u>3</u> meters

LIMIT : $43 + 10 \log_{10} (W) = 35.37$ dBc

Freq.	LEVEL@	SUBSTITUTE	CORRECT	POL			
	ANTENNA	ANTENNA	GENERATOR				
	TERMINALS	GAIN	LEVEL				
(MHz)	(dBm)	(dBi)	(dBm)	(H/V)	(dBc)		
-	-	-	-	-	-		
No emissions were detected are a level greater than 20dB below limit.							
_	-	1	-	-	1		

Note1: Radiated measurements at 3 meters by Substitution Method.

--- Continue

OPERATING FREQUENCY : 1907.6 MHz

CHANNEL: 9538(High)

MEASURED OUTPUT POWER : 22.37 dBm = 0.173 W

MODULATION : WCDMA

DISTANCE : 3 meters

LIMIT : $43 + 10 \log_{10} (W) = 35.37$ dBc

Freq.	LEVEL@	SUBSTITUTE	CORRECT	POL				
	ANTENNA	ANTENNA	GENERATOR					
	TERMINALS	GAIN	LEVEL					
(MHz)	(dBm)	(dBi)	(dBm)	(H/V)	(dBc)			
-	-	-	-	-	-			
No emissions were detected are a level greater than 20dB below limit.								
_	-	-	-	-	-			

Note1: Radiated measurements at 3 meters by Substitution Method.

APPENDIX

TEST EQUIPMENT USED FOR TESTS

	Description	Model No.	Serial No.	Manufacturer	Next Cal. Date
1	Spectrum Analyzer	FSV-30	100757	R&S	Feb-10
2	Spectrum Analyzer	8563E	3425A02505	HP	Apr-10
3	Spectrum Analyzer	8594E	3710A04074	НР	Oct-09
4	Signal Generator	8648C	3623A02597	HP	Apr-10
5	Signal Generator	83711B	US34490456	HP	Apr-10
6	Attenuator (3dB)	8491A	37822	HP	Oct-09
7	Attenuator (10dB)	8491A	63196	НР	Oct-09
8	Attenuator (30dB)	8498A	1801A06689	HP	Oct-09
9	EMI Test Receiver	ESVD	843748/001	R&S	Apr-10
10	Horn Antenna(18 ~ 40GHz)	SAS-574	154	Schwarzbeck	Nov-10
11	Horn Antenna(18 ~ 40GHz)	SAS-574	155	Schwarzbeck	Nov-10
12	RF Amplifier	8447D	2949A02670	HP	Oct-10
13	RF Amplifier	8449B	3008A02126	HP	Apr-10
14	Test Receiver	ESHS10	828404/009	R&S	Apr-10
15	TRILOG Antenna	VULB 9160	9160-3212	SCHWARZBECK	Apr-11
16	LogPer. Antenna	VULP 9118	9118 A 401	SCHWARZBECK	Apr-11
17	Biconical Antenna	BBA 9106	VHA 9103-2315	SCHWARZBECK	Apr-11
18	Horn Antenna	3115	00055005	ETS LINDGREN	Mar-11
19	Horn Antenna	BBHA 9120D	9120D122	SCHWARZBECK	Dec-11
20	Dipole Antenna	VHA9103	2116	SCHWARZBECK	Nov-09
21	Dipole Antenna	VHA9103	2117	SCHWARZBECK	Nov-09
22	Dipole Antenna	VHA9105	2261	SCHWARZBECK	Nov-09
23	Dipole Antenna	VHA9105	2262	SCHWARZBECK	Nov-09
24	Hygro-Thermograph	THB-36	0041557-01	ISUZU	Apr-10
25	Splitter (SMA)	ZFSC-2-2500	SF617800326	Mini-Circuits	-
26	Signal Generator	E4436B	US39260781	Agilent	May-10
27	Power Divider	11636A	6243	HP	Oct-09
28	DC Power Supply	6622A	3448A03079	HP	Oct-09
29	Frequency Counter	5342A	2826A12411	HP	Apr-10
30	Power Meter	EPM-441A	GB32481702	HP	Apr-10
31	Power Sensor	8481A	2702A64048	HP	Apr-10
32	Audio Analyzer	8903B	3729A18901	HP	Oct-09
33	Modulation Analyzer	8901B	3749A05878	HP	Oct-09
34	TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	Oct-09
35	LOOP-ANTENNA	FMZB 1516	151602/94	SCHWARZBECK	Mar-11
36	Communication Equipment	E5515C	GB42230452	Agilent	July-10
37	LISN	ENV216	100408	R&S	Oct-09