



TEST REPORT

No. I20Z61629-WMD02

for

Shenzhen Tinno Mobile Technology Corp.

Feature Phone

Model Name: U102AA

FCC ID: XD6U102AA

with

Hardware Version: V1.0

Software Version: U102AAV01.99.11

Issued Date: 2020-10-22

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn

REPORT HISTORY

Report Number	Revision	Description	Issue Date
I20Z61629-WMD02	Rev.0	1 st edition	2020-10-20
I20Z61629-WMD02	Rev.1	2 nd edition. Updated radiated testing results	2020-10-21
I20Z61629-WMD02	Rev.2	3 rd edition. Updated the FCC KDB in page 12.	2020-10-22

Note: the latest revision of the test report supersedes all previous version.

CONTENTS

1. TEST LABORATORY.....	4
1.1. INTRODUCTION & ACCREDITATION	4
1.2. TESTING LOCATION	4
1.3. TESTING ENVIRONMENT	5
1.4. PROJECT DATA.....	5
1.5. SIGNATURE	5
2. CLIENT INFORMATION.....	6
2.1. APPLICANT INFORMATION.....	6
2.2. MANUFACTURER INFORMATION.....	6
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.1. ABOUT EUT	7
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	7
4. REFERENCE DOCUMENTS	8
4.1. REFERENCE DOCUMENTS FOR TESTING.....	8
5. LABORATORY ENVIRONMENT	9
6. SUMMARY OF TEST RESULT	10
7. TEST EQUIPMENT UTILIZED	13
ANNEX A: MEASUREMENT RESULTS	14
A.1 OUTPUT POWER.....	14
A.2 EMISSION LIMIT	48
A.3 FREQUENCY STABILITY	62
A.4 OCCUPIED BANDWIDTH	68
A.5 EMISSION BANDWIDTH.....	91
A.6 BAND EDGE COMPLIANCE	114
A.7 CONDUCTED SPURIOUS EMISSION	130
A.8 PEAK-TO-AVERAGE POWER RATIO	136
ANNEX B: ACCREDITATION CERTIFICATE	137

1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0 and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Location 1: CTTL (huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China 100191

Location 2: CTTL (Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,
Haidian District, Beijing, P. R. China 100191

1.3. Testing Environment

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

1.4. Project data

Testing Start Date: 2019-12-19

Testing End Date: 2020-09-30

1.5. Signature



Dong Yuan
(Prepared this test report)



Zhou Yu
(Reviewed this test report)



Zhao Hui Lin
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: Shenzhen Tinno Mobile Technology Corp.
Address /Post: 4/F, H-3 Building,OCT Eastern Industrial Park. NO.1 XiangShan East
Road, Nan Shan District,Shenzhen, P.R.China
Contact: Xiaoping Li
Email: xiaoping.li@tinno.com
Telephone: 0755-86095550
Fax: NA

2.2. Manufacturer Information

Company Name: Shenzhen Tinno Mobile Technology Corp.
Address /Post: 4/F, H-3 Building,OCT Eastern Industrial Park. NO.1 XiangShan East
Road, Nan Shan District,Shenzhen, P.R.China
Contact: Xiaoping Li
Email: xiaoping.li@tinno.com
Telephone: 0755-86095550
Fax: NA

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Feature Phone
Model Name	U102AA
FCC ID	XD6U102AA
Antenna	Embedded
Output power	27.21dBm maximum EIRP measured for LTE Band 2
Extreme vol. Limits	3.4VDC to 4.35VDC (nominal: 3.85VDC)
Extreme temp. Tolerance	-10C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version	Date of receipt
UT17a	869101041688140	V1.0	U102AAV01.99.11	2020-09-22

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery

AE1

Model	LP484354R
Manufacturer	Shenzhen byd lithium battery co., LTD.
Capacitance	1450mAh

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-19 Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-19 Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS SERVICES	10-1-19 Edition
FCC Part 90	PRIVATE LAND MOBILE RADIO SERVICES	10-1-19 Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2016
ANSI C63.26	American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services	2015
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS	v03r01

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber 2 / Fully-anechoic chamber 3 (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	<±3.5 dB, 3 m distance
Site voltage standing-wave ratio (S_{VSWR})	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

6. SUMMARY OF TEST RESULT

LTE Band 2

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	24.232	P
2	Emission Limit	2.1051/24.238	P
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	24.238	BR
6	Band Edge Compliance	24.238	BR
7	Conducted Spurious Emission	24.238	BR
8	Peak-to-Average Power Ratio	24.232	BR

LTE Band 4

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	P
2	Emission Limit	2.1051/27.53	P
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	27.53	BR
6	Band Edge Compliance	27.53	BR
7	Conducted Spurious Emission	27.53	BR
8	Peak-to-Average Power Ratio	27.50	BR

LTE Band 5

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	22.913	P
2	Emission Limit	2.1051/22.917	P
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	22.917	BR
6	Band Edge Compliance	22.917	BR
7	Conducted Spurious Emission	22.917	BR

LTE Band 12

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	P
2	Emission Limit	2.1051/27.53	P
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	27.53	BR
6	Band Edge Compliance	27.53	BR
7	Conducted Spurious Emission	27.53	BR
8	Peak-to-Average Power Ratio	27.50	BR

LTE Band 14

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	90.542	P
2	Emission Limit	2.1051/90.543	P
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	2.1049	BR
6	Band Edge Compliance	90.543	BR
7	Conducted Spurious Emission	90.543	BR

Terms used in Verdict column

P	Pass. The EUT complies with the essential requirements in the standard.
NP	Not Performed. The test was not performed by CTTL.
NA	Not Applicable. The test was not applicable.
BR	Re-use test data from basic model report.
F	Fail. The EUT does not comply with the essential requirements in the standard.

Explanation of worst-case configuration

The worst-case scenario for all measurements is based on the conducted output power measurement investigation results. Output power was measured on QPSK and 16QAM modulations. It was found that QPSK was the worst case. All testing was performed using QPSK modulations to represent the worst case unless otherwise stated. The test results shown in the following sections represent the worst case emission.



The Equipment Under Test (EUT) model U102AA (FCC ID: XD6U102AA) is a variant product of U102AA (FCC ID: XD6U102AA), according to the declaration of changes provided by the applicant and FCC KDB publication 178919 D01, spot check measurements were performed on this device, other test results are derived from test report No. I19Z62134-WMD02. Please refer Annex A for detail spot check verification data and reference data. The spot check test results are consistent with basic model.

For detail differences between two models please refer the Declaration of Changes document.

7. Test Equipment Utilized

NO .	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	Universal Radio Communication Tester	CMW500	159082	R&S	2020-12-24	1 year
2	Spectrum Analyzer	FSU26	200030	R&S	2021-06-01	1 year
3	Climate chamber	SH-242	93008556	ESPEC	2020-12-21	3 years
4	power amplifier	5S1G4	0341863	AR	/	/
5	EMI Antenna	VULB9163	9163-235	Schwarzbeck	2020-11-24	1 year
6	EMI Antenna	3117	00058889	ETS-Lindgren	2020-11-18	1 year
7	EMI Antenna	3117	00119024	ETS-Lindgren	2021-05-06	1 year
8	EMI Antenna	9117	177	Schwarzbeck	2021-10-12	1 year
9	Signal Generator	SMF100A	101295	R&S	2020-12-27	1 year
10	Test Receiver	E4440A	MY48250642	Agilent	2021-03-12	1 year
11	Universal Radio Communication Tester	CMW500	143008	R&S	2020-11-26	1 year
12	Power Amplifier	5S1G4	0341863	AR	/	

ANNEX A: MEASUREMENT RESULTS

A.1 OUTPUT POWER

A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation. In all cases, output power is within the specified limits.

A.1.2 Conducted

A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation. These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.

A.1.2.2 Measurement result

LTE band 2

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
1.4MHz	1 RB high	1909.3	22.33	21.47
		1880.0	22.20	21.15
		1850.7	22.46	20.99
	1 RB low	1909.3	22.37	21.41
		1880.0	22.03	21.03
		1850.7	22.38	21.26
	50% RB mid	1909.3	22.89	21.47
		1880.0	22.76	21.58
		1850.7	22.87	21.63
	100% RB	1909.3	21.54	20.56
		1880.0	21.38	20.57
		1850.7	21.35	20.45
3MHz	1 RB high	1908.5	22.24	21.56
		1880.0	22.14	21.25
		1851.5	22.39	21.07
	1 RB low	1908.5	22.41	21.38
		1880.0	22.07	20.98
		1851.5	22.38	21.24
	50% RB mid	1908.5	21.72	20.60
		1880.0	21.54	20.69
		1851.5	21.58	20.56

	100% RB	1908.5	21.60	20.60
		1880.0	21.40	20.65
		1851.5	21.39	20.48
5MHz	1 RB high	1907.5	22.67	21.32
		1880.0	22.66	21.16
		1852.5	22.49	21.32
	1 RB low	1907.5	22.77	21.30
		1880.0	22.74	21.25
		1852.5	22.49	21.27
	50% RB mid	1907.5	21.73	20.69
		1880.0	21.69	20.69
		1852.5	21.62	20.70
	100% RB	1907.5	21.66	20.89
		1880.0	21.68	20.72
		1852.5	21.48	20.74
10MHz	1 RB high	1905.0	22.45	21.55
		1880.0	22.92	21.74
		1855.0	22.52	22.03
	1 RB low	1905.0	22.79	21.53
		1880.0	22.67	21.61
		1855.0	22.48	21.86
	50% RB mid	1905.0	21.72	20.87
		1880.0	21.74	20.76
		1855.0	21.64	20.80
	100% RB	1905.0	21.72	20.75
		1880.0	21.72	20.64
		1855.0	21.42	20.52
15MHz	1 RB high	1902.5	22.45	22.20
		1880.0	22.93	21.67
		1857.5	22.44	21.32
	1 RB low	1902.5	22.69	22.19
		1880.0	22.71	21.64
		1857.5	22.37	21.50
	50% RB mid	1902.5	21.82	20.92
		1880.0	21.66	20.65
		1857.5	21.71	20.72
	100% RB	1902.5	21.65	20.76
		1880.0	21.57	20.67
		1857.5	21.47	20.59

20MHz	1 RB high	1900.0	22.32	21.54
		1880.0	22.19	21.23
		1860.0	22.48	21.07
	1 RB low	1900.0	22.41	21.38
		1880.0	22.05	21.05
		1860.0	22.42	21.23
	50% RB mid	1900.0	21.75	20.67
		1880.0	21.61	20.68
		1860.0	21.55	20.61
	100% RB	1900.0	21.57	20.60
		1880.0	21.42	20.62
		1860.0	21.34	20.49

LTE band 4

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
1.4MHz	1 RB high	1754.3	22.68	21.80
		1732.5	22.87	21.89
		1710.7	23.00	22.11
	1 RB low	1754.3	22.69	21.64
		1732.5	22.90	21.79
		1710.7	22.94	21.40
	50% RB mid	1754.3	22.72	22.13
		1732.5	22.86	21.87
		1710.7	22.95	22.17
	100% RB	1754.3	21.74	20.78
		1732.5	21.96	21.08
		1710.7	21.92	20.84
3MHz	1 RB high	1753.5	22.68	21.87
		1732.5	22.83	21.81
		1711.5	22.95	22.06
	1 RB low	1753.5	22.79	21.40
		1732.5	22.91	21.68
		1711.5	22.95	21.49
	50% RB mid	1753.5	21.72	20.53
		1732.5	21.74	20.98
		1711.5	21.77	20.86
	100% RB	1753.5	21.62	20.53
		1732.5	21.72	20.96
		1711.5	21.84	20.97
5MHz	1 RB high	1752.5	22.92	21.55
		1732.5	22.85	21.63
		1712.5	22.74	21.59
	1 RB low	1752.5	22.82	21.32
		1732.5	22.94	21.38
		1712.5	22.83	21.42
	50% RB mid	1752.5	21.85	20.85
		1732.5	21.91	20.95
		1712.5	21.80	20.80
	100% RB	1752.5	21.72	20.56
		1732.5	21.86	20.94
		1712.5	21.76	20.87
10MHz	1 RB high	1750	22.83	21.82
		1732.5	22.94	21.40

	1 RB low	1715	22.95	21.90
		1750	22.73	21.61
		1732.5	22.72	21.69
		1715	22.69	22.14
	50% RB mid	1750	21.73	21.08
		1732.5	21.82	20.93
		1715	21.85	20.81
	100% RB	1750	21.69	20.89
		1732.5	21.76	20.94
		1715	21.81	20.85
15MHz	1 RB high	1747.5	23.06	21.70
		1732.5	22.72	21.44
		1717.5	22.83	22.28
	1 RB low	1747.5	23.02	21.86
		1732.5	22.71	21.65
		1717.5	22.81	22.22
	50% RB mid	1747.5	21.95	20.82
		1732.5	22.01	20.98
		1717.5	21.89	20.89
	100% RB	1747.5	21.73	20.72
		1732.5	21.91	20.87
		1717.5	21.82	20.91
20MHz	1 RB high	1745	22.99	21.73
		1732.5	22.83	21.50
		1720	23.06	21.92
	1 RB low	1745	23.34	21.86
		1732.5	22.67	21.70
		1720	22.60	21.34
	50% RB mid	1745	22.02	21.03
		1732.5	22.25	21.06
		1720	22.00	21.04
	100% RB	1745	21.92	21.03
		1732.5	21.98	20.91
		1720	22.02	20.98

LTE band 5

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
1.4MHz	1 RB high	848.3	23.39	22.69
		836.5	23.45	22.58
		824.7	23.52	22.63
	1 RB low	848.3	23.35	22.51
		836.5	23.44	22.58
		824.7	23.43	22.66
	50% RB mid	848.3	23.78	22.34
		836.5	23.49	22.67
		824.7	23.53	22.57
	100% RB	848.3	22.40	21.30
		836.5	22.52	21.70
		824.7	22.49	21.52
3MHz	1 RB high	847.5	23.27	22.28
		836.5	23.55	22.46
		825.5	23.26	21.90
	1 RB low	847.5	23.45	22.45
		836.5	23.45	22.55
		825.5	23.28	22.84
	50% RB mid	847.5	22.33	21.43
		836.5	22.37	21.71
		825.5	22.35	21.51
	100% RB	847.5	22.31	21.14
		836.5	22.35	21.39
		825.5	22.40	21.36
5MHz	1 RB high	846.5	23.19	21.90
		836.5	23.55	22.17
		826.5	23.18	22.31
	1 RB low	846.5	23.12	22.23
		836.5	23.31	21.73
		826.5	23.07	21.81
	50% RB mid	846.5	22.39	21.24
		836.5	22.37	21.42
		826.5	22.40	21.29
	100% RB	846.5	22.29	21.27
		836.5	22.31	21.38
		826.5	22.33	21.37
10MHz	1 RB high	844.0	23.40	22.52
		836.5	23.40	22.03

	1 RB low	829.0	23.26	22.63
		844.0	23.21	22.08
		836.5	23.46	22.39
		829.0	23.03	22.55
	50% RB mid	844.0	22.30	21.51
		836.5	22.46	21.47
		829.0	22.51	21.64
	100% RB	844.0	22.23	21.30
		836.5	22.33	21.24
		829.0	22.36	21.38

LTE band 12

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
1.4MHz	1 RB high	715.3	22.63	21.68
		707.5	22.41	21.66
		699.7	22.72	21.35
	1 RB low	715.3	22.46	21.72
		707.5	22.32	21.40
		699.7	22.41	22.05
	50% RB mid	715.3	22.68	21.43
		707.5	22.69	21.39
		699.7	22.81	21.73
	100% RB	715.3	21.69	20.68
		707.5	21.75	20.62
		699.7	21.56	20.66
3MHz	1 RB high	714.5	22.62	21.37
		707.5	22.72	21.65
		700.5	22.78	21.77
	1 RB low	714.5	22.82	21.60
		707.5	22.75	21.59
		700.5	22.64	21.91
	50% RB mid	714.5	21.67	20.92
		707.5	21.61	20.39
		700.5	21.63	20.30
	100% RB	714.5	21.75	20.70
		707.5	21.72	20.67
		700.5	21.80	20.67
5MHz	1 RB high	713.5	22.42	21.25
		707.5	22.57	21.30
		701.5	22.61	21.63
	1 RB low	713.5	22.80	21.29
		707.5	22.42	21.21
		701.5	22.48	21.23
	50% RB mid	713.5	21.81	20.43
		707.5	21.67	20.61
		701.5	21.61	20.43
	100% RB	713.5	21.66	20.49
		707.5	21.65	20.80
		701.5	21.66	20.70
10MHz	1 RB high	711.0	22.60	21.74
		707.5	22.43	21.40

	1 RB low	704.0	22.72	21.50
		711.0	22.53	22.02
		707.5	22.38	21.44
		704.0	22.34	21.71
	50% RB mid	711.0	21.69	20.67
		707.5	21.67	20.86
		704.0	21.73	20.73
	100% RB	711.0	21.75	20.58
		707.5	21.72	20.76
		704.0	21.76	20.73

LTE band 14

Bandwidth	RB size/offset	Frequency (MHz)	Power (dBm)	
			QPSK	16QAM
5MHz	1 RB high	795.5	22.22	21.27
		793.0	22.55	21.08
		790.5	22.13	21.51
	1 RB low	795.5	22.73	20.85
		793.0	22.74	20.95
		790.5	22.34	21.29
	50% RB mid	795.5	21.71	20.73
		793.0	21.61	20.75
		790.5	21.60	20.50
	100% RB	795.5	21.65	20.68
		793.0	21.61	20.77
		790.5	21.59	20.80
10MHz	1 RB high	793.0	22.57	21.26
	1 RB low	793.0	22.61	21.66
	50% RB mid	793.0	21.72	20.86
	100% RB	793.0	21.65	20.74

A.1.3 Radiated

A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 22.913(a) specifies "Mobile stations are limited to 2.0 watts EIRP".

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power". and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."

Rule Part 27.50(d) specifies "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP".


Rule Part 27.50(c) specifies "Portable stations (hand-held de-vices) are limited to 3 watts ERP".

Rule Part 90.542(a) specifies "Mobile stations are limited to 3 watts ERP".


A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360 and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.
The cable loss (P_{cl}), the substitution antenna Gain (G_a) and the amplifier Gain (P_{Ag}) should be recorded after test.

The measurement results are obtained as described below:

$$\text{Power (EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15$.

A.1.3.3 Measurement result

Spot Check Measurement Results:

LTE Band 2- EIRP

Limits: $\leq 33\text{dBm}$ (2W)

LTE Band 2_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.70	-22.75	2.92	43.75	4.87	22.95	33.00	10.05	H
1880.00	-21.45	2.85	43.75	4.82	24.27	33.00	8.73	H
1909.30	-18.83	2.87	43.77	4.76	26.83	33.00	6.17	H

LTE Band 2_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.50	-22.70	2.87	43.75	4.87	23.05	33.00	9.95	H
1880.00	-21.84	2.85	43.75	4.82	23.88	33.00	9.12	H
1908.50	-19.20	2.89	43.78	4.76	26.45	33.00	6.55	H

LTE Band 2_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.50	-22.53	2.87	43.75	4.87	23.22	33.00	9.78	H
1880.00	-21.69	2.85	43.75	4.82	24.03	33.00	8.97	H
1907.50	-18.49	2.84	43.77	4.77	27.21	33.00	5.79	H

LTE Band 2_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.00	-22.87	2.88	43.74	4.86	22.85	33.00	10.15	H
1880.00	-21.37	2.85	43.75	4.82	24.35	33.00	8.65	H
1905.00	-19.01	2.87	43.77	4.77	26.66	33.00	6.34	H

LTE Band 2_15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.50	-22.76	2.87	43.75	4.86	22.98	33.00	10.02	H
1880.00	-21.71	2.85	43.75	4.82	24.01	33.00	8.99	H
1902.50	-19.43	2.86	43.77	4.78	26.26	33.00	6.74	H

LTE Band 2_20 MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.00	-22.19	2.86	43.75	4.85	23.55	33.00	9.45	H
1880.00	-21.39	2.85	43.75	4.82	24.33	33.00	8.67	H
1900.00	-19.79	2.87	43.77	4.78	25.89	33.00	7.11	H

LTE Band 2_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.70	-23.51	2.92	43.75	4.87	22.19	33.00	10.81	H
1880.00	-22.11	2.85	43.75	4.82	23.61	33.00	9.39	V
1909.30	-19.88	2.87	43.77	4.76	25.78	33.00	7.22	H

LTE Band 2_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.50	-23.86	2.87	43.75	4.87	21.89	33.00	11.11	H
1880.00	-22.74	2.85	43.75	4.82	22.98	33.00	10.02	H
1908.50	-20.03	2.89	43.78	4.76	25.62	33.00	7.38	H

LTE Band 2_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.50	-23.56	2.87	43.75	4.87	22.19	33.00	10.81	H
1880.00	-22.30	2.85	43.75	4.82	23.42	33.00	9.58	H
1907.50	-20.14	2.84	43.77	4.77	25.56	33.00	7.44	H

LTE Band 2_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.00	-23.24	2.88	43.74	4.86	22.48	33.00	10.52	H
1880.00	-22.07	2.85	43.75	4.82	23.65	33.00	9.35	H
1905.00	-20.11	2.87	43.77	4.77	25.56	33.00	7.44	H

LTE Band 2_15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.50	-23.90	2.87	43.75	4.86	21.84	33.00	11.16	H
1880.00	-22.15	2.85	43.75	4.82	23.57	33.00	9.43	H
1902.50	-20.58	2.86	43.77	4.78	25.11	33.00	7.89	H

LTE Band 2_20 MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.00	-22.82	2.86	43.75	4.85	22.92	33.00	10.08	H
1880.00	-22.47	2.85	43.75	4.82	23.25	33.00	9.75	H
1900.00	-20.65	2.87	43.77	4.78	25.03	33.00	7.97	H

LTE Band 4- EIRP

Limits: $\leq 30\text{dBm}$ (1W)

LTE Band 4_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.70	-23.29	3.17	44.10	5.12	22.76	30.00	7.24	H
1732.50	-23.86	3.33	44.14	5.08	22.03	30.00	7.97	H
1754.30	-22.44	3.76	44.14	5.04	22.98	30.00	7.02	H

LTE Band 4_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.50	-23.04	3.40	44.10	5.12	22.78	30.00	7.22	H
1732.50	-23.83	3.33	44.14	5.08	22.06	30.00	7.94	H
1753.50	-22.35	3.80	44.13	5.04	23.02	30.00	6.98	H

LTE Band 4_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.50	-23.18	3.66	44.10	5.12	22.38	30.00	7.62	H
1732.50	-23.98	3.33	44.14	5.08	21.91	30.00	8.09	H
1752.50	-22.68	3.82	44.14	5.05	22.69	30.00	7.31	H

LTE Band 4_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.00	-22.68	3.56	44.10	5.11	22.97	30.00	7.03	H
1732.50	-23.72	3.33	44.14	5.08	22.17	30.00	7.83	H
1750.00	-23.56	3.00	44.15	5.05	22.64	30.00	7.36	H

LTE Band 4_15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.50	-22.85	3.47	44.11	5.11	22.90	30.00	7.10	H
1732.50	-23.65	3.33	44.14	5.08	22.24	30.00	7.76	H
1747.50	-23.63	3.34	44.15	5.05	22.23	30.00	7.77	H

LTE Band 4_20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.00	-22.92	3.37	44.11	5.10	22.92	30.00	7.08	H
1732.50	-23.52	3.33	44.14	5.08	22.37	30.00	7.63	H
1745.00	-23.42	3.68	44.16	5.06	22.12	30.00	7.88	H

LTE Band 4_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.70	-24.16	3.17	44.10	5.12	21.89	30.00	8.11	H
1732.50	-24.73	3.33	44.14	5.08	21.16	30.00	8.84	H
1754.30	-23.25	3.76	44.14	5.04	22.17	30.00	7.83	H

LTE Band 4_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.50	-23.94	3.40	44.10	5.12	21.88	30.00	8.12	H
1732.50	-24.71	3.33	44.14	5.08	21.18	30.00	8.82	H
1753.50	-23.46	3.80	44.13	5.04	21.91	30.00	8.09	H

LTE Band 4_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.50	-23.92	3.66	44.10	5.12	21.64	30.00	8.36	H
1732.50	-24.75	3.33	44.14	5.08	21.14	30.00	8.86	H
1752.50	-23.63	3.82	44.14	5.05	21.74	30.00	8.26	H

LTE Band 4_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.00	-23.58	3.56	44.10	5.11	22.07	30.00	7.93	H
1732.50	-24.46	3.33	44.14	5.08	21.43	30.00	8.57	H
1750.00	-24.39	3.00	44.15	5.05	21.81	30.00	8.19	H

LTE Band 4_15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.50	-23.83	3.47	44.11	5.11	21.92	30.00	8.08	H
1732.50	-24.48	3.33	44.14	5.08	21.41	30.00	8.59	H
1747.50	-24.47	3.34	44.15	5.05	21.39	30.00	8.61	H

LTE Band 4_20MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.00	-23.78	3.37	44.11	5.10	22.06	30.00	7.94	H
1732.50	-25.08	3.33	44.14	5.08	20.81	30.00	9.19	H
1745.00	-24.10	3.68	44.16	5.06	21.44	30.00	8.56	H

LTE Band 5- ERP

Limits: $\leq 38.45\text{dBm}$ (7W)

LTE Band 5_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-21.15	2.26	45.79	0.95	2.15	21.18	38.45	17.27	H
836.50	-21.04	2.26	45.66	0.82	2.15	21.03	38.45	17.42	H
848.30	-21.51	2.27	45.55	0.80	2.15	20.42	38.45	18.03	H

LTE Band 5_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-21.10	2.26	45.79	0.94	2.15	21.22	38.45	17.23	H
836.50	-21.00	2.26	45.66	0.82	2.15	21.07	38.45	17.38	H
847.50	-21.32	2.27	45.56	0.81	2.15	20.63	38.45	17.82	H

LTE Band 5_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-21.22	2.25	45.77	0.93	2.15	21.08	38.45	17.37	H
836.50	-21.19	2.26	45.66	0.82	2.15	20.88	38.45	17.57	H
846.50	-21.57	2.26	45.56	0.82	2.15	20.40	38.45	18.05	H

LTE Band 5_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-21.56	2.13	45.74	0.90	2.15	20.80	38.45	17.65	H
836.50	-21.13	2.26	45.66	0.82	2.15	20.94	38.45	17.51	H
844.00	-21.96	2.26	45.59	0.82	2.15	20.04	38.45	18.41	H

LTE Band 5_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-21.85	2.26	45.79	0.95	2.15	20.48	38.45	17.97	H
836.50	-21.81	2.26	45.66	0.82	2.15	20.26	38.45	18.19	H
848.30	-22.48	2.27	45.55	0.80	2.15	19.45	38.45	19.00	H

LTE Band 5_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-21.83	2.26	45.79	0.94	2.15	20.49	38.45	17.96	H
836.50	-21.72	2.26	45.66	0.82	2.15	20.35	38.45	18.10	H
847.50	-22.31	2.27	45.56	0.81	2.15	19.64	38.45	18.81	H

LTE Band 5_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-21.96	2.25	45.77	0.93	2.15	20.34	38.45	18.11	H
836.50	-21.95	2.26	45.66	0.82	2.15	20.12	38.45	18.33	H
846.50	-22.48	2.26	45.56	0.82	2.15	19.49	38.45	18.96	H

LTE Band 5_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-22.28	2.13	45.74	0.90	2.15	20.08	38.45	18.37	H
836.50	-21.65	2.26	45.66	0.82	2.15	20.42	38.45	18.03	H
844.00	-22.65	2.26	45.59	0.82	2.15	19.35	38.45	19.10	H

LTE Band 12 - ERP

Limits: $\leq 34.77\text{dBm}$ (3W)

LTE Band 12_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
699.70	-22.55	1.90	44.66	0.77	2.15	18.83	34.77	15.94	H
707.50	-22.78	1.91	44.94	0.62	2.15	18.72	34.77	16.05	H
715.30	-22.77	1.92	45.26	0.50	2.15	18.92	34.77	15.85	V

LTE Band 12_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
700.50	-22.83	1.90	44.68	0.76	2.15	18.56	34.77	16.21	H
707.50	-22.84	1.91	44.94	0.62	2.15	18.66	34.77	16.11	V
714.50	-22.75	1.92	45.26	0.50	2.15	18.94	34.77	15.83	V

LTE Band 12_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
701.50	-22.78	1.90	44.81	0.74	2.15	18.72	34.77	16.05	H
707.50	-22.81	1.91	44.94	0.62	2.15	18.69	34.77	16.08	H
713.50	-22.96	1.92	45.22	0.50	2.15	18.69	34.77	16.08	V

LTE Band 12_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
704.00	-22.59	1.91	44.93	0.70	2.15	18.98	34.77	15.79	V
707.50	-22.77	1.91	44.94	0.62	2.15	18.73	34.77	16.04	V
711.00	-22.46	1.92	45.19	0.53	2.15	19.19	34.77	15.58	V

LTE Band 12_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
699.70	-23.43	1.90	44.66	0.77	2.15	17.95	34.77	16.82	V
707.50	-23.49	1.91	44.94	0.62	2.15	18.01	34.77	16.76	H
715.30	-23.28	1.92	45.26	0.50	2.15	18.41	34.77	16.36	V

LTE Band 12_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
700.50	-23.32	1.90	44.68	0.76	2.15	18.07	34.77	16.70	H
707.50	-23.57	1.91	44.94	0.62	2.15	17.93	34.77	16.84	H
714.50	-23.29	1.92	45.26	0.50	2.15	18.40	34.77	16.37	V

LTE Band 12_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
701.50	-23.41	1.90	44.81	0.74	2.15	18.09	34.77	16.68	V
707.50	-23.71	1.91	44.94	0.62	2.15	17.79	34.77	16.98	V
713.50	-23.57	1.92	45.22	0.50	2.15	18.08	34.77	16.69	V

LTE Band 12_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
704.00	-23.31	1.91	44.93	0.70	2.15	18.26	34.77	16.51	V
707.50	-23.24	1.91	44.94	0.62	2.15	18.26	34.77	16.51	H
711.00	-23.04	1.92	45.19	0.53	2.15	18.61	34.77	16.16	V

LTE Band 14- ERP

Limits: ≤ 34.77 dBm (3W)

LTE Band 14_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
790.50	-22.32	2.02	45.71	0.18	2.15	19.40	34.77	15.37	V
793.00	-22.53	2.03	45.72	0.19	2.15	19.20	34.77	15.57	V
795.50	-22.66	2.03	45.74	0.20	2.15	19.10	34.77	15.67	V

LTE Band 14_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
793.00	-22.70	2.03	45.72	0.19	2.15	19.03	34.77	15.74	V

LTE Band 14_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
790.50	-23.61	2.02	45.71	0.18	2.15	18.11	34.77	16.66	V
793.00	-23.63	2.03	45.72	0.19	2.15	18.10	34.77	16.67	V
795.50	-23.48	2.03	45.74	0.20	2.15	18.28	34.77	16.49	V

LTE Band 14_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
793.00	-23.75	2.03	45.72	0.19	2.15	17.98	34.77	16.79	V

Reference Measurement Results from basic model:

LTE Band 2-EIRP

Limits: $\leq 33\text{dBm}$ (2W)

LTE Band 2_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.70	-23.42	2.92	43.75	4.87	22.28	33.00	10.72	H
1880.00	-20.78	2.85	43.75	4.82	24.94	33.00	8.06	V
1909.30	-19.44	2.87	43.77	4.76	26.22	33.00	6.78	H

LTE Band 2_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.50	-23.31	2.87	43.75	4.87	22.44	33.00	10.56	V
1880.00	-21.12	2.85	43.75	4.82	24.60	33.00	8.40	V
1908.50	-19.77	2.89	43.78	4.76	25.88	33.00	7.12	V

LTE Band 2_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.50	-23.64	2.87	43.75	4.87	22.11	33.00	10.89	H
1880.00	-21.06	2.85	43.75	4.82	24.66	33.00	8.34	V
1907.50	-20.30	2.84	43.77	4.77	25.40	33.00	7.60	H

LTE Band 2_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.00	-23.72	2.88	43.74	4.86	22.00	33.00	11.00	H
1880.00	-21.59	2.85	43.75	4.82	24.13	33.00	8.87	V
1905.00	-20.49	2.87	43.77	4.77	25.18	33.00	7.82	H

LTE Band 2_15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.50	-23.57	2.87	43.75	4.86	22.17	33.00	10.83	H
1880.00	-21.90	2.85	43.75	4.82	23.82	33.00	9.18	V
1902.50	-20.82	2.86	43.77	4.78	24.87	33.00	8.13	H

LTE Band 2_20 MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.00	-23.51	2.86	43.75	4.85	22.23	33.00	10.77	V
1880.00	-21.68	2.85	43.75	4.82	24.04	33.00	8.96	V
1900.00	-20.90	2.87	43.77	4.78	24.78	33.00	8.22	H

LTE Band 2_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.70	-23.81	2.92	43.75	4.87	21.89	33.00	11.11	H
1880.00	-21.69	2.85	43.75	4.82	24.03	33.00	8.97	V
1909.30	-20.34	2.87	43.77	4.76	25.32	33.00	7.68	H

LTE Band 2_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.50	-24.64	2.87	43.75	4.87	21.11	33.00	11.89	H
1880.00	-22.08	2.85	43.75	4.82	23.64	33.00	9.36	V
1908.50	-20.38	2.89	43.78	4.76	25.27	33.00	7.73	H

LTE Band 2_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.50	-24.66	2.87	43.75	4.87	21.09	33.00	11.91	H
1880.00	-22.08	2.85	43.75	4.82	23.64	33.00	9.36	V
1907.50	-20.88	2.84	43.77	4.77	24.82	33.00	8.18	H

LTE Band 2_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.00	-24.97	2.88	43.74	4.86	20.75	33.00	12.25	H
1880.00	-22.66	2.85	43.75	4.82	23.06	33.00	9.94	V
1905.00	-21.22	2.87	43.77	4.77	24.45	33.00	8.55	H

LTE Band 2_15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.50	-24.87	2.87	43.75	4.86	20.87	33.00	12.13	H
1880.00	-23.27	2.85	43.75	4.82	22.45	33.00	10.55	V
1902.50	-21.39	2.86	43.77	4.78	24.30	33.00	8.70	H

LTE Band 2_20 MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.00	-24.48	2.86	43.75	4.85	21.26	33.00	11.74	V
1880.00	-22.60	2.85	43.75	4.82	23.12	33.00	9.88	V
1900.00	-21.74	2.87	43.77	4.78	23.94	33.00	9.06	H

LTE Band 2_1.4MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.70	-24.29	2.92	43.75	4.87	21.41	33.00	11.59	V
1880.00	-22.49	2.85	43.75	4.82	23.23	33.00	9.77	V
1909.30	-20.66	2.87	43.77	4.76	25.00	33.00	8.00	H

LTE Band 2_3MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.50	-25.03	2.87	43.75	4.87	20.72	33.00	12.28	V
1880.00	-22.90	2.85	43.75	4.82	22.82	33.00	10.18	V
1908.50	-20.77	2.89	43.78	4.76	24.88	33.00	8.12	H

LTE Band 2_5MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.50	-25.03	2.87	43.75	4.87	20.72	33.00	12.28	H
1880.00	-22.87	2.85	43.75	4.82	22.85	33.00	10.15	V
1907.50	-21.25	2.84	43.77	4.77	24.45	33.00	8.55	H

LTE Band 2_10MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.00	-25.47	2.88	43.74	4.86	20.25	33.00	12.75	H
1880.00	-23.47	2.85	43.75	4.82	22.25	33.00	10.75	V
1905.00	-21.55	2.87	43.77	4.77	24.12	33.00	8.88	H

LTE Band 2_15MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.50	-25.42	2.87	43.75	4.86	20.32	33.00	12.68	H
1880.00	-23.69	2.85	43.75	4.82	22.03	33.00	10.97	H
1902.50	-21.81	2.86	43.77	4.78	23.88	33.00	9.12	H

LTE Band 2_20 MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.00	-25.12	2.86	43.75	4.85	20.62	33.00	12.38	V
1880.00	-23.24	2.85	43.75	4.82	22.48	33.00	10.52	H
1900.00	-22.23	2.87	43.77	4.78	23.45	33.00	9.55	H

LTE Band 4-EIRP

Limits: ≤30dBm (1W)

LTE Band 4_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.70	-24.59	3.17	44.10	5.12	21.46	30.00	8.54	H
1732.50	-25.34	3.33	44.14	5.08	20.55	30.00	9.45	V
1754.30	-23.60	3.76	44.14	5.04	21.82	30.00	8.18	H

LTE Band 4_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.50	-24.78	3.40	44.10	5.12	21.04	30.00	8.96	H
1732.50	-25.71	3.33	44.14	5.08	20.18	30.00	9.82	V
1753.50	-23.55	3.80	44.13	5.04	21.82	30.00	8.18	H

LTE Band 4_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.50	-24.45	3.66	44.10	5.12	21.11	30.00	8.89	V
1732.50	-25.57	3.33	44.14	5.08	20.32	30.00	9.68	H
1752.50	-23.90	3.82	44.14	5.05	21.47	30.00	8.53	H

LTE Band 4_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.00	-24.52	3.56	44.10	5.11	21.13	30.00	8.87	V
1732.50	-25.28	3.33	44.14	5.08	20.61	30.00	9.39	H
1750.00	-24.79	3.00	44.15	5.05	21.41	30.00	8.59	H

LTE Band 4_15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.50	-24.31	3.47	44.11	5.11	21.44	30.00	8.56	V
1732.50	-25.24	3.33	44.14	5.08	20.65	30.00	9.35	H
1747.50	-25.02	3.34	44.15	5.05	20.84	30.00	9.16	H

LTE Band 4_20 MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.00	-24.37	3.37	44.11	5.10	21.47	30.00	8.53	V
1732.50	-25.21	3.33	44.14	5.08	20.68	30.00	9.32	V
1745.00	-24.81	3.68	44.16	5.06	20.73	30.00	9.27	H

LTE Band 4_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.70	-25.51	3.17	44.10	5.12	20.54	30.00	9.46	H
1732.50	-26.22	3.33	44.14	5.08	19.67	30.00	10.33	H
1754.30	-24.33	3.76	44.14	5.04	21.09	30.00	8.91	H

LTE Band 4_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.50	-25.94	3.40	44.10	5.12	19.88	30.00	10.12	H
1732.50	-26.55	3.33	44.14	5.08	19.34	30.00	10.66	H
1753.50	-24.56	3.80	44.13	5.04	20.81	30.00	9.19	H

LTE Band 4_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.50	-25.77	3.66	44.10	5.12	19.79	30.00	10.21	V
1732.50	-26.33	3.33	44.14	5.08	19.56	30.00	10.44	H
1752.50	-24.56	3.82	44.14	5.05	20.81	30.00	9.19	H

LTE Band 4_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.00	-25.57	3.56	44.10	5.11	20.08	30.00	9.92	V
1732.50	-26.42	3.33	44.14	5.08	19.47	30.00	10.53	H
1750.00	-25.61	3.00	44.15	5.05	20.59	30.00	9.41	H

LTE Band 4_15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.50	-25.40	3.47	44.11	5.11	20.35	30.00	9.65	V
1732.50	-26.38	3.33	44.14	5.08	19.51	30.00	10.49	H
1747.50	-25.66	3.34	44.15	5.05	20.20	30.00	9.80	H

LTE Band 4_20 MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.00	-25.51	3.37	44.11	5.10	20.33	30.00	9.67	V
1732.50	-26.20	3.33	44.14	5.08	19.69	30.00	10.31	H
1745.00	-25.45	3.68	44.16	5.06	20.09	30.00	9.91	V

LTE Band 4_1.4MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1710.70	-26.42	3.17	44.10	5.12	19.63	30.00	10.37	H
1732.50	-27.23	3.33	44.14	5.08	18.66	30.00	11.34	H
1754.30	-25.20	3.76	44.14	5.04	20.22	30.00	9.78	H

LTE Band 4_3MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1711.50	-26.83	3.40	44.10	5.12	18.99	30.00	11.01	V
1732.50	-27.44	3.33	44.14	5.08	18.45	30.00	11.55	H
1753.50	-25.37	3.80	44.13	5.04	20.00	30.00	10.00	H

LTE Band 4_5MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1712.50	-26.61	3.66	44.10	5.12	18.95	30.00	11.05	V
1732.50	-26.89	3.33	44.14	5.08	19.00	30.00	11.00	V
1752.50	-25.52	3.82	44.14	5.05	19.85	30.00	10.15	H

LTE Band 4_10MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1715.00	-26.55	3.56	44.10	5.11	19.10	30.00	10.90	V
1732.50	-27.50	3.33	44.14	5.08	18.39	30.00	11.61	H
1750.00	-26.53	3.00	44.15	5.05	19.67	30.00	10.33	H

LTE Band 4_15MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1717.50	-26.15	3.47	44.11	5.11	19.60	30.00	10.40	V
1732.50	-27.24	3.33	44.14	5.08	18.65	30.00	11.35	H
1747.50	-26.33	3.34	44.15	5.05	19.53	30.00	10.47	H

LTE Band 4_20 MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1720.00	-26.36	3.37	44.11	5.10	19.48	30.00	10.52	V
1732.50	-27.10	3.33	44.14	5.08	18.79	30.00	11.21	H
1745.00	-26.10	3.68	44.16	5.06	19.44	30.00	10.56	V

LTE Band 5-ERP

Limits: $\leq 38.45\text{dBm}$ (7W)

LTE Band 5_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-22.16	2.26	45.79	0.95	2.15	20.17	38.45	18.28	H
836.50	-21.32	2.26	45.66	0.82	2.15	20.75	38.45	17.70	H
848.30	-21.56	2.27	45.55	0.80	2.15	20.37	38.45	18.08	H

LTE Band 5_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-22.18	2.26	45.79	0.94	2.15	20.14	38.45	18.31	H
836.50	-21.35	2.26	45.66	0.82	2.15	20.72	38.45	17.73	H
847.50	-21.56	2.27	45.56	0.81	2.15	20.39	38.45	18.06	H

LTE Band 5_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-22.25	2.25	45.77	0.93	2.15	20.05	38.45	18.40	H
836.50	-21.25	2.26	45.66	0.82	2.15	20.82	38.45	17.63	H
846.50	-21.48	2.26	45.56	0.82	2.15	20.49	38.45	17.96	H

LTE Band 5_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-22.41	2.25	45.77	0.90	2.15	19.86	38.45	18.59	H
836.50	-21.20	2.26	45.66	0.82	2.15	20.87	38.45	17.58	H
844.00	-21.44	2.26	45.59	0.82	2.15	20.56	38.45	17.89	H

LTE Band 5_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-22.85	2.26	45.79	0.95	2.15	19.48	38.45	18.97	H
836.50	-22.19	2.26	45.66	0.82	2.15	19.88	38.45	18.57	H
848.30	-22.47	2.27	45.55	0.80	2.15	19.46	38.45	18.99	H

LTE Band 5_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-22.84	2.26	45.79	0.94	2.15	19.48	38.45	18.97	H
836.50	-22.24	2.26	45.66	0.82	2.15	19.83	38.45	18.62	H
847.50	-22.53	2.27	45.56	0.81	2.15	19.42	38.45	19.03	H

LTE Band 5_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-23.00	2.25	45.77	0.93	2.15	19.30	38.45	19.15	H
836.50	-22.10	2.26	45.66	0.82	2.15	19.97	38.45	18.48	H
846.50	-22.35	2.26	45.56	0.82	2.15	19.62	38.45	18.83	H

LTE Band 5_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-23.12	2.25	45.77	0.90	2.15	19.15	38.45	19.30	H
836.50	-22.07	2.26	45.66	0.82	2.15	20.00	38.45	18.45	H
844.00	-22.30	2.26	45.59	0.82	2.15	19.70	38.45	18.75	H

LTE Band 5_1.4MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.70	-23.97	2.26	45.79	0.95	2.15	18.36	38.45	20.09	H
836.50	-23.40	2.26	45.66	0.82	2.15	18.67	38.45	19.78	H
848.30	-23.70	2.27	45.55	0.80	2.15	18.23	38.45	20.22	H

LTE Band 5_3MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
825.50	-23.99	2.26	45.79	0.94	2.15	18.33	38.45	20.12	H
836.50	-23.44	2.26	45.66	0.82	2.15	18.63	38.45	19.82	H
847.50	-23.74	2.27	45.56	0.81	2.15	18.21	38.45	20.24	H

LTE Band 5_5MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
826.50	-24.01	2.25	45.77	0.93	2.15	18.29	38.45	20.16	H
836.50	-23.34	2.26	45.66	0.82	2.15	18.73	38.45	19.72	H
846.50	-23.51	2.26	45.56	0.82	2.15	18.46	38.45	19.99	H

LTE Band 5_10MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
829.00	-24.15	2.25	45.77	0.90	2.15	18.12	38.45	20.33	H
836.50	-23.33	2.26	45.66	0.82	2.15	18.74	38.45	19.71	H
844.00	-23.41	2.26	45.59	0.82	2.15	18.59	38.45	19.86	H

LTE Band 12 -ERP

Limits: $\leq 34.77\text{dBm}$ (3W)

LTE Band 12_1.4MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
699.70	-21.84	1.90	44.66	0.77	2.15	19.54	34.77	15.23	V
707.50	-22.08	1.91	44.94	0.62	2.15	19.42	34.77	15.35	V
715.30	-22.46	1.92	45.26	0.50	2.15	19.23	34.77	15.54	V

LTE Band 12_3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
700.50	-21.70	1.90	44.68	0.76	2.15	19.69	34.77	15.08	V
707.50	-22.12	1.91	44.94	0.62	2.15	19.38	34.77	15.39	V
714.50	-22.44	1.92	45.26	0.50	2.15	19.25	34.77	15.52	V

LTE Band 12_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
701.50	-21.77	1.90	44.81	0.74	2.15	19.73	34.77	15.04	V
707.50	-22.15	1.91	44.94	0.62	2.15	19.35	34.77	15.42	V
713.50	-22.42	1.92	45.22	0.50	2.15	19.23	34.77	15.54	V

LTE Band 12_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
704.00	-22.28	1.91	44.93	0.70	2.15	19.29	34.77	15.48	H
707.50	-22.04	1.91	44.94	0.62	2.15	19.46	34.77	15.31	V
711.00	-22.26	1.92	45.19	0.53	2.15	19.39	34.77	15.38	V

LTE Band 12_1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
699.70	-22.69	1.90	44.66	0.77	2.15	18.69	34.77	16.08	V
707.50	-23.06	1.91	44.94	0.62	2.15	18.44	34.77	16.33	V
715.30	-22.85	1.92	45.26	0.50	2.15	18.84	34.77	15.93	V

LTE Band 12_3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
700.50	-22.53	1.90	44.68	0.76	2.15	18.86	34.77	15.91	V
707.50	-23.14	1.91	44.94	0.62	2.15	18.36	34.77	16.41	V
714.50	-22.99	1.92	45.26	0.50	2.15	18.70	34.77	16.07	V

LTE Band 12_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
701.50	-22.61	1.90	44.81	0.74	2.15	18.89	34.77	15.88	V
707.50	-23.21	1.91	44.94	0.62	2.15	18.29	34.77	16.48	V
713.50	-23.04	1.92	45.22	0.50	2.15	18.61	34.77	16.16	V

LTE Band 12_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
704.00	-22.56	1.91	44.93	0.70	2.15	19.01	34.77	15.76	V
707.50	-23.00	1.91	44.94	0.62	2.15	18.50	34.77	16.27	V
711.00	-22.71	1.92	45.19	0.53	2.15	18.94	34.77	15.83	V

LTE Band 12_1.4MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
699.70	-23.83	1.90	44.66	0.77	2.15	17.55	34.77	17.22	H
707.50	-23.75	1.91	44.94	0.62	2.15	17.75	34.77	17.02	V
715.30	-23.25	1.92	45.26	0.50	2.15	18.44	34.77	16.33	V

LTE Band 12_3MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
700.50	-23.55	1.90	44.68	0.76	2.15	17.84	34.77	16.93	H
707.50	-23.82	1.91	44.94	0.62	2.15	17.68	34.77	17.09	V
714.50	-23.65	1.92	45.26	0.50	2.15	18.04	34.77	16.73	V

LTE Band 12_5MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
701.50	-23.83	1.90	44.81	0.74	2.15	17.67	34.77	17.10	H
707.50	-23.89	1.91	44.94	0.62	2.15	17.61	34.77	17.16	V
713.50	-23.50	1.92	45.22	0.50	2.15	18.15	34.77	16.62	V

LTE Band 12_10MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{Cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
704.00	-23.41	1.91	44.93	0.70	2.15	18.16	34.77	16.61	H
707.50	-23.87	1.91	44.94	0.62	2.15	17.63	34.77	17.14	V
711.00	-23.29	1.92	45.19	0.53	2.15	18.36	34.77	16.41	V

LTE Band 14-ERP

Limits: ≤ 34.77 dBm (3W)

LTE Band 14_5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
790.50	-22.59	2.02	45.71	0.18	2.15	19.13	34.77	15.64	H
793.00	-22.74	2.03	45.72	0.19	2.15	18.99	34.77	15.78	H
795.50	-22.71	2.03	45.74	0.20	2.15	19.05	34.77	15.72	H

LTE Band 14_10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
793.00	-22.84	2.03	45.72	0.19	2.15	18.89	34.77	15.88	H

LTE Band 14_5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
790.50	-24.15	2.02	45.71	0.18	2.15	17.57	34.77	17.20	V
793.00	-23.98	2.03	45.72	0.19	2.15	17.75	34.77	17.02	V
795.50	-23.42	2.03	45.74	0.20	2.15	18.34	34.77	16.43	V

LTE Band 14_10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
793.00	-23.35	2.03	45.72	0.19	2.15	18.38	34.77	16.39	V

LTE Band 14_5MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
790.50	-24.70	2.02	45.71	0.18	2.15	17.02	34.77	17.75	H
793.00	-24.62	2.03	45.72	0.19	2.15	17.11	34.77	17.66	H
795.50	-24.05	2.03	45.74	0.20	2.15	17.71	34.77	17.06	H

LTE Band 14_10MHz_64QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	P _{Ag} (dB)	G _a (dBi)	Correction (dB)	ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
793.00	-24.77	2.03	45.72	0.19	2.15	16.96	34.77	17.81	H

Peak EIRP (dBm) = P_{Mea}(-18.49dBm) - G_a(-4.77dBi) - P_{Ag}(-43.77dB) - P_{cl}(2.84dB) = 27.21dBm

ANALYZER SETTINGS:

RBW = VBW = 8MHz for occupied bandwidths equal to or less than 5MHz.

RBW = VBW = 20MHz for occupied bandwidths equal to or greater than 10MHz.

Note: Expanded measurement uncertainty is $U = 2.84$ dB, $k = 2$.

A.2 EMISSION LIMIT


A.2.1 Measurement Method

The measurements procedures in TIA-603E-2016 are used. This measurement is carried out in fully-anechoic chamber FAC-3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier. The resolution bandwidth is set 1MHz. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE Bands 2,4,5,12,14.

The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5-meter-high non-conductive stand at a 3-meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360 and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with RMS detector.



2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere

with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

4. The Path loss (P_{pl}) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G_a) should be recorded after test.

An amplifier should be connected in for the test.

The Path loss (P_{pl}) is the summation of the cable loss and the gain of the amplifier.

The measurement results are obtained as described below:

Power (EIRP) = $P_{Mea} + P_{pl} + G_a$

5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
6. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15dB$.

A.2.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following: (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB; (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB; (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 +$

10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

Part 90.543 states that For operations in the 758–768 MHz and the 788–798 MHz bands, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following: (1) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations. (2) On all frequencies between 769–775 MHz and 799–805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations. (3) On any frequency between 775–788 MHz, above 805 MHz, and below 758 MHz, by at least $43 + 10 \log (P)$ dB. (4) Compliance with the provisions of paragraphs (e)(1) and (2) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment. (5) Compliance with the provisions of paragraph (e)(3) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of 30 kHz may be employed.

A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the LTE Bands 2,4,5,12,14. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE Bands 2,4,5,12,14. into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this. The evaluated frequency range is from 30MHz to 26GHz.

Spot Check Measurement Results:
LTE Band 2, 1.4MHz, QPSK, Channel 18607

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3702.02	-53.76	6.42	8.48	-51.70	-13.00	38.70	V
5595.02	-56.82	7.23	10.58	-53.47	-13.00	40.47	V
7389.01	-55.18	8.12	12.07	-51.23	-13.00	38.23	V
9281.01	-54.55	9.11	13.27	-50.39	-13.00	37.39	H
11119.01	-52.42	9.75	13.18	-48.99	-13.00	35.99	V
12929.01	-49.74	10.50	13.46	-46.78	-13.00	33.78	H

LTE Band 2, 1.4MHz, QPSK, Channel 18900

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.02	-52.13	6.26	8.56	-49.83	-13.00	36.83	V
5684.02	-56.59	7.28	10.56	-53.31	-13.00	40.31	H
7564.01	-55.29	8.12	12.25	-51.16	-13.00	38.16	H
9403.01	-53.40	9.05	13.34	-49.11	-13.00	36.11	H
11243.01	-51.61	9.66	13.15	-48.12	-13.00	35.12	V
13115.01	-48.29	10.87	13.66	-45.50	-13.00	32.50	V

LTE Band 2, 1.4MHz, QPSK, Channel 19193

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.02	-49.42	6.08	8.65	-46.85	-13.00	33.85	V
5771.02	-56.22	7.23	10.55	-52.90	-13.00	39.90	H
7634.01	-55.19	8.13	12.31	-51.01	-13.00	38.01	V
9555.01	-51.73	9.34	13.34	-47.73	-13.00	34.73	H
11458.01	-51.63	9.92	13.11	-48.44	-13.00	35.44	V
13333.01	-48.58	10.58	13.97	-45.19	-13.00	32.19	V

LTE Band 4, 1.4MHz QPSK, Channel 19957

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3422.02	-54.35	5.38	8.01	-51.72	-13.00	38.72	V
5144.02	-56.49	6.87	10.10	-53.26	-13.00	40.26	V
6889.01	-53.80	7.77	11.47	-50.10	-13.00	37.10	H
8560.01	-54.17	8.56	13.01	-49.72	-13.00	36.72	H
10238.01	-52.35	9.43	13.00	-48.78	-13.00	35.78	H
11989.01	-49.38	10.10	13.00	-46.48	-13.00	33.48	H

LTE Band 4, 1.4MHz, QPSK, Channel 20175

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3465.02	-54.99	5.46	8.12	-52.33	-13.00	39.33	H
5243.02	-57.26	7.00	10.24	-54.02	-13.00	41.02	H
6977.01	-55.12	8.12	11.57	-51.67	-13.00	38.67	H
8669.01	-52.77	8.40	13.03	-48.14	-13.00	35.14	H
10408.01	-50.60	9.79	13.06	-47.33	-13.00	34.33	H
12140.01	-49.68	10.23	13.06	-46.85	-13.00	33.85	V

LTE Band 4, 1.4MHz, QPSK, Channel 20393

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3509.02	-53.34	5.54	8.21	-50.67	-13.00	37.67	H
5251.02	-57.09	7.00	10.25	-53.84	-13.00	40.84	H
6987.01	-54.56	8.20	11.58	-51.18	-13.00	38.18	H
8776.01	-49.99	8.59	13.06	-45.52	-13.00	32.52	V
10539.01	-49.93	9.51	13.11	-46.33	-13.00	33.33	H
12274.01	-50.06	10.01	13.11	-46.96	-13.00	33.96	H

LTE Band 5, 1.4MHz, QPSK, Channel 20407

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1650.01	-42.57	3.57	5.23	2.15	-43.06	-13.00	30.06	V
2474.00	-50.16	4.60	6.02	2.15	-50.89	-13.00	37.89	V
3299.02	-44.47	5.29	7.72	2.15	-44.19	-13.00	31.19	H
4126.02	-51.84	6.04	9.03	2.15	-51.00	-13.00	38.00	V
4951.01	-53.10	6.69	9.85	2.15	-52.09	-13.00	39.09	V
5782.01	-54.65	7.22	10.54	2.15	-53.48	-13.00	40.48	H

LTE Band 5, 1.4MHz, QPSK, Channel 20525

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.01	-40.80	3.58	5.19	2.15	-41.34	-13.00	28.34	V
2510.00	-47.84	4.63	6.12	2.15	-48.50	-13.00	35.50	H
3346.02	-41.75	5.31	7.83	2.15	-41.38	-13.00	28.38	H
4185.02	-50.21	6.17	9.09	2.15	-49.44	-13.00	36.44	V
5024.01	-53.78	6.56	9.93	2.15	-52.56	-13.00	39.56	V
5851.01	-53.91	7.24	10.53	2.15	-52.77	-13.00	39.77	H

LTE Band 5, 1.4MHz, QPSK, Channel 20643

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.01	-36.86	3.60	5.15	2.15	-37.46	-13.00	24.46	V
2545.00	-45.23	4.66	6.18	2.15	-45.86	-13.00	32.86	H
3394.02	-40.32	5.36	7.95	2.15	-39.88	-13.00	26.88	V
4243.02	-51.83	6.25	9.14	2.15	-51.09	-13.00	38.09	H
5085.01	-54.95	6.73	10.02	2.15	-53.81	-13.00	40.81	H
5943.01	-53.23	7.47	10.51	2.15	-52.34	-13.00	39.34	H

LTE Band 12, 1.4MHz, QPSK, Channel 23017

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1400.01	-51.61	3.24	4.98	2.15	-52.02	-13.00	39.02	V
2099.00	-42.42	4.19	4.90	2.15	-43.86	-13.00	30.86	V
2811.00	-52.46	4.93	6.66	2.15	-52.88	-13.00	39.88	V
3486.02	-56.62	5.49	8.17	2.15	-56.09	-13.00	43.09	H
4200.02	-55.54	6.21	9.10	2.15	-54.80	-13.00	41.80	H
4910.01	-54.64	6.73	9.81	2.15	-53.71	-13.00	40.71	H

LTE Band 12, 1.4MHz, QPSK, Channel 23095

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1415.01	-48.93	3.25	5.06	2.15	-49.27	-13.00	36.27	H
2123.00	-44.27	4.21	4.97	2.15	-45.66	-13.00	32.66	V
2822.00	-52.77	4.94	6.68	2.15	-53.18	-13.00	40.18	H
3546.02	-55.33	5.78	8.26	2.15	-55.00	-13.00	42.00	V
4257.02	-55.87	6.23	9.16	2.15	-55.09	-13.00	42.09	H
4947.01	-55.77	6.69	9.85	2.15	-54.76	-13.00	41.76	V

LTE Band 12, 1.4MHz, QPSK, Channel 23173

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1431.01	-51.33	3.28	5.14	2.15	-51.62	-13.00	38.62	H
2146.00	-43.71	4.24	5.04	2.15	-45.06	-13.00	32.06	V
2873.00	-52.44	4.97	6.77	2.15	-52.79	-13.00	39.79	H
3579.02	-55.99	6.12	8.31	2.15	-55.95	-13.00	42.95	V
4298.02	-55.20	6.20	9.20	2.15	-54.35	-13.00	41.35	H
5010.01	-55.73	6.59	9.91	2.15	-54.56	-13.00	41.56	V

LTE Band 14, 5 MHz, QPSK, Channel 23305

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1581.01	-57.56	3.50	5.35	2.15	-57.86	-13.00	44.86	V
2386.00	-53.89	4.50	5.76	2.15	-54.78	-13.00	41.78	H
3169.02	-54.60	5.34	7.41	2.15	-54.68	-13.00	41.68	H
3949.02	-55.46	6.11	8.83	2.15	-54.89	-13.00	41.89	H
4746.02	-54.56	6.56	9.65	2.15	-53.62	-13.00	40.62	H
5531.01	-55.55	7.16	10.59	2.15	-54.27	-13.00	41.27	H

LTE Band 14, 5 MHz, QPSK, Channel 23330

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1586.01	-53.68	3.50	5.35	2.15	-53.98	-13.00	40.98	V
2380.00	-52.75	4.49	5.74	2.15	-53.65	-13.00	40.65	V
3173.02	-52.80	5.34	7.42	2.15	-52.87	-13.00	39.87	V
3966.02	-53.49	6.09	8.85	2.15	-52.88	-13.00	39.88	H
4759.01	-52.42	6.59	9.66	2.15	-51.50	-13.00	38.50	V
5539.01	-54.69	7.17	10.59	2.15	-53.42	-13.00	40.42	H

LTE Band 14, 5 MHz, QPSK, Channel 23355

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1591.01	-53.33	3.51	5.34	2.15	-53.65	-13.00	40.65	V
2387.00	-51.68	4.50	5.76	2.15	-52.57	-13.00	39.57	V
3183.02	-51.78	5.32	7.44	2.15	-51.81	-13.00	38.81	V
3979.02	-52.88	6.08	8.87	2.15	-52.24	-13.00	39.24	H
4776.01	-53.14	6.62	9.68	2.15	-52.23	-13.00	39.23	V
5562.01	-54.70	7.19	10.59	2.15	-53.45	-13.00	40.45	V

Reference Measurement Results from basic model:
LTE Band 2, 1.4MHz, QPSK, Channel 18607

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3701.02	-52.31	6.42	8.48	-50.25	-13.00	37.25	V
5602.02	-54.75	7.24	10.58	-51.41	-13.00	38.41	H
7426.01	-54.14	8.19	12.11	-50.22	-13.00	37.22	V
9257.01	-52.41	9.06	13.25	-48.22	-13.00	35.22	H
11119.01	-50.94	9.75	13.18	-47.51	-13.00	34.51	V
12953.01	-48.48	10.49	13.47	-45.50	-13.00	32.50	V

LTE Band 2, 1.4MHz, QPSK, Channel 18900

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3759.02	-43.92	6.26	8.56	-41.62	-13.00	28.62	V
5639.02	-51.01	7.27	10.57	-47.71	-13.00	34.71	H
7499.01	-53.75	8.39	12.20	-49.94	-13.00	36.94	H
9402.01	-51.51	9.05	13.34	-47.22	-13.00	34.22	H
11279.01	-49.85	9.87	13.14	-46.58	-13.00	33.58	V
13188.01	-47.55	10.55	13.76	-44.34	-13.00	31.34	V

LTE Band 2, 1.4MHz, QPSK, Channel 19193

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3818.02	-42.64	6.08	8.65	-40.07	-13.00	27.07	V
5728.02	-46.93	7.30	10.55	-43.68	-13.00	30.68	H
7639.01	-53.56	8.15	12.31	-49.40	-13.00	36.40	V
9550.01	-47.86	9.36	13.35	-43.87	-13.00	30.87	H
11477.01	-50.29	9.87	13.10	-47.06	-13.00	34.06	V
13390.01	-47.44	10.57	14.05	-43.96	-13.00	30.96	V

LTE Band 4, 1.4MHz QPSK, Channel 19957

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3421.02	-67.13	5.38	8.01	-64.50	-13.00	51.50	V
5134.02	-64.85	6.86	10.09	-61.62	-13.00	48.62	H
6845.01	-64.51	7.83	11.41	-60.93	-13.00	47.93	V
8554.01	-63.40	8.58	13.01	-58.97	-13.00	45.97	V
10270.01	-59.44	9.54	13.01	-55.97	-13.00	42.97	H
12007.01	-59.88	10.07	13.00	-56.95	-13.00	43.95	V

LTE Band 4, 1.4MHz, QPSK, Channel 20175

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3464.02	-66.71	5.45	8.11	-64.05	-13.00	51.05	H
5199.02	-65.14	6.96	10.18	-61.92	-13.00	48.92	H
6979.01	-64.46	8.14	11.57	-61.03	-13.00	48.03	V
8664.01	-63.41	8.41	13.03	-58.79	-13.00	45.79	V
10404.01	-60.07	9.80	13.06	-56.81	-13.00	43.81	H
12174.01	-59.41	10.13	13.07	-56.47	-13.00	43.47	V

LTE Band 4, 1.4MHz, QPSK, Channel 20393

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3508.02	-65.86	5.53	8.21	-63.18	-13.00	50.18	H
5265.02	-65.31	6.99	10.27	-62.03	-13.00	49.03	H
6979.01	-64.47	8.14	11.57	-61.04	-13.00	48.04	V
8773.01	-63.73	8.58	13.05	-59.26	-13.00	46.26	V
10534.01	-60.51	9.53	13.11	-56.93	-13.00	43.93	V
12269.01	-59.62	10.01	13.11	-56.52	-13.00	43.52	V

LTE Band 5, 1.4MHz, QPSK, Channel 20407

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1649.01	-43.06	3.56	5.23	2.15	-43.54	-13.00	30.54	V
2473.00	-46.45	4.60	6.02	2.15	-47.18	-13.00	34.18	V
3297.02	-38.56	5.29	7.71	2.15	-38.29	-13.00	25.29	V
4125.02	-46.61	6.04	9.03	2.15	-45.77	-13.00	32.77	V
4953.01	-53.98	6.68	9.85	2.15	-52.96	-13.00	39.96	V
5772.01	-52.15	7.23	10.55	2.15	-50.98	-13.00	37.98	V

LTE Band 5, 1.4MHz, QPSK, Channel 20525

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1672.01	-41.67	3.58	5.19	2.15	-42.21	-13.00	29.21	V
2508.00	-42.96	4.63	6.11	2.15	-43.63	-13.00	30.63	V
3344.02	-38.44	5.31	7.83	2.15	-38.07	-13.00	25.07	V
4184.02	-46.43	6.17	9.08	2.15	-45.67	-13.00	32.67	V
5020.01	-52.28	6.57	9.93	2.15	-51.07	-13.00	38.07	V
5856.01	-50.45	7.25	10.53	2.15	-49.32	-13.00	36.32	V

LTE Band 5, 1.4MHz, QPSK, Channel 20643

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1696.01	-43.10	3.60	5.15	2.15	-43.70	-13.00	30.70	V
2544.00	-44.82	4.66	6.18	2.15	-45.45	-13.00	32.45	V
3392.02	-37.18	5.35	7.94	2.15	-36.74	-13.00	23.74	H
4241.02	-46.50	6.25	9.14	2.15	-45.76	-13.00	32.76	V
5090.01	-51.33	6.74	10.03	2.15	-50.19	-13.00	37.19	V
5939.01	-48.36	7.47	10.51	2.15	-47.47	-13.00	34.47	V

LTE Band 12, 1.4MHz, QPSK, Channel 23017

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1399.01	-58.12	3.23	4.97	2.15	-58.53	-13.00	45.53	H
2098.00	-50.03	4.19	4.89	2.15	-51.48	-13.00	38.48	V
2807.00	-53.11	4.92	6.65	2.15	-53.53	-13.00	40.53	H
3508.02	-54.71	5.53	8.21	2.15	-54.18	-13.00	41.18	H
4208.02	-48.67	6.22	9.11	2.15	-47.93	-13.00	34.93	H
4890.01	-53.64	6.73	9.79	2.15	-52.73	-13.00	39.73	V

LTE Band 12, 1.4MHz, QPSK, Channel 23095

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1414.01	-55.63	3.25	5.05	2.15	-55.98	-13.00	42.98	H
2121.00	-54.25	4.21	4.96	2.15	-55.65	-13.00	42.65	V
2842.00	-52.48	4.95	6.72	2.15	-52.86	-13.00	39.86	V
3533.02	-54.80	5.65	8.25	2.15	-54.35	-13.00	41.35	V
4238.02	-47.79	6.25	9.14	2.15	-47.05	-13.00	34.05	H
4938.01	-53.05	6.71	9.84	2.15	-52.07	-13.00	39.07	H

LTE Band 12, 1.4MHz, QPSK, Channel 23173

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1420.01	-58.05	3.26	5.08	2.15	-58.38	-13.00	45.38	V
2149.00	-54.73	4.25	5.05	2.15	-56.08	-13.00	43.08	V
2866.00	-41.64	4.96	6.76	2.15	-41.99	-13.00	28.99	V
3577.02	-53.90	6.10	8.31	2.15	-53.84	-13.00	40.84	V
4278.02	-53.35	6.21	9.18	2.15	-52.53	-13.00	39.53	H
4999.01	-53.88	6.60	9.90	2.15	-52.73	-13.00	39.73	V

LTE Band 14, 5 MHz, QPSK, Channel 23305

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1578.01	-55.26	3.49	5.36	2.15	-55.54	-13.00	42.54	V
2368.00	-51.83	4.48	5.70	2.15	-52.76	-13.00	39.76	V
3149.02	-52.87	5.37	7.36	2.15	-53.03	-13.00	40.03	V
3946.02	-54.29	6.11	8.82	2.15	-53.73	-13.00	40.73	H
4756.01	-53.88	6.58	9.66	2.15	-52.95	-13.00	39.95	V
5539.01	-54.23	7.17	10.59	2.15	-52.96	-13.00	39.96	V

LTE Band 14, 5 MHz, QPSK, Channel 23330

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1584.01	-55.55	3.50	5.35	2.15	-55.85	-13.00	42.85	V
2375.00	-52.45	4.49	5.73	2.15	-53.36	-13.00	40.36	V
3167.02	-53.01	5.35	7.40	2.15	-53.11	-13.00	40.11	H
3959.02	-54.09	6.10	8.84	2.15	-53.50	-13.00	40.50	H
4753.01	-53.33	6.58	9.65	2.15	-52.41	-13.00	39.41	V
5550.01	-53.70	7.18	10.59	2.15	-52.44	-13.00	39.44	H

LTE Band 14, 5 MHz, QPSK, Channel 23355

Frequency (MHz)	P _{Mea} (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1588.01	-55.82	3.51	5.34	2.15	-56.14	-13.00	43.14	V
2382.00	-52.60	4.49	5.75	2.15	-53.49	-13.00	40.49	V
3177.02	-52.51	5.33	7.42	2.15	-52.57	-13.00	39.57	V
3971.02	-54.41	6.09	8.86	2.15	-53.79	-13.00	40.79	H
4773.01	-54.61	6.61	9.67	2.15	-53.70	-13.00	40.70	V
5565.01	-53.78	7.20	10.59	2.15	-52.54	-13.00	39.54	V

Note: The maximum value of expanded measurement uncertainty for this test item is $U = 5.16$ dB, $k = 2$.

A.3 FREQUENCY STABILITY

A.3.1 Method of Measurement

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at +20 °C and rated supply voltage. Two reference points are established at the applicable unwanted emissions limit using a RBW equal to the RBW required by the unwanted emissions specification of the applicable regulatory standard. These reference points measured using the lowest and highest channel of operation shall be identified as F_L and F_H respectively.

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE Bands 2,4,5,7,12,13,14,17,25,26,30,38,40,41,66,71, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
5. Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the center channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 °C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.4VDC and 4.35VDC, with a nominal voltage of 3.85VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.

A.3.2 Measurement results

LTE Band 2, 20MHz bandwidth QPSK (worst case of all bandwidths)

Frequency Error vs Temperature

Temperature(°C)	Voltage(V)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.85	1850.801	1909.199		
50				1.24	0.0007
40				0.5	0.0003
30				0.48	0.0003
10				0.33	0.0002
0				0.13	0.0001
-10				0.45	0.0002
-20				0.43	0.0002
-30				0.93	0.0005

Frequency Error vs Voltage

Voltage(V)	Temperature(°C)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
3.4	20	1850.801	1909.199	0.77	0.0004
4.35				1.76	0.0009

LTE Band 4, 20MHz bandwidth QPSK (worst case of all bandwidths)

Frequency Error vs Temperature

Temperature(°C)	Voltage(V)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.85	1710.801	1754.183		
50				9.01	0.0052
40				0.84	0.0005
30				0.18	0.0001
10				1.33	0.0008
0				0.21	0.0001
-10				7.53	0.0043
-20				0.51	0.0003
-30				7.95	0.0046

Frequency Error vs Voltage

Voltage(V)	Temperature(°C)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
3.4	20	1710.801	1754.183	10.04	0.0058
4.35				0.25	0.0001

LTE Band 5, 10MHz bandwidth QPSK (worst case of all bandwidths)

Frequency Error vs Temperature

Temperature(°C)	Voltage(V)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.85	824.417	848.583		
50				0.21	0.0003
40				1.95	0.0023
30				1.27	0.0015
10				1.79	0.0021
0				0.47	0.0006
-10				1.17	0.0014
-20				0.3	0.0004
-30				1.27	0.0015

Frequency Error vs Voltage

Voltage(V)	Temperature(°C)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
3.4	20	824.417	848.583	0.43	0.0005
4.35				0.07	0.0001

LTE Band 12, 10MHz bandwidth QPSK (worst case of all bandwidths)

Frequency Error vs Temperature

Temperature(°C)	Voltage(V)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.85	699.481	715.519		
50				1.79	0.0025
40				0.82	0.0012
30				1.61	0.0023
10				2.01	0.0028
0				1.72	0.0024
-10				0.45	0.0006
-20				0.37	0.0005
-30				0.45	0.0006

Frequency Error vs Voltage

Voltage(V)	Temperature(°C)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
3.4	20	699.481	715.519	0.3	0.0004
4.35				0.53	0.0007

LTE Band 14, 10MHz bandwidth QPSK (worst case of all bandwidths)

Frequency Error vs Temperature

Temperature(°C)	Voltage(V)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
20	3.85	788.417	797.583		
50				1.49	0.0019
40				0.8	0.0010
30				0.15	0.0002
10				1.93	0.0024
0				5.92	0.0075
-10				4.13	0.0052
-20				1.39	0.0018
-30				0.23	0.0003

Frequency Error vs Voltage

Voltage(V)	Temperature(°C)	F _L (MHz)	F _H (MHz)	Offset(Hz)	Frequency error(ppm)
3.4	20	788.417	797.583	0.69	0.0009
4.35				0.53	0.0007

A.4 OCCUPIED BANDWIDTH

A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the US Cellular/PCS frequency bands. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.


The measurement method is from ANSI C63.26:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts.
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
- d) Set the detection mode to peak, and the trace mode to max-hold.

LTE band 2, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	1105.77	1089.74

LTE band 2, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:31:00

LTE band 2, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:32:25

LTE band 2, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	2708.33	2708.33

LTE band 2, 3MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:33:51

LTE band 2, 3MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:35:16

LTE band 2, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	4519.23	4519.23

LTE band 2, 5MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:36:42

LTE band 2, 5MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:38:07

LTE band 2, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	8942.31	8990.38

LTE band 2, 10MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:39:32

LTE band 2, 10MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:40:57

LTE band 2, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	13485.58	13485.58

LTE band 2, 15MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:42:24

LTE band 2, 15MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:43:49

LTE band 2, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1880.0	QPSK	16QAM
	17884.62	17884.62

LTE band 2, 20MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:45:15

LTE band 2, 20MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:46:40

LTE band 4, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	1097.76	1097.76

LTE band 4, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:48:11

LTE band 4, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:49:35

LTE band 4, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	2692.31	2692.31

LTE band 4, 3MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:51:02

LTE band 4, 3MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:52:26

LTE band 4, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	4543.27	4519.23

LTE band 4, 5MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:53:53

LTE band 4, 5MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:55:17

LTE band 4, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	8990.38	8990.38

LTE band 4, 10MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:56:44

LTE band 4, 10MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 18:58:09

LTE band 4, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	13485.58	13485.58

LTE band 4, 15MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 18:59:35

LTE band 4, 15MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:01:00

LTE band 4, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
1732.5	QPSK	16QAM
	17884.62	17884.62

LTE band 4, 20MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:02:26

LTE band 4, 20MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:03:51

LTE band 5, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
	1097.76	1097.76

LTE band 5, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:06:05

LTE band 5, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:07:30

LTE band 5, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
	2692.31	2692.31

LTE band 5, 3MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:08:57

LTE band 5, 3MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:10:21

LTE band 5, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
	4495.19	4519.23

LTE band 5, 5MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:11:48

LTE band 5, 5MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:13:13

LTE band 5, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
836.5	QPSK	16QAM
	8942.31	8990.38

LTE band 5, 10MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:14:39

LTE band 5, 10MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:16:04

LTE band 12, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
	1097.76	1097.76

LTE band 12, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:17:32

LTE band 12, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:18:56

LTE band 12, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
	2692.31	2708.33

LTE band 12, 3MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:20:23

LTE band 12, 3MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:21:48

LTE band 12, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
	4495.19	4519.23

LTE band 12, 5MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:23:14

LTE band 12, 5MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:24:39

LTE band 12, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
707.5	QPSK	16QAM
	8942.31	8942.31

LTE band 12, 10MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:26:05

LTE band 12, 10MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:27:30

LTE band 14, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
793.0	QPSK	16QAM
	4519.23	4495.19

LTE band 14, 5MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:28:58

LTE band 14, 5MHz Bandwidth, 16QAM (99% BW)




Date: 18.DEC.2019 19:30:23

LTE band 14, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%) (kHz)	
793.0	QPSK	16QAM
	8942.31	8942.31

LTE band 14, 10MHz Bandwidth, QPSK (99% BW)



Date: 18.DEC.2019 19:31:49

LTE band 14, 10MHz Bandwidth, 16QAM (99% BW)



Date: 18.DEC.2019 19:33:14

A.5 EMISSION BANDWIDTH

A.5.1 Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.


The measurement method is from ANSI C63.26:

- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be wide enough to see sufficient roll off of the signal to make the measurement.
- The nominal RBW shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times \text{RBW}$.
- Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
- The dynamic range of the spectrum analyzer at the selected RBW shall be more than 10 dB below the target “-X dB” requirement, i.e., if the requirement calls for measuring the -26 dB OBW, the spectrum analyzer noise floor at the selected RBW shall be at least 36 dB below the reference level.
- Set spectrum analyzer detection mode to peak, and the trace mode to max hold.

LTE band 2, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	1322.12	1322.12

LTE band 2, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 19:35:15

LTE band 2, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 19:36:40

LTE band 2, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	2964.74	2980.77

LTE band 2, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 19:38:06

LTE band 2, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 19:39:31

LTE band 2, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	4975.96	5024.04

LTE band 2, 5MHz Bandwidth, QPSK (-26dB BW)



Date: 18.DEC.2019 19:40:58

LTE band 2, 5MHz Bandwidth, 16QAM (-26dB BW)




Date: 18.DEC.2019 19:42:24

LTE band 2, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	9855.77	9807.69

LTE band 2, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 19:43:50

LTE band 2, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 19:45:15

LTE band 2, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	14783.65	14711.54

LTE band 2, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 19:46:42

LTE band 2, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 19:48:07

LTE band 2, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1880.0	QPSK	16QAM
	19230.77	19326.92

LTE band 2, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 19:49:34

LTE band 2, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 19:50:59

LTE band 4, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
	QPSK	16QAM
1732.5	1322.12	1314.10

LTE band 4, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 19:52:31

LTE band 4, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 19:53:56

LTE band 4, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
	2964.74	2980.77

LTE band 4, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 19:55:23

LTE band 4, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 19:56:48

LTE band 4, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
	5000.00	5000.00

LTE band 4, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 19:58:14

LTE band 4, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 19:59:40

LTE band 4, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
	9903.85	9807.69

LTE band 4, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:01:06

LTE band 4, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:02:31

LTE band 4, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
	14783.65	14711.54

LTE band 4, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:03:58

LTE band 4, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:05:24

LTE band 4, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
1732.5	QPSK	16QAM
	19423.08	19326.92

LTE band 4, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:06:50

LTE band 4, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:08:15

LTE band 5, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
	1306.09	1306.09

LTE band 5, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:10:30

LTE band 5, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:11:56

LTE band 5, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
	2948.72	2964.74

LTE band 5, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:13:22

LTE band 5, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:14:47

LTE band 5, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
	4927.88	4951.92

LTE band 5, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:16:14

LTE band 5, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:17:40

LTE band 5, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
836.5	QPSK	16QAM
	9855.77	9807.69

LTE band 5, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:19:06

LTE band 5, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:20:32

LTE band 12, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
	1306.09	1314.10

LTE band 12, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:22:02

LTE band 12, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:23:27

LTE band 12, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
	2980.77	2980.77

LTE band 12, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:24:54

LTE band 12, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:26:20

LTE band 12, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
	5000.00	5000.00

LTE band 12, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:27:46

LTE band 12, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:29:12

LTE band 12, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
707.5	QPSK	16QAM
	9903.85	9807.69

LTE band 12, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:30:39

LTE band 12, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:32:04

LTE band 14, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
793.0	QPSK	16QAM
	5000.00	5024.04

LTE band 14, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:33:32

LTE band 14, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 18.DEC.2019 20:34:57

LTE band 14, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc) (kHz)	
793.0	QPSK	16QAM
	9903.85	9807.69

LTE band 14, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 18.DEC.2019 20:36:24

LTE band 14, 10MHz Bandwidth, 16QAM (-26dBc BW)



Date: 18.DEC.2019 20:37:49

A.6 BAND EDGE COMPLIANCE

A.6.1 Measurement limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to KDB 971168, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following: (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB; (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB; (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.

Part 27.53(a) states for mobile and portable stations operating in the 2305–2315 MHz and 2350–2360 MHz bands: By a factor of not less than: $43 + 10 \log(P)$ dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log(P)$ dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than $61 + 10 \log(P)$

dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337MHz; By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2300 and 2305 MHz, $55 + 10 \log (P)$ dB on all frequencies between 2296 and 2300MHz, $61 + 10 \log (P)$ dB on all frequencies between 2292 and 2296 MHz, $67 + 10 \log (P)$ dB on all frequencies between 2288 and 2292 MHz, and $70 + 10 \log (P)$ dB below 2288 MHz; By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365 MHz, and not less than $70 + 10 \log (P)$ dB above 2365 MHz.


Part 90.691 states that out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows: For any frequency removed from the EA licensee’s frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz. For any frequency removed from the EA licensee’s frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

A.6.2 Measurement result

Only the worst case result is given below


LTE band 2

OBW: 1RB-low_offset




Date: 13.FEB.2020 12:12:57

LOW BAND EDGE BLOCK-1RB-low_offset




Date: 13.FEB.2020 12:15:12

OBW: 1RB-high_offset




Date: 13.FEB.2020 12:20:06

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 13.FEB.2020 12:21:45

LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 13.FEB.2020 12:17:07


HIGH BAND EDGE BLOCK-20MHz-100%RB



Date: 13.FEB.2020 12:23:39


LTE band 4

OBW: 1RB-low_offset




Date: 13.FEB.2020 12:27:15

LOW BAND EDGE BLOCK-1RB-low_offset




Date: 13.FEB.2020 12:28:54

OBW: 1RB-high_offset




Date: 13.FEB.2020 12:35:11

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 13.FEB.2020 12:36:49

LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 13.FEB.2020 12:33:24


HIGH BAND EDGE BLOCK-20MHz-100%RB



Date: 13.FEB.2020 12:38:44


LTE band 5

OBW: 1RB-low_offset




Date: 13.FEB.2020 12:45:44

LOW BAND EDGE BLOCK-1RB-low_offset




Date: 13.FEB.2020 12:47:22

OBW: 1RB-high_offset




Date: 13.FEB.2020 12:50:36

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 13.FEB.2020 12:52:14

LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 13.FEB.2020 12:49:17


HIGH BAND EDGE BLOCK-10MHz-100%RB



Date: 13.FEB.2020 12:54:06


LTE band 12

OBW: 1RB-low_offset




Date: 13.FEB.2020 13:00:09

LOW BAND EDGE BLOCK-1RB-low_offset




Date: 13.FEB.2020 13:01:47

OBW: 1RB-high_offset




Date: 13.FEB.2020 13:06:22

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 13.FEB.2020 13:08:01

LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 13.FEB.2020 13:03:41


HIGH BAND EDGE BLOCK-10MHz-100%RB



Date: 13.FEB.2020 13:09:57


LTE band 14

LOW BAND EDGE BLOCK-1RB-low_offset




Date: 20.FEB.2020 15:30:56

HIGH BAND EDGE BLOCK-1RB-high_offset




Date: 20.FEB.2020 15:26:30

LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 20.FEB.2020 15:41:35

HIGH BAND EDGE BLOCK-10MHz-100%RB



Date: 20.FEB.2020 15:44:19

A.7 CONDUCTED SPURIOUS EMISSION

A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. In measuring unwanted emissions, the spectrum shall be investigated from 30 MHz or the lowest radio frequency signal generated in the equipment, whichever is lower, without going below 9 kHz, up to at least the frequency given below:
 - (a) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
 - (b) If the equipment operates at or above 10 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
3. The number of sweep points of spectrum analyzer is set to 30001 which is greater than span/RBW.

A. 7.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 +$

10 log (P) dB;(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations.


Part 27.53(a) states for mobile and portable stations operating in the 2305–2315 MHz and 2350–2360 MHz bands: By a factor of not less than: $43 + 10 \log (P)$ dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log (P)$ dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than $61 + 10 \log (P)$ dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337MHz; By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2300 and 2305 MHz, $55 + 10 \log (P)$ dB on all frequencies between 2296 and 2300MHz, $61 + 10 \log (P)$ dB on all frequencies between 2292 and 2296 MHz, $67 + 10 \log (P)$ dB on all frequencies between 2288 and 2292 MHz, and $70 + 10 \log (P)$ dB below 2288 MHz; By a factor of not less than $43 + 10 \log (P)$ dB on all frequencies between 2360 and 2365 MHz, and not less than $70 + 10 \log (P)$ dB above 2365 MHz.

Part 90.691 states that out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:For any frequency removed from the EA licensee’s frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz. For any frequency removed from the EA licensee’s frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

A. 7.2 Measurement result


Only the worst case result is given below

LTE band 2: 30MHz – 19.1GHz




Date: 13.FEB.2020 13:12:45

LTE band 4: 30MHz – 17.55GHz




Date: 13.FEB.2020 13:13:14

LTE band 5: 30MHz – 8.49GHz




Date: 13.FEB.2020 13:14:49

LTE band 12: 30MHz – 7.16GHz




Date: 13.FEB.2020 13:15:16

LTE band 14: 30MHz – 7.98GHz




Date: 20.FEB.2020 16:40:34

LTE band 14: 769MHz – 775MHz



Date: 20.FEB.2020 16:49:35

LTE band 14: 799MHz –805MHz



Date: 20.FEB.2020 16:51:05

A.8 PEAK-TO-AVERAGE POWER RATIO

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.

- a) Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e) Record the maximum PAPR level associated with a probability of 0.1%

LTE band 2, 20MHz

Frequency(MHz)	PAPR(dB)	
1880.0	QPSK	16QAM
	6.67	7.28


LTE band 4, 20MHz

Frequency(MHz)	PAPR(dB)	
1732.5	QPSK	16QAM
	6.59	7.15

LTE band 12, 10MHz

Frequency(MHz)	PAPR(dB)	
707.5	QPSK	16QAM
	5.22	6.15

ANNEX B: Accreditation Certificate

United States Department of Commerce National Institute of Standards and Technology NVLAP[®]  ilac-MRA Certificate of Accreditation to ISO/IEC 17025:2017	
NVLAP LAB CODE: 600118-0	
Telecommunication Technology Labs, CAICT Beijing China	
<i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i>	
Electromagnetic Compatibility & Telecommunications	
<i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i>	
2020-09-29 through 2021-09-30 <i>Effective Dates</i>	 DEPARTMENT OF COMMERCE UNITED STATES OF AMERICA  For the National Voluntary Laboratory Accreditation Program

END OF REPORT