RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in § 1.1307(b)

Limits for Maximum Permissible Exposure(MPE)

Frequency	Electric Field	Magnetic Field	Power	Average				
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm ²)	Time				
(A) Limits for Occupational/Control Exposures								
300-1500		F/300		6				
1500-100000			5	6				
(B) Limits for General Population/Uncontrol Exposures								
300-1500		F/1500		6				
1500-100000			1	30				

11.1 Friis transmission formula: Pd=(Pout*G)\(4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= gain of antenna in linear scale

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

. Antenna gain: 1 dBi

Channel	Channel	Output	Output	Antenna	Power density	Power density
	Frequency	Peak power	Peak power	Gain (dBi)	at 20cm	Limits
	(MHz)	(dBm)	(mW)		(mW/cm^2)	(mW/cm^2)
1	2402.00	12.98	19.86	1	0.0049	1
6	2440.00	13.08	20.32	1	0.0050	1
11	2480.00	12.87	19.36	1	0.0048	1