

TEST REPORT

Applicant: Shenzhen Xinguodu Technology Co., Ltd.

Address: 17B JinSong Mansion, Terra Industrial & Trade Park
Chegongmiao, Futian District, Shenzhen, Guangdong, China.

Product Name: POS terminal


FCC ID: XDQCT20-02

Standard(s): 47 CFR Part 15, Subpart E(15.407)
ANSI C63.10-2013
KDB 789033 D02 General U-NII Test Procedures New Rules
v02r01

Report Number: 2402T77670E-RF-00D


Report Date: 2024/6/21

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).



Reviewed By: Gavin Xu

Title: RF Engineer



Approved By: Ivan Cao

Title: EMC Manager

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL ▲	6
1.4 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	8
3.1 OPERATION FREQUENCY DETAIL	8
3.2 EUT OPERATION CONDITION	9
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	11
3.4 SUPPORT CABLE LIST AND DETAILS	11
3.5 BLOCK DIAGRAM OF TEST SETUP	12
3.6 TEST FACILITY	13
3.7 MEASUREMENT UNCERTAINTY	13
4. REQUIREMENTS AND TEST PROCEDURES	14
4.1 AC LINE CONDUCTED EMISSIONS	14
4.1.1 Applicable Standard	14
4.1.2 EUT Setup	15
4.1.3 EMI Test Receiver Setup	15
4.1.4 Test Procedure	16
4.1.5 Corrected Amplitude & Margin Calculation	16
4.1.6 Test Result	16
4.2 RADIATION SPURIOUS EMISSIONS	17
4.2.1 Applicable Standard	17
4.2.2 EUT Setup	18
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	19
4.2.4 Test Procedure	20
4.2.5 Corrected Result & Margin Calculation	20
4.2.6 Test Result	20
4.3 EMISSION BANDWIDTH	21
4.3.1 Applicable Standard	21
4.3.2 EUT Setup	21
4.3.3 Test Procedure	21
4.3.4 Test Result	22
4.4 MAXIMUM CONDUCTED OUTPUT POWER	23
4.4.1 Applicable Standard	23
4.4.2 EUT Setup	23
4.4.3 Test Procedure	23
4.4.4 Test Result	23
4.5 MAXIMUM POWER SPECTRAL DENSITY	24
4.5.1 Applicable Standard	24

4.5.2 EUT Setup	24
4.5.3 Test Procedure	24
4.5.4 Test Result	25
4.6 DUTY CYCLE	26
4.6.1 EUT Setup	26
4.6.2 Test Procedure	26
4.6.3 Judgment	26
4.7 ANTENNA REQUIREMENT	27
4.7.1 Applicable Standard	27
4.7.2 Judgment	27
5. Test DATA AND RESULTS	28
5.1 AC LINE CONDUCTED EMISSIONS	28
5.2 RADIATION SPURIOUS EMISSIONS	31
5.3 EMISSION BANDWIDTH	53
5.4 99% OCCUPIED BANDWIDTH	63
5.5 MAXIMUM CONDUCTED OUTPUT POWER	73
5.6 POWER SPECTRAL DENSITY	76
5.7 DUTY CYCLE	86
APPENDIX A - EUT PHOTOGRAPHS	88
APPENDIX B - TEST SETUP PHOTOGRAPHS	89

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402T77670E-RF-00D	Original Report	2024/6/21

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	POS Terminal
EUT Model:	CT20
Operation Frequency:	5150-5250MHz: 5180-5240 MHz(802.11a/n ht20/ac vht20) 5190-5230 MHz(802.11n ht40/ac vht40) 5210 MHz(802.11ac vht80) 5250-5350MHz: 5260-5320 MHz (802.11a/n ht20/ac vht20) 5270-5310 MHz(802.11n ht40/ac vht40) 5290 MHz(802.11ac vht80) 5470-5725MHz: 5500-5720 MHz (802.11a/n ht20/ac vht20) 5510-5710 MHz(802.11n ht40/vht40) 5530-5690MHz(802.11ac vht80) 5725-5850MHz: 5745-5825 MHz (802.11a/n ht20/ac vht20) 5755-5795 MHz(802.11n ht40/ac vht40) 5775 MHz(802.11ac vht80)
Maximum Average Conducted Output Power:	14.56dBm(5150-5250MHz) 14.58dBm(5250-5350MHz) 14.76dBm(5470-5725MHz) 14.54dBm(5725-5850MHz)
Modulation Type:	802.11a/n/ac: OFDM-BPSK, QPSK, 16QAM, 64QAM,256QAM
Rated Input Voltage:	DC 9.0V from Adapter
Serial Number:	AC Line Conducted Emissions and Radiated Spurious Emission:2LXK-1 RF Conducted:2LT9-5
EUT Received Date:	2024/5/23
EUT Received Status:	Good

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
Adapter	Jiangxi Jian Aohai Technology Co.,Ltd.	A931-090200W-M2	Input: 100-240Vac 50/60Hz 1.2A Output: 9.0Vdc 2.0A 18.0W

1.3 Antenna Information Detail ▲

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Sunnyway Technology (China)Co., Ltd.	FPC	50	5.15~5.25GHz	2.02dBi
			5.25~5.35 GHz	1.83dBi
			5.47~5.725 GHz	2.93dBi
			5.725~5.85 GHz	1.97dBi
The design of compliance with §15.203: ☒ Unit uses a permanently attached antenna. ☐ Unit uses a unique coupling to the intentional radiator. ☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.203	Antenna Requirement	Compliant
FCC §15.207(a)	AC Line Conducted Emissions	Compliant
FCC §15.207(a)	Radiated Spurious Emissions	Compliant
FCC§15.407(a) (e)	Emission Bandwidth	Compliant
FCC§15.407 (a)	Maximum Conducted Output Power	Compliant
FCC§15.407 (a)	Power Spectral Density	Compliant
C63.10 §11.6	Duty Cycle	Compliant
Note 1: For AC line conducted emissions, the maximum output power mode and channel was tested. Note 2: For Radiated Spurious Emissions 9kHz~ 1GHz, the maximum output power mode and channel was tested.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For 802.11a/n ht20/ac vht20:

5150-5250MHz Band		5250-5350 MHz Band		5470-5725 MHz Band		5725-5850MHz Band	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	52	5260	100	5500	149	5745
40	5200	56	5280	104	5520	153	5765
44	5220	60	5300	108	5540	157	5785
48	5240	64	5320	112	5560	161	5805
/	/	/	/	116	5580	165	5825
/	/	/	/	120	5600	/	/
/	/	/	/	124	5620	/	/
/	/	/	/	128	5640	/	/
/	/	/	/	132	5660	/	/
/	/	/	/	136	5680	/	/
/	/	/	/	140	5700	/	/
/	/	/	/	144	5720	/	/

For 802.11n ht40/ac vht40:

5150-5250MHz		5250-5350 MHz		5470-5725 MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	54	5270	102	5510	151	5755
46	5230	62	5310	110	5550	159	5795
/	/	/	/	118	5590	/	/
/	/	/	/	126	5630	/	/
/	/	/	/	134	5670	/	/
/	/	/	/	142	5710	/	/

For 802.11ac vht80:

5150-5250MHz		5250-5350 MHz		5470-5725 MHz		5725-5850MHz	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	58	5290	106	5530	155	5775
/	/	/	/	122	5610	/	/
/	/	/	/	138	5690	/	/

Note: Additional channels cross the band 5470-5725MHz and 5725-5850 MHz, Conducted output power/ Power Spectral Density/bandwidth test with the additional channel to compliance with stricter limit of the two bands(5470-5725MHz more stricter).

3.2 EUT Operation Condition

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

The EUT configuration is below:

EUT Exercise Software:		engineering mode		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:				
5150-5250 MHz Band:				
Test Modes	Test Channels	Test Frequency	Data rate	Power Level Setting
802.11a	Lowest	5180	6Mbps	18
	Middle	5200	6Mbps	18
	Highest	5240	6Mbps	18
802.11n ht20	Lowest	5180	MCS0	19
	Middle	5200	MCS0	19
	Highest	5240	MCS0	19
802.11n ht40	Lowest	5190	MCS0	18
	Highest	5230	MCS0	18
802.11ac vht80	Middle	5210	MCS0	17
5250-5350 MHz Band:				
Test Modes	Test Channels	Test Frequency	Data rate	Power Level Setting
802.11a	Lowest	5260	6Mbps	20
	Middle	5280	6Mbps	20
	Highest	5320	6Mbps	20
802.11n ht20	Lowest	5260	MCS0	20
	Middle	5280	MCS0	20
	Highest	5320	MCS0	20
802.11n ht40	Lowest	5270	MCS0	18
	Highest	5310	MCS0	18
802.11ac vht80	Middle	5290	MCS0	17

5470-5725 MHz Band:				
Test Modes	Test Channels	Test Frequency	Data rate	Power Level Setting
802.11a	Lowest	5500	6Mbps	18
	Middle	5580	6Mbps	18
	Highest	5700	6Mbps	18
	Cross	5720	6Mbps	18
802.11n ht20	Lowest	5500	MCS0	17
	Middle	5580	MCS0	17
	Highest	5700	MCS0	17
	Cross	5720	MCS0	17
802.11n ht40	Lowest	5510	MCS0	17
	Middle	5550	MCS0	17
	Highest	5670	MCS0	17
	Cross	5710	MCS0	17
802.11ac vht80	Lowest	5530	MCS0	16
	Highest	5610	MCS0	16
	Cross	5690	MCS0	16
5725-5850 MHz Band:				
Test Modes	Test Channels	Test Frequency	Data rate	Power Level Setting
802.11a	Lowest	5745	6Mbps	18
	Middle	5785	6Mbps	18
	Highest	5825	6Mbps	18
802.11n ht20	Lowest	5745	MCS0	18
	Middle	5785	MCS0	18
	Highest	5825	MCS0	18
802.11n ht40	Lowest	5755	MCS0	18
	Highest	5795	MCS0	18
802.11ac vht80	Middle	5775	MCS0	18
Note: 1.The system support 802.11a/n ht20/n ht40/ac vht20/vht40/vht80, the vht20/vht40 were reduced since the identical parameters with 802.11n ht20 and ht40. 2.The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the average power and PSD across all data rates, bandwidths, and modulations.				

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Kingston	USB Disk	32G	EMZBUD21103001
SanDisk	TF Card	UHS-I-16G	9292DVDSV0XZ
Unknown	SIM Card	Unknown	Unknown
Lenovo	Adapter	92P1109	11S92P1109Z1ZBTZ93A6YG
Lenovo	Laptop	E480	PF-1QQYYYP 19/06
ZIONCOM	Router	MB-R210-00	EMZBWR21103004
Dell	Keyboard	KB212-B	CN-0K6KPN-71616-24N-0658-A00
PHILIPS	Mouse	SPK7214	M214BQ210411115
IPro	Earphone	Phonenix 5.0s	EMZBEP21103002B
Bacl	RS232 load	RS232X7	Unknown

3.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	no	no	1.2	Adapter	EUT
DC Cable	no	no	1.2	Adapter	Laptop
RJ45 Cable	yes	no	1.2	Laptop	Router
RJ45 Cable	yes	no	1.5	EUT	Router
Signal Cable	no	no	1.2	Laptop	Keyboard
Signal Cable	no	no	1.2	Laptop	Mouse
earphone Cable	no	no	0.8	earphone	EUT
USB Cable	no	no	2.8	Laptop	EUT
RS232 cable	yes	no	1.2	EUT	RS232 load

3.5 Block Diagram of Test Setup

AC line conducted emissions:



Radiated Spurious Emission:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions

4.2.1 Applicable Standard


FCC §15.407 (b);

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating solely in the 5.725-5.850 GHz band:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (8) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (9) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in § 15.207.
- (10) The provisions of § 15.205 apply to intentional radiators operating under this section.
- (11) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency band edges as the design of the equipment permits.
- (c) The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization a description of how this requirement is met.


4.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:

The radiated emission tests were performed in the semi-anechoic chamber, using the setup accordance with the ANSI C63.10-2013. The specification used was FCC 15.209, FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W
9 kHz – 150 kHz	QP/AV	200 Hz	1 kHz	200 Hz
150 kHz – 30 MHz	QP/AV	9 kHz	30 kHz	9 kHz
30 MHz – 1000 MHz	PK	100 kHz	300 kHz	/
	QP	/	/	120 kHz

1GHz- 40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	$\geq 1/T$

Note: T is minimum transmission duration

If the maximized peak measured value is under the QP limit by more than 6dB, then it is unnecessary to perform an QP measurement.

If the maximized peak measured value is under the average limit, then it is unnecessary to perform an QP measurement.

4.2.4 Test Procedure

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz -1 GHz, except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, emission shall be computed as: $E [dB\mu V/m] = EIRP[dBm] + 95.2$, for $d = 3$ meters.

For Radiated Bandedge test, which was performed at 1.5 m distance, according to C63.10, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m

Distance extrapolation Factor = $20 \log (\text{specific distance } [3m] / \text{test distance } [1.5m])$ dB = 6.0 dB

4.2.5 Corrected Result & Margin Calculation

The basic equation except radiated bandedge test is as follows:

Factor = Antenna Factor + Cable Loss- Amplifier Gain

Result = Reading + Factor

For Radiated Bandedge test:

Factor = Antenna Factor + Cable Loss-Distance extrapolation Factor

Result = Reading + Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.2.6 Test Result

Please refer to section 5.2.

4.3 Emission Bandwidth

4.3.1 Applicable Standard


FCC §15.407 (a),(h)

(h)(2) Radar Detection Function of Dynamic Frequency Selection (DFS). U-NII devices operating with any part of its 26 dB emission bandwidth in the 5.25-5.35 GHz and 5.47-5.725 GHz bands shall employ a DFS radar detection mechanism to detect the presence of radar systems and to avoid co-channel operation with radar systems.

FCC §15.407 (e)

Within the 5.725-5.850 GHz and 5.850-5.895 GHz bands, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer.

4.3.3 Test Procedure

26dB Emission Bandwidth:

According to ANSI C63.10-2013 Section 12.4.1

- Set RBW = approximately 1% of the emission bandwidth.
- Set the VBW > RBW.
- Detector = peak.
- Trace mode = max hold
- Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6 dB emission bandwidth:

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) ≥ 3 RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described in this section. For devices that use channel aggregation refer to III.A and III.C for determining emission bandwidth.

99% Occupied Bandwidth:

According to ANSI C63.10-2013 Section 12.4.2&6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

4.3.4 Test Result

Please refer to section 5.3 and section 5.4.

4.4 Maximum Conducted Output Power

4.4.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15 – 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

4.4.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The cable loss of this RF cable was offset into the setting of test equipment, which was provided by manufacturer ▲.

4.4.3 Test Procedure

According to ANSI C63.10-2013 Section 12.3.3.1

Method PM-G is measurement using a gated RF average power meter.

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.4.4 Test Result

Please refer to section 5.5.

4.5 Maximum Power Spectral Density

4.5.1 Applicable Standard

FCC §15.407(a) (1)(iv)

For client devices in the 5.15 – 5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


FCC §15.407(a) (2)

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC §15.407(a) (3)(i)

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

4.5.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The cable loss of this RF cable was offset into the setting of test equipment, which was provided by manufacturer ▲.

4.5.3 Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01

Duty cycle $\geq 98\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-1 should be applied.

Duty cycle <98%, duty cycle variations are less than $\pm 2\%$

KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-2 should be applied.

Duty cycle <98%, duty cycle variations exceed $\pm 2\%$


KDB 789033 D02 General UNII Test Procedures New Rules v02r01 Method SA-3 should be applied.

4.5.4 Test Result

Please refer to section 5.6.

4.6 Duty Cycle

4.6.1 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer.

4.6.2 Test Procedure

According to ANSI C63.10-2013 Section 12.2

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- 1) Set the center frequency of the instrument to the center frequency of the transmission.
- 2) Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- 3) Set $VBW \geq RBW$. Set detector = peak or average.
- 4) The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

4.6.3 Judgment

Report Only. Please refer to section 5.7.

4.7 Antenna Requirement

4.7.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.7.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. Test DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	2LXK-1	Test Date:	2024/5/31
Test Site:	CE	Test Mode:	Transmitting
Tester:	Wright Lai	Test Result:	Pass

Environmental Conditions:


Temperature: (°C)	25.5	Relative Humidity: (%)	65	ATM Pressure: (kPa)	100.1
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2023/10/18	2024/10/17
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2023/9/5	2024/9/4
R&S	EMI Test Receiver	ESCI	100035	2023/8/18	2024/8/17
R&S	Test Software	EMC32	V9.10.00	N/A	N/A


** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*

Project No: 2402T77670E-RF
Test Engineer: Wright Lai
Test Date: 2024-5-31
Port: L
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht40 5510MHz



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.156106	38.52	---	65.67	27.15	9.000	L1	10.8
0.161652	38.05	---	65.38	27.33	9.000	L1	10.8
0.282606	---	31.79	50.74	18.95	9.000	L1	10.8
0.289742	---	32.08	50.53	18.45	9.000	L1	10.8
0.291191	36.73	---	60.49	23.76	9.000	L1	10.8
0.301537	---	31.39	50.20	18.81	9.000	L1	10.8
0.304559	---	34.37	50.12	15.75	9.000	L1	10.8
0.309151	---	32.51	49.99	17.48	9.000	L1	10.8
0.326585	37.68	---	59.54	21.86	9.000	L1	10.8
0.379296	---	38.89	48.29	9.40	9.000	L1	10.8
0.381193	42.70	---	58.25	15.55	9.000	L1	10.8
0.470023	28.25	---	56.51	28.26	9.000	L1	10.8

Project No: 2402T77670E-RF
Test Engineer: Wright Lai
Test Date: 2024-5-31
Port: N
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht40 5510MHz



Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Limit (dB μ V)	Margin (dB)	Bandwidth (kHz)	Line	Corr. (dB)
0.158459	38.10	---	65.54	27.44	9.000	N	10.9
0.188682	35.45	---	64.09	28.64	9.000	N	10.9
0.288300	---	29.64	50.57	20.93	9.000	N	10.8
0.295580	38.04	---	60.37	22.33	9.000	N	10.8
0.298544	---	34.11	50.28	16.17	9.000	N	10.8
0.313811	---	30.58	49.87	19.29	9.000	N	10.8
0.320135	---	30.09	49.70	19.61	9.000	N	10.8
0.360843	---	39.15	48.71	9.56	9.000	N	10.8
0.377409	42.73	---	58.34	15.61	9.000	N	10.8
0.396710	---	38.09	47.92	9.83	9.000	N	10.8
0.474735	30.02	---	56.43	26.41	9.000	N	10.7
0.603146	21.39	---	56.00	34.61	9.000	N	10.7

5.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

Serial Number:	2LXK-1	Test Date:	2024/6/3
Test Site:	Chamber10m	Test Mode:	Transmitting
Tester:	Zoo Zou	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.8	Relative Humidity: (%)	65	ATM Pressure: (kPa)	100.9
----------------------	------	------------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/21	2026/10/20
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Coaxial Attenuator	779-6dB	04269	2023/9/6	2026/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2023/8/1	2024/7/31
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2023/8/1	2024/7/31
Sonoma	Amplifier	310N	185914	2023/8/1	2024/7/31
R&S	EMI Test Receiver	ESCI	100224	2023/8/18	2024/8/17
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Please refer to the below table and plots.

9kHz~30MHz

The 802.11n ht40 5510MHz was tested. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.


30MHz-1GHz

Project No: 2402T77670E-RF
Test Engineer: Zoo Zou
Test Date: 2024-6-3
Polarization: Horizontal
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht40 5510MHz



No.	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)
1	30.9700	28.10	peak	-4.31	23.79	40.00	16.21
2	162.8900	36.62	peak	-11.25	25.37	43.50	18.13
3	196.8400	36.37	peak	-11.68	24.69	43.50	18.81
4	250.1900	38.90	peak	-11.43	27.47	46.00	18.53
5	375.3200	45.83	peak	-7.89	37.94	46.00	8.06
6	500.4500	38.83	peak	-4.28	34.55	46.00	11.45

Project No: 2402T77670E-RF
Test Engineer: Zoo Zou
Test Date: 2024-6-3
Polarization: Vertical
Test Mode: Transmitting
Power Source: AC 120V/60Hz
Note: 802.11n ht40 5510MHz



No.	Frequency	Reading	Detector	Corrected	Result	Limit	Margin
	(MHz)	(dBuV)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)
1	30.0000	27.76	peak	-3.80	23.96	40.00	16.04
2	55.2200	42.97	peak	-16.79	26.18	40.00	13.82
3	116.3300	35.53	peak	-10.30	25.23	43.50	18.27
4	183.2600	37.77	peak	-12.35	25.42	43.50	18.08
5	375.3200	39.77	peak	-7.89	31.88	46.00	14.12
6	500.4500	35.65	peak	-4.28	31.37	46.00	14.63

2) 1-40GHz:

Serial Number:	2LXK-1		Test Date:	2024/6/4	
Test Site:	Chamber B		Test Mode:	Transmitting	
Tester:	Nat Zhou, Colin Yang		Test Result:	Pass	
Environmental Conditions:					
Temperature: (℃)	23.7	Relative Humidity: %	46	ATM Pressure: (kPa)	100.9
Test Equipment List and Details:					
Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-021304	2023/2/22	2026/2/21
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-011302	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004#0001	2023/11/17	2024/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001#0001	2023/12/11	2024/12/10
AH	Preamplifier	PAM-0118P	469	2023/8/19	2024/8/18
AH	Preamplifier	PAM-1840VH	191	2023/9/7	2024/9/6
R&S	Spectrum Analyzer	FSV40	101944	2023/10/18	2024/10/17
Audix	Test Software	E3	191218 (V9)	N/A	N/A
Sinoscite	Band Rejection Filter	BSF5150-5850MN	0899003	2024/2/21	2025/2/20
Mini-Circuits	High Pass Filter	VHF-6010+	31118	2023/12/1	2024/11/30

* Statement of Traceability: Bay Area Compliance Laboratories Corp.(Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

802.11a_U-NII-1

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel 5180 MHz								
5150.00	34.83	PK	H	34.76	69.59	63.59	74.00	10.41
5150.00	22.47	AV	H	34.76	57.23	51.23	54.00	2.77
5150.00	36.19	PK	V	34.76	70.95	64.95	74.00	9.05
5150.00	23.01	AV	V	34.76	57.77	51.77	54.00	2.23
10360.00	49.17	PK	H	0.33	49.50	49.50	68.20	18.70
10360.00	48.26	PK	V	0.33	48.59	48.59	68.20	19.61
15540.00	48.19	PK	H	0.60	48.79	48.79	74.00	25.21
15540.00	36.38	AV	H	0.60	36.98	36.98	54.00	17.02
15540.00	48.25	PK	V	0.60	48.85	48.85	74.00	25.15
15540.00	36.69	AV	V	0.60	37.29	37.29	54.00	16.71
Middle channel 5200 MHz								
10400.00	48.90	PK	H	0.40	49.30	49.30	68.20	18.90
10400.00	48.94	PK	V	0.40	49.34	49.34	68.20	18.86
15600.00	49.28	PK	H	0.58	49.86	49.86	74.00	24.14
15600.00	37.23	AV	H	0.58	37.81	37.81	54.00	16.19
15600.00	48.63	PK	V	0.58	49.21	49.21	74.00	24.79
15600.00	36.16	AV	V	0.58	36.74	36.74	54.00	17.26
High channel 5240 MHz								
5350.00	30.26	PK	H	35.15	65.41	59.41	74.00	14.59
5350.00	18.41	AV	H	35.15	53.56	47.56	54.00	6.44
5350.00	30.57	PK	V	35.15	65.72	59.72	74.00	14.28
5350.00	18.39	AV	V	35.15	53.54	47.54	54.00	6.46
10480.00	48.37	PK	H	0.56	48.93	48.93	68.20	19.27
10480.00	49.02	PK	V	0.56	49.58	49.58	68.20	18.62
15720.00	48.79	PK	H	0.55	49.34	49.34	74.00	24.66
15720.00	36.54	AV	H	0.55	37.09	37.09	54.00	16.91
15720.00	48.74	PK	V	0.55	49.29	49.29	74.00	24.71
15720.00	36.92	AV	V	0.55	37.47	37.47	54.00	16.53

802.11n20_U-NII-1

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5180	MHz			
5150.00	34.96	PK	H	34.76	69.72	63.72	74.00	10.28
5150.00	22.85	AV	H	34.76	57.61	51.61	54.00	2.39
5150.00	33.98	PK	V	34.76	68.74	62.74	74.00	11.26
5150.00	22.03	AV	V	34.76	56.79	50.79	54.00	3.21
10360.00	48.77	PK	H	0.33	49.10	49.10	68.20	19.10
10360.00	48.56	PK	V	0.33	48.89	48.89	68.20	19.31
15540.00	48.68	PK	H	0.60	49.28	49.28	74.00	24.72
15540.00	36.46	AV	H	0.60	37.06	37.06	54.00	16.94
15540.00	48.73	PK	V	0.60	49.33	49.33	74.00	24.67
15540.00	36.22	AV	V	0.60	36.82	36.82	54.00	17.18
Middle channel				5200	MHz			
10400.00	48.88	PK	H	0.40	49.28	49.28	68.20	18.92
10400.00	49.23	PK	V	0.40	49.63	49.63	68.20	18.57
15600.00	48.46	PK	H	0.58	49.04	49.04	74.00	24.96
15600.00	36.52	AV	H	0.58	37.10	37.10	54.00	16.90
15600.00	48.93	PK	V	0.58	49.51	49.51	74.00	24.49
15600.00	36.54	AV	V	0.58	37.12	37.12	54.00	16.88
High channel				5240	MHz			
5350.00	30.63	PK	H	35.15	65.78	59.78	74.00	14.22
5350.00	18.76	AV	H	35.15	53.91	47.91	54.00	6.09
5350.00	30.41	PK	V	35.15	65.56	59.56	74.00	14.44
5350.00	18.14	AV	V	35.15	53.29	47.29	54.00	6.71
10480.00	48.89	PK	H	0.56	49.45	49.45	68.20	18.75
10480.00	48.33	PK	V	0.56	48.89	48.89	68.20	19.31
15720.00	48.96	PK	H	0.55	49.51	49.51	74.00	24.49
15720.00	36.59	AV	H	0.55	37.14	37.14	54.00	16.86
15720.00	48.81	PK	V	0.55	49.36	49.36	74.00	24.64
15720.00	36.46	AV	V	0.55	37.01	37.01	54.00	16.99

802.11n40_U-NII-1

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5190	MHz			
5150.00	38.04	PK	H	34.76	72.80	66.80	74.00	7.20
5150.00	23.25	AV	H	34.76	58.01	52.01	54.00	1.99
5150.00	37.27	PK	V	34.76	72.03	66.03	74.00	7.97
5150.00	23.01	AV	V	34.76	57.77	51.77	54.00	2.23
10380.00	48.46	PK	H	0.37	48.83	48.83	68.20	19.37
10380.00	48.29	PK	V	0.37	48.66	48.66	68.20	19.54
15570.00	49.34	PK	H	0.59	49.93	49.93	74.00	24.07
15570.00	37.26	AV	H	0.59	37.85	37.85	54.00	16.15
15570.00	48.47	PK	V	0.59	49.06	49.06	74.00	24.94
15570.00	36.59	AV	V	0.59	37.18	37.18	54.00	16.82
High channel				5230	MHz			
5350.00	30.35	PK	H	35.15	65.50	59.50	74.00	14.50
5350.00	18.55	AV	H	35.15	53.70	47.70	54.00	6.30
5350.00	30.69	PK	V	35.15	65.84	59.84	74.00	14.16
5350.00	18.38	AV	V	35.15	53.53	47.53	54.00	6.47
10460.00	48.31	PK	H	0.51	48.82	48.82	68.20	19.38
10460.00	48.63	PK	V	0.51	49.14	49.14	68.20	19.06
15690.00	49.17	PK	H	0.56	49.73	49.73	74.00	24.27
15690.00	37.05	AV	H	0.56	37.61	37.61	54.00	16.39
15690.00	49.60	PK	V	0.56	50.16	50.16	74.00	23.84
15690.00	37.26	AV	V	0.56	37.82	37.82	54.00	16.18

802.11ac80_U-NII-1

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5210	MHz			
5150.00	37.30	PK	H	34.76	72.06	66.06	74.00	7.94
5150.00	22.35	AV	H	34.76	57.11	51.11	54.00	2.89
5150.00	35.84	PK	V	34.76	70.60	64.60	74.00	9.40
5150.00	22.61	AV	V	34.76	57.37	51.37	54.00	2.63
5350.00	30.26	PK	H	35.15	65.41	59.41	74.00	14.59
5350.00	18.57	AV	H	35.15	53.72	47.72	54.00	6.28
5350.00	30.45	PK	V	35.15	65.60	59.60	74.00	14.40
5350.00	18.21	AV	V	35.15	53.36	47.36	54.00	6.64
10420.00	48.44	PK	H	0.43	48.87	48.87	68.20	19.33
10420.00	48.26	PK	V	0.43	48.69	48.69	68.20	19.51
15630.00	48.63	PK	H	0.57	49.20	49.20	74.00	24.80
15630.00	36.48	AV	H	0.57	37.05	37.05	54.00	16.95
15630.00	49.26	PK	V	0.57	49.83	49.83	74.00	24.17
15630.00	37.15	AV	V	0.57	37.72	37.72	54.00	16.28

802.11a_U-NII-2A

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5260	MHz			
5150.00	30.35	PK	H	34.76	65.11	59.11	74.00	14.89
5150.00	18.26	AV	H	34.76	53.02	47.02	54.00	6.98
5150.00	30.78	PK	V	34.76	65.54	59.54	74.00	14.46
5150.00	18.47	AV	V	34.76	53.23	47.23	54.00	6.77
10520.00	49.17	PK	H	0.60	49.77	49.77	68.20	18.43
10520.00	48.65	PK	V	0.60	49.25	49.25	68.20	18.95
15780.00	49.50	PK	H	0.55	50.05	50.05	74.00	23.95
15780.00	37.26	AV	H	0.55	37.81	37.81	54.00	16.19
15780.00	48.86	PK	V	0.55	49.41	49.41	74.00	24.59
15780.00	36.71	AV	V	0.55	37.26	37.26	54.00	16.74
Middle channel				5280	MHz			
10560.00	48.53	PK	H	0.61	49.14	49.14	68.20	19.06
10560.00	49.11	PK	V	0.61	49.72	49.72	68.20	18.48
15840.00	48.44	PK	H	0.54	48.98	48.98	74.00	25.02
15840.00	36.19	AV	H	0.54	36.73	36.73	54.00	17.27
15840.00	48.36	PK	V	0.54	48.90	48.90	74.00	25.10
15840.00	36.29	AV	V	0.54	36.83	36.83	54.00	17.17
High channel				5320	MHz			
5350.00	38.61	PK	H	35.15	73.76	67.76	74.00	6.24
5350.00	21.79	AV	H	35.15	56.94	50.94	54.00	3.06
5350.00	39.73	PK	V	35.15	74.88	68.88	74.00	5.12
5350.00	23.01	AV	V	35.15	58.16	52.16	54.00	1.84
10640.00	48.41	PK	H	0.62	49.03	49.03	74.00	24.97
10640.00	36.29	AV	H	0.62	36.91	36.91	54.00	17.09
10640.00	48.58	PK	V	0.62	49.20	49.20	74.00	24.80
10640.00	36.44	AV	V	0.62	37.06	37.06	54.00	16.94
15960.00	48.53	PK	H	0.50	49.03	49.03	74.00	24.97
15960.00	36.23	AV	H	0.50	36.73	36.73	54.00	17.27
15960.00	48.44	PK	V	0.50	48.94	48.94	74.00	25.06
15960.00	36.39	AV	V	0.50	36.89	36.89	54.00	17.11

802.11n20_U-NII-2A

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5260	MHz			
5150.00	30.61	PK	H	34.76	65.37	59.37	74.00	14.63
5150.00	18.33	AV	H	34.76	53.09	47.09	54.00	6.91
5150.00	30.49	PK	V	34.76	65.25	59.25	74.00	14.75
5150.00	18.53	AV	V	34.76	53.29	47.29	54.00	6.71
10520.00	48.64	PK	H	0.60	49.24	49.24	68.20	18.96
10520.00	48.41	PK	V	0.60	49.01	49.01	68.20	19.19
15780.00	48.50	PK	H	0.55	49.05	49.05	74.00	24.95
15780.00	36.78	AV	H	0.55	37.33	37.33	54.00	16.67
15780.00	48.71	PK	V	0.55	49.26	49.26	74.00	24.74
15780.00	36.35	AV	V	0.55	36.90	36.90	54.00	17.10
Liddle channel				5280	MHz			
10560.00	48.63	PK	H	0.61	49.24	49.24	68.20	18.96
10560.00	48.85	PK	V	0.61	49.46	49.46	68.20	18.74
15840.00	48.37	PK	H	0.54	48.91	48.91	74.00	25.09
15840.00	36.39	AV	H	0.54	36.93	36.93	54.00	17.07
15840.00	48.35	PK	V	0.54	48.89	48.89	74.00	25.11
15840.00	36.11	AV	V	0.54	36.65	36.65	54.00	17.35
High channel				5320	MHz			
5350.00	38.79	PK	H	35.15	73.94	67.94	74.00	6.06
5350.00	22.54	AV	H	35.15	57.69	51.69	54.00	2.31
5350.00	38.91	PK	V	35.15	74.06	68.06	74.00	5.94
5350.00	22.79	AV	V	35.15	57.94	51.94	54.00	2.06
10640.00	48.26	PK	H	0.62	48.88	48.88	74.00	25.12
10640.00	36.11	AV	H	0.62	36.73	36.73	54.00	17.27
10640.00	48.43	PK	V	0.62	49.05	49.05	74.00	24.95
10640.00	36.28	AV	V	0.62	36.90	36.90	54.00	17.10
15960.00	48.79	PK	H	0.50	49.29	49.29	74.00	24.71
15960.00	36.55	AV	H	0.50	37.05	37.05	54.00	16.95
15960.00	48.73	PK	V	0.50	49.23	49.23	74.00	24.77
15960.00	36.31	AV	V	0.50	36.81	36.81	54.00	17.19

802.11n40_U-NII-2A

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5270	MHz			
5150.00	30.69	PK	H	34.76	65.45	59.45	74.00	14.55
5150.00	18.36	AV	H	34.76	53.12	47.12	54.00	6.88
5150.00	30.35	PK	V	34.76	65.11	59.11	74.00	14.89
5150.00	18.64	AV	V	34.76	53.40	47.40	54.00	6.60
10540.00	49.32	PK	H	0.59	49.91	49.91	68.20	18.29
10540.00	48.25	PK	V	0.59	48.84	48.84	68.20	19.36
15810.00	48.40	PK	H	0.54	48.94	48.94	74.00	25.06
15810.00	36.12	AV	H	0.54	36.66	36.66	54.00	17.34
15810.00	49.08	PK	V	0.54	49.62	49.62	74.00	24.38
15810.00	37.24	AV	V	0.54	37.78	37.78	54.00	16.22
High channel				5310	MHz			
5350.00	38.09	PK	H	35.15	73.24	67.24	74.00	6.76
5350.00	22.41	AV	H	35.15	57.56	51.56	54.00	2.44
5350.00	39.05	PK	V	35.15	74.20	68.20	74.00	5.80
5350.00	22.38	AV	V	35.15	57.53	51.53	54.00	2.47
10620.00	48.69	PK	H	0.62	49.31	49.31	74.00	24.69
10620.00	36.51	AV	H	0.62	37.13	37.13	54.00	16.87
10620.00	48.32	PK	V	0.62	48.94	48.94	74.00	25.06
10620.00	36.38	AV	V	0.62	37.00	37.00	54.00	17.00
15930.00	48.49	PK	H	0.51	49.00	49.00	74.00	25.00
15930.00	36.37	AV	H	0.51	36.88	36.88	54.00	17.12
15930.00	48.22	PK	V	0.51	48.73	48.73	74.00	25.27
15930.00	36.43	AV	V	0.51	36.94	36.94	54.00	17.06

802.11ac80_U-NII-2A

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5290	MHz			
5150.00	30.73	PK	H	34.76	65.49	59.49	74.00	14.51
5150.00	18.34	AV	H	34.76	53.10	47.10	54.00	6.90
5150.00	30.67	PK	V	34.76	65.43	59.43	74.00	14.57
5150.00	18.74	AV	V	34.76	53.50	47.50	54.00	6.50
5350.00	36.81	PK	H	35.15	71.96	65.96	74.00	8.04
5350.00	22.27	AV	H	35.15	57.42	51.42	54.00	2.58
5350.00	37.51	PK	V	35.15	72.66	66.66	74.00	7.34
5350.00	22.48	AV	V	35.15	57.63	51.63	54.00	2.37
10580.00	48.51	PK	H	0.61	49.12	49.12	68.20	19.08
10580.00	48.78	PK	V	0.61	49.39	49.39	68.20	18.81
15870.00	48.28	PK	H	0.53	48.81	48.81	74.00	25.19
15870.00	36.35	AV	H	0.53	36.88	36.88	54.00	17.12
15870.00	48.05	PK	V	0.53	48.58	48.58	74.00	25.42
15870.00	36.13	AV	V	0.53	36.66	36.66	54.00	17.34

802.11a_U-NII-2C

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5500	MHz			
5470.00	33.43	PK	H	35.36	68.79	62.79	68.20	5.41
5470.00	35.91	PK	V	35.36	71.27	65.27	68.20	2.93
11000.00	49.01	PK	H	0.72	49.73	49.73	74.00	24.27
11000.00	36.87	AV	H	0.72	37.59	37.59	54.00	16.41
11000.00	48.10	PK	V	0.72	48.82	48.82	74.00	25.18
11000.00	36.24	AV	V	0.72	36.96	36.96	54.00	17.04
16500.00	48.19	PK	H	1.10	49.29	49.29	68.20	18.91
16500.00	48.59	PK	V	1.10	49.69	49.69	68.20	18.51
Middle channel				5580	MHz			
11160.00	49.22	PK	H	1.00	50.22	50.22	74.00	23.78
11160.00	37.14	AV	H	1.00	38.14	38.14	54.00	15.86
11160.00	48.33	PK	V	1.00	49.33	49.33	74.00	24.67
11160.00	36.07	AV	V	1.00	37.07	37.07	54.00	16.93
16740.00	48.37	PK	H	2.42	50.79	50.79	68.20	17.41
16740.00	47.84	PK	V	2.42	50.26	50.26	68.20	17.94
High channel				5700	MHz			
5725.00	36.06	PK	H	35.81	71.87	65.87	68.20	2.33
5725.00	36.14	PK	V	35.81	71.95	65.95	68.20	2.25
11400.00	47.67	PK	H	1.40	49.07	49.07	74.00	24.93
11400.00	35.59	AV	H	1.40	36.99	36.99	54.00	17.01
11400.00	47.92	PK	V	1.40	49.32	49.32	74.00	24.68
11400.00	35.98	AV	V	1.40	37.38	37.38	54.00	16.62
17100.00	47.38	PK	H	4.00	51.38	51.38	68.20	16.82
17100.00	47.69	PK	V	4.00	51.69	51.69	68.20	16.51

802.11n20_U-NII-2C

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5500	MHz			
5470.00	34.70	PK	H	35.36	70.06	64.06	68.20	4.14
5470.00	34.94	PK	V	35.36	70.30	64.30	68.20	3.90
11000.00	48.29	PK	H	0.72	49.01	49.01	74.00	24.99
11000.00	36.11	AV	H	0.72	36.83	36.83	54.00	17.17
11000.00	48.62	PK	V	0.72	49.34	49.34	74.00	24.66
11000.00	36.37	AV	V	0.72	37.09	37.09	54.00	16.91
16500.00	48.38	PK	H	1.10	49.48	49.48	68.20	18.72
16500.00	48.50	PK	V	1.10	49.60	49.60	68.20	18.60
Middle channel				5580	MHz			
11160.00	49.08	PK	H	1.00	50.08	50.08	74.00	23.92
11160.00	36.84	AV	H	1.00	37.84	37.84	54.00	16.16
11160.00	48.55	PK	V	1.00	49.55	49.55	74.00	24.45
11160.00	36.37	AV	V	1.00	37.37	37.37	54.00	16.63
16740.00	48.13	PK	H	2.42	50.55	50.55	68.20	17.65
16740.00	47.88	PK	V	2.42	50.30	50.30	68.20	17.90
High channel				5700	MHz			
5725.00	36.11	PK	H	35.81	71.92	65.92	68.20	2.28
5725.00	36.48	PK	V	35.81	72.29	66.29	68.20	1.91
11400.00	47.26	PK	H	1.40	48.66	48.66	74.00	25.34
11400.00	35.49	AV	H	1.40	36.89	36.89	54.00	17.11
11400.00	47.27	PK	V	1.40	48.67	48.67	74.00	25.33
11400.00	35.69	AV	V	1.40	37.09	37.09	54.00	16.91
17100.00	47.53	PK	H	4.00	51.53	51.53	68.20	16.67
17100.00	47.78	PK	V	4.00	51.78	51.78	68.20	16.42

802.11n40_U-NII-2C

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5510	MHz			
5470.00	36.57	PK	H	35.36	71.93	65.93	68.20	2.27
5470.00	36.31	PK	V	35.36	71.67	65.67	68.20	2.53
11020.00	48.47	PK	H	0.75	49.22	49.22	74.00	24.78
11020.00	36.30	AV	H	0.75	37.05	37.05	54.00	16.95
11020.00	49.07	PK	V	0.75	49.82	49.82	74.00	24.18
11020.00	37.31	AV	V	0.75	38.06	38.06	54.00	15.94
16530.00	48.13	PK	H	1.27	49.40	49.40	68.20	18.80
16530.00	47.96	PK	V	1.27	49.23	49.23	68.20	18.97
Middle channel				5550	MHz			
11100.00	48.21	PK	H	0.89	49.10	49.10	74.00	24.90
11100.00	36.06	AV	H	0.89	36.95	36.95	54.00	17.05
11100.00	48.62	PK	V	0.89	49.51	49.51	74.00	24.49
11100.00	36.24	AV	V	0.89	37.13	37.13	54.00	16.87
16650.00	48.43	PK	H	1.93	50.36	50.36	68.20	17.84
16650.00	48.89	PK	V	1.93	50.82	50.82	68.20	17.38
High channel				5670	MHz			
5725.00	35.80	PK	H	35.81	71.61	65.61	68.20	2.59
5725.00	34.84	PK	V	35.81	70.65	64.65	68.20	3.55
11340.00	47.93	PK	H	1.29	49.22	49.22	74.00	24.78
11340.00	35.46	AV	H	1.29	36.75	36.75	54.00	17.25
11340.00	47.86	PK	V	1.29	49.15	49.15	74.00	24.85
11340.00	35.19	AV	V	1.29	36.48	36.48	54.00	17.52
17010.00	47.31	PK	H	3.87	51.18	51.18	68.20	17.02
17010.00	47.44	PK	V	3.87	51.31	51.31	68.20	16.89

802.11ac80_U-NII-2C

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5530	MHz			
5470.00	36.02	PK	H	35.36	71.38	65.38	68.20	2.82
5470.00	34.92	PK	V	35.36	70.28	64.28	68.20	3.92
11060.00	48.24	PK	H	0.82	49.06	49.06	74.00	24.94
11060.00	36.39	AV	H	0.82	37.21	37.21	54.00	16.79
11060.00	49.10	PK	V	0.82	49.92	49.92	74.00	24.08
11060.00	37.22	AV	V	0.82	38.04	38.04	54.00	15.96
16590.00	48.38	PK	H	1.60	49.98	49.98	68.20	18.22
16590.00	48.14	PK	V	1.60	49.74	49.74	68.20	18.46
High channel				5610	MHz			
5725.00	31.53	PK	H	35.81	67.34	61.34	68.20	6.86
5725.00	31.89	PK	V	35.81	67.70	61.70	68.20	6.50
11220.00	48.23	PK	H	1.10	49.33	49.33	74.00	24.67
11220.00	36.13	AV	H	1.10	37.23	37.23	54.00	16.77
11220.00	48.34	PK	V	1.10	49.44	49.44	74.00	24.56
11220.00	36.71	AV	V	1.10	37.81	37.81	54.00	16.19
16830.00	47.19	PK	H	2.91	50.10	50.10	68.20	18.10
16830.00	47.34	PK	V	2.91	50.25	50.25	68.20	17.95

802.11a_U-NII-3

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5745	MHz			
5725.00	40.11	PK	H	35.81	75.92	69.92	122.20	52.28
5720.00	37.28	PK	H	35.80	73.08	67.08	110.80	43.72
5700.00	30.90	PK	H	35.77	66.67	60.67	105.20	44.53
5650.00	30.41	PK	H	35.69	66.10	60.10	68.20	8.10
5725.00	41.30	PK	V	35.81	77.11	71.11	122.20	51.09
5720.00	36.21	PK	V	35.80	72.01	66.01	110.80	44.79
5700.00	31.31	PK	V	35.77	67.08	61.08	105.20	44.12
5650.00	30.45	PK	V	35.69	66.14	60.14	68.20	8.06
11490.00	46.59	PK	H	1.55	48.14	48.14	74.00	25.86
11490.00	36.26	AV	H	1.55	37.81	37.81	54.00	16.19
11490.00	46.71	PK	V	1.55	48.26	48.26	74.00	25.74
11490.00	36.38	AV	V	1.55	37.93	37.93	54.00	16.07
17235.00	46.24	PK	H	4.20	50.44	50.44	68.20	17.76
17235.00	46.78	PK	V	4.20	50.98	50.98	68.20	17.22
Middle channel				5785	MHz			
11570.00	46.35	PK	H	1.59	47.94	47.94	74.00	26.06
11570.00	36.14	AV	H	1.59	37.73	37.73	54.00	16.27
11570.00	46.61	PK	V	1.59	48.20	48.20	74.00	25.80
11570.00	36.29	AV	V	1.59	37.88	37.88	54.00	16.12
17355.00	47.48	PK	H	4.37	51.85	51.85	68.20	16.35
17355.00	47.66	PK	V	4.37	52.03	52.03	68.20	16.17
High channel				5825	MHz			
5850.00	32.99	PK	H	36.00	68.99	62.99	122.20	59.21
5855.00	30.94	PK	H	36.01	66.95	60.95	110.80	49.85
5875.00	31.71	PK	H	36.04	67.75	61.75	105.20	43.45
5925.00	31.28	PK	H	36.12	67.40	61.40	68.20	6.80
5850.00	33.99	PK	V	36.00	69.99	63.99	122.20	58.21
5855.00	31.94	PK	V	36.01	67.95	61.95	110.80	48.85
5875.00	31.51	PK	V	36.04	67.55	61.55	105.20	43.65
5925.00	31.38	PK	V	36.12	67.50	61.50	68.20	6.70
11650.00	46.25	PK	H	1.59	47.84	47.84	74.00	26.16
11650.00	36.16	AV	H	1.59	37.75	37.75	54.00	16.25
11650.00	46.51	PK	V	1.59	48.10	48.10	74.00	25.90
11650.00	36.39	AV	V	1.59	37.98	37.98	54.00	16.02
17475.00	47.58	PK	H	4.56	52.14	52.14	68.20	16.06
17475.00	48.05	PK	V	4.56	52.61	52.61	68.20	15.59

802.11n20_U-NII-3

Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5745	MHz			
5725.00	45.27	PK	H	35.81	81.08	75.08	122.20	47.12
5720.00	36.69	PK	H	35.80	72.49	66.49	110.80	44.31
5700.00	30.71	PK	H	35.77	66.48	60.48	105.20	44.72
5650.00	30.84	PK	H	35.69	66.53	60.53	68.20	7.67
5725.00	41.22	PK	V	35.81	77.03	71.03	122.20	51.17
5720.00	36.40	PK	V	35.80	72.20	66.20	110.80	44.60
5700.00	31.44	PK	V	35.77	67.21	61.21	105.20	43.99
5650.00	30.42	PK	V	35.69	66.11	60.11	68.20	8.09
11490.00	46.47	PK	H	1.55	48.02	48.02	74.00	25.98
11490.00	36.33	AV	H	1.55	37.88	37.88	54.00	16.12
11490.00	46.69	PK	V	1.55	48.24	48.24	74.00	25.76
11490.00	36.49	AV	V	1.55	38.04	38.04	54.00	15.96
17235.00	46.57	PK	H	4.20	50.77	50.77	68.20	17.43
17235.00	46.40	PK	V	4.20	50.60	50.60	68.20	17.60
Middle channel				5785	MHz			
11570.00	46.57	PK	H	1.59	48.16	48.16	74.00	25.84
11570.00	36.23	AV	H	1.59	37.82	37.82	54.00	16.18
11570.00	46.61	PK	V	1.59	48.20	48.20	74.00	25.80
11570.00	36.38	AV	V	1.59	37.97	37.97	54.00	16.03
17355.00	46.55	PK	H	4.37	50.92	50.92	68.20	17.28
17355.00	46.34	PK	V	4.37	50.71	50.71	68.20	17.49
High channel				5825	MHz			
5850.00	35.15	PK	H	36.00	71.15	65.15	122.20	57.05
5855.00	32.67	PK	H	36.01	68.68	62.68	110.80	48.12
5875.00	31.78	PK	H	36.04	67.82	61.82	105.20	43.38
5925.00	31.75	PK	H	36.12	67.87	61.87	68.20	6.33
5850.00	36.06	PK	V	36.00	72.06	66.06	122.20	56.14
5855.00	32.74	PK	V	36.01	68.75	62.75	110.80	48.05
5875.00	31.40	PK	V	36.04	67.44	61.44	105.20	43.76
5925.00	31.98	PK	V	36.12	68.10	62.10	68.20	6.10
11650.00	46.61	PK	H	1.59	48.20	48.20	74.00	25.80
11650.00	36.58	AV	H	1.59	38.17	38.17	54.00	15.83
11650.00	46.45	PK	V	1.59	48.04	48.04	74.00	25.96
11650.00	36.44	AV	V	1.59	38.03	38.03	54.00	15.97
17475.00	46.34	PK	H	4.56	50.90	50.90	68.20	17.30
17475.00	46.25	PK	V	4.56	50.81	50.81	68.20	17.39

802.11n40_U-NII-3


Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5755	MHz			
5725.00	45.01	PK	H	35.81	80.82	74.82	122.20	47.38
5720.00	43.99	PK	H	35.80	79.79	73.79	110.80	37.01
5700.00	34.08	PK	H	35.77	69.85	63.85	105.20	41.35
5650.00	30.95	PK	H	35.69	66.64	60.64	68.20	7.56
5725.00	43.37	PK	V	35.81	79.18	73.18	122.20	49.02
5720.00	42.67	PK	V	35.80	78.47	72.47	110.80	38.33
5700.00	34.38	PK	V	35.77	70.15	64.15	105.20	41.05
5650.00	30.86	PK	V	35.69	66.55	60.55	68.20	7.65
11510.00	46.16	PK	H	1.57	47.73	47.73	74.00	26.27
11510.00	36.22	AV	H	1.57	37.79	37.79	54.00	16.21
11510.00	47.23	PK	V	1.57	48.80	48.80	74.00	25.20
11510.00	36.68	AV	V	1.57	38.25	38.25	54.00	15.75
17265.00	46.38	PK	H	4.24	50.62	50.62	68.20	17.58
17265.00	47.08	PK	V	4.24	51.32	51.32	68.20	16.88
High channel				5795	MHz			
5850.00	36.21	PK	H	36.00	72.21	66.21	122.20	55.99
5855.00	32.14	PK	H	36.01	68.15	62.15	110.80	48.65
5875.00	31.57	PK	H	36.04	67.61	61.61	105.20	43.59
5925.00	31.29	PK	H	36.12	67.41	61.41	68.20	6.79
5850.00	33.78	PK	V	36.00	69.78	63.78	122.20	58.42
5855.00	31.57	PK	V	36.01	67.58	61.58	110.80	49.22
5875.00	31.36	PK	V	36.04	67.40	61.40	105.20	43.80
5925.00	31.64	PK	V	36.12	67.76	61.76	68.20	6.44
11590.00	46.60	PK	H	1.58	48.18	48.18	74.00	25.82
11590.00	36.41	AV	H	1.58	37.99	37.99	54.00	16.01
11590.00	46.58	PK	V	1.58	48.16	48.16	74.00	25.84
11590.00	36.49	AV	V	1.58	38.07	38.07	54.00	15.93
17385.00	47.04	PK	H	4.42	51.46	51.46	68.20	16.74
17385.00	48.48	PK	V	4.42	52.90	52.90	68.20	15.30

802.11ac80_U-NII-3




Frequency	Reading	Detector	Polar	Factor	Corrected Amplitude	Extrapolation result	Limit	Margin
MHz	dBμV	PK/QP/AV	H/V	dB/m	dBμV/m	dBμV/m	dBμV/m	dB
Low channel				5775	MHz			
5725.00	38.68	PK	H	35.81	74.49	68.49	122.20	53.71
5720.00	37.94	PK	H	35.80	73.74	67.74	110.80	43.06
5700.00	34.54	PK	H	35.77	70.31	64.31	105.20	40.89
5650.00	31.10	PK	H	35.69	66.79	60.79	68.20	7.41
5850.00	35.05	PK	H	36.00	71.05	65.05	122.20	57.15
5855.00	34.60	PK	H	36.01	70.61	64.61	110.80	46.19
5875.00	32.79	PK	H	36.04	68.83	62.83	105.20	42.37
5925.00	32.11	PK	H	36.12	68.23	62.23	68.20	5.97
5725.00	38.41	PK	V	35.81	74.22	68.22	122.20	53.98
5720.00	37.17	PK	V	35.80	72.97	66.97	110.80	43.83
5700.00	35.20	PK	V	35.77	70.97	64.97	105.20	40.23
5650.00	31.24	PK	V	35.69	66.93	60.93	68.20	7.27
5850.00	36.55	PK	V	36.00	72.55	66.55	122.20	55.65
5855.00	35.18	PK	V	36.01	71.19	65.19	110.80	45.61
5875.00	31.99	PK	V	36.04	68.03	62.03	105.20	43.17
5925.00	31.43	PK	V	36.12	67.55	61.55	68.20	6.65
11550.00	46.04	PK	H	1.57	47.61	47.61	74.00	26.39
11550.00	36.11	AV	H	1.57	37.68	37.68	54.00	16.32
11550.00	46.27	PK	V	1.57	47.84	47.84	74.00	26.16
11550.00	36.33	AV	V	1.57	37.90	37.90	54.00	16.10
17325.00	46.47	PK	H	4.33	50.80	50.80	68.20	17.40
17325.00	47.20	PK	V	4.33	51.53	51.53	68.20	16.67

Worst Channel Test plots:

802.11n ht40, 5795MHz, Horizontal



802.11n ht40, 5795MHz, Vertical




802.11n ht40, 5795MHz, Horizontal

Project No.: 2402T77670E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40_U-NII-3_high channel 5795MHz

Serial No.: 2LXX-1
Tester: Nat Zhou

Date: 2024-06-04




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	20645.20	47.20	5.69	52.89	74.00	21.11	Peak
2	20645.20	41.79	5.69	47.48	54.00	6.52	Average

802.11n ht40, 5795MHz, Vertical

Project No.: 2402T77670E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40_U-NII-3_high channel 5795MHz

Serial No.: 2LXX-1
Tester: Nat Zhou

Date: 2024-06-04




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	22161.60	44.76	7.70	52.46	74.00	21.54	Peak
2	22161.60	39.93	7.70	47.63	54.00	6.37	Average

Project No.: 2402T77670E-RF
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40_U-NII-3_high channel 5795MHz

Serial No.: 2LXX-1
Tester: Nat Zhou

Date: 2024-06-04




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	37899.40	44.57	17.44	62.01	68.20	6.19	Peak
2	39843.40	44.31	17.38	61.69	74.00	12.31	Peak
3	39843.40	30.18	17.38	47.56	54.00	6.44	Average

Project No.: 2402T77670E-RF
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40_U-NII-3_high channel 5795MHz

Serial No.: 2LXX-1
Tester: Nat Zhou


Date: 2024-06-04



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	37975.00	44.19	17.81	62.00	68.20	6.20	Peak
2	39873.10	44.09	17.39	61.48	74.00	12.52	Peak
3	39873.10	30.25	17.39	47.64	54.00	6.36	Average

802.11n ht40, 5795MHz, Bandedge, Horizontal


Project No.: 2402T77670E-RF
Polarization: Horizontal
Test Mode: Transmitting
Serial No.: 2LXK-1
Tester: Nat Zhou
Note: 802.11n40_U-NII-3_high channel 5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	36.21	30.00	66.21	122.20	55.99	Peak
2	5855.00	32.14	30.01	62.15	110.80	48.65	Peak
3	5875.00	31.57	30.04	61.61	105.20	43.59	Peak
4	5925.00	31.29	30.12	61.41	68.20	6.79	Peak

802.11n ht40, 5795MHz, Bandedge, Vertical

Project No.: 2402T77670E-RF
Polarization: Vertical
Test Mode: Transmitting
Serial No.: 2LXK-1
Tester: Nat Zhou
Note: 802.11n40_U-NII-3_high channel 5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5850.00	33.78	30.00	63.78	122.20	58.42	Peak
2	5855.00	31.57	30.01	61.58	110.80	49.22	Peak
3	5875.00	31.36	30.04	61.40	105.20	43.80	Peak
4	5925.00	31.64	30.12	61.76	68.20	6.44	Peak

5.3 Emission Bandwidth

Serial No.:	2LT9-5	Test Date:	2024/06/13-2024/06/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26.5-26.9	Relative Humidity: (%)	59-63	ATM Pressure: (kPa)	100.4-100.5
-------------------------------	-----------	---------------------------------------	-------	--------------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/09/10	2024/09/09

** Statement of Traceability: Bay Area Compliance Laboratories Corp. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).*

**26dB Emission Bandwidth
5.2G**

Mode	Value (MHz)
a_5180MHz_Chain 0	37.323
a_5200MHz_Chain 0	37.643
a_5240MHz_Chain 0	35.885
n20_5180MHz_Chain 0	38.902
n20_5200MHz_Chain 0	38.251
n20_5240MHz_Chain 0	35.394
n40_5190MHz_Chain 0	76.944
n40_5230MHz_Chain 0	72.072
ac80_5210MHz_Chain 0	150.591

5.3G

Mode	Value (MHz)
a_5260MHz_Chain 0	35.582
a_5280MHz_Chain 0	29.843
a_5320MHz_Chain 0	28.718
n20_5260MHz_Chain 0	32.483
n20_5280MHz_Chain 0	45.923
n20_5320MHz_Chain 0	28.029
n40_5270MHz_Chain 0	66.410
n40_5310MHz_Chain 0	70.918
ac80_5290MHz_Chain 0	148.653


5.6G

Mode	Value (MHz)
a_5500MHz_Chain 0	21.882
a_5580MHz_Chain 0	22.366
a_5700MHz_Chain 0	32.515
a_5720MHz_Chain 0	25.576
n20_5500MHz_Chain 0	21.620
n20_5580MHz_Chain 0	22.352
n20_5700MHz_Chain 0	25.725
n20_5720MHz_Chain 0	26.112
n40_5510MHz_Chain 0	57.862
n40_5550MHz_Chain 0	58.097
n40_5670MHz_Chain 0	72.765
n40_5710MHz_Chain 0	49.800
ac80_5530MHz_Chain 0	134.600
ac80_5610MHz_Chain 0	127.490
ac80_5690MHz_Chain 0	116.130

6dB Emission Bandwidth**5.8G**


Mode	Value (MHz)	Limit (MHz)	Result
a_5745MHz_Chain 0	16.500	0.5	Pass
a_5785MHz_Chain 0	16.450	0.5	Pass
a_5825MHz_Chain 0	16.450	0.5	Pass
n20_5745MHz_Chain 0	17.700	0.5	Pass
n20_5785MHz_Chain 0	17.750	0.5	Pass
n20_5825MHz_Chain 0	17.750	0.5	Pass
n40_5755MHz_Chain 0	36.400	0.5	Pass
n40_5795MHz_Chain 0	36.300	0.5	Pass
ac80_5775MHz_Chain 0	76.800	0.5	Pass

a_5180MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:39:22

a_5200MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:40:27

a_5240MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:41:33

n20_5180MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:22:47

n20_5200MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:24:12

n20_5240MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:25:33

n40_5190MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:25:26


n40_5230MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:26:19


5.3G

ac80_5210MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:57:35

a_5260MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:42:51

a_5280MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:44:11

a_5320MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:45:34

n20_5260MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:26:46

n20_5280MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:28:14

n20_5320MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:29:33

n40_5270MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:27:19

n40_5310MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:28:46


ac80_5290MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:59:10


5.6G

a_5500MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:46:49

a_5580MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:48:01

a_5700MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:49:21

a_5720MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:50:28

n20_5500MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:58:26

n20_5580MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:00:30

n20_5700MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:02:01

n20_5720MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:03:11

n40_5510MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:29:56

n40_5550MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:30:59

n40_5670MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:31:55

n40_5710MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:33:05

ac80_5530MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:00:14


ac80_5610MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:01:17


5.8G

ac80_5690MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:02:23

a_5745MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:51:32

a_5785MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:52:44

a_5825MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:53:39

n20_5745MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:04:36

n20_5785MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:05:55

n20_5825MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:07:16

n40_5755MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:34:10

n40_5795MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:34:57

ac80_5775MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:03:09

5.4 99% Occupied Bandwidth

Serial No.:	2LT9-5	Test Date:	2024/06/13-2024/06/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	/

Environmental Conditions:

Temperature: (°C):	26.5-26.9	Relative Humidity: (%)	59-63	ATM Pressure: (kPa)	100.4-100.5
-------------------------------	-----------	---------------------------------------	-------	--------------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/09/10	2024/09/09

** Statement of Traceability: Bay Area Compliance Laboratories Corp. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).*

5.2G

Mode	99% OBW (MHz)
a_5180MHz_Chain 0	17.300
a_5200MHz_Chain 0	17.400
a_5240MHz_Chain 0	17.150
n20_5180MHz_Chain 0	18.100
n20_5200MHz_Chain 0	18.200
n20_5240MHz_Chain 0	18.250
n40_5190MHz_Chain 0	36.800
n40_5230MHz_Chain 0	37.000
ac80_5210MHz_Chain 0	76.400

Note:

The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.

5.3G

Mode	99% OBW (MHz)
a_5260MHz_Chain 0	16.900
a_5280MHz_Chain 0	16.800
a_5320MHz_Chain 0	16.900
n20_5260MHz_Chain 0	17.900
n20_5280MHz_Chain 0	17.850
n20_5320MHz_Chain 0	17.850
n40_5270MHz_Chain 0	36.600
n40_5310MHz_Chain 0	36.500
ac80_5290MHz_Chain 0	76.200

5.6G

Mode	99% OBW (MHz)
a_5500MHz_Chain 0	16.600
a_5580MHz_Chain 0	16.600
a_5700MHz_Chain 0	16.750
a_5720MHz_Chain 0	16.750
n20_5500MHz_Chain 0	17.700
n20_5580MHz_Chain 0	17.700
n20_5700MHz_Chain 0	17.800
n20_5720MHz_Chain 0	17.800
n40_5510MHz_Chain 0	36.400
n40_5550MHz_Chain 0	36.300
n40_5670MHz_Chain 0	36.500
n40_5710MHz_Chain 0	36.500
ac80_5530MHz_Chain 0	75.800
ac80_5610MHz_Chain 0	76.000
ac80_5690MHz_Chain 0	75.800

5.8G


Mode	99% OBW (MHz)
a_5745MHz_Chain 0	16.700
a_5785MHz_Chain 0	16.700
a_5825MHz_Chain 0	17.100
n20_5745MHz_Chain 0	17.800
n20_5785MHz_Chain 0	17.700
n20_5825MHz_Chain 0	17.750
n40_5755MHz_Chain 0	36.300
n40_5795MHz_Chain 0	36.400
ac80_5775MHz_Chain 0	76.200

Note:


The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.

5.2G


a_5180MHz_Chain 0




a_5200MHz_Chain 0




a_5240MHz_Chain 0




n20_5180MHz_Chain 0




n20_5200MHz_Chain 0



n20_5240MHz_Chain 0




n40_5190MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:25:00


n40_5230MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:25:54


5.3G

ac80_5210MHz_Chain




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:57:07

a_5260MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:42:10

a_5280MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:43:39

a_5320MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:45:04

n20_5260MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:26:12

n20_5280MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:25:36

n20_5320MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:28:57

n40_5270MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:26:57

n40_5310MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:28:24


ac80_5290MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:58:42


5.6G

a_5500MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:46:15

a_5580MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:47:29

a_5700MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:48:19

a_5720MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:49:56

n20_5500MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:57:51

n20_5580MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:59:57

n20_5700MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:01:25

n20_5720MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:02:39

n40_5510MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:29:28

n40_5550MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:30:31

n40_5670MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:31:30

n40_5710MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:32:49

ac80_5530MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:59:45


ac80_5610MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:00:46


5.8G

ac80_5690MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:01:52

a_5745MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:51:08

a_5785MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:52:16

a_5825MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:53:20

n20_5745MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:04:12

n20_5785MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:05:25

n20_5825MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:06:55

n40_5755MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:33:57

n40_5795MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:34:43

ac80_5775MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:02:53

5.5 Maximum Conducted Output Power

Serial No.:	2LT9-5	Test Date:	2024/06/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26.5-26.9	Relative Humidity: (%)	59-63	ATM Pressure: (kPa)	100.4-100.5
------------------------------	-----------	----------------------------------	-------	-------------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Anritsu	Microwave Peak Power Sensor	MA24418A	12618	2023/09/04	2024/09/03
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM504	2024/06/07	2025/06/07

** Statement of Traceability: Bay Area Compliance Laboratories Corp. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).*

Test Data:**5.2G**

Mode	Average Output Power (dBm)	Limit (dBm)	Result
a_5180MHz_Chain 0	14.32	24.00	Pass
a_5200MHz_Chain 0	14.27	24.00	Pass
a_5240MHz_Chain 0	14.56	24.00	Pass
n20_5180MHz_Chain 0	14.33	24.00	Pass
n20_5200MHz_Chain 0	14.22	24.00	Pass
n20_5240MHz_Chain 0	14.27	24.00	Pass
n40_5190MHz_Chain 0	14.28	24.00	Pass
n40_5230MHz_Chain 0	14.46	24.00	Pass
ac80_5210MHz_Chain 0	13.42	24.00	Pass

Note: The device is a Client device.

5.3G

Mode	Average Output Power (dBm)	Limit (dBm)	Result
a_5260MHz_Chain 0	14.01	24.00	Pass
a_5280MHz_Chain 0	14.10	24.00	Pass
a_5320MHz_Chain 0	14.58	24.00	Pass
n20_5260MHz_Chain 0	14.02	24.00	Pass
n20_5280MHz_Chain 0	13.97	24.00	Pass
n20_5320MHz_Chain 0	14.49	24.00	Pass
n40_5270MHz_Chain 0	13.88	24.00	Pass
n40_5310MHz_Chain 0	14.35	24.00	Pass
ac80_5290MHz_Chain 0	13.86	24.00	Pass

5.6G

Mode	Average Output Power (dBm)	Limit (dBm)	Result
a_5500MHz_Chain 0	14.02	24.00	Pass
a_5580MHz_Chain 0	13.51	24.00	Pass
a_5700MHz_Chain 0	13.79	24.00	Pass
a_5720MHz_Chain 0	13.83	24.00	Pass
n20_5500MHz_Chain 0	13.92	24.00	Pass
n20_5580MHz_Chain 0	14.33	24.00	Pass
n20_5700MHz_Chain 0	13.81	24.00	Pass
n20_5720MHz_Chain 0	13.75	24.00	Pass
n40_5510MHz_Chain 0	14.76	24.00	Pass
n40_5550MHz_Chain 0	14.56	24.00	Pass
n40_5670MHz_Chain 0	14.00	24.00	Pass
n40_5710MHz_Chain 0	13.80	24.00	Pass
ac80_5530MHz_Chain 0	14.39	24.00	Pass
ac80_5610MHz_Chain 0	14.18	24.00	Pass
ac80_5690MHz_Chain 0	13.59	24.00	Pass

5.8G

Mode	Average Output Power (dBm)	Limit (dBm)	Result
a_5745MHz_Chain 0	13.81	30.00	Pass
a_5785MHz_Chain 0	13.86	30.00	Pass
a_5825MHz_Chain 0	13.82	30.00	Pass
n20_5745MHz_Chain 0	13.71	30.00	Pass
n20_5785MHz_Chain 0	13.73	30.00	Pass
n20_5825MHz_Chain 0	13.70	30.00	Pass
n40_5755MHz_Chain 0	13.77	30.00	Pass
n40_5795MHz_Chain 0	13.66	30.00	Pass
ac80_5775MHz_Chain 0	14.54	30.00	Pass

5.6 Power Spectral Density

Serial No.:	2LT9-5	Test Date:	2024/06/13-2024/06/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	26.5-26.9	Relative Humidity: (%)	59-63	ATM Pressure: (kPa)	100.4-100.5
-------------------------------	-----------	---------------------------------------	-------	--------------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/09/10	2024/09/09

** Statement of Traceability: Bay Area Compliance Laboratories Corp. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).*

5.2G

Mode	Value (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5180MHz_Chain 0	5.08	0.00	5.08	11.00	Pass
a_5200MHz_Chain 0	5.16	0.00	5.16	11.00	Pass
a_5240MHz_Chain 0	5.45	0.00	5.45	11.00	Pass
n20_5180MHz_Chain 0	4.44	0.00	4.44	11.00	Pass
n20_5200MHz_Chain 0	4.67	0.00	4.67	11.00	Pass
n20_5240MHz_Chain 0	4.96	0.00	4.96	11.00	Pass
n40_5190MHz_Chain 0	1.60	0.00	1.60	11.00	Pass
n40_5230MHz_Chain 0	1.42	0.00	1.42	11.00	Pass
ac80_5210MHz_Chain 0	-2.71	0.00	-2.71	11.00	Pass

Note: The device is a Client device.

5.3G

Mode	Value (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5260MHz_Chain 0	5.07	0.00	5.07	11.00	Pass
a_5280MHz_Chain 0	5.04	0.00	5.04	11.00	Pass
a_5320MHz_Chain 0	5.43	0.00	5.43	11.00	Pass
n20_5260MHz_Chain 0	4.49	0.00	4.49	11.00	Pass
n20_5280MHz_Chain 0	4.98	0.00	4.98	11.00	Pass
n20_5320MHz_Chain 0	5.15	0.00	5.15	11.00	Pass
n40_5270MHz_Chain 0	1.28	0.00	1.28	11.00	Pass
n40_5310MHz_Chain 0	0.57	0.00	0.57	11.00	Pass
ac80_5290MHz_Chain 0	-1.94	0.00	-1.94	11.00	Pass

5.6G


Mode	Value (dBm/MHz)	Duty Cycle Factor (dB)	PSD (dBm/MHz)	Limit (dBm/MHz)	Result
a_5500MHz_Chain 0	4.70	0.00	4.70	11.00	Pass
a_5580MHz_Chain 0	4.30	0.00	4.30	11.00	Pass
a_5700MHz_Chain 0	4.73	0.00	4.73	11.00	Pass
a_5720MHz_Chain 0	4.62	0.00	4.62	11.00	Pass
n20_5500MHz_Chain 0	4.42	0.00	4.42	11.00	Pass
n20_5580MHz_Chain 0	6.43	0.00	6.43	11.00	Pass
n20_5700MHz_Chain 0	4.16	0.00	4.16	11.00	Pass
n20_5720MHz_Chain 0	4.32	0.00	4.32	11.00	Pass
n40_5510MHz_Chain 0	1.65	0.00	1.65	11.00	Pass
n40_5550MHz_Chain 0	1.38	0.00	1.38	11.00	Pass
n40_5670MHz_Chain 0	0.86	0.00	0.86	11.00	Pass
n40_5710MHz_Chain 0	0.67	0.00	0.67	11.00	Pass
ac80_5530MHz_Chain 0	-1.92	0.00	-1.92	11.00	Pass
ac80_5610MHz_Chain 0	-2.07	0.00	-2.07	11.00	Pass
ac80_5690MHz_Chain 0	-2.69	0.00	-2.69	11.00	Pass

5.8G

Mode	Value (dBm/500kHz)	Duty Cycle Factor (dB)	PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
a_5745MHz_Chain 0	2.19	0.00	2.19	30	Pass
a_5785MHz_Chain 0	1.80	0.00	1.80	30	Pass
a_5825MHz_Chain 0	1.91	0.00	1.91	30	Pass
n20_5745MHz_Chain 0	1.66	0.00	1.66	30	Pass
n20_5785MHz_Chain 0	1.67	0.00	1.67	30	Pass
n20_5825MHz_Chain 0	1.80	0.00	1.80	30	Pass
n40_5755MHz_Chain 0	-1.95	0.00	-1.95	30	Pass
n40_5795MHz_Chain 0	-1.93	0.00	-1.93	30	Pass
ac80_5775MHz_Chain 0	-4.32	0.00	-4.32	30	Pass


5.2G

a_5180MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:20:29

a_5200MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:12:13

a_5240MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:12:43

n20_5180MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:21:06

n20_5200MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:23:59

n20_5240MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:24:24

n40_5190MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:21:46


n40_5230MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:50:23


5.3G

ac80_5210MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:12:54

a_5260MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:13:11

a_5280MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:13:37

a_5320MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:14:12

n20_5260MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:24:55

n20_5280MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:25:20

n20_5320MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:25:44

n40_5270MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:50:52

n40_5310MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:51:38


ac80_5290MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:13:18


5.6G

a_5500MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:14:37

a_5580MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:15:13

a_5700MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:15:53

a_5720MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 18:16:23

n20_5500MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:26:10

n20_5580MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:26:33

n20_5700MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:26:57

n20_5720MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:27:23

n40_5510MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:52:12

n40_5550MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:53:09

n40_5670MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:53:38

n40_5710MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:54:02

ac80_5530MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:13:42


ac80_5610MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:14:08


5.8G

ac80_5690MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:14:43

a_5745MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:16:53

a_5785MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:17:25

a_5825MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:18:00

n20_5745MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:27:48

n20_5785MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:28:18

n20_5825MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:28:59

n40_5755MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:54:38

n40_5795MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:55:09

ac80_5775MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:15:11

5.7 Duty Cycle

Serial No.:	2LT9-5	Test Date:	2024/06/13-2024/06/14
Test Site:	RF	Test Mode:	Transmitting
Tester:	Roy Xiao	Test Result:	/

Environmental Conditions:

Temperature: (°C):	26.5-26.9	Relative Humidity: (%)	59-63	ATM Pressure: (kPa)	100.4-100.5
------------------------------	-----------	----------------------------------	-------	-------------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2023/10/18	2024/10/17
Eastsheep	Coaxial Attenuator	5W-N-JK-6G-10dB	F-08-EM488	2023/09/10	2024/09/09

* Statement of Traceability: Bay Area Compliance Laboratories Corp. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


Test Data:
5.2G

Mode	Ton (ms)	Ton+Toff (ms)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/T (Hz)	VBW Setting (kHz)
a_5200MHz_Chain 0	100.000	100.000	100.00	0.00	/	0.010
n20_5200MHz_Chain 0	100.000	100.000	100.00	0.00	/	0.010
n40_5190MHz_Chain 0	100.000	100.000	100.00	0.00	/	0.010
ac80_5210MHz_Chain 0	100.000	100.000	100.00	0.00	/	0.010

Duty Cycle = Ton/(Ton+Toff)*100%


5.2G

a_5200MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 17:55:03

n20_5200MHz_Chain 0




ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 13.JUN.2024 19:10:35

n40_5190MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 09:35:58

ac80_5210MHz_Chain 0



ProjectNo.:2402T77670E-RF Tester:Roy Xiao
Date: 14.JUN.2024 10:04:14

APPENDIX A - EUT PHOTOGRAPHS

Please refer to the attachment 2402T77670E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2402T77670E-RF-INP EUT INTERNAL PHOTOGRAPHS.

APPENDIX B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2402T77670E-RF-00D-TSP TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******