

Test Report

Report No.: MTi160413E002

Date of issue: Jul. 16, 2016

Sample Description: Wireless POS Terminal

Model(s): G3

Applicant: Shenzhen Xinguodu Technology Co., Ltd.

Address: 17/A, Jinsong Building Tairan Industry And Trading

Garden Shenzhen China

Date of Test: Jun. 04, 2016 to Jul. 14, 2016



This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel:(86-755)88850135 Fax: (86-755) 88850136 http://www.mtitest.com E-mail:mti@51mti.com
Address: No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China



- Page 2 of 16 -

Report No.: MTi160413E002

Table of Contents

| 1 G | eneral description | 5 |
|------|---------------------------------------|----|
| | Feature of equipment under test (EUT) | |
| | Test mode | |
| 1.3 | Test conditions | 5 |
| 1.4 | EUT test setup | 5 |
| | Ancillary equipment | |
| | Measurement Uncertainty | |
| 2 Te | esting Site | 7 |
| 3 Li | st of test equipment | 8 |
| 4 EN | MC emission test | 9 |
| 4.1 | Conducted emission | 9 |
| 4.2 | Radiated emission | 12 |



- Page 3 of 16 - Report No.: MTi160413E002

| Test result certification | | | | |
|---|--|--|--|--|
| | | | | |
| Applicant's name: | Shenzhen Xinguodu Technology Co., Ltd. | | | |
| Address: | 17/A, Jinsong Building Tairan Industry And Trading Garden Shenzhen China | | | |
| Manufacture's Name: | Shenzhen Xinguodu Technology Co., Ltd. | | | |
| Address: 17/A, Jinsong Building Tairan Industry And Trading Garder Shenzhen China | | | | |
| Product description | | | | |
| Product name: | Wireless POS Terminal | | | |
| Trademark: | NEXGO | | | |
| Model name: | G3 | | | |
| Standards: | FCC Part 15 Subpart B | | | |
| Test Method: | ANSI C63.4-2014 | | | |

This device described above has been tested by Shenzhen Microtest Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

| Tested by: | David Chen | | |
|----------------------------|------------|---------------|--|
| | David Chen | Jul. 16, 2016 | |
| Reviewed by: | (en che | Y | |
| | Leon Chen | Jul. 16, 2016 | |
| Approved by: Approved by: | | iu. | |
| | Ares Liu | Jul. 16, 2016 | |



- Page 4 of 16 - Report No.: MTi160413E002

Summary of Test Result

| Item | Item Description of Test | |
|----------------|--------------------------|------|
| FCC Part 15 Su | | |
| 1 | Conducted emission | Pass |
| 2 | Radiated emission | Pass |



- Page 5 of 16 - Report No.: MTi160413E002

1 General description

1.1 Feature of equipment under test (EUT)

| Product name: | Wireless POS Terminal | |
|----------------------|--|--|
| Model name: | G3 | |
| Power supply: | DC 7.4V form Polymer-Li-ion battery | |
| Adapter information: | Model: HKA02108525-8A Input: 100-240V~0.8A 50/60Hz Output: 8.5V 2.5A | |

1.2 Test mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Test mode | Description |
|-----------|-----------------------|
| Mode 1 | Communication with PC |

NOTE: The test modes were carried out for all operation modes. The final test mode of the EUT was the worst test mode for EMI, and its test data was showed.

1.3 Test conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 20°C~30°CHumidity: 30%~70%

- Atmospheric pressure: 98kPa~101kPa

1.4 EUT test setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.5 Ancillary equipment

| Equipment | Model | S/N | Manufacturer |
|------------------------|------------------------|----------------------------------|--------------|
| Display | Display U2879VF | | AOC |
| PC computer VOSTRO3900 | | 18006239306 | Dell |
| Printer | HPLASERJET1020 PLUS | CNCGC60435 | HP |
| Keyboard SK-8120 | | CN-ODJ365-71616- 571-1ROV-AOO | DELL |
| Mouse | MS111-7 | CN-OKW2YH-7161 6-58R-17BA | DELL |



- Page 6 of 16 - Report No.: MTi160413E002

1.6 Measurement Uncertainty

Measurement Uncertainty for a Level of Confidence of 95 %, U=2xUc(y)

| Conducted emission(150kHz~30MHz) | ± 2.5 dB |
|----------------------------------|-----------|
| Radiated emission(30MHz~1GHz) | ± 4.2 dB |
| Radiated emission (above 1GHz) | ± 4.3 dB |
| Temperature | ±1 degree |
| Humidity | ± 5 % |



- Page 7 of 16 - Report No.: MTi160413E002

2 Testing Site

| Test Site | Shenzhen Microtest Co., Ltd. | | |
|------------------------|--|--|--|
| Test Site Location | No.102A & 302A, East Block, Hengfang Industrial Park, Xingye Road, Xixiang, Bao'an District, Shenzhen, Guangdong, China | | |
| Telephone: | (86-755)88850135 | | |
| Fax: | (86-755)88850136 | | |
| CNAS Registration No.: | CNAS L5868 | | |



- Page 8 of 16 - Report No.: MTi160413E002

3 List of test equipment

For AC power line conducted emission:

| Equipment | Manufacturer | Model | Serial No. | Calibration Due |
|-------------------|--------------|------------|------------|-----------------|
| LISN | R&S | ENV216 | 101313 | 2016.12.06 |
| LISN | SCHWARZBECK | NNLK 8129 | 8129245 | 2016.12.25 |
| Pulse Limiter | SCHWARZBECK | VTSD 9561F | 9716 | 2016.12.25 |
| Test Cable | N/A | N/A | C01 | 2016.12.06 |
| EMI Test Receiver | R&S | ESCI | 101160 | 2016.12.06 |

For Radiated emission:

| Equipment | Manufacturer | Model | Serial No. | Calibration Due |
|-------------------------|---------------------|-------------|------------|-----------------|
| Log-Bicon Antenna | MESS-ELEKTRO NIK | VULB 9160 | 3058 | 2016.12.11 |
| Horn Antenna | Schwarzbeck | BBHA 9120D | 631 | 2016.12.05 |
| Horn Antenna | Schwarzbeck | BBHA 9170 | 373 | 2016.12.05 |
| Test Cable | United Microwave | 57793 | 1m | 2016.12.05 |
| Test Cable | United Microwave | A30A30-5006 | 10m | 2016.12.05 |
| Microwave Pre_amplifier | Agilent | 8449B | 3008A01714 | 2016.12.05 |
| Pre-Amplifier | Anritsu | MH648A | M09961 | 2016.12.05 |
| EMI Test Receiver | R&S | ESPI-7 | 101318 | 2016.12.05 |
| Spctrum analyzer | Agient | E4470B | MY41441082 | 2017.06.01 |

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).



- Page 9 of 16 - Report No.: MTi160413E002

4 EMC emission test

4.1 Conducted emission

4.1.1 Limits

| Frequency | Class A | (dBµV) | Class B | (dBµV) |
|-----------|------------|---------|------------|-----------|
| (MHz) | Quasi-peak | Average | Quasi-peak | Average |
| 0.15 -0.5 | 79 | 66 | 66 - 56 * | 56 - 46 * |
| 0.5 -5 | 73 | 60 | 56 | 46 |
| 5 -30 | 73 | 60 | 60 | 50 |

Note 1: the tighter limit applies at the band edges.

Note 2: the limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

4.1.2 Test Procedures

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.


Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN is at least 80 cm from nearest part of EUT chassis.

For the actual test configuration, please refer to the related Item – photographs of the test setup.

4.1.3 Test Setup




4.1.4 Test Result



- Page 10 of 16 -

Report No.: MTi160413E002

| Temperature: | 22 ℃ | Relative Humidity: | 51% |
|---------------|--------------|--------------------|--------|
| Pressure: | 101kPa | Phase: | L |
| Test voltage: | AC 120V/60Hz | Test mode: | Mode 1 |




| 1 18.2075 4.72 30.09 34.81 60.00 -25.19 QP 2 18.2075 -3.42 30.09 26.67 50.00 -23.33 AVG |
|--|
| 2 19 2075 2 42 20 00 26 67 50 00 23 23 AV/C |
| 2 16.2075 -5.42 50.09 20.07 50.00 -25.55 AVG |



- Page 11 of 16 -

Report No.: MTi160413E002

| Temperature: | 22 ℃ | Relative Humidity: | 51% |
|---------------|--------------|--------------------|--------|
| Pressure: | 101kPa | Phase: | N |
| Test voltage: | AC 120V/60Hz | Test mode: | Mode 1 |



| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure- ment | Limit | Over | | |
|-----|-----|--------|------------------|-------------------|------------------|-------|--------|----------|---------|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | Detector | Comment |
| 1 | | 0.1728 | 6.10 | 30.02 | 36.12 | 64.82 | -28.70 | QP | |
| 2 | | 0.1728 | -1.68 | 30.02 | 28.34 | 54.82 | -26.48 | AVG | |
| 3 | | 0.4599 | 5.72 | 30.02 | 35.74 | 56.69 | -20.95 | QP | |
| 4 | * | 0.4599 | -2.04 | 30.02 | 27.98 | 46.69 | -18.71 | AVG | |
| 5 | | 0.5893 | -0.07 | 30.02 | 29.95 | 56.00 | -26.05 | QP | |
| 6 | | 0.5893 | -3.90 | 30.02 | 26.12 | 46.00 | -19.88 | AVG | |
| 7 | | 1.1787 | -0.77 | 30.02 | 29.25 | 56.00 | -26.75 | QP | |
| 8 | | 1.1787 | -4.14 | 30.02 | 25.88 | 46.00 | -20.12 | AVG | |
| 9 | | 2.2726 | -0.43 | 30.03 | 29.60 | 56.00 | -26.40 | QP | |
| 10 | | 2.2726 | -5.30 | 30.03 | 24.73 | 46.00 | -21.27 | AVG | |
| 11 | | 4.4681 | -0.30 | 30.04 | 29.74 | 56.00 | -26.26 | QP | |
| 12 | | 4.4681 | -5.17 | 30.04 | 24.87 | 46.00 | -21.13 | AVG | |



- Page 12 of 16 - Report No.: MTi160413E002

4.2 Radiated emission

4.2.1 Limits

Limits of radiated emission measurement

| Frequency (MHz) | Class B device (at 3m) dBµV/m | Class A device (at 3m) dBµV/m | Detector |
|--------------------|----------------------------------|----------------------------------|----------|
| 30-88 | 40 | 49 | QP |
| 88-216 | 43.5 | 53.5 | QP |
| 216-960 | 46 | 56.4 | QP |
| 960-1000 | 54 | 59.5 | QP |
| Above 1000 | 54 | 59.5 | AV |
| Above 1000 | 74 | 79.5 | PK |

4.2.2 Test Procedures

The radiated emission tests were performed in the 3 meters.

The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.


The height of the test antenna shall vary between 1m to 4m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

If the peak mode measured value compliance with and lower than quasi peak mode limit, the EUT shall be deemed to meet QP limits and then no additional QP mode measurement performed.

If the peak mode measured value compliance with and lower than average mode limit, the EUT shall be deemed to meet average limits and then no additional average mode measurement performed.

For the actual test configuration, please refer to the related item – EUT test photos.

4.2.3 Test Setup



4.2.4 Test Result


Note: the highest working frequency of EUT is 400MHz.



- Page 13 of 16 -

Report No.: MTi160413E002

| Temperature: | 21 ℃ | Relative Humidity: | 55% |
|---------------|--------------|--------------------|------------|
| Pressure: | 101kPa | Polarization: | Horizontal |
| Test voltage: | AC 120V/60Hz | Test mode: | Mode 1 |




| No. | Mk. | Freq. | Reading Level | Correct Factor | Measure- ment | Limit | Over | | Antenna Height | Table Degree | |
|-----|-----|----------|------------------|-------------------|------------------|--------|--------|----------|-------------------|-----------------|---------|
| | | MHz | dBuV | dBuV/m | dBuV/m | dBuV/m | dB | Detector | cm | degree | Comment |
| 1 | | 132.2204 | 45.50 | -17.20 | 28.30 | 43.50 | -15.20 | QP | | | |
| 2 | | 155.9097 | 47.00 | -17.00 | 30.00 | 43.50 | -13.50 | QP | | | |
| 3 | | 216.0240 | 44.50 | -13.40 | 31.10 | 46.00 | -14.90 | QP | | | |
| 4 | ; | 239.9874 | 43.66 | -12.76 | 30.90 | 46.00 | -15.10 | QP | | | |
| 5 | | 408.9460 | 40.31 | -9.01 | 31.30 | 46.00 | -14.70 | QP | | | |
| 6 | * (| 672.8444 | 40.40 | -4.90 | 35.50 | 46.00 | -10.50 | QP | | | |



- Page 14 of 16 -

Report No.: MTi160413E002

| Temperature: | 21 ℃ | Relative Humidity: | 55% |
|---------------|--------------|--------------------|----------|
| Pressure: | 101kPa | Polarization: | Vertical |
| Test voltage: | AC 120V/60Hz | Test mode: | Mode 1 |






- Page 15 of 16 -

Report No.: MTi160413E002

| Temperature: | 21 ℃ | Relative Humidity: | 55% |
|---------------|--------------|--------------------|------------|
| Pressure: | 101kPa | Polarization: | Horizontal |
| Test voltage: | AC 120V/60Hz | Test mode: | Mode 1 |




| No. Mk | . Freq. | Reading Level | Correct Factor | Measure- ment | Limit | Over | | Antenna Height | Table Degree | |
|--------|----------|------------------|-------------------|------------------|--------|--------|----------|-------------------|-----------------|---------|
| | MHz | dBuV | dBuV/m | dBuV/m | dBuV/m | dB | Detector | cm | degree | Comment |
| 1 | 1258.690 | 60.08 | -2.25 | 57.83 | 74.00 | -16.17 | peak | | | |
| 2 * | 1258.690 | 42.93 | -2.25 | 40.68 | 54.00 | -13.32 | AVG | | | |
| 3 | 1926.340 | 53.97 | -0.11 | 53.86 | 74.00 | -20.14 | peak | | | |
| 4 | 1926.340 | 38.68 | -0.11 | 38.57 | 54.00 | -15.43 | AVG | | | |



- Page 16 of 16 -

Report No.: MTi160413E002

| Temperature: | 21 ℃ | Relative Humidity: | 55% |
|---------------|--------------|--------------------|----------|
| Pressure: | 101kPa | Polarization: | Vertical |
| Test voltage: | AC 120V/60Hz | Test mode: | Mode 1 |



| No. | Mk. | . Freq. | Reading Level | Correct Factor | Measure- ment | Limit | Over | | Antenna Height | Table Degree | |
|-----|-----|----------|------------------|-------------------|------------------|--------|--------|----------|-------------------|-----------------|---------|
| | | MHz | dBuV | dBuV/m | dBuV/m | dBuV/m | dB | Detector | cm | degree | Comment |
| 1 | | 1186.790 | 62.21 | -2.59 | 59.62 | 74.00 | -14.38 | peak | | | |
| 2 | | 1186.790 | 46.30 | -2.59 | 43.71 | 54.00 | -10.29 | AVG | | | |
| 3 | | 1722.640 | 56.57 | -1.08 | 55.49 | 74.00 | -18.51 | peak | | | |
| 4 | * | 1722.640 | 47.47 | -1.08 | 46.39 | 54.00 | -7.61 | AVG | | | |

----END OF REPORT----