

## FCC SAR TEST REPORT

**Applicant:** Shenzhen Xinguodu Technology Co., Ltd.

**Address:** 17B JinSong Mansion, Terra Industrial & Trade Park  
Chegongmiao, Futian District, Shenzhen, Guangdong, China.

**Product Name:** POS terminal

**FCC ID:** XDQN80-01

**Standard(s):** 47 CFR Part 2(2.1093)

**Report Number:** 2402U80198E-20

**Report Date:** 2024/09/03

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

*Mark Dong*

*Brave Lu*

**Reviewed By:** Mark Dong

**Approved By:** Brave Lu

Title: SAR Engineer

Title: SAR Engineer

---

**Bay Area Compliance Laboratories Corp. (Dongguan)**  
No.12, Pulong East 1<sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

[www.baclcorp.com.cn](http://www.baclcorp.com.cn)

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

## SAR TEST RESULTS SUMMARY

| Mode       |                          | Max. Reported SAR Level(s) (W/kg) |               | Limit (W/kg) |
|------------|--------------------------|-----------------------------------|---------------|--------------|
| Body Mode  | <b>GSM 850</b>           | 1g Body SAR                       | 0.65          | 1.6          |
|            | <b>GSM 1900</b>          | 1g Body SAR                       | <b>1.47</b>   |              |
|            | <b>WCDMA Band 2</b>      | 1g Body SAR                       | 1.46          |              |
|            | <b>WCDMA Band 4</b>      | 1g Body SAR                       | 1.04          |              |
|            | <b>WCDMA Band 5</b>      | 1g Body SAR                       | 0.31          |              |
|            | <b>LTE Band 2</b>        | 1g Body SAR                       | 1.43          |              |
|            | <b>LTE Band 5</b>        | 1g Body SAR                       | 0.33          |              |
|            | <b>LTE Band 7</b>        | 1g Body SAR                       | 1.04          |              |
|            | <b>LTE Band 66&amp;4</b> | 1g Body SAR                       | 1.00          |              |
|            | <b>WLAN 2.4G</b>         | 1g Body SAR                       | 0.17          |              |
|            | <b>WLAN 5.2G</b>         | 1g Body SAR                       | 0.65          |              |
|            | <b>WLAN 5.3G</b>         | 1g Body SAR                       | 0.64          |              |
|            | <b>WLAN 5.6G</b>         | 1g Body SAR                       | 1.14          |              |
|            | <b>WLAN 5.8G</b>         | 1g Body SAR                       | 1.41          |              |
|            | <b>Simultaneous</b>      | 1g Body SAR                       | 1.53          |              |
|            |                          | 1g Body SAR                       | 1.47(Hotspot) |              |
| Limb Mode* | <b>GSM 1900</b>          | 10g Extremity SAR                 | 2.88          | 4.0          |
|            | <b>WCDMA Band 2</b>      | 10g Extremity SAR                 | 2.73          |              |
|            | <b>LTE Band 2</b>        | 10g Extremity SAR                 | 2.74          |              |
|            | <b>WLAN 2.4G</b>         | 10g Extremity SAR                 | 0.44          |              |
|            | <b>WLAN 5.8G</b>         | 10g Extremity SAR                 | 2.38          |              |
|            | <b>Simultaneous</b>      | 10g Extremity SAR                 | <b>2.88</b>   |              |

Note\*: For Limb mode, The worst case bands of WWAN(GSM/WCDMA/LTE), WLAN 2.4G and WLAN 5G were selected to SAR testing.

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Applicable Standards                                                                                                                                                                                                                                                                                                                                                                                                                                                     | <b>FCC 47 CFR part 2.1093</b><br>Radiofrequency radiation exposure evaluation: portable devices                                                                                                                                                                                                                                                                      |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <b>IEEE1528:2013</b><br>IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques                                                                                                                                                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <b>IEC 62209-2:2010</b><br>Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices-Human models, instrumentation, and procedures-Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz) |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <b>KDB procedures</b><br>KDB 447498 D01 General RF Exposure Guidance v06<br>KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04<br>KDB 865664 D02 RF Exposure Reporting v01r02<br>KDB 941225 D01 3G SAR Procedures v03r01<br>KDB 941225 D05 SAR for LTE Devices v02r05<br>KDB 941225 D06 Hotspot Mode v02r01<br>KDB 248227 D01 802.11 Wi-Fi SAR v02r02            |
| <p><b>Note:</b> This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in <b>FCC 47 CFR part 2.1093</b> and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures.</p> <p><b>The results and statements contained in this report pertain only to the device(s) evaluated.</b></p> |                                                                                                                                                                                                                                                                                                                                                                      |

## CONTENTS

|                                                                            |           |
|----------------------------------------------------------------------------|-----------|
| <b>SAR TEST RESULTS SUMMARY .....</b>                                      | <b>2</b>  |
| <b>DOCUMENT REVISION HISTORY .....</b>                                     | <b>5</b>  |
| <b>1. GENERAL INFORMATION .....</b>                                        | <b>6</b>  |
| <b>1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....</b>         | <b>6</b>  |
| <b>2. REFERENCE, STANDARDS, AND GUIDELINES .....</b>                       | <b>8</b>  |
| <b>2.1 SAR LIMITS.....</b>                                                 | <b>8</b>  |
| <b>2.2 TEST FACILITY .....</b>                                             | <b>9</b>  |
| <b>3. DESCRIPTION OF TEST SYSTEM.....</b>                                  | <b>10</b> |
| <b>4. EQUIPMENT LIST AND CALIBRATION .....</b>                             | <b>15</b> |
| <b>4.1 EQUIPMENTS LIST &amp; CALIBRATION INFORMATION .....</b>             | <b>15</b> |
| <b>5. SAR MEASUREMENT SYSTEM VERIFICATION .....</b>                        | <b>16</b> |
| <b>5.1 LIQUID VERIFICATION.....</b>                                        | <b>16</b> |
| <b>5.2 LIQUID VERIFICATION RESULTS .....</b>                               | <b>16</b> |
| <b>5.3 SYSTEM ACCURACY VERIFICATION .....</b>                              | <b>19</b> |
| <b>5.4 SYSTEM ACCURACY CHECK RESULTS.....</b>                              | <b>19</b> |
| <b>5.5 SAR SYSTEM VALIDATION DATA .....</b>                                | <b>20</b> |
| <b>6. EUT TEST STRATEGY AND METHODOLOGY .....</b>                          | <b>28</b> |
| <b>6.1 TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS .....</b>     | <b>28</b> |
| <b>6.2 TEST DISTANCE FOR SAR EVALUATION.....</b>                           | <b>28</b> |
| <b>6.3 SAR EVALUATION PROCEDURE .....</b>                                  | <b>29</b> |
| <b>7. CONDUCTED OUTPUT POWER MEASUREMENT.....</b>                          | <b>30</b> |
| <b>7.1 TEST PROCEDURE .....</b>                                            | <b>30</b> |
| <b>7.2 RADIO CONFIGURATION .....</b>                                       | <b>30</b> |
| <b>7.3 MAXIMUM TARGET OUTPUT POWER.....</b>                                | <b>35</b> |
| <b>7.4 TEST RESULTS:.....</b>                                              | <b>37</b> |
| <b>8. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS .....</b>               | <b>56</b> |
| <b>8.1 ANTENNAS LOCATION: .....</b>                                        | <b>56</b> |
| <b>8.2 ANTENNA DISTANCE TO EDGE.....</b>                                   | <b>56</b> |
| <b>8.3 STANDALONE SAR TEST EXCLUSION CONSIDERATIONS .....</b>              | <b>56</b> |
| <b>8.4 STANDALONE SAR ESTIMATION: .....</b>                                | <b>58</b> |
| <b>8.5 SAR TEST EXCLUSION FOR THE EUT EDGE CONSIDERATIONS RESULT .....</b> | <b>58</b> |
| <b>9. SAR MEASUREMENT RESULTS.....</b>                                     | <b>59</b> |
| <b>9.1 SAR TEST DATA .....</b>                                             | <b>59</b> |

---

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| <b>10. MEASUREMENT VARIABILITY .....</b>                          | <b>74</b> |
| <b>11. DUT HOLDER PERTURBATIONS .....</b>                         | <b>75</b> |
| <b>12. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION .....</b>        | <b>76</b> |
| <b>12.1 SIMULTANEOUS TRANSMISSION: .....</b>                      | <b>76</b> |
| <b>12.2 SIMULTANEOUS SAR TEST EXCLUSION CONSIDERATIONS: .....</b> | <b>76</b> |
| <b>APPENDIX A - MEASUREMENT UNCERTAINTY .....</b>                 | <b>78</b> |
| <b>APPENDIX B - SAR PLOTS .....</b>                               | <b>80</b> |
| <b>APPENDIX C - EUT TEST POSITION PHOTOS .....</b>                | <b>81</b> |
| <b>APPENDIX D - PROBE CALIBRATION CERTIFICATES .....</b>          | <b>82</b> |
| <b>APPENDIX E - DIPOLE CALIBRATION CERTIFICATES .....</b>         | <b>83</b> |

DOCUMENT REVISION HISTORY

| Revision Number | Report Number  | Description of Revision | Date of Revision |
|-----------------|----------------|-------------------------|------------------|
| 1.0             | 2402U80198E-20 | Original Report         | 2024/09/03       |

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment under Test (EUT)

|                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EUT Name:</b>              | POS terminal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>EUT Model:</b>             | N80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Device Type:</b>           | Portable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <b>Exposure Category:</b>     | Population / Uncontrolled                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <b>Antenna Type(s):</b>       | Internal Antenna                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Body-Worn Accessories:</b> | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Proximity Sensor:</b>      | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Carrier Aggregation:</b>   | None                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Operation Modes:</b>       | GPRS/EDGE Data,<br>WCDMA( R99 (Data), HSUPA/HSDPA/DC-HSDPA/HSPA+),<br>FDD-LTE,WLAN, Bluetooth and NFC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Frequency Band:</b>        | GSM 850: 824-849 MHz(TX); 869-894 MHz(RX)<br>PCS 1900: 1850-1910 MHz(TX); 1930-1990 MHz(RX)<br>WCDMA Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX)<br>WCDMA Band 4: 1710-1755 MHz(TX); 2110-2155 MHz(RX)<br>WCDMA Band 5: 824-849 MHz(TX); 869-894 MHz(RX)<br>LTE Band 2: 1850-1910 MHz(TX); 1930-1990 MHz(RX)<br>LTE Band 4: 1710-1755 MHz(TX); 2110-2155 MHz(RX)<br>LTE Band 5: 824-849 MHz(TX); 869-894 MHz(RX)<br>LTE Band 7: 2500-2570 MHz(TX); 2620-2690 MHz(RX)<br>LTE Band 66: 1710-1780 MHz(TX); 2110-2200 MHz(RX)<br>Wi-Fi 2.4G: 2412-2462 MHz<br>Wi-Fi 5.2G: 5150-5250 MHz<br>Wi-Fi 5.3G: 5250-5350 MHz<br>Wi-Fi 5.6G: 5470-5725 MHz<br>Wi-Fi 5.8G: 5725-5850 MHz<br>Bluetooth: 2402-2480 MHz<br>NFC:13.56 MHz |
| <b>Maximum Output Power</b>   | GSM 850: 33.11 dBm, PCS 1900: 29.54 dBm<br>WCDMA Band 2: 23.09 dBm, WCDMA Band 4: 23.27 dBm<br>WCDMA Band 5: 23.57 dBm<br>LTE Band 2: 22.69 dBm, LTE Band 4: 22.80 dBm<br>LTE Band 5: 23.37 dBm, LTE Band 7: 22.08 dBm<br>LTE Band 66: 23.03 dBm<br>WLAN 2.4G: 14.94 dBm<br>WLAN 5.2G: 13.22 dBm,WLAN 5.3G: 13.23 dBm<br>WLAN 5.6G: 13.44 dBm,WLAN 5.8G: 13.69 dBm<br>Bluetooth(BDR/EDR): 4.33 dBm<br>BLE: -3.15 dBm                                                                                                                                                                                                                                                                                                     |
| <b>Dimensions (L*W*H):</b>    | 180mm (L) *80mm (W) *70mm (H)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Rated Input Voltage:</b>   | DC 7.4V from Rechargeable Battery                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Serial Number:</b>         | 2MT3-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Normal Operation:</b>      | Body and Limb                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>EUT Received Date:</b>     | 2024/6/12                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

|                             |                       |
|-----------------------------|-----------------------|
| <b>Test Date:</b>           | 2024/08/29~2024/09/03 |
| <b>EUT Received Status:</b> | Good                  |

## 2. REFERENCE, STANDARDS, AND GUIDELINES

### FCC:

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

### 2.1 SAR Limits

#### FCC Limit

| EXPOSURE LIMITS                                                  | SAR (W/kg)                                                     |                                                        |
|------------------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------|
|                                                                  | (General Population /<br>Uncontrolled Exposure<br>Environment) | (Occupational /<br>Controlled Exposure<br>Environment) |
| Spatial Average<br>(averaged over the whole body)                | 0.08                                                           | 0.4                                                    |
| Spatial Peak<br>(averaged over any 1 g of tissue)                | 1.6                                                            | 8                                                      |
| Spatial Peak<br>(hands/wrists/feet/ankles<br>averaged over 10 g) | 4                                                              | 20                                                     |

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that maybe incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) for Body SAR and limit 4.0W/kg (FCC) for Extremity SAR applied to the EUT.

## 2.2 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. :829273, the FCC Designation No. : CN5044.


### 3. DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



#### DASY5 System Description

The DASY5 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

### **DASY5 Measurement Server**

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.



The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized point out, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

### **Data Acquisition Electronics**

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200M $\Omega$ ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

**EX3DV4 E-Field Probes**

|                             |                                                                                                                                                                                                               |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Frequency</b>            | 4 MHz–10 GHz<br>Linearity: $\pm 0.2$ dB (30 MHz–10 GHz)                                                                                                                                                       |
| <b>Directivity(typical)</b> | $\pm 0.1$ dB in TSL (rotation around probe axis)<br>$\pm 0.3$ dB in TSL (rotation normal to probe axis)                                                                                                       |
| <b>Dynamic Range</b>        | 10 $\mu$ W/g – > 100 mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)                                                                                                                         |
| <b>Dimensions</b>           | Overall length: 337 mm (tip: 20 mm)<br>Tip diameter: 2.5 mm (body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                                                                          |
| <b>Applications</b>         | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%. |
| <b>Compatibility</b>        | DASY3, DASY4, DASY52, DASY6, DASY8, EASY6, EASY4/MRI                                                                                                                                                          |

### SAM Twin Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness

increases to 6 mm). The phantom has three measurement areas:

- \_ Left Head
- \_ Right Head
- \_ Flat phantom

The phantom table for the DASY systems based on the robots have the size of 100 x 50 x 85 cm (L x W x H). For easy dislocation these tables have fork lift cut outs at the bottom.

The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids)



A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible.

Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.

### Robots

The DASY5 system uses the high precision industrial robot. The robot offers the same features important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The above mentioned robots are controlled by the Staubli CS7MB robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is contained on the CDs delivered along with the robot. Paper manuals are available upon request direct from Staubli.

### Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm<sup>2</sup> step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

### Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m<sup>3</sup> is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x 7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

### Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEC 62209-1:2016

#### Recommended Tissue Dielectric Parameters for Head liquid

**Table A.3 – Dielectric properties of the head tissue-equivalent liquid**

| Frequency<br>MHz | Relative permittivity<br>$\epsilon_r$ | Conductivity ( $\sigma$ )<br>S/m |
|------------------|---------------------------------------|----------------------------------|
| 300              | 45,3                                  | 0,87                             |
| 450              | 43,5                                  | 0,87                             |
| <i>750</i>       | <i>41,9</i>                           | <i>0,89</i>                      |
| 835              | 41,5                                  | 0,90                             |
| 900              | 41,5                                  | 0,97                             |
| 1 450            | 40,5                                  | 1,20                             |
| <i>1 500</i>     | <i>40,4</i>                           | <i>1,23</i>                      |
| <i>1 640</i>     | <i>40,2</i>                           | <i>1,31</i>                      |
| <i>1 750</i>     | <i>40,1</i>                           | <i>1,37</i>                      |
| 1 800            | 40,0                                  | 1,40                             |
| 1 900            | 40,0                                  | 1,40                             |
| 2 000            | 40,0                                  | 1,40                             |
| <i>2 100</i>     | <i>39,8</i>                           | <i>1,49</i>                      |
| <i>2 300</i>     | <i>39,5</i>                           | <i>1,67</i>                      |
| 2 450            | 39,2                                  | 1,80                             |
| <i>2 600</i>     | <i>39,0</i>                           | <i>1,96</i>                      |
| 3 000            | 38,5                                  | 2,40                             |
| <i>3 500</i>     | <i>37,9</i>                           | <i>2,91</i>                      |
| <i>4 000</i>     | <i>37,4</i>                           | <i>3,43</i>                      |
| <i>4 500</i>     | <i>36,8</i>                           | <i>3,94</i>                      |
| <i>5 000</i>     | <i>36,2</i>                           | <i>4,45</i>                      |
| <i>5 200</i>     | <i>36,0</i>                           | <i>4,66</i>                      |
| <i>5 400</i>     | <i>35,8</i>                           | <i>4,86</i>                      |
| <i>5 600</i>     | <i>35,5</i>                           | <i>5,07</i>                      |
| <i>5 800</i>     | <i>35,3</i>                           | <i>5,27</i>                      |
| <i>6 000</i>     | <i>35,1</i>                           | <i>5,48</i>                      |

NOTE For convenience, permittivity and conductivity values at those frequencies which are not part of the original data provided by Drossos et al. [33] or the extension to 5 800 MHz are provided (i.e. the values shown *in italics*). These values were linearly interpolated between the values in this table that are immediately above and below these values, except the values at 6 000 MHz that were linearly extrapolated from the values at 3 000 MHz and 5 800 MHz.


## 4. EQUIPMENT LIST AND CALIBRATION

### 4.1 Equipments List & Calibration Information

| Equipment                           | Model           | S/N                            | Calibration Date | Calibration Due Date |
|-------------------------------------|-----------------|--------------------------------|------------------|----------------------|
| DASY5 Test Software                 | DASY52.10       | N/A                            | NCR              | NCR                  |
| DASY5 Measurement Server            | DASY5 4.5.12    | 1470                           | NCR              | NCR                  |
| Data Acquisition Electronics        | DAE4            | 772                            | 2024/1/23        | 2025/1/22            |
| E-Field Probe                       | EX3DV4          | 7839                           | 2023/9/21        | 2024/9/20            |
| Mounting Device                     | MD4HHTV5        | SD 000 H01 KA                  | NCR              | NCR                  |
| Twin SAM                            | Twin SAM V5.0   | 1874                           | NCR              | NCR                  |
| Dipole, 835 MHz                     | D835V2          | 453                            | 2021/8/31        | 2024/8/30            |
| Dipole, 1750 MHz                    | D1750V2         | 1141                           | 2024/6/17        | 2027/6/16            |
| Dipole, 1900 MHz                    | D1900V2         | 543                            | 2022/11/2        | 2025/11/1            |
| Dipole, 2450 MHz                    | D2450V2         | 971                            | 2024/6/15        | 2027/6/14            |
| Dipole, 2600 MHz                    | D2600V2         | 1132                           | 2022/11/1        | 2025/10/31           |
| Dipole,5GHz                         | D5GHzV2         | 1246                           | 2022/11/1        | 2025/10/31           |
| Simulated Tissue Liquid Head        | HBBL600-10000V6 | SL AAH U16 BC(Batch: 220809-1) | Each Time        | /                    |
| Network Analyzer                    | 8753C           | 3033A02857                     | 2023/11/18       | 2024/11/17           |
| Dielectric assessment kit           | 1253            | SM DAK 040 CA                  | NCR              | NCR                  |
| synthesized signal generator        | 8665B           | 3438a00584                     | 2023/10/18       | 2024/10/17           |
| EPM Series Power Meter              | E4419B          | MY45103907                     | 2023/10/18       | 2024/10/17           |
| USB Wideband Power Sensor           | U2022XA         | MY54170006                     | 2023/10/18       | 2024/10/17           |
| Power Amplifier                     | ZVE-6W-83+      | 637202210                      | NCR              | NCR                  |
| Power Amplifier                     | ZHL-5W-202-S+   | 416402204                      | NCR              | NCR                  |
| Directional Coupler                 | 441493          | 520Z                           | NCR              | NCR                  |
| Coaxial Attenuator                  | 20dB, 100W      | LN749                          | NCR              | NCR                  |
| Attenuator                          | 6dB, 150W       | 2754                           | NCR              | NCR                  |
| Thermometer                         | DTM3000         | 3635                           | 2024/8/12        | 2025/8/11            |
| Hygrothermograph                    | HTC-2           | EM072                          | 2023/11/6        | 2024/11/5            |
| Wireless communication tester       | 8960            | MY50266471                     | 2023/10/18       | 2024/10/17           |
| Wideband Radio Communication Tester | CMW500          | 147473                         | 2023/10/18       | 2024/10/17           |

## 5. SAR MEASUREMENT SYSTEM VERIFICATION

### 5.1 Liquid Verification



### 5.2 Liquid Verification Results

| Frequency (MHz) | Liquid Type                  | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                              | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 824.2           | Simulated Tissue Liquid Head | 41.066           | 0.943          | 41.55        | 0.9            | -1.16              | 4.78                 | $\pm 5$       |
| 826.4           | Simulated Tissue Liquid Head | 41.038           | 0.943          | 41.54        | 0.9            | -1.21              | 4.78                 | $\pm 5$       |
| 835             | Simulated Tissue Liquid Head | 40.927           | 0.945          | 41.5         | 0.9            | -1.38              | 5                    | $\pm 5$       |
| 836.5           | Simulated Tissue Liquid Head | 40.907           | 0.945          | 41.5         | 0.9            | -1.43              | 5                    | $\pm 5$       |
| 836.6           | Simulated Tissue Liquid Head | 40.905           | 0.945          | 41.5         | 0.9            | -1.43              | 5                    | $\pm 5$       |
| 846.6           | Simulated Tissue Liquid Head | 40.768           | 0.95           | 41.5         | 0.91           | -1.76              | 4.4                  | $\pm 5$       |
| 848.8           | Simulated Tissue Liquid Head | 40.738           | 0.951          | 41.5         | 0.91           | -1.84              | 4.51                 | $\pm 5$       |

\*Liquid Verification above was performed on 2024/08/29.

| Frequency (MHz) | Liquid Type                  | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                              | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 1712.4          | Simulated Tissue Liquid Head | 39.461           | 1.332          | 40.13        | 1.35           | -1.67              | -1.33                | $\pm 5$       |
| 1720            | Simulated Tissue Liquid Head | 39.424           | 1.339          | 40.13        | 1.35           | -1.76              | -0.81                | $\pm 5$       |
| 1732.6          | Simulated Tissue Liquid Head | 39.378           | 1.351          | 40.12        | 1.36           | -1.85              | -0.66                | $\pm 5$       |
| 1745            | Simulated Tissue Liquid Head | 39.326           | 1.364          | 40.11        | 1.37           | -1.95              | -0.44                | $\pm 5$       |
| 1750            | Simulated Tissue Liquid Head | 39.305           | 1.368          | 40.1         | 1.37           | -1.98              | -0.15                | $\pm 5$       |
| 1752.6          | Simulated Tissue Liquid Head | 39.293           | 1.371          | 40.09        | 1.37           | -1.99              | 0.07                 | $\pm 5$       |
| 1770            | Simulated Tissue Liquid Head | 39.219           | 1.388          | 40.06        | 1.38           | -2.10              | 0.58                 | $\pm 5$       |

\*Liquid Verification above was performed on 2024/09/02.

| Frequency (MHz) | Liquid Type                  | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                              | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 1850.2          | Simulated Tissue Liquid Head | 39.63            | 1.413          | 40           | 1.4            | -0.93              | 0.93                 | $\pm 5$       |
| 1852.4          | Simulated Tissue Liquid Head | 39.582           | 1.414          | 40           | 1.4            | -1.05              | 1                    | $\pm 5$       |
| 1860            | Simulated Tissue Liquid Head | 39.418           | 1.416          | 40           | 1.4            | -1.46              | 1.14                 | $\pm 5$       |
| 1880            | Simulated Tissue Liquid Head | 39.347           | 1.42           | 40           | 1.4            | -1.63              | 1.43                 | $\pm 5$       |
| 1900            | Simulated Tissue Liquid Head | 39.315           | 1.424          | 40           | 1.4            | -1.71              | 1.71                 | $\pm 5$       |
| 1907.6          | Simulated Tissue Liquid Head | 39.223           | 1.422          | 40           | 1.4            | -1.94              | 1.57                 | $\pm 5$       |
| 1909.8          | Simulated Tissue Liquid Head | 39.197           | 1.422          | 40           | 1.4            | -2.01              | 1.57                 | $\pm 5$       |

\*Liquid Verification above was performed on 2024/09/01.

| Frequency (MHz) | Liquid Type                  | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                              | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 2412            | Simulated Tissue Liquid Head | 40.526           | 1.774          | 39.28        | 1.77           | 3.17               | 0.23                 | $\pm 5$       |
| 2437            | Simulated Tissue Liquid Head | 40.406           | 1.804          | 39.23        | 1.79           | 3                  | 0.78                 | $\pm 5$       |
| 2450            | Simulated Tissue Liquid Head | 40.321           | 1.823          | 39.2         | 1.8            | 2.86               | 1.28                 | $\pm 5$       |
| 2462            | Simulated Tissue Liquid Head | 40.301           | 1.833          | 39.18        | 1.81           | 2.86               | 1.27                 | $\pm 5$       |

\*Liquid Verification above was performed on 2024/09/01.

| Frequency (MHz) | Liquid Type                  | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                              | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 2510            | Simulated Tissue Liquid Head | 40.102           | 1.892          | 39.12        | 1.86           | 2.51               | 1.72                 | $\pm 5$       |
| 2535            | Simulated Tissue Liquid Head | 40.060           | 1.930          | 39.09        | 1.89           | 2.48               | 2.12                 | $\pm 5$       |
| 2560            | Simulated Tissue Liquid Head | 40.236           | 1.991          | 39.05        | 1.92           | 3.04               | 3.70                 | $\pm 5$       |
| 2600            | Simulated Tissue Liquid Head | 40.071           | 2.032          | 39.00        | 1.96           | 2.75               | 3.67                 | $\pm 5$       |

\*Liquid Verification above was performed on 2024/09/02.

| Frequency (MHz) | Liquid Type                  | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                              | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 5180            | Simulated Tissue Liquid Head | 36.774           | 4.534          | 36.02        | 4.64           | 2.09               | -2.28                | $\pm 5$       |
| 5200            | Simulated Tissue Liquid Head | 36.738           | 4.554          | 36           | 4.66           | 2.05               | -2.27                | $\pm 5$       |
| 5240            | Simulated Tissue Liquid Head | 36.677           | 4.599          | 35.96        | 4.7            | 1.99               | -2.15                | $\pm 5$       |
| 5250            | Simulated Tissue Liquid Head | 36.662           | 4.609          | 35.95        | 4.71           | 1.98               | -2.14                | $\pm 5$       |
| 5260            | Simulated Tissue Liquid Head | 36.619           | 4.62           | 35.94        | 4.72           | 1.89               | -2.12                | $\pm 5$       |
| 5280            | Simulated Tissue Liquid Head | 36.525           | 4.638          | 35.92        | 4.74           | 1.68               | -2.15                | $\pm 5$       |
| 5320            | Simulated Tissue Liquid Head | 36.442           | 4.679          | 35.88        | 4.78           | 1.57               | -2.11                | $\pm 5$       |

\*Liquid Verification above was performed on 2024/09/02.

| Frequency (MHz) | Liquid Type                  | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                              | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 5500            | Simulated Tissue Liquid Head | 36.014           | 4.895          | 35.65        | 4.97           | 1.02               | -1.51                | $\pm 5$       |
| 5580            | Simulated Tissue Liquid Head | 35.792           | 5              | 35.53        | 5.05           | 0.74               | -0.99                | $\pm 5$       |
| 5600            | Simulated Tissue Liquid Head | 35.754           | 5.04           | 35.5         | 5.07           | 0.72               | -0.59                | $\pm 5$       |

\*Liquid Verification above was performed on 2024/09/02.

| Frequency (MHz) | Liquid Type                  | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                              | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 5700            | Simulated Tissue Liquid Head | 35.604           | 5.134          | 35.4         | 5.17           | 0.58               | -0.7                 | $\pm 5$       |
| 5720            | Simulated Tissue Liquid Head | 35.528           | 5.162          | 35.38        | 5.19           | 0.42               | -0.54                | $\pm 5$       |
| 5745            | Simulated Tissue Liquid Head | 35.506           | 5.191          | 35.36        | 5.22           | 0.41               | -0.56                | $\pm 5$       |
| 5750            | Simulated Tissue Liquid Head | 35.483           | 5.199          | 35.35        | 5.22           | 0.38               | -0.4                 | $\pm 5$       |
| 5785            | Simulated Tissue Liquid Head | 35.41            | 5.239          | 35.32        | 5.26           | 0.25               | -0.4                 | $\pm 5$       |
| 5825            | Simulated Tissue Liquid Head | 35.39            | 5.326          | 35.28        | 5.3            | 0.31               | 0.49                 | $\pm 5$       |

\*Liquid Verification above was performed on 2024/09/03.


### 5.3 System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of  $\pm 10\%$ . The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

The spacing distances in the **System Verification Setup Block Diagram** is given by the following:

- $s = 15 \text{ mm} \pm 0,2 \text{ mm}$  for  $300 \text{ MHz} \leq f \leq 1\,000 \text{ MHz}$ ;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$  for  $1\,000 \text{ MHz} < f \leq 3\,000 \text{ MHz}$ ;
- $s = 10 \text{ mm} \pm 0,2 \text{ mm}$  for  $3\,000 \text{ MHz} < f \leq 6\,000 \text{ MHz}$ .

### System Verification Setup Block Diagram



### 5.4 System Accuracy Check Results

| Date       | Frequency Band (MHz) | Liquid Type | Input Power (mW) | Measured SAR (W/kg) |       | Normalized to 1W (W/kg) | Target Value (W/Kg) | Delta (%) | Tolerance (%) |
|------------|----------------------|-------------|------------------|---------------------|-------|-------------------------|---------------------|-----------|---------------|
| 2024/08/29 | 835MHz               | Head        | 100              | 1g                  | 0.918 | 9.18                    | 9.33                | -1.61     | $\pm 10$      |
| 2024/09/02 | 1750MHz              | Head        | 100              | 1g                  | 3.32  | 33.2                    | 36.1                | -8.03     | $\pm 10$      |
| 2024/09/01 | 1900MHz              | Head        | 100              | 1g                  | 4.04  | 40.4                    | 40.2                | 0.5       | $\pm 10$      |
|            |                      |             |                  | 10g                 | 2.21  | 22.1                    | 20.9                | 5.74      | $\pm 10$      |
| 2024/09/01 | 2450MHz              | Head        | 100              | 1g                  | 4.92  | 49.2                    | 52.7                | -6.64     | $\pm 10$      |
| 2024/09/02 | 2600MHz              | Head        | 100              | 1g                  | 5.86  | 58.6                    | 55.8                | 5.02      | $\pm 10$      |
| 2024/09/02 | 5250MHz              | Head        | 100              | 1g                  | 8.31  | 83.1                    | 77.5                | 7.23      | $\pm 10$      |
| 2024/09/02 | 5600MHz              | Head        | 100              | 1g                  | 8.86  | 88.6                    | 80.7                | 9.79      | $\pm 10$      |
| 2024/09/03 | 5750MHz              | Head        | 100              | 1g                  | 7.18  | 71.8                    | 78.4                | -8.42     | $\pm 10$      |
|            |                      |             |                  | 10g                 | 2.11  | 21.1                    | 22                  | -4.09     | $\pm 10$      |

**Note:**

All the SAR values are normalized to 1Watt forward power.

## 5.5 SAR SYSTEM VALIDATION DATA

### System Performance 835 MHz Head

**DUT: D835V2; Type: 835 MHz; Serial: 453;**

Communication System: CW (0); Frequency: 835MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 835$  MHz;  $\sigma = 0.945$  S/m;  $\epsilon_r = 40.927$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7839; ConvF(9.55, 8.6, 8.54) @ 835 MHz; Calibrated: 2023/9/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2024/1/23
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan(7x12x1):**Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.16 W/kg


**Zoom Scan (5x5x7)/Cube 0:**Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value =33.31 V/m; Power Drift = -0.14 dB

Peak SAR (extrapolated) = 1.34 W/kg

**SAR(1 g) = 0.918 W/kg; SAR(10 g) = 0.617 W/kg**

Maximum value of SAR (measured) = 1.02 W/kg



0 dB = 1.02 W/kg = 0.09 dBW/kg

**System Performance 1750 MHz Head****DUT: D1750V2; Type: 1750 MHz; Serial: 1141;**

Communication System: CW (0); Frequency: 1750MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.368$  S/m;  $\epsilon_r = 39.305$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7839; ConvF(8.54, 7.65, 7.43) @ 1750 MHz; Calibrated: 2023/9/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2024/1/23
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan(7x9x1):**Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 3.73 W/kg


**Zoom Scan (5x5x7)/Cube 0:**Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value =52.07 V/m; Power Drift =0.15dB

Peak SAR (extrapolated) = 5.72 W/kg

**SAR(1 g) = 3.32 W/kg; SAR(10 g) = 1.85 W/kg**

Maximum value of SAR (measured) = 4.16 W/kg



**System Performance 1900 MHz Head****DUT: D1900V2; Type: 1900 MHz; Serial: 543;**

Communication System: CW (0); Frequency: 1900MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 1900$  MHz;  $\sigma = 1.424$  S/m;  $\epsilon_r = 39.315$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7839; ConvF(8, 7.27, 7.03) @ 1900 MHz; Calibrated: 2023/9/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2024/1/23
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan(6x9x1):**Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 4.53 W/kg


**Zoom Scan (5x5x7)/Cube 0:**Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value =54.82 V/m; Power Drift = 0.15 dB

Peak SAR (extrapolated) = 7.25 W/kg

**SAR(1 g) = 4.04 W/kg; SAR(10 g) = 2.21 W/kg**

Maximum value of SAR (measured) = 5.27 W/kg



**System Performance 2450MHz Head****DUT: D2450V2; Type: 2450 MHz; Serial: 971**

Communication System: CW (0); Frequency: 2450MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.823$  S/m;  $\epsilon_r = 40.321$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7839; ConvF(7.49, 6.81, 6.61) @ 2450 MHz; Calibrated: 2023/9/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2024/1/23
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan(6x9x1):**Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 5.07 W/kg


**Zoom Scan (7x7x7)/Cube 0:**Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value =49.53 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 9.78 W/kg

**SAR(1 g) = 4.92 W/kg; SAR(10 g) = 2.37 W/kg**

Maximum value of SAR (measured) = 6.13 W/kg



**System Performance 2600 MHz Head****DUT: D2600V2; Type: 2600 MHz; Serial: 1132;**

Communication System: CW (0); Frequency: 2600MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 2600$  MHz;  $\sigma = 2.032$  S/m;  $\epsilon_r = 40.071$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7839; ConvF(7.61, 6.94, 6.73) @ 2600 MHz; Calibrated: 2023/9/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2024/1/23
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan(7x10x1):**Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 7.82 W/kg


**Zoom Scan (7x7x7)/Cube 0:**Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value =56.79 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 11.2 W/kg

**SAR(1 g) = 5.86 W/kg; SAR(10 g) = 2.76 W/kg**

Maximum value of SAR (measured) = 7.64 W/kg



**System Performance 5250 MHz Head****DUT: D5GHzV2; Type: 5250 MHz; Serial: 1246;**

Communication System: CW (0); Frequency: 5250MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 5250$  MHz;  $\sigma = 4.609$  S/m;  $\epsilon_r = 36.662$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7839; ConvF(5.62, 5.1, 4.97) @ 5250 MHz; Calibrated: 2023/9/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2024/1/23
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan(5x6x1):**Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 17.5 W/kg


**Zoom Scan (7x7x16)/Cube 0:**Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value =45.32 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 36.8 W/kg

**SAR(1 g) = 8.31 W/kg; SAR(10 g) = 2.34 W/kg**

Maximum value of SAR (measured) = 21.8 W/kg



**System Performance 5600 MHz Head****DUT: D5GHzV2; Type: 5600 MHz; Serial: 1246;**

Communication System: CW (0); Frequency: 5600MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 5600$  MHz;  $\sigma = 5.04$  S/m;  $\epsilon_r = 35.754$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7839; ConvF(4.94, 4.48, 4.39) @ 5600 MHz; Calibrated: 2023/9/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2024/1/23
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan(9x10x1):**Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 18.3 W/kg


**Zoom Scan (8x8x15)/Cube 0:**Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value =41.34 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 33.5 W/kg

**SAR(1 g) = 8.86 W/kg; SAR(10 g) = 2.47 W/kg**

Maximum value of SAR (measured) = 20.4 W/kg



**System Performance 5750 MHz Head****DUT: D5GHzV2; Type: 5750 MHz; Serial: 1246**

Communication System: CW (0); Frequency: 5750MHz;Duty Cycle: 1:1

Medium parameters used:  $f = 5750$  MHz;  $\sigma = 5.199$  S/m;  $\epsilon_r = 35.483$ ;  $\rho = 1000$  kg/m<sup>3</sup>;

Phantom section: Flat Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7839; ConvF(5.04, 4.65, 4.62) @ 5750 MHz; Calibrated: 2023/9/21
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn772; Calibrated: 2024/1/23
- Phantom: SAM (30deg probe tilt) with CRP v5.0\_20150321; Type: QD000P40CD; Serial: TP:1874
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7470)

**Area Scan(8x8x1):**Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (measured) = 18.2 W/kg


**Zoom Scan (7x7x16)/Cube 0:**Measurement grid: dx=4mm, dy=4mm, dz=2mm

Reference Value =31.48 V/m; Power Drift = 0.16 dB

Peak SAR (extrapolated) = 30.3 W/kg

**SAR(1 g) = 7.18 W/kg; SAR(10 g) = 2.11 W/kg**

Maximum value of SAR (measured) = 18.7 W/kg



## 6. EUT TEST STRATEGY AND METHODOLOGY

### 6.1 Test positions for body-worn and other configurations

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.




Figure 5 – Test positions for body-worn devices

### 6.2 Test Distance for SAR Evaluation

For Body SAR the EUT(Equipment Under Test) is set 10mm away from the phantom, the test distance is 10mm.

For Limb mode(10g Extremity SAR) the EUT(Equipment Under Test) is set directly against the phantom, the test distance is 0mm;

### 6.3 SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.


All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.


## 7. CONDUCTED OUTPUT POWER MEASUREMENT

### 7.1 Test Procedure

The RF output of the transmitter was connected to the input of the Wireless Communication Test Set through Connector.



The RF output of the transmitter was connected to the input port of the USB Wideband Power Sensor through Connector.



### 7.2 Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

#### GPRS/EGPRS

Function: Menu select > GSM Mobile Station > GSM 850/1900  
 Press Connection control to choose the different menus  
 Press RESET > choose all the reset all settings  
 Connection Press Signal Off to turn off the signal and change settings  
 Network Support > GPRS  
 Main Service > Packet Data  
 Service selection > Test Mode A – Auto Slot Config. off  
 MS Signal Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting

- > Slot configuration > Uplink/Gamma
- > 33 dBm for GPRS 850
- > 30 dBm for GPRS 1900
- > 27 dBm for EGPRS 850
- > 26 dBm for EGPRS 1900

BS Signal Enter the same channel number for TCH channel (test channel) and BCCH channel  
 Frequency Offset > + 0 Hz  
 Mode > BCCH and TCH  
 BCCH Level > -85 dBm (May need to adjust if link is not stable)  
 BCCH Channel > choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]

Channel Type > Off  
 P0 > 4 dB  
 Slot Config > Unchanged (if already set under MS signal)  
 TCH > choose desired test channel  
 Hopping > Off

Main Timeslot > 3  
 Network Coding Scheme > CS4 (GPRS) and MCS5 (EGPRS)  
 Bit Stream > 2E9-1 PSR Bit Stream  
 AF/RF Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input  
 Connection Press Signal on to turn on the signal and change settings

**WCDMA Release 99**

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP

TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

|                                       |                         |              |
|---------------------------------------|-------------------------|--------------|
| <b>WCDMA<br/>General<br/>Settings</b> | Loopback Mode           | Test Mode 1  |
|                                       | Rel99 RMC               | 12.2kbps RMC |
|                                       | Power Control Algorithm | Algorithm2   |
|                                       | $\beta_c/\beta_d$       | 8/15         |

**HSDPA**

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP

TS34.121-1 specification.

|                                        | Mode<br>Subset             | HSDPA<br>1   | HSDPA<br>2 | HSDPA<br>3 | HSDPA<br>4 |
|----------------------------------------|----------------------------|--------------|------------|------------|------------|
| <b>WCDMA<br/>General<br/>Settings</b>  | Loopback Mode              | Test Mode 1  |            |            |            |
|                                        | Rel99 RMC                  | 12.2kbps RMC |            |            |            |
|                                        | HSDPA FRC                  | H-Set1       |            |            |            |
|                                        | Power Control Algorithm    | Algorithm2   |            |            |            |
|                                        | $\beta_c$                  | 2/15         | 12/15      | 15/15      | 15/15      |
|                                        | $\beta_d$                  | 15/15        | 15/15      | 8/15       | 4/15       |
|                                        | $\beta_d(\text{SF})$       | 64           |            |            |            |
|                                        | $\beta_c/\beta_d$          | 2/15         | 12/15      | 15/8       | 15/4       |
|                                        | $\beta_{hs}$               | 4/15         | 24/15      | 30/15      | 30/15      |
|                                        | MPR(dB)                    | 0            | 0          | 0.5        | 0.5        |
| <b>HSDPA<br/>Specific<br/>Settings</b> | DACK                       | 8            |            |            |            |
|                                        | DNAK                       | 8            |            |            |            |
|                                        | DCQI                       | 8            |            |            |            |
|                                        | Ack-Nack repetition factor | 3            |            |            |            |
|                                        | CQI Feedback               | 4ms          |            |            |            |
|                                        | CQI Repetition Factor      | 2            |            |            |            |
|                                        | Ahs= $\beta_{hs}/\beta_c$  | 30/15        |            |            |            |

**HSUPA**

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

|                                | Mode                             | HSUPA                                                                                                                                        | HSUPA | HSUPA                                                | HSUPA | HSUPA                                                                                                                                        |
|--------------------------------|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|-------|------------------------------------------------------|-------|----------------------------------------------------------------------------------------------------------------------------------------------|
|                                | Subset                           | 1                                                                                                                                            | 2     | 3                                                    | 4     | 5                                                                                                                                            |
| <b>WCDMA General Settings</b>  | Loopback Mode                    | Test Mode 1                                                                                                                                  |       |                                                      |       |                                                                                                                                              |
|                                | Rel99 RMC                        | 12.2kbps RMC                                                                                                                                 |       |                                                      |       |                                                                                                                                              |
|                                | HSDPA FRC                        | H-Set1                                                                                                                                       |       |                                                      |       |                                                                                                                                              |
|                                | HSUPA Test                       | HSUPA Loopback                                                                                                                               |       |                                                      |       |                                                                                                                                              |
|                                | Power Control Algorithm          | Algorithm2                                                                                                                                   |       |                                                      |       |                                                                                                                                              |
|                                | $\beta_c$                        | 11/15                                                                                                                                        | 6/15  | 15/15                                                | 2/15  | 15/15                                                                                                                                        |
|                                | $\beta_d$                        | 15/15                                                                                                                                        | 15/15 | 9/15                                                 | 15/15 | 0                                                                                                                                            |
|                                | $\beta_{ec}$                     | 209/225                                                                                                                                      | 12/15 | 30/15                                                | 2/15  | 5/15                                                                                                                                         |
|                                | $\beta_c/\beta_d$                | 11/15                                                                                                                                        | 6/15  | 15/9                                                 | 2/15  | -                                                                                                                                            |
|                                | $\beta_{hs}$                     | 22/15                                                                                                                                        | 12/15 | 30/15                                                | 4/15  | 5/15                                                                                                                                         |
|                                | CM(dB)                           | 1.0                                                                                                                                          | 3.0   | 2.0                                                  | 3.0   | 1.0                                                                                                                                          |
|                                | MPR(dB)                          | 0                                                                                                                                            | 2     | 1                                                    | 2     | 0                                                                                                                                            |
| <b>HSDPA Specific Settings</b> | DACK                             | 8                                                                                                                                            |       |                                                      |       |                                                                                                                                              |
|                                | DNAK                             | 8                                                                                                                                            |       |                                                      |       |                                                                                                                                              |
|                                | DCQI                             | 8                                                                                                                                            |       |                                                      |       |                                                                                                                                              |
|                                | Ack-Nack repetition factor       | 3                                                                                                                                            |       |                                                      |       |                                                                                                                                              |
|                                | CQI Feedback                     | 4ms                                                                                                                                          |       |                                                      |       |                                                                                                                                              |
|                                | CQI Repetition Factor            | 2                                                                                                                                            |       |                                                      |       |                                                                                                                                              |
|                                | $A_{hs}=\beta_{hs}/\beta_c$      | 30/15                                                                                                                                        |       |                                                      |       |                                                                                                                                              |
| <b>HSUPA Specific Settings</b> | DE-DPCCH                         | 6                                                                                                                                            | 8     | 8                                                    | 5     | 7                                                                                                                                            |
|                                | DHARQ                            | 0                                                                                                                                            | 0     | 0                                                    | 0     | 0                                                                                                                                            |
|                                | AG Index                         | 20                                                                                                                                           | 12    | 15                                                   | 17    | 21                                                                                                                                           |
|                                | ETFCI                            | 75                                                                                                                                           | 67    | 92                                                   | 71    | 81                                                                                                                                           |
|                                | Associated Max UL Data Rate kbps | 242.1                                                                                                                                        | 174.9 | 482.8                                                | 205.8 | 308.9                                                                                                                                        |
|                                | Reference E_FCI                  | E-TFCI 11 E<br>E-TFCI PO 4<br>E-TFCI 67<br>E-TFCI PO 18<br>E-TFCI 71<br>E-TFCI PO23<br>E-TFCI 75<br>E-TFCI PO26<br>E-TFCI 81<br>E-TFCI PO 27 |       | E-TFCI 11<br>E-TFCI PO4<br>E-TFCI 92<br>E-TFCI PO 18 |       | E-TFCI 11 E<br>E-TFCI PO 4<br>E-TFCI 67<br>E-TFCI PO 18<br>E-TFCI 71<br>E-TFCI PO23<br>E-TFCI 75<br>E-TFCI PO26<br>E-TFCI 81<br>E-TFCI PO 27 |
|                                |                                  |                                                                                                                                              |       |                                                      |       |                                                                                                                                              |

**DC-HSDPA**

The following tests were conducted according to the test requirements in Table C.8.1.12 of 3GPP TS 34.121-1

**Table C.8.1.12: Fixed Reference Channel H-Set 12**

| Parameter                                                                                                                                              | Unit      | Value |
|--------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|
| Nominal Avg. Inf. Bit Rate                                                                                                                             | kbps      | 60    |
| Inter-TTI Distance                                                                                                                                     | TTI's     | 1     |
| Number of HARQ Processes                                                                                                                               | Processes | 6     |
| Information Bit Payload ( $N_{INF}$ )                                                                                                                  | Bits      | 120   |
| Number Code Blocks                                                                                                                                     | Blocks    | 1     |
| Binary Channel Bits Per TTI                                                                                                                            | Bits      | 960   |
| Total Available SML's in UE                                                                                                                            | SML's     | 19200 |
| Number of SML's per HARQ Proc.                                                                                                                         | SML's     | 3200  |
| Coding Rate                                                                                                                                            |           | 0.15  |
| Number of Physical Channel Codes                                                                                                                       | Codes     | 1     |
| Modulation                                                                                                                                             |           | QPSK  |
| Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.               |           |       |
| Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used. |           |       |

**HSPA+**

| Sub-test                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | $\beta_c$<br>(Note 3) | $\beta_d$ | $\beta_{HS}$<br>(Note 1) | $\beta_{ec}$ | $\beta_{ed}$<br>(2xSF2)<br>(Note 4)            | $\beta_{ed}$<br>(2xSF4)<br>(Note 4)            | CM<br>(dB)<br>(Note 2) | MPR<br>(dB)<br>(Note 2) | AG<br>Index<br>(Note 4) | E-TFCI<br>(Note 5) | E-TFCI<br>(boost) |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------|--------------------------|--------------|------------------------------------------------|------------------------------------------------|------------------------|-------------------------|-------------------------|--------------------|-------------------|
| 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1                     | 0         | 30/15                    | 30/15        | $\beta_{ed1}$ : 30/15<br>$\beta_{ed2}$ : 30/15 | $\beta_{ed3}$ : 24/15<br>$\beta_{ed4}$ : 24/15 | 3.5                    | 2.5                     | 14                      | 105                | 105               |
| Note 1: $\Delta_{ACK}$ , $\Delta_{NACK}$ and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$ .<br>Note 2: CM = 3.5 and the MPR is based on the relative CM difference, MPR = MAX(CM-1,0).<br>Note 3: DPDCH is not configured, therefore the $\beta_c$ is set to 1 and $\beta_d = 0$ by default.<br>Note 4: $\beta_{ed}$ can not be set directly; it is set by Absolute Grant Value.<br>Note 5: All the sub-tests require the UE to transmit 2SF2+2SF4 16QAM EDCH and they apply for UE using E-DPDCH category 7. E-DCH TTI is set to 2ms TTI and E-DCH table index = 2. To support these E-DCH configurations DPDCH is not allocated. The UE is signalled to use the extrapolation algorithm. |                       |           |                          |              |                                                |                                                |                        |                         |                         |                    |                   |

The following tests were conducted according to the test requirements in Table C.11.1.4 of 3GPP TS 34.121-1

**FDD-LTE**

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

**Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3**

| Modulation | Channel bandwidth / Transmission bandwidth ( $N_{RB}$ ) |         |       |        |        |        | MPR (dB) |
|------------|---------------------------------------------------------|---------|-------|--------|--------|--------|----------|
|            | 1.4 MHz                                                 | 3.0 MHz | 5 MHz | 10 MHz | 15 MHz | 20 MHz |          |
| QPSK       | > 5                                                     | > 4     | > 8   | > 12   | > 16   | > 18   | ≤ 1      |
| 16 QAM     | ≤ 5                                                     | ≤ 4     | ≤ 8   | ≤ 12   | ≤ 16   | ≤ 18   | ≤ 1      |
| 64 QAM     | > 5                                                     | > 4     | > 8   | > 12   | > 16   | > 18   | ≤ 2      |

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.

**Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)**

| Network Signalling value | Requirements (subclause)      | E-UTRA Band              | Channel bandwidth (MHz) | Resources Blocks ( $N_{RB}$ )                     | A-MPR (dB) |
|--------------------------|-------------------------------|--------------------------|-------------------------|---------------------------------------------------|------------|
| NS_01                    | 6.6.2.1.1                     | Table 5.5-1              | 1.4, 3, 5, 10, 15, 20   | Table 5.6-1                                       | N/A        |
| NS_03                    | 6.6.2.2.1                     | 2, 4, 10, 23, 25, 35, 36 | 3                       | >5                                                | ≤ 1        |
|                          |                               |                          | 5                       | >6                                                | ≤ 1        |
|                          |                               |                          | 10                      | >6                                                | ≤ 1        |
|                          |                               |                          | 15                      | >8                                                | ≤ 1        |
|                          |                               |                          | 20                      | >10                                               | ≤ 1        |
| NS_04                    | 6.6.2.2.2                     | 41                       | 5                       | >6                                                | ≤ 1        |
| NS_05                    | 6.6.3.3.1                     | 1                        | 10, 15, 20              | ≥ 50                                              | ≤ 1        |
| NS_06                    | 6.6.2.2.3                     | 12, 13, 14, 17           | 1.4, 3, 5, 10           | Table 5.6-1                                       | N/A        |
| NS_07                    | 6.6.2.2.3<br>6.6.3.3.2        | 13                       | 10                      | Table 6.2.4-2                                     |            |
| NS_08                    | 6.6.3.3.3                     | 19                       | 10, 15                  | > 44                                              | ≤ 3        |
| NS_09                    | 6.6.3.3.4                     | 21                       | 10, 15                  | > 40                                              | ≤ 1        |
|                          |                               |                          |                         | > 55                                              | ≤ 2        |
| NS_10                    |                               | 20                       | 15, 20                  | Table 6.2.4-3                                     |            |
| NS_11                    | 6.6.2.2.1                     | 23                       | 1.4, 3, 5, 10, 15, 20   | Table 6.2.4-5                                     |            |
| NS_12                    | 6.6.3.3.5                     | 26                       | 1.4, 3, 5               | Table 6.2.4-6                                     |            |
| NS_13                    | 6.6.3.3.6                     | 26                       | 5                       | Table 6.2.4-7                                     |            |
| NS_14                    | 6.6.3.3.7                     | 26                       | 10, 15                  | Table 6.2.4-8                                     |            |
| NS_15                    | 6.6.3.3.8                     | 26                       | 1.4, 3, 5, 10, 15       | Table 6.2.4-9<br>Table 6.2.4-10                   |            |
| NS_16                    | 6.6.3.3.9                     | 27                       | 3, 5, 10                | Table 6.2.4-11, Table 6.2.4-12,<br>Table 6.2.4-13 |            |
| NS_17                    | 6.6.3.3.10                    | 28                       | 5, 10                   | Table 5.6-1                                       | N/A        |
| NS_18                    | 6.6.3.3.11                    | 28                       | 5                       | ≥ 2                                               | ≤ 1        |
|                          |                               |                          | 10, 15, 20              | ≥ 1                                               | ≤ 4        |
| NS_19                    | 6.6.3.3.12                    | 44                       | 10, 15, 20              | Table 6.2.4-14                                    |            |
| NS_20                    | 6.2.2<br>6.6.2.2.1<br>6.6.3.2 | 23                       | 5, 10, 15, 20           | Table 6.2.4-15                                    |            |
| ...                      |                               |                          |                         |                                                   |            |
| NS_32                    | -                             | -                        | -                       | -                                                 | -          |

### 7.3 Maximum Target Output Power

| Max Target Power(dBm)   |         |        |      |
|-------------------------|---------|--------|------|
| Mode/Band               | Channel |        |      |
|                         | Low     | Middle | High |
| GSM 850 GPRS 1 TX Slot  | 33.5    | 33.5   | 33.5 |
| GSM 850 GPRS 2 TX Slot  | 32      | 32     | 32   |
| GSM 850 GPRS 3 TX Slot  | 31      | 31     | 31   |
| GSM 850 GPRS 4 TX Slot  | 29      | 29     | 29   |
| GSM 850 EDGE 1 TX Slot  | 28      | 28     | 28   |
| GSM 850 EDGE 2 TX Slot  | 26.5    | 26.5   | 26.5 |
| GSM 850 EDGE 3 TX Slot  | 25.5    | 25.5   | 25.5 |
| GSM 850 EDGE 4 TX Slot  | 23.5    | 23.5   | 23.5 |
| GSM 1900 GPRS 1 TX Slot | 30      | 30     | 30   |
| GSM 1900 GPRS 2 TX Slot | 28.5    | 28.5   | 28.5 |
| GSM 1900 GPRS 3 TX Slot | 27.2    | 27.2   | 27.2 |
| GSM 1900 GPRS 4 TX Slot | 25.5    | 25.5   | 25.5 |
| GSM 1900 EDGE 1 TX Slot | 26      | 26     | 26   |
| GSM 1900 EDGE 2 TX Slot | 25.5    | 25.5   | 25.5 |
| GSM 1900 EDGE 3 TX Slot | 24      | 24     | 24   |
| GSM 1900 EDGE 4 TX Slot | 22      | 22     | 22   |
| WCDMA Band 2            | 23.2    | 23.2   | 23.2 |
| HSDPA                   | 20.5    | 20.5   | 20.5 |
| HSUPA                   | 20.5    | 20.5   | 20.5 |
| DC-HSDPA                | 22.5    | 22.5   | 22.5 |
| HSPA+                   | 22.5    | 22.5   | 22.5 |
| WCDMA Band 4            | 23.5    | 23.5   | 23.5 |
| HSDPA                   | 21      | 21     | 21   |
| HSUPA                   | 21      | 21     | 21   |
| DC-HSDPA                | 22.5    | 22.5   | 22.5 |
| HSPA+                   | 23      | 23     | 23   |
| WCDMA Band 5            | 24      | 24     | 24   |
| HSDPA                   | 22      | 22     | 22   |
| HSUPA                   | 21      | 21     | 21   |
| DC-HSDPA                | 23      | 23     | 23   |
| HSPA+                   | 23      | 23     | 23   |
| LTE Band 2(20M)         | 22.8    | 22.8   | 22.8 |
| LTE Band 4(20M)         | 23.5    | 23.5   | 23.5 |
| LTE Band 5(10M)         | 23.5    | 23.5   | 23.5 |
| LTE Band 7(20M)         | 22.5    | 22.5   | 22.5 |
| LTE Band 66(20M)        | 23.5    | 23.5   | 23.5 |
| WLAN 2.4G(802.11b)      | 15      | 15     | 15   |
| WLAN 2.4G(802.11g)      | 13      | 13     | 13   |
| WLAN 2.4G(802.11n ht20) | 12      | 12     | 12   |
| WLAN 5.2G(802.11a)      | 13.5    | 13.5   | 13.5 |
| WLAN 5.2G(802.11n20)    | 12.5    | 12.5   | 12.5 |
| WLAN 5.2G(802.11n40)    | 12      | /      | 12   |
| WLAN 5.2G(802.11ac20)   | 12.5    | 12.5   | 12.5 |

| Max Target Power(dBm) |         |        |      |
|-----------------------|---------|--------|------|
| Mode/Band             | Channel |        |      |
|                       | Low     | Middle | High |
| WLAN 5.2G(802.11ac40) | 12      | /      | 12   |
| WLAN 5.2G(802.11ac80) | /       | 11.5   | /    |
| WLAN 5.3G(802.11a)    | 13.5    | 13.5   | 13.5 |
| WLAN 5.3G(802.11n20)  | 13      | 13     | 13   |
| WLAN 5.3G(802.11n40)  | 12.5    | /      | 12.5 |
| WLAN 5.3G(802.11ac20) | 13      | 13     | 13   |
| WLAN 5.3G(802.11ac40) | 12.5    | /      | 12.5 |
| WLAN 5.3G(802.11ac80) | /       | 11.5   | /    |
| WLAN 5.6G(802.11a)    | 13.5    | 13.5   | 13.5 |
| WLAN 5.6G(802.11n20)  | 12.5    | 12.5   | 12.5 |
| WLAN 5.6G(802.11n40)  | 13      | 13     | 13   |
| WLAN 5.6G(802.11ac20) | 12.5    | 12.5   | 12.5 |
| WLAN 5.6G(802.11ac40) | 13      | 13     | 13   |
| WLAN 5.6G(802.11ac80) | 11.5    | 11.5   | 11.5 |
| WLAN 5.8G(802.11a)    | 14      | 14     | 14   |
| WLAN 5.8G(802.11n20)  | 12.5    | 12.5   | 12.5 |
| WLAN 5.8G(802.11n40)  | 13      | /      | 13   |
| WLAN 5.8G(802.11ac20) | 12.5    | 12.5   | 12.5 |
| WLAN 5.8G(802.11ac40) | 13      | /      | 13   |
| WLAN 5.8G(802.11ac80) | /       | 11.5   | /    |
| Bluetooth BDR/ EDR    | 3.5     | 4.5    | 3.5  |
| BLE                   | -4      | -3     | -4   |

**7.4 Test Results:****GPRS:**

| Band     | Channel No. | Frequency (MHz) | RF Output Power (dBm) |         |         |         |
|----------|-------------|-----------------|-----------------------|---------|---------|---------|
|          |             |                 | 1 slot                | 2 slots | 3 slots | 4 slots |
| GSM 850  | 128         | 824.2           | 32.77                 | 31.53   | 30.24   | 28.55   |
|          | 190         | 836.6           | <b>33.11</b>          | 31.80   | 30.80   | 28.90   |
|          | 251         | 848.8           | 32.55                 | 31.42   | 30.65   | 28.49   |
| GSM 1900 | 512         | 1850.2          | 29.37                 | 28.32   | 27.15   | 25.08   |
|          | 661         | 1880            | <b>29.54</b>          | 27.79   | 27.07   | 24.95   |
|          | 810         | 1909.8          | 28.80                 | 28.03   | 26.86   | 24.80   |

**EDGE:**

| Band     | Channel No. | Frequency (MHz) | RF Output Power (dBm) |         |         |         |
|----------|-------------|-----------------|-----------------------|---------|---------|---------|
|          |             |                 | 1 slot                | 2 slots | 3 slots | 4 slots |
| GSM 850  | 128         | 824.2           | 27.39                 | 26.23   | 24.94   | 23.08   |
|          | 190         | 836.6           | 27.22                 | 26.35   | 24.88   | 23.38   |
|          | 251         | 848.8           | 27.57                 | 26.36   | 24.71   | 23.19   |
| GSM 1900 | 512         | 1850.2          | 25.59                 | 24.79   | 23.60   | 21.13   |
|          | 661         | 1880            | 25.84                 | 24.75   | 23.26   | 21.33   |
|          | 810         | 1909.8          | 25.95                 | 25.19   | 23.72   | 21.43   |

**For SAR, the time based average power is relevant, the difference in between depends on the duty cycle of the TDMA signal.**

| Number of Time slot                                  | 1     | 2     | 3        | 4     |
|------------------------------------------------------|-------|-------|----------|-------|
| Duty Cycle                                           | 1:8   | 1:4   | 1:2.66   | 1:2   |
| Time based Ave. power compared to slotted Ave. power | -9 dB | -6 dB | -4.25 dB | -3 dB |
| Crest Factor                                         | 8     | 4     | 2.66     | 2     |

**The time based average power for GPRS**

| Band     | Channel No. | Frequency (MHz) | RF Output Power (dBm) |         |              |         |
|----------|-------------|-----------------|-----------------------|---------|--------------|---------|
|          |             |                 | 1 slot                | 2 slots | 3 slots      | 4 slots |
| GSM 850  | 128         | 824.2           | 23.77                 | 25.53   | 25.99        | 25.55   |
|          | 190         | 836.6           | 24.11                 | 25.8    | <b>26.55</b> | 25.9    |
|          | 251         | 848.8           | 23.55                 | 25.42   | 26.4         | 25.49   |
| GSM 1900 | 512         | 1850.2          | 20.37                 | 22.32   | <b>22.9</b>  | 22.08   |
|          | 661         | 1880            | 20.54                 | 21.79   | 22.82        | 21.95   |
|          | 810         | 1909.8          | 19.8                  | 22.03   | 22.61        | 21.8    |

**The time based average power for EDGE**

| Band     | Channel No. | Frequency (MHz) | RF Output Power (dBm) |         |         |         |
|----------|-------------|-----------------|-----------------------|---------|---------|---------|
|          |             |                 | 1 slot                | 2 slots | 3 slots | 4 slots |
| GSM 850  | 128         | 824.2           | 18.39                 | 20.23   | 20.69   | 20.08   |
|          | 190         | 836.6           | 18.22                 | 20.35   | 20.63   | 20.38   |
|          | 251         | 848.8           | 18.57                 | 20.36   | 20.46   | 20.19   |
| GSM 1900 | 512         | 1850.2          | 16.59                 | 18.79   | 19.35   | 18.13   |
|          | 661         | 1880            | 16.84                 | 18.75   | 19.01   | 18.33   |
|          | 810         | 1909.8          | 16.95                 | 19.19   | 19.47   | 18.43   |

**Note:**

1. Agilent Technologies Communication Tester (8960) was used for the measurement of GSM peak and average output power for active timeslots.
2. For GPRS, 1, 2, 3 and 4 timeslots has been activated separately with power level 3(850 MHz band) and 3(1900 MHz band).
3. According to KDB941225D01-SAR for EGPRS mode are not required when the source-based time-averaged output power for data mode is lower than that in the normal GPRS mode.

**WCDMA:****WCDMA Band 2:**

| Test Mode         | Conducted Average Output Power(dBm) |                |                 |
|-------------------|-------------------------------------|----------------|-----------------|
|                   | Lowest Channel                      | Middle Channel | Highest Channel |
| WCDMA             | 23.03                               | <b>23.09</b>   | 22.96           |
| HSDPA Subset 1    | 20.36                               | 20.09          | 20.36           |
| HSDPA Subset 2    | 19.99                               | 20.07          | 20.35           |
| HSDPA Subset 3    | 19.90                               | 20.01          | 20.00           |
| HSDPA Subset 4    | 19.73                               | 19.82          | 19.91           |
| HSUPA Subset 1    | 20.27                               | 20.07          | 20.12           |
| HSUPA Subset 2    | 19.95                               | 19.62          | 20.10           |
| HSUPA Subset 3    | 20.25                               | 19.98          | 19.72           |
| HSUPA Subset 4    | 19.91                               | 19.41          | 20.06           |
| HSUPA Subset 5    | 19.82                               | 19.78          | 20.00           |
| DC-HSDPA Subset 1 | 21.87                               | 21.92          | 21.88           |
| DC-HSDPA Subset 2 | 21.90                               | 22.03          | 22.14           |
| DC-HSDPA Subset 3 | 21.87                               | 22.08          | 22.17           |
| DC-HSDPA Subset 4 | 21.97                               | 22.12          | 22.15           |
| HSPA+             | 22.13                               | 21.90          | 22.01           |

**WCDMA Band 4:**

| Test Mode         | Conducted Average Output Power(dBm) |                |                 |
|-------------------|-------------------------------------|----------------|-----------------|
|                   | Lowest Channel                      | Middle Channel | Highest Channel |
| WCDMA             | 22.96                               | <b>23.27</b>   | 23.21           |
| HSDPA Subset 1    | 20.31                               | 20.39          | 20.47           |
| HSDPA Subset 2    | 20.80                               | 20.41          | 20.53           |
| HSDPA Subset 3    | 20.57                               | 20.53          | 20.89           |
| HSDPA Subset 4    | 20.55                               | 20.94          | 20.67           |
| HSUPA Subset 1    | 20.10                               | 20.57          | 20.21           |
| HSUPA Subset 2    | 20.56                               | 20.35          | 20.40           |
| HSUPA Subset 3    | 20.55                               | 20.12          | 20.06           |
| HSUPA Subset 4    | 20.82                               | 20.15          | 20.00           |
| HSUPA Subset 5    | 20.61                               | 20.06          | 20.16           |
| DC-HSDPA Subset 1 | 22.03                               | 22.05          | 22.06           |
| DC-HSDPA Subset 2 | 22.12                               | 22.15          | 21.99           |
| DC-HSDPA Subset 3 | 22.25                               | 22.04          | 21.86           |
| DC-HSDPA Subset 4 | 22.37                               | 22.20          | 22.01           |
| HSPA+             | 22.76                               | 22.28          | 22.16           |

**WCDMA Band 5:**

| Test Mode         | Conducted Average Output Power(dBm) |                |                 |
|-------------------|-------------------------------------|----------------|-----------------|
|                   | Lowest Channel                      | Middle Channel | Highest Channel |
| WCDMA             | <b>23.57</b>                        | 23.19          | 23.24           |
| HSDPA Subset 1    | 21.18                               | 21.53          | 20.95           |
| HSDPA Subset 2    | 21.09                               | 20.86          | 21.09           |
| HSDPA Subset 3    | 21.61                               | 21.43          | 20.98           |
| HSDPA Subset 4    | 21.38                               | 21.21          | 21.27           |
| HSUPA Subset 1    | 20.98                               | 20.39          | 20.36           |
| HSUPA Subset 2    | 20.56                               | 20.58          | 20.44           |
| HSUPA Subset 3    | 20.69                               | 20.84          | 20.50           |
| HSUPA Subset 4    | 20.67                               | 20.35          | 20.55           |
| HSUPA Subset 5    | 20.40                               | 20.59          | 20.99           |
| DC-HSDPA Subset 1 | 22.49                               | 22.15          | 22.20           |
| DC-HSDPA Subset 2 | 22.33                               | 22.11          | 22.37           |
| DC-HSDPA Subset 3 | 22.41                               | 22.20          | 22.35           |
| DC-HSDPA Subset 4 | 22.65                               | 22.03          | 22.52           |
| HSPA+             | 22.62                               | 21.81          | 22.63           |

**Note:**

1. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC (reference measurement Channel) Configured in Test Loop Model 1.
2. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/DC-HSDPA/HSPA+ when the maximum average output of each RF channel is less than ¼ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.

**LTE Band 2:**

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
| 1.4M           | QPSK            | 1@0                        | 22.47             | 22.02                | 22.32              |
|                |                 | 1@3                        | <b>22.69</b>      | 22.45                | 22.30              |
|                |                 | 1@5                        | 22.38             | 22.44                | 22.23              |
|                |                 | 3@0                        | 22.38             | 22.27                | 22.31              |
|                |                 | 3@1                        | 22.39             | 22.47                | 22.30              |
|                |                 | 3@3                        | 22.48             | 22.40                | 22.43              |
|                |                 | 6@0                        | 21.25             | 21.30                | 21.20              |
|                | 16-QAM          | 1@0                        | 21.41             | 21.41                | 20.87              |
|                |                 | 1@3                        | 21.41             | 21.42                | 21.01              |
|                |                 | 1@5                        | 21.37             | 21.31                | 20.81              |
|                |                 | 3@0                        | 21.54             | 21.29                | 21.20              |
|                |                 | 3@1                        | 21.45             | 21.24                | 21.16              |
|                |                 | 3@3                        | 21.25             | 21.27                | 21.12              |
|                |                 | 6@0                        | 20.10             | 20.08                | 20.36              |
| 3M             | QPSK            | 1@0                        | 22.42             | 22.29                | 22.13              |
|                |                 | 1@8                        | 22.37             | 22.29                | 22.25              |
|                |                 | 1@14                       | 22.13             | 22.32                | 22.18              |
|                |                 | 8@0                        | 21.42             | 21.32                | 21.41              |
|                |                 | 8@4                        | 21.42             | 21.29                | 21.22              |
|                |                 | 8@7                        | 21.29             | 21.34                | 21.26              |
|                |                 | 15@0                       | 21.38             | 21.25                | 21.17              |
|                | 16-QAM          | 1@0                        | 20.93             | 21.29                | 20.87              |
|                |                 | 1@8                        | 20.96             | 21.38                | 20.83              |
|                |                 | 1@14                       | 21.01             | 21.15                | 20.86              |
|                |                 | 8@0                        | 20.16             | 19.92                | 19.94              |
|                |                 | 8@4                        | 20.17             | 20.12                | 19.90              |
|                |                 | 8@7                        | 20.25             | 20.09                | 20.00              |
|                |                 | 15@0                       | 20.19             | 20.11                | 19.89              |
| 5M             | QPSK            | 1@0                        | 22.17             | 22.07                | 22.23              |
|                |                 | 1@12                       | 22.64             | 22.48                | 22.28              |
|                |                 | 1@24                       | 22.16             | 22.09                | 22.01              |
|                |                 | 12@0                       | 21.42             | 21.28                | 21.31              |
|                |                 | 12@7                       | 21.39             | 21.42                | 21.33              |
|                |                 | 12@13                      | 21.49             | 21.40                | 21.31              |
|                |                 | 25@0                       | 21.43             | 21.24                | 21.32              |
|                | 16-QAM          | 1@0                        | 21.08             | 21.59                | 20.89              |
|                |                 | 1@12                       | 21.06             | 21.68                | 21.02              |
|                |                 | 1@24                       | 21.13             | 21.50                | 21.01              |
|                |                 | 12@0                       | 20.21             | 20.11                | 20.13              |
|                |                 | 12@7                       | 20.11             | 20.08                | 20.19              |
|                |                 | 12@13                      | 20.30             | 20.21                | 20.00              |
|                |                 | 25@0                       | 20.19             | 20.18                | 19.95              |
| 10M            | QPSK            | 1@0                        | 22.25             | 22.53                | 22.24              |

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
|                |                 | 1@25                       | 22.38             | 22.49                | 22.26              |
|                |                 | 1@49                       | 22.26             | 22.41                | 22.18              |
|                |                 | 25@0                       | 21.24             | 21.32                | 21.24              |
|                |                 | 25@12                      | 21.29             | 21.23                | 21.18              |
|                |                 | 25@25                      | 21.29             | 21.30                | 21.22              |
|                |                 | 50@0                       | 21.23             | 21.39                | 21.24              |
|                | 16-QAM          | 1@0                        | 20.81             | 21.10                | 20.69              |
|                |                 | 1@25                       | 21.24             | 21.41                | 20.98              |
|                |                 | 1@49                       | 20.90             | 21.19                | 20.78              |
|                |                 | 25@0                       | 20.13             | 20.09                | 20.17              |
|                |                 | 25@12                      | 20.23             | 20.10                | 20.20              |
|                |                 | 25@25                      | 20.22             | 20.11                | 20.27              |
|                |                 | 50@0                       | 20.10             | 20.06                | 20.04              |
| 15M            | QPSK            | 1@0                        | 22.11             | 22.48                | 22.25              |
|                |                 | 1@37                       | 22.34             | 22.69                | 22.34              |
|                |                 | 1@74                       | 22.07             | 22.59                | 22.24              |
|                |                 | 36@0                       | 21.38             | 21.25                | 21.36              |
|                |                 | 36@20                      | 21.27             | 21.45                | 21.40              |
|                |                 | 36@39                      | 21.25             | 21.19                | 21.23              |
|                |                 | 75@0                       | 21.25             | 21.50                | 21.28              |
|                | 16-QAM          | 1@0                        | 21.03             | 21.38                | 21.02              |
|                |                 | 1@37                       | 21.25             | 21.51                | 21.00              |
|                |                 | 1@74                       | 20.87             | 21.06                | 21.06              |
|                |                 | 36@0                       | 20.16             | 19.99                | 20.22              |
|                |                 | 36@20                      | 20.31             | 20.02                | 19.99              |
|                |                 | 36@39                      | 19.99             | 20.10                | 19.91              |
|                |                 | 75@0                       | 20.10             | 20.06                | 19.92              |
| 20M            | QPSK            | 1@0                        | 22.53             | 22.58                | 22.59              |
|                |                 | 1@49                       | 22.59             | 22.55                | 22.60              |
|                |                 | 1@99                       | 22.63             | 22.65                | 22.61              |
|                |                 | 50@0                       | 22.52             | 22.57                | 22.56              |
|                |                 | 50@24                      | 22.53             | 22.51                | 22.51              |
|                |                 | 50@50                      | 22.58             | 22.65                | 22.62              |
|                |                 | 100@0                      | 22.53             | 22.50                | 22.53              |
|                | 16-QAM          | 1@0                        | 21.64             | 21.61                | 21.57              |
|                |                 | 1@49                       | 21.64             | 21.63                | 21.60              |
|                |                 | 1@99                       | 21.60             | 21.55                | 21.54              |
|                |                 | 50@0                       | 21.59             | 21.54                | 21.58              |
|                |                 | 50@24                      | 21.61             | 21.61                | 21.63              |
|                |                 | 50@50                      | 21.63             | 21.62                | 21.58              |
|                |                 | 100@0                      | 21.65             | 21.68                | 21.63              |

**LTE Band 4:**

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
| 1.4M           | QPSK            | 1@0                        | 22.39             | 22.65                | 22.07              |
|                |                 | 1@3                        | 22.49             | 22.24                | 22.38              |
|                |                 | 1@5                        | 22.46             | 22.13                | 22.20              |
|                |                 | 3@0                        | 22.61             | 22.14                | 22.36              |
|                |                 | 3@1                        | 22.75             | 22.13                | 22.52              |
|                |                 | 3@3                        | 22.69             | 22.19                | 22.38              |
|                |                 | 6@0                        | 21.43             | 21.58                | 21.49              |
|                | 16-QAM          | 1@0                        | 21.12             | 21.04                | 21.00              |
|                |                 | 1@3                        | 21.09             | 21.57                | 20.89              |
|                |                 | 1@5                        | 21.18             | 21.03                | 21.01              |
|                |                 | 3@0                        | 21.48             | 21.36                | 21.38              |
|                |                 | 3@1                        | 21.49             | 21.38                | 21.33              |
|                |                 | 3@3                        | 21.45             | 21.37                | 21.25              |
|                |                 | 6@0                        | 20.64             | 19.70                | 20.43              |
| 3M             | QPSK            | 1@0                        | 22.55             | 22.45                | 22.71              |
|                |                 | 1@8                        | 22.58             | 21.89                | 22.64              |
|                |                 | 1@14                       | 22.55             | 22.00                | <b>22.80</b>       |
|                |                 | 8@0                        | 21.67             | 21.28                | 21.65              |
|                |                 | 8@4                        | 21.52             | 21.15                | 21.63              |
|                |                 | 8@7                        | 21.74             | 21.23                | 21.63              |
|                |                 | 15@0                       | 21.44             | 20.98                | 21.45              |
|                | 16-QAM          | 1@0                        | 21.03             | 20.79                | 21.54              |
|                |                 | 1@8                        | 21.04             | 20.76                | 21.63              |
|                |                 | 1@14                       | 21.09             | 20.87                | 21.45              |
|                |                 | 8@0                        | 20.42             | 19.83                | 20.42              |
|                |                 | 8@4                        | 20.30             | 20.00                | 20.40              |
|                |                 | 8@7                        | 20.25             | 20.07                | 20.52              |
|                |                 | 15@0                       | 20.22             | 20.12                | 20.27              |
| 5M             | QPSK            | 1@0                        | 22.27             | 22.62                | 22.03              |
|                |                 | 1@12                       | 22.75             | 22.11                | 22.44              |
|                |                 | 1@24                       | 22.41             | 22.01                | 22.18              |
|                |                 | 12@0                       | 21.56             | 21.09                | 21.60              |
|                |                 | 12@7                       | 21.46             | 21.31                | 21.55              |
|                |                 | 12@13                      | 21.73             | 21.07                | 21.49              |
|                |                 | 25@0                       | 21.61             | 21.24                | 21.42              |
|                | 16-QAM          | 1@0                        | 21.05             | 20.80                | 21.69              |
|                |                 | 1@12                       | 21.35             | 20.93                | 22.05              |
|                |                 | 1@24                       | 21.29             | 20.74                | 21.57              |
|                |                 | 12@0                       | 20.35             | 19.98                | 20.44              |
|                |                 | 12@7                       | 20.25             | 20.06                | 20.24              |
|                |                 | 12@13                      | 20.63             | 20.01                | 20.47              |
|                |                 | 25@0                       | 20.41             | 20.43                | 20.36              |
| 10M            | QPSK            | 1@0                        | 22.29             | 22.33                | 22.24              |

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
|                |                 | 1@25                       | 22.59             | 22.26                | 22.77              |
|                |                 | 1@49                       | 22.47             | 22.15                | 22.29              |
|                |                 | 25@0                       | 21.69             | 21.07                | 21.54              |
|                |                 | 25@12                      | 21.67             | 21.32                | 21.46              |
|                |                 | 25@25                      | 21.38             | 21.23                | 21.51              |
|                |                 | 50@0                       | 21.72             | 21.32                | 21.29              |
|                | 16-QAM          | 1@0                        | 20.58             | 20.96                | 21.31              |
|                |                 | 1@25                       | 20.92             | 20.98                | 21.71              |
|                |                 | 1@49                       | 20.77             | 20.79                | 21.51              |
|                |                 | 25@0                       | 20.17             | 20.04                | 20.27              |
|                |                 | 25@12                      | 20.35             | 20.01                | 20.43              |
|                |                 | 25@25                      | 20.59             | 20.16                | 20.34              |
|                |                 | 50@0                       | 20.34             | 19.89                | 20.32              |
| 15M            | QPSK            | 1@0                        | 22.47             | 21.93                | 22.09              |
|                |                 | 1@37                       | 22.76             | 22.20                | 22.65              |
|                |                 | 1@74                       | 22.34             | 22.14                | 21.98              |
|                |                 | 36@0                       | 21.05             | 21.25                | 21.70              |
|                |                 | 36@20                      | 21.50             | 21.35                | 21.44              |
|                |                 | 36@39                      | 21.54             | 21.16                | 21.63              |
|                |                 | 75@0                       | 21.57             | 21.09                | 21.28              |
|                | 16-QAM          | 1@0                        | 21.05             | 20.63                | 21.62              |
|                |                 | 1@37                       | 21.22             | 20.97                | 21.71              |
|                |                 | 1@74                       | 21.03             | 20.81                | 21.60              |
|                |                 | 36@0                       | 19.92             | 19.81                | 20.43              |
|                |                 | 36@20                      | 19.91             | 19.79                | 20.48              |
|                |                 | 36@39                      | 20.18             | 19.98                | 20.32              |
|                |                 | 75@0                       | 20.06             | 19.99                | 20.21              |
| 20M            | QPSK            | 1@0                        | 22.21             | 21.84                | 21.65              |
|                |                 | 1@49                       | 22.41             | 22.31                | 21.90              |
|                |                 | 1@99                       | 22.25             | 21.88                | 21.72              |
|                |                 | 50@0                       | 21.66             | 21.35                | 21.98              |
|                |                 | 50@24                      | 21.36             | 21.03                | 21.44              |
|                |                 | 50@50                      | 21.54             | 21.12                | 21.07              |
|                |                 | 100@0                      | 21.55             | 21.35                | 21.24              |
|                | 16-QAM          | 1@0                        | 21.55             | 21.50                | 21.55              |
|                |                 | 1@49                       | 21.48             | 21.55                | 21.54              |
|                |                 | 1@99                       | 21.55             | 21.52                | 21.46              |
|                |                 | 50@0                       | 21.48             | 21.53                | 21.54              |
|                |                 | 50@24                      | 21.47             | 21.53                | 21.57              |
|                |                 | 50@50                      | 21.57             | 21.60                | 21.58              |
|                |                 | 100@0                      | 21.58             | 21.54                | 21.48              |

**LTE Band 5:**

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
| 1.4M           | QPSK            | 1@0                        | 22.84             | 22.74                | 22.82              |
|                |                 | 1@3                        | 23.05             | 23.04                | 22.42              |
|                |                 | 1@5                        | 22.96             | 23.05                | 22.51              |
|                |                 | 3@0                        | 23.20             | 23.03                | 22.47              |
|                |                 | 3@1                        | 22.77             | 22.86                | 22.42              |
|                |                 | 3@3                        | 22.62             | 22.58                | 22.54              |
|                |                 | 6@0                        | 22.06             | 21.81                | 21.50              |
|                | 16-QAM          | 1@0                        | 20.97             | 21.64                | 21.05              |
|                |                 | 1@3                        | 21.66             | 22.08                | 21.13              |
|                |                 | 1@5                        | 21.18             | 21.94                | 21.02              |
|                |                 | 3@0                        | 21.68             | 22.14                | 21.44              |
|                |                 | 3@1                        | 21.93             | 22.01                | 21.41              |
|                |                 | 3@3                        | 21.64             | 22.02                | 21.37              |
|                |                 | 6@0                        | 21.07             | 20.48                | 20.32              |
| 3M             | QPSK            | 1@0                        | 22.91             | 22.85                | 23.09              |
|                |                 | 1@8                        | 23.03             | 22.69                | 22.54              |
|                |                 | 1@14                       | 23.02             | 22.71                | 22.78              |
|                |                 | 8@0                        | 21.98             | 22.04                | 21.76              |
|                |                 | 8@4                        | 22.09             | 22.01                | 21.52              |
|                |                 | 8@7                        | 22.18             | 21.95                | 21.55              |
|                |                 | 15@0                       | 21.89             | 21.89                | 21.47              |
|                | 16-QAM          | 1@0                        | 21.26             | 21.58                | 21.63              |
|                |                 | 1@8                        | 21.29             | 21.55                | 21.71              |
|                |                 | 1@14                       | 21.63             | 21.52                | 21.59              |
|                |                 | 8@0                        | 20.51             | 20.87                | 20.21              |
|                |                 | 8@4                        | 20.50             | 20.69                | 20.51              |
|                |                 | 8@7                        | 20.81             | 20.64                | 20.47              |
|                |                 | 15@0                       | 20.68             | 20.74                | 20.27              |
| 5M             | QPSK            | 1@0                        | 23.02             | 22.88                | 22.84              |
|                |                 | 1@12                       | 23.14             | 22.68                | 23.17              |
|                |                 | 1@24                       | 22.88             | 22.43                | 22.36              |
|                |                 | 12@0                       | 21.42             | 21.89                | 21.59              |
|                |                 | 12@7                       | 21.69             | 22.01                | 21.63              |
|                |                 | 12@13                      | 22.07             | 22.20                | 21.44              |
|                |                 | 25@0                       | 21.56             | 22.13                | 21.56              |
|                | 16-QAM          | 1@0                        | 21.36             | 22.17                | 21.18              |
|                |                 | 1@12                       | 21.50             | 22.29                | 21.41              |
|                |                 | 1@24                       | 21.16             | 22.04                | 21.15              |
|                |                 | 12@0                       | 20.25             | 20.92                | 20.44              |
|                |                 | 12@7                       | 20.53             | 20.77                | 20.57              |
|                |                 | 12@13                      | 20.59             | 20.83                | 20.52              |
|                |                 | 25@0                       | 20.74             | 20.90                | 20.62              |
| 10M            | QPSK            | 1@0                        | 23.07             | 22.90                | 23.15              |

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
|                |                 | 1@25                       | 23.03             | 22.94                | <b>23.37</b>       |
|                |                 | 1@49                       | 22.80             | 22.60                | 22.79              |
|                |                 | 25@0                       | 22.25             | 21.94                | 21.73              |
|                |                 | 25@12                      | 22.17             | 22.00                | 22.09              |
|                |                 | 25@25                      | 22.16             | 21.98                | 22.05              |
|                |                 | 50@0                       | 22.15             | 21.78                | 22.10              |
|                | 16-QAM          | 1@0                        | 21.71             | 21.74                | 21.77              |
|                |                 | 1@25                       | 21.80             | 21.75                | 21.76              |
|                |                 | 1@49                       | 21.76             | 21.82                | 21.79              |
|                |                 | 25@0                       | 21.73             | 21.80                | 21.84              |
|                |                 | 25@12                      | 21.74             | 21.71                | 21.65              |
|                |                 | 25@25                      | 21.70             | 21.72                | 21.69              |
|                |                 | 50@0                       | 21.79             | 21.86                | 21.86              |

**LTE Band 7:**

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
| 5M             | QPSK            | 1@0                        | 21.52             | 21.47                | 21.30              |
|                |                 | 1@12                       | 21.97             | 21.46                | 21.47              |
|                |                 | 1@24                       | 21.27             | 21.14                | 21.18              |
|                |                 | 12@0                       | 20.39             | 20.36                | 20.26              |
|                |                 | 12@7                       | 20.24             | 20.72                | 20.27              |
|                |                 | 12@13                      | 20.56             | 20.50                | 20.49              |
|                |                 | 25@0                       | 20.26             | 20.65                | 20.30              |
|                | 16-QAM          | 1@0                        | 19.80             | 20.44                | 20.43              |
|                |                 | 1@12                       | 20.26             | 20.30                | 20.71              |
|                |                 | 1@24                       | 20.01             | 20.00                | 20.69              |
|                |                 | 12@0                       | 19.02             | 19.47                | 19.26              |
|                |                 | 12@7                       | 19.01             | 19.54                | 19.17              |
|                |                 | 12@13                      | 19.07             | 19.32                | 19.07              |
|                |                 | 25@0                       | 19.03             | 19.60                | 19.16              |
| 10M            | QPSK            | 1@0                        | 21.41             | 22.03                | 21.70              |
|                |                 | 1@25                       | 21.85             | <b>22.08</b>         | 21.45              |
|                |                 | 1@49                       | 21.24             | 22.03                | 21.39              |
|                |                 | 25@0                       | 20.39             | 21.04                | 20.49              |
|                |                 | 25@12                      | 20.29             | 21.03                | 20.46              |
|                |                 | 25@25                      | 20.17             | 20.82                | 20.54              |
|                |                 | 50@0                       | 20.83             | 21.04                | 20.57              |
|                | 16-QAM          | 1@0                        | 19.56             | 20.73                | 20.00              |
|                |                 | 1@25                       | 19.91             | 20.96                | 20.15              |
|                |                 | 1@49                       | 20.58             | 20.59                | 19.97              |
|                |                 | 25@0                       | 19.50             | 19.76                | 19.40              |
|                |                 | 25@12                      | 19.74             | 19.73                | 19.41              |
|                |                 | 25@25                      | 19.53             | 19.65                | 19.19              |
|                |                 | 50@0                       | 18.94             | 19.84                | 19.26              |
| 15M            | QPSK            | 1@0                        | 21.86             | 21.32                | 21.48              |
|                |                 | 1@37                       | 21.63             | 21.65                | 21.90              |
|                |                 | 1@74                       | 21.36             | 21.42                | 21.65              |
|                |                 | 36@0                       | 20.53             | 20.64                | 20.59              |
|                |                 | 36@20                      | 20.49             | 20.62                | 20.51              |
|                |                 | 36@39                      | 20.41             | 20.43                | 20.62              |
|                |                 | 75@0                       | 21.00             | 20.60                | 20.52              |
|                | 16-QAM          | 1@0                        | 20.15             | 19.95                | 20.35              |
|                |                 | 1@37                       | 20.18             | 20.32                | 20.80              |
|                |                 | 1@74                       | 20.03             | 19.91                | 20.54              |
|                |                 | 36@0                       | 19.11             | 19.15                | 19.17              |
|                |                 | 36@20                      | 19.01             | 19.63                | 19.31              |
|                |                 | 36@39                      | 19.04             | 19.60                | 19.38              |
|                |                 | 75@0                       | 19.13             | 19.17                | 19.32              |
| 20M            | QPSK            | 1@0                        | 21.90             | 21.90                | 21.83              |

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
|                |                 | 1@49                       | 21.88             | 21.87                | 21.88              |
|                |                 | 1@99                       | 21.88             | 21.93                | 21.98              |
|                |                 | 50@0                       | 21.84             | 21.88                | 21.93              |
|                |                 | 50@24                      | 21.88             | 21.87                | 21.92              |
|                |                 | 50@50                      | 21.94             | 21.89                | 21.93              |
|                |                 | 100@0                      | 21.84             | 21.88                | 21.91              |
|                | 16-QAM          | 1@0                        | 21.26             | 21.22                | 21.22              |
|                |                 | 1@49                       | 21.30             | 21.36                | 21.36              |
|                |                 | 1@99                       | 21.27             | 21.22                | 21.21              |
|                |                 | 50@0                       | 21.34             | 21.29                | 21.24              |
|                |                 | 50@24                      | 21.34             | 21.38                | 21.36              |
|                |                 | 50@50                      | 21.29             | 21.36                | 21.38              |
|                |                 | 100@0                      | 21.30             | 21.28                | 21.27              |

**LTE Band 66:**

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
| 1.4M           | QPSK            | 1@0                        | 22.46             | 22.06                | 22.46              |
|                |                 | 1@3                        | 22.19             | 22.31                | 22.18              |
|                |                 | 1@5                        | 21.96             | 21.77                | 22.28              |
|                |                 | 3@0                        | 22.08             | 21.92                | 22.19              |
|                |                 | 3@1                        | 22.10             | 21.95                | 22.19              |
|                |                 | 3@3                        | 22.04             | 22.26                | 22.19              |
|                |                 | 6@0                        | 21.44             | 20.90                | 20.90              |
|                | 16-QAM          | 1@0                        | 20.60             | 20.41                | 21.02              |
|                |                 | 1@3                        | 20.79             | 21.12                | 21.40              |
|                |                 | 1@5                        | 20.51             | 20.82                | 21.03              |
|                |                 | 3@0                        | 21.07             | 21.31                | 21.10              |
|                |                 | 3@1                        | 20.97             | 21.27                | 21.16              |
|                |                 | 3@3                        | 21.00             | 21.26                | 21.18              |
|                |                 | 6@0                        | 20.07             | 19.96                | 19.82              |
| 3M             | QPSK            | 1@0                        | 22.35             | 22.39                | 22.77              |
|                |                 | 1@8                        | 22.09             | 22.24                | 22.39              |
|                |                 | 1@14                       | 22.55             | 22.47                | 22.27              |
|                |                 | 8@0                        | 21.64             | 21.25                | 21.06              |
|                |                 | 8@4                        | 21.31             | 21.29                | 21.15              |
|                |                 | 8@7                        | 21.32             | 21.53                | 21.12              |
|                |                 | 15@0                       | 21.29             | 21.41                | 21.18              |
|                | 16-QAM          | 1@0                        | 20.77             | 21.11                | 21.33              |
|                |                 | 1@8                        | 20.73             | 20.97                | 21.35              |
|                |                 | 1@14                       | 20.86             | 21.15                | 21.30              |
|                |                 | 8@0                        | 19.82             | 20.33                | 19.83              |
|                |                 | 8@4                        | 19.74             | 20.35                | 19.90              |
|                |                 | 8@7                        | 20.11             | 20.50                | 20.03              |
|                |                 | 15@0                       | 19.66             | 20.44                | 19.90              |
| 5M             | QPSK            | 1@0                        | 22.35             | 22.27                | 22.29              |
|                |                 | 1@12                       | 22.65             | 22.25                | 22.08              |
|                |                 | 1@24                       | 21.89             | 22.16                | 21.99              |
|                |                 | 12@0                       | 21.43             | 21.49                | 21.15              |
|                |                 | 12@7                       | 21.09             | 21.57                | 21.18              |
|                |                 | 12@13                      | 21.48             | 21.58                | 21.04              |
|                |                 | 25@0                       | 21.23             | 21.57                | 21.20              |
|                | 16-QAM          | 1@0                        | 20.70             | 21.16                | 21.20              |
|                |                 | 1@12                       | 21.02             | 21.12                | 21.62              |
|                |                 | 1@24                       | 20.74             | 20.92                | 21.39              |
|                |                 | 12@0                       | 19.80             | 20.25                | 19.86              |
|                |                 | 12@7                       | 20.23             | 20.25                | 19.95              |
|                |                 | 12@13                      | 20.26             | 20.41                | 19.97              |
|                |                 | 25@0                       | 20.28             | 20.15                | 19.85              |
| 10M            | QPSK            | 1@0                        | 22.36             | 22.04                | 22.58              |

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|-------------------|----------------------|--------------------|
|                |                 | 1@25                       | 22.37             | 22.35                | 22.45              |
|                |                 | 1@49                       | 22.04             | 21.98                | 22.25              |
|                |                 | 25@0                       | 21.12             | 21.17                | 21.09              |
|                |                 | 25@12                      | 21.19             | 21.13                | 21.24              |
|                |                 | 25@25                      | 21.08             | 21.16                | 21.18              |
|                |                 | 50@0                       | 21.58             | 21.09                | 21.13              |
|                | 16-QAM          | 1@0                        | 20.71             | 20.84                | 21.30              |
|                |                 | 1@25                       | 20.67             | 21.19                | 21.24              |
|                |                 | 1@49                       | 20.80             | 20.90                | 21.05              |
|                |                 | 25@0                       | 20.06             | 20.35                | 19.86              |
|                |                 | 25@12                      | 20.14             | 20.39                | 20.05              |
|                |                 | 25@25                      | 20.18             | 20.28                | 20.00              |
|                |                 | 50@0                       | 19.85             | 19.90                | 20.01              |
| 15M            | QPSK            | 1@0                        | 22.61             | 22.06                | 22.61              |
|                |                 | 1@37                       | 22.27             | 22.13                | <b>23.03</b>       |
|                |                 | 1@74                       | 22.12             | 22.06                | 22.79              |
|                |                 | 36@0                       | 21.20             | 21.29                | 21.74              |
|                |                 | 36@20                      | 21.10             | 21.31                | 21.55              |
|                |                 | 36@39                      | 21.30             | 21.15                | 21.64              |
|                |                 | 75@0                       | 21.72             | 21.25                | 21.80              |
|                | 16-QAM          | 1@0                        | 20.98             | 20.54                | 21.64              |
|                |                 | 1@37                       | 21.16             | 20.75                | 21.72              |
|                |                 | 1@74                       | 21.00             | 21.38                | 21.49              |
|                |                 | 36@0                       | 19.97             | 20.33                | 20.46              |
|                |                 | 36@20                      | 19.81             | 20.55                | 20.55              |
|                |                 | 36@39                      | 19.87             | 20.50                | 20.59              |
|                |                 | 75@0                       | 19.72             | 19.89                | 20.40              |
| 20M            | QPSK            | 1@0                        | 22.85             | 22.89                | 22.94              |
|                |                 | 1@49                       | 22.93             | 22.92                | 22.91              |
|                |                 | 1@99                       | 22.88             | 22.87                | 22.89              |
|                |                 | 50@0                       | 22.82             | 22.89                | 22.94              |
|                |                 | 50@24                      | 22.90             | 22.97                | 22.92              |
|                |                 | 50@50                      | 22.86             | 22.84                | 22.84              |
|                |                 | 100@0                      | 22.88             | 22.87                | 22.85              |
|                | 16-QAM          | 1@0                        | 22.19             | 22.16                | 22.13              |
|                |                 | 1@49                       | 22.11             | 22.15                | 22.20              |
|                |                 | 1@99                       | 22.14             | 22.20                | 22.25              |
|                |                 | 50@0                       | 22.19             | 22.26                | 22.23              |
|                |                 | 50@24                      | 22.12             | 22.13                | 22.06              |
|                |                 | 50@50                      | 22.20             | 22.19                | 22.12              |
|                |                 | 100@0                      | 22.10             | 22.14                | 22.17              |

**WLAN: 2.4G**

| Mode         | Channel frequency (MHz) | Data Rate | Duty cycle (%) | RF Output Power (dBm) |
|--------------|-------------------------|-----------|----------------|-----------------------|
| 802.11b      | 2412                    | 1Mbps     | 100            | 14.50                 |
|              | 2437                    |           |                | <b>14.94</b>          |
|              | 2462                    |           |                | 14.57                 |
| 802.11g      | 2412                    | 6Mbps     | 100            | 12.35                 |
|              | 2437                    |           |                | 12.62                 |
|              | 2462                    |           |                | 12.22                 |
| 802.11n ht20 | 2412                    | MCS0      | 100            | 11.81                 |
|              | 2437                    |           |                | 11.94                 |
|              | 2462                    |           |                | 11.14                 |

Note: The duty cycle test data and plots, please refer to the radio report: 2402U80198E-RF-00A.

**WLAN: 5.2G**

| Mode       | Channel frequency (MHz) | Data Rate | Duty cycle (%) | RF Output Power (dBm) |
|------------|-------------------------|-----------|----------------|-----------------------|
| 802.11a    | 5180                    | 6Mbps     | 100            | 13.21                 |
|            | 5200                    |           |                | 13.12                 |
|            | 5240                    |           |                | <b>13.22</b>          |
| 802.11n20  | 5180                    | MCS0      | 100            | 11.67                 |
|            | 5200                    |           |                | 12.19                 |
|            | 5240                    |           |                | 12.42                 |
| 802.11n40  | 5190                    | MCS0      | 100            | 11.50                 |
|            | 5230                    |           |                | 11.75                 |
| 802.11ac20 | 5180                    | MCS0      | 100            | 11.43                 |
|            | 5200                    |           |                | 11.86                 |
|            | 5240                    |           |                | 12.16                 |
| 802.11ac40 | 5190                    | MCS0      | 100            | 11.18                 |
|            | 5230                    |           |                | 11.03                 |
| 802.11ac80 | 5210                    | MCS0      | 88.04          | 11.08                 |

Note: The duty cycle test data and plots, please refer to the radio report: 2402U80198E-RF-00D.

**WLAN: 5.3G**

| Mode       | Channel frequency (MHz) | Data Rate | Duty cycle (%) | RF Output Power (dBm) |
|------------|-------------------------|-----------|----------------|-----------------------|
| 802.11a    | 5260                    | 6Mbps     | 100            | 13.20                 |
|            | 5280                    |           |                | 13.11                 |
|            | 5320                    |           |                | <b>13.23</b>          |
| 802.11n20  | 5260                    | MCS0      | 100            | 12.55                 |
|            | 5280                    |           |                | 12.47                 |
|            | 5320                    |           |                | 12.22                 |
| 802.11n40  | 5270                    | MCS0      | 100            | 12.28                 |
|            | 5310                    |           |                | 12.06                 |
| 802.11ac20 | 5260                    | MCS0      | 100            | 12.37                 |
|            | 5280                    |           |                | 12.25                 |
|            | 5320                    |           |                | 12.16                 |
| 802.11ac40 | 5270                    | MCS0      | 100            | 12.19                 |
|            | 5310                    |           |                | 12.13                 |
| 802.11ac80 | 5290                    | MCS0      | 88.04          | 11.01                 |

*Note: The duty cycle test data and plots, please refer to the radio report: 2402U80198E-RF-00D.*

**WLAN: 5.6G**

| Mode       | Channel frequency (MHz) | Data Rate | Duty cycle (%) | RF Output Power (dBm) |
|------------|-------------------------|-----------|----------------|-----------------------|
| 802.11a    | 5500                    | 6Mbps     | 100            | 13.38                 |
|            | 5580                    |           |                | <b>13.44</b>          |
|            | 5700                    |           |                | 13.22                 |
|            | 5720                    |           |                | 13.29                 |
| 802.11n20  | 5500                    | MCS0      | 100            | 12.45                 |
|            | 5580                    |           |                | 12.34                 |
|            | 5700                    |           |                | 12.21                 |
|            | 5720                    |           |                | 12.06                 |
| 802.11n40  | 5510                    | MCS0      | 100            | 12.51                 |
|            | 5550                    |           |                | 12.34                 |
|            | 5670                    |           |                | 12.32                 |
|            | 5710                    |           |                | 12.02                 |
| 802.11ac20 | 5500                    | MCS0      | 100            | 12.33                 |
|            | 5580                    |           |                | 12.14                 |
|            | 5700                    |           |                | 12.01                 |
|            | 5720                    |           |                | 12.37                 |
| 802.11ac40 | 5510                    | MCS0      | 100            | 12.21                 |
|            | 5550                    |           |                | 12.29                 |
|            | 5670                    |           |                | 12.12                 |
|            | 5710                    |           |                | 11.98                 |
| 802.11ac80 | 5530                    | MCS0      | 88.04          | 11.34                 |
|            | 5610                    |           |                | 10.55                 |
|            | 5690                    |           |                | 10.81                 |

Note: The duty cycle test data and plots, please refer to the radio report: 2402U80198E-RF-00D.

**WLAN: 5.8G**

| Mode       | Channel frequency (MHz) | Data Rate | Duty cycle (%) | RF Output Power (dBm) |
|------------|-------------------------|-----------|----------------|-----------------------|
| 802.11a    | 5745                    | 6Mbps     | 100            | 13.44                 |
|            | 5785                    |           |                | <b>13.69</b>          |
|            | 5825                    |           |                | 13.52                 |
| 802.11n20  | 5745                    | MCS0      | 100            | 12.24                 |
|            | 5785                    |           |                | 12.17                 |
|            | 5825                    |           |                | 12.38                 |
| 802.11n40  | 5755                    | MCS0      | 100            | 12.55                 |
|            | 5795                    |           |                | 12.46                 |
| 802.11ac20 | 5745                    | MCS0      | 100            | 12.05                 |
|            | 5785                    |           |                | 12.03                 |
|            | 5825                    |           |                | 12.18                 |
| 802.11ac40 | 5755                    | MCS0      | 100            | 12.34                 |
|            | 5795                    |           |                | 12.22                 |
| 802.11ac80 | 5775                    | MCS0      | 88.04          | 10.92                 |


Note: The duty cycle test data and plots, please refer to the radio report: 2402U80198E-RF-00D.

**Bluetooth:**

| Mode                 | Channel frequency (MHz) | RF Output Power (dBm) |
|----------------------|-------------------------|-----------------------|
| BDR(GFSK)            | 2402                    | 3.01                  |
|                      | 2441                    | <b>4.33</b>           |
|                      | 2480                    | 3.42                  |
| EDR( $\pi/4$ -DQPSK) | 2402                    | 2.19                  |
|                      | 2441                    | 3.50                  |
|                      | 2480                    | 2.51                  |
| EDR(8DPSK)           | 2402                    | 2.24                  |
|                      | 2441                    | 3.53                  |
|                      | 2480                    | 2.56                  |
| BLE 1M               | 2402                    | -4.65                 |
|                      | 2440                    | -3.15                 |
|                      | 2480                    | -4.08                 |
| BLE 2M               | 2402                    | -4.70                 |
|                      | 2440                    | -3.26                 |
|                      | 2480                    | -4.06                 |

## 8. STANDALONE SAR TEST EXCLUSION CONSIDERATIONS

### 8.1 Antennas Location:



### 8.2 Antenna Distance To Edge

| Antenna Distance To Edge(mm)   |      |       |      |       |     |        |
|--------------------------------|------|-------|------|-------|-----|--------|
| Antenna                        | Back | Front | Left | Right | Top | Bottom |
| WWAN<br>Antenna(GSM/WCDMA/LTE) | < 5  | < 5   | 71   | < 5   | 35  | 113    |
| WLAN/BT Antenna                | < 5  | < 5   | < 5  | 74    | 40  | 111    |

### 8.3 Standalone SAR test exclusion considerations

| Mode       | Frequency (MHz) | Output Power (dBm) | Output Power (mW) | Distance (mm) | Calculated value | Threshold (1-g) | SAR Test Exclusion |
|------------|-----------------|--------------------|-------------------|---------------|------------------|-----------------|--------------------|
| WLAN 2.4G  | 2462            | 15                 | 31.62             | 0             | 9.9              | 3               | NO                 |
| Wi-Fi 5.2G | 5240            | 13.5               | 22.39             | 0             | 10.3             | 3               | NO                 |
| Wi-Fi 5.3G | 5320            | 13.5               | 22.39             | 0             | 10.3             | 3               | NO                 |
| Wi-Fi 5.6G | 5720            | 13.5               | 22.39             | 0             | 10.7             | 3               | NO                 |
| Wi-Fi 5.8G | 5825            | 14                 | 25.12             | 0             | 12.1             | 3               | NO                 |
| Bluetooth  | 2480            | 4.5                | 2.82              | 0             | 0.9              | 3               | YES                |

Note: The WLAN based average power for calculation. and bluetooth based peak output power for calculation.

## NOTE:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

According to KDB447498 D01 General RF Exposure Guidance v06: 4.3. General SAR test exclusion guidance

c) For frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

1) For test separation distances  $> 50$  mm and  $< 200$  mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$

2) For test separation distances  $\leq 50$  mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$

3) SAR measurement procedures are not established below 100 MHz

## Measurement Result:

For NFC, the power of EUT: E Field@3m is 74.33dBuV/m = -20.87dBm (0.008mW)

Note:  $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$  for  $d = 3$  m.

SAR test exclusion threshold for NFC(13.56MHz) separation distance  $< 50$ mm

$$= [474 * (1 + \log(100/f(\text{MHz}))) / 2]$$

$$= 443\text{mW}$$

$$> 0.008\text{mW}$$

## Conclusion:

The NFC SAR evaluation can be exempted.

**8.4 Standalone SAR estimation:**

| Mode    | Frequency (MHz) | Output Power (dBm) | Output Power (mW) | Distance (mm) | Estimated 1-g (W/kg) |
|---------|-----------------|--------------------|-------------------|---------------|----------------------|
| BT Body | 2480            | 4.5                | 2.82              | 10            | 0.06                 |

Note: The bluetooth based peak power for calculation.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{(\text{min. test separation distance, mm})^2} \right] \cdot \left[ \frac{1}{f(\text{GHz})} \right]$$

W/kg for test separation distances  $\leq 50$  mm;

where  $x = 7.5$  for 1-g SAR.

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion

**8.5 SAR test exclusion for the EUT edge considerations Result**

| Antenna Distance To Edge(mm) |            |            |            |            |            |            |
|------------------------------|------------|------------|------------|------------|------------|------------|
| Mode                         | Back       | Front      | Left       | Right      | Top        | Bottom     |
| BT                           | Exclusion* | Exclusion* | Exclusion* | Exclusion* | Exclusion* | Exclusion* |
| WLAN                         | Required   | Required   | Required   | Exclusion  | Exclusion  | Exclusion  |
| WWAN(GSM/WCDMA/LTE)          | Required   | Required   | Exclusion  | Required   | Exclusion  | Exclusion  |

Note:

**Required:** The distance to Edge is less than 25mm, testing is required.

**Exclusion\*:** SAR test exclusion evaluation has been done above.

**Exclusion:** The distance to Edge is more than 25 mm, testing is not required.

**Extremity Exposure Considerations**

Per KDB 648474 D04 D04v01r03, this device is considered a “Phablet” since the diagonal dimension is  $>160$ mm and  $< 200$ mm, when hotspot mode applies, extremity SAR is required only for the surfaces and edges with hotspot mode scaled to the maximum output power (with tolerance is 1g SAR  $> 1.2$ W/kg)

| Extremity Exposure Condition |                   |                          |
|------------------------------|-------------------|--------------------------|
| Worst Mode                   | Hotspot SAR value | Extremity Condition Test |
| GSM 1900                     | 1.47W/kg          | Required                 |

## 9. SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

### 9.1 SAR Test Data

#### Environmental Conditions

|                           |              |              |              |              |
|---------------------------|--------------|--------------|--------------|--------------|
| <b>Temperature:</b>       | 22.9-23.6 °C | 22.5-23.1 °C | 22.5-23.4 °C | 22.7-23.5 °C |
| <b>Relative Humidity:</b> | 34%          | 43%          | 63%          | 40%          |
| <b>ATM Pressure:</b>      | 99.9 kPa     | 100.9 kPa    | 100.2 kPa    | 100.8 kPa    |
| <b>Test Date:</b>         | 2024/8/29    | 2024/9/1     | 2024/9/2     | 2024/9/3     |

Testing was performed by Lily Yang, Petre Ma, Mark Dong.

**GSM 850:**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 824.2           | GPRS      | /                      | /                      | /             | /         | /           | /    |
|                   | 836.6           | GPRS      | 30.8                   | 31                     | 1.047         | 0.340     | 0.36        | /    |
|                   | 848.8           | GPRS      | /                      | /                      | /             | /         | /           | /    |
| Body Back (10mm)  | 824.2           | GPRS      | /                      | /                      | /             | /         | /           | /    |
|                   | 836.6           | GPRS      | 30.8                   | 31                     | 1.047         | 0.301     | 0.32        | /    |
|                   | 848.8           | GPRS      | /                      | /                      | /             | /         | /           | /    |
| Body Right (10mm) | 824.2           | GPRS      | /                      | /                      | /             | /         | /           | /    |
|                   | 836.6           | GPRS      | 30.8                   | 31                     | 1.047         | 0.619     | <b>0.65</b> | 1#   |
|                   | 848.8           | GPRS      | /                      | /                      | /             | /         | /           | /    |

**Note:**

1. When the SAR value is less than half of the limit, testing for low and high channel is optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is > 0.5 dB, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 2DL+3UL is the worst case.

**GSM 1900:****Body Mode**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 1850.2          | GPRS      | /                      | /                      | /             | /         | /           | /    |
|                   | 1880            | GPRS      | 27.07                  | 27.2                   | 1.03          | 0.093     | 0.1         | /    |
|                   | 1909.8          | GPRS      | /                      | /                      | /             | /         | /           | /    |
| Body Back (10mm)  | 1850.2          | GPRS      | /                      | /                      | /             | /         | /           | /    |
|                   | 1880            | GPRS      | 27.07                  | 27.2                   | 1.03          | 0.292     | 0.3         | /    |
|                   | 1909.8          | GPRS      | /                      | /                      | /             | /         | /           | /    |
| Body Right (10mm) | 1850.2          | GPRS      | 27.15                  | 27.2                   | 1.012         | 1.24      | 1.26        | /    |
|                   | 1880            | GPRS      | 27.07                  | 27.2                   | 1.03          | 1.17      | 1.21        | /    |
|                   | 1909.8          | GPRS      | 26.86                  | 27.2                   | 1.081         | 1.36      | <b>1.47</b> | 2#   |

**Limb Mode**

| EUT Position     | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 10g SAR (W/kg) |           |             |      |
|------------------|-----------------|-----------|------------------------|------------------------|----------------|-----------|-------------|------|
|                  |                 |           |                        |                        | Scaled Factor  | Meas. SAR | Scaled SAR  | Plot |
| Limb Right (0mm) | 1850.2          | GPRS      | 27.15                  | 27.2                   | 1.012          | 2.01      | 2.03        | /    |
|                  | 1880            | GPRS      | 27.07                  | 27.2                   | 1.03           | 2.24      | 2.31        | /    |
|                  | 1909.8          | GPRS      | 26.86                  | 27.2                   | 1.081          | 2.66      | <b>2.88</b> | 3#   |

**Note:**

1. When the SAR value is less than half of the limit, testing for low and high channel is optional.
2. The EUT transmit and receive through the same GSM antenna while testing SAR.
3. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
4. When the maximum output power variation across the required test channels is > 0.5 dB, instead of the middle channel, the highest output power channel must be used.
5. The Multi-slot Classes of EUT is Class 12 which has maximum 4 Downlink slots and 4 Uplink slots, the maximum active slots is 5, when perform the multiple slots scan, 2DL+3UL is the worst case.

**WCDMA Band 2:****Body Mode**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 1852.4          | RMC       | /                      | /                      | /             | /         | /           | /    |
|                   | 1880            | RMC       | 23.09                  | 23.2                   | 1.026         | 0.145     | 0.15        | /    |
|                   | 1907.6          | RMC       | /                      | /                      | /             | /         | /           | /    |
| Body Back (10mm)  | 1852.4          | RMC       | /                      | /                      | /             | /         | /           | /    |
|                   | 1880            | RMC       | 23.09                  | 23.2                   | 1.026         | 0.516     | 0.53        | /    |
|                   | 1907.6          | RMC       | /                      | /                      | /             | /         | /           | /    |
| Body Right (10mm) | 1852.4          | RMC       | 23.03                  | 23.2                   | 1.04          | 1.28      | 1.33        | /    |
|                   | 1880            | RMC       | 23.09                  | 23.2                   | 1.026         | 1.29      | 1.32        | /    |
|                   | 1907.6          | RMC       | 22.96                  | 23.2                   | 1.057         | 1.38      | <b>1.46</b> | 4#   |

**Limb Mode**

| EUT Position     | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 10g SAR (W/kg) |           |             |      |
|------------------|-----------------|-----------|------------------------|------------------------|----------------|-----------|-------------|------|
|                  |                 |           |                        |                        | Scaled Factor  | Meas. SAR | Scaled SAR  | Plot |
| Limb Right (0mm) | 1852.4          | RMC       | 23.03                  | 23.2                   | 1.04           | 2.57      | 2.67        | /    |
|                  | 1880            | RMC       | 23.09                  | 23.2                   | 1.026          | 2.54      | 2.61        | /    |
|                  | 1907.6          | RMC       | 22.96                  | 23.2                   | 1.057          | 2.58      | <b>2.73</b> | 5#   |

**WCDMA Band 4:**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 1712.4          | RMC       | /                      | /                      | /             | /         | /           | /    |
|                   | 1732.6          | RMC       | 23.27                  | 23.5                   | 1.054         | 0.098     | 0.10        | /    |
|                   | 1752.6          | RMC       | /                      | /                      | /             | /         | /           | /    |
| Body Back (10mm)  | 1712.4          | RMC       | /                      | /                      | /             | /         | /           | /    |
|                   | 1732.6          | RMC       | 23.27                  | 23.5                   | 1.054         | 0.327     | 0.34        | /    |
|                   | 1752.6          | RMC       | /                      | /                      | /             | /         | /           | /    |
| Body Right (10mm) | 1712.4          | RMC       | 22.96                  | 23.5                   | 1.132         | 0.745     | 0.84        | /    |
|                   | 1732.6          | RMC       | 23.27                  | 23.5                   | 1.054         | 0.948     | 1.00        | /    |
|                   | 1752.6          | RMC       | 23.21                  | 23.5                   | 1.069         | 0.974     | <b>1.04</b> | 6#   |

**WCDMA Band 5:**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 826.4           | RMC       | /                      | /                      | /             | /         | /           | /    |
|                   | 836.6           | RMC       | 23.19                  | 24                     | 1.205         | 0.165     | 0.20        | /    |
|                   | 846.6           | RMC       | /                      | /                      | /             | /         | /           | /    |
| Body Back (10mm)  | 826.4           | RMC       | /                      | /                      | /             | /         | /           | /    |
|                   | 836.6           | RMC       | 23.19                  | 24                     | 1.205         | 0.140     | 0.17        | /    |
|                   | 846.6           | RMC       | /                      | /                      | /             | /         | /           | /    |
| Body Right (10mm) | 826.4           | RMC       | /                      | /                      | /             | /         | /           | /    |
|                   | 836.6           | RMC       | 23.19                  | 24                     | 1.205         | 0.260     | <b>0.31</b> | 7#   |
|                   | 846.6           | RMC       | /                      | /                      | /             | /         | /           | /    |

**Note:**

1. When the SAR value is less than half of the limit, testing for low and high channel is optional.
2. The EUT transmit and receive through the same antenna while testing SAR.
3. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2 kbps RMC(reference measurement Channel) Configured in Test Loop Model.
4. KDB 941225 D01-Body SAR is not required for HSDPA/HSUPA/DC-HSDPA/HSPA+ when the maximum average output of each RF channel is less than ¼ dB higher than measured 12.2kbps RMC or the maximum SAR for 12.2kbps RMC is < 75% of SAR limit.
5. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

**LTE Band 2:****Body Mode**

| EUT Position      | Frequency (MHz) | Bandwidth (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |           |             |      |
|-------------------|-----------------|-----------------|-----------|------------------------|------------------------|---------------|-----------|-------------|------|
|                   |                 |                 |           |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 1860            | 20M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 1880            | 20M             | 1RB       | 22.65                  | 22.8                   | 1.035         | 0.123     | 0.13        | /    |
|                   | 1900            | 20M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 1880            | 20M             | 50%RB     | 22.65                  | 22.8                   | 1.035         | 0.103     | 0.11        | /    |
| Body Back (10mm)  | 1860            | 20M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 1880            | 20M             | 1RB       | 22.65                  | 22.8                   | 1.035         | 0.440     | 0.46        | /    |
|                   | 1900            | 20M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 1880            | 20M             | 50%RB     | 22.65                  | 22.8                   | 1.035         | 0.359     | 0.37        | /    |
| Body Right (10mm) | 1860            | 20M             | 1RB       | 22.63                  | 22.8                   | 1.04          | 1.19      | 1.24        | /    |
|                   | 1880            | 20M             | 1RB       | 22.65                  | 22.8                   | 1.035         | 1.24      | 1.28        | /    |
|                   | 1900            | 20M             | 1RB       | 22.61                  | 22.8                   | 1.045         | 1.37      | <b>1.43</b> | 8#   |
|                   | 1860            | 20M             | 50%RB     | 22.58                  | 22.8                   | 1.052         | 1.18      | 1.24        | /    |
|                   | 1880            | 20M             | 50%RB     | 22.65                  | 22.8                   | 1.035         | 1.01      | 1.05        | /    |
|                   | 1900            | 20M             | 50%RB     | 22.62                  | 22.8                   | 1.042         | 1.25      | 1.30        | /    |
|                   | 1900            | 20M             | 100%RB    | 22.53                  | 22.8                   | 1.064         | 1.2       | 1.28        | /    |

**Limb Mode**

| EUT Position     | Frequency (MHz) | Bandwidth (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 10g SAR (W/kg) |           |             |      |
|------------------|-----------------|-----------------|-----------|------------------------|------------------------|----------------|-----------|-------------|------|
|                  |                 |                 |           |                        |                        | Scaled Factor  | Meas. SAR | Scaled SAR  | Plot |
| Limb Right (0mm) | 1860            | 20M             | 1RB       | 22.63                  | 22.8                   | 1.04           | 2.61      | 2.71        | /    |
|                  | 1880            | 20M             | 1RB       | 22.65                  | 22.8                   | 1.035          | 2.65      | <b>2.74</b> | 9#   |
|                  | 1900            | 20M             | 1RB       | 22.61                  | 22.8                   | 1.045          | 2.58      | 2.7         | /    |
|                  | 1860            | 20M             | 50%RB     | 22.58                  | 22.8                   | 1.052          | 2.07      | 2.18        | /    |
|                  | 1880            | 20M             | 50%RB     | 22.65                  | 22.8                   | 1.035          | 2.13      | 2.21        | /    |
|                  | 1900            | 20M             | 50%RB     | 22.62                  | 22.8                   | 1.042          | 2.09      | 2.18        | /    |
|                  | 1880            | 20M             | 100%RB    | 22.5                   | 22.8                   | 1.072          | 2.04      | 2.19        | /    |

**LTE Band 5:**

| EUT Position      | Frequency (MHz) | Bandwidth (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |           |             |      |
|-------------------|-----------------|-----------------|-----------|------------------------|------------------------|---------------|-----------|-------------|------|
|                   |                 |                 |           |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 829             | 10M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 836.5           | 10M             | 1RB       | 22.94                  | 23.5                   | 1.138         | 0.195     | 0.22        | /    |
|                   | 844             | 10M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 836.5           | 10M             | 50%RB     | 22                     | 23.5                   | 1.413         | 0.156     | 0.22        | /    |
| Body Back (10mm)  | 829             | 10M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 836.5           | 10M             | 1RB       | 22.94                  | 23.5                   | 1.138         | 0.108     | 0.12        | /    |
|                   | 844             | 10M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 836.5           | 10M             | 50%RB     | 22                     | 23.5                   | 1.413         | 0.087     | 0.12        | /    |
| Body Right (10mm) | 829             | 10M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 836.5           | 10M             | 1RB       | 22.94                  | 23.5                   | 1.138         | 0.286     | <b>0.33</b> | 10#  |
|                   | 844             | 10M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 836.5           | 10M             | 50%RB     | 22                     | 23.5                   | 1.413         | 0.229     | 0.32        | /    |

**LTE Band 7:**

| EUT Position      | Frequency (MHz) | Bandwidth (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |           |             |      |
|-------------------|-----------------|-----------------|-----------|------------------------|------------------------|---------------|-----------|-------------|------|
|                   |                 |                 |           |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 2510            | 20M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 2535            | 20M             | 1RB       | 21.93                  | 22.5                   | 1.14          | 0.129     | 0.15        | /    |
|                   | 2560            | 20M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 2535            | 20M             | 50%RB     | 21.89                  | 22.5                   | 1.151         | 0.103     | 0.12        | /    |
| Body Back (10mm)  | 2510            | 20M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 2535            | 20M             | 1RB       | 21.93                  | 22.5                   | 1.14          | 0.354     | 0.4         | /    |
|                   | 2560            | 20M             | 1RB       | /                      | /                      | /             | /         | /           | /    |
|                   | 2535            | 20M             | 50%RB     | 21.89                  | 22.5                   | 1.151         | 0.284     | 0.33        | /    |
| Body Right (10mm) | 2510            | 20M             | 1RB       | 21.88                  | 22.5                   | 1.153         | 0.778     | 0.9         | /    |
|                   | 2535            | 20M             | 1RB       | 21.93                  | 22.5                   | 1.14          | 0.908     | <b>1.04</b> | 11#  |
|                   | 2560            | 20M             | 1RB       | 21.98                  | 22.5                   | 1.127         | 0.739     | 0.83        | /    |
|                   | 2535            | 20M             | 50%RB     | 21.89                  | 22.5                   | 1.151         | 0.637     | 0.73        | /    |
|                   | 2535            | 20M             | 100%RB    | 21.88                  | 22.5                   | 1.153         | 0.621     | 0.72        | /    |

**LTE Band 66&4:**

| EUT Position      | Frequency (MHz) | Bandwidth (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |           |            |      |
|-------------------|-----------------|-----------------|-----------|------------------------|------------------------|---------------|-----------|------------|------|
|                   |                 |                 |           |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR | Plot |
| Body Front (10mm) | 1720            | 20M             | 1RB       | /                      | /                      | /             | /         | /          | /    |
|                   | 1745            | 20M             | 1RB       | 22.92                  | 23.5                   | 1.143         | 0.086     | 0.1        | /    |
|                   | 1770            | 20M             | 1RB       | /                      | /                      | /             | /         | /          | /    |
|                   | 1745            | 20M             | 50%RB     | 22.97                  | 23.5                   | 1.13          | 0.062     | 0.07       | /    |
| Body Back (10mm)  | 1720            | 20M             | 1RB       | /                      | /                      | /             | /         | /          | /    |
|                   | 1745            | 20M             | 1RB       | 22.92                  | 23.5                   | 1.143         | 0.347     | 0.4        | /    |
|                   | 1770            | 20M             | 1RB       | /                      | /                      | /             | /         | /          | /    |
|                   | 1745            | 20M             | 50%RB     | 22.97                  | 23.5                   | 1.13          | 0.288     | 0.33       | /    |
| Body Right (10mm) | 1720            | 20M             | 1RB       | 22.93                  | 23.5                   | 1.14          | 0.598     | 0.68       | /    |
|                   | 1745            | 20M             | 1RB       | 22.92                  | 23.5                   | 1.143         | 0.851     | 0.97       | /    |
|                   | 1770            | 20M             | 1RB       | 22.94                  | 23.5                   | 1.138         | 0.874     | <b>1</b>   | 12#  |
|                   | 1745            | 20M             | 50%RB     | 22.97                  | 23.5                   | 1.13          | 0.657     | 0.74       | /    |
|                   | 1770            | 20M             | 100%RB    | 22.85                  | 23.5                   | 1.161         | 0.641     | 0.74       | /    |

**Note:**

1. When the SAR value is less than half of the limit, testing for low and high channel is optional.
2. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02.
3. KDB941225D05-SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is > 0.5 dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg
4. KDB941225D05-For QPSK with 100% RB allocation, when the reported SAR measured for the Highest output power channel is <1.45 W/kg, tests for the remaining required test channels are optional.
5. KDB941225D05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg.
6. KDB941225D05- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offset the upper edge, middle and lower edge of each required test channel.
7. KDB941225D05- other channel bandwidths SAR test is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is > 0.5 dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

**WLAN 2.4G:**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |                   |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-------------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Duty cycle Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 2412            | 802.11b   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 2437            | 802.11b   | 14.94                  | 15                     | 1.014         | 1                 | 0.032     | 0.03        | /    |
|                   | 2462            | 802.11b   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Back (10mm)  | 2412            | 802.11b   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 2437            | 802.11b   | 14.94                  | 15                     | 1.014         | 1                 | 0.044     | 0.04        | /    |
|                   | 2462            | 802.11b   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Left (10mm)  | 2412            | 802.11b   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 2437            | 802.11b   | 14.94                  | 15                     | 1.014         | 1                 | 0.169     | <b>0.17</b> | 13#  |
|                   | 2462            | 802.11b   | /                      | /                      | /             | /                 | /         | /           | /    |

**Limb Mode**

| EUT Position    | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 10g SAR (W/kg) |                   |           |             |      |
|-----------------|-----------------|-----------|------------------------|------------------------|----------------|-------------------|-----------|-------------|------|
|                 |                 |           |                        |                        | Scaled Factor  | Duty cycle Factor | Meas. SAR | Scaled SAR  | Plot |
| Limb Left (0mm) | 2412            | 802.11b   | /                      | /                      | /              | /                 | /         | /           | /    |
|                 | 2437            | 802.11b   | 14.94                  | 15                     | 1.014          | 1                 | 0.438     | <b>0.44</b> | 14#  |
|                 | 2462            | 802.11b   | /                      | /                      | /              | /                 | /         | /           | /    |

**Note:**

1. When the SAR value is less than half of the limit, testing for low and high channel is optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.

**WLAN 5.2G:**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |                   |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-------------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Duty cycle Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 5180            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5200            | 802.11a   | 13.12                  | 13.5                   | 1.092         | 1                 | 0.110     | 0.12        | /    |
|                   | 5240            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Back (10mm)  | 5180            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5200            | 802.11a   | 13.12                  | 13.5                   | 1.092         | 1                 | 0.078     | 0.09        | /    |
|                   | 5240            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Left (10mm)  | 5180            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5200            | 802.11a   | 13.12                  | 13.5                   | 1.092         | 1                 | 0.595     | <b>0.65</b> | 15#  |
|                   | 5240            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |

**WLAN 5.3G:**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |                   |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-------------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Duty cycle Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 5260            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5280            | 802.11a   | 13.11                  | 13.5                   | 1.094         | 1                 | 0.123     | 0.13        | /    |
|                   | 5320            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Back (10mm)  | 5260            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5280            | 802.11a   | 13.11                  | 13.5                   | 1.094         | 1                 | 0.066     | 0.07        | /    |
|                   | 5320            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Left (10mm)  | 5260            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5280            | 802.11a   | 13.11                  | 13.5                   | 1.094         | 1                 | 0.585     | <b>0.64</b> | 16#  |
|                   | 5320            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |

**WLAN 5.6G:**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |                   |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-------------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Duty cycle Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 5500            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5580            | 802.11a   | 13.44                  | 13.5                   | 1.014         | 1                 | 0.159     | 0.16        | /    |
|                   | 5700            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5720            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Back (10mm)  | 5500            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5580            | 802.11a   | 13.44                  | 13.5                   | 1.014         | 1                 | 0.103     | 0.10        | /    |
|                   | 5700            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5720            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Left (10mm)  | 5500            | 802.11a   | 13.38                  | 13.5                   | 1.028         | 1                 | 0.839     | 0.86        | /    |
|                   | 5580            | 802.11a   | 13.44                  | 13.5                   | 1.014         | 1                 | 0.972     | 0.99        | /    |
|                   | 5700            | 802.11a   | 13.22                  | 13.5                   | 1.067         | 1                 | 1.07      | <b>1.14</b> | 17#  |
|                   | 5720            | 802.11a   | 13.29                  | 13.5                   | 1.05          | 1                 | 0.869     | 0.91        | /    |

**WLAN 5.8G:****Body Mode**

| EUT Position      | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/kg) |                   |           |             |      |
|-------------------|-----------------|-----------|------------------------|------------------------|---------------|-------------------|-----------|-------------|------|
|                   |                 |           |                        |                        | Scaled Factor | Duty cycle Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Front (10mm) | 5745            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5785            | 802.11a   | 13.69                  | 14                     | 1.074         | 1                 | 0.163     | 0.18        | /    |
|                   | 5825            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Back (10mm)  | 5745            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
|                   | 5785            | 802.11a   | 13.69                  | 14                     | 1.074         | 1                 | 0.137     | 0.15        | /    |
|                   | 5825            | 802.11a   | /                      | /                      | /             | /                 | /         | /           | /    |
| Body Left (10mm)  | 5745            | 802.11a   | 13.44                  | 14                     | 1.138         | 1                 | 1.01      | 1.15        | /    |
|                   | 5785            | 802.11a   | 13.69                  | 14                     | 1.074         | 1                 | 1.19      | 1.28        | /    |
|                   | 5825            | 802.11a   | 13.52                  | 14                     | 1.117         | 1                 | 1.26      | <b>1.41</b> | 18#  |

**Limb Mode**

| EUT Position    | Frequency (MHz) | Test Mode | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 10g SAR (W/kg) |                   |           |             |      |
|-----------------|-----------------|-----------|------------------------|------------------------|----------------|-------------------|-----------|-------------|------|
|                 |                 |           |                        |                        | Scaled Factor  | Duty cycle Factor | Meas. SAR | Scaled SAR  | Plot |
| Limb Left (0mm) | 5745            | 802.11a   | 13.44                  | 14                     | 1.138          | 1                 | 2.04      | 2.32        | /    |
|                 | 5785            | 802.11a   | 13.69                  | 14                     | 1.074          | 1                 | 2.05      | 2.20        | /    |
|                 | 5825            | 802.11a   | 13.52                  | 14                     | 1.117          | 1                 | 2.13      | <b>2.38</b> | 19#  |

**Note:**

1. When the SAR value is less than half of the limit, testing for low and high channel is optional.
2. When SAR or MPE is not measured at the maximum power level allowed for production units, the results must be scaled to the maximum tune-up tolerance limit according to the power applied to the individual channels tested to determine compliance.
3. For 802.11a mode power is the largest among 802.11a/n20/n40/ac, 802.11 a mode as initial test configuration is selected to test.
4. According KDB 248227 D01, for SAR testing of WLAN with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/( duty cycle)"..

## 10. MEASUREMENT VARIABILITY

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

*Note: The same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.*

### The Highest Measured SAR Configuration in Each Frequency Band

#### Body

| SAR probe calibration point | Frequency Band | Freq.(MHz) | EUT Position | Meas. SAR (W/kg) |          | Largest to Smallest SAR Ratio |
|-----------------------------|----------------|------------|--------------|------------------|----------|-------------------------------|
|                             |                |            |              | Original         | Repeated |                               |
| 1750MHz                     | WCDMA Band 4   | 1752.6     | Body Right   | 0.974            | 0.967    | 1.01                          |
| 1900MHz                     | WCDMA Band 2   | 1907.6     | Body Right   | 1.38             | 1.34     | 1.03                          |
| 2600MHz                     | LTE Band 7     | 2535       | Body Right   | 0.908            | 0.883    | 1.03                          |
| 5600MHz                     | WLAN 5.6G      | 5580       | Body Left    | 0.972            | 0.964    | 1.01                          |
| 5750MHz                     | WLAN 5.8G      | 5825       | Body Left    | 1.26             | 1.23     | 1.02                          |

#### Note:

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not  $> 1.20$ .
2. The measured SAR results **do not** have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
3. SAR measurement variability must be assessed for each frequency band, which is determined by the **SAR probe calibration point and tissue-equivalent medium** used for the device measurements.

## 11. DUT HOLDER PERTURBATIONS

In accordance with TCB workshop October 2016:

- 1) SAR perturbation due to test device holders, depending on antenna locations, buttons locations on phones or device, form factor (e.g. dongles etc.), the measured SAR could be influenced by the relative positions of the test device and its holder
- 2) SAR measurement standards have included protocols to evaluate this with a flat phantom, with and without the device holder
- 3) When the highest reported SAR of an antenna is  $> 1.2$  W/kg, holder perturbation verification is required for each antenna, using the highest SAR configuration among all applicable frequency bands in the same exact device and holder positions used for head and body SAR measurements; i.e. same device/button locations in the holder

Per IEEE 1528: 2013/Annex E/E.4.1.1: Device holder perturbation tolerance for a specific test device: Type B

When it is unknown if a device holder perturbs the fields of a test device, the SAR uncertainty shall be assessed with a flat phantom (see Clause 5) by comparing the SAR with and without the device holder according to the following tests:

The SAR tolerance for device holder disturbance is computed using Equation (E.21) and entered in the corresponding row of the appropriate uncertainty table with an assumed rectangular probability distribution and  $\nu_i = \infty$  degrees of freedom:

$$SAR_{\text{tolerance}} [\%] = 100 \times \left( \frac{SAR_{\text{w/ holder}} - SAR_{\text{w/o holder}}}{SAR_{\text{w/o holder}}} \right) \quad (\text{E.21})$$

### The Highest Measured SAR Configuration among all applicable Frequency Band

| Frequency Band | Freq.(MHz) | EUT Position | Meas. SAR (W/kg) |                | The Device holder perturbation uncertainty |
|----------------|------------|--------------|------------------|----------------|--------------------------------------------|
|                |            |              | With holder      | Without holder |                                            |
| 1900MHz        | 1909.8     | Limb Right   | 2.66             | 2.58           | 3.1%                                       |

## 12. SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

### 12.1 Simultaneous Transmission:

| Description of Simultaneous Transmit Capabilities |               |          |
|---------------------------------------------------|---------------|----------|
| Transmitter Combination                           | Simultaneous? | Hotspot? |
| WWAN(GSM/WCDMA/LTE) Antenna + WLAN 2.4G + NFC     | √             | √        |
| WWAN(GSM/WCDMA/LTE) Antenna + WLAN 5G + NFC       | √             | ×        |
| WWAN(GSM/WCDMA/LTE) Antenna + Bluetooth + NFC     | √             | ×        |
| WLAN 2.4G + Bluetooth                             | ×             | ×        |
| WLAN 5G + Bluetooth                               | ×             | ×        |
| WLAN 2.4G + WLAN 5G                               | ×             | ×        |

### 12.2 Simultaneous SAR test exclusion considerations:

#### Body Mode:

| Mode(SAR1+SAR2)                                      | Position   | SAR1 | SAR2 | ΣSAR < 1.6W/kg |
|------------------------------------------------------|------------|------|------|----------------|
| WWAN(GSM/WCDMA/LTE) Antenna + Bluetooth              | Body Front | 0.36 | 0.06 | 0.42           |
|                                                      | Body Back  | 0.53 | 0.06 | 0.59           |
|                                                      | Body Left  | NA   | 0.06 | 0.06           |
|                                                      | Body Right | 1.47 | 0.06 | <b>1.53</b>    |
| WWAN(GSM/WCDMA/LTE) Antenna + WLAN 2.4G              | Body Front | 0.36 | 0.03 | 0.39           |
|                                                      | Body Back  | 0.53 | 0.04 | 0.57           |
|                                                      | Body Left  | NA   | 0.17 | 0.17           |
|                                                      | Body Right | 1.47 | NA   | <b>1.47</b>    |
| WWAN(GSM/WCDMA/LTE) Antenna + WLAN 5G                | Body Front | 0.36 | 0.18 | 0.54           |
|                                                      | Body Back  | 0.53 | 0.15 | 0.68           |
|                                                      | Body Left  | NA   | 1.41 | 1.41           |
|                                                      | Body Right | 1.47 | NA   | 1.47           |
| WWAN(GSM/WCDMA/LTE) Antenna + WLAN 2.4G<br>(Hotspot) | Body Front | 0.36 | 0.03 | 0.39           |
|                                                      | Body Back  | 0.53 | 0.04 | 0.57           |
|                                                      | Body Left  | NA   | 0.17 | 0.17           |
|                                                      | Body Right | 1.47 | NA   | 1.47           |

#### Conclusion:

Sum of SAR:  $\Sigma\text{SAR} \leq 1.6 \text{ W/kg}$  therefore simultaneous transmission SAR with Volume Scans is **not required**.

**Limbs Mode:**

| Mode(SAR1+SAR2)                       | Position   | Reported SAR(W/kg) |      | $\Sigma$ SAR < 4.0W/kg |
|---------------------------------------|------------|--------------------|------|------------------------|
|                                       |            | SAR1               | SAR2 |                        |
| MAX.WWAN(GSM/WCDMA/LTE)+<br>WLAN 2.4G | Limb Left  | NA                 | 0.44 | 0.44                   |
|                                       | Limb Right | 2.88               | NA   | 2.88                   |
| MAX.WWAN(GSM/WCDMA/LTE)+<br>WLAN 5G   | Limb Left  | NA                 | 2.38 | 2.38                   |
|                                       | Limb Right | 2.88               | NA   | <b>2.88</b>            |

**Conclusion:**

Sum of SAR:  $\Sigma$ SAR  $\leq 4.0$  W/kg therefore simultaneous transmission SAR with Volume Scans is **not required**.

## APPENDIX A - MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

**Measurement uncertainty evaluation for IEEE1528-2013 SAR test**

| Uncertainty component                                                            | Tolerance/uncertainty<br>± % | Probability distribution | Divisor    | ci<br>(1 g)  | ci<br>(10 g) | Standard uncertainty<br>± %, (1 g) | Standard uncertainty<br>± %, (10 g) |
|----------------------------------------------------------------------------------|------------------------------|--------------------------|------------|--------------|--------------|------------------------------------|-------------------------------------|
| <b>Measurement system</b>                                                        |                              |                          |            |              |              |                                    |                                     |
| Probe calibration(k=1)                                                           | 6.55                         | N                        | 1          | 1            | 1            | 6.6                                | 6.6                                 |
| Axial isotropy                                                                   | 4.7                          | R                        | $\sqrt{3}$ | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 1.9                                | 1.9                                 |
| Hemispherical isotropy                                                           | 9.6                          | R                        | $\sqrt{3}$ | $\sqrt{0.5}$ | $\sqrt{0.5}$ | 3.9                                | 3.9                                 |
| Boundary effect                                                                  | 1.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 0.6                                | 0.6                                 |
| Linearity                                                                        | 4.7                          | R                        | $\sqrt{3}$ | 1            | 1            | 2.7                                | 2.7                                 |
| System detection limits                                                          | 1.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 0.6                                | 0.6                                 |
| Modulation response                                                              | 0.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 0.0                                | 0.0                                 |
| Readout electronics                                                              | 0.3                          | N                        | 1          | 1            | 1            | 0.3                                | 0.3                                 |
| Response time                                                                    | 0.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 0.0                                | 0.0                                 |
| Integration time                                                                 | 0.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 0.0                                | 0.0                                 |
| RF ambientconditions-noise                                                       | 1.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 0.6                                | 0.6                                 |
| RF ambient conditions-reflections                                                | 1.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 0.6                                | 0.6                                 |
| Probe positioner mech.tolerance                                                  | 0.8                          | R                        | $\sqrt{3}$ | 1            | 1            | 0.5                                | 0.5                                 |
| Probe positioning with respect to phantom shell                                  | 6.7                          | R                        | $\sqrt{3}$ | 1            | 1            | 3.9                                | 3.9                                 |
| Extrapolation, interpolation, and integrationsalgorithms for max. SAR evaluation | 2.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 1.2                                | 1.2                                 |
| <b>Test sample related</b>                                                       |                              |                          |            |              |              |                                    |                                     |
| Test sample positioning                                                          | 3.3                          | N                        | 1          | 1            | 1            | 3.3                                | 3.3                                 |
| Device holder uncertainty                                                        | 3.1                          | N                        | 1          | 1            | 1            | 3.1                                | 3.1                                 |
| Output power variation –SAR draft measurement                                    | 5.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 2.9                                | 2.9                                 |
| SAR scaling                                                                      | 2.8                          | R                        | $\sqrt{3}$ | 1            | 1            | 1.6                                | 1.6                                 |
| <b>Phantom and tissue parameters</b>                                             |                              |                          |            |              |              |                                    |                                     |
| Phantom shell uncertainty–shape, thicknessand permittivity                       | 4.0                          | R                        | $\sqrt{3}$ | 1            | 1            | 2.3                                | 2.3                                 |
| Uncertainty in SARcorrection for deviationsin permittivity and conductivity      | 1.9                          | N                        | 1          | 1            | 0.84         | 1.9                                | 1.6                                 |
| Liquid conductivity meas.                                                        | 2.5                          | N                        | 1          | 0.78         | 0.71         | 2.0                                | 1.8                                 |
| Liquid permittivity meas.                                                        | 2.5                          | N                        | 1          | 0.23         | 0.26         | 0.6                                | 0.7                                 |
| Liquid conductivity – temperatureuncertainty                                     | 1.7                          | R                        | $\sqrt{3}$ | 0.78         | 0.71         | 0.8                                | 0.7                                 |
| Liquid permittivity – temperatureuncertainty                                     | 0.3                          | R                        | $\sqrt{3}$ | 0.23         | 0.26         | 0.0                                | 0.0                                 |
| Combined standard uncertainty                                                    |                              | RSS                      |            |              |              | 12.1                               | 12.0                                |
| Expanded uncertainty (95 % confidence interval)                                  |                              | k=2                      |            |              |              | 23.2                               | 23.0                                |

## Measurement uncertainty evaluation for IEC62209-2 SAR test

| Source of uncertainty                                                        | Tolerance/<br>Uncertainty<br>value<br>± % | Probability<br>Distribution | Divisor    | ci<br>(1 g) | ci<br>(10 g) | Standard<br>uncertainty<br>± %, (1 g) | Standard<br>uncertainty<br>± %, (10 g) |
|------------------------------------------------------------------------------|-------------------------------------------|-----------------------------|------------|-------------|--------------|---------------------------------------|----------------------------------------|
| <b>Measurement system</b>                                                    |                                           |                             |            |             |              |                                       |                                        |
| Probe calibration                                                            | 6.55                                      | N                           | 1          | 1           | 1            | 6.6                                   | 6.6                                    |
| Isotropy                                                                     | 4.7                                       | R                           | $\sqrt{3}$ | 1           | 1            | 2.7                                   | 2.7                                    |
| Linearity                                                                    | 4.7                                       | R                           | $\sqrt{3}$ | 1           | 1            | 2.7                                   | 2.7                                    |
| Probe modulation response                                                    | 0.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 0.0                                   | 0.0                                    |
| Detection limits                                                             | 1.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| Boundary effect                                                              | 1.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| Readout electronics                                                          | 0.3                                       | N                           | 1          | 1           | 1            | 0.3                                   | 0.3                                    |
| Response time                                                                | 0.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 0.0                                   | 0.0                                    |
| Integration time                                                             | 0.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 0.0                                   | 0.0                                    |
| RF ambient conditions – noise                                                | 1.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| RF ambient conditions – reflections                                          | 1.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| Probe positioner mech. restrictions                                          | 0.8                                       | R                           | $\sqrt{3}$ | 1           | 1            | 0.5                                   | 0.5                                    |
| Probe positioning with respect to phantom shell                              | 6.7                                       | R                           | $\sqrt{3}$ | 1           | 1            | 3.9                                   | 3.9                                    |
| Post-processing                                                              | 2.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 1.2                                   | 1.2                                    |
| <b>Test sample related</b>                                                   |                                           |                             |            |             |              |                                       |                                        |
| Device holder uncertainty                                                    | 3.1                                       | N                           | 1          | 1           | 1            | 3.1                                   | 3.1                                    |
| Test sample positioning                                                      | 3.3                                       | N                           | 1          | 1           | 1            | 3.3                                   | 3.3                                    |
| Power scaling                                                                | 4.5                                       | R                           | $\sqrt{3}$ | 1           | 1            | 2.6                                   | 2.6                                    |
| Drift of output power (measured SAR drift)                                   | 5.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 2.9                                   | 2.9                                    |
| <b>Phantom and set-up</b>                                                    |                                           |                             |            |             |              |                                       |                                        |
| Phantom uncertainty (shape and thickness tolerances)                         | 4.0                                       | R                           | $\sqrt{3}$ | 1           | 1            | 2.3                                   | 2.3                                    |
| Algorithm for correcting SAR for deviations in permittivity and conductivity | 1.9                                       | N                           | 1          | 1           | 0.84         | 1.9                                   | 1.6                                    |
| Liquid conductivity (meas.)                                                  | 2.5                                       | N                           | 1          | 0.78        | 0.71         | 2.0                                   | 1.8                                    |
| Liquid permittivity (meas.)                                                  | 2.5                                       | N                           | 1          | 0.23        | 0.26         | 0.6                                   | 0.7                                    |
| Liquid conductivity – temperature uncertainty                                | 1.7                                       | R                           | $\sqrt{3}$ | 0.78        | 0.71         | 0.8                                   | 0.7                                    |
| Liquid permittivity – temperature uncertainty                                | 0.3                                       | R                           | $\sqrt{3}$ | 0.23        | 0.26         | 0.0                                   | 0.0                                    |
| Combined standard uncertainty                                                |                                           | RSS                         |            |             |              | 11.8                                  | 11.7                                   |
| Expanded uncertainty (95 % confidence interval)                              |                                           |                             |            |             |              | 22.4                                  | 22.2                                   |

---

## **APPENDIX B - SAR PLOTS**

---

Please refer to the attachment.

---

## **APPENDIX C - EUT TEST POSITION PHOTOS**

---

Please refer to the attachment.

---

## **APPENDIX D - PROBE CALIBRATION CERTIFICATES**

---

Please refer to the attachment.

---

## **APPENDIX E - DIPOLE CALIBRATION CERTIFICATES**

---

Please refer to the attachment.

**===== END OF REPORT =====**