



# TEST REPORT

**Applicant:** Shenzhen Xinguodu Technology Co., Ltd.

**Address:** 17B JinSong Mansion, Terra Industrial & Trade Park  
Chegongmiao, Futian District, Shenzhen, Guangdong, China.

**Product Name:** POS terminal

**FCC ID:** XDQN92-01

**47 CFR Part 15, Subpart C(15.247)**

**Standard(s):** ANSI C63.10-2013  
KDB 558074 D01 15.247 Meas Guidance v05r02

**Report Number:** 2402V85163E-RF-00AA1

**Report Date:** 2025/4/17

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

**Reviewed By:** Pedro Yun

**Approved By:** Gavin Xu

Title: Project Engineer

Title: RF Supervisor

---

**Bay Area Compliance Laboratories Corp. (Dongguan)**  
No.12, Pulong East 1<sup>st</sup> Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

[www.baclcorp.com.cn](http://www.baclcorp.com.cn)

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

## CONTENTS

<b>DOCUMENT REVISION HISTORY</b>	4
<b>1. GENERAL INFORMATION</b>	5
1.1 GENERAL DESCRIPTION OF EQUIPMENT UNDER TEST	5
1.2 ACCESSORY INFORMATION	5
1.3 ANTENNA INFORMATION DETAIL▲	6
1.4 EQUIPMENT MODIFICATIONS	6
<b>2. SUMMARY OF TEST RESULTS</b>	7
<b>3. DESCRIPTION OF TEST CONFIGURATION</b>	8
3.1 OPERATION FREQUENCY DETAIL	8
3.2 EUT OPERATION CONDITION	8
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	8
3.4 SUPPORT CABLE LIST AND DETAILS	8
3.5 BLOCK DIAGRAM OF TEST SETUP	9
3.6 TEST FACILITY	10
3.7 MEASUREMENT UNCERTAINTY	10
<b>4. REQUIREMENTS AND TEST PROCEDURES</b>	11
4.1 AC LINE CONDUCTED EMISSIONS	11
4.1.1 Applicable Standard	11
4.1.2 EUT Setup	12
4.1.3 EMI Test Receiver Setup	12
4.1.4 Test Procedure	13
4.1.5 Corrected Amplitude & Margin Calculation	13
4.1.6 Test Result	13
4.2 RADIATED SPURIOUS EMISSIONS	14
4.2.1 Applicable Standard	14
4.2.2 EUT Setup	14
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	16
4.2.4 Test Procedure	16
4.2.5 Corrected Result & Margin Calculation	17
4.2.6 Test Result	17
4.3 MAXIMUM CONDUCTED OUTPUT POWER	18
4.3.1 Applicable Standard	18
4.3.2 EUT Setup	18
4.3.3 Test Procedure	18
4.3.4 Test Result	18
4.4 ANTENNA REQUIREMENT	19
4.4.1 Applicable Standard	19
4.4.2 Judgment	19
<b>5. TEST DATA AND RESULTS</b>	20
5.1 AC LINE CONDUCTED EMISSIONS	20
5.2 RADIATED SPURIOUS EMISSIONS	23

<b>5.3 SPOT CHECK WITH MAXIMUM CONDUCTED OUTPUT POWER</b>	34
<b>EXHIBIT A - EUT PHOTOGRAPHS</b>	37
<b>EXHIBIT B - TEST SETUP PHOTOGRAPHS</b>	38
<b>EXHIBIT C - RF EXPOSURE EVALUATION</b>	39
<b>SAR EVALUATION</b>	39

## DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2402V85163E-RF-00A	Original Report	2024/10/25
2.0	2402V85163E-RF-00AA1	CIIPC Report	2025/4/17

Note: This is a CIIPC report application which was based on the original report. The differences between them as following:

1. Antenna changes(Bluetooth & wifi & GPS antenna).
2. Minor circuitry for non-transmitter portions.
  - a. Added a secondary screen , Back camera(200W) and Top camera (200W).
  - b. Deleted Fingerprint module , Audio jack and related circuits.
  - c. Added eMMC and LPDDR4X.
- 3.Added a Battery(Model: GX11).

The changes between the previous device and the current one is stated and guaranteed by the Applicant, the differences between them will affect the test items, we will change the test data, test photos , and the EUT photos.

## 1. GENERAL INFORMATION

### 1.1 General Description of Equipment under Test

<b>EUT Name:</b>	POS terminal
<b>EUT Model:</b>	N92
<b>Operation Frequency:</b>	2402-2480 MHz
<b>Maximum Peak Output Power (Conducted)▲:</b>	4.13dBm
<b>Modulation Type:</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK
<b>Rated Input Voltage:</b>	DC 7.2V from battery or DC 5V from adapter or DC 5V from Charging Base
<b>Serial Number:</b>	For Radiated Spurious Emission Below 1G Test: 2ZYH-2 (Configuration 3#) For RF Conducted /AC Line Conducted Emissions /Radiated Spurious Emission Above 1G Tests: 2ZYH-1 (Configuration 2#)
<b>EUT Received Date:</b>	2025/3/19
<b>EUT Received Status:</b>	Good

### 1.2 Accessory Information

<b>Accessory Description</b>	<b>Manufacturer</b>	<b>Model</b>	<b>Parameters</b>
Adapter	SHENZHEN RUIJING INDUSTRIAL CO.,LTD	STC-A520A-Z	Input: 100-240Vac~50/60Hz 400mA Output: 5.0Vdc 2000mA
Battery 1#	Zhengzhou BAK Battery Co.,Ltd	GX12	Typical Capacity:3300mAh Rated Capacity:3200mAh Typical Energy:23.76Wh Nominal Energy:23.04Wh Output: DC 7.2V
Battery 2# (new)	Zhengzhou BAK Battery Co.,Ltd	GX11	Typical Capacity:2600mAh Rated Capacity:2500mAh Typical Energy:18.72Wh Nominal Energy:18Wh Output: DC 7.2V

Note: Battery 1# and battery 2# are available in all configurations.

### Optional Material:

<b>Material Description</b>	<b>Manufacturer</b>	<b>Parameter</b>
Back Camera 1	/	500W
Back Camera 2	/	200W
Front Camera	/	200W
Top Camera	/	200W
eMMC 1	SAMSUNG	KLMBG2JETD-B041(32GB)
eMMC 2	FORESEE	FEMDNN032G-C9A55(32GB)
LPDDR4X 1	SAMSUNG	K4U6E3S4AB-MGCL(2GB)
LPDDR4X 2	ChangXin	CXDB4CBAM-MK-A(2GB)
Battery 1#	Zhengzhou BAK Battery Co.,Ltd	3300mAh
Battery 2#	Zhengzhou BAK Battery Co.,Ltd	2600mAh

**EUT Information:**

The following Configuration were select to test:

Items	Configuration 1# (old)	Configuration 2# (new)	Configuration 3# (new)
Front Camera	200W	200W	×
Back camera	500W	200W	200W
Top Camera	×	×	200W
Secondary screen	×	√	√
Fingerprint module	√	×	×
Audio jack	√	×	×
Flash lamp	√	×	√
Printer	√	×	×
Battery	Battery 1#	Battery 2#	Battery 1#
eMMC	SAMSUNG	FORESEE	FORESEE
LPDDR4X	SAMSUNG	ChangXin	ChangXin

**1.3 Antenna Information Detail▲**

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Shenzhen Xinguodu Technology Co., Ltd.	FPC	50	2400-2500MHz	-0.26dBi

**The design of compliance with §15.203:**

<input checked="" type="checkbox"/>	Unit uses a permanently attached antenna.
<input type="checkbox"/>	Unit uses a unique coupling to the intentional radiator.
<input type="checkbox"/>	Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

**1.4 Equipment Modifications**

No modifications are made to the EUT during all test items.

## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.207(a)	AC Line Conducted Emissions	Compliant
FCC §15.205, §15.209, §15.247(d)	Radiated Spurious Emissions	Compliant
FCC §15.247(a)(1)	20 dB Emission Bandwidth	Compliant*
FCC §15.247(a)(1)	Channel Separation	Compliant*
FCC §15.247(a)(1)(iii)	Number Of Hopping Frequency	Compliant*
FCC §15.247(a)(1)(iii)	Time Of Occupancy (dwell time)	Compliant*
FCC §15.247(b)(1)	Maximum Conducted Output Power	Reporting
FCC §15.247(d)	100 kHz Bandwidth Of Frequency Band Edge	Compliant*
FCC §15.203	Antenna Requirement	Compliant
§15.247 (i) & §1.1310 & §2.1093	SAR Evaluation	Compliant

Note 1:

For AC line conducted emissions and Radiated Spurious Emissions 9kHz~1GHz and 18~25GHz, the maximum output power mode and channel was tested.

Note 2: Per the original report: 2402V85163E-RF-00A<sup>▲</sup>, Powered by Adapter was the worst, so only performed it.

Note 3: Per BLE report, for AC Line Conducted Emissions , Configuration 2# & Battery 2# was the worst, and for Radiated Spurious Emissions Below 1G, Configuration 3# & Battery 1# was the worst, so only performed it.

Note 4:

Compliant\*: The change of the EUT does not affect the test result, please refer to the original report: 2402V85163E-RF-00A<sup>▲</sup>.

### 3. DESCRIPTION OF TEST CONFIGURATION

#### 3.1 Operation Frequency Detail

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	<b>2402</b>	40	2442
1	2404	41	2443
...	...	...	...
...	...	...	...
...	...	78	<b>2480</b>
39	<b>2441</b>	/	/

Note: The above frequencies in bold were performed the test.

#### 3.2 EUT Operation Condition

The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer.  
The EUT configuration as below:

<b>EUT Exercise Software:</b>	WIFI Tool for MT3031.exe		
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲ :			
Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
GFSK	6	6	6
$\pi/4$ -DQPSK	6	6	6
8DPSK	6	6	6

#### 3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

#### 3.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	no	no	1.5	Adapter	EUT

### 3.5 Block Diagram of Test Setup

AC Line Conducted Emissions:



Radiated Spurious Emission:



### 3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

### 3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz: 5.47 dB, 26.5GHz~40GHz: 5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

## 4. REQUIREMENTS AND TEST PROCEDURES

### 4.1 AC Line Conducted Emissions

#### 4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:


(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000  $\mu$ V within the frequency band 535-1705 kHz, as measured using a 50  $\mu$ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

#### 4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

#### 4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

#### 4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

#### 4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

#### 4.1.6 Test Result

Please refer to section 5.1.

## 4.2 Radiated Spurious Emissions


### 4.2.1 Applicable Standard



FCC §15.247 (d);

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 4.2.2 EUT Setup

9kHz~30MHz:



**30MHz~1GHz:****Above 1GHz:**

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

#### 4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	300 Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	10 kHz	30 kHz	9 kHz	QP/AV
30 MHz – 1000 MHz	PK	100 kHz	300 kHz	/	PK
	QP	/	/	120 kHz	QP

1GHz- 25GHz:

Pre-scan:

Measurement	RBW	Video B/W	Detector
PK	1MHz	3 MHz	PK
Ave.	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	RBW	Video B/W	Detector
PK	1MHz	3 MHz	PK
Ave.	1MHz	10 Hz	PK

#### 4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

#### **4.2.5 Corrected Result & Margin Calculation**

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “Margin” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

#### **4.2.6 Test Result**

Please refer to section 5.2.


### 4.3 Maximum Conducted Output Power

#### 4.3.1 Applicable Standard

FCC §15.247 (b)(1)

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

#### 4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

#### 4.3.3 Test Procedure

According to ANSI C63.10-2013 Section 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. Offset the Insertion loss of the RF cable, DC Block/ Attenuator into the spectrum analyzer. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
  - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
  - 2) RBW > 20 dB bandwidth of the emission being measured.
  - 3) VBW  $\geq$  RBW.
  - 4) Sweep: Auto.
  - 5) Detector function: Peak.
  - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

NOTE—A peak responding power meter may be used, where the power meter and sensor system video bandwidth is greater than the occupied bandwidth of the unlicensed wireless device, rather than a spectrum analyzer.

#### 4.3.4 Test Result

Please refer to section 5.3.

## 4.4 Antenna Requirement

### 4.4.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

### 4.4.2 Judgment

**Compliant.** Please refer to the Antenna Information detail in Section 1.3.

## 5. TEST DATA AND RESULTS

### 5.1 AC Line Conducted Emissions

Serial Number:	2ZYH-1	Test Date:	2025/04/01
Test Site:	CE	Test Mode:	Transmitting
Tester:	Yukin Qiu	Test Result:	Pass

#### Environmental Conditions:

Temperature: (°C)	21.4	Relative Humidity: (%)	41	ATM Pressure: (kPa)	101.4
-------------------	------	------------------------	----	---------------------	-------

#### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2024/9/5	2025/9/4
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2024/9/5	2025/9/4
R&S	EMI Test Receiver	ESCI	101121	2024/9/5	2025/9/4
Audix	Test Software	E3	191218 V9	N/A	N/A


\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### Test Data:

Note: BDR High channel was tested.

Project No.: 2402V85163E-RF-A1  
Port: Line  
Test Mode: Transmitting  
IF B/W 9KHz PK/AV


Serial No.: 2ZYH-1  
Tester: Yukin Qiu



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Measurement
1	0.49	38.33	10.84	49.17	56.23	7.06	QP
2	0.49	30.29	10.84	41.13	46.23	5.10	Average
3	0.53	41.29	10.83	52.12	56.00	3.88	QP
4	0.53	31.81	10.83	42.64	46.00	3.36	Average
5	0.56	36.12	10.83	46.95	56.00	9.05	QP
6	0.56	22.73	10.83	33.56	46.00	12.44	Average
7	1.07	36.91	10.85	47.76	56.00	8.24	QP
8	1.07	27.37	10.85	38.22	46.00	7.78	Average
9	1.15	37.14	10.85	47.99	56.00	8.01	QP
10	1.15	26.85	10.85	37.70	46.00	8.30	Average
11	1.28	34.52	10.84	45.36	56.00	10.64	QP
12	1.28	24.07	10.84	34.91	46.00	11.09	Average
13	1.31	34.22	10.84	45.06	56.00	10.94	QP
14	1.31	23.51	10.84	34.35	46.00	11.65	Average

Project No.: 2402V85163E-RF-A1  
Port: neutral  
Test Mode: Transmitting  
IF B/W 9KHz PK/AV

Serial No.: 2ZYH-1  
Tester: Yukin Qiu



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB)	Result (dB $\mu$ V)	Limit (dB $\mu$ V)	Margin (dB)	Measurement
1	0.49	40.16	10.74	50.90	56.20	5.30	QP
2	0.49	29.50	10.74	40.24	46.20	5.96	Average
3	0.57	40.19	10.73	50.92	56.00	5.08	QP
4	0.57	29.53	10.73	40.26	46.00	5.74	Average
5	0.80	37.30	10.78	48.08	56.00	7.92	QP
6	0.80	23.08	10.78	33.86	46.00	12.14	Average
7	0.93	36.93	10.84	47.77	56.00	8.23	QP
8	0.93	23.18	10.84	34.02	46.00	11.98	Average
9	1.07	36.84	10.86	47.70	56.00	8.30	QP
10	1.07	23.63	10.86	34.49	46.00	11.51	Average
11	1.15	36.06	10.87	46.93	56.00	9.07	QP
12	1.15	22.55	10.87	33.42	46.00	12.58	Average

## 5.2 Radiated Spurious Emissions

### 1) 9kHz - 1GHz

Serial Number:	2ZYH-2	Test Date:	2025/3/29
Test Site:	Chamber10m	Test Mode:	Transmitting
Tester:	Willem Qiu	Test Result:	Pass

#### Environmental Conditions:

Temperature: (°C)	23.8	Relative Humidity: (%)	49	ATM Pressure: (kPa)	101.3
-------------------	------	------------------------	----	---------------------	-------

#### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Coaxial Attenuator	779-6dB	04269	2023/9/6	2026/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	185914	2024/8/26	2025/8/25
R&S	EMI Test Receiver	ESCI	100224	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### Test Data:


Please refer to the below table and plots.

After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to table and plots.

*Note: BDR High channel was tested.*


**9kHz~30MHz**

Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:



Project No.: 2402V85163E-RF-A1  
Polarization: Parallel  
Test Mode: Transmitting  
Note:  
RBW:10kHz VBW:30kHz

Serial No.: 2ZYH-2  
Tester: Willem Qiu




No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement
1	0.582	15.34	22.65	37.99	72.27	34.28	Peak
2	0.661	15.13	21.85	36.98	71.14	34.16	Peak
3	0.809	15.62	20.38	36.00	69.36	33.36	Peak
4	0.899	15.67	18.58	34.25	68.42	34.17	Peak
5	1.210	19.75	15.63	35.38	65.78	30.40	Peak
6	1.403	18.17	14.77	32.94	64.47	31.53	Peak

**30MHz-1GHz**

Project No.: 2402V85163E-RF-A1  
Polarization: Horizontal  
Test Mode: Transmitting  
Note:  
RBW:100kHz VBW:300kHz


Serial No.: 2ZYH-2  
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement
1	62.98	32.73	-16.56	16.17	40.00	23.83	Peak
2	111.48	30.65	-11.15	19.50	43.50	24.00	Peak
3	128.94	31.21	-9.86	21.35	43.50	22.15	Peak
4	163.86	29.31	-11.39	17.92	43.50	25.58	Peak
5	286.08	29.31	-9.63	19.68	46.00	26.32	Peak
6	811.82	28.30	0.56	28.86	46.00	17.14	Peak

Project No.: 2402V85163E-RF-A1  
Polarization: Vertical  
Test Mode: Transmitting  
Note:  
RBW:100kHz VBW:300kHz

Serial No.: 2ZYH-2  
Tester: Willem Qiu



No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement
1	35.82	29.39	-8.01	21.38	40.00	18.62	Peak
2	64.92	36.59	-16.50	20.09	40.00	19.91	Peak
3	121.18	30.97	-9.94	21.03	43.50	22.47	Peak
4	200.72	30.40	-11.60	18.80	43.50	24.70	Peak
5	288.02	29.18	-9.60	19.58	46.00	26.42	Peak
6	792.42	28.38	0.34	28.72	46.00	17.28	Peak

**2) 1-25GHz:**

Serial Number:	2ZYH-1	Test Date:	2025/4/2
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Leo Xiao	Test Result:	Pass

<b>Environmental Conditions:</b>					
Temperature: (°C)	19.8	Relative Humidity: (%)	46	ATM Pressure: (kPa)	101.4

**Test Equipment List and Details:**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2024/11/17	2025/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2024/12/9	2025/12/8
AH	Preamplifier	PAM-0118P	469	2024/4/15	2025/4/14
AH	Preamplifier	PAM-1840VH	191	2024/9/5	2025/9/4
R&S	Spectrum Analyzer	FSV40	101589	2024/9/5	2025/9/4
Audix	Test Software	E3	191218 V9	N/A	N/A
Decentest	Multiplex Switch Test Control Set & Filter Switch Unit	DT7220SCU & DT7220FCU	DC79902 & DC79905	2024/8/27	2025/8/26

\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


**Test Data:**


Please refer to the below table and plots.


After pre-scan in the X, Y and Z axes of orientation, the worst case is refer to table and plots.

The maximum output power mode was tested.

1-18GHz:












**18-25GHz:**

No Emission was detected in the range 18-25GHz, test was performed on the mode and channel which with the maximum power.



**Bandedge:**

BDR, Low Channel, Bandedge, Horizontal	BDR, Low Channel, Bandedge, Vertical																																
<p>Project No.: 2402V85163E-RF-A1 Polarization: Horizontal Test Mode: Transmitting Note: BDR Mode low channel 2402MHz Peak:RBW:1MHz,VBW:3MHz</p> <p>Serial No.: 22VH-1 Tester: Leo Xiao</p>  <table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dB<math>\mu</math>V)</th><th>Factor (dB/m)</th><th>Result (dB<math>\mu</math>V/m)</th><th>Limit (dB<math>\mu</math>V/m)</th><th>Margin (dB)</th><th>Measurement</th></tr> </thead> <tbody> <tr> <td>1</td><td>2390.00</td><td>47.65</td><td>-0.49</td><td>47.16</td><td>74.00</td><td>26.84</td><td>Peak</td></tr> </tbody> </table>	No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement	1	2390.00	47.65	-0.49	47.16	74.00	26.84	Peak	<p>Project No.: 2402V85163E-RF-A1 Polarization: Vertical Test Mode: Transmitting Note: BDR Mode low channel 2402MHz Peak:RBW:1MHz,VBW:3MHz</p> <p>Serial No.: 22VH-1 Tester: Leo Xiao</p>  <table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dB<math>\mu</math>V)</th><th>Factor (dB/m)</th><th>Result (dB<math>\mu</math>V/m)</th><th>Limit (dB<math>\mu</math>V/m)</th><th>Margin (dB)</th><th>Measurement</th></tr> </thead> <tbody> <tr> <td>1</td><td>2390.00</td><td>47.58</td><td>-0.49</td><td>47.09</td><td>74.00</td><td>26.91</td><td>Peak</td></tr> </tbody> </table>	No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement	1	2390.00	47.58	-0.49	47.09	74.00	26.91	Peak
No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement																										
1	2390.00	47.65	-0.49	47.16	74.00	26.84	Peak																										
No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement																										
1	2390.00	47.58	-0.49	47.09	74.00	26.91	Peak																										
BDR, High Channel, Bandedge, Horizontal	BDR, High Channel, Bandedge, Vertical																																
<p>Project No.: 2402V85163E-RF-A1 Polarization: Horizontal Test Mode: Transmitting Note: BDR Mode high channel 2480MHz Peak:RBW:1MHz,VBW:3MHz</p> <p>Serial No.: 22VH-1 Tester: Leo Xiao</p>  <table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dB<math>\mu</math>V)</th><th>Factor (dB/m)</th><th>Result (dB<math>\mu</math>V/m)</th><th>Limit (dB<math>\mu</math>V/m)</th><th>Margin (dB)</th><th>Measurement</th></tr> </thead> <tbody> <tr> <td>1</td><td>2483.50</td><td>47.63</td><td>-0.05</td><td>47.58</td><td>74.00</td><td>26.42</td><td>Peak</td></tr> </tbody> </table>	No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement	1	2483.50	47.63	-0.05	47.58	74.00	26.42	Peak	<p>Project No.: 2402V85163E-RF-A1 Polarization: Vertical Test Mode: Transmitting Note: BDR Mode high channel 2480MHz Peak:RBW:1MHz,VBW:3MHz</p> <p>Serial No.: 22VH-1 Tester: Leo Xiao</p>  <table border="1"> <thead> <tr> <th>No.</th><th>Frequency (MHz)</th><th>Reading (dB<math>\mu</math>V)</th><th>Factor (dB/m)</th><th>Result (dB<math>\mu</math>V/m)</th><th>Limit (dB<math>\mu</math>V/m)</th><th>Margin (dB)</th><th>Measurement</th></tr> </thead> <tbody> <tr> <td>1</td><td>2483.50</td><td>48.20</td><td>-0.05</td><td>48.15</td><td>74.00</td><td>25.85</td><td>Peak</td></tr> </tbody> </table>	No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement	1	2483.50	48.20	-0.05	48.15	74.00	25.85	Peak
No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement																										
1	2483.50	47.63	-0.05	47.58	74.00	26.42	Peak																										
No.	Frequency (MHz)	Reading (dB $\mu$ V)	Factor (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)	Measurement																										
1	2483.50	48.20	-0.05	48.15	74.00	25.85	Peak																										

### 5.3 Spot Check With Maximum Conducted Output Power

<b>Serial No.:</b>	2ZYH-1	<b>Test Date:</b>	2025/04/12
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Tower Qing	<b>Test Result:</b>	Pass

#### Environmental Conditions:

<b>Temperature:</b> (°C)	24.5	<b>Relative Humidity:</b> (%)	66	<b>ATM Pressure:</b> (kPa)	100.7
-----------------------------	------	----------------------------------	----	-------------------------------	-------

#### Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSV40	101589	2024/09/05	2025/09/04
R&S	Coaxial Attenuator	10dB	F-08-EM512	2024/06/13	2025/06/12


\* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### Test Data:

Mode	Test Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)	Verdict
DH1	2402	3.30	21.00	Pass
	2441	3.34	21.00	Pass
	2480	3.89	21.00	Pass
2DH1	2402	3.18	21.00	Pass
	2441	2.31	21.00	Pass
	2480	3.29	21.00	Pass
3DH1	2402	3.42	21.00	Pass
	2441	2.51	21.00	Pass
	2480	3.24	21.00	Pass


Note: The Spot Check data were similar to the original data.

## DH1\_Low




ProjectNo.:2402V85163E-RF-A1 Tester:Tower Qing  
Date: 12.APR.2025 09:05:16

## DH1\_Middle




ProjectNo.:2402V85163E-RF-A1 Tester:Tower Qing  
Date: 12.APR.2025 09:05:50

## DH1\_High




ProjectNo.:2402V85163E-RF-A1 Tester:Tower Qing  
Date: 12.APR.2025 09:06:16

## 2DH1\_Low



ProjectNo.:2402V85163E-RF-A1 Tester:Tower Qing  
Date: 12.APR.2025 09:07:31

## 2DH1\_Middle




ProjectNo.:2402V85163E-RF-A1 Tester:Tower Qing  
Date: 12.APR.2025 09:10:53

## 2DH1\_High




ProjectNo.:2402V85163E-RF-A1 Tester:Tower Qing  
Date: 12.APR.2025 09:11:20


## 3DH1\_Low



## 3DH1\_Middle



## 3DH1\_High



---

## **EXHIBIT A - EUT PHOTOGRAPHS**

---

Please refer to the attachment 2402V85163E-RF-A1-EXP EUT EXTERNAL PHOTOGRAPHS and 2402V85163E-RF-A1-INP EUT INTERNAL PHOTOGRAPHS.

---

## **EXHIBIT B - TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment 2402V85163E-RF-00AA1-TSP TEST SETUP PHOTOGRAPHS.

## **EXHIBIT C - RF EXPOSURE EVALUATION**

### **SAR Evaluation**

#### **Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### **Measurement Result**

The max conducted power including tune-up tolerance is 4.5 dBm (2.82 mW).  
 $[(\text{max. power of channel, mW}) / (\text{min. test separation distance, mm})] [\sqrt{f(\text{GHz})}]$   
 $= 2.82 / 5 * (\sqrt{2.480}) = 0.9 < 3.0$

Note: the max conducted power including tune-up tolerance was declared by manufacturer.

**Result: Compliant. The stand-alone SAR evaluation is not necessary.**

**\*\*\*\*\* END OF REPORT \*\*\*\*\***