



A D T

# FCC TEST REPORT

**REPORT NO.:** RF991207D13

**MODEL NO.:** SW205

**FCC ID:** XDTSW205

**RECEIVED:** Dec. 7, 2010

**TESTED:** Dec. 13 ~ 16, 2010

**ISSUED:** Jan. 11, 2011

**APPLICANT:** PECO Inc.

**ADDRESS:** 4707 SE 17th Avenue P.O.Box 82189, Portland, OR9

**ISSUED BY:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**LAB LOCATION:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang, Taipei Hsien 244, Taiwan

This test report consists of 33 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





A D T

## Table of Contents

RELEASE CONTROL RECORD.....	.3
1. CERTIFICATION .....	.4
2. SUMMARY OF TEST RESULTS .....	.5
2.1 MEASUREMENT UNCERTAINTY.....	.5
3. GENERAL INFORMATION.....	.6
3.1 GENERAL DESCRIPTION OF EUT .....	.6
3.2 DESCRIPTION OF TEST MODES .....	.7
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST .....	.7
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL: .....	.8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	.10
3.4 DESCRIPTION OF SUPPORT UNITS .....	.10
4. TEST TYPES AND RESULTS .....	.11
4.1 CONDUCTED EMISSION MEASUREMENT .....	.11
4.2 RADIATED EMISSION MEASUREMENT .....	.11
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT .....	.11
4.2.2 TEST INSTRUMENTS .....	.12
4.2.3 TEST PROCEDURES .....	.13
4.2.4 DEVIATION FROM TEST STANDARD .....	.13
4.2.5 TEST SETUP .....	.14
4.2.6 EUT OPERATING CONDITIONS .....	.14
4.2.7 TEST RESULTS .....	.15
4.3 20dB OCCUPIED BANDWIDTH MEASUREMENT .....	.22
4.3.1 LIMITS OF EMISSION BANDWIDTH MEASUREMENT .....	.22
4.3.2 TEST INSTRUMENTS .....	.22
4.3.3 TEST PROCEDURE .....	.22
4.3.4 DEVIATION FROM TEST STANDARD .....	.23
4.3.5 TEST SETUP .....	.23
4.3.6 TEST RESULTS .....	.24
4.4 DEACTIVATION TIME .....	.27
4.4.1 LIMITS OF DEACTIVATION TIME MEASUREMENT .....	.27
4.4.2 TEST INSTRUMENTS .....	.27
4.4.3 TEST PROCEDURES .....	.27
4.4.4 DEVIATION FROM TEST STANDARD .....	.27
4.4.5 TEST SETUP .....	.27
4.4.6 TESE RESULTS .....	.28
5. PHOTOGRAPHS OF THE TEST CONFIGURATION.....	.31
6. INFORMATION ON THE TESTING LABORATORIES .....	.32
7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	.33



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	N/A	Jan. 11, 2011



A D T

## 1. CERTIFICATION

**PRODUCT:** Wireless Occupancy Sensor  
**BRAND NAME:** PECO  
**MODEL NO.:** SW205  
**APPLICANT:** PECO Inc.  
**TESTED:** Dec. 13 ~ 16, 2010  
**TEST SAMPLE:** ENGINEERING SAMPLE  
**STANDARDS:** FCC Part 15, Subpart C (Section 15.231)  
ANSI C63.4-2003  
ANSI C63.10-2009

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Annie Chang , DATE: Jan. 11. 2011  
( Annie Chang / Senior Specialist )

**APPROVED BY :** Ken Liu , DATE: Jan. 11. 2011  
( Ken Liu / Manager )



A D T

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.231)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	Conducted Emission Test	N/A	Power supply is 3Vdc from batteries
15.231(b)	Radiated Emission Test	PASS	Minimum passing margin is -0.7dB at 915.00MHz
15.231(c)	Emission Bandwidth Measurement	PASS	Meet the requirement of limit
15.231(a)	De-activation	PASS	Meet the requirement of limit

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Frequency	Uncertainty
Radiated emissions	30MHz ~ 1GHz	3.72 dB
	Above 1GHz	2.89 dB



A D T

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	Wireless Occupancy Sensor
<b>MODEL NO.</b>	SW205
<b>FCC ID</b>	XDTSW205
<b>POWER SUPPLY</b>	3Vdc from batteries
<b>RADIO TECHNOLOGY</b>	FHSS
<b>OPERATING FREQUENCY</b>	902.4 ~ 927.5MHz
<b>NUMBER OF CHANNEL</b>	50
<b>ANTENNA TYPE</b>	Monopole antenna
<b>ANTENNA CONNECTOR</b>	N/A
<b>DATA CABLE</b>	N/A
<b>I/O PORTS</b>	N/A
<b>ASSOCIATED DEVICES</b>	N/A

#### NOTE:

1. The EUT is a transmitter.
2. The EUT could operate under Z Axis only.
3. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



A D T

## 3.2 DESCRIPTION OF TEST MODES

50 channels were provided to this EUT.

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
27	902.400000	47	911.030303	31	920.380952
10	903.111111	38	911.500000	8	920.500000
7	903.500000	33	912.500000	29	921.025641
23	904.296296	0	912.969697	41	921.481481
36	904.500000	22	913.548387	17	922.000000
43	905.025641	19	914.000000	18	922.536585
48	905.481481	30	914.461538	24	922.947368
28	906.000000	25	915.000000	45	923.500000
16	906.536585	1	915.500000	4	924.000000
37	906.947368	3	916.000000	34	924.500000
11	907.500000	9	916.500000	12	925.000000
26	908.000000	49	917.052632	13	925.538462
32	908.500000	35	917.463415	20	926.000000
14	909.000000	42	918.000000	46	926.451613
6	909.538462	15	918.518519	40	927.030303
39	910.000000	44	918.974359	35	927.500000
2	910.451613	5	919.500000		

### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

EUT

(Powered from batteries)

\*Test table



A D T

### 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to					Description
	PLC	RE<1G	RE <sup>3</sup> 1G	EB	DT	
-	Note	√	√	√	√	-

Where **PLC**: Power Line Conducted Emission**RE<1G**: Radiated Emission below 1GHz**RE<sup>3</sup>1G**: Radiated Emission above 1GHz**EB**: 20dB Bandwidth Measurement**DT**: Deactivation Time Measurement**Note:** No need to concern of Conducted Emission due to the EUT is powered by DC power supply.

#### RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY
0 to 49	27, 25, 35	FHSS

#### RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulation and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY
0 to 49	27, 25, 35	FHSS

#### EMISSION BANDWIDTH MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY
0 to 49	27, 25, 35	FHSS



A D T

**DEACTIVATION TIME MEASUREMENT:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY
0 to 49	27, 25, 35	FHSS

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE<1G	20deg. C, 76% RH, 1009hPa	3Vdc	Nick Chen
RE <sup>3</sup> 1G	20deg. C, 76% RH, 1009hPa	3Vdc	Nick Chen
EB	20deg. C, 78% RH, 1019hPa	3Vdc	Nick Chen
DT	20deg. C, 78% RH, 1019hPa	3Vdc	Nick Chen



A D T

### **3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.231)**

**ANSI C63.4-2003**

**ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

### **3.4 DESCRIPTION OF SUPPORT UNITS**

The EUT has been tested as an independent unit together without any other necessary accessories or support units.



A D T

## 4. TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

N/A

### 4.2 RADIATED EMISSION MEASUREMENT

#### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

According to 15.231 the field strength of emissions from intentional radiators operated under these frequencies bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental		Field Strength of Spurious	
	uV/meter	dBuV/meter	uV/meter	dBuV/meter
40.66 ~ 40.70	2250	67.04	225	48.04
70 ~ 130	1250	61.94	125	41.94
130 ~ 174	1250 ~ 3750	61.94 ~ 71.48	125 ~ 375	41.94 ~ 51.48
174 ~ 260	3750	71.48	75	37.50
260 ~ 470	3750 ~ 12500	71.48 ~ 81.94	375 ~ 1250	51.48 ~ 61.94
Above 470	12500	81.94	1250	61.94

**NOTE:**

1. Where F is the frequency in MHz, the formula for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters =  $56.81818(F)-6136.3636$ ; for the band 260-470 MHz, uV/m at 3 meters =  $41.6667(F)-7083.3333$ . The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.
2. The above field strength limits are specified at a distance of 3meters. The tighter limits apply at the band edges.



A D T

## 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	May 06, 2010	May 05, 2011
HP Preamplifier	8449B	3008A01924	Jul. 14, 2010	Jul. 13, 2011
HP Preamplifier	8449B	3008A01292	Jul. 14, 2010	Jul. 13, 2011
ROHDE & SCHWARZ TEST RECEIVER	ESU26	100005	Jun. 10, 2010	Jun. 09, 2011
Schwarzbeck Antenna	VULB 9168	137	Apr. 29, 2010	Apr. 28, 2011
Schwarzbeck Antenna	VHBA 9123	480	Apr. 29, 2010	Apr. 28, 2011
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	ADT_Radiated_V 7.6.15.9.2	NA	NA	NA
SUHNER RF cable	SF102	CABLE-CH6	Aug. 20, 2010	Aug. 19, 2011
EMCO Horn Antenna	3115	6714	Oct. 26, 2010	Oct. 25, 2011
EMCO Horn Antenna	3115	9312-4192	Apr. 23, 2010	Apr. 22, 2011
Highpass filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	NA	NA

**NOTE:** 1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.  
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.  
3. The test was performed in Chamber No. 6.  
4. The Industry Canada Reference No. IC 7450E-6.  
5. The FCC Site Registration No. is 447212.



A D T

### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak method or average method as specified and then reported in data sheet.


#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.



A D T

## 4.2.7 TEST RESULTS

### ABOVE 1GHz DATA

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 27		FREQUENCY RANGE 1 ~ 25GHz
INPUT POWER		3Vdc		DETECTOR FUNCTION Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS		20deg. C, 76% RH 1009hPa		TESTED BY Nick Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1804.80	45.2 PK	81.9	-36.7	1.34 H	238	14.66	30.54
2	1804.80	40.5 AV	61.9	-21.4	1.34 H	238	9.96	30.54
3	2707.20	45.2 PK	81.9	-36.8	1.00 H	218	11.31	33.88
4	2707.20	40.5 AV	61.9	-21.5	1.00 H	218	6.61	33.88
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1804.80	45.4 PK	81.9	-36.6	1.19 V	327	14.81	30.54
2	1804.80	40.7 AV	61.9	-21.3	1.19 V	327	10.11	30.54
3	2707.20	44.9 PK	81.9	-37.0	1.04 V	296	11.03	33.88
4	2707.20	40.2 AV	61.9	-21.7	1.04 V	296	6.33	33.88

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:  

$$20 \log (\text{Duty cycle}) = 20 \log (58.33 \text{ ms} / 100 \text{ ms}) = -4.7 \text{ dB}$$
Please see page 22 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 25	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20deg. C, 76% RH 1009hPa	TESTED BY	Nick Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1830.00	49.4 PK	81.9	-32.6	1.29 H	237	18.81	30.58
2	1830.00	44.7 AV	61.9	-17.3	1.29 H	237	14.11	30.58
3	2745.00	44.5 PK	81.9	-37.4	1.18 H	246	10.50	34.01
4	2745.00	39.8 AV	61.9	-22.1	1.18 H	246	5.80	34.01
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1830.00	47.6 PK	81.9	-34.4	1.00 V	308	16.98	30.58
2	1830.00	42.9 AV	61.9	-19.1	1.00 V	308	12.28	30.58
3	2745.00	43.2 PK	81.9	-38.8	1.02 V	298	9.16	34.01
4	2745.00	38.5 AV	61.9	-23.5	1.02 V	298	4.46	34.01

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:  
20 log (Duty cycle) = 20 log (58.33 ms / 100 ms) = -4.7 dB  
Please see page 22 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 35	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	3Vdc	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	20deg. C, 76% RH 1009hPa	TESTED BY	Nick Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1855.00	43.4 PK	81.9	-38.5	1.27 H	244	12.80	30.62
2	1855.00	38.7 AV	61.9	-23.2	1.27 H	244	8.10	30.62
3	2782.50	44.6 PK	81.9	-37.3	1.16 H	253	10.48	34.14
4	2782.50	39.9 AV	61.9	-22.0	1.16 H	253	5.78	34.14
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1855.00	44.3 PK	81.9	-37.7	1.00 V	95	13.65	30.62
2	1855.00	39.6 AV	61.9	-22.4	1.00 V	95	8.95	30.62
3	2782.50	44.1 PK	81.9	-37.8	1.05 V	169	9.98	34.14
4	2782.50	39.4 AV	61.9	-22.5	1.05 V	169	5.28	34.14

**REMARKS:** 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).  
 2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).  
 3. The other emission levels were very low against the limit.  
 4. Margin value = Emission level – Limit value.  
 5. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:  
 $20 \log (\text{Duty cycle}) = 20 \log (58.33 \text{ ms} / 100 \text{ ms}) = -4.7 \text{ dB}$   
 Please see page 22 for plotted duty.



A D T

## BELOW 1GHZ WORST-CASE DATA

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 27	FREQUENCY RANGE	Below 1000MHz	
INPUT POWER	3Vdc	DETECTOR FUNCTION	Quasi-Peak Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	20deg. C, 76% RH 1009hPa	TESTED BY	Nick Chen	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	31.55	26.9 QP	61.9	-35.1	1.05 H	319	14.62	12.24
2	135.71	22.0 QP	61.9	-39.9	1.17 H	133	8.01	14.01
3	407.74	27.3 QP	61.9	-34.7	1.08 H	4	8.74	18.54
4	496.35	28.9 QP	61.9	-33.0	1.23 H	190	8.19	20.74
5	567.85	31.1 QP	61.9	-30.9	1.17 H	157	8.53	22.55
6	687.55	32.4 QP	61.9	-29.5	1.00 H	286	7.77	24.65
7	*902.40	83.1 PK	101.9	-18.8	1.00 H	181	55.16	27.94
8	*902.40	78.4 AV	81.9	-3.5	1.00 H	181	50.46	27.94
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	48.65	32.2 QP	61.9	-29.8	1.03 V	108	18.39	13.80
2	98.39	32.2 QP	61.9	-29.8	1.00 V	193	23.15	9.02
3	194.77	32.6 QP	61.9	-29.4	1.07 V	264	21.36	11.21
4	241.85	31.4 QP	61.9	-30.5	1.07 V	215	18.17	13.25
5	280.27	29.4 QP	61.9	-32.6	1.02 V	46	14.41	14.96
6	440.38	31.9 QP	61.9	-30.1	1.02 V	55	12.77	19.09
7	*902.40	85.2 PK	101.9	-16.8	1.09 V	69	57.25	27.94
8	*902.40	80.5 AV	81.9	-1.4	1.09 V	69	52.55	27.94

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:  

$$20 \log (\text{Duty cycle}) = 20 \log (58.33 \text{ ms} / 100 \text{ ms}) = -4.7 \text{ dB}$$
Please see page 22 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 25		FREQUENCY RANGE
INPUT POWER		3Vdc		DETECTOR FUNCTION
ENVIRONMENTAL CONDITIONS		20deg. C, 76% RH 1009hPa		TESTED BY
				Nick Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	159.02	23.5 QP	61.9	-38.4	1.05 H	16	8.64	14.89
2	375.10	26.1 QP	61.9	-35.9	1.13 H	76	8.33	17.75
3	493.24	28.6 QP	61.9	-33.4	1.07 H	166	7.94	20.64
4	654.90	33.3 QP	61.9	-28.7	1.08 H	1	9.11	24.16
5	718.64	33.1 QP	61.9	-28.8	1.13 H	304	8.01	25.10
6	841.44	35.7 QP	61.9	-26.2	1.00 H	175	8.73	26.99
7	*915.00	82.7 PK	101.9	-19.2	1.00 H	177	54.61	28.11
8	*915.00	78.0 AV	81.9	-3.9	1.00 H	177	49.91	28.11

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	160.58	23.3 QP	61.9	-38.7	1.02 V	352	8.33	14.94
2	280.27	26.1 QP	61.9	-35.9	1.11 V	16	11.09	14.96
3	440.38	27.8 QP	61.9	-34.1	1.07 V	337	8.73	19.09
4	575.62	30.4 QP	61.9	-31.5	1.32 V	187	7.69	22.73
5	685.99	32.2 QP	61.9	-29.7	1.09 V	307	7.58	24.63
6	808.80	34.8 QP	61.9	-27.2	1.12 V	13	8.40	26.39
7	*915.00	85.9 PK	101.9	-16.1	1.07 V	65	57.75	28.11
8	*915.00	81.2 AV	81.9	-0.7	1.07 V	65	53.05	28.11

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:  

$$20 \log (\text{Duty cycle}) = 20 \log (58.33 \text{ ms} / 100 \text{ ms}) = -4.7 \text{ dB}$$
Please see page 22 for plotted duty.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 35		FREQUENCY RANGE
INPUT POWER		3Vdc		DETECTOR FUNCTION
ENVIRONMENTAL CONDITIONS		20deg. C, 76% RH 1009hPa		TESTED BY
				Nick Chen

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	278.72	25.1 QP	61.9	-36.8	1.07 H	10	10.24	14.89
2	427.95	27.8 QP	61.9	-34.2	1.03 H	127	8.91	18.88
3	542.98	29.8 QP	61.9	-32.2	1.14 H	10	7.80	21.95
4	645.58	31.7 QP	61.9	-30.2	1.08 H	28	7.68	24.02
5	745.06	32.8 QP	61.9	-29.1	1.00 H	223	7.35	25.46
6	844.55	35.5 QP	61.9	-26.5	1.09 H	109	8.44	27.05
7	*927.50	80.9 PK	101.9	-21.1	1.00 H	179	52.59	28.28
8	*927.50	76.2 AV	81.9	-5.7	1.00 H	179	47.89	28.28

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	70.42	26.0 QP	61.9	-36.0	1.02 V	70	13.81	12.15
2	157.47	23.2 QP	61.9	-38.8	1.11 V	175	8.48	14.67
3	266.28	25.2 QP	61.9	-36.8	1.03 V	10	10.78	14.37
4	493.24	28.5 QP	61.9	-33.5	1.17 V	286	7.81	20.64
5	687.55	31.1 QP	61.9	-30.9	1.08 V	10	6.44	24.65
6	763.72	34.3 QP	61.9	-27.6	1.28 V	178	8.59	25.72
7	*927.50	83.9 PK	101.9	-18.1	1.09 V	54	55.59	28.28
8	*927.50	79.2 AV	81.9	-2.7	1.09 V	54	50.89	28.28


**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “\*”: Fundamental frequency
6. The average value of fundamental frequency is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula:  

$$20 \log (\text{Duty cycle}) = 20 \log (58.33 \text{ ms} / 100 \text{ ms}) = -4.7 \text{ dB}$$
Please see page 22 for plotted duty.



A D T





A D T

## 4.3 20dB OCCUPIED BANDWIDTH MEASUREMENT

### 4.3.1 LIMITS OF EMISSION BANDWIDTH MEASUREMENT

The bandwidth of the emission shall be no wider than 0.5% of the center frequency for device operating above 900 MHz.

Fundamental Frequency (MHz)	Limit of Emission Bandwidth(kHz)
902.4	4512.0
915.0	4575.0
927.5	4637.5

### 4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP 40	100036	Apr. 27, 2010	Apr. 26, 2011

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


### 4.3.3 TEST PROCEDURE

- a. The EUT was placed on the turn table.
- b. The signal was coupled to the spectrum analyzer through an antenna.
- c. Set the resolution bandwidth to 100kHz and video bandwidth to 300kHz then select Peak function to scan the channel frequency.
- d. The emission bandwidth was measured and recorded.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation


#### 4.3.5 TEST SETUP



### 4.3.6 TEST RESULTS

Frequency (MHz)	20dB Bandwidth (kHz)	Maximum Limit (kHz)	PASS/FAIL
902.4	272.44	4512.0	PASS

The plot of test result is attached as below.






A D T

Frequency (MHz)	20dB Bandwidth (kHz)	Maximum Limit (kHz)	PASS/FAIL
915.0	266.03	4575.0	PASS

The plot of test result is attached as below.






A D T

Frequency (MHz)	20dB Bandwidth (kHz)	Maximum Limit (kHz)	PASS/FAIL
927.5	259.62	4637.5	PASS

The plot of test result is attached as below.





A D T

## 4.4 DEACTIVATION TIME

### 4.4.1 LIMITS OF DEACTIVATION TIME MEASUREMENT

A transmitter activated automatically shall cease transmission within 5 seconds after activation.

### 4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSP 40	100036	Apr. 27, 2010	Apr. 26, 2011

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


### 4.4.3 TEST PROCEDURES

- The EUT was placed on the turning table.
- The signal was coupled to the spectrum analyzer through an antenna.
- Set the resolution bandwidth to 100kHz and video bandwidth to 300kHz. The spectrum analyser was turned to the centre frequency of the transmitter's and the analyser's marker function was used to determine the duration of transmission.
- The transmission duration was measured and recorded.

### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.4.5 TEST SETUP






A D T

#### 4.4.6 TESE RESULTS

Trigger	Frequency (MHz)	Maximum limit (sec)	PASS/FAIL
1	902.4	5	PASS

The plots of test results are attached as below.






A D T

Trigger	Frequency (MHz)	Maximum limit (sec)	PASS/FAIL
1	915.0	5	PASS

The plots of test results are attached as below.






A D T

Trigger	Frequency (MHz)	Maximum limit (sec)	PASS/FAIL
1	927.5	5	PASS

The plots of test results are attached as below.





A D T

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



A D T

## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**

Tel: 886-3-3183232  
Fax: 886-3-3185050

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



A D T

## 7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---