

## FCC 47 CFR PART 15 SUBPART C AND ANSI C63.10: 2013

### TEST REPORT

For

**ANALOG PLAYER**

**Model: TN-280BT**

**Data Applies To: N/A**

**Brand Name: TEAC**

Issued for

**TEAC CORPORATION  
1-47 Ochiai, Tama-shi, Tokyo 206-8530, Japan**

Issued By

**Compliance Certification Services Inc.**

**Tainan Laboratory**

**No.8, Jiucengling, Xinhua Dist., Tainan City  
712, Taiwan (R.O.C.)**

**TEL: 886-6-580-2201**

**FAX: 886-6-580-2202**

**<http://www.ccsrf.com>**

**E-Mail : [service@ccsrf.com](mailto:service@ccsrf.com)**

**Issued Date: June 27, 2018**



---

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.

Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

#### REVISION HISTORY

| Rev. | Issue Date    | Revisions     | Effect Page | Revised By |
|------|---------------|---------------|-------------|------------|
| 00   | June 27, 2018 | Initial Issue | ALL         | Gina Lin   |
|      |               |               |             |            |
|      |               |               |             |            |
|      |               |               |             |            |

## TABLE OF CONTENTS

| TITLE   | PAGE NO.  |
|---|-----------|
| <b>1. TEST REPORT CERTIFICATION .....</b>             | <b>4</b>  |
| <b>2. EUT DESCRIPTION .....</b>                       | <b>5</b>  |
| 2.1 DESCRIPTION OF EUT & POWER.....                   | 5         |
| <b>3. DESCRIPTION OF TEST MODES .....</b>             | <b>6</b>  |
| <b>4. TEST METHODOLOGY .....</b>                      | <b>7</b>  |
| <b>5. FACILITIES AND ACCREDITATIONS.....</b>          | <b>8</b>  |
| 5.1 FACILITIES .....                                  | 8         |
| 5.2 EQUIPMENT .....                                   | 8         |
| 5.3 LABORATORY ACCREDITATIONS LISTINGS.....           | 8         |
| 5.4 TABLE OF ACCREDITATIONS AND LISTINGS .....        | 9         |
| <b>6. SETUP OF EQUIPMENT UNDER TEST.....</b>          | <b>10</b> |
| 6.1 SETUP CONFIGURATION OF EUT .....                  | 10        |
| 6.2 SUPPORT EQUIPMENT .....                           | 11        |
| <b>7. APPLICABLE LIMITS AND TEST RESULTS.....</b>     | <b>13</b> |
| 7.1 20DB BANDWIDTH FOR HOPPING.....                   | 13        |
| 7.2 MAXIMUM PEAK OUTPUT POWER .....                   | 19        |
| 7.3 HOPPING CHANNEL SEPARATION.....                   | 25        |
| 7.4 NUMBER OF HOPPING FREQUENCY USED .....            | 30        |
| 7.5 DWELL TIME ON EACH CHANNEL .....                  | 33        |
| 7.6 DUTY CYCLE.....                                   | 47        |
| 7.7 CONDUCTED SPURIOUS EMISSION .....                 | 53        |
| 7.8 RADIATED EMISSIONS .....                          | 60        |
| 7.7.1 TRANSMITTER RADIATED SUPURIOUS EMSSIONS .....   | 60        |
| 7.7.2 WORST-CASE RADIATED EMISSION BELOW 1 GHZ.....   | 64        |
| 7.7.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHZ ..... | 67        |
| 7.9 POWERLINE CONDUCTED EMISSIONS .....               | 81        |
| <b>APPENDIX I PHOTOGRPHS OF TEST SETUP .....</b>      | <b>85</b> |
| <b>APPENDIX II PHOTOGRAPHS OF EUT .....</b>           | <b>A1</b> |

## 1. TEST REPORT CERTIFICATION

|                             |   |
|-----------------------------|---|
| <b>Applicant</b>            | <b>TEAC CORPORATION</b><br>1-47 Ochiai, Tama-shi, Tokyo 206-8530,Japan  |
| <b>Manufacturer</b>         | <b>1) Ya Horng Electronic Co., Ltd.</b><br>No. 35, Shalun, Jon Sha Village, Anding Dist., Tainan City<br>745, Taiwan (R.O.C.)<br><b>2) Atten Electronic (Dongguan) Co., Ltd.</b><br>No.34 Gao Yu Nan Road.188 Industrial District, Ping Shan<br>Administrative District, Tang Xia Town, Dong Guan,<br>Guangdong, 523728, China. |
| <b>Equipment Under Test</b> | ANALOG PLAYER   |
| <b>Model Number</b>         | TN-280BT  |
| <b>Data Applies To</b>      | N/A   |
| <b>Brand Name</b>           | TEAC  |
| <b>Date of Test</b>         | June13, 2018  |

| APPLICABLE STANDARD                            |             |
|--|-------------|
| STANDARD                                       | TEST RESULT |
| FCC Part 15 Subpart C AND<br>ANSI C63.10: 2013 | PASS        |

### We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.10: 2013** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:



Jeter Wu  
Assistant Manager

Reviewed by:

Eric Huang  
Section Manager

## 2. EUT DESCRIPTION

### 2.1 DESCRIPTION OF EUT & POWER

|                             |  |
|-----------------------------|--|
| <b>Product</b>              | ANALOG PLAYER  |
| <b>Model Number</b>         | TN-280BT   |
| <b>Data Applies To</b>      | N/A  |
| <b>Brand Name</b>           | TEAC   |
| <b>Identify Number</b>      | T180604N01   |
| <b>Received Date</b>        | June 04, 2018  |
| <b>Frequency Range</b>      | 2402 ~ 2480 MHz  |
| <b>Transmit Peak Power</b>  | GFSK : 7.732dBm / 5.931984397mW<br>8DPSK: 6.501dBm / 4.467864567mW                                   |
| <b>Channel Spacing</b>      | 1MHz   |
| <b>Transmit Data Rate</b>   | GFSK (1Mbps), $\pi/4$ -DQPSK (2Mbps), 8-DPSK (3Mbps)   |
| <b>Modulation Technique</b> | Frequency Hopping Spread Spectrum  |
| <b>Number of Channels</b>   | 79 Channels  |
| <b>Power Supply</b>         | DC12V, 500mA, 6W (Powered by adapter)  |
| <b>Antenna Type</b>         | Manufacturer: BRITO TECHNOLOGY<br>Type: Dipole antenna<br>Model: WF-EM-1510-0067-A<br>Gain: 2.31 dBi |
| <b>Hardware Version</b>     | TN-280BT   |
| <b>Software Version</b>     | N/A  |

**Power Adapter:**

| No. | Manufacturer | Model No.         | Power Input               | Power Output |
|-----|--------------|-------------------|---------------------------|--------------|
| 1   | GPE          | GPE053A-V120050-Z | 100-240Vac, 50/60Hz, 0.2A | 12Vdc, 500mA |

**Remark:**

1. The sample selected for test was production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for **FCC ID: XEG-TN280BT** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.
3. For more details, please refer to the User's manual of the EUT.

### 3. DESCRIPTION OF TEST MODES

The EUT had been tested under operating condition.

There are three channels have been tested as following :

| Channel | Frequency (MHz) |
|---------|-----------------|
| Low     | 2402            |
| Middle  | 2441            |
| High    | 2480            |

#### Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Normal Operation

#### Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| Tested Channel | Modulation Technology | Modulation Type | Packet Type |
|----------------|-----------------------|-----------------|-------------|
| Low, Mid, High | FHSS                  | GFSK            | DH5         |
| Low, Mid, High | FHSS                  | 8-DPSK          | 3-DH5       |

#### Bandedge Measurement :

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| Tested Channel | Modulation Technology | Modulation Type | Packet Type |
|----------------|-----------------------|-----------------|-------------|
| Low, High      | FHSS                  | GFSK            | DH5         |
| Low, High      | FHSS                  | 8-DPSK          | 3-DH5       |

**Antenna Port Conducted Measurement :**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

| Tested Channel | Modulation Technology | Modulation Type | Packet Type |
|----------------|-----------------------|-----------------|-------------|
| Low, Mid, High | FHSS                  | GFSK            | DH5         |
| Low, Mid, High | FHSS                  | 8-DPSK          | 3-DH5       |

**4. TEST METHODOLOGY**

The tests documented in this report were performed in accordance with ANSI C63.10 : 2013 and FCC CFR 47 15.207, 15.209 and 15.247.

## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

- No.8, Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 5.3 LABORATORY ACCREDITATIONS LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by Taiwan Accreditation Foundation for the specific scope of accreditation under Lab Code: 1109 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by TAF or any agency of the Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: TW1109).

## 5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.


|                |                 |
|----------------|-----------------|
| <b>Taiwan</b>  | TAF             |
| <b>Canada</b>  | INDUSTRY CANADA |
| <b>Germany</b> | TUV NORD        |
| <b>Taiwan</b>  | BSMI            |
| <b>USA</b>     | FCC             |

The measuring facility of laboratories has been authorized or registered by the following approval agencies.


## 6. SETUP OF EQUIPMENT UNDER TEST

### 6.1 SETUP CONFIGURATION OF EUT

#### EMI



#### RF



## 6.2 SUPPORT EQUIPMENT

### For EMI test

| No. | Product        | Manufacturer | Model No. | Certify No. | Signal cable             |
|-----|----------------|--------------|-----------|-------------|--------------------------|
| 1   | Speaker System | T.C.SATR     | TCS2285   | DoC         | Power cable, unshd, 1.4m |
| 2   | Speaker System | KINYO        | BTS-672   | DoC         | N/A                      |

| No. | Signal cable description |                        |
|-----|--------------------------|------------------------|
| A   | DC Power Cable           | Unshielded, 1.4m 1 pcs |
| B   | Audio Cable              | Shielded, 1.0m 1 pcs   |

### For RF test

| No. | Product   | Manufacturer | Model No. | Certify No. | Signal cable             |
|-----|-----------|--------------|-----------|-------------|--------------------------|
| 1   | Note Book | Acer         | AS 3830TG | DoC         | Power cable, unshd, 1.6m |

| No. | Signal cable description |                                    |
|-----|--------------------------|------------------------------------|
| A   | Power Cable              | Unshielded, 1.6m 1 pcs             |
| B   | Audio Cable              | Unshielded, 1.0m 1 pcs             |
| C   | Command Cable            | Unshielded, 0.15m 1 pcs            |
| D   | USB Cable                | Shielded, 1.4m 1 pcs, with 1 core. |

#### Note:

- 1) All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2) Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3) shd. = shielded; unshd. = unshielded

## EUT OPERATING CONDITION

### **RF Setup**

1. Set up all computers like the setup diagram.
2. The “CSR BlueSuite 2.4.8”, “Blue Test 3” software was used for testing.
3. Choose Transport “SPI” and Port “USB SPI (10003)”.

### **TX Mode:**

#### **GFSK(DH1):**

CFG PKT > Packet Type : 4 , Packet Type : 27  
TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 255,50 (255,30)

#### **GFSK(DH3):**

CFG PKT > Packet Type : 11 , Packet Type : 183  
TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 255,50 (255,30)

#### **GFSK(DH5):**

CFG PKT > Packet Type : 15 , Packet Type : 339  
TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 255,50 (255,30)

#### **8-DPSK(3DH1):**

CFG PKT > Packet Type : 24 , Packet Type : 83  
TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 255,50

#### **8-DPSK(3DH3):**

CFG PKT > Packet Type : 27 , Packet Type : 552  
TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 255,50

#### **8-DPSK(3DH5):**

CFG PKT > Packet Type : 31 , Packet Type : 1021  
TXDATA1 > LO Freq : 2402 (2402,2441,2480) , Power : 255,50

### **DSSS:**

BLE TEST TX > Channel :0 (0,20,39)  
Length : 37  
Bit pattern : 0

### **RX Mode:**

#### **GFSK , 8-DPSK:**

RXDATA1

#### **DSSS:**

BLE TEST RX

4. All of the function are under run.
5. Start test.

## 7. APPLICABLE LIMITS AND TEST RESULTS

### 7.1 20dB BANDWIDTH FOR HOPPING

#### LIMIT

None; for reporting purposes only.

#### TEST EQUIPMENT

| Name of Equipment     | Manufacturer | Model  | Serial Number | Calibration Due |
|-----------------------|--------------|--------|---------------|-----------------|
| EXA Spectrum Analyzer | KEYSIGHT     | N9010A | MY54430216    | 05/08/2019      |

#### TEST SETUP



#### TEST PROCEDURE

The 20dB band width was measured with a spectrum analyzer connected to RF antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer. Display Line and Marker Delta functions, the 20dB band width of the emission was determined.

## TEST RESULTS

|                 |             |           |            |
|-----------------|-------------|-----------|------------|
| Model Name      | TN-280BT    | Test By   | Ted Huang  |
| Temp & Humidity | 26.5°C, 42% | Test Date | 2018/06/13 |


### Modulation Type: GFSK / DH5


| Channel | Channel Frequency (MHz) | 20dB Bandwidth (kHz) | Pass / Fail |
|---------|-------------------------|----------------------|-------------|
| Low     | 2402                    | 883.00               | N/A         |
| Middle  | 2441                    | 878.00               | N/A         |
| High    | 2480                    | 880.00               | N/A         |


### Modulation Type: 8-DPSK / 3-DH5


| Channel | Channel Frequency (MHz) | 20dB Bandwidth (kHz) | Pass / Fail |
|---------|-------------------------|----------------------|-------------|
| Low     | 2402                    | 1261.00              | N/A         |
| Middle  | 2441                    | 1261.00              | N/A         |
| High    | 2480                    | 1262.00              | N/A         |

## 20dB BANDWIDTH









## 7.2 MAXIMUM PEAK OUTPUT POWER


### LIMIT

§15.247(b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### TEST EQUIPMENT

| Name of Equipment     | Manufacturer | Model  | Serial Number | Calibration Due |
|-----------------------|--------------|--------|---------------|-----------------|
| EXA Spectrum Analyzer | KEYSIGHT     | N9010A | MY54430216    | 05/08/2019      |

### Test Configuration



### TEST PROCEDURE

The RF power output was measured with a Spectrum Analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency. A power meter was used to record the shape of the transmit signal.

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

## TEST RESULTS

|                 |             |           |            |
|-----------------|-------------|-----------|------------|
| Model Name      | TN-280BT    | Test By   | Ted Huang  |
| Temp & Humidity | 26.5°C, 42% | Test Date | 2018/06/13 |


### Modulation Type: GFSK / DH5


| Channel | Channel Frequency (MHz) | Peak Power Output (dBm) | Peak Power Output (mW) | Limit (mW) | Result |
|---------|-------------------------|-------------------------|------------------------|------------|--------|
| Low     | 2402                    | 7.14                    | 5.17845                | 125        | PASS   |
| Mid     | 2441                    | 7.73                    | 5.93198                |            | PASS   |
| High    | 2480                    | 5.87                    | 3.86367                |            | PASS   |


### Modulation Type: 8-DPSK / 3-DH5


| Channel | Channel Frequency (MHz) | Peak Power Output (dBm) | Peak Power Output (mW) | Limit (mW) | Result |
|---------|-------------------------|-------------------------|------------------------|------------|--------|
| Low     | 2402                    | 6.14                    | 4.10771                | 125        | PASS   |
| Mid     | 2441                    | 6.50                    | 4.46786                |            | PASS   |
| High    | 2480                    | -0.02                   | 0.99541                |            | PASS   |

## MAXIMUM PEAK OUTPUT POWER









## 7.3 HOPPING CHANNEL SEPARATION


### LIMIT

§15.247(a)(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### TEST EQUIPMENT

| Name of Equipment     | Manufacturer | Model  | Serial Number | Calibration Due |
|-----------------------|--------------|--------|---------------|-----------------|
| EXA Spectrum Analyzer | KEYSIGHT     | N9010A | MY54430216    | 05/08/2019      |

### TEST SETUP



### TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of adjacent channels.
4. Measure the frequency difference of these two adjacent channels by spectrum analyzer MARK function. And then plot the result on spectrum analyzer screen.
5. Repeat above procedures until all frequencies measured were complete.

## TEST RESULTS

Refer to section 8.1, 20dB bandwidth measurement, the measured channel separation should be greater than two-third of 20dB bandwidth or Minimum bandwidth.

|                            |             |                  |            |
|----------------------------|-------------|------------------|------------|
| <b>Model Name</b>          | TN-280BT    | <b>Test By</b>   | Ted Huang  |
| <b>Temp &amp; Humidity</b> | 26.5°C, 42% | <b>Test Date</b> | 2018/06/13 |



### Modulation Type: GFSK / DH5



| Channel | Adjacent Hopping Channel Separation (MHz) | Two –third of 20dB bandwidth (MHz) | Minimum Bandwidth (kHz) | Result |
|---------|---|------------------------------------|-------------------------|--------|
| 2402MHz | 1.00                                      | 0.59                               | 25 KHz                  | PASS   |
| 2441MHz | 1.00                                      | 0.59                               | 25 KHz                  | PASS   |
| 2480MHz | 1.00                                      | 0.59                               | 25 KHz                  | PASS   |



### Modulation Type: 8-DPSK / 3-DH5

| Channel | Adjacent Hopping Channel Separation (kHz) | Two –third of 20dB bandwidth (kHz) | Minimum Bandwidth (kHz) | Result |
|---------|---|------------------------------------|-------------------------|--------|
| 2402MHz | 1.00                                      | 0.84                               | 25 KHz                  | PASS   |
| 2441MHz | 1.00                                      | 0.84                               | 25 KHz                  | PASS   |
| 2480MHz | 1.00                                      | 0.84                               | 25 KHz                  | PASS   |

## **HOPPING CHANNEL SEPARATION**







## 7.4 NUMBER OF HOPPING FREQUENCY USED


### LIMIT

§15.247(a)(1)(iii) For frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### TEST EQUIPMENT

| Name of Equipment     | Manufacturer | Model  | Serial Number | Calibration Due |
|-----------------------|--------------|--------|---------------|-----------------|
| EXA Spectrum Analyzer | KEYSIGHT     | N9010A | MY54430216    | 05/08/2019      |

### TEST SETUP



### TEST PROCEDURE

- 1 Check the calibration of the measuring instrument (spectrum analyzer) using either an internal calibrator or a known signal from an external generator.
- 2 Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- 3 Set the spectrum analyzer on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- 4 Set the spectrum analyzer on View mode and then plot the result on spectrum analyzer screen.
- 5 Repeat above procedures until all frequencies measured were complete.

## TEST RESULTS

|                            |             |                  |            |
|----------------------------|-------------|------------------|------------|
| <b>Model Name</b>          | TN-280BT    | <b>Test By</b>   | Ted Huang  |
| <b>Temp &amp; Humidity</b> | 26.5°C, 42% | <b>Test Date</b> | 2018/06/13 |

### Modulation Type: GFSK / DH5


| Result(No.of CH) | Limit(No.of CH) | Result |
|------------------|-----------------|--------|
| 79               | >75             | PASS   |

### Modulation Type: 8-DPSK / 3-DH5


| Result(No.of CH) | Limit(No.of CH) | Result |
|------------------|-----------------|--------|
| 79               | >75             | PASS   |

## NUMBER OF HOPPING FREQUENCY USED

### GFSK



### 8-DPSK



## 7.5 DWELL TIME ON EACH CHANNEL


### LIMIT

§15.247(a)(1)(iii) For frequency hopping system operating in the 2400-2483.5MHz band, the average time of occupancy on any frequency shall not be greater than 0.4 second within a 31.6 second period.

### TEST EQUIPMENT

| Name of Equipment     | Manufacturer | Model  | Serial Number | Calibration Due |
|-----------------------|--------------|--------|---------------|-----------------|
| EXA Spectrum Analyzer | KEYSIGHT     | N9010A | MY54430216    | 05/08/2019      |

### TEST SETUP



### TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT as shown in test setup without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of spectrum analyzer on any frequency to be measured and set spectrum analyzer to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.
6. The Bluetooth Headset has 3 type of payload, DH1, DH3, DH5. The hopping rate is 1600 per second. The longer the payload is, the slower the hopping rate is.

## TEST RESULTS

Time of occupancy on the TX channel in 31.6sec = time domain slot length × hop rate ÷ number of hop per channel × 31.6

Refer to the attached graph.

The hopping rates of Bluetooth devices change with different types of payload. The longer the payload is, the slower the hopping rate. The hopping rate scenario is defined in Bluetooth core specification.

|                 |             |  |           |            |
|-----------------|-------------|--|-----------|------------|
| Model Name      | TN-280BT    |  | Test By   | Ted Huang  |
| Temp & Humidity | 26.5°C, 42% |  | Test Date | 2018/06/13 |

### Modulation Type: GFSK / DH5

| Transmitting Frequency | Packet type | Dwell time (ms) | Time of occupancy on the TX channel in 31.6sec (ms) | Limit for Time of occupancy on the TX channel in 31.6sec (ms) | Results |
|------------------------|-------------|-----------------|---|---|---------|
| 2441MHz                | DH1         | 0.405           | 129.60  | 400.00  | PASS    |
| 2441MHz                | DH3         | 1.650           | 264.00  | 400.00  | PASS    |
| 2441MHz                | DH5         | 2.900           | 309.33  | 400.00  | PASS    |
| 2441MHz                | AFH         | 2.900           | 154.67  | 400.00  | PASS    |

DH1 Dwell time=  $0.405 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 129.60 \text{ (ms)}$

DH3 Dwell time=  $1.650 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 264.00 \text{ (ms)}$

DH5 Dwell time=  $2.900 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 309.33 \text{ (ms)}$

AFH Dwell time=  $2.900 \text{ ms} \times (800 \div 6) \div 20 \times 8 = 154.67 \text{ (ms)}$

### Modulation Type: 8-DPSK / 3-DH5

| Transmitting Frequency | Packet type | Dwell time (ms) | Time of occupancy on the TX channel in 31.6sec (ms) | Limit for Time of occupancy on the TX channel in 31.6sec (ms) | Results |
|------------------------|-------------|-----------------|---|---|---------|
| 2441MHz                | 3DH1        | 0.415           | 132.80  | 400.00  | PASS    |
| 2441MHz                | 3DH3        | 1.670           | 267.20  | 400.00  | PASS    |
| 2441MHz                | 3DH5        | 2.910           | 310.40  | 400.00  | PASS    |
| 2441MHz                | AFH         | 2.910           | 155.20  | 400.00  | PASS    |


3DH1 Dwell time=  $0.415 \text{ ms} \times (1600 \div 2) \div 79 \times 31.6 = 132.80 \text{ (ms)}$


3DH3 Dwell time=  $1.670 \text{ ms} \times (1600 \div 4) \div 79 \times 31.6 = 267.20 \text{ (ms)}$


3DH5 Dwell time=  $2.910 \text{ ms} \times (1600 \div 6) \div 79 \times 31.6 = 310.40 \text{ (ms)}$


AFH Dwell time=  $2.910 \text{ ms} \times (800 \div 6) \div 20 \times 8 = 155.20 \text{ (ms)}$


## DWELL TIME ON EACH PAYLOAD
































## 7.6 DUTY CYCLE

### LIMIT


Nil (No dedicated limit specified in the Rules)

### TEST EQUIPMENT

| Name of Equipment     | Manufacturer | Model  | Serial Number | Calibration Due |
|-----------------------|--------------|--------|---------------|-----------------|
| EXA Spectrum Analyzer | KEYSIGHT     | N9010A | MY54430216    | 05/08/2019      |

*Remark:* Each piece of equipment is scheduled for calibration once a year.

### TEST SETUP



### TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW  $\geq$  OBW if possible; otherwise, set RBW to the largest available value. Set VBW  $\geq$  RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)

## TEST RESULTS

No non-compliance noted.

## TEST DATA

|                 |             |           |            |
|-----------------|-------------|-----------|------------|
| Model Name      | TN-280BT    | Test By   | Ted Huang  |
| Temp & Humidity | 26.5°C, 42% | Test Date | 2018/06/13 |

### Modulation Type: GFSK / DH5

|      | us       | Times | Ton  | Total Ton time(ms) |
|------|----------|-------|------|--------------------|
| Ton1 | 2900.000 | 1     | 2900 |                    |
| Ton2 |          | 0     | 0    |                    |
| Ton3 |          |       | 0    | 2.9                |
| Tp   |          |       |      | 3.75               |

|              |             |
|--------------|-------------|
| Ton          | 2.9         |
| Tp(Ton+Toff) | 3.75        |
| Duty Cycle   | 0.773333333 |
| Duty Factor  | 1.116332698 |


### Modulation Type: 8-DPSK / 3-DH5


|      | us       | Times | Ton  | Total Ton time(ms) |
|------|----------|-------|------|--------------------|
| Ton1 | 2910.000 | 1     | 2910 |                    |
| Ton2 |          | 0     | 0    |                    |
| Ton3 |          |       | 0    | 2.91               |
| Tp   |          |       |      | 3.75               |


|              |             |
|--------------|-------------|
| Ton          | 2.91        |
| Tp(Ton+Toff) | 3.75        |
| Duty Cycle   | 0.776       |
| Duty Factor  | 1.101382787 |


## **TEST PLOT**

## Duty Cycle









## 7.7 CONDUCTED SPURIOUS EMISSION

### LIMITS

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the and that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### TEST EQUIPMENT

| Name of Equipment     | Manufacturer | Model  | Serial Number | Calibration Due |
|-----------------------|--------------|--------|---------------|-----------------|
| EXA Spectrum Analyzer | KEYSIGHT     | N9010A | MY54430216    | 05/08/2019      |

### TEST SETUP



### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

## TEST RESULTS


|                 |             |           |            |
|-----------------|-------------|-----------|------------|
| Model Name      | TN-280BT    | Test By   | Ted Huang  |
| Temp & Humidity | 26.5°C, 42% | Test Date | 2018/06/13 |


### OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT



CH Low ( 30MHz ~ 26.5GHz / GFSK )



CH Mid ( 30MHz ~ 26.5GHz / GFSK )













## BAND-EDGE COMPLIANCE OF RF CONDUCTED EMISSIONS

CH Low / GFSK



## CH High / GFSK





## 7.8 RADIATED EMISSIONS

### 7.7.1 TRANSMITTER RADIATED SUPURIOUS EMISSIONS

#### LIMITS

§ 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz                        | MHz                   | MHz             | GHz              |
|----------------------------|-----------------------|-----------------|------------------|
| 0.090 - 0.110              | 16.42 - 16.423        | 399.9 - 410     | 4.5 - 5.15       |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525   | 608 - 614       | 5.35 - 5.46      |
| 2.1735 - 2.1905            | 16.80425 - 16.80475   | 960 - 1240      | 7.25 - 7.75      |
| 4.125 - 4.128              | 25.5 - 25.67          | 1300 - 1427     | 8.025 - 8.5      |
| 4.17725 - 4.17775          | 37.5 - 38.25          | 1435 - 1626.5   | 9.0 - 9.2        |
| 4.20725 - 4.20775          | 73 - 74.6             | 1645.5 - 1646.5 | 9.3 - 9.5        |
| 6.215 - 6.218              | 74.8 - 75.2           | 1660 - 1710     | 10.6 - 12.7      |
| 6.26775 - 6.26825          | 108 - 121.94          | 1718.8 - 1722.2 | 13.25 - 13.4     |
| 6.31175 - 6.31225          | 123 - 138             | 2200 - 2300     | 14.47 - 14.5     |
| 8.291 - 8.294              | 149.9 - 150.05        | 2310 - 2390     | 15.35 - 16.2     |
| 8.362 - 8.366              | 156.52475 - 156.52525 | 2483.5 - 2500   | 17.7 - 21.4      |
| 8.37625 - 8.38675          | 156.7 - 156.9         | 2655 - 2900     | 22.01 - 23.12    |
| 8.41425 - 8.41475          | 162.0125 - 167.17     | 3260 - 3267     | 23.6 - 24.0      |
| 12.29 - 12.293             | 167.72 - 173.2        | 3332 - 3339     | 31.2 - 31.8      |
| 12.51975 - 12.52025        | 240 - 285             | 3345.8 - 3338   | 36.43 - 36.5     |
| 12.57675 - 12.57725        | 322 - 335.4           | 3600 - 4400     | ( <sup>2</sup> ) |
| 13.36 - 13.41              |                       |                 |                  |

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§ 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 30 - 88         | 100 **                            | 3                             |
| 88 - 216        | 150 **                            | 3                             |
| 216 - 960       | 200 **                            | 3                             |
| Above 960       | 500                               | 3                             |

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz, However, operation within these frequency bands is permitted under other sections of this Part, e-g, Sections 15.231 and 15.241.

§ 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

#### TEST EQUIPMENT


| Chamber 966                      |               |                 |               |                 |
|----------------------------------|---------------|-----------------|---------------|-----------------|
| Name of Equipment                | Manufacturer  | Model           | Serial Number | Calibration Due |
| Active Loop Antenna              | ETS-LINDREN   | 6502            | 8905-2356     | 07/19/2019      |
| Amplifier                        | HP            | 8447F           | 2443A01671    | 01/21/2019      |
| Bi-Log Antenna                   | Sunol         | JB1             | A070506-2     | 02/08/2019      |
| Cable                            | Rosnol+Suhner | SUCOFLEX 104PEA | SN25737 /4PEA | 01/26/2019      |
| Double Ridged Guide Horn Antenna | ETS-LINDGREN  | 3116            | 00078900      | 03/19/2019      |
| EMI Test Receiver                | R&S           | ESCI            | 100782        | 06/11/2019      |
| Horn Antenna                     | Com-Power     | AH-118          | 071032        | 04/18/2019      |
| Pre-Amplifier                    | EMCI          | EMC012645       | 980098        | 01/21/2019      |
| PSA Series Spectrum Analyzer     | Agilent       | E4446A          | MY43360132    | 06/06/2019      |
| Software                         | Excel         |                 |               |                 |

**Remark:** 1. Each piece of equipment is scheduled for calibration once a year.  
 2. N.C.R = No Calibration Request.


## TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission from below 1GHz.


### 9kHz ~ 30MHz



### 30MHz ~ 1GHz



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



## TEST PROCEDURE

- The EUT was placed on the top of a rotating table 0.8/1.5 meters above the ground at a 10/3 meter open site/chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- While measuring the radiated emission below 1GHz, the EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 or 10 meters away from the interference-receiving antenna
- The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Note :

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 510 Hz for Average detection (AV) at frequency above 1GHz.

## 7.7.2 WORST-CASE RADIATED EMISSION BELOW 1 GHz


### BELOW 1 GHz (9kHz ~ 30MHz)

No emission found between lowest internal used/generated frequency to 30MHz.

**BELOW 1 GHz (30MHz ~ 1GHz)**

|                     |               |                            |             |
|---------------------|---------------|----------------------------|-------------|
| <b>Product Name</b> | ANALOG PLAYER | <b>Test Date</b>           | 2018/06/13  |
| <b>Model Name</b>   | TN-280BT      | <b>Test By</b>             | Ted Huang   |
| <b>Test Mode</b>    | TX            | <b>Temp &amp; Humidity</b> | 25.4°C, 43% |


Vertical


**Remark:**

1. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).
2. Radiated emissions measured were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Margin (dB) = Remark result (dB $\mu$ V/m) – Quasi-peak limit (dB $\mu$ V/m).

|                     |               |                            |             |
|---------------------|---------------|----------------------------|-------------|
| <b>Product Name</b> | ANALOG PLAYER | <b>Test Date</b>           | 2018/06/13  |
| <b>Model Name</b>   | TN-280BT      | <b>Test By</b>             | Ted Huang   |
| <b>Test Mode</b>    | TX            | <b>Temp &amp; Humidity</b> | 25.4°C, 43% |

## Horizontal


**Remark:**

1. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).
2. Radiated emissions measured were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Margin (dB) = Remark result (dB $\mu$ V/m) – Quasi-peak limit (dB $\mu$ V/m).

### 7.7.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHz

|              |                  |  |  |           |                 |  |  |  |
|--------------|------------------|--|--|-----------|-----------------|--|--|--|
| Product Name | ANALOG PLAYER    |  |  | Test Date | 2018/06/13      |  |  |  |
| Model Name   | TN-280BT         |  |  |           | Test By         |  |  |  |
| Test Mode    | CH Low TX / GFSK |  |  |           | Temp & Humidity |  |  |  |

Horizontal

| TX mode / CH Low |              |        |            | Measurement Distance at 3m |        |                | Horizontal polarity |        |         |   |
|------------------|--------------|--------|------------|----------------------------|--------|----------------|---------------------|--------|---------|---|
| Freq.            | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit               | Margin | Mark    |   |
| (MHz)            | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)      | (dB)   | (P/Q/A) |   |
| *                | 1038.54      | 58.67  | 24.56      | 1.90                       | 45.40  | 0.40           | 40.13               | 74.00  | -33.87  | P |
| *                | 1038.54      | 48.96  | 24.56      | 1.90                       | 45.40  | 0.40           | 30.43               | 54.00  | -23.57  | A |
| *                | 4804.02      | 59.26  | 32.91      | 4.37                       | 44.32  | 0.22           | 52.46               | 74.00  | -21.54  | P |
| *                | 4804.02      | 52.48  | 32.91      | 4.37                       | 44.32  | 0.22           | 45.67               | 54.00  | -8.33   | A |
|                  | 7205.68      | 56.63  | 38.70      | 5.50                       | 44.04  | 0.27           | 57.07               | 74.00  | -16.93  | P |
|                  | 7205.68      | 45.62  | 38.70      | 5.50                       | 44.04  | 0.27           | 46.05               | 54.00  | -7.95   | A |

Vertical

| TX mode / CH Low |              |        |            | Measurement Distance at 3m |        |                | Vertical polarity |        |         |   |
|------------------|--------------|--------|------------|----------------------------|--------|----------------|-------------------|--------|---------|---|
| Freq.            | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit             | Margin | Mark    |   |
| (MHz)            | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)    | (dB)   | (P/Q/A) |   |
| *                | 1328.08      | 60.30  | 25.78      | 2.16                       | 45.16  | 0.44           | 43.52             | 74.00  | -30.48  | P |
| *                | 1328.08      | 50.12  | 25.78      | 2.16                       | 45.16  | 0.44           | 33.34             | 54.00  | -20.66  | A |
| *                | 4804.00      | 59.36  | 32.91      | 4.37                       | 44.32  | 0.22           | 52.55             | 74.00  | -21.45  | P |
| *                | 4804.00      | 54.15  | 32.91      | 4.37                       | 44.32  | 0.22           | 47.34             | 54.00  | -6.66   | A |
|                  | 7205.80      | 56.97  | 38.70      | 5.50                       | 44.04  | 0.27           | 57.41             | 74.00  | -16.59  | P |
|                  | 7205.80      | 48.55  | 38.70      | 5.50                       | 44.04  | 0.27           | 48.98             | 54.00  | -5.02   | A |

#### Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=510Hz
3. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}$$

$$\text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.

|              |                  |  |  |                 |             |  |  |
|--------------|------------------|--|--|-----------------|-------------|--|--|
| Product Name | ANALOG PLAYER    |  |  | Test Date       | 2018/06/13  |  |  |
| Model Name   | TN-280BT         |  |  | Test By         | Ted Huang   |  |  |
| Test Mode    | CH Mid TX / GFSK |  |  | Temp & Humidity | 26.5°C, 42% |  |  |

## Horizontal

| TX mode / CH Mid |              |        |            | Measurement Distance at 3m |        |                | Horizontal polarity |        |         |   |
|------------------|--------------|--------|------------|----------------------------|--------|----------------|---------------------|--------|---------|---|
| Freq.            | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit               | Margin | Mark    |   |
| (MHz)            | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)      | (dB)   | (P/Q/A) |   |
| *                | 1038.62      | 58.78  | 24.56      | 1.90                       | 45.40  | 0.40           | 40.24               | 74.00  | -33.76  | P |
| *                | 1038.62      | 49.23  | 24.56      | 1.90                       | 45.40  | 0.40           | 30.69               | 54.00  | -23.31  | A |
| *                | 4881.83      | 59.05  | 33.15      | 4.42                       | 44.34  | 0.23           | 52.51               | 74.00  | -21.49  | P |
| *                | 4881.83      | 51.45  | 33.15      | 4.42                       | 44.34  | 0.23           | 44.90               | 54.00  | -9.10   | A |
| *                | 7322.91      | 55.57  | 39.10      | 5.53                       | 43.94  | 0.27           | 56.53               | 74.00  | -17.47  | P |
| *                | 7322.91      | 45.60  | 39.10      | 5.53                       | 43.94  | 0.27           | 46.57               | 54.00  | -7.43   | A |

## Vertical

| TX mode / CH Mid |              |        |            | Measurement Distance at 3m |        |                | Vertical polarity |        |         |   |
|------------------|--------------|--------|------------|----------------------------|--------|----------------|-------------------|--------|---------|---|
| Freq.            | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit             | Margin | Mark    |   |
| (MHz)            | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)    | (dB)   | (P/Q/A) |   |
| *                | 1328.25      | 60.48  | 25.78      | 2.16                       | 45.16  | 0.44           | 43.70             | 74.00  | -30.30  | P |
| *                | 1328.25      | 50.28  | 25.78      | 2.16                       | 45.16  | 0.44           | 33.50             | 54.00  | -20.50  | A |
| *                | 4881.96      | 60.59  | 33.15      | 4.42                       | 44.34  | 0.23           | 54.04             | 74.00  | -19.96  | P |
| *                | 4881.96      | 55.32  | 33.15      | 4.42                       | 44.34  | 0.23           | 48.77             | 54.00  | -5.23   | A |
| *                | 7323.02      | 57.10  | 39.10      | 5.53                       | 43.94  | 0.27           | 58.06             | 74.00  | -15.94  | P |
| *                | 7323.02      | 47.64  | 39.10      | 5.53                       | 43.94  | 0.27           | 48.61             | 54.00  | -5.39   | A |

## Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=510Hz
3. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}$$

$$\text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.

|              |                   |  |  |                 |             |  |  |
|--------------|-------------------|--|--|-----------------|-------------|--|--|
| Product Name | ANALOG PLAYER     |  |  | Test Date       | 2018/06/13  |  |  |
| Model Name   | TN-280BT          |  |  | Test By         | Ted Huang   |  |  |
| Test Mode    | CH High TX / GFSK |  |  | Temp & Humidity | 26.5°C, 42% |  |  |

## Horizontal

| TX mode / CH High |              |        |            | Measurement Distance at 3m |        |                | Horizontal polarity |        |         |   |
|-------------------|--------------|--------|------------|----------------------------|--------|----------------|---------------------|--------|---------|---|
| Freq.             | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit               | Margin | Mark    |   |
| (MHz)             | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)      | (dB)   | (P/Q/A) |   |
| *                 | 1038.40      | 58.58  | 24.56      | 1.90                       | 45.40  | 0.40           | 40.04               | 74.00  | -33.96  | P |
| *                 | 1038.40      | 48.86  | 24.56      | 1.90                       | 45.40  | 0.40           | 30.32               | 54.00  | -23.68  | A |
| *                 | 4960.02      | 59.50  | 33.38      | 4.46                       | 44.36  | 0.24           | 53.21               | 74.00  | -20.79  | P |
| *                 | 4960.02      | 53.01  | 33.38      | 4.46                       | 44.36  | 0.24           | 46.73               | 54.00  | -7.27   | A |
| *                 | 7439.80      | 56.00  | 39.50      | 5.56                       | 43.83  | 0.27           | 57.49               | 74.00  | -16.51  | P |
| *                 | 7439.80      | 46.12  | 39.50      | 5.56                       | 43.83  | 0.27           | 47.61               | 54.00  | -6.39   | A |

## Vertical

| TX mode / CH High |              |        |            | Measurement Distance at 3m |        |                | Vertical polarity |        |         |   |
|-------------------|--------------|--------|------------|----------------------------|--------|----------------|-------------------|--------|---------|---|
| Freq.             | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit             | Margin | Mark    |   |
| (MHz)             | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)    | (dB)   | (P/Q/A) |   |
| *                 | 1328.14      | 60.46  | 25.78      | 2.16                       | 45.16  | 0.44           | 43.68             | 74.00  | -30.32  | P |
| *                 | 1328.14      | 50.28  | 25.78      | 2.16                       | 45.16  | 0.44           | 33.50             | 54.00  | -20.50  | A |
| *                 | 4959.95      | 61.86  | 33.38      | 4.46                       | 44.36  | 0.24           | 55.57             | 74.00  | -18.43  | P |
| *                 | 4959.95      | 56.80  | 33.38      | 4.46                       | 44.36  | 0.24           | 50.51             | 54.00  | -3.49   | A |
| *                 | 7439.81      | 56.03  | 39.50      | 5.56                       | 43.83  | 0.27           | 57.52             | 74.00  | -16.48  | P |
| *                 | 7439.81      | 46.94  | 39.50      | 5.56                       | 43.83  | 0.27           | 48.44             | 54.00  | -5.56   | A |

## Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=510Hz
3. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}$$

$$\text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.

|              |                    |                 |             |
|--------------|--------------------|-----------------|-------------|
| Product Name | ANALOG PLAYER      | Test Date       | 2018/06/13  |
| Model Name   | TN-280BT           | Test By         | Ted Huang   |
| Test Mode    | CH Low TX / 8-DPSK | Temp & Humidity | 26.5°C, 42% |

## Horizontal

| TX mode / CH Low |              |        |            | Measurement Distance at 3m |        |                | Horizontal polarity |        |         |   |
|------------------|--------------|--------|------------|----------------------------|--------|----------------|---------------------|--------|---------|---|
| Freq.            | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit               | Margin | Mark    |   |
| (MHz)            | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)      | (dB)   | (P/Q/A) |   |
| *                | 1038.60      | 58.88  | 24.56      | 1.90                       | 45.40  | 0.40           | 40.34               | 74.00  | -33.66  | P |
| *                | 1038.60      | 49.46  | 24.56      | 1.90                       | 45.40  | 0.40           | 30.92               | 54.00  | -23.08  | A |
| *                | 4803.96      | 58.93  | 32.91      | 4.37                       | 44.32  | 0.22           | 52.12               | 74.00  | -21.88  | P |
| *                | 4803.96      | 51.99  | 32.91      | 4.37                       | 44.32  | 0.22           | 45.19               | 54.00  | -8.81   | A |
|                  | 7205.44      | 56.05  | 38.70      | 5.50                       | 44.04  | 0.27           | 56.48               | 74.00  | -17.52  | P |
|                  | 7205.44      | 45.36  | 38.70      | 5.50                       | 44.04  | 0.27           | 45.79               | 54.00  | -8.21   | A |

## Vertical

| TX mode / CH Low |              |        |            | Measurement Distance at 3m |        |                | Vertical polarity |        |         |   |
|------------------|--------------|--------|------------|----------------------------|--------|----------------|-------------------|--------|---------|---|
| Freq.            | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit             | Margin | Mark    |   |
| (MHz)            | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)    | (dB)   | (P/Q/A) |   |
| *                | 1328.32      | 60.68  | 25.78      | 2.16                       | 45.16  | 0.44           | 43.90             | 74.00  | -30.10  | P |
| *                | 1328.32      | 50.35  | 25.78      | 2.16                       | 45.16  | 0.44           | 33.57             | 54.00  | -20.43  | A |
| *                | 4803.97      | 59.86  | 32.91      | 4.37                       | 44.32  | 0.22           | 53.06             | 74.00  | -20.94  | P |
| *                | 4803.97      | 53.38  | 32.91      | 4.37                       | 44.32  | 0.22           | 46.57             | 54.00  | -7.43   | A |
|                  | 7205.71      | 55.81  | 38.70      | 5.50                       | 44.04  | 0.27           | 56.25             | 74.00  | -17.75  | P |
|                  | 7205.71      | 44.99  | 38.70      | 5.50                       | 44.04  | 0.27           | 45.43             | 54.00  | -8.57   | A |

## Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=510Hz
3. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}$$

$$\text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.

|                     |                    |                            |             |
|---------------------|--------------------|----------------------------|-------------|
| <b>Product Name</b> | ANALOG PLAYER      | <b>Test Date</b>           | 2018/06/13  |
| <b>Model Name</b>   | TN-280BT           | <b>Test By</b>             | Ted Huang   |
| <b>Test Mode</b>    | CH Mid TX / 8-DPSK | <b>Temp &amp; Humidity</b> | 26.5°C, 42% |

## Horizontal

| TX mode / CH Mid |              |        |            | Measurement Distance at 3m |        |                | Horizontal polarity |        |         |   |
|------------------|--------------|--------|------------|----------------------------|--------|----------------|---------------------|--------|---------|---|
| Freq.            | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit               | Margin | Mark    |   |
| (MHz)            | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)      | (dB)   | (P/Q/A) |   |
| *                | 1038.45      | 58.67  | 24.56      | 1.90                       | 45.40  | 0.40           | 40.13               | 74.00  | -33.87  | P |
| *                | 1038.45      | 48.96  | 24.56      | 1.90                       | 45.40  | 0.40           | 30.42               | 54.00  | -23.58  | A |
| *                | 4881.89      | 58.28  | 33.15      | 4.42                       | 44.34  | 0.23           | 51.73               | 74.00  | -22.27  | P |
| *                | 4881.89      | 51.15  | 33.15      | 4.42                       | 44.34  | 0.23           | 44.60               | 54.00  | -9.40   | A |
| *                | 7323.35      | 54.84  | 39.10      | 5.53                       | 43.94  | 0.27           | 55.81               | 74.00  | -18.19  | P |
| *                | 7323.35      | 45.00  | 39.10      | 5.53                       | 43.94  | 0.27           | 45.97               | 54.00  | -8.03   | A |

## Vertical

| TX mode / CH Mid |              |        |            | Measurement Distance at 3m |        |                | Vertical polarity |        |         |   |
|------------------|--------------|--------|------------|----------------------------|--------|----------------|-------------------|--------|---------|---|
| Freq.            | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit             | Margin | Mark    |   |
| (MHz)            | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)    | (dB)   | (P/Q/A) |   |
| *                | 1328.18      | 60.75  | 25.78      | 2.16                       | 45.16  | 0.44           | 43.97             | 74.00  | -30.03  | P |
| *                | 1328.18      | 50.48  | 25.78      | 2.16                       | 45.16  | 0.44           | 33.70             | 54.00  | -20.30  | A |
| *                | 4881.85      | 59.71  | 33.15      | 4.42                       | 44.34  | 0.23           | 53.16             | 74.00  | -20.84  | P |
| *                | 4881.85      | 53.23  | 33.15      | 4.42                       | 44.34  | 0.23           | 46.69             | 54.00  | -7.31   | A |
| *                | 7323.22      | 55.46  | 39.10      | 5.53                       | 43.94  | 0.27           | 56.42             | 74.00  | -17.58  | P |
| *                | 7323.22      | 44.33  | 39.10      | 5.53                       | 43.94  | 0.27           | 45.30             | 54.00  | -8.70   | A |

## Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=510Hz
3. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}$$

$$\text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.

|              |                     |                 |             |
|--------------|---------------------|-----------------|-------------|
| Product Name | ANALOG PLAYER       | Test Date       | 2018/06/13  |
| Model Name   | TN-280BT            | Test By         | Ted Huang   |
| Test Mode    | CH High TX / 8-DPSK | Temp & Humidity | 26.5°C, 42% |

## Horizontal

| TX mode / CH High |              |        |            | Measurement Distance at 3m |        |                | Horizontal polarity |        |         |   |
|-------------------|--------------|--------|------------|----------------------------|--------|----------------|---------------------|--------|---------|---|
| Freq.             | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit               | Margin | Mark    |   |
| (MHz)             | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)      | (dB)   | (P/Q/A) |   |
| *                 | 1038.54      | 58.45  | 24.56      | 1.90                       | 45.40  | 0.40           | 39.91               | 74.00  | -34.09  | P |
| *                 | 1038.54      | 48.78  | 24.56      | 1.90                       | 45.40  | 0.40           | 30.24               | 54.00  | -23.76  | A |
| *                 | 4960.02      | 59.23  | 33.38      | 4.46                       | 44.36  | 0.24           | 52.95               | 74.00  | -21.05  | P |
| *                 | 4960.02      | 52.18  | 33.38      | 4.46                       | 44.36  | 0.24           | 45.90               | 54.00  | -8.10   | A |
| *                 | 7440.17      | 54.82  | 39.50      | 5.56                       | 43.83  | 0.27           | 56.31               | 74.00  | -17.69  | P |
| *                 | 7440.17      | 44.37  | 39.50      | 5.56                       | 43.83  | 0.27           | 45.87               | 54.00  | -8.13   | A |

## Vertical

| TX mode / CH High |              |        |            | Measurement Distance at 3m |        |                | Vertical polarity |        |         |   |
|-------------------|--------------|--------|------------|----------------------------|--------|----------------|-------------------|--------|---------|---|
| Freq.             | Reading      | AF     | Cable Loss | Pre-amp                    | Filter | Level          | Limit             | Margin | Mark    |   |
| (MHz)             | (dB $\mu$ V) | (dB/m) | (dB)       | (dB)                       | (dB)   | (dB $\mu$ V/m) | (dB $\mu$ V/m)    | (dB)   | (P/Q/A) |   |
| *                 | 1328.12      | 60.58  | 25.78      | 2.16                       | 45.16  | 0.44           | 43.80             | 74.00  | -30.20  | P |
| *                 | 1328.12      | 50.45  | 25.78      | 2.16                       | 45.16  | 0.44           | 33.67             | 54.00  | -20.33  | A |
| *                 | 4959.96      | 60.79  | 33.38      | 4.46                       | 44.36  | 0.24           | 54.50             | 74.00  | -19.50  | P |
| *                 | 4959.96      | 54.50  | 33.38      | 4.46                       | 44.36  | 0.24           | 48.22             | 54.00  | -5.78   | A |
| *                 | 7440.15      | 55.23  | 39.50      | 5.56                       | 43.83  | 0.27           | 56.72             | 74.00  | -17.28  | P |
| *                 | 7440.15      | 45.01  | 39.50      | 5.56                       | 43.83  | 0.27           | 46.51             | 54.00  | -7.49   | A |

## Remark:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=510Hz
3. The result basic equation calculation is as follow:  

$$\text{Level} = \text{Reading} + \text{AF} + \text{Cable} - \text{Preamp} + \text{Filter}$$


$$\text{Margin} = \text{Level} - \text{Limit}$$
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.

## 7.7.4 RESTRICTED BAND EDGES

|                            |             |                  |            |
|----------------------------|-------------|------------------|------------|
| <b>Model Name</b>          | TN-280BT    | <b>Test By</b>   | Ted Huang  |
| <b>Temp &amp; Humidity</b> | 26.5°C, 42% | <b>Test Date</b> | 2018/06/13 |


## Detector Mode : Peak

## Polarity : Horizontal




## Detector Mode : Average

## Polarity : Horizontal




**Detector Mode : Peak**

**Polarity : Vertical**




**Detector Mode : Average**

**Polarity : Vertical**




**Detector Mode : Peak**

**Polarity : Horizontal**




**Detector Mode : Average**

**Polarity : Horizontal**




Detector Mode : Peak

Polarity : Vertical




Detector Mode : Average

Polarity : Vertical




**Detector Mode : Peak**

**Polarity : Horizontal**




**Detector Mode : Average**

**Polarity : Horizontal**




**Detector Mode : Peak**

**Polarity : Vertical**




**Detector Mode : Average**

**Polarity : Vertical**




Detector Mode : Peak

Polarity : Horizontal




Detector Mode : Average

Polarity : Horizontal




Detector Mode : Peak

Polarity : Vertical



Detector Mode : Average

Polarity : Vertical



## 7.9 POWERLINE CONDUCTED EMISSIONS

### LIMITS

§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.



| Frequency of Emission (MHz) | Conducted limit (dB $\mu$ V) |          |
|-----------------------------|------------------------------|----------|
|                             | Quasi-peak                   | Average  |
| 0.15 - 0.5                  | 66 to 56                     | 56 to 46 |
| 0.5 - 5                     | 56                           | 46       |
| 5 - 30                      | 60                           | 50       |

### TEST EQUIPMENT

| Conducted Emission room #1 |                |                  |               |                 |
|----------------------------|----------------|------------------|---------------|-----------------|
| Name of Equipment          | Manufacturer   | Model            | Serial Number | Calibration Due |
| BNC Coaxial Cable          | CCS            | BNC50            | 11            | 01/23/2019      |
| EMI Test Receiver          | R&S            | ESCS 30          | 100348        | 01/30/2019      |
| LISN                       | SCHWARZBECK    | NNLK8130         | 8130124       | 11/30/2018      |
| LISN                       | FCC            | FCC-LISN-50-32-2 | 08009         | 05/23/2019      |
| Pulse Limiter              | R&S            | ESH3-Z2          | 100116        | 01/23/2019      |
| Software                   | e-3 (5.04211j) |                  |               |                 |

**Remark:** Each piece of equipment is scheduled for calibration once a year.

## TEST SETUP



## TEST PROCEDURE

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80cm above the horizontal ground plane. The EUT IS CONFIGURED IN ACCORDANCE WITH ANSI C63.10 : 2013.

The resolution bandwidth is set to 9 kHz for both quasi-peak detection and average detection measurements.


Line conducted data is recorded for both NEUTRAL and LINE.

## TEST RESULTS

|                                 |               |                             |                  |
|---------------------------------|---------------|-----------------------------|------------------|
| <b>Model No.</b>                | TN-280BT      | <b>Test Mode</b>            | Normal Operation |
| <b>Environmental Conditions</b> | 24.4 , 55% RH | <b>Resolution Bandwidth</b> | 9 kHz            |
| <b>Tested by</b>                | Peter Chu     |                             |                  |

### LINE

(The chart below shows the highest readings taken from the final data.)




REMARKS : 1. Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB)  
 2. Over Limit (dBuV) = Measured Level (dBuV) – Limits (dBuV)

|                                 |               |                             |                  |
|---------------------------------|---------------|-----------------------------|------------------|
| <b>Model No.</b>                | TN-280BT      | <b>Test Mode</b>            | Normal Operation |
| <b>Environmental Conditions</b> | 24.4 , 55% RH | <b>Resolution Bandwidth</b> | 9 kHz            |
| <b>Tested by</b>                | Peter Chu     |                             |                  |

## NEUTRAL

(The chart below shows the highest readings taken from the final data.)



REMARKS : 1. Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB)  
 2. Over Limit (dBuV) = Measured Level (dBuV) – Limits (dBuV)