

## 5.5. RF EXPOSURE REQUIREMENTS [§§ 1.1310 & 2.1091]

### 5.5.1. Limits

§ 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
<b>(A) Limits for Occupational/Control Exposures</b>				
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30

**Note:** f is frequency in MHz

### 5.5.2. Method of Measurements

#### Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi \cdot r^2} = \frac{EIRP}{4\pi \cdot r^2}$$

Where,

P: power input to the antenna in mW

EIRP: Equivalent (effective) isotropic radiated power.

S: power density mW/cm<sup>2</sup>

G: numeric gain of antenna relative to isotropic radiator

r: distance to centre of radiation in cm

$$r = \sqrt{\frac{PG}{4\pi \cdot S}} = \sqrt{\frac{EIRP}{4\pi \cdot S}}$$

FCC radio frequency exposure limits may be exceeded at distances closer than r cm from the antenna of this device.

### 5.5.3. Evaluation of RF Exposure Compliance Requirements

Maximum RF Power conducted,  $P_{\text{conducted}}[\text{dBm}] = 33.19$  at 769.5 MHz

Maximum Antenna Gain,  $G[\text{dBi}] = 3$

Maximum EIRP,  $P_{\text{EIRP}}[\text{dBm}] = 36.19$

MPE Limit for Occupational/Controlled Exposure,  $S_{\text{controlled}}[\text{mW/cm}^2] = 769.5/300 = 2.57$

MPE Limit for General Population/Uncontrolled Exposure,  $S_{\text{uncontrolled}}[\text{mW/cm}^2] = 769.5/1500 = 0.51$

Calculated RF Safety Distance for Occupational/Controlled Exposure,  $r_{\text{safety\_controlled}}[\text{cm}] = 11.36$

Calculated RF Safety Distance for General Population/Uncontrolled Exposure,  $r_{\text{safety\_uncontrolled}}[\text{cm}] = 25.40$