

元件品号	元件规格	单位	组成用量	备注
X-PW2061Q001-G	(CPS1A+R0RS) Double head socket plug wire black row 6P * 10cm in the same direction with a spacing of 1.0mm	pcs	2	
F-STD40529-F	(R0RS) Gold plated spring needle 5P spacing 2.54mm with plastic bracket free height 6.5mm tail	pcs	1	
F-SW0292-F	(R0RS) EC11 plug-in encoder, 20 pulse 20 position, EC110202ED-HA1-120 metal semi-circular handle, handle height 10.5MM, total height 15MM, no downward pressure function, without nut and washer rotation force: 5-20mNm (50-200 gf. cm)	pcs	1	
F-SW4102-F	(R0RS) Plug in switch, vertical RS28 13 pin 12 speed switch, no downward pressure function, semi-circular plastic handle (RS260112A0X-HA1-008), rotation force: 500g ± 30g	pcs	3	
F-SW05036-F	(R0RS) plug-in mechanical button jog switch force is about 400g ± 60g, diameter 12mm * cap 14.4mm * height 23.3mm, transparent black key, with laser engraved font: (OK, without nuts and washers. (XD-12B) --- (LS mold opening)	pcs	8	
X-PW10713302-G	(CPS1A+R0RS) Single head plug-in gray wire 7P * 13cm spacing 1.25mm with red edge tail soldered 3.5mm	pcs	1	
F-PBS003BL101-F	(R0RS) Left directional key board PCB - TB-RS003-DPAH-1 A1 double-sided fiberglass board/thickness 1.2mm/tin spraying process/double-sided black oil 23.6 * 16 * 1.2mm	pcs	1	
F-SW0359-F	R0RS plug-in horizontal tactile switch 2P handle height 0.8mm foot length 3.0mm 4.5 * 4.5 * 3.8mm 250g	pcs	4	
X-PW10504000-G	(CPS1A+R0RS) Grey wire 5P * 4cm 28 * wire core 7mm with red edge, both ends dipped in tin 3.0 ± 0.5mm	pcs	1	
X-SW0A01-F	(R0RS) plug-in vertical micro switch 3P DFT-10 with handle 20 * 6 * 0.5mm, with a lifespan of 100000	pcs	1	
X-PW10808301-G	(CPS1A+R0RS) Single head plug-in gray wire 8P * 8cm spacing 1.25mm UL2651/28 * with red edge tail soldered 3.5mm	pcs	1	
F-SW03067-F	(R0RS) plug-in with sound and no lock touch switch 6P handle height 5.7mm 8.5 * 8.5 * 14mm 350g ± 30g lifespan 10000 times	pcs	1	
F-PB0V12P1201-F	(R0RS) V12 face plate POGO PIN1 board PCB --- PC-V12-POG01-AY-2 A1 double-sided fiberglass board/1.2/10 inch thick gold-plated process/black oil white letters 34 * 34 * 1.2mm	pcs	1	
F-STS20201-F	(R0RS) SMT socket 2P spacing 2.0mm vertical, high temperature resistant	pcs	1	
F-CS210405-F	(R0RS) SMT capacitor 0402 100nF ± 20% 50V Y5V	pcs	22	
F-CS210501-F	(R0RS)SMT capacitor 0402 1uF -20%-+60% 10V Y5V	pcs	1	
F-CS10602-F	(R0RS)SMT capacitor 0603 10uF ±20% 50V X5R	pcs	2	
F-D0S2C05201-F	▲ (R0RS) SMD ESD diode PT2C051V 5V/SPP 0402 (bidirectional TVS electrostatic tube)	pcs	21	
F-D0S2P03001-F	(R0RS)SMT ESD diode KPESDC2P03V3B 3.3V 0402	pcs	1	
F-D0SSS14501-F	(R0RS)SMD Schottky diode SS14 1A 40V (K14) S0D-123(1206)	pcs	1	
F-D0S8S19003-F	(R0RS)SMD diode B5819W 350MA 40V S0D-323(0805)	pcs	1	
F-DLSWC23-F	(R0RS) SMT LED model: JL-J-3528RGB TBB with IC fog 3.5.0 * 2.8.0 * 1.6mm, RGB embedded control type LED with high temperature resistance	pcs	11	
F-IC(S208RB101-F	(R0RS) SMT main control IC, C832V208RBTS, packaged with LQFP64M pin 64, size 10 * 10mm, brand: Qianhengwei	pcs	1	
F-IC(S8211A102-F	▲ (R0RS) Surface mount voltage regulator IC M8S211A3PG-N, 3.3V, low ripple, current 500mA, package SOT-89-3, pin position: 3, brand: Weineng	pcs	1	
F-LLS060001-F	(R0RS) Surface mounted magnetic beads 600 OHM 0402 100MHz ± 20% (laminated ferrite)	pcs	3	
F-RS23230101-F	(R0RS) Surface mount field-effect transistor S12301DS SOT-23 P channel	pcs	1	
F-PBS0030A101-F	(R0RS) TBRS003 Direct Drive Steering Wheel Panel Motherboard PCB - TB-R003-A-AY-1 A2 Double sided Fiberglass Board/Thickness 1.6mm/10 inch Sinking Gold Process/Double sided Black Oil 143.6 * 89.4 * 1.6mm	pcs	1	
F-RS200001-F	(R0RS)SMT resistor 0 OHM 0402 1/16W ±5%	pcs	1	
F-RS210101-F	(R0RS)SMT resistor 100 OHM 0402 1/16W ±5%	pcs	2	
F-RS210201-F	(R0RS)SMT resistor 1 Kohm 0402 1/16W ±5%	pcs	2	
F-RS210302-F	(R0RS)SMT resistor 10 Kohm 0402 1/16W ±5%	pcs	4	
F-RS210401-F	(R0RS)SMT resistor 100 Kohm 0402 1/16W ±1%	pcs	7	
F-RS210502-F	(R0RS)SMT resistor 1 Mohm 0402 1/16W ±5%	pcs	1	
F-RS222001-F	(R0RS)RSMT resistor 22 OHM 0402 1/16W ±5%	pcs	2	
F-RS222301-F	(R0RS)SMT resistor 22 Kohm 0402 1/16W ±1%	pcs	6	
F-RS224301-F	(R0RS)SMT resistor 24 Kohm 0402 1/16W ±1%	pcs	6	
F-RS242002-F	(R0RS)SMT resistor 3 Kohm 0402 1/16W ±1%	pcs	6	
F-RS247101-F	(R0RS)SMT resistor 470 OHM 0402 1/16W ±5%	pcs	1	
F-RS247302-F	(R0RS)SMT resistor 47 Kohm 0402 1/16W ±1%	pcs	6	
F-RS251202-F	(R0RS)SMT resistor 5.1 Kohm 0402 1/16W ±5%	pcs	2	
F-RS291201-F	(R0RS)SMT resistor 9.1 Kohm 0402 1/16W ±1%	pcs	6	
F-RS300001-F	(R0RS)SMT resistor 0 OHM 0603 1/10W ±5%	pcs	2	
F-STS20201-F	(R0RS)SMT socket 2P spacing 2.0mm vertical, high temperature resistant	pcs	1	
F-STS20609-F	(R0RS) (R0RS) SMT socket with 6P spacing of 1.25mm horizontal, high temperature resistance	pcs	1	
F-STS20609-F	(R0RS)SMT socket 6P with a spacing of 1.0mm, horizontal, high temperature resistant	pcs	2	
F-STS20704-F	(R0RS)Surface mount socket 7P, spacing 1.25mm, horizontal high temperature resistance	pcs	1	
F-STS20807-F	(R0RS)SMT socket 8P spacing 1.25mm horizontal high temperature resistance	pcs	2	
F-STS01613-F	(R0RS)SMT Type-C female seat vertical 16pin length 5.5mm iron shell four pin straight insertion	pcs	1	
F-SWS3060-F	(R0RS)RSurface mounted vertical tactile switch 4P silicone handle height 1.0mm 4.5 * 4.5 * 4mm 250g ± 30g lifespan 100000 times	pcs	2	
F-TBS2N3901-F	(R0RS)SMT transistor 2N3904 SOT-23 NPN	pcs	1	
F-XT3200502-F	(R0RS)SMD crystal 32.000MHz SMD-3225-4P 10PPM CL=12PF	pcs	1	
F-PBS0032L101-F	(R0RS) Left 2 button board PCB - TB-R003-2LKEY-1 A2 double-sided fiberglass board/thickness 1.2mm/10 inch gold-plated process/double-sided black oil 47.4 * 16.6 * 1.2mm	pcs	1	
F-DLSWC19-F	(R0RS) SMT LED 2020 RGB Phantom Light (JL-J2020 RGB-TBB) RGB Embedded Control LED (Timing: ToF=0.3, TOL=0.9)	pcs	27	
F-PBS0032R101-F	(R0RS) Right 2 key board PCB - TB-RS003-2RKEY-1 A2 double-sided fiberglass board/1.2mm thick 10 inch gold plating process/double-sided black oil 47.4 * 16.6 * 1.2mm	pcs	1	
F-IC(S44903101-F	(R0RS) SMT Hall IC - ES4903DS Package SOT-23-3L Pin Position: 3 Brand: Yiliangsheng	pcs	1	
F-PBS003HL101-F	(R0RS) Left wing PCB - TB-RS003-HL-1A3 double-sided fiberglass board/thickness 1.2mm/10 inch gold-plated process/double-sided black oil 28.2 * 27 * 1.2mm	pcs	1	
F-PBS003HR101-F	(R0RS) Right wing PCB - TB-RS003-HR-1 A3 double-sided fiberglass board/thickness 1.2mm/10 inch gold-plated process/double-sided black oil 28.2 * 27 * 1.2mm	pcs	1	
F-PBS003SL101-F	(R0RS) Left large key board PCB - TB-RS003-SRL-1 A3 double-sided fiberglass board/thickness 1.2mm/10 inch gold-plated process/double-sided black oil 28.6 * 18.7 * 1.2mm	pcs	1	
F-PBS003SR101-F	(R0RS) Right large key board PCB - TB-RS003-SRR-1 A3 double-sided fiberglass board/thickness 1.2mm/10 inch gold-plated process/double-sided black oil 28.6 * 18.7 * 1.2mm	pcs	1	
F-PBS003VR101-F	(R0RS) Side Encoder Board PCB - TB-RS003-VR-1 A2 Double sided Fiberglass Board/Thickness 1.2mm/10 inch Gold Sinking Process/Double sided Black Oil 20.7 * 17 * 1.2mm	pcs	1	
F-STS20609-F	(R0RS) SMT socket 6P, spacing 1.0mm, horizontal, high temperature resistant	pcs	1	