

RF EXPOSURE REPORT

FCC ID: XGB-CWBB0027

Report Reference No.: 25EFSB08001 09161

Date of issue: 2025-08-26

Applicant's name: Voyetra Turtle Beach, Inc.

Address: 44 South Broadway, 4th Floor, White Plains NY 10601, USA

Equipment: NSW2 Rematch Wireless Controller

Trade Mark: /

Model: CWBB0027

Ratings: I/P: 5VDC 500mA (Provided by USB-C)
3.7VDC 600mAh (Provided by the battery)

Testing Laboratory: DongGuan ShuoXin Electronic Technology Co., Ltd.

Address: Zone A, 1F, No. 6, XinGang Road YuanGang Street,
XinAn District, ChangAn Town, DongGuan City,
GuangDong, China

According: KDB 447498 D04 Interim General RF Exposure Guidance v01

Test Engineer:



Blue Qiu

Responsible Engineer :



Leo Chen

Authorized Signatory:



Smile Wang

MPE CALCULATION METHOD:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Antenna gain = 1.63dBi

MAX Output Power : 3.371dBm@2402MHz

ERP=3.371+1.63-2.15= 2.851dBm

WORSE CASE:

$$10^{0.337} = 2.17 \text{ mW} < 3 \times 2.5 \text{ mW} = 7.5 \text{ mW}$$

Then SAR evaluation is not required.

END