



FCC PART 15.247

TEST REPORT

For

Voyetra Turtle Beach, Inc.

150 Clearbrook Road, Suite 162, Elmsford, New York 10523, USA

FCC ID: XGB-TB2266

Report Type: Product Type:

Original Report EAR FORCE X32 Transmitter

Test Engineer: Felix Li

Report Number: R1DG111130022-00A

Report Date: 2012-01-30

Alvin Huang

Reviewed By: EMC Engineer

Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen)

6/F, the 3rd Phase of WanLi Industrial Building,

Di Hung

ShiHua Road, FuTian Free Trade Zone

Shenzhen, Guangdong, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report contains data that are not covered by the NVLAP accreditation and are marked with an asterisk "★" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S) TEST METHODOLOGY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	6
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	
External I/O CableBlock Diagram of Test Setup	
SUMMARY OF TEST RESULTS	
FCC §15.247(i) & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)	8
Applicable Standard	
TEST DATA	
FCC §15.203 - ANTENNA REQUIREMENT	9
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	9
FCC§15.207 - CONDUCTED EMISSIONS	10
Measurement Uncertainty	
EUT SETUP	
EMI TEST RECEIVER SETUP TEST PROCEDURE	
TEST PROCEDURE TEST EQUIPMENT LIST AND DETAILS	
TEST RESULTS SUMMARY	
Test Data	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	14
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUPEMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	16
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	

FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER	21
APPLICABLE STANDARD	21
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	23
APPLICABLE STANDARD	23
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	23
TEST DATA	
FCC §15.247(e) - POWER SPECTRAL DENSITY	26
APPLICABLE STANDARD	26
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS.	26
TEST DATA	26

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Voyetra Turtle Beach, Inc.*'s product, model number: *TB300-2266-01 (FCC ID: XGB-TB2266)* ("EUT") in this report was an *EAR FORCE X32 Transmitter*, which was measured approximately: 10.0 cm (L) x 7.0 cm (W) x 3.0 cm (H), rated input voltage: DC 5V from USB port.

Report No.: R1DG111130022-00A

Item	Transmitter Specification
Operation Channel	2462 MHz
Channel Bandwidth	20 MHz
Antennas (soldered on the PCB)	-1.0 dBi
RF Output Power	< 10 dBm
Modulation	OFDM

^{*} All measurement and test data in this report was gathered from production sample serial number: 11113022 (Assigned by Shenzhen BACL). The EUT was received on 2011-11-30.

Objective

This report is prepared on behalf of *Voyetra Turtle Beach, Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

Part 15.407 NII submission with FCC ID: XGB-TB2266 Part 15.247, 15.407 submissions with FCC ID: XGB-TB2265

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is ± 0.96 dB, the uncertainty of any radiation on emissions measurement is ± 4.0 dB

FCC Part 15.247 Page 4 of 27

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Report No.: R1DG111130022-00A

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at http://ts.nist.gov/Standards/scopes/2007070.htm

FCC Part 15.247 Page 5 of 27

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

EUT Exercise Software

Test software: Docklight scripting

Equipment Modifications

No modification was made to the EUT tested.


Local Support Equipment List and Details

Manufacturer	cturer Description Model		Serial Number	
IBM	Laptop	T40	N/A	

External I/O Cable

Cable Description	Length (m)	From Port	То
Unshielded Undetectable USB Cable	2.0	Laptop	EUT
Unshielded Undetectable audio Cable	0.1	Laptop	EUT

Block Diagram of Test Setup



FCC Part 15.247 Page 6 of 27

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC Part 15.247 Page 7 of 27

FCC §15.247(i) & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Report No.: R1DG111130022-00A

Applicable Standard

According to subpart FCC §15.247(i) and §2.1091 systems operating under the provisions of t his section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure							
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mw/cm²)	Averaging Time (Minutes)			
0.3-1.34	614	1.63	*(100)	30			
1.34-30	824/f	2.19/f	$*(180/f^2)$	30			
30-300	27.5	0.073	0.2	30			
300-1500	/	/	f/1500	30			
1500-100,000	/	/	1.0	30			

f = frequency in MHz

Test Data

Predication of MPE limit at a given distance

$$S = PG/4\pi R^2$$

Where:

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally *numeric* gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency	Antenna Gain		Conducted Power		Evaluation Distance	Power Density	MPE Limit
(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm ²)	(mW/cm ²)
2462	-1.0	0.79	-0.42	0.97	20	0.00015	1.0

Result: The device meets FCC MPE limit at 20 cm distance.

FCC Part 15.247 Page 8 of 27

^{* =} Plane-wave equivalent power density

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: R1DG111130022-00A

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (i), Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi

Antenna Connector Construction

The EUT has one patch ceramic antenna on the PCB, which in accordance to section 15.203, the maximum gain is -1.0 dBi; please refer to the internal photos.

Result: Compliance.

FCC Part 15.247 Page 9 of 27


FCC§15.207 - CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is 2.4 dB (k=2, 95% level of confidence).

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC 15.207 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The laptop was connected to a 120 VAC/60 Hz power source.

FCC Part 15.247 Page 10 of 27

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Report No.: R1DG111130022-00A

Test Procedure

During the conducted emission test, the laptop was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	830245/006	2011-03-03	2012-03-02
Rohde & Schwarz	L.I.S.N.	ESH2-Z5	892107/021	2011-03-09	2012-03-08

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15 .207</u>, with the worst margin reading of:

11.02 dB at 0.605 MHz in the Line conducted mode.

Test Data

Environmental Conditions


Temperature:	20 ° C
Relative Humidity:	48 %
ATM Pressure:	100.0 kPa

The testing was performed by Felix li on 2011-12-15.

FCC Part 15.247 Page 11 of 27

Test Mode: Transmitting


120 V, 60 Hz, Line:



Conducted Emissions			FCC Part 15.207		
Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)
0.605	34.98	10.10	46.00	11.02	Ave.
10.075	36.89	10.10	50.00	13.11	Ave.
8.060	34.52	10.10	50.00	15.48	Ave.
19.840	33.27	10.10	50.00	16.73	Ave.
5.340	29.60	10.10	50.00	20.40	Ave.
0.605	35.27	10.10	56.00	20.73	QP
10.070	38.73	10.10	60.00	21.27	QP
19.720	35.96	10.10	60.00	24.04	QP
8.055	34.93	10.10	60.00	25.07	QP
0.200	27.18	10.10	54.57	27.39	Ave.
5.335	29.98	10.10	60.00	30.02	QP
0.200	30.01	10.10	64.57	34.56	QP

FCC Part 15.247 Page 12 of 27

120 V, 60 Hz, Neutral:



Co	Conducted Emissions			FCC Part 15.207			
Frequency (MHz)	Corrected Amplitude (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/Ave./QP)		
0.705	34.04	10.10	46.00	11.96	Ave.		
0.200	39.49	10.10	54.57	15.08	Ave.		
8.960	33.66	10.10	50.00	16.34	Ave.		
2.015	29.61	10.10	46.00	16.39	Ave.		
0.300	34.28	10.10	51.71	17.43	Ave.		
19.590	30.78	10.10	50.00	19.22	Ave.		
0.705	34.28	10.10	56.00	21.72	QP		
19.465	36.45	10.10	60.00	23.55	QP		
0.200	39.54	10.10	64.57	25.03	QP		
2.015	30.13	10.10	56.00	25.87	QP		
8.960	33.75	10.10	60.00	26.25	QP		
0.300	34.77	10.10	61.71	26.94	QP		

FCC Part 15.247 Page 13 of 27

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is $\pm 4.0 \text{ dB}(k=2, 95\% \text{ level of confidence})$.

EUT Setup



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter of laptop was connected to a 120 VAC/60 Hz power source

FCC Part 15.247 Page 14 of 27

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Report No.: R1DG111130022-00A

Frequency Range	RBW	Video B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave.

Test Procedure

During the radiated emission test, the adapter of laptop was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 15 of 27

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Pre-amplifier	HP8447D	2944A09795	2011-08-02	2012-08-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2011-11-11	2012-11-10
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2011-07-05	2012-07-04
Mini-circuits	Pre-amplifier	ZVA-213+	T-E27H	2011-03-08	2012-03-07
Sunol Sciences	Horn Antenna	DRH-118	A052604	2011-05-05	2012-05-04
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07
Electro-Mechanics	Horn antenna	3116	9510-2270	2011-10-11	2012-11-10

Report No.: R1DG111130022-00A

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47</u>, <u>Part 15</u>, <u>Subpart C</u>, <u>section 15.205</u>, <u>15.209</u> and <u>15.247</u>, with the worst margin reading of:

6.0 dB at 749.356500 MHz in the Horizontal polarization

Test Data

Environmental Conditions

Temperature:	25 ° C		
Relative Humidity:	56 %		
ATM Pressure:	100.0 kPa		

The testing was performed by Felix Li on 2011-12-16.


FCC Part 15.247 Page 16 of 27

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Mode: Transmitting

1) 30-1000 MHz:

Auto Test(FCC 15 Class B)




Frequency (MHz)	Corrected Amplitude (dBµV/m)	Ant. Height (cm)	Ant. Polarity (H/V)	Turntable Position (degree)	Correction Factor (dB)	Limit (dBµV/m)	Margin (dB)
749.356500	40.0	182.0	Н	5.0	-2.4	46.0	6.0
99.571250	32.3	252.0	Н	136.0	-14.7	43.5	11.2
948.660000	34.8	199.0	Н	5.0	0.6	46.0	11.2
30.200289	28.6	100.0	V	89.0	-5.5	40.0	11.4
38.620750	26.6	134.0	V	53.0	-11.2	40.0	13.4
299.777000	30.5	100.0	V	22.0	-12.4	46.0	15.5

FCC Part 15.247 Page 17 of 27

Indica	ited	Table -		Test Ar	itenna	Cor	rection 1	Factor	FCC	Part 15.247	/15.205/1	15.209
Frequency (MHz)	S.A. Reading (dBµV)	Detector (PK/Ave.)	Angle	Height (m)	Polar (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre- Amp. (dB)	Cord. Amp. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Comment
Channel Frequency (2462 MHz)												
4924	44.67	PK	120	1.0	V	35.0	4.30	26.75	57.22	74	16.78	harmonic
4924	41.50	PK	90	1.0	Н	36.3	4.30	26.75	55.35	74	18.65	harmonic
4924	21.32	Ave.	90	1.0	Н	36.3	4.30	26.75	35.17	54	18.83	harmonic
4924	21.89	Ave.	35	1.0	V	35.0	4.30	26.75	34.44	54	19.56	harmonic
2498.96	20.66	Ave.	130	1.0	Н	30.9	3.03	26.85	27.74	54	26.26	spurious
2499.60	20.53	Ave.	145	1.0	V	30.3	3.03	26.85	27.01	54	26.99	spurious
2498.96	39.50	PK	130	1.0	Н	30.9	3.03	26.85	46.58	74	27.42	spurious
2499.60	39.17	PK	145	1.0	V	30.3	3.03	26.85	45.65	74	28.35	spurious

Report No.: R1DG111130022-00A

3) Conducted Spurious Emissions at Antenna Port:



FCC Part 15.247 Page 18 of 27

FCC $\S15.247(a)$ (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: R1DG111130022-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions


Temperature:	25 °C		
Relative Humidity:	56%		
ATM Pressure:	100.0kPa		

The testing was performed by Felix Li on 2011-12-16.

Test Result: Pass, please refer to the following table and plot.

FCC Part 15.247 Page 19 of 27

Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)	Result	
2462	10.50	> 500	Pass	



FCC Part 15.247 Page 20 of 27

FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Report No.: R1DG111130022-00A

Test Procedure

- 1. Place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
- 3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 ° C		
Relative Humidity:	56 %		
ATM Pressure:	100.0 kPa		


The testing was performed by Felix Li on 2011-12-16.

FCC Part 15.247 Page 21 of 27

Test Mode: Transmitting

Frequency (MHz)	Conducted Output Power (dBm)	Limit (dBm)	Result
2462	-0.42	30	pass

Output Power



FCC Part 15.247 Page 22 of 27

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Report No.: R1DG111130022-00A

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07

^{*} **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 ° C	
Relative Humidity:	56 %	
ATM Pressure:	100.0 kPa	

The testing was performed by Felix Li on 2011-12-16


Test Result: Compliance

FCC Part 15.247 Page 23 of 27

Frequency Band (MHz)	Delta Peak to Band Emission (dBc)	Limit (dBc)	Result
Left-band	43.03	≥ 20	Pass
Right-band	42.11	≥ 20	Pass


Please refer to following plots.

Left Band Edge



FCC Part 15.247 Page 24 of 27

Right Band Edge



FCC Part 15.247 Page 25 of 27

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Report No.: R1DG111130022-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Adjust the center frequency of SA on any frequency be measured and set SA to 1.5MHz span mode. And then, set RBW and VBW of spectrum analyzer to proper value. (DTS)
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2011-07-08	2012-07-07

^{*} **Statement of Traceability:** Bay Area Compliance Lab Corp. (ShenZhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 ° C	
Relative Humidity:	56 %	
ATM Pressure:	100.0 kPa	


The testing was performed by Felix Li on 2011-12-16.

Test Mode: Transmitting

Test Result: Pass

FCC Part 15.247 Page 26 of 27

Frequency (MHz)	Power Spectral Density (dBm)	Limit (dBm)	Result
2462	-17.95	8	pass



***** END OF REPORT *****

FCC Part 15.247 Page 27 of 27