

Emissions Test Report

EUT Name: Wireless Audio Headset **Model No.:** Ear Force Stealth 500P RX CFR 47 Part 15.247:2014 and RSS 210:2010

Prepared for:

Voyetra Turtle Beach, Inc. 100 Summit Lake Drive, Suite 100 Valhalla, New York 10595 USA

Prepared by:

TUV Rheinland of North America, Inc. 1279 Quarry Lane

Pleasanton, CA 94566 Tel: (925) 249-9123 Fax: (925) 249-9124 http://www.tuv.com/

Report/Issue Date: October 7, 2014 Report Number: 31462893.001

Revision Number: 0

Project Number: 0000122834

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

Statement of Compliance

Manufacturer: Voyetra Turtle Beach, Inc.

100 Summit Lake Drive, Suite 100 Valhalla, New York 10595 USA

Requester / Applicant: Tim Blaney

(530) 277-3482

Name of Equipment: Wireless Audio Headset

Model No. Ear Force Stealth 500P RX (TB300-3270-01)

Type of Equipment: Intentional Radiator

Application of Regulations: CFR 47 Part 15.247:2014 and RSS 210:2010

Test Dates: July 2, 2014 to July 8, 2014

Guidance Documents:

Emissions: ANSI C63.10: 2009, KDB 558074 D01 DTS Measurement Guidance v03r01

Test Methods:

Emissions: ANSI C63.10: 2009, KDB 558074 D01 DTS Measurement Guidance v03r01

The electromagnetic compatibility test and documented data described in this report has been performed and recorded by TUV Rheinland, in accordance with the standards and procedures listed herein. As the responsible authorized agent of the EMC laboratory, I hereby declare that the equipment described above has been shown to be compliant with the EMC requirements of the stated regulations and standards based on these results. If any special accessories and/or modifications were required for compliance, they are listed in the Executive Summary of this report.

This report must not be used to claim product endorsement by A2LA or any agency of the U.S. Government. This report contains data that are not covered by A2LA accreditation. This report shall not be reproduced except in full, without the written authorization of TUV Rheinland of North America.

Jeremy Luong

October 7, 2014

Sarbjit Shelopal

October 7, 2014

Test Engineer

Date

Laboratory Signatory

Date

-onbird Ihelofal









industry Canada Industrie Canada

Testing Cert #3331.02

US5254

2932M-1

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

FCCID: XGB-TB3270, IC: 3879A-3270

Page 2 of 51

Table of Contents

1	Exe	cutive Summary	6
	1.1	Scope	6
	1.2	Purpose	6
	1.3	Summary of Test Results	6
	1.4	Special Accessories	7
	1.5	Equipment Modifications	7
2	Lab	oratory Information	8
	2.1	Accreditations & Endorsements	
	2.1.1	US Federal Communications Commission	8
	2.1.2		
	2.1.3 2.1.4	- · · · · · · · · · · · · · · · · · · ·	
	2.1.4	· · · · · · · · · · · · · · · · · · ·	
	2.2 2.2.1	Test Facilities Emission Test Facility	
	2.2.1	J control of the cont	
		•	
	2.3 2.3.1	Measurement Uncertainty	
	2.3.1	ı	
	2.4	Calibration Traceability	
2		·	
3	Proc	duct Informationduct	
	3.1	Product Description	12
	3.2	Equipment Configuration	12
	3.3	Operating Mode	12
	3.4	Unique Antenna Connector	13
	3.4.1	Results	13
4	Emi	issions	14
	4.1	Output Power Requirements	14
	4.1.1	•	
	4.1.2	Results	15
	4.2	Occupied Bandwidth	19
	4.2.1	1	
	4.2.2	Results	20
	4.3	Out-of-Band Emissions	24
	4.3.1	Test Method	24
	4.3.2	Test Result	25
	4.4	Peak Power Spectral Density	29
	4.4.1		
	4.4.2	Results	30
	4.5	Maximum Permissible Exposure	33

Table of Contents

	4.5.1	Test Methodology	33
	4.5.2	FCC KDB 447498 D01 – General SAR Test Exclusion Guidance	
	4.5.3	EUT Operating Condition	
	4.5.4	Classification	
	4.5.5	SAR Test Exclusion Threshold	
	4.6	Transmitter Spurious Emissions	35
	4.6.1	Test Methodology	
	4.6.2	Transmitter Spurious Emission Limit	36
	4.6.3	Test Results.	36
	4.6.4	Sample Calculation	44
	4.7	AC Conducted Emissions	45
	4.7.1	Test Methodology	
	4.7.2	Test Results	45
5	Test	Equipment List	46
	5.1	Equipment List	46
6	EMC	C Test Plan	47
	6.1	Introduction	47
	6.2	Customer	47
	6.3	Equipment Under Test (EUT)	48
	6.4	Test Specifications	51

Index of Tables

Table 1: Summary of Test Results	6
Table 2: Summary of Uncertainties	11
Table 3: RF Output Power at the Antenna Port – Test Results	15
Table 4: Average Output Power at the Antenna Port – Reference Use Only	15
Table 5: Occupied Bandwidth – Test Results	20
Table 6: Out of Band Emissions – Test Results	25
Table 7: Peak Power Spectral Density – Test Results	30
Table 8: Transmit Spurious Emission at Band-Edge Requirements	37
Table 9: Customer Information	47
Table 10: Technical Contact Information	47
Table 11: EUT Specifications	48
Table 12: Interface Specifications	49
Table 13: Supported Equipment	49
Table 14: Description of Sample used for Testing.	49
Table 15: Description of Test Configuration used for Radiated Measurement.	49
Table 16: Final Test Mode for 2403.35 MHz to 2477.35MHz Band	50
Table 17: Test Specifications	51

1 Executive Summary

1.1 Scope

This report is intended to document the status of conformance with the requirements of the CFR 47 Part 15.247:2014 and RSS 210:2010 based on the results of testing performed on July 2, 2014 through July 8, 2014 on the Wireless Audio Headset Model Ear Force Stealth 500P RX (TB300-3270-01) manufactured by Voyetra Turtle Beach, Inc.. This report only applies to the specific samples tested under the stated test conditions. It is the responsibility of the manufacturer to assure that additional production units of this model are manufactured with identical or EMI equivalent electrical and mechanical components. This report is further intended to document changes and modifications to the EUT throughout its life cycle. All documentation will be included as a supplement.

1.2 Purpose

Testing was performed to evaluate the EMC performance of the EUT in accordance with the applicable requirements, procedures, and criteria defined in the application of regulations and application of standards listed in this report.

1.3 Summary of Test Results

Table 1: Summary of Test Results

10010 10 00111111011	table 1. Summary of Test Results					
Test	Test Method ANSI C63.4: 2009 / ANSI C64.10:2009	Test Parameters	Measured Value	Result		
Spurious Emission in Transmitted Mode	CFR47 15.209, RSS-GEN Sect.7.2.3	Class B	-4.58 dB	Complied		
Restricted Bands of Operation	CFR47 15.205, RSS-210 Sect.2.6	Class B	(Margin)	Complied		
AC Power Conducted Emission	CFR47 15.207, RSS-GEN Sect.7.2.2	Class B	NA	Complied		
Occupied Bandwidth	CFR47 15.247 (a2), RSS GEN Sect.4.4.1	≥ 500 kHz	1.6448 MHz	Complied		
Maximum Transmitted Power	CFR47 15.247 (b3), RSS-210 Sect. A.8.4	30 dBm w/ 6 dBi antenna	+0.02 dBm	Complied		
Peak Power Spectral Density	CFR47 15.247 (e), RSS-210 Sect. A.8.2	8 dBm/ 3 kHz	-25.49 dBm	Complied		
Band Edge Measurement	CFR47 15.247 (d), RSS-210 Sect. A.8.5	-30 dBr	-24.60 dB (Margin)	Complied		

Note: Since EUT is portable device where the end user will have the direct contact as head wear device, RF Exposure/SAR requirements are calculated for human head and body, and EUT met FCC KDB 447498 SAR exclusion. See Section 4.5 of this report

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

1.4 Special Accessories

No special accessories were necessary in order to achieve compliance.

1.5 Equipment Modifications

None.

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

2 Laboratory Information

2.1 Accreditations & Endorsements

2.1.1 US Federal Communications Commission



TUV Rheinland of North America at 1279 Quarry Lane, Ste. A., Pleasanton, CA 94566, is accredited by the commission for performing testing services for the general public on a fee basis. These laboratory test facilities have been fully described in reports submitted to and

accepted by the FCC. The laboratory scope of accreditation includes: Title 47 CFR Parts 15, 18, and 90. The accreditation is updated every 3 years.

2.1.2 NIST / A2LA



TUV Rheinland of North America is accredited by the National Voluntary Laboratory Accreditation Program, which is administered under the auspices of the National Institute of Standards and Technology. The laboratory has been assessed and accredited in accordance with ISO Guide 17025:1999 and ISO 9002 (Lab Code US5254). The scope of laboratory accreditation includes

emission and immunity testing. The accreditation is updated annually.

2.1.3 Canada – Industry Canada



TUV Rheinland of North America at the 1279 Quarry Ln, Pleasanton, CA 94566 address is accredited by Industry Canada for performing testing services for the general public on a fee basis. This laboratory test facilities have been

fully described in reports submitted to and accepted by Industry Canada (File Number 2932M). This reference number is the indication to the Industry Canada Certification Officers that the site meets the requirements of RSS 212, Issue 1 (Provisional). The accreditation is updated every 3 years.

2.1.4 Japan – VCCI



The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) is a group that consists of Information Technology Equipment (ITE) manufacturers and EMC test laboratories. The purpose of the Council is to take voluntary control measures against electromagnetic interference from Information Technology Equipment,

and thereby contribute to the development of a socially beneficial and responsible state of affairs in the realm of Information Technology Equipment in Japan. TUV Rheinland of North America at 1279 Quarry Ln, Pleasanton, CA 94566 has been assessed and approved in accordance with the Regulations for Voluntary Control Measures.

VCCI Registration No. for Pleasanton: A-0031 VCCI Registration No. for Santa Clara: A-0032

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

2.1.5 Acceptance by Mutual Recognition Arrangement



The United States has an established agreement with specific countries under the Asia Pacific Laboratory Accreditation Corporation (APLAC) Mutual Recognition Arrangement. Under this agreement, all TUV Rheinland at 1279 Quarry Ln, Pleasanton, CA 94566 test results and test reports within the scope of the laboratory NIST / A2LA accreditation will be accepted by each member country.

2.2 Test Facilities

All of the test facilities are located at 1279 Quarry Lane, Ste. A, Pleasanton, California 94566, USA. The 2305 Mission College, Santa Clara, 95054, USA location is considered a Pleasanton annex.

2.2.1 Emission Test Facility

The Semi-Anechoic chamber and AC Line Conducted measurement facility used to collect the radiated and conducted data has been constructed in accordance with ANSI C63.7:1992. The site has been measured in accordance with and verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2009, at a test distance of 3 and 5 meters. The site is listed with the FCC and accredited by A2LA (Lab Code US5254). The 3/5-meter semi-anechoic chamber used to collect the radiated data has been verified to comply with the theoretical normalized site attenuation requirements of ANSI C63.4-2009, at a test distance of 3 meters and 5 meters. A report detailing this site can be obtained from TUV Rheinland of North America.

2.2.2 Immunity Test Facility

ESD, EFT, Surge, PQF: These tests are performed in an environmentally controlled room with a $3.7 \text{ m} \times 4.8 \text{ m} \times 3.175 \text{ mm}$ thick aluminum floor connected to PE ground.

For ESD testing, tabletop equipment is placed on an insulated mat with a surface resistivity of 10^9 Ohms/square on a 1.6 m x 0.8 m x 0.8 m high non-conductive table with a 3.175 mm aluminum top (Horizontal Coupling Plane). The HCP is connected to the main ground plane via a low impedance ground strap through two 470-k Ω resistors. The Vertical Coupling Plane consists of an aluminum plate $50~{\rm cm}~x~50~{\rm cm}~x~3.175~{\rm mm}$ thick. The VCP is connected to the main ground plane via a low impedance ground strap through two 470-k Ω resistors.

For EFT, Surge, PQF, the HCP and VCP are removed.

RF Field Immunity testing is performed in a 7.3m x 4.3m x 4.1m anechoic chamber.

RF Conducted and Magnetic Field Immunity testing is performed on a 4.8m x 3.7m x 3.175mm thick aluminum ground plane.

All test areas allow a minimum distance of 1 meter from the EUT to walls or conducting objects.

2.3 Measurement Uncertainty

Two types of measurement uncertainty are expressed in this report, per *ISO Guide To The Expression Of Uncertainty In Measurement*, 1st Edition, 1995.

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Janua Data: October 7, 2014

Issue Date: October 7, 2014

The Combined Standard Uncertainty is the standard uncertainty of the result of a measurement when that result is obtained from the values of a number of other quantities; it is equal to the positive square root of the sum of the variances or co-variances of these other quantities, weighted according to how the measurement result varies with changes in these quantities. The term *standard uncertainty* is the result of a measurement expressed as a standard deviation.

The Expanded Uncertainty defines an interval about the result of a measurement that may be expected to encompass a large fraction of the distribution of values that could reasonably be attributed to the measurand. The fraction may be viewed as the coverage probability or level of confidence of the interval.

2.3.1 Sample Calculation – radiated & conducted emissions

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

Field Strength $(dB\mu V/m) = RAW - AMP + CBL + ACF$

Where: RAW = Measured level before correction $(dB\mu V)$

AMP = Amplifier Gain (dB)

CBL = Cable Loss (dB)

ACF = Antenna Correction Factor (dB/m)

$$\mu V/m = 10^{\frac{\textit{dB}\mu V \, / \, \textit{m}}{20}}$$

Sample radiated emissions calculation @ 30 MHz

Measurement +Antenna Factor-Amplifier Gain+Cable loss=Radiated Emissions (dBuV/m)

25 dBuV/m + 17.5 dB - 20 dB + 1.0 dB = 23.5 dBuV/m

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

2.3.2 Measurement Uncertainties

Table 2: Summary of Uncertainties

	$ m U_{lab}$	$ m U_{cispr}$				
Radiated Disturbance	Radiated Disturbance					
30 MHz – 25,000 MHz	3.2 dB	5.2 dB				
Conducted Disturbance @ M	Conducted Disturbance @ Mains Terminals					
150 kHz – 30 MHz	2.4 dB	3.6 dB				
Disturbance Power						
30 MHz – 300 MHz	3.92 dB	4.5 dB				

Note: U_{lab} is the calculated Combined Standard Uncertainty

 $\mathbf{U}_{\text{cispr}}$ is the measurement uncertainty requirement per CISPR 16.

Measurement Uncertainty Immunity

The estimated combined standard uncertainty for ESD immunity measurements is $\pm 4.1\%$.

The estimated combined standard uncertainty for radiated immunity measurements is $\pm 2.7 dB$.

The estimated combined standard uncertainty for conducted immunity measurements is ± 1.4 dB.

The estimated combined standard uncertainty for damped oscillatory wave immunity measurements is $\pm 8.8\%$.

The estimated combined standard uncertainty for harmonic current and flicker measurements is $\pm 0.45\%$.

Measurement Uncertainty – Radio Testing

The estimated combined standard uncertainty for frequency error measurements is \pm 3.88 Hz

The estimated combined standard uncertainty for carrier power measurements is \pm 1.59 dB.

The estimated combined standard uncertainty for adjacent channel power measurements is ± 1.47 dB.

The estimated combined standard uncertainty for modulation frequency response measurements is $\pm\,0.46$ dB.

The estimated combined standard uncertainty for transmitter conducted emission measurements is ± 4.01 dB

The expanded uncertainty at a level of 95% confidence is obtained by multiplying the combined standard uncertainty by a coverage factor of 2. Compliance criteria are not based on measurement uncertainty.

2.4 **Calibration Traceability**

All measurement instrumentation is traceable to the National Institute of Standards and Technology (NIST). Measurement method complies with ANSI/NCSL Z540-1-1994 and ISO Guide 17025:2005.

Report Number: 31462893.001

EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

Product Information

3.1 Product Description

The Ear Force Stealth 500P Wireless Gaming System consists of two main communication modules, the Stealth 500P RX ("Headset") and the Stealth 500P TX ("Transmitter"). These two modules comprise a closed-loop wireless audio gaming system that utilize a proprietary 2.4 GHz communication technology to offer wireless streaming audio and chat/talkback capabilities.

3.2 **Equipment Configuration**

A description of the equipment configuration is given in Test Plan Section. The EUT was tested as called for in the test standard and was configured and operated in a manner consistent with its intended use. The EUT was connected to rated power and allowed to reach intended operating conditions. The placement of the EUT system components was guided by the test standard and selected to represent typical installation conditions.

In the case of an EUT that can operate in more than one configuration, preliminary testing was performed to determine the configuration that produced maximum radiation.

The final configuration was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

3.3 Operating Mode

A description of the operation mode is given in Test Plan Section. In the case of an EUT that can operate in more than one state, preliminary testing was performed to determine the operating mode that produced maximum radiation.

The final operating mode was selected to produce the worst case radiation for emissions testing and to place the EUT in the most susceptible state for immunity testing.

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX


Issue Date: October 7, 2014

3.4 Unique Antenna Connector

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of CFR47 Parts 15.211, 15.213, 15.217, 15.219, or 15.221.

3.4.1 Results

The Ear Force Stealth 500P RX uses the permanently attached PCB trace antennas inside the device. See EUT Photo for details.



Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4 Emissions

Testing was performed in accordance with CFR 47 Part 15.247:2014 and RSS 210 Annex 8:2010. These test methods are listed under the laboratory's A2LA Scope of Accreditation. This test measures the levels emanating from the EUT, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices. Procedures described in ANSI C63.10: 2009 were used.

4.1 Output Power Requirements

The maximum peak output power requirement is the maximum equivalent isotropic radiated power delivering at the transmitting antenna under specified conditions of measurements in the presence of modulation.


The maximum output power and harmonics shall not exceed CFR47 Part 15.247 (b3):2014 and RSS-210 A.8.4: 2010

The maximum transmitted power is +30 dBm or 1 Watt.

4.1.1 Test Method

The conducted method was used to measure the channel power output according to ANSI C63.10:2009 Section 6.10.3.1. The measurement was performed with modulation per CFR47 Part15.247 (b3):2014 and RSS-210 A.8.4: 2010. This test was conducted on 3 channels of Sample, S/N PP #1. The worst mode result indicated below.

Test Setup:



Method AVGSA-1 of "KDB 558074 – DTS Measurement Guidance v03r01" applies since the Ear Force Stealth 500P RX continuously transmits with duty cycle greater than 98%. Sample detector was used.

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.1.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 3: RF Output Power at the Antenna Port – Test Results

Test Conditi	ons: Conducted	l Measurement	Da	nte: July 2, 2014	
Antenna Typ	e: Integrated		Power	r Setting: See test	plan
Antenna Gai	in: +2.0 dBi		Signal	State: Modulated	
Ambient Ter	Ambient Temp.: 23 °C Relative Humidity:33%				
Wireless Audio Headset					
Frequency (MHz)	Limit [dBm]	Output [dBm]	Duty Cycle [dB]	∑ Power [dBm]	Margin [dB]
2403.35	+30.00	0.02			-29.98
2441.35	+30.00	-0.20			-30.20
2477.35	+30.00	-0.16			-30.16
Note: The he	adset transmitte	ed at 100% duty cy	rcle.		

Table 4: Average Output Power at the Antenna Port – Reference Use Only

Test Condition	ons: Conducted	d Measurement	D	ate: July 2, 2014	
Antenna Typ	e: Integrated		Power	r Setting: See test	plan
Antenna Gai	n: +2.0 dBi		Signal	State: Modulated	
Ambient Ter	np.: 23 °C		Relati	ve Humidity:33%	
		Wireles	s Audio Headset		
Frequency (MHz)	Limit [dBm]	Chain 0 [dBm]	Duty Cycle [dB]	∑ Power [dBm]	Margin [dB]
2403.35	N/A	-0.18			N/A
2441.35	N/A	-0.43			N/A
2477.35 N/A -0.45					N/A
Note: The he	adset transmitte	ed at 100% duty cy	cle.		

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014



Figure 1: Maximum Conducted Output Power at 2403.35MHz – Headset




Figure 2: Maximum Conducted Output Power at 2441.35MHz - Headset



Figure 3: Maximum Conducted Output Power at 2477.35MHz - Headset

Issue Date: October 7, 2014

4.2 Occupied Bandwidth

The occupied bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency.

The 99% bandwidth is the bandwidth in which 99% of the transmitted power occupied.


The 6dB bandwidth is defined the bandwidth of 6dBr from highest transmitted level of the fundamental frequency.

The bandwidth shall be at least 500 kHz per Section CFR47 15.247(a2) 2014 and RSS Gen Sect. 4.4.1: 2010.

4.2.1 Test Method

The conducted method was used to measure the occupied bandwidth according to ANSI C63.10:2009 Section 6.9.1. The measurement was performed with modulation per CFR47 15.247(a2) 2014 and RSS Gen Sect. 4.4.1:2010. This test was conducted on 3 channels in each mode of Sample S/N PP #1. The worst sample result indicated below.

Test Setup:



Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.2.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 5: Occupied Bandwidth – Test Results

Test Conditions: Cond	ucted Measurement	Date: Ju	aly 2, 2014			
Antenna Type: Integra	ted	Power Setti	ng: See test plan			
Antenna Gain: +2.0 dF	Bi	Signal State	: Modulated			
Ambient Temp.: 23 °C	Ambient Temp.: 23 °C Relative Humidity:33%					
	Bandwidth (MHz) for Wireless Audio Headset					
Frequency (MHz)	Limit (kHz)	99% Bandwidth	6 dB Bandwidth	Results		
2403.35	500	1.9041	1.6448	Pass		
2441.35	500	1.9017	1.6958	Pass		
2477.35 500 1.9042 1.6613 Pass						
Note : The bandwidth w	as measured at 100%	duty cycle				

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014



Figure 4: DTS Bandwidth-Headset -2403.35MHz



Figure 5: DTS Bandwidth-Headset -2441.35MHz

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014



Figure 6: DTS Bandwidth-Headset -2477.35MHz




Figure 7: 99% Bandwidth-Headset -2403.35MHz

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

1279 Quarry Lane, Ste. A, Pleasanton, CA 95466

Tel: (925) 249-9123, Fax: (925) 249-9124




Figure 8: 99% Bandwidth-Headset -2441.35MHz




Figure 9: 99% Bandwidth-Headset -2477.35MHz

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.3 Out-of-Band Emissions


The setup was identical to RF output power measurement. Intentional radiators operating under the alternative provisions to the general emission limits, must be designed to ensure that the 20 dB or 30 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If the frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Since the transmitter complies with the conducted power limits base on the use of RMS averaging per CFR47 Part 15.247(b)(3), any frequency outside the band of 2400MHz to 2483.5MHz, the power output level must be below 30db from the in-band transmitting signal; CFR 47 Part 15.215, 15.247(d) and RSS-210 A8.5

4.3.1 Test Method

The conducted method was used to measure the out-of-band emission requirement. The measurement was performed with modulation per CFR47 15.247(4)(d) 2014 and *RSS-210 A8.5: 2010*. This test was conducted on 3 channels of Sample S/N PP #1. The worst sample result indicated below.

Test Setup:



Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.3.2 Test Result

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 6: Out of Band Emissions – Test Results

Test Conditions: Conducted Measurement	Date: July 2, 2014
Antenna Type: Integrated	Power Setting: See test plan
Antenna Gain: +2.0 dBi	Signal State: Modulated
Ambient Temp.: 23 °C	Relative Humidity: 33%

Out of Band Results for Wireless Audio Headset						
Operating Channel	Out of Band Level (dBm)	30 dBr Level (dBm)	Margin (dB)			
2403.35 MHz	-56.79	-31.33	-25.46			
2441.35 MHz	-56.46	-31.86	-24.60			
2477.35 MHz	-56.67	-31.85	-24.82			

Note: The band-edge level must lower than the 30dBr level.

The maximum out of band emission on each individual output put is at least 30 dB below the maximum in-band PSD on that output.

(*) The band-edge is compared to the highest -30dBr level of the test mode.

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014



Figure 10: Conducted Band Edge at 2403.35MHz-Headset




Figure 11: Out of band Emission-2403.35MHz-Headset

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

Tel: (925) 249-9123, Fax: (925) 249-9124




Figure 12: Conducted Band Edge-2441.35MHz-Headset




Figure 13: Out of band Emission-2441.35MHz-Headset

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014




Figure 14: Conducted Band Edge-2477.35MHz-Headset




Figure 15: Out of band Emission-2477.35MHz-Headset

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014


4.4 Peak Power Spectral Density

According to the CFR47 Part 15.247 (e) and RSS-210 (A8.2), the spectral power density output of the antenna port shall be less than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.4.1 Test Method

The conducted method was used to measure the channel power output per ANSI C63.10:2009 Section 6.11.2. The measurement was performed with modulation per CFR47 Part 15.247 (e) and RSS-210 (A8.2). This test was conducted on 3 channels of Sample SN PP #1. The worst sample result indicated below.

Test Setup:



Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.4.2 Results

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Table 7: Peak Power Spectral Density – Test Results

Test Conditions: Conducted Measurement	Date: July 2, 2014	
Antenna Type: Integrated	Power Setting: See test plan	
Antenna Gain: +2.0 dBi	Signal State: Modulated	
- 11 · 17 · 22 · 23		

Ambient Temp.: 23 °C Relative Humidity:33%

Peak Power Spectral Density

Freq. (MHz)	Config.	Output [dBm]	CF [dB]	Max. PPSD [dBm]	Limit [dBm]	Margin [dB]
2403.35	Headset	-10.26	-15.23	-25.49	8.00	-33.49
2441.35	Headset	-10.35	-15.23	-25.58	8.00	-33.58
2477.35	Headset	-10.46	-15.23	-25.69	8.00	-33.69

Note: CF was accounted for the measured RBW.

The bandwidth ratio is 10*log (3kHz/100kHz) or -15.23 dB.

Headset transmitted at 100% duty cycle.

Report Number: 31462893.001

EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014




Figure 16: Maximum Power Spectral Density-2403.35MHz-Headset



Figure 17: Maximum Power Spectral Density-2441.35MHz-Headset

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

1279 Quarry Lane, Ste. A, Pleasanton, CA 95466

Tel: (925) 249-9123, Fax: (925) 249-9124




Figure 18: Maximum Power Spectral Density-2477.35MHz-Headset

4.5 Maximum Permissible Exposure

4.5.1 Test Methodology

In this section, we try to prove the safety of radiation harmfulness to the human body for our product. The KDB 447498 D01 General RF Exposure Guidance is followed. The Gain of the antenna used in this calculation is declared by the manufacturer, and the maximum average power input to the antenna is measured. Using the general SAR test exclusion guidance in Section 4.3 of KDB 447498, we show the device meeting the SAR exclusion threshold.

4.5.2 FCC KDB 447498 D01 – General SAR Test Exclusion Guidance

The SAR exclusion threshold conditions are listed:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation
distances ≤ 50 mm are determined by:
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]
$[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,16 where
☐ f(GHz) is the RF channel transmit frequency in GHz
Power and distance are rounded to the nearest mW and mm before calculation17
☐ The result is rounded to one decimal place for comparison
The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm
and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test
separation distance is $< \hat{5}$ mm, a distance of 5 mm is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following, and as illustrated in Appendix B:18
- a) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·(f(MHz)/150)] mW, at 100 MHz to 1500 MHz
- b) [Threshold at 50 mm in step 1) + (test separation distance 50 mm) \cdot 10] mW at > 1500 MHz and \leq 6 GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion, and as illustrated in Appendix C:19
- a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(MHz))]$ for test separation distances > 50 mm and < 200 mm
- b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for test separation distances \leq 50 mm
- c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.5.3 EUT Operating Condition

The software provided by Manufacturer enabled the EUT to transmit data at lowest, middle and highest channel individually.

4.5.4 Classification

The antenna of the product, under normal use condition, is less than 20cm away from the body of the user. This device is classified as a **Portable Device**. It is intended to be used with head wear device; extremity SAR limit is applied.

4.5.5 SAR Test Exclusion Threshold

4.5.5.1 Antenna Gain

The transmitting antenna was integrated. The omni-directional antenna gain was 2.0 dBi.

4.5.5.2 SAR Exclusion Threshold Calculation

Mode	Max. Power (dBm)	EIRP (dBm)	Min. Separation Distance (mm)	Cal. Excl. Threshold	1-g SAR Limit	10-g extremity SAR Limit	Result
Modulated	0.02	2.02	5	0.5018	<u><</u> 3.0	<u><</u> 7.5	Exempted *

Note:

- Since EUT can operate at distance less than 50 mm, the minimum distance, 5 mm, was used for calculation per condition #1 of SAR Exclusion Threshold.
- 2. The maximum output power was taken from Table 2.
- 3. (*) The calculated threshold is less than 3.0; therefore, EUT is SAR exempted for head and body usage.

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.6 Transmitter Spurious Emissions

Transmitter spurious emissions are emissions outside the frequency range of the equipment when the equipment is in transmit mode; per requirement of CFR47 15.205, 15.209, 15.247(d), RSS-210 Sect. A.8.5

4.6.1 Test Methodology

4.6.1.1 Preliminary Test

A test program that controls instrumentation and data logging was used to automate the preliminary RF emission test procedure. The frequency range of interest was divided into sub-ranges to yield a frequency resolution of approximately 120 kHz and provide a reading at each frequency for no more than 12° of turntable rotation. For each frequency sub-range the turntable was rotated 360° while peak emission data was recorded and plotted over the frequency range of interest in horizontal and vertical antenna polarization's.

Preliminary emission profile testing was performed inside the anechoic chamber. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm above the floor. The EUT was positioned as shown in the setup photographs. The receiving antenna was placed at a distance of 3m at a fixed height of 1m. Measurement equipment was located outside of the chamber. A video camera was placed inside the chamber to view the EUT.

4.6.1.2 Final Test

For each frequency measured, the peak emission was maximized by manipulating the receiving antenna from 1 to 4 meters above the ground plane and placing it at the position that produced the maximum signal strength reading. The turntable was then rotated through 360° while observing the peak signal and placing the EUT at the position that produced maximum radiation. The six highest emissions relative to the limit were measured unless such emissions were more than 20 dB below the limit. If less than six emissions are within 20 dB of the limit, than the noise level of the receiver is measured at frequencies where emissions are expected. Multiples of all oscillator and microprocessor frequencies were also checked.

Final testing was performed on an NSA compliant test site. The EUT was placed on a 1.0m x 1.5m non-conductive table 80cm above the ground plane. The placement of EUT and cables were the same as for preliminary testing and is shown in the setup photographs.

The final scans performed on the worst axis, Y-Axis up, for three operating channels in each operating mode;

2403.35MHz, 2441.35MHz, and 2477.35MHz

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.6.1.3 Deviations

None.

4.6.2 Transmitter Spurious Emission Limit

Above 960..... 500

The spurious emissions of the transmitter shall not exceed the values in CFR47 Part 15.205, 15.209: 2014 and RSS-210 A1.1.2 2010.

______ Measurement Frequency (MHz) Field strength distance (microvolts/meter) (meters) 30 30 3 88-216...... 150 ** 3 3

All harmonics and spurious emission which are outside of the restricted band shall be 20dB below the inband emission.

4.6.3 Test Results

The final measurement data was taken under the worst case operating modes, configurations, and/or cable positions. It also reflects the results including any modifications and/or special accessories listed in Sections 1.4 and Test Plan.

As originally tested, the EUT was found to be compliant to the requirements of the test standard(s).

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

Table 8: Transmit Spurious Emission at Band-Edge Requirements

Test Conditions: Radiated Measurement, Normal Temperature and Voltage only

Antenna Type: Integrated Power Setting: See Test Plan

Max. Antenna Gain: +2.0 dBi Signal State: Modulated

Ambient Temp.: 23 °C Relative Humidity:32%

Band-Edge Results

Center		Edge							
Freq.	Mode	Freq.	Pol.	Ant.	Table	Det.	Level	Limit	Margin
MHz		MHz	V/H	cm	Deg.	Pk/Avg	dBuV/m	dBuV/m	dB
2403.35	Headset – Up Right	2390.00	V	249	45	Pk	59.65	74.00	-14.35
2403.35	Headset – Up Right	2390.00	V	249	45	Ave	44.60	54.00	-9.40
2403.35	Headset – Up Right	2390.00	Н	249	85	Pk	49.58	74.00	-24.42
2403.35	Headset – Up Right	2390.00	Н	249	85	Ave	39.44	54.00	-14.56
2477.35	Headset – Up Right	2483.50	Н	301	77	Pk	55.80	74.00	-18.20
2477.35	Headset – Up Right	2483.50	Н	301	77	Ave	49.16	54.00	-4.84
2477.35	Headset – Up Right	2483.50	V	160	-10	Pk	56.19	74.00	-17.81
2477.35	Headset – Up Right	2483.50	V	160	-10	Ave	49.42	54.00	-4.58
Note: The	emissions were measured	at the adia	cant ra	etricted	hand of th	a fundam	antal cional	•	

Note: The emissions were measured at the adjacent restricted band of the fundamental signal.

1279 Quarry Lane, Ste. A, Pleasanton, CA 95466 Tel: (925) 249-9123, Fax: (925) 249-9124

SOP 1 Radiated Emissions						Track	ing #	31462893.	001 Page	1 of 6	
EUT Name Wireless Audio Headset					Date	Date July 7, 2014					
EUT Mod	el Earl	Force S	tealth 500	P RX			Ten	າp / Hເ	ım in 23	°C / 33%rl	1
EUT Seria		‡2						•	um out N/		
EUT Con		dset up						AC/		'VDC	
Standard	CFR	47 Part	15 Subpa	rt C			RB\	W / VB	W 12	0 kHz/ 300) kHz
Dist/Ant I	Jsed 3m/	JB3					Per	orme	d by Jei	remy Luon	g
Freq.	Raw	Cbl	AF	Level	Det.	Pol.	Hght.	Azt	Limit	Margin	Result
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB	
		•		Transmitte	d Data	at 244	1.35MH	Z			
228.04	43.36	1.84	-21.43	23.76	QP	Н	180	112	46.00	-22.24	Pass
784.91	23.41	2.71	-11.60	14.53	QP	Н	257	336	46.00	-31.48	Pass
30.76	36.15	1.27	-11.80	25.63	QP	V	115	48	40.00	-14.37	Pass
34.94	42.60	1.29	-14.94	28.95	QP	V	100	22	40.00	-11.05	Pass
76.17	37.62	1.45	-24.88	14.19	QP	V	124	12	40.00	-25.81	Pass
330.16	31.89	2.04	-18.39	15.54	QP	V	101	184	46.00	-30.46	Pass
373.51											
CF= Amp (Spec Margin = Level - Limit, Level = Raw+ Cbl+ CF ± Uncertainty CF= Amp Gain + ANT Factor										
Combined S	Combined Standard Uncertainty $u_c(y) = \pm 3.2$ dB Expanded Uncertainty $U = ku_c(y)$ $k = 2$ for 95% confidence										

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Note: The worst case was observed at Channel 2441.35 MHz.

Issue Date: October 7, 2014


1279 Quarry Lane, Ste. A, Pleasanton, CA 95466 Tel: (925) 249-9123, Fax: (925) 249-9124

SOP 1 Ra	SOP 1 Radiated Emissions						Т	racking	g# 3146	62893.001	Page 2 of 6
EUT Name Wireless Audio Headset							Date		July 7	, 2014	
EUT Model	Ear I	orce S	tealth 50	0P RX				Temp	/ Hum ii	23°C	/ 33%rh
EUT Serial	PP#	2						•	/ Hum o		
EUT Config									AC / Fred	•	
Standard			: 15 Subp						/ VBW		:/3MHz
Dist/Ant Us	ed 3m/	DRH-1	18, 1m /	RA42-K-F	-4B-C			Perfo	rmed by	Jerem	ny Luong
Freq	Raw	Cbl	AF	Level	Det	Pol	Hght	Azt	Limit	Margin	Comment
MHz	dBuV/m	dB	dB	dBuV/m		H/V	cm	deg	dBuV/m	dB	
				Transmi	tted Da	ita at 2	1 2403.35	MHz			
4806.00	55.74	2.65	-17.42	40.97	Ave	Н	104	98	54.00	-13.03	Harmonics
7209.70	41.49	3.05	-11.73	32.82	Ave	Η	129	66	54.00	-21.18	Harmonics
9612.99	41.93	3.41	-8.49	36.85	Ave	Н	235	192	54.00	-17.15	Harmonics
				Transmi	tted Da	ita at 2	2441.35	MHz			
4880.06	54.80	2.70	-17.20	40.30	Ave	Ι	194	56	54.00	-13.70	Harmonics
7318.18	42.02	3.07	-11.31	33.78	Ave	V	214	250	54.00	-20.22	Harmonics
9764.74	42.29	3.43	-8.58	37.14	Ave	V	153	146	54.00	-16.86	Harmonics
				Transmi	tted Da	ita at 2	2477.35	MHz			
2994.50	56.75	2.29	-20.46	38.58	Ave	V	241	20	54.00	-15.42	Spurious
4955.07	49.12	2.68	-17.10	34.70	Ave	V	207	58	54.00	-19.30	Harmonics
7425.88 38.94 3.09 -11.07 30.96 Ave V 237 214 54.00 -23.04 Harmonics											
CF= Amp Gai	Spec Margin = Level - Limit, Level = Raw+ Cbl+ CF ± Uncertainty CF= Amp Gain + ANT Factor Combined Standard Uncertainty (1/4) = 2.2 dB = Expended Uncertainty (1/4) = 1/4 (1										


Combined Standard Uncertainty $U_c(y) = \pm 3.2$ dB Expanded Uncertainty $U = ku_c(y)$ k = 2 for 95% confidence


Notes: All emissions passed the spurious emission limit.

Issue Date: October 7, 2014




Tracking # 31462893.001 Page 4 **SOP 1** Radiated Emissions **EUT Name Date** Wireless Audio Headset July 7, 2014 **EUT Model** Ear Force Stealth 500P RX Temp / Hum in 23°C / 33%rh **EUT Serial** PP #2 Temp / Hum out N/A **EUT Config.** Line AC / Freq 3.7VDC Headset **RBW / VBW** Standard CFR47 Part 15 Subpart C 1MHz/3MHz Dist/Ant Used 3m / DRH-118, 1m / RA42-K-F-4B-C Performed by Jeremy Luong Above 1GHz Plots for Transmit Mode at 2403.35MHz 100.0







Notes: Limit was extrapolated to 1m distance for 18GHz – 26GHz range. 1GHz – 25GHz Setting: RBW = 1MHz/ VBW = 3MHz Tel: (925) 249-9123, Fax: (925) 249-9124



Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014





Operator: Jeremy Luong
RE-18GHz-26GHz-3.TIL
05:02:47 PM, Thursday, July 10,2014

Notes: Limit was extrapolated to 1m distance for 18GHz – 25GHz range.

1GHz – 25GHz Setting: RBW = 1MHz/VBW = 3MHz

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.6.4 Sample Calculation

The field strength is calculated by subtracting the Amplifier Gain and adding the Cable Loss and Antenna Correction Factor to the measured reading. The basic equation is as follows:

$$\begin{aligned} \text{Field Strength } (dB\mu V/m) &= \text{FIM - AMP} + \text{CBL} + \text{ACF} \\ \text{Where: FIM} &= \text{Field Intensity Meter } (dB\mu V) \\ \text{AMP} &= \text{Amplifier Gain } (dB) \\ \text{CBL} &= \text{Cable Loss } (dB) \\ \text{ACF} &= \text{Antenna Correction Factor } (dB/m) \\ \mu V/m &= 10^{\frac{dB\mu V/m}{20}} \end{aligned}$$

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

4.7 AC Conducted Emissions

Testing was performed in accordance with ANSI C63.4: 2003. These test methods are listed under the laboratory's A2LA Scope of Accreditation.

This test measures the levels emanating from the EUT's AC input port, thus evaluating the potential for the EUT to cause radio frequency interference to other electronic devices.

The AC conducted emissions of equipment under test shall not exceed the values in CFR47 Part 15.207: 2013 and RSS-210: 2010.

4.7.1 Test Methodology

A test program that controls instrumentation and data logging was used to automate the AC Power Line Conducted emission test procedure. The frequency range of interest was divided into sub-ranges such as to yield a frequency resolution of 9 kHz. Each phase and neutral of the AC power line were measured with respect to ground. Measurements were performed using a set of $50\mu\text{H}$ / 50Ω LISNs.

Testing is either performed in 5m Chamber. The setup photographs clearly identify which site was used. The vertical ground plane used in the semi-anechoic chamber is a 2m x 2m solid aluminum frame and panel, and it is bonded to the horizontal ground plane.

In the case of tabletop equipment, the EUT is placed on a 1.0m x 1.5m non-conductive table 80cm above the ground plane and 40cm from a vertical ground reference plane. The rear of the EUT was positioned flush with the backside of the table and directly over the LISNs. The power and I/O cables were routed over the edge of the table and bundled approximately 40cm from the ground plane. Support equipment was powered from a separate LISN.

4.7.1.1 Deviations

There were no deviations from this test methodology.

4.7.2 Test Results

This test is not required since EUT is powered by DC voltage.

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

5 Test Equipment List

5.1 Equipment List

Equipment	Manufacturer	Model #	Serial/Inst #	Last Cal mm/dd/yy	Next Cal mm/dd/yy
Bilog Antenna	Sunol Sciences	JB3	A020502	04/12/2013	04/12/2015
Horn Antenna	Sunol Sciences	DRH-118	A040806	10/05/2012	10/05/2014
Horn Antenna	CMT	RA42-K-F-4B-C	020131-004	06/20/2013	07/20/2014
Spectrum Analyzer	Rohde & Schwarz	FSL6	100169	01/08/2014	02/08/2015
Spectrum Analyzer	Agilent	N9038A	MY52260210	01/08/2014	02/08/2015
Spectrum Analyzer	Rohde & Schwarz	ESIB	832427/002	01/08/2014	02/08/2015
Spectrum Analyzer	Hewlett Packard	8546A	3325A00168	11/14/2013	11/14/2014
RF Pre-Selector	Hewlett Packard	85460A	3330A00174	11/14/2013	11/14/2014
Amplifier	Hewlett Packard	8447D	2944A07996	01/07/2014	02/07/2015
Amplifier	Miteq	TTA1800-30-4G	1842452	01/08/2014	02/08/2015
Amplifier	Rhode & Schwarz	TS-PR26	100011	06/20/2013	07/20/2014
LISN	Com-Power	LI-250	12111	01/07/2014	02/07/2015
Transient Limiter	Com-Power	LIT930	531582	01/08/2014	02/08/2015
Power Meter	Agilent	E4418B	MY45103902	01/09/2014	02/09/2015
Power Sensor	Hewlett Packard	8482A	55-5131	01/09/2014	02/09/2015
Notch Filter	Micro-Tronics	BRM50702	9	01/06/2014	02/06/2016

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

6 EMC Test Plan

6.1 Introduction

This section provides a description of the Equipment Under Test (EUT), configurations, operating conditions, and performance acceptance criteria. It is an overview of information provided by the manufacturer so that the test laboratory may perform the requested testing.

6.2 Customer

Table 9: Customer Information

Company Name	Voyetra Turtle Beach, Inc.		
Address	100 Summit Lake Drive, Suite 100		
City, State, Zip	Valhalla, New York 10595		
Country	USA		

Table 10: Technical Contact Information

Name Tim Blaney	
E-mail	tim@commcepts.net
Phone	(530) 277-3482
Fax	NA

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

6.3 Equipment Under Test (EUT)

Table 11: EUT Specifications

EUT Specification					
Package Dimensions	225mm (8.9") x 252mm (9.9") x 115mm (4.5")				
Power Input	Headset Input Voltage: 3.7 Vdc (battery)				
Environment	Indoor				
Operating Temperature Range:	0 to 50 degrees C				
Multiple Feeds:	☐ Yes and how many ☐ No				
Hardware Version	PP				
Part Number	N/A				
RF Software Version	VMI Test Software V0.5				
Operating Mode	VMI RF Protocol				
Transmitter Frequency Band	2403.35 GHz to 2477.35 GHz				
Max. Rated Power Output	+0.02 dBm				
Power Setting @ Operating Channel	0 dBm				
Antenna Type	Attached on board				
Modulation Type	☐ AM ☐ FM ☐ DSSS ☐ OFDM ☐ Other describe:				
Date Rate	11 kbps				
TX/RX Chain (s)	1				
Antenna Gain	2.0 dBi				
Directional Gain Type	✓ Uncorrelated✓ No Beam-Forming✓ Other describe:				
Type of Equipment	☐ Table Top ☐ Wall-mount ☐ Floor standing cabinet ☐ Other describe: Head wear device.				
Note: Aux 0 is the default antenna output.					

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

Table 12: Interface Specifications

Interface Type	Cabled with what type of cable?	Is the cable shielded?	Maximum potential length of the cable?	Metallic (M), Coax (C), Fiber (F), or Not Applicable?
USB	Unterminated	⊠ No	☐ Metric: 0.6m	\boxtimes M
Headset	Unterminated	⊠ No	Metric: 1m	\boxtimes M
Microphone	Terminated	∑ Yes	Metric: 0.1m	⊠M

Table 13: Supported Equipment

Equipment	Manufacturer	Model	Serial	Used for
Laptop	Dell Computer	D630	28353268189	Set test mode

Table 14: Description of Sample used for Testing

Device	Serial Number	Configuration	Used For
Ear Force Stealth 500P RX	PP #2	Radiated Sample	Radiated Emission.
Ear Force Stealth 500P RX	PP #1	Conducted Sample	Output Power, Occupied Bandwidth, Conducted Spurious Emission, Peak Power Spectral Density
Note: None			

 Table 15: Description of Test Configuration used for Radiated Measurement.

Device	Antenna	Mode	Setup Description			
Ear Force Stealth 500P RX	Integrated	Transmit & Receive	Ear Force Stealth 500P RX positioned vertically, normal usage.			
Note: The final setup configuration used for testing.						

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014

Table 16: Final Test Mode for 2403.35 MHz to 2477.35MHz Band

Test	Ear Force Stealth 500P RX			
Occupied Bandwidth	2403.35, 2441.35, 2477.35 MHz @ 11 kbps			
Output Power	2403.35, 2441.35, 2477.35 MHz @ 11 kbps			
Peak Power Spectral Density	2403.35, 2441.35, 2477.35 MHz @ 11 kbps			
Out-of-Band (-30 dBr)	2403.35, 2441.35, 2477.35 MHz @ 11 kbps			
Band-Edge (Radiated)	2403.35, 2477.35 MHz @ 11 kbps			
Transmitted Spurious Emission	2403.35, 2441.35, 2477.35 MHz @ 11 kbps			
AC Conducted Emission	NA			
Note: EUT transmits at 100% duty cycle.				

6.4 Test Specifications

Testing requirements

Table 17: Test Specifications

Emissions and Immunity	
Standard	Requirement
CFR 47 Part 15.247: 2014	All
RSS-210 Iss. 8 2010	All

Report Number: 31462893.001 EUT: Wireless Audio Headset Model: Ear Force Stealth 500P RX

Issue Date: October 7, 2014