



TÜVRheinland®
Precisely Right.

RF Exposure Exhibit

EUT Name: Wireless Audio Headset

EUT Model: Elite Atlas Aero RX (TB300-6296-01)

PMN: Elite Atlas Aero RX

HVIN: Atlas Aero RX

CFR47 Part 2.1093, RSS-102 Iss. 5 March 2015

Prepared for:

Tim Blaney
Voyetra Turtle Beach Inc.
100 Summit Lake Drive, Suite 100
Valhalla, New York 10959, USA

Prepared by:

TUV Rheinland of North America
1279 Quarry Lane, Ste. A
Pleasanton, CA 94566
Tel: (929) 249-9123
Fax: (925) 249-9124
<http://www.tuv.com/>

Report/Issue Date: August 16, 2019

Report Number: 31962555.002

1.1 Maximum Permissible Exposure

1.1.1 Test Methodology

In this section, we try to prove the safety of radiation harmfulness to the human body for our product. The KDB 447498 D01v06 General RF Exposure Guidance is followed. The Gain of the antenna used in this calculation is declared by the manufacturer, and the maximum average power input to the antenna is measured. Using the general SAR test exclusion guidance in Section 4.3 of KDB 447498, we show the device meeting the SAR exclusion threshold found in Appendix A of KDB 447498 D01v06 and SAR exemption limits found in Table 1 of RSS-102 Issue 5.

ISED accepts the KDB 447498 D01 Procedure.

1.1.2 FCC KDB 447498 D01 – General SAR Test Exclusion Guidance

The SAR exclusion threshold conditions are listed:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$$\text{Exclusion Threshold} = [P / d] * [\sqrt{f}]$$

Where

P = max power of channel (including tune-up tolerance) in mW

d = min. test separation distance in mm

f = the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Limit: \leq 3.0 of 1-g SAR \leq 7.5 of 10-g extremity SAR


The test exclusions are applicable only when the minimum test separation distance is $<$ 50 mm for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR exclusion.

1.1.3 EUT Operating Condition

The software provided by Manufacturer enabled the EUT to transmit data at lowest, middle and highest channel individually.

1.1.4 Classification

The antenna of the product, under normal use condition, is 17 mm away from the body of the user. This device classified as a **Portable Device**.



1.1.5 Antenna Gain

The antenna used is 3.5 dBi / 2.24 (numeric).

1.1.6 SAR Test Exclusion Threshold

FCC SAR Exclusion Threshold Calculation

Mode	Frequency (GHz)	Max. Power (dBm)	Max. Power (mW)	Ant. Gain (dbi)	Min. Distance (mm)	Cal. Excl. Threshold	1-g SAR Limit	10-g extremity SAR Limit	Result
Modulated	2.402	3.81	2.40	3.5	17	0.209	<3.0	<7.5	Exempted *

Note:

1. Since EUT can operate at distance less than 50 mm, the minimum distance, 5 mm, was used for calculation per condition #1 of SAR Exclusion Threshold.
2. The maximum output power was taken from Table 3 of "Turtle Beach – Elite Atlas Aero RX - FCC 15.247 Report 31962555.001 Rev0".
3. (*) The calculated threshold is less than 3.0; therefore, EUT is SAR exempted for head usage.

RSS-102 SAR Exclusion Threshold Calculation

Mode	Frequency (GHz)	Min. Distance (mm)	Max. Power (dBm)	Ant. Gain (dbi)	EIRP (mW)	SAR Exemption Limit (mW)	Result
Modulated	2.402	17	3.81	3.5	5.38	< 15	Exempted *

Note:

1. The maximum output power was taken from Table 3 of "Turtle Beach – Elite Atlas Aero RX - FCC 15.247 Report 31962555.001 Rev0."
2. (*) The eirp power in mW is less the limit of 15mW at 15mm distance per RSS 102 Table 1; therefore, EUT is SAR exempted for head and body usage.