

FCC/ IC REPORT

Applicant: COPPERNIC

Address of Applicant: 185 avenue Archimede, 13857 Aix en Provence, FRANCE

Equipment Under Test (EUT)

Product Name: C-One² HF ASK

Model No.: C-One HF ASK

Trade mark: COPPERNIC

FCC ID: XGK-C-ONE-HF-ASK

Canada IC: 8402A--CONEHFASK

FCC CFR Title 47 Part 15 Subpart C

Applicable standards: RSS-210 Issue 10, December 2019

RSS-Gen Issue 5, March 2019 Amendment 1

Date of sample receipt: 07 Apr., 2020

Date of Test: 07 Apr., 2020 to 25 May, 2020

Date of report issue: 16 Jun., 2020

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	26 May, 2020	Original
01	16 Jun., 2020	Update Model No

Tested by:



Date:

16 Jun., 2020

Test Engineer

Reviewed by:



Date:

16 Jun., 2020

Project Engineer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE	5
5.4 DESCRIPTION OF SUPPORT UNITS.....	5
5.5 MEASUREMENT UNCERTAINTY.....	5
5.6 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD.....	5
5.7 LABORATORY FACILITY.....	6
5.8 LABORATORY LOCATION	6
5.9 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 ANTENNA REQUIREMENT	8
6.2 RADIATED EMISSION	9
6.3 99% BANDWIDTH	16
6.4 CONDUCTED EMISSION	18
6.5 FREQUENCY STABILITY	21
7 TEST SETUP PHOTOS.....	23
8 EUT CONSTRUCTIONAL DETAILS	24

4 Test Summary

Test Item	Section		Result
	FCC	IC	
Antenna requirement	15.203	/	Pass
AC Power Line Conducted Emission	15.207	RSS-GEN Section 8.8	Pass
99% Bandwidth	2.202(a)	RSS-GEN Section 6.7	Pass
Field strength of the fundamental signal	15.209	RSS-GEN Section 8.9 RSS-GEN 210 Annex B Section B.6	Pass
Radiated Spurious Emission	15.209	RSS-GEN Section 8.9	Pass
Frequency Stability	/	RSS-GEN 210 Annex B Section B.6	Pass

Remark:
Pass: The EUT complies with the essential requirements in the standard.

Test Method:	ANSI C63.10-2013 FCC PART 2 RSS-GEN Issue 5
---------------------	---

5 General Information

5.1 Client Information

Applicant:	COPPERNIC
Address:	185 avenue Archimede, 13857 Aix en Provence, FRANCE
Manufacturer:	ASKEY COMPUTER Corp.
Address:	10 F, N°119, JIANKANG RD., ZHONGHE DIST., New Taipei City, TAIWAN

5.2 General Description of E.U.T.

Product Name:	C-One ² HF ASK
Model No.:	C-One HF ASK
Operation Frequency:	13.56MHz
Channel numbers:	1
Modulation type:	ASK
Antenna Type:	Internal Antenna
Power supply:	Rechargeable Li-ion Battery DC3.7V-3300mAh
AC adapter:	Model: SYS1561-1105-1 Input: AC100-240V, 50/60Hz, 1A Output: DC 5.35V, 2A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

5.3 Test mode

Transmitting mode:	Keep the EUT in transmitting mode with modulation					
Pre-Test Mode:						
CCIS has verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:						
Axis	X	Y	Z			
	13.56MHz	13.56MHz	13.56MHz			
Field Strength(dB _u V/m)	71.93	70.32	68.57			
Final Test Mode:						
According to ANSI C63.4 standards, the test results are both the "worst case" and "worst setup": Y axis (see the test setup photo).						

5.4 Description of Support Units

The EUT has been tested as an independent unit.

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)

5.6 Additions to, deviations, or exclusions from the method

No

5.7 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

- **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.8 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No.110~116, Building B, Jinyuan Business Building, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>

5.9 Test Instrumentslist

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-07-2020	03-06-2021
Biconical Antenna	SCHWARZBECK	VUBA9117	359	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-07-2020	03-06-2021
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-18-2019	11-17-2020
Loop Antenna	SCHWARZBECK	FMZB 1519 B	00044	03-07-2020	03-06-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2020	03-06-2021
Pre-amplifier	CD	PAP-1G18	11804	03-07-2020	03-06-2021
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-05-2020	03-04-2021
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-18-2019	11-17-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-05-2020	03-04-2021
Signal Generator	Rohde & Schwarz	SMX	835454/016	03-05-2020	03-04-2021
Signal Generator	R&S	SMR20	1008100050	03-05-2020	03-04-2021
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2020	03-06-2021
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2020	03-06-2021
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2020	03-06-2021

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	07-22-2017	07-21-2020
EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	03-05-2020	03-04-2021
LISN	CHASE	MN2050D	CCIS0074	03-05-2020	03-04-2021
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2020
Coaxial Cable	CCIS	N/A	CCIS0086	03-05-2020	03-04-2021
EMI Test Software	AUDIX	E3	Version: 6.110919b		


6 Test results and Measurement Data


6.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
E.U.T Antenna:	The EUT make use of an Induction coil antenna.



6.2 Radiated Emission


Test Requirement:	FCC Part15 C Section 15.209 RSS-GEN Section 8.9, RSS-210 Annex B Section B.6						
Test Frequency Range:	9 kHz to 1000MHz						
Test site:	Measurement Distance: 3m(Semi-Anechoic Chamber)						
Receiver setup:	Frequency	Detector	RBW	VBW	Remark		
	9kHz-150kHz	Quasi-peak	200Hz	600Hz	Quasi-peak Value		
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value		
	30MHz-1GHz	Quasi-peak	120kHz	300KHz	Quasi-peak Value		
Limit:	Above 1GHz	Peak	1MHz	3MHz	Peak Value		
	Frequency (MHz)	Limit (uV/m @3m)		Distance (m)			
	0.009-0.490	2400/F(kHz)		300			
	0.490-1.705	24000/F(kHz)		30			
	1.705-30	30		30			
	30-88	100		3			
	88-216	150		3			
	216-960	200		3			
Test Procedure:	Above 1GHz	500		3			
	a.	The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.					
	b.	The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.					
	c.	The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.					
	d.	For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.					
	e.	The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.					
	f.	If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
	Test setup:	9kHz-30MHz					
							

	<p>30MHz-1GHz</p> 
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Spurious Emissions:

Field Strength of fundamental signal:

Product Name:	C-One ² HF ASK	Product Model:	C-One HF ASK
Test By:	Carey	Test mode:	RFID 13.56MHz Tx mode
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq MHz	Read	Antenna	Cable	Aux	Preampl	Limit Line	Over Limit	Remark
	Level dB _{uV}	Level Factor	Cable Loss dB	Factor Factor	dB			
1 13.348	29.87	-26.47	0.63	51.50	0.00	55.53	80.50	-24.97 Peak
2 13.450	31.74	-26.47	0.63	51.50	0.00	57.40	90.50	-33.10 Peak
3 13.560	46.26	-26.47	0.64	51.50	0.00	71.93	124.00	-52.07 Peak
4 13.662	29.88	-26.48	0.64	51.50	0.00	55.54	90.50	-34.96 Peak
5 13.772	26.27	-26.48	0.64	51.50	0.00	51.93	80.50	-28.57 Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. IC limit level are the same as FCC, So not show in test report.

Test frequency range: 9 kHz- 30 MHz

Product Name:	C-One ² HF ASK	Product Model:	C-One HF ASK
Test By:	Carey	Test mode:	RFID Tx mode
Test Frequency:	9 kHz ~ 30 MHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Aux	Preamp	Limit	Over	Remark	
	Freq	Level	Factor	Loss	Factor	Factor	Line	Line	
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB
1	0.016	35.58	20.38	0.01	0.00	0.00	55.97	143.71	-87.74 Peak
2	0.021	30.83	20.30	0.01	0.00	0.00	51.14	141.31	-90.17 Peak
3	0.031	28.21	20.24	0.02	0.00	0.00	48.47	137.65	-89.18 Peak
4	0.046	29.88	20.53	0.02	0.00	0.00	50.43	134.41	-83.98 Peak
5	0.154	29.66	20.21	0.03	0.00	0.00	49.90	123.88	-73.98 Peak
6	0.668	19.69	20.67	0.09	0.00	0.00	40.45	71.11	-30.66 Peak

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- IC limit level are the same as FCC, So not show in test report.

Product Name:	C-One ² HF ASK	Product Model:	C-One HF ASK
Test By:	Carey	Test mode:	RFID Tx mode
Test Frequency:	9 kHz ~ 30 MHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%



Freq	Read		Antenna	Cable	Aux	Preamp	Limit	Over	Line	Limit	Remark
	Level	Factor	Level	Loss	Factor	Factor					
MHz	dBuV	dB/m	dB	dB	dB	dB	dBuV/m	dBuV/m	dB	dB	
1	0.016	35.93	20.38	0.01	0.00	0.00	56.32	143.71	-87.39	Peak	
2	0.027	29.65	20.23	0.01	0.00	0.00	49.89	139.06	-89.17	Peak	
3	0.031	28.95	20.23	0.02	0.00	0.00	49.20	137.72	-88.52	Peak	
4	0.047	27.15	20.55	0.02	0.00	0.00	47.72	134.20	-86.48	Peak	
5	0.158	28.46	20.22	0.03	0.00	0.00	48.71	123.67	-74.96	Peak	
6	0.587	22.82	20.73	0.09	0.00	0.00	43.64	72.24	-28.60	Peak	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. IC limit level are the same as FCC, So not show in test report.

Test frequency range: 30MHz-1000MHz


Product Name:	C-One ² HF ASK			Product Model:	C-One HF ASK		
Test By:	Carey			Test mode:	RFID Tx mode		
Test Frequency:	30 MHz ~ 1 GHz			Polarization:	Vertical		
Test Voltage:	AC 120/60Hz			Environment:	Temp: 24°C Huni: 57%		

Freq	Read	Antenna	Cable	Aux	Preampl	Limit	Over	Line	Over	Remark
MHz	Level	Factor	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	dB	
	dBuV	dB/m	dB	dB	dB					
1	40.559	55.47	12.39	1.22	0.00	29.90	39.18	40.00	-0.82	QP
2	67.675	51.82	8.99	1.46	0.00	29.74	32.53	40.00	-7.47	QP
3	595.133	48.51	19.39	3.94	0.00	28.95	42.89	46.00	-3.11	QP
4	842.130	46.44	22.44	4.22	0.00	28.03	45.07	46.00	-0.93	QP
5	851.035	46.35	22.59	4.18	0.00	28.00	45.12	46.00	-0.88	QP
6	965.542	42.03	22.73	4.29	0.00	27.63	41.42	54.00	-12.58	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.
3. IC limit level are the same as FCC, So not show in test report.

Product Name:	C-One ² HF ASK	Product Model:	C-One HF ASK
Test By:	Carey	Test mode:	RFID Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	Read	Antenna	Cable	Aux	Preampl	Limit	Line	Over	Remark	
	Freq	Level	Factor	Loss	Factor					
	MHz	dBuV	dB/m	dB	dB	dB	dBuV/m	dBuV/m	dB	
1	729.358	43.38	20.52	4.29	0.00	28.56	39.63	46.00	-6.37	QP
2	821.710	45.78	21.97	4.28	0.00	28.11	43.92	46.00	-2.08	QP
3	851.035	46.20	22.59	4.18	0.00	28.00	44.97	46.00	-1.03	QP
4	860.035	46.32	22.58	4.10	0.00	27.98	45.02	46.00	-0.98	QP
5	869.130	46.41	22.56	4.01	0.00	27.95	45.03	46.00	-0.97	QP
6	958.794	39.61	22.72	4.26	0.00	27.67	38.92	46.00	-7.08	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are lower than the limit 20dB and not show in test report.
3. IC limit level are the same as FCC, So not show in test report.


6.3 99% Bandwidth

Test Requirement:	FCC Part 2.202(a) RSS-GEN Section 6.7
Limit:	N/A
Test setup:	
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data

99% bandwidth	Limit	Results
13.56MHz		
22.6 kHz	N/A	Passed

Test plot as follows:




6.4 Conducted Emission

Test Requirement:	FCC Part15 B Section 15.207 RSS-210 RSS-GEN Section 8.8		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)		Limit (dB μ V)
			Quasi-peak Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	0.5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	 <p>Remark: <i>E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i></p>		
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). It provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement. 		
Test Instruments:	Refer to section 5.9 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

Measurement Data:


Product name:	C-One ² HF ASK	Product model:	C-One HF ASK
Test by:	Carey	Test mode:	RFID Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%



Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Aux Factor + Cable Loss.
4. IC limit level are the same as FCC, So not show in test report.

Product name:	C-One ² HF ASK	Product model:	C-One HF ASK
Test by:	Carey	Test mode:	RFID Tx mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%




Freq MHz	Read Level dBuV	LISN Factor dB	Aux Factor dB	Cable Loss dB	Limit Line dBuV	Over Line dB	Remark
	MHz	dB	dB	dB			
1	0.334	24.78	-0.63	-0.02	10.73	34.86	59.35 -24.49 QP
2	0.421	13.31	-0.64	-0.04	10.73	23.36	47.42 -24.06 Average
3	0.481	16.00	-0.65	0.02	10.75	26.12	46.32 -20.20 Average
4	0.489	25.32	-0.65	0.02	10.76	35.45	56.19 -20.74 QP
5	0.549	28.76	-0.65	0.03	10.76	38.90	56.00 -17.10 QP
6	0.549	16.33	-0.65	0.03	10.76	26.47	46.00 -19.53 Average
7	1.000	21.16	-0.63	0.08	10.87	31.48	56.00 -24.52 QP
8	1.016	7.39	-0.63	0.08	10.87	17.71	46.00 -28.29 Average
9	1.810	18.59	-0.66	0.16	10.95	29.04	56.00 -26.96 QP
10	2.636	9.44	-0.67	0.27	10.93	19.97	46.00 -26.03 Average
11	2.824	9.37	-0.67	0.29	10.93	19.92	46.00 -26.08 Average
12	3.381	18.10	-0.68	0.40	10.91	28.73	56.00 -27.27 QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Aux Factor + Cable Loss.
4. IC limit level are the same as FCC, So not show in test report.

6.5 Frequency Stability

Test Requirement:	RSS-210 Annex B Section B.6
Receiver setup:	RBW=200Hz, VBW=300Hz, span=14kHz, detector: Peak
Limit:	$\pm 0.01\%$ (± 100 ppm).
Test mode:	Transmitting mode
Test Procedure:	<p>Frequency stability V.S. Temperature measurement</p> <ol style="list-style-type: none"> 1. The equipment under test was powered by a fresh battery. 2. RF output was connected to spectrum analyzer via feed through attenuators. 3. The EUT was placed inside the temperature chamber. 4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. 5. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. 6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached <p>Frequency stability V.S. Voltage measurement</p> <ol style="list-style-type: none"> 1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage. 2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency. <p>Reduce the input voltage to specify extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.</p>
Test setup:	 <p>The diagram illustrates the test setup. A 'Spectrum Analyzer' is connected to the 'E.U.T.' (Equipment Under Test) via a feed-through attenuator. The entire setup is placed on a 'Non-Conducted Table', which sits on a 'Ground Reference Plane'.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:**13.56MHz:****a) Frequency stability V.S. Temperature measurement**

Voltage (Vdc)	Temperature (°C)	Frequency Tolerance (MHz)	Frequency Error (%)	Limit (%)	Results
3.7	-20	-0.00041	-0.0030	±0.01	Pass
	-10	-0.00030	-0.0022	±0.01	Pass
	0	-0.00026	-0.0019	±0.01	Pass
	+10	-0.00028	-0.0021	±0.01	Pass
	+20	-0.00032	-0.0024	±0.01	Pass
	+30	-0.00038	-0.0028	±0.01	Pass
	+40	-0.00040	-0.0029	±0.01	Pass
	+50	-0.00029	-0.0021	±0.01	Pass

b) Frequency stability V.S. Voltage measurement

Temperature (°C)	Voltage (Vdc)	Frequency Tolerance (MHz)	Frequency Error (%)	Limit (%)	Results
25.0	3.5	-0.00038	-0.0028	±0.01	Pass
	3.7	-0.00036	-0.0027	±0.01	Pass
	4.2	-0.00029	-0.0021	±0.01	Pass