	Ellott An <u>OZAS</u> company	EMC Test Data		
Client:	Ambient Systems	Job Number:	J75672	
Model	SmartPoint (TAG)	T-Log Number:	T75761	
woder.		Account Manager:	Christine Krebill	

Maximum Permissible Exposure

Test Specific Details

Contact: Bob Ashlock Standard: FCC 15.247/RSS-210

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Class: N/A

Date of Test: 7/27/2009 Test Engineer: Mark Hill

General Test Configuration

Calculation uses the free space transmission formula:

 $S = (PG)/(4 \pi d^2)$

Where: S is power density (W/m²), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20cm separation:	VΔc
Worse Case Power Density (mW/cm^2)	0.002

Use: General Antenna: Internal

	EUT		Cable	Ant	Power		Power Density (S)	MPE Limit
Freq.	Power		Loss	Gain	at Ant	EIRP	at 20 cm	at 20 cm
MHz	dBm	mW*	dB	dBi	dBm	mW	mW/cm ²	mW/cm ²
2405	-	-	-	-	-	9.36	0.002	1.000
2440	-	-	-	-	-	10.60	0.002	1.000
2475	-	-	-	-	-	7.06	0.001	1.000

Note - EIRP values calculated from field strengths

FCC Threshold = 60/f(GHz) mW = 60/2.475 = 24.2 mW

EUT max power = 10.60 mW

Result - EUT is below the FCC and IC threshold for RF Exposure