

RADIO TEST REPORT

Report ID

REP049440

Project ID

PRJ0055892

Type of assessment:

MPE Calculation report

Manufacturer:

ORBCOMM License Corp.

Hardware Version Identification Number (HVIN):

ST6002

Product Marketing Name (PMN):

Mobile Satellite Earth Station (MSES) module

FCC identifier:

FCC ID: XGS-ST6002

ISED certification number:

IC: 11881A-ST6002

Specification:

- ◆ FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ FCC KDB 447498 D01 General RF Exposure Guidance v06
- ◆ ISED Canada RSS-102 Issue 5 Amendment 1, (February 2021)

RSS-102 Annex B - Declaration of RF Exposure Compliance

ATTESTATION: I attest that the information provided in Annex A is correct; that the Technical Brief was prepared and the information contained therein is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed; and that the device meets the SAR and/or RF field strength limits of RSS-102.

Date of issue: July 24, 2024

Fahar Abdul Sukkoor, EMC/RF Specialist

Prepared by



Signature

Nemko Canada Inc., a testing laboratory, is accredited by ANSI National Accreditation Board (ANAB).

The tests included in this report are within the scope of this accreditation.

The ANAB symbol is an official symbol of the ANSI National Accreditation Board, used under licence.

ANAB File Number: AT-3195 (Ottawa); AT-3193 (Pointe-Claire); AT-3194 (Cambridge)



Lab locations

Company name	Nemko Canada Inc.			
Facilities	<i>Ottawa site:</i> 303 River Road Ottawa, Ontario Canada K1V 1H2	<i>Montréal site:</i> 292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8	<i>Cambridge site:</i> 1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2	
	Tel: +1 613 737 9680 Fax: +1 613 737 9691	Tel: +1 514 694 2684 Fax: +1 514 694 3528	Tel: +1 519 650 4811	
Test site identifier	Organization FCC: ISED:	Ottawa CA2040 2040A-4	Montreal CA2041 2040G-5	Cambridge CA0101 24676
Website	www.nemko.com			

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

Section 1 Evaluation summary

1.1 MPE calculation for standalone transmission

1.1.1 References, definitions and limits

FCC §2.1091(d)

- (2) (2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

Table 1.1-1: Table 1 to §1.1310(e)(1) — Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842 / f	4.89 / f	*(900 / f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1500			f / 300	<6
1500–100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824 / f	2.19 / f	*(180 / f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1500			f / 1500	<30
1500–100000			1.0	<30

Notes: f = frequency in MHz. * = Plane-wave equivalent power density.

RSS-102, Section 4

For the purpose of this standard, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6:

Table 1.1-2: Table 4 to RSS-102 — RF Field Strength Limits

Frequency range (MHz)	Electric field strength (V/m rms)	Magnetic field strength (A/m rms)	Power density (W/m ²)	Reference Period (minutes)
Limits for Controlled Environment				
10–20	61.4	0.163	10	6
20–48	129.8 / f ^{0.25}	0.3444 / f ^{0.25}	44.72 / f ^{0.5}	6
48–100	49.33	0.1309	6.455	6
100–6000	15.60 f ^{0.25}	0.04138 f ^{0.25}	0.6455 f ^{0.5}	6
6000–15000	137	0.364	50	6
Limits for Uncontrolled Environment				
10–20	27.46	0.0728	2	6
20–48	58.07 / f ^{0.25}	0.1540 / f ^{0.25}	8.944 / f ^{0.5}	6
48–300	22.06	0.05852	1.291	6
300–6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000–15000	61.4	0.163	10	6

Notes: f = frequency in MHz

References, definitions and limits, continued

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm² or W/m²)
 P = power input to the antenna (mW or W)
 G = power gain of the antenna in the direction of interest relative to an isotropic radiator
 R = distance to the center of radiation of the antenna (cm or m)

1.1.2 EUT technical information

Prediction frequency	1643.500 MHz
Antenna type	Internal built in PCB antenna
Antenna gain	5.4 dBi
Number of antennas	1
Maximum transmitter power	32.27 dBm (conducted)
Prediction distance (declared)	20/21 cm

1.1.3 MPE calculation

Fundamental transmit (prediction) frequency:	1643.5 MHz	
Maximum measured conducted peak output power:	32.27 dBm	
Cable and/or jumper loss:	0 dB	
Maximum peak power at antenna input terminal:	32.27 dBm	
Duty cycle:	40 %	
Maximum calculated average power at antenna input terminal:	674.6212102 mW	
Single Antenna gain (typical):	5.4 dBi	
Number of antennae:	1	
Total system gain:	5.40 dBi	
FCC limit:		ISED limit:
MPE limit for <u>uncontrolled</u> exposure at prediction frequency:	1.000000 mW/cm ²	0.412850 mW/cm ²
	10.000000 W/m ²	4.128502 W/m ²
MPE limit for <u>controlled</u> exposure at prediction frequency:	5.000000 mW/cm ²	2.616864 mW/cm ²
	50.000000 W/m ²	26.168637 W/m ²
Minimum calculated prediction distance for compliance:	20 cm	21 cm
Typical (declared) distance:	20 cm	21 cm
Average power density at prediction frequency:	0.465361 mW/cm ²	0.410290 mW/cm ²
	4.653612 W/m ²	4.102900 W/m ²
Margin of Compliance for <u>uncontrolled</u> environment:	3.32 dB	0.03 dB
with Maximum premitted antenna gain:	8.72 dBi	5.43 dBi
Margin of Compliance for <u>controlled</u> environment:	10.31 dB	8.05 dB
with Maximum permitted antenna gain:	44.00 dBi	41.74 dBi

1.1.4 Verdict

The calculation is below the limit; therefore, the product is passing the RF Exposure requirements for the declared distance.

1.1.5 RSS-102, Annex A - RF technical brief cover sheet

ISED certification number	IC: 11881A-ST6002		
Product marketing name (PMN)	Mobile Satellite Earth Station (MSES) module		
Hardware version identification number (HVIN)	ST6002		
Firmware version identification number (FVIN)	N/A		
Host marketing name (HMN)	N/A		
Applicant name	ORBCOMM License Corp.		
SAR/RF exposure test laboratory	24676 (3 m semi anechoic chamber - Cambridge)		
Type of evaluation	<input type="checkbox"/> SAR Evaluation: Device Used in the Vicinity of the Human Head <input type="checkbox"/> SAR Evaluation: Body-Worn Device and Body-Supported Device <input type="checkbox"/> SAR Evaluation: Limb-Worn Device <input checked="" type="checkbox"/> RF Exposure Evaluation <input type="checkbox"/> Nerve Stimulation Exposure Evaluation (SPR-002)		
SAR evaluation	Multiple transmitters: <input type="checkbox"/> Yes <input type="checkbox"/> No Evaluated against exposure limits: <input type="checkbox"/> General Public Use <input type="checkbox"/> Controlled Use Duty cycle used in evaluation: N/A % Separation distance: N/A mm Standard used for evaluation: N/A SAR value: N/A W/kg <input type="checkbox"/> Measured <input type="checkbox"/> Computed <input type="checkbox"/> Calculated		
Nerve Stimulation Evaluation (SPR-002)	Evaluated against exposure limits: <input type="checkbox"/> General Public Use <input type="checkbox"/> Controlled Use Measurement distance: N/A m Field Strength: N/A <input type="checkbox"/> V/m (electric) <input type="checkbox"/> A/m (magnetic) <input type="checkbox"/> Measured <input type="checkbox"/> Computed <input type="checkbox"/> Calculated Exposure condition: <input type="checkbox"/> Whole body/Torso/Head <input type="checkbox"/> Leg <input type="checkbox"/> Arm <input type="checkbox"/> Hand/Foot		
RF exposure evaluation	Evaluated against exposure limits: <input checked="" type="checkbox"/> General Public Use <input type="checkbox"/> Controlled Use Duty cycle used in evaluation: 100 % Operational frequency: 1643.5 MHz Standard used for evaluation: Safety Code 6 Measurement distance: 0.2 m RF value: 4.10 <input checked="" type="checkbox"/> W/m ² <input type="checkbox"/> V/m <input type="checkbox"/> A/m <input type="checkbox"/> Measured <input type="checkbox"/> Computed <input checked="" type="checkbox"/> Calculated		

End of the test report