

**Test Report No. S09EEC02515/04**  
dated 13 Oct 2009

**Note:** This report is issued subject to TÜV SÜD PSB's "Terms and Conditions Governing Technical Services". The terms and conditions governing the issue of this report are set out as attached within this report.



PSB Singapore

Choose certainty.  
Add value.

FORMAL REPORT ON TESTING IN ACCORDANCE WITH  
FCC Parts 2, 15, and 25 : 2007  
OF A  
**FLEETBROADBAND SATELLITE COMMUNICATION SYSTEM**  
[ Model : SATLINK FB150 ]  
[ FCC ID : XGW-FB150SL ]

**TEST FACILITY**

TÜV SÜD PSB Pte Ltd,  
Electrical & Electronics Centre (EEC), Product Services,  
1 Science Park Drive, Singapore 118221

**FCC REG. NO.**

90937 (3m & 10m OATS)  
99142 (10m Semi-Anechoic Chamber)  
871638 (3m Semi-Anechoic Chamber)  
325572 (10m Semi-Anechoic Chamber)

**IND. CANADA REG. NO.**

2932I-1 (3m and 10m Semi-Anechoic Chambers)

**PREPARED FOR**

Mr Prabakar Kuttaniseeri  
Addvalue Communications Pte Ltd  
190 Changi Road  
#02-02 MDIS Building  
Singapore 419974

Tel : (65) 6342 5420      Tel : (65) 6342 5420

**QUOTATION NUMBER**

Q09EEC01846 & Q09EEC03248

**JOB NUMBER**

S09EEC01452 & S09EEC02515

**TEST PERIOD**

15 Jun 2009 – 03 Jul 2009

**PREPARED BY**

Quek Keng Huat  
Associate Engineer

**APPROVED BY**

Lim Cher Hwee  
Assistant Vice President



Laboratory:  
TÜV SÜD PSB Pte. Ltd.  
Testing Services  
No.1 Science Park Drive  
Singapore 118221



Phone : +65-6885 1333  
Fax : +65-6776 8670  
E-mail: testing@tuv-sud-psb.sg  
www.tuv-sud-psb.sg  
Co. Reg : 199002667R

LA-2007-0380-A  
LA-2007-0380-A-1  
LA-2007-0381-F  
LA-2007-0382-B  
LA-2007-0383-G  
LA-2007-0384-G  
LA-2007-0385-E  
LA-2007-0386-C  
LA-2007-0388-C

The results reported herein have been performed in accordance with the laboratory's terms of accreditation under the Singapore Accreditation Council - Singapore Laboratory Accreditation Scheme. Tests/Calibrations marked "Not SAC-SINGLAS Accredited" in this Report are not included in the SAC-SINGLAS Accreditation Schedule for our laboratory.

Regional Head Office:  
TÜV SÜD Asia Pacific Pte. Ltd.  
3 Science Park Drive, #04-01/05  
The Franklin, Singapore 118223

## **TABLE OF CONTENTS**

TEST SUMMARY

PRODUCT DESCRIPTION

SUPPORTING EQUIPMENT DESCRIPTION

EUT OPERATING CONDITIONS

RADIATED EMISSION TEST

RF OUTPUT POWER TEST

UNWANTED EMISSIONS AT ANTENNA TERMINAL  
TEST

RADIATED SPURIOUS EMISSION TEST

PROTECTION OF AERONAUTICAL RADIO  
NAVIGATION SATELLITE SERVICE TEST

FREQUENCY STABILITY (TEMPERATURE  
VARIATION) TEST

FREQUENCY STABILITY (VOLTAGE VARIATION)  
TEST

MAXIMUM PERMISSIBLE EXPOSURE (MPE) TEST

ANNEX A

- EUT PHOTOGRAPHS / DIAGRAMS

ANNEX B

- FCC LABEL & POSITION

ANNEX C

- USER MANUAL, TECHNICAL DESCRIPTION,  
BLOCK & CIRCUIT DIAGRAMS

## TEST SUMMARY

The product was tested in accordance with the customer's specifications.

### Test Results Summary

Test Standard	Description	Pass / Fail
FCC Parts 2, 15 and 25: 2007		
15.107(a), 15.207	Conducted Emissions	Not Applicable *See Note 3
15.109	Radiated Emissions (Class B)	Pass
2.1046(a), 25.204	RF Output Power	Pass
2.1051, 25.202(f)	Unwanted Emissions at Antenna Terminal	Pass
2.1053, 25.202(f)	Radiated Spurious Emissions	Pass
25.216(h)(i)(j)	Protection of Aeronautical Radio Navigation Satellite Service	Pass
2.1055, 25.202(d)	Frequency Stability (Temperature Variation)	Pass
2.1055, 25.202(d)	Frequency Stability (Voltage Variation)	Pass
1.1310	Maximum Permissible Exposure	Refer to page 95 for details

### Notes

- Three channels as listed below, which respectively represent the lower, middle and upper channels (transmit and receive) of the Equipment Under Test (EUT) when it was configured to operate under test mode condition.

Transmit Channel	Frequency (GHz)	Receive Channel	Frequency (GHz)
Lower Channel	1.6315	Lower Channel	1.5250
Middle Channel	1.6435	Middle Channel	1.5421
Upper Channel	1.6604	Upper Channel	1.5590

- The following tests were based on conducted measurement method:
  - RF Output Power
  - Unwanted Emissions at Antenna Terminal
  - Frequency Stability (Temperature Variation)
  - Frequency Stability (Voltage Variation)
- The Equipment Under Test (EUT) is a DC operated device and contains no provision for public utility connections.
- All test measurement procedures are according to ANSI/TIA-603-B-2002.
- The EUT is a Class B device when in non-transmitting state and meets the FCC Part15B Class B requirements.

---

**TEST SUMMARY**

**Notes (Continued)**

6. This test report was generated from S09EEC01452 without further testing. This report is to update the model / brand / trademark based on below declaration from SATLINK:



12<sup>th</sup> October 2009.

**TIMCO Engineering Inc**  
849 N.W.State Road 45  
P.O.Box 370  
Newberry, Florida 32669 USA  
Phone (352) 472-5500 or (888) 472-2424  
FAX (352) 472-2030

**Product Identical Declaration**

Product 1 : **SKIPPER 150**, FCC ID:QY9-SKIPPER150WE  
Product 2 : **SATLINK FB150**, FCC ID:XGW-FB150SL


We are Satlink,S.L. OEM customer of the above product 2, here by declare that, both products 1 & 2 is identically same where by the product 2 is marketed at our own brand / trademark in the name of **SATLINK FB150**,which is an OEM version from Addvalue communications Pte Ltd's Wideye branded **SKIPPER 150**. In the product technical construction, the BASEBAND board, RF board, Crystal board & Interface board with shields (Core module) and Power supply module assembly all are identically same in both products.

We here by enclosed that the product 2- appearance in logo artwork and product rating label artwork for your reference and record.

For further information or clarification about the products, please contact the undersigned at:  
Email address: ldr@satlink.es

Telephone Contact:-  
Office main line : +34913272131  
Office fax line : +34913272169

Yours truly,



Luis Diaz del Río  
Chief Executive Officer  
12<sup>th</sup> October 2009.

## PRODUCT DESCRIPTION

Description	: The Equipment Under Test (EUT) is a <b>Fleetbroadband Satellite Communication System</b> .
Manufacturers	: Addvalue Communications Pte Ltd 190 Changi Road #02-02 MDIS Building Singapore 419974
Model Number	: SATLINK FB150
FCC ID	: XGW-FB150SL
Serial Number	: Q23
Microprocessor	: OMAP5912
Operating / Transmitting Frequency	: 1626.5MHz – 1660.5MHz (Satellite Transmit) 1525MHz – 1559MHz (Satellite Receive) 1575.42MHz (GPS)
Clock / Oscillator Frequency	: <u>Baseband Board</u> 32.768kHz, 12.0MHz, 16.384MHz, 25.0MHz and 39.3216MHz  <u>Below Deck Unit (BDU) Board</u> 24.192MHz
Modulation / Emissions Designator	: pi/4QPSK and 16QAM (Satellite Transmit) pi/4QPSK and 16QAM (Satellite Receive) QPSK (GPS)
Antenna Gain	: 10.0dBi
Port / Connectors	: 1 x RJ45 Ethernet port 1 x 10 Base-T Ethernet port (POE Line) 1 x RJ11 Phone port 1 x DC input port
Rated Input Power	: 12VDC, 8A / 24VDC, 4A
Accessories	: Primary Handset (Model : FB150-PH)



PSB Singapore

**SUPPORTING DESCRIPTION DESCRIPTION**

<b>Equipment Description (Including Brand Name)</b>	<b>Model, Serial &amp; FCC ID Number</b>	<b>Cable Description (List Length, Type &amp; Purpose)</b>
Insteek Programmable Power Supply	M/N: PSH-6012A S/N: EI110020 FCC ID: Nil	2.00m shielded power cable
IBM Thinkpad Laptop	M/N: 2388 S/N: KM-31535-0306 FCC ID: DoC	1.80m unshielded power cable
IBM AC Adapter	M/N: PA-1121-061 S/N: 11S02K7093Z1Z6C635COH7	
Ear piece with Mic (unbranded)	M/N: Nil S/N: Nil FCC ID: Nil	1.0m standard microphone cable
Satlink250 Handset	M/N: FB250-H S/N: Nil FCC ID: DoC	1.0m standard handset cable

**EUT OPERATING CONDITIONS**

**FCC Parts 2, 15 and 25**

1. RF Output Power
2. Unwanted Emissions at Antenna Terminal
3. Radiated Spurious Emissions
4. Protection of Aeronautical Radio Navigation Satellite Service
5. Frequency Stability (Temperature Variation)
6. Frequency Stability (Voltage Variation)
7. Maximum Permissible Exposure

The EUT was exercised by operating in following modes with the EUT simulating the transmission and reception using the client's provided test programs, "ttermpw.exe" and "wftpd32.exe"

**Satellite Transmission Mode**

- Continuous RF transmission at lower channel at maximum RF power
- Continuous maximum RF transmission at middle channel at maximum RF power
- Continuous maximum RF transmission at upper channel at maximum RF power

**Satellite Reception (Receive) Mode**

- Continuous RF reception at lower channel
- Continuous RF reception at middle channel
- Continuous RF reception at upper channel

**GPS Reception (Receive) Mode**

- Continuous GPS signal reception

**RADIATED EMISSION TEST**

**FCC Part 15.109 Radiated Emission Limits (Class B)**

Frequency Range (MHz)	Quasi-Peak Limit Values (dB $\mu$ V/m) @ 3m
30 - 88	40.0
88 - 216	43.5
216 - 960	46.0
Above 960	54.0*

\* Above 1GHz, average detector was used. A peak limit of 20dB above the average limit does apply.

**FCC Part 15.109 Radiated Emission Test Instrumentation**

Instrument	Model	S/No	Cal Due Date
R&S Test Receiver (20Hz-26.5GHz) – ESMI2	ESMI	829214/006 829550/001	27 May 2010
Teseq Preamplifier (PA16)	LNA6018	70214	06 Oct 2009
Schaffner Preamplifier (9kHz-2GHz) – PA19	CPA9231A	18763	16 Feb 2010
Schaffner Bilog Antenna – BL4	CBL6112B	2593	19 May 2010
EMCO Horn Antenna – H14	3115	0003-6087	14 May 2010



## RADIATED EMISSION TEST

### **FCC Part 15.109 Radiated Emission Test Setup**

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard as shown in the setup photos.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.

### **FCC Part 15.109 Radiated Emission Test Method**

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A prescan was carried out to pick the worst emission frequencies from the EUT. For EUT which is a portable device, the prescan was carried out by rotating the EUT through three orthogonal axes to determine which altitude and equipment arrangement produces such emissions.
3. The test was carried out at the selected frequency points obtained from the prescan in step 2. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
  - a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
  - b. The EUT was then rotated to the direction that gave the maximum emission.
  - c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
4. A Quasi-peak measurement was made for that frequency point if it was less than or equal to 1GHz. For frequency point that above 1GHz, both Peak and Average measurements were carried out.
5. Steps 3 and 4 were repeated for the next frequency point, until all selected frequency points were measured.
6. The frequency range covered was from 30MHz to 5<sup>th</sup> harmonic of the highest frequency used or generated by the EUT, using the Bi-log antenna for frequencies from 30MHz up to 1GHz, and the Horn antenna above 1GHz.

### **Sample Calculation Example**

At 300 MHz

Q-P limit (Class B) = 70.8  $\mu$ V/m = 37.0 dB $\mu$ V/m

Log-periodic antenna factor & cable loss at 300 MHz = 18.5 dB

Q-P reading obtained directly from EMI Receiver = 31.0 dB $\mu$ V/m  
(Calibrated level including antenna factors & cable losses)

Therefore, Q-P margin = 31.0 - 37.0 = -6.0

i.e. 6 dB below Q-P limit

**RADIATED EMISSION TEST**



**Radiated Emissions Test Setup (Front View)**



**Radiated Emissions Test Setup (Rear View)**

**RADIATED EMISSION TEST**

**FCC Part 15.109 Radiated Emission Results**

Operating Mode	GPS	Temperature	34°C
Test Input Power	24VDC (Worst voltage)	Relative Humidity	50%
Test Distance	3m	Atmospheric Pressure	1030mbar
Class	B	Tested By	Zechs Ng Chee Siong

Emissions ranging from 30MHz – 1GHz

Frequency (MHz)	Q-P Value (dB $\mu$ V/m)	Q-P Margin (dB)	Azimuth (Degrees)	Height (cm)	Polarisation (H/V)
30.1200	7.2	-32.8	275	100	V
98.5500	7.0	-33.0	100	100	V
170.2300	4.0	-36.0	270	132	V
239.9600	10.5	-36.5	335	100	V
601.2580	12.5	-34.5	180	189	V
812.4560	14.2	-32.8	21	100	V

Emissions above 1GHz

Frequency (GHz)	Peak Value (dB $\mu$ V/m)	Average Value (dB $\mu$ V/m)	Average Margin (dB)	Azimuth (Degrees)	Height (cm)	Pol (H/V)
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--
--	--	--	--	--	--	--

Notes

1. All possible modes of operation were investigated. Only the worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. EMI receiver Resolution Bandwidth (RBW) and Video Bandwidth (VBW) settings:  
30MHz - 1GHz  
RBW: 120kHz      VBW: 1MHz  
>1GHz  
RBW: 1MHz      VBW: 1MHz
5. "--" indicates no emissions were found and shows compliance to the limits.
6. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95%, with a coverage factor of 2, in the range 30MHz – 25.0GHz is  $\pm 4.6$ dB.

## **RF OUTPUT POWER TEST**

### **FCC Parts 2.1046 and 25.204 RF Output Power Test Limits**

1. 25.204 Power Limits
  - (a) In bands shared coequally with terrestrial radio communication services, the equivalent isotropically radiated power transmitted in any direction towards the horizon by an earth station, other than an ESV, operating in frequency bands between 1GHz and 5GHz, shall not exceed the following limits except as provided for in paragraph (c) of this section:  
+40dBW in any 4kHz band for  $\theta: 0^\circ$   
+40dBW + 3.0dBW in any 4kHz band for  $0^\circ < \theta \leq 5^\circ$   
where  $\theta$  is the angle of elevation of the horizon viewed from the center of radiation of the antenna of the earth station and measured in degrees as positive above the horizontal plane and negative below it.
  - (c) For angles of evaluation of the horizon greater than  $5^\circ$  there shall be no restriction as to the equivalent isotropically radiated power transmitted by an earth station towards the horizon.
  - (d) Notwithstanding the e.i.r.p and e.i.r.p density limits specified in the station authorization, each earth station transmission shall be conducted at the lowest power level that will provide the required signal quality as indicated in the application and further amended by coordination agreements.
2. 2.1046 Measurements Required: RF Power Output
  - (a) For transmission other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in 2.1033(c)(8). The electrical characteristics of the radio frequency load attached to the output terminals when this test is made shall be stated.
  - (c) For measurements conducted pursuant to paragraphs (a) and (b) of this section, all calculations and methods used by the applicant for determining carrier power or peak envelope power, as appropriate, on the basis of measured power in the radio frequency load attached to the transmitter output terminals shall be shown. Under the test conditions specified, no components of the emission spectrum shall exceed the limits specified in the applicable rule parts as necessary for meeting occupied bandwidth or emission limitations.

### **FCC Parts 2.1046 and 25.204 RF Output Power Test Instrumentation**

<b>Instrument</b>	<b>Model</b>	<b>S/No</b>	<b>Cal Due Date</b>
Agilent EMC Analyzer (9kHz-26.5GHz) (Ref)	E7405A	US40240195	20 Jan 2010
Bird 20dB 25W RF Attenuator	25-A-MFN-20	Nil	25 May 2010
R&S Universal Radio Communication Tester	CMU 200	837587/068	25 Dec 2010

## **RF OUTPUT POWER TEST**

### **FCC Parts 2.1046 and 25.204 RF Output Power Test Setup**

1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the Universal Radio Communication Tester, which set into power analyser mode via a RF attenuator and a low-loss coaxial cable.
4. The spectrum analyser was then calibrated to the power meter level as shown by the Universal Radio Communicator Tester with a calibrated RF signal source.
5. All other supporting equipment were powered separately from another filtered mains.

### **FCC Parts 2.1046 and 25.204 RF Output Power Test Method**


1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode, transmitting frequency at lower channel.
2. The maximum peak power of the transmitting frequency was measured and recorded.
3. The RF carrier peak and average pots were plotted.
4. The steps 2 to 4 were repeated with the transmitting frequency was set to middle and upper channels respectively.



**RF OUTPUT POWER TEST**



**RF Output Power Test Setup**



## RF OUTPUT POWER TEST


### FCC Parts 2.1046 and 25.204 RF Output Power Results

Operating Mode	Satellite Transmission (CW)	Temperature	24°C
Test Input Power	24VDC	Relative Humidity	60%
Antenna Gain	10.0dBi	Atmospheric Pressure	1030mbar
Attached Plots	1 - 6	Tested By	Foo Kai Maun

Frequency (MHz)	Channel	Peak Output Power (dBm)		Average Output Power (dBm)	
		EIRP	ERP	EIRP	ERP
1631.5	Lower	43.8	33.8	43.8	33.8
1643.5	Middle	43.4	33.4	43.4	33.4
1660.4	Upper	44.2	34.2	44.1	34.1


### Notes

1. Power analyser of Universal Radio Communication Tester was used for power measurement. The power analyser mode supports a wideband power measurement ranging from 100kHz to 2700MHz.
2. RF Output Power Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of 95%, with a coverage factor of 2 is  $\pm 1.0\text{dB}$ .




## RF OUTPUT POWER TEST

### Output Power Plots





Plot 1 – Lower Channel (Peak)



Plot 2 – Lower Channel (Average)



## RF OUTPUT POWER TEST

### Output Power Plots



## RF OUTPUT POWER TEST

### Output Power Plots



**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**FCC Parts 2.1051 and 25.202(f) Unwanted Emissions at Antenna Terminal Test Limits**

1. 25.202 Emissions Limitations
  - (f) The mean power of the emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:
    - (1) In any 4kHz band, the center frequency of which is removed from the assigned frequency by more than 50% up to and including 100% of the authorized bandwidth: 25 decibels;
    - (2) In any 4kHz band, the center frequency of which is removed from the assigned frequency by more than 100% up to and including 250% of the authorized bandwidth: 35 decibels;
    - (3) In any 4kHz band, the center frequency of which is removed from the assigned frequency by more than 250% of the authorized bandwidth: an amount equal to 43 decibels plus 10 times logarithm (to the base 10) of the transmitter power in watts.
2. 2.1051 Measurements Required: Spurious Emissions at Antenna Terminals  
The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20dB below the permissible value need not be specified.

**FCC Parts 2.1051 and 25.202(f) Unwanted Emissions at Antenna Terminal Test Instrumentation**

Instrument	Model	S/No	Cal Due Date
Agilent EMC Analyzer (9kHz-26.5GHz) (Ref)	E7405A	US40240195	20 Jan 2010
Bird 20dB 25W RF Attenuator	25-A-MFN-20	Nil	25 May 2010

---

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**FCC Parts 2.1051 and 25.202(f) Unwanted Emissions at Antenna Terminal Test Setup**

1. The EUT and supporting equipment were set up as shown in the setup photo.
2. The power supply for the EUT was connected to a filtered mains.
3. The RF antenna connector was connected to the spectrum analyser via a RF attenuator and a low-loss coaxial cable.
4. All other supporting equipment were powered separately from another filtered mains.

**FCC Parts 2.1051 and 25.202(f) Unwanted Emissions at Antenna Terminal Test Method**

1. The EUT was switched on and allowed to warm up to its normal operating condition. The EUT was then configured to operate in the test mode, transmitting frequency at lower channel.
2. The 26dB bandwidth of the transmitting channel was measured.
3. The emission mask was drawn based on the authorized bandwidth and the measured average output power.
4. The transmitting channel emissions were plotted.
5. The steps 2 to 5 were repeated with the transmitting frequency was set to middle and upper channels respectively.



**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**



**Unwanted Emissions at Antenna Terminal Test Setup**



**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**FCC Parts 22.917(b) and 2.1049 Occupied Bandwidth Results**

Operating Mode	Satellite Transmission	Temperature	24°C
Test Input Power	24VDC	Relative Humidity	60%
Attached Plots	7 – 27 (26dB Bandwidth) 28 – 48 (In Band Emissions) 49 – 90 (Out of Band Spurious)	Atmospheric Pressure	1030mbar
		Tested By	Foo Kai Maun

All emissions are within the emission mask. Please refer to the attached plots.

**Notes**


1. The Resolution Bandwidth (RBW) was corrected from 4kHz by  $10\log_{10}[(\text{used RBW}) / 4\text{kHz}]$ .
2. Emission limits are computed based on following:
  - a. Emissions Limits (dBm) (50% - 100% authorised bandwidth) =  $P - 25 + CF$
  - b. Emissions Limits (dBm) (100% - 250% authorised bandwidth) =  $P - 35 + CF$
  - c. Emissions Limits (dBm) (> 250% authorised bandwidth) =  $P - [43 + 10 \log_{10} P_w] + 30 + CF$

where

P	=	Measured mean power in dBm
$P_w$	=	Measured mean power in dBW
CF	=	RBW correction factor (see Note 1)

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**26dB Bandwidth Plots (Bearer Type: 0)**



**Plot 7 – Lower Channel**



**Plot 8 – Middle Channel**

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**



**26dB Bandwidth Plots (Bearer Type: 0)**



**Plot 9 – Upper Channel**

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**


**26dB Bandwidth Plots (Bearer Type: 3)**



**Plot 11 – Middle Channel**

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**


**26dB Bandwidth Plots (Bearer Type: 3)**




Plot 12 – Upper Channel

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**26dB Bandwidth Plots (Bearer Type: 5)**




**Plot 13 – Lower Channel**



**Plot 14 – Middle Channel**


UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

26dB Bandwidth Plots (Bearer Type: 5)




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**26dB Bandwidth Plots (Bearer Type: 7)**




**Plot 16 – Lower Channel**



**Plot 17 – Middle Channel**



**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**26dB Bandwidth Plots (Bearer Type: 7)**




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**26dB Bandwidth Plots (Bearer Type: 11)**



**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**


**26dB Bandwidth Plots (Bearer Type: 11)**




Plot 21 – Upper Channel

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**26dB Bandwidth Plots (Bearer Type: 13)**




**Plot 22 – Lower Channel**



**Plot 23 – Middle Channel**

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**


**26dB Bandwidth Plots (Bearer Type: 13)**




Plot 24 – Upper Channel

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**26dB Bandwidth Plots (Bearer Type: 15)**




**Plot 25 – Lower Channel**



**Plot 26 – Upper Channel**

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**26dB Bandwidth Plots (Bearer Type: 15)**




Plot 27 – Upper Channel




UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

In Band Emissions Plots (Bearer Type: 0)




Plot 28 - Lower Channel



Plot 29 – Middle Channel



**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 0)**




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 3)**



**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 3)**




Plot 33 – Upper Channel




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 5)**




**Plot 34 – Lower Channel**



**Plot 35 – Middle Channel**


**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 5)**




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 7)**



**Plot 37 – Lower Channel**



**Plot 38 – Middle Channel**


**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 7)**




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 11)**




**Plot 40 – Lower Channel**



**Plot 41 – Middle Channel**


**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 11)**




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 13)**




Plot 43 – Lower Channel



Plot 44 – Middle Channel


**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 13)**




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 15)**




Plot 46 – Lower Channel



Plot 47 – Middle Channel


**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**In Band Emissions Plots (Bearer Type: 15)**




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 0)**




**Plot 49 – Lower Channel**




**Plot 50 – Lower Channel**

UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

Out of Band Spurious Plots (Bearer Type: 0)




Plot 51 – Middle Channel




Plot 52 – Middle Channel

UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

Out of Band Spurious Plots (Bearer Type: 0)




Plot 53 – Upper Channel




Plot 54 – Upper Channel

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 3)**




Plot 55 – Lower Channel




Plot 56 – Lower Channel

UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

Out of Band Spurious Plots (Bearer Type: 3)





Plot 57 – Middle Channel



Plot 58 – Middle Channel


**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 3)**




UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

Out of Band Spurious Plots (Bearer Type: 5)





Plot 61 – Lower Channel



Plot 62 – Lower Channel


**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 5)**




UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

Out of Band Spurious Plots (Bearer Type: 5)




Plot 65 – Upper Channel




Plot 66 – Upper Channel

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 7)**




**Plot 67 – Lower Channel**




**Plot 68 – Lower Channel**

UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

Out of Band Spurious Plots (Bearer Type: 7)





Plot 69 – Middle Channel



Plot 70 – Middle Channel



**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 7)**




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 11)**




UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

Out of Band Spurious Plots (Bearer Type: 11)




Plot 75 – Middle Channel




Plot 76 – Middle Channel

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 11)**




**Plot 77 – Upper Channel**




**Plot 78 – Upper Channel**

UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

Out of Band Spurious Plots (Bearer Type: 13)




Plot 79 – Lower Channel




Plot 80 – Lower Channel

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 13)**





**Plot 81 – Middle Channel**



**Plot 82 – Middle Channel**



**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 13)**




**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 15)**




UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST

Out of Band Spurious Plots (Bearer Type: 15)




Plot 87 – Middle Channel




Plot 88 – Middle Channel

**UNWANTED EMISSIONS AT ANTENNA TERMINAL TEST**

**Out of Band Spurious Plots (Bearer Type: 15)**



**Plot 89 – Upper Channel**



**Plot 90 – Upper Channel**

**RADIATED SPURIOUS EMISSION TEST**

**FCC Parts 2.1053 and 25.202(f) Radiated Spurious Emission Limits**

1. 25.202 Emissions Limitations
  - (f) The mean power of the emissions shall be attenuated below the mean output power of the transmitter in accordance with the following schedule:
    - (1) In any 4kHz band, the center frequency of which is removed from the assigned frequency by more than 50% up to and including 100% of the authorized bandwidth: 25 decibels;
    - (2) In any 4kHz band, the center frequency of which is removed from the assigned frequency by more than 100% up to and including 250% of the authorized bandwidth: 35 decibels;
    - (3) In any 4kHz band, the center frequency of which is removed from the assigned frequency by more than 250% of the authorized bandwidth: an amount equal to 43 decibels plus 10 times logarithm (to the base 10) of the transmitter power in watts.
2. 2.1053 Measurements Required: Field Strength of Spurious Emissions
  - (a) Measurement shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of 2.1049, as appropriate. For equipment operating on frequencies below 890MHz, an open field test is normally required, with the measuring instrument antenna located in the far-field at all test frequencies. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from half-wave dipole antennas.
  - (b) The measurements specified in paragraph (a) of this section shall be made for the following equipment:
    - (1) Those in which the spurious emission are required to be 60dB or more below the mean power of the transmitter.
    - (2) All equipment operating on frequencies higher than 25MHz.
    - (3) All equipment where the antenna is an integral part of, and attached directly to the transmitter.
    - (4) Other types of equipment as required, when deemed necessary by the Commission.

**FCC Parts 2.1053 and 25.202(f) Radiated Spurious Emission Test Instrumentation**

<b>Instrument</b>	<b>Model</b>	<b>S/No</b>	<b>Cal Due Date</b>
R&S Test Receiver (20Hz–26.5GHz) – ESMI2	ESMI	829214/006 829550/001	27 May 2010
Teseq Preamplifier (PA16)	LNA6018	70214	06 Oct 2009
Schaffner Preamplifier (9kHz-2GHz) – PA19	CPA9231A	18763	16 Feb 2010
Schaffner Bilog Antenna – BL4	CBL6112B	2593	19 May 2010
Schaffner Bilog Antenna – BL3	CBL6112B	2549	18 Dec 2009
EMCO Horn Antenna – H14	3115	0003-6087	14 May 2010
ETS Horn Antenna	3116	0004-2474	02 Apr 2010

## RADIATED SPURIOUS EMISSION TEST

### **FCC Parts 2.1053 and 25.202(f) Radiated Spurious Emission Test Setup**

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant antenna was set at the required test distance away from the EUT and supporting equipment boundary

### **FCC Parts 2.1053 and 25.202(f) Radiated Spurious Emission Test Method**

1. The EUT was set to transmit at the maximum power at the lower channel with the modulation on at normal test condition.
2. The receiving antenna (test antenna) was set at vertical polarization with the height of 1m.
3. With the spectrum analyser was set to max hold enabled (peak detector mode), the spurious emissions were searched and recorded. For EUT which is a portable device, the spurious emission search was carried out by rotating the EUT through three orthogonal axes to determine which attitude and equipment arrangement produces worst emissions.
4. For each spurious emission found, the test antenna was raised or lowered through the specified range of heights (1m – 4m) until a maximum signal level was detected on the test receiver.
5. The EUT was then rotated through 360° in the horizontal plane until the maximum signal was received. The maximum received signal level was recorded as A (in dBm).
6. The EUT was replaced with the substitution antenna with the antenna input was connected to the signal generator via a 10dB attenuator (if required).
7. The signal generator was set to the found spurious frequency. The output level of the signal generator was adjusted until the test receiver was at least 20dB above the level when the signal generator was switched off.
8. The test antenna was raised and lowered through the specified range of heights (1m – 4m) until the maximum signal level was received on the test receiver.
9. The substitution antenna was rotated until the maximum level was detected on the test receiver.
10. The output level of the signal generator was adjusted until the received signal level at the test receiver was equal to the level recorded in step 5 (A dBm). The signal generator output level was recorded as B (in dBm).
11. The spurious emission level, P (e.i.r.p) was computed as followed:  
P (e.i.r.p) = B – C – D + E  
where C = cable loss between the signal generator and the substitution  
D = attenuation level if attenuator is used  
E = substitution antenna gain
12. The steps 2 to 11 were repeated with the receiving antenna was set to horizontal polarization.
13. Comparison was made on both measured results with vertical and horizontal polarizations. The highest value out of vertical and horizontal polarizations was recorded.
14. The steps 2 to 13 were repeated until all the spurious emissions (up to 10<sup>th</sup> harmonics of the carrier frequency) were measured.
15. The steps 1 to 14 were repeated with the EUT was set to operate at the middle and upper channels respectivley.

**RADIATED SPURIOUS EMISSION TEST**



**Radiated Spurious Emissions Test Setup (Front View)**



**Radiated Spurious Emissions Test Setup (Rear View)**



PSB Singapore

**RADIATED SPURIOUS EMISSIONS TEST**

**FCC Parts 2.1053 and 25.202(f) Radiated Spurious Emission Results**

Operating Mode	Satellite Transmission	Temperature	34°C
Test Input Power	24VDC (Worst voltage)	Relative Humidity	50%
Test Distance	3m	Atmospheric Pressure	1030mbar
Type Bearer	13 (Worst Bearer)	Tested By	Anthony Toh

**30MHz – 1GHz**

**Lower Channel**

Frequency (GHz)	Amplitude (dBm)	Limit (dBm)
51.3421	-32.6	1.0
87.0394	-34.1	1.0
--	--	--
--	--	--
--	--	--
--	--	--

**Middle Channel**

Frequency (GHz)	Amplitude (dBm)	Limit (dBm)
68.9120	-28.5	1.0
105.8418	-36.3	1.0
--	--	--
--	--	--
--	--	--
--	--	--

**Upper Channel**

Frequency (GHz)	Amplitude (dBm)	Limit (dBm)
70.7545	-35.9	1.0
321.4435	-32.5	1.0
--	--	--
--	--	--
--	--	--
--	--	--

**RADIATED SPURIOUS EMISSIONS TEST**

**1GHz – 17GHz**

**Lower Channel**

Frequency (GHz)	Amplitude (dBm)	Limit (dBm)
1.4794	-59.3	1.0
1.5956	-56.1	1.0
1.6242	-54.0	1.0
3.2578	-47.7	1.0
14.2283	-32.9	1.0
--	--	--

**Middle Channel**

Frequency (GHz)	Amplitude (dBm)	Limit (dBm)
1.2316	-59.1	1.0
1.5558	-59.1	1.0
1.5823	-56.2	1.0
9.9768	-40.9	1.0
14.2270	-32.9	1.0
--	--	--

**Upper Channel**

Frequency (GHz)	Amplitude (dBm)	Limit (dBm)
1.5409	-59.3	1.0
1.5930	-56.3	1.0
1.6251	-45.7	1.0
9.6655	-40.3	1.0
14.0904	-33.2	1.0
--	--	--

**RADIATED SPURIOUS EMISSIONS TEST**

**Notes**

1. All possible modes of operation were investigated. Only the worst case emissions measured. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. "--" indicates no emissions were found and shows compliance to the limits.
4. The Resolution Bandwidth (RBW) was corrected from 4kHz by  $10\log_{10}[(\text{used RBW}) / 4\text{kHz}]$ .
5. EMI receiver Resolution Bandwidth (RBW) and Video Bandwidth (VBW) settings:  
30MHz - 20GHz  
RBW: 100kHz VBW: 300kHz
6. Emission limits are computed based on following:
  - a. Emissions Limits (dBm) (50% - =  $P - 25 + CF$   
100% authorised bandwidth)
  - b. Emissions Limits (dBm) (100% - =  $P - 35 + CF$   
250% authorised bandwidth)
  - c. Emissions Limits (dBm) (> 250% =  $P - [43 + 10 \log_{10} P_w] + 30 + CF$   
authorised bandwidth)  
where  $P$  = Measured mean power in dBm  
 $P_w$  = Measured mean power in dBW  
 $CF$  = RBW correction factor (see Note 1)
7. **Radiated Spurious Emissions Measurement Uncertainty**  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95%, with a coverage factor of 2, in the range 30MHz – 25GHz is  $\pm 4.6\text{dB}$ .

**PROTECTION OF AERONAUTICAL RADIO NAVIGATION SATELLITE SERVICE TEST**

**FCC Part 25.216(h)(i)(j) Protection of Aeronautical Radio Navigation Satellite Service Limits**

25.216(h)(i)(j) Limits on Emissions from Mobile Earth Stations for Protection of Aeronautical Radionavigation-Satellite Service

- (h) Mobile earth stations manufactured more than six months after Federal Register publication of the rule changes adopted in FC 03-283 (from November 6, 2003) with assigned uplink frequencies in the 1626.5MHz - 1660.5MHz band shall suppress the power density of emissions in the 1605MHz - 1610MHz band-segment to an extent determined by linear interoperation from -70dBW/MHz at 1605MHz to -46dBW/MHz at 1610MHz, averaged over any 2ms active transmission interval. The e.i.r.p of discrete emissions of less than 700Hz bandwidth from such stations shall not exceed a level determined by linear interoperation from -80dBW at 1605MHz to -56dBW at 1610MHz, averaged over any 2ms active transmission interval.
- (i) The e.i.r.p density of carrier-off state emissions from mobile earth stations manufactured more than six months after Federal Register publication of the rule changes adopted in FCC 03-283 with assigned uplink frequencies between 1GHz and 3GHz shall not exceed -80dBW/MHz in the 1559MHz - 1610MHz band averaged over any 2ms interval.
- (j) A Root-Mean-Square detector shall be used for all power density measurements.

**FCC Part 25.216(h)(i)(j) Protection of Aeronautical Radio Navigation Satellite Service Test Instrumentation**

Instrument	Model	S/No	Cal Due Date
R&S Test Receiver (20Hz–26.5GHz) – ESMI2	ESMI	829214/006 829550/001	27 May 2010
Teseq Preamplifier (PA16)	LNA6018	70214	06 Oct 2009
Schaffner Preamplifier (9kHz-2GHz) – PA19	CPA9231A	18763	16 Feb 2010
Schaffner Bilog Antenna – BL4	CBL6112B	2593	19 May 2010
Schaffner Bilog Antenna – BL3	CBL6112B	2549	18 Dec 2009
EMCO Horn Antenna – H14	3115	0003-6087	14 May 2010
ETS Horn Antenna	3116	0004-2474	02 Apr 2010

## **PROTECTION OF AERONAUTICAL RADIO NAVIGATION SATELLITE SERVICE TEST**

### **FCC Part 25.216(h)(i)(j) Protection of Aeronautical Radio Navigation Satellite Service Test Setup**

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant antenna was set at the required test distance away from the EUT and supporting equipment boundary

### **FCC Part 25.216(h)(i)(j) Protection of Aeronautical Radio Navigation Satellite Service Test Method**

1. The EUT was set to transmit at the maximum power at the lower channel with the modulation on at normal test condition.
2. The receiving antenna (test antenna) was set at vertical polarization with the height of 1m.
3. A prescan was carried out in the frequency range under investigations with the EMI receiver set to max hold mode. For EUT which is a portable device, the prescan was carried out by rotating the EUT through three orthogonal axes to determine which attitude and equipment arrangement produces such emissions.
4. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner:
  - a. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen.
  - b. The EUT was then rotated to the direction that gave the maximum emission.
  - c. Finally, the antenna height was adjusted to the height that gave the maximum emission.
5. The maximized emissions were plotted with inclusion of corrector factor of measured radiated emissions to EIRP.
6. The steps 1 to 5 were repeated with the EUT was set to operate at the middle and upper channels respectively.
7. The measurements were repeated with the EUT in carrier off state (standby).

---

**PROTECTION OF AERONAUTICAL RADIO NAVIGATION SATELLITE SERVICE TEST**

---



**Protection of Aeronautical Radio Navigation Satellite Service Test Setup (Front View)**



**Protection of Aeronautical Radio Navigation Satellite Service Test Setup (Rear View)**



PSB Singapore

---

**PROTECTION OF AERONAUTICAL RADIO NAVIGATION SATELLITE SERVICE TEST**

---

**FCC Part 25.216(h)(i)(j) Protection of Aeronautical Radio Navigation Satellite Service Results**


Operating Mode	Satellite Transmission	Temperature	34°C
Test Input Power	24VDC (Worst voltage)	Relative Humidity	50%
Test Distance	3m	Atmospheric Pressure	1030mbar
Type Bearer	7 (worst bearer)	Tested By	Foo Kai Maun
Attached Plots	91 - 96		

All spurious signals found were below the specified limit. Please refer to the attached plots.




**PROTECTION OF AERONAUTICAL RADIO NAVIGATION SATELLITE SERVICE TEST**

Type Bearer: 7 - Transmitter On



Plot 91 – Lower Channel




Plot 92 – Middle Channel



PSB Singapore



**PROTECTION OF AERONAUTICAL RADIO NAVIGATION SATELLITE SERVICE TEST**

Type Bearer: 7 - Transmitter On




**PROTECTION OF AERONAUTICAL RADIO NAVIGATION SATELLITE SERVICE TEST**

**Carrier Off**



**PROTECTION OF AERONAUTICAL RADIO NAVIGATION SATELLITE SERVICE TEST**

**Carrier Off**



Plot 96 – Upper Channel



## **FREQUENCY STABILITY (TEMPERATURE VARIATION) TEST**

### **FCC Parts 2.1055 and 25.202(d) Frequency Stability (Temperature Variation) Test Limits**

1. 25.202(d) Frequency Tolerance, Earth Stations  
The carrier frequency of each earth station transmitter authorised in these services shall be maintained within 0.001% (10ppm) of the reference frequency.
2. 2.1055 Measurements Required: Frequency Stability
  - (a) The frequency stability shall be measured with variation of ambient temperature as follows:
    - (1) From -30°C to +50°C for all equipment except that specified in paragraphs (a)(2) and (3) of this section.
    - (b) Frequency measurements shall be made at the extremes of the specified temperature range and at interval of not more than 10°C throughout the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion of portions of the transmitter containing the frequency determining and stabilizing circuitry need to be subjected to the temperature variation test.
    - (d) The frequency stability shall be measured with variation of primary supply voltage as follows:
      - (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
      - (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.
      - (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

### **FCC Parts 2.1055 and 25.202(d) Frequency Stability (Temperature Variation) Test Instrumentation**

<b>Instrument</b>	<b>Model</b>	<b>S/No</b>	<b>Cal Due Date</b>
Bird 20dB 25W RF Attenuator	25-A-MFN-20	Nil	25 May 2010
HP Universal Counter	53132A	3736A06236	07 Mar 2010


## FREQUENCY STABILITY (TEMPERATURE VARIATION) TEST

### FCC Parts 2.1055 and 25.202(d) Frequency Stability (Temperature Variation) Test Setup

1. The EUT and supporting equipment were set up as shown in the test setup photo. A temperature-controlled chamber was used.
2. The EUT was connected to an appropriate power source while all other supporting equipment were powered separately from another power source.
3. The RF antenna connector of the EUT was connected to the spectrum analyser via a RF attenuator and a low-loss coaxial cable.

### FCC Parts 2.1055 and 25.202(d) Frequency Stability (Temperature Variation) Test Method

1. The temperature chamber was set at 20°C and permitted to stabilize. The EUT was set to transmit at lower channel without modulation. The carrier frequency was measured as the reference frequency.
2. With the EUT power removed, the temperature of the temperature chamber was set to -30°C and permitted to stabilize.
3. The EUT was turned on and set to operate at lower channel without modulation. The maximum change in the carrier frequency was recorded within a minute.
4. The EUT was powered off and the temperature was raised to -20°C.
5. The EUT was left stabilized for at least an hour before next measurement was taken as described in step 3.
6. The steps 4 and 5 were repeated with increment of temperature in 10°C step until the temperature reached 50°C.
7. The steps 1 to 6 were repeated with the EUT was set to operate at the middle and upper channels respectively.



**FREQUENCY STABILITY (TEMPERATURE VARIATION) TEST**



**Frequency Stability (Temperature Variation) Test Setup**



**FREQUENCY STABILITY (TEMPERATURE VARIATION) TEST**

**FCC Parts 2.1055 and 25.202(d) Frequency Stability (Temperature Variation) Results**

Operating Mode	Satellite Transmission (CW)	Temperature	See table below
Test Input Power	24VDC	Relative Humidity	50%
		Atmospheric Pressure	1030mbar
		Tested By	Foo Kai Maun

**Lower Channel**

Temperature (°C)	Measured Frequency (GHz)	Reference Channel Frequency (GHz)	Deviation (ppm)
-30	1.631500946	1.631501125	-0.109715
-20	1.631500944	1.631501125	-0.110941
-10	1.631500907	1.631501125	-0.133619
0	1.631500970	1.631501125	-0.095005
10	1.631500977	1.631501125	-0.090714
20	1.631500937	1.631501125	-0.115231
30	1.631500993	1.631501125	-0.080907
40	1.631500963	1.631501125	-0.099295
50	1.631500943	1.631501125	-0.111554

**Middle Channel**

Temperature (°C)	Measured Frequency (GHz)	Reference Channel Frequency (GHz)	Deviation (ppm)
-30	1.643500907	1.643501125	-0.132644
-20	1.643500946	1.643501125	-0.108914
-10	1.643500945	1.643501125	-0.109522
0	1.643501000	1.643501125	-0.076057
10	1.643500991	1.643501125	-0.081533
20	1.643500987	1.643501125	-0.083967
30	1.643500922	1.643501125	-0.123517
40	1.643500990	1.643501125	-0.082142
50	1.643500971	1.643501125	-0.093702

**FREQUENCY STABILITY (TEMPERATURE VARIATION) TEST**

**Upper Channel**

Temperature (°C)	Measured Frequency (GHz)	Reference Channel Frequency (GHz)	Deviation (ppm)
-30	1.660400903	1.660401125	-0.133703
-20	1.660400941	1.660401125	-0.110817
-10	1.660400942	1.660401125	-0.110214
0	1.660400997	1.660401125	-0.077090
10	1.660400987	1.660401125	-0.083112
20	1.660400983	1.660401125	-0.085522
30	1.660400979	1.660401125	-0.087931
40	1.660400976	1.660401125	-0.089737
50	1.660400974	1.660401125	-0.090942



## **FREQUENCY STABILITY (VOLTAGE VARIATION) TEST**

### **FCC Parts 2.1055 and 25.202(d) Frequency Stability (Voltage Variation) Test Limits**

1. 25.202(d) Frequency Tolerance, Earth Stations  
The carrier frequency of each earth station transmitter authorised in these services shall be maintained within 0.001% (10ppm) of the reference frequency.
2. 2.1055 Measurements Required: Frequency Stability
  - (a) The frequency stability shall be measured with variation of ambient temperature as follows:
    - (1) From -30°C to +50°C for all equipment except that specified in paragraphs (a)(2) and (3) of this section.
    - (b) Frequency measurements shall be made at the extremes of the specified temperature range and at interval of not more than 10°C throughout the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion of portions of the transmitter containing the frequency determining and stabilizing circuitry need to be subjected to the temperature variation test.
    - (d) The frequency stability shall be measured with variation of primary supply voltage as follows:
      - (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
      - (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.
      - (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

### **FCC Parts 2.1055 and 25.202(d) Frequency Stability (Voltage Variation) Test Instrumentation**

<b>Instrument</b>	<b>Model</b>	<b>S/No</b>	<b>Cal Due Date</b>
Bird 20dB 25W RF Attenuator	25-A-MFN-20	Nil	25 May 2010
HP Universal Counter	53132A	3736A06236	07 Mar 2010

## **FREQUENCY STABILITY (VOLTAGE VARIATION) TEST**

### **FCC Parts 2.1055 and 25.202(d) Frequency Stability (Voltage Variation) Test Setup**

1. The EUT and supporting equipment were set up as shown in the test setup photo. A temperature-controlled chamber was used.
2. The EUT was connected to an appropriate power source while all other supporting equipment were powered separately from another power source.
3. The RF antenna connector of the EUT was connected to the spectrum analyser via a RF attenuator and a low-loss coaxial cable.

### **FCC Parts 2.1055 and 25.202(d) Frequency Stability (Voltage Variation) Test Method**

1. The temperature chamber was set at 20°C and permitted to stabilize. The EUT was set to transmit at lower channel without modulation. The carrier frequency was measured as the reference frequency.
2. The EUT was powered from 85% of the nominal supplied voltage and set to operate at lower channel without modulation.
3. The EUT power was varied from 85% to 115% of the nominal supplied voltage. The carrier frequency variation was recorded.
4. The steps 1 to 3 were repeated with the EUT was set to operate at the middle and upper channels respectively.



**FREQUENCY STABILITY (VOLTAGE VARIATION) TEST**



**Frequency Stability (Voltage Variation) Test Setup**



**FREQUENCY STABILITY (VOLTAGE VARIATION) TEST**

**FCC Parts 2.1055 and 25.202(d) Frequency Stability (Voltage Variation) Results**

Operating Mode	Satellite Transmission (CW)	Temperature	20°C
Test Input Power	See table below	Relative Humidity	50%
		Atmospheric Pressure	1030mbar
		Tested By	Foo Kai Maun

**Lower Channel**

Voltage (V)	Measured Frequency (GHz)	Nominal Channel Frequency (GHz)	Deviation (ppm)
20.4	1.631500828	1.631501125	-0.182041
24.0	1.631501125	1.631501125	0.000000
27.6	1.631500821	1.631501125	-0.186331

**Middle Channel**

Voltage (V)	Measured Frequency (GHz)	Nominal Channel Frequency (GHz)	Deviation (ppm)
20.4	1.643500823	1.643501125	-0.183754
24.0	1.643501125	1.643501125	0.000000
27.6	1.643500818	1.643501125	-0.186796

**Upper Channel**

Voltage (V)	Measured Frequency (GHz)	Nominal Channel Frequency (GHz)	Deviation (ppm)
20.4	1.660400825	1.660401125	-0.180679
24.0	1.660401125	1.660401125	0.000000
27.6	1.660400815	1.660401125	-0.186702

### MAXIMUM PERMISSIBLE EXPOSURE (MPE) TEST

#### FCC Part 1.1310 Maximum Permissible Exposure (MPE) Limits

The EUT shows compliance to the requirements of this section, which states the MPE limits for general population / uncontrolled exposure are as shown below:

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (min)
0.3 - 1.34	614	1.63	100 <sup>Note 2</sup>	30
1.34 - 30	824 / f	2.19 / f	180 / f <sup>2</sup> <sup>Note 2</sup>	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	-	-	f / 1500	30
1500 - 100000	-	-	1.0	30

Notes

1. f = frequency in MHz
2. Plane wave equivalent power density

#### FCC Part 1.1310 Maximum Permissible Exposure Computation

The minimum safe distance between the EUT and field probe was computed from the following formula:

$$d = \sqrt{[(30GP) / 377S]}$$

where S = Power density, 10W/m<sup>2</sup>  
 P = 44.2W  
 d = Minimum safety distance, m  
 G = Numerical isotropic gain, 10.0 (10.0dBi)

Substituting the relevant parameters into the formula:

$$d = \sqrt{[(30GP) / 377S]}$$

$$= 1.8754m$$

$$\approx 1.9m$$

∴ The distance between users and the EUT shall be maintained at a minimum distance of 1.9m during normal operation in order to ensure RF exposure to the users is within the allowable safety margin.


This Report is issued under the following conditions:

1. Results of the testing/calibration in the form of a report will be issued immediately after the service has been completed or terminated.
2. Unless otherwise requested, a report shall contain only technical results. Analysis and interpretation of the results and professional opinion and recommendations expressed thereupon, if required, shall be clearly indicated and additional fee paid for, by the Client.
3. This report applies to the sample of the specific product/equipment given at the time of its testing/calibration. The results are not used to indicate or imply that they are applicable to other similar items. In addition, such results must not be used to indicate or imply that TÜV SÜD PSB approves, recommends or endorses the manufacturer, supplier or user of such product/equipment, or that TÜV SÜD PSB in any way "guarantees" the later performance of the product/equipment.
4. The sample/s mentioned in this report is/are submitted/supplied/manufactured by the Client. TÜV SÜD PSB therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.
5. Additional copies of the report are available to the Client at an additional fee. No third party can obtain a copy of this report through TÜV SÜD PSB, unless the Client has authorised TÜV SÜD PSB in writing to do so.
6. TÜV SÜD PSB may at its sole discretion add to or amend the conditions of the report at the time of issue of the report and such report and such additions or amendments shall be binding on the Client.
7. All copyright in the report shall remain with TÜV SÜD PSB and the Client shall, upon payment of TÜV SÜD PSB's fees for the carrying out of the tests/calibrations, be granted a license to use or publish the report to the third parties subject to the terms and conditions herein, provided always that TÜV SÜD PSB may at its absolute discretion be entitled to impose such conditions on the license as it sees fit.
8. Nothing in this report shall be interpreted to mean that TÜV SÜD PSB has verified or ascertained any endorsement or marks from any other testing authority or bodies that may be found on that sample.
9. This report shall not be reproduced wholly or in parts and no reference shall be made by the Client to TÜV SÜD PSB or to the report or results furnished by TÜV SÜD PSB in any advertisements or sales promotion.
10. Unless otherwise stated, the tests are carried out in TÜV SÜD PSB Pte Ltd, No.1 Science Park Drive Singapore 118221.

March 2009

**FCC LABEL & POSITION**

**ANNEX B**



## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR SATLINK FB150



Front View



Rear View

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR HANDSET



Front View




Rear View

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR SATLINK FB150




Internal View 1

## **EUT PHOTOGRAPHS / DIAGRAMS**

## **ANNEX A**

### **EUT PHOTOGRAPHS FOR SATLINK FB150**




**Internal View 2**

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR SATLINK FB150




**Base-Band Board Component Side**

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR SATLINK FB150




**Base-Band Board PCB Trace Side**

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR SATLINK FB150




RF Module Board Component Side

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR SATLINK FB150



RF Module Board PCB Trace Side

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR SATLINK FB150




Crystal Board Component Side

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR SATLINK FB150




Crystal Board PCB Trace Side

## **EUT PHOTOGRAPHS / DIAGRAMS**

## **ANNEX A**

### **EUT PHOTOGRAPHS FOR SATLINK FB150**




**Interface Board Component Side**

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR SATLINK FB150




Interface Board PCB Trace Side

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A


### EUT PHOTOGRAPHS FOR SATLINK FB150



## **EUT PHOTOGRAPHS / DIAGRAMS**

## ANNEX A

## **EUT PHOTOGRAPHS FOR SATLINK FB150**



## Power Supply Board PCB Trace Side

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR HANDSET




Internal View

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR HANDSET




Main-Board Component Side

## EUT PHOTOGRAPHS / DIAGRAMS

## ANNEX A

### EUT PHOTOGRAPHS FOR HANDSET



Main-Board PCB Trace Side

**FCC LABEL & POSITION**

**ANNEX B**



## FCC LABEL & POSITION

## ANNEX B

Labelling requirements per Section 2.925 & 15.19

The label shown will be permanently affixed at a conspicuous location on the device and be readily visible to the user at the time of purchase.



Physical Location of FCC Label on EUT

**USER MANUAL TECHINICAL DESCRIPTION BLOCK  
& CIRCUIT DIAGRAM**

**ANNEX C**

