



Underwriters
Laboratories UL Japan, Inc.

FCC ID : XHEAZKT101
Test report No. : 29IE0196-YK-01-C
Page : 1 of 29
Issued date : June 24, 2009

RADIO TEST REPORT

Test Report No.: 29IE0196-YK-01-C

Applicant : ARUZE CORP.

Type of Equipment : Universal Bill Validator

Model No. : AZ-KT101-1000

FCC ID : XHEAZKT101

Test regulation : FCC Part15 Subpart C: 2009

Test result : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the limits of the above regulation.
4. The test results in this test report are traceable to the national or international standards.

Date of test: May 26 and June 1, 2009

Tested by:

M. Nakatake
Minoru Nakatake

&

A. Sato
Akira Sato

Approved by:

T. Imamura
Toyokazu Imamura
Assistant Manager of Yamakita EMC lab.

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

MF060b (09.01.08)

Table of Contents	Page
1 Applicant information	3
2 Equipment under test (E.U.T.)	3
3 Test specification, procedures and results	4
4 System test configuration	6
5 Conducted emission	7
6 Radiated emissions (Fundamental, Spurious and Outside the Allocated bands)	8
7 20dB bandwidth & Occupied bandwidth (99%)	10
8 Frequency tolerance	10
<u>Contents of Appendixes</u>	11
APPENDIX 1: Photographs of test setup	12
APPENDIX 2: Test data	16
APPENDIX 3: Test instruments	26
APPENDIX 4: Reference data	27

1 Applicant information

Company Name : ARUZE CORP.
Address : Ariake Frontier Bldg A, 3-1-25 Ariake, Koto-ku, Tokyo, 135-0063 Japan
Telephone Number : +81-3-5530-3055
Facsimile Number : +81-3-5530-3159
Contact Person : Kazuki Emori

2 Equipment under test (E.U.T.)

2.1 Identification of E.U.T.

Type of Equipment : Universal Bill Validator
Model No. : AZ-KT101-1000
Serial No. : Refer to 4.2 in this report.
Rating : DC12.0V
Country of Mass-production : Philippines
Condition of EUT : Production prototype
(Not for Sale: This sample is equivalent to mass-produced items.)
Modification of EUT : No modification by the test lab.
Receipt Date of Sample : May 26 and June 1, 2009

2.2 Product description

Model: AZ-KT101-1000 (referred to as the EUT in this report) is a Universal Bill Validator.

Clock frequency : CPU: 183MHz, SDRAM: 91.5MHz, FPGA: 50MHz, USB: 6MHz

Equipment type : Transceiver
Frequency of operation : 13.56MHz
Type of modulation : ASK
Antenna type : Loop
Antenna connector type : None
ITU code : A1D
Operation temperature range : -10 to +60 deg.C.

Similar model: AZ-KT101-500

The models are different in the capacity of the Cash Box.

Model No.	Capacity of Cash Box
AZ-KT101-500	500 Bills
AZ-KT101-1000	1000 Bills

FCC Part15.31 (e)

Host device provides the RFID transmitter with stable power supply, and the power is not changed when voltage of the device is varied. Therefore, the equipment complies power supply regulation.

FCC Part15.203 Antenna requirement

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT. Therefore, the equipment complies with the antenna requirement of Section 15.203.

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

3 Test specification, procedures and results

3.1 Test specification

Test specification : FCC Part15 Subpart C: 2009, final revised on February 27, 2009
 Title : FCC 47CFR Part15 Radio Frequency Device, Subpart C Intentional Radiators
 Section 15.207 Conducted limits
 Section 15.209 Radiated emission limits, general requirements
 Section 15.215 Additional provisions to the general radiated emission limitations.
 Section 15.225 Operation within the bands 13.110-14.010MHz.

The EUT complies with FCC Part 15 Subpart B: 2009, final revised on February 27, 2009. Refer to the test report 29IE0196-YK-01-D.

3.2 Procedures & Results

Item	Test Procedure	Specification	Remarks	Deviation	Worst Margin	Results
Conducted emission	ANSI C63.4:2003 7. AC powerline conducted emission measurements	FCC Section15.207	-	N/A	3.2dB (27.1197MHz, AV, L1)	Complied
Electric field strength of Fundamental emission	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.225 (a)	Radiated	N/A	76.4dB (Vertical)	Complied
Electric field strength of Outside the allocated bands	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.225 (b)(c)	Radiated	N/A	46.3dB (13.110MHz, Horizontal) (14.010MHz, Vertical)	Complied
Electric field strength of Spurious emission	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.209 FCC Section15.225 (d)	Radiated	N/A	2.1dB (412.05MHz, Vertical)	Complied
20dB bandwidth	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.215 (c)	Radiated	N/A	-	Complied
Frequency tolerance	ANSI C63.4:2003 13. Measurement of intentional radiators	FCC Section15.225 (e)	Radiated	N/A	-	Complied

Note: UL Japan's EMI Work Procedures No.QPM05 and QPM15.

3.3 Addition to standard

Item	Test Procedure	Specification	Remarks	Worst Margin	Results
Occupied bandwidth (99%)	ANSI C63.4:2003 13. Measurement of intentional radiators RSS-Gen 4.6.1	RSS-Gen 4.6.1	Conducted	-	Complied

* Other than above, no addition, exclusion nor deviation has been made from the standard.

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

3.4 Uncertainty

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

	No.1 open site (±)	No.2 open site (±)	No.1 anechoic chamber (±)
Conducted emission			
150kHz-30MHz	2.7 dB	2.7 dB	2.8 dB
Radiated emission (3m)			
<30MHz	2.4 dB	2.4 dB	2.7 dB
30-300MHz	4.3 dB	4.3 dB	4.6 dB
300-1000MHz	4.3 dB	4.3 dB	4.5 dB
1GHz<	5.7 dB	5.8 dB	5.7 dB

Conducted emission test

The data listed in this test report has enough margin, more than site margin.

Radiated emission test

The data listed in this report meets the limits unless the uncertainty is taken into consideration.

Frequency tolerance	(±)
	0.000014dB

3.5 Test location

UL Japan, Inc. Yamakita EMC Lab.

907, Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken 258-0124 JAPAN

Telephone number : +81 465 77 1011

Facsimile number : +81 465 77 2112

JAB Accreditation No. : RTL02610

No. 1 test site has been fully described in a report submitted to FCC office, and accepted on July 23, 2008 (Registration No.: 95486).

IC Registration No. : 2973B-1

No. 2 test site has been fully described in a report submitted to FCC office, and accepted on February 27, 2008 (Registration No.: 466226).

IC Registration No. : 2973B-3

No. 1 anechoic chamber has been fully described in a report submitted to FCC office, and accepted on October 22, 2008 (Registration No.: 95967).

IC Registration No. : 2973B-2

Test room	Width x Depth x Height (m)	Test room	Width x Depth x Height (m)
No.1 shielded room	8.0 x 5.0 x 2.5	No.1	10.0 x 7.5 x 5.7
No.2 shielded room	5.0 x 4.0 x 2.5	Semi-anechoic chamber	
No.3 shielded room	4.0 x 5.0 x 2.7		

Open test site	Maximum measurement distance
No.1 open test site	30m
No.2 open test site	10m

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN


Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

4 System test configuration

4.1 Justification

The EUT exercise program used during testing was designed to exercise the various system components in a manner similar to typical use.


Test item	Operating mode	Tested frequency
All test	ISO15693 (1 out of 4) modulation: 100% subcarrier: FM rate: high (26.69kbit/s)	13.56MHz



Start of frame of the 1 out of 4 mode

Justification: The system was configured in typical fashion (as customer would normally use it) for testing.

4.2 Configuration and peripherals



* Test data was taken under worse case conditions.

Description of EUT and support equipment

No.	Item	Model number	Serial number	Manufacturer	Remarks
A	Universal Bill Validator	AZ-KT101-1000	*1)	ARUZE	EUT
B	Power supply	HWS30-12	20K-814CT4-0174W3207	TDK Lambda	-

*1) 000052 or 000053 (Refer to the data.)

*2) For Conducted emission test, the EUT did not comply with the limit with the antenna. (Refer to the Appendix 4) Then, the test was performed with the dummy load to terminate the antenna port.

List of cables used

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	DC cable	0.45	Unshielded	Unshielded	-
2	AC cable	2.0	Unshielded	Unshielded	-

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

5 Conducted emissions

5.1 Operating environment

The test was carried out in No.2 shielded room.

5.2 Test configuration

EUT was placed on a wooden platform of nominal size, 1m by 1.8m, raised 80cm above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting plane. The rear of the EUT and its peripherals were aligned and flushed with rear of tabletop. All other surfaces of tabletop were at least 80cm from any other grounded conducting surface. EUT was located 80cm from a Line Impedance Stabilization Network (LISN) and excess AC cable was bundled in center. Photographs of the set up are shown in Appendix 1.

5.3 Test conditions

Frequency range : 0.15 - 30MHz

5.4 Test procedure

The EUT was connected to a LISN (AMN). An overview sweep with peak detection has been performed. The Conducted emission measurements were made with the following detector function of the test receiver.

Detector: QP/AV

IF Bandwidth: 9kHz

5.5 Results

Summary of the test results : Pass

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

6 Radiated emissions (Fundamental, Spurious and Outside the Allocated bands)

6.1 Operating environment

The test was carried out in No.1 anechoic chamber.

6.2 Test configuration

EUT was placed on a urethane platform of nominal size, 1.0m by 1.8m, raised 80cm above the conducting ground plane to prevent the reflection influence. Photographs of the setup are shown in Appendix 1.

6.3 Test conditions

Frequency range : 9kHz - 1GHz
Test distance : 3m

6.4 Test procedure

The Radiated Electric Field Strength intensity has been measured with a ground plane and at a distance of 3m.

Frequency: From 9kHz to 30MHz at distance 3m

The EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for vertical polarization (antenna angle: 0deg.to 360deg.) and horizontal polarization. The horizontal angle has not changed because there was a margin enough. Drawing of the antenna direction is shown in Figure 1.

Frequency: From 30MHz to 1GHz at distance 3m

The measuring antenna height was varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization.

Measurements were performed with QP, PK, and AV detector.

The radiated emission measurements were made with the following detector function of the test receiver.

	9kHz to 90kHz & 110kHz to 150kHz	90kHz to 110kHz	150kHz to 490kHz	490kHz to 30MHz	30MHz to 1GHz
Detector Type	PK/AV	QP	PK/AV	QP	QP
IF Bandwidth	200Hz	200Hz	10kHz	9kHz	120kHz
Measuring antenna	Loop antenna				Biconical (30-299.99MHz) Logperiodic (300MHz-1GHz)

* FCC Part 15 Section 15.31 (f)(2) (9kHz-30MHz)

9kHz – 490kHz [Limit at 3m]= [Limit at 300m]-40log (3[m]/300[m])

490kHz – 30MHz [Limit at 3m]= [Limit at 30m]-40log (3[m]/30[m])

The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

Frequency	Worst position (each antenna polarization)	
9kHz - 30MHz	Horizontal: X	Vertical: X
30 - 1000MHz	Horizontal: Y	Vertical: Y

6.6 Results

Summary of the test results : Pass *No noise was detected above the 5th order harmonics.

UL Japan, Inc.


Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN


Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

Figure 1: Direction of the Loop Antenna

Side View (Vertical)



Top View (Horizontal)



7 20dB bandwidth & Occupied bandwidth (99%)

Test procedure

The measurement was performed in the antenna height to gain the maximum of Electric field strength.

Summary of the test results: Pass

8 Frequency tolerances

Test procedure

The measurement was performed in the antenna height to gain the maximum of Electric field strength.
The temperature test was started after the temperature stabilization time of 30 minutes.

Summary of the test results: Pass

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112

APPENDIX 1: Photographs of test setup

Page 12 : Conducted emission
Page 13-14 : Radiated emission
Page 15 : Pre-check of the worst position

APPENDIX 2: Test data

Page 16 - 18 : Conducted emission
Page 19 - 21 : Radiated emission
19 : Fundamental and outside the allocated bands
20 - 21 : Spurious emission
Page 22 : Bandwidth
Page 23 - 25 : Frequency tolerance

APPENDIX 3: Test instruments

Page 26 : Test instruments

APPENDIX 4: Reference data

Page 27 - 29 : Reference data

UL Japan, Inc.

Yamakita EMC Lab.

907 Kawanishi, Yamakita-machi, Ashigarakami-gun, Kanagawa-ken, 258-0124 JAPAN

Telephone: +81 465 77 1011 Facsimile: +81 465 77 2112